
Brass fittings, double thread, without grounding terminal

Minimum Size	Maximum Size	Material	Туре	Model
1"	M77×2	Brass	Double thread, no ground	66RB

	ompatible acc	C33011C3		
X 66JP	X 6	66NL		
X 66JF	★ 66XN			
Compatible enclosures				
X Y303	X Y3P5	X Y3N2		
X Y304	X Y3P6	X Y3N3		
X Y305	X Y3H1	X Y3N4		
X Y306	X Y3H2	XY3L1		
X Y307	X Y3H3	XY3L3		
X Y309	X Y3J1	X Y3S3		
X Y310	X Y3J2	X Y3S5		
X Y3P1	X Y3G1	X Y3SA		
X Y3P3	X Y3G2	X Y3S7		
X Y3P4	X Y3N1			





Because of permanent improvement of our products, drawings, descriptions, features used on these data sheets are for guidance only and can be modified without prior advice

	1"	1-1/4"	1-1/2"	M45x2	2"	2-1/2"	M77x2
Α	1"	1-1/4"	1-1/2"	M45x2	2"	2-1/2"	M77x2
В	31	31	31	31	34	34	34
С	Ø27	Ø35	Ø36	Ø36	Ø50	Ø66	Ø66
D	1"	1-1/4"	1-1/2"	M45x2	2"	2-1/2"	M77x2
Ε	10	10	10	10	10	10	10
F	8	8	8	8	8	8	8
G	17	17	17	17	20	20	20
Н	25	25	25	25	28	28	28
1	50.5	65.5	65.5	65.5	79.5	102.5	102.5
J	Hex 45	Hex 58	Hex 58	Hex 58	Hex 70	Hex 90	Hex 90
K	4	4	4	4	4	4	4

Main references

Dimension	References	Dimension	References
1"	66RBA1T000000000	2"	66RBA5T000000000
1-1/4"	66RBA2T000000000	2-1/2"	66RBA7T000000000
1-1/2"	66RBA3T000000000	M77×2	66RBMGT000000000
M45×2	66RBMDT000000000		

Links



Page (.pdf)



Drawing 2D (.dwg)



Drawing 3D (.stp)

Red dimensions inside rectangular frames are used for assembly on enclosures or on fitting



E-Mail: info@ultimheat.com Web: www.ultimheat.com