



CHECKLIST

SMALL CRAFT - WATERTIGHT OR QUICK-DRAINING RECESSES AND COCKPITS

Ref.: ISO 11812:2020 [Note: not yet harmonised for RCD 2013/53/EU]

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



Subject to check	Clause	Requirements	Checked ?
1 All surfaces and appliances in watertight recesses have a watertightness of degree 1 up to hc.	6.1	[Yes / NA ?]	
2 All surfaces for quick draining recesses have a watertightness degree of 1.	6.2	[Yes / NA ?]	
3 Opening appliances installed on the surface of a quick-draining recess are secured in closed position by manually operated mechanical positive device.	6.2	[Yes / NA ?]	
4 Watertightness degree of appliances in quick-draining recesses are: -for the bottom and side up to hsmn - Degree 2; -between hsmn and 2hsmn - Degree 3; -above 2hsmn - Degree 4.	6.2	[Yes / NA ?]	
5 The minimum height $H_{B_{min}}$ of the recess bottom above waterline for quick-draining recesses are at least: -0,15 m -Design Category A; - 0,1 m - Design Category B; - 0,075 m -Design Category C; - 0,05 m - Design Category D.	8	[Yes / NA ?]	
6 Is the craft fully enclosed?.	7.2	[Yes / No ?]	
7 Is the recess open to the sea?.	7.2	[Yes / No ?]	
8 All of the recesses are located aft of the mid hull length of the craft?.	7.2	[Yes / No ?]	
9 Companionway sills			
10 Is there a sill for any companionway opening?.	7.2	[Yes / No ?]	
11 Companionways are installed on the rear face of a superstructure?	7.2	[Yes / No ?]	
12 Companionway within the limits of a recess or located within an area extending 0,6m outside of the recess boundary?	7.1	[Yes / No ?]	
13 The lowest point of the companionway opening is higher than ((LH/17)+hsmn) above the reference waterline.	7.2	[Yes / No ?]	
14 Companionway opening appliance is permanently installed, enabling immediate closure?.	7.2	[Yes / No ?]	
15 The permanent part of semi-fixed sills is at least hsmn/2.	7.4	[Yes / NA ?]	
16 The sill height is according to the requirements of Table 5.	7.4	[Yes / NA ?]	
17 Draining			
18 Drainage only by gravity.	9.1	[Yes ?]	
19 Drainage system arranged to minimize trapping of water in the recess, in both reference and heeled waterline condition.	9.1	[Yes / NA ?]	

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



20	Linked recesses are treated as being separate if the total link cross section area is < 120% of the minimum drainage area of the total volume of relevant recesses.	9.1	[Yes / NA ?]	
21	At least two drains are installed, one port and one starboard.	9.2.1	[Yes / NA ?]	
22	Drains with a circular cross section have an internal diameter of at least 25 mm.	9.2.1	[Yes / NA ?]	
23	Drains with other cross-sectional shapes have an internal cross section area of at least 500 mm ² and an internal minimum dimension of 20 mm.	9.2.1	[Yes / NA ?]	
24	The drain outlets are located above the waterline.	9.2.3	[Yes / NA ?]	
25	The drain outlets are located below the waterline, in maximum load condition and fitted with seacocks.	9.2.3	[Yes / NA ?]	
26	All drain piping systems have a watertightness degree 1.	9.2.3	[Yes / NA ?]	
27	Drain piping are protected against damage.	9.2.3	[Yes / NA ?]	
28	Drain piping in the engine room are insulated from the heat or withstand 70°C.	9.2.3	[Yes / NA ?]	
29	Drain piping can not trap water.	9.2.3	[Yes / NA ?]	

The following questions shall be filled in by the watercraft manufacturer and appropriate documentation shall be submitted to the inspector for verification.

Subject to check	Clause	Requirements	Checked ?
30 The loading and measurement conditions are in the "maximum load" condition according to ISO 8666.	5.1	[Yes ?]	
31 The measurements/calculations were made with the craft upright and at rest in calm water.	5.1	[Yes ?]	
32 Quick draining recesses - Single bottom recess drainage: The minimum recess bottom height $H_{B \min}$ above waterline is measured at the centre of the surface of the bottom.	8	[Yes / NA ?]	
33 Quick draining recesses - Multi Bottom recess drainage: The minimum recess bottom height $H_{B \min}$ above waterline is measured at the centre of the surface of the lowest bottom.	8	[Yes / NA ?]	
34 Calculation(s) and/or test report(s) for the cockpit is/are submitted.		[Yes ?]	

Instructions/Warnings to be included in the owner's manual

35 Recommendation to keep the drain system clear of debris or ropes, and checking seacock operation, where relevant.	11	[Yes / NA ?]	
36 All opening appliances covering downflooding openings shall be identified.	11	[Yes ?]	
37 How to secure opening appliances covering downflooding points in the closed position while underway.	11	[Yes ?]	
38 Recommendation that all opening appliances in the recesses shall be closed at sea. Only companionway appliances are opened to allow passage when entering and leaving the interior.	11	[Yes / NA ?]	
39 Recommendation that semi-fixed sills, including washboards, shall be raised in the closed position.	11	[Yes / NA ?]	

Comments:

compliant: Yes or V

not applicable: NA

follow up on variation report: Rpt or X