



CHECKLIST

SMALL CRAFT - WINDOWS, PORTLIGHTS, HATCHES, DEADLIGHTS AND DOORS

Ref.: EN ISO 12216:2020 [Note: not yet harmonised for RCD 2013/53/EU]

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



Subject to check		Requirements	Checked ?
1	The appliances fulfill the minimum degree of watertightness.	4.3.1 [Yes ?]	
2	No sliding appliances used in Area I ?.	4.3.2.1 [Yes ?]	
3	No sliding appliances used as deck hatches of trimaran outrigger hulls?	4.3.2.3 [Yes / NA ?]	
4	Are simply supported plates used in area I ? Please submit technical information if applicable.	6.1.1.1 [Yes / No ?]	
5	The maximum unsupported area of any appliance within area I is not more than 0,852 m ² .	6.3.1.1 [Yes / NA ?]	
6	The small unsupported dimension of any appliance in area I does not exceed 300 mm and 600mm for laminated glass. Excluded are escape hatches.	6.3.1.1 [Yes / NA ?]	
7	Technical datasheet(s) for glazing material is/are submitted. This includes the interlayer in case of laminated glass.	6.3.1.2 [Yes ?]	
8	The lower edge of any opening appliances is at least: -500 mm (Design Category A); -400 mm (Design Category B); -300 mm (Design Category C); -200 mm (Design Category D); above the waterline, in mldc condition and upright. Excluded are escape hatches.	6.3.1.3.1 [Yes / NA ?]	
9	All opening appliances shall open inwards. Excluded are escape hatches and transoms.	6.3.1.3.2 [Yes / NA ?]	
10	A companionway deck hatch have a sill height according to the standard.	6.3.3 [Yes / NA ?]	
11	Alternative for companionways which are not the main companionway: Label: KEEP CLOSED WHILE UNDERWAY IN CATEGORY XX CONDITION. Affixed: At the flush deck companionway deck hatch.	6.3.3 [Yes / NA ?]	
12	Sliding appliances are fitted with stops at each end of ist stroke.	6.3.4.2 [Yes / NA ?]	
13	Washboards are fitted with a device to keep them in place, when in use.	6.3.5 [Yes / NA ?]	
14	Washboards are stowed in the vicinity of the door opening and easily reached without the use of tools.	6.3.5 [Yes / NA ?]	
15	Washboards of crafts of design category A are equipped with a device connecting the boards together when not in use.	6.3.5 [Yes / NA ?]	
16	Any opening appliance has a securing device, operable at least from inside. Excluded are deadlights.	6.3.6 [Yes / NA ?]	
17	A securing device for the open position is required on sliding hatched and sliding cabin doors	6.3.6 [Yes / NA ?]	

compliant: Yes or V

not applicable: NA

follow up on variation report: Rpt or X

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



18	Minimum clearing characteristics of escape hatched according to ISO 12217?	6.3.8	[Yes / NA ?]	
----	--	-------	--------------	--

The following questions shall be filled in by the watercraft manufacturer and appropriate documentation shall be submitted to the inspector for verification.

	Subject to check		Requirements	Checked ?
19	All appliances are designed and fixed to prevent substantial ingress of water when closed.	4.3	[Yes ?]	
20	All types of fastening ensure watertightness of the plate or frame, and resistance to loads due to normal operating pressure.	6.2.1	[Yes ?]	
21	Glued joints are resistant to sunlight, environmental effects or cleaning chemicals.	6.2.3	[Yes / NA ?]	
22	Glued joints fulfil at least one of the following requirements of this standard: -inside pressure test; -separation test; -manufacturers gluing procedure and conditions are followed and the band strength was checked through calculation.	6.2.3	[Yes / NA ?]	
23	Deadlights of windows installed in area I are permanently attached to the appliance or the craft structure. They are only operative in the case of rupture. Of the opening part of the window.	6.3.7	[Yes / NA ?]	
24	Calculation worksheet and/or test report(s) for all appliances are submitted.		[Yes ?]	
Instructions/Warnings to be included in the owner's manual				
25	Warning if a companionway deck hatch has no sill height and is not the main companionway.	10	[Yes / NA ?]	

Comments:
