



CHECKLIST

SMALL CRAFT- ANCHORING, MOORING AND TOWING - STRONG POINTS

Ref.: EN ISO 15084:2018 (ISO 15084:2003)

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



Subject to check	Clause	Requirements	Checked ?
1 Is the anchoring or towing strong point be used for mooring as well.	5.1	[Yes / No ?]	
2 The minimum number of strong points is as required - all craft: one anchoring/towing point forward; - craft over 6 m LH: at least one mooring point aft; - craft over 12 m LH: at least one additional mooring point both forward & aft; - craft over 18 m LH: at least one additional mooring point port and starboard.	5.2	[Yes ?]	
3 If strong points secured with nuts and bolts, doubling plates or washers of adequate size are used.	7.1	[Yes / NA ?]	
4 Where the intended use of a strong point for anchoring and/or being towed is not self evident, the strong point is labelled.	7.3	[Yes / NA ?]	

The following questions shall be filled in by the watercraft manufacturer and appropriate documentation shall be submitted to the inspector for verification.

Subject to check	Clause	Requirements	Checked ?
5 The strong points are assessed to comply with the horizontal loads defined in clause 6.2 by direct calculation or a test.	6.2; 6.3	[Yes ?]	
6 If the boat manufacturer specifies or supplies lines, chains or cables which exceed the requirements with the breaking strength defined in clause 6.2, the breaking strength are assessed to withstand a breaking strength of not less than 125 % of the rope or chain that is specified or supplied.	6.4	[Yes / NA ?]	
7 The craft structure in the vicinity of strong points is reinforced to take the loads calculated for the breaking strength.	7.1	[Yes ?]	
8 All strong points are made of corrosion resistant materials.	7.2	[Yes ?]	
9 Non metallic strong points are UV stabilized.	7.2	[Yes / NA ?]	

Instructions/Warnings to be included in the owner's manual

10 Information on the breaking strength of the strong points.	Annex A	[Yes ?]	
11 Where the purpose of a specific strong point is not self evident, it shall be explained.	Annex A	[Yes / NA ?]	
12 CAUTION - Always tow or be towed at a slow speed. Never exceed the hull speed of a displacement craft when being towed.	Annex A	[Yes ?]	
13 CAUTION - A tow line shall always be made fast in such a way that it can be released when under load.	Annex A	[Yes ?]	

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



14	It is the owner's/operators responsibility to ensure that mooring lines, towing lines, anchor chain(s), anchor lines and anchor(s) are adequate for the vessel's intended use.	Annex A	[Yes ?]	
15	Where non-metallic strong points are installed, their limited life time shall be taken into consideration. They shall be replaced once they show any signs of deterioration, visible surface cracks or permanent deformation.	Annex A	[Yes / NA ?]	

Comments:
