



CHECKLIST

SMALL CRAFT- NAVIGATION LIGHTS - INSTALLATION, PLACEMENT AND VISIBILITY

Ref.: EN ISO 16180:2018 (ISO 16180:2013)

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



Subject to check	Clause	Requirements	Checked ?
1 Length of hull [m]			
2 Maximum speed [knots]			
3 Craft type (<u>Non</u> -Powered , <u>Power</u> , <u>Sail</u> , <u>Sail+Power</u>)			

Power craft and/or sailing craft under power

- 4 Please indicate the configuration for power craft or sailing craft under power less than 12 m in length of hull.



☐	☐	☐
--------------------------	--------------------------	--------------------------



☐	☐
--------------------------	--------------------------



Green



Red

- 5 Please indicate the configuration for a power craft or sailing craft under power ≥ 12 m to < 20 m in length of hull.



☐	☐
--------------------------	--------------------------



White

- 6 Please indicate the configuration for power craft and sailing craft under power ≥ 20 m in length of hull.



☐	☐
--------------------------	--------------------------

Watercraft manufacturer:	
Watercraft model name:	

**Sailing craft**

- 7 Please indicate the navigation light configuration for the sailing craft.

			Green
☐	☐		Red
			White
☐	☐		

8	Navigation lights are visible under normal operating condition.	4.2.2	[Yes ?]	
9	Navigation lights are not obscured by fixed structures or optional equipment.	4.2.3	[Yes ?]	
10	Navigation lights are mounted so that they do not shine in operators' eyes in normal operation position to prevent reflection of a craft's structure within operator's field of vision.	4.2.4	[Yes ?]	
11	One switch or one position of a multiple position switch, shall display the complete navigation light configuration as required for the craft while underway.	4.2.6	[Yes ?]	
12	Another switch or switch position shall display the anchor light only.	4.2.6	[Yes ?]	
13	Damage of navigation lights caused by contact with other objects under normal operating conditions is minimized.	4.2.7	[Yes ?]	
Power driven craft (including sailing craft under power and sail) - underway				
14	If two masthead lights are carried the aft one shall be at least 4,5 m vertically higher than the forward one.	4.4.2.1	[Yes / NA ?]	
15	If two masthead lights are carried the horizontal distance between them shall not be less than one half of the length of the craft.	4.4.2.1	[Yes / NA ?]	
16	If two masthead lights are carried the forward light shall be placed not more than one quarter of the length of the craft from the stem.	4.4.2.1	[Yes / NA ?]	
17	Craft less than 7m with a maximum speed of less than 7knots exhibit an all-round white light.	4.4.2.1	[Yes / NA ?]	
18	If craft less than 7m with a maximum speed of less than 7knots carries sidelights then the all-round white light is 1 m higher.	4.4.2.1	[Yes / NA ?]	

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



19	The masthead light or all-round light for craft less than 12 m in length of hull displaced from the fore and aft centreline provided that the sidelights are combined into one lantern or are located as close as possible to the same fore and aft line as the masthead light or all-round light.	4.4.2.2.2	[Yes / NA ?]	
20	If craft less than 12m, masthead light 1m minimum above the sidelines.	4.4.2	[Yes / NA ?]	
21	If craft ≥12 m to <20 m in length of hull, masthead light 2,5 m minimum above the gunwale.	4.4.2.3	[Yes / NA ?]	
22	If craft ≥20 m in length of hull, masthead light forward of midship at a height above the hull of not less than 6 m.	4.4.2.4	[Yes / NA ?]	
23	If craft ≥20 m in length of hull and breadth of the craft exceeds 6 m, masthead light at a height above the hull not less than such breadth, not greater than 12m.	4.4.2.4	[Yes / NA ?]	
Sailing craft - Underway under sail alone				
24	Two all-around lights in a vertical line installed where they can best be seen.	4.4.3.1	[Yes / NA ?]	
25	If two all-around lights are installed, the upper being red and the lower green, in addition to the prescribed sidelights and stern light but not with a tricolour light.	4.4.3.1	[Yes / NA ?]	
26	Sailing craft under 7 m in length of hull have lights as prescribed for craft under 12m in length of hull,	4.4.3.1	[Yes / NA ?]	
27	Sailing craft under 7 m in length of hull have ready an electric torch or lantern showing a white light.	4.4.3.1	[Yes / NA ?]	
28	If craft less than 12m, combination sidelight on the fore and aft centreline.	4.4.3.2	[Yes / NA ?]	
29	If craft ≥12 m to <20 m in length of hull, combination sidelight placed over the fore and aft centreline.	4.4.3.3	[Yes / NA ?]	

The following questions shall be filled in by the watercraft manufacturer and appropriate documentation shall be submitted to the inspector for verification.

Subject to check	Clause	Requirements	Checked ?
30 Navigation lights comply with positioning COLREG? Documentation about the position is submitted.	4.2.1	[Yes / NA ?]	
31 Navigation lights comply with technical requirements of COLREG? Documentation about the technical compliance is submitted.	4.2.1	[Yes / NA ?]	
32 Navigation lights ensure required arcs of visibility, vertical separation and location requirements when craft is in fully loaded, ready-to-use condition.	4.2.5	[Yes / NA ?]	
33 Navigation lights installed according manufacturers' instructions.	4.3.1	[Yes / NA ?]	
34 Electric navigation lights installed in accordance with ISO 10133 or ISO 13297 or equivalent safety standard.	4.3.2	[Yes / NA ?]	
35 Used conductors are sized for no more than 3% voltage drop.	4.3.2	[Yes / NA ?]	
36 If a metallic frame or enclosure in a direct current (dc) system has a current carrying connection, it shall be mounted on an electrically nonconductive surface and polarity of the electrical leads shall be observed.	4.3.3	[Yes / NA ?]	

compliant: Yes or V

not applicable: NA

follow up on variation report: Rpt or X

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



Instructions/Warnings to be included in the owner's manual				
37	Diagram(s) identifying the electrical circuits of the craft with the location of navigation lights in the craft and identification of conductors by colour or other means.	Annex A	[Yes ?]	
38	Location and description of functions of electrical controls, dials, switches, fuses and also circuitbreakers installed on the panel-board for the operation of the navigation lights.	Annex A	[Yes ?]	
39	Details of replacement light sources.	Annex A	[Yes ?]	
40	Access to navigation light fixtures.	Annex A	[Yes ?]	
41	NEVER - work on the electrical installation while the system is energized.	Annex A	[Yes ?]	
42	NEVER - modify the craft's electrical system or relevant drawings. Installation, alterations and maintenance should be performed by a competent marine electrical technician.	Annex A	[Yes ?]	
43	NEVER - alter or modify the rated current amperage of overcurrent protective devices.	Annex A	[Yes ?]	
44	NEVER - install or replace electrical appliances or devices with components which exceed the rated current amperage of the circuit.	Annex A	[Yes ?]	

Comments:
