



CHECKLIST

SMALL CRAFT - WATERTIGHT COCKPITS AND QUICK-DRAINING COCKPITS

Ref.: EN ISO 11812:2018 (ISO 11812:2001)

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



Subject to check	Clause	Requirements	Checked ?
1 The loading and measurement conditions are in the "fully loaded ready-for-use" condition according to ISO 8666.	5.1	[Yes ?]	
2 The measurements/calculations were made with the boat upright and at rest in smooth water.	5.1	[Yes ?]	
3 Watertight cockpits have sills in accordance with clause 8.	5.2	[Yes / NA ?]	
4 Watertight cockpits have a degree of water tightness according to clause 9.	5.2	[Yes / NA ?]	
5 Quick-draining cockpits/recesses have the bottom height HB above the waterline, in accordance with clause 6.	5.3	[Yes / NA ?]	
6 Quick-draining cockpits/recesses have draining devices according to clause 7.	5.3	[Yes / NA ?]	
7 Quick-draining cockpits/recesses have sills in accordance with clause 8.	5.3	[Yes / NA ?]	
8 Quick-draining cockpits/recesses show a degree of water tightness according to clause 9.	5.3	[Yes / NA ?]	
9 If the cockpit bottom has more than one level, annex B is used.	5.3	[Yes / NA ?]	
10 Closing appliances fitted in watertight and/or quick-draining cockpits, giving access to the interior of the boat, fulfil the requirements of ISO 12216 and clause 9.	5.4	[Yes / NA ?]	
11 The minimum cockpit bottom height $H_{B,min}$ is according to Table 2.	6.1	[Yes ?]	
12 Are surfaces up to 10% of the horizontal projection of the cockpit bottom which are not required to comply with 6.1 considered to be full of water when assessing the fully load condition.	6.2.1	[Yes / No ?]	
13 Lockers in cockpit bottoms fulfilling the requirements of 5.3 and clause 9 need not be considered full of water, but only filled with the maximum loading corresponding to the "fully loaded" condition.	6.2.2	[Yes / NA ?]	
14 Cockpit draining only by gravity.	7.1.1	[Yes ?]	
15 The requirements of 7.1.3.1 and 7.1.3.2 are fulfilled when the boat is heeled to port and starboard.	7.1.3	[Yes ?]	
16 If a sailing monohull: Drainage is provided for at least 90% of the cockpit volume at the lesser heel angle of 30°, or when the deck at side touches the water.	7.1.3.1	[Yes / NA ?]	
17 If a non-sailing boat or multihull: Drainage is provided for at least 90% of the cockpit volume at 10° heel.	7.1.3.2	[Yes / NA ?]	

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



18	The quick-draining cockpit has at least two drains, one port and one starboard, unless one opening enables drainage when the boat is heeled to both port and starboard, as required in 7.1.	7.3	[Yes / NA ?]	
19	Drains with a circular cross section have a diameter of at least 25 mm.	7.4.1	[Yes / NA ?]	
20	Drains with other cross-sectional shapes have an area of at least 500 mm ² , and a minimum dimension of 20 mm.	7.4.1	[Yes / NA ?]	
21	When devices that prevent loose objects from falling into the draining system are used, like grids: The requirements of Table 4 or annex D are fulfilled.	7.4.2	[Yes / NA ?]	
22	Centreboard housings and other types of aperture are used as drains and are designed for this purpose.	7.5	[Yes / NA ?]	
23	Drain outlets are: - above waterline, or - below waterline and fitted with seacocks, unless the drain outlet is an integral part of the hull extending from the outlet up to 0,75 HB,min above the waterline.	7.6	[Yes / NA ?]	
24	Drain piping is protected against damage from loose objects stowed in the boat and against being kicked or stepped on.	7.7	[Yes / NA ?]	
25	Drain piping does not trap water and is only used for cockpit drainage.	7.7	[Yes / NA ?]	
26	Watertight cockpits have no opening below the height h _c .	8.1	[Yes / NA ?]	
27	The sill height is measured vertically from the cockpit bottom to the lowest point on the sill edge that allows ingress of water.	8.2.1.	[Yes ?]	
28	The sill height is according to the requirements of Table 5.	8.2.2	[Yes ?]	
29	Above sill level, appliances complying with ISO 12216 are used up to h _c .	8.2.3	[Yes ?]	
30	Semi-fixed sills and washboards have a device maintaining them in place, when in use, at least operable from the inside.	8.2.4	[Yes / NA ?]	
31	Semi-fixed sills and washboards meet the strength requirements of ISO 12216.	8.2.4	[Yes / NA ?]	
32	Semi-fixed sills are only detachable with the use of tools.	8.2.4	[Yes / NA ?]	
33	A provision is made for washboards to be stored in a specific location in the vicinity of the companionway.	8.2.4	[Yes / NA ?]	
34	All surfaces of watertight cockpits up to h _c have water tightness degree 1.	9.1	[Yes / NA ?]	
35	All surfaces of quick-draining cockpits up to h _c have water tightness degree 1.	9.2.1	[Yes / NA ?]	
36	The water tightness of the closing appliances is according to Table 6 and a test report has been submitted.	9.2.1	[Yes / NA ?]	
37	Hatches and appliances located in the cockpit bottom or sides up to h _{s,min} are fitted with seals and sills at least 12 mm high, or tested as installed to water tightness degree 2 according to annex E. A test report has been submitted.	9.2.1	[Yes / NA ?]	
38	The lowest point of non-closable ventilation openings are at least 2h _{s,min} , or 0,3 m, whichever is the greater, above cockpit bottom, and watertight to degree 4.	8.2.2	[Yes / NA ?]	

compliant: Yes or V

not applicable: NA

follow up on variation report: Rpt or X

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



The following questions shall be filled in by the watercraft manufacturer and appropriate documentation shall be submitted to the inspector for verification.

Subject to check	Clause	Requirements	Checked ?
39 When the boat is upright, 98% of the cockpit volume drains, excluding any recess in according with the exceptions of 6.2.	7.1.2	[Yes ?]	
40 The draining time is determined by measurement of actual draining time and a test report has been submitted.	7.8.1	[Yes / NA ?]	
41 The draining time is determined by calculation and has been submitted.	7.8.1	[Yes / NA ?]	
42 The draining time is calculated according to the quick method in 7.8.4 and has been submitted.	7.8.3	[Yes / NA ?]	
43 The draining time is calculated according to the thorough method in Annex C and has been submitted.	7.8.3	[Yes / NA ?]	

Instructions/Warnings to be included in the owner's manual

44 The cockpit is documented with "watertight" or "quick-draining".	10	[Yes ?]	
---	----	---------	--

Comments:
