



CHECKLIST

SMALL CRAFT - WINDOWS, PORTLIGHTS, HATCHES, DEADLIGHTS AND DOORS

Ref.: EN ISO 12216:2018 (ISO 12216:2002)

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



Subject to check		Requirements	Checked ?
1 Opening appliances are positively fixed when closed.	4.3	[Yes / NA ?]	
2 The appliances fulfill the minimum degree of watertightness.	4.4.1	[Yes / NA ?]	
3 No sliding appliances used in Area I ?.	4.4.2.1	[Yes / NA ?]	
4 No sliding appliances used as deck hatches of trimaran outrigger hulls?	4.4.2.2	[Yes / NA ?]	
5 Are simply supported plates used in area I ?	6.1.1.1	[Yes / NA ?]	
6 The lower edge of any opening appliances is at least 200 mm above the waterline, in fully loaded ready-for use condition. Excluded are escape hatches.	6.3.1.1	[Yes ?]	
7 The small unsupported dimension of any appliance in area I does not exceed 300 mm. Excluded are escape hatches.	6.3.1.1	[Yes ?]	
8 All opening appliances shall open inwards. Excluded are escape hatches.	6.3.1.2	[Yes / NA ?]	
9 Technical datasheet for material of the appliances is submitted, including the one of the interlayer in case of laminated glass.	6.3.1.4	[Yes ?]	
10 Sliding appliances are fitted with stops at each end of its stroke.	6.3.3.1	[Yes / NA ?]	
11 Doors made with removable sections are fitted with a device to keep them in position, when in use.	6.3.4	[Yes / NA ?]	
12 Doors made with removable sections are stored inside the craft in the vicinity of the door opening and easily reached without the use of tools.	6.3.4	[Yes / NA ?]	
13 Doors made with removable sections of crafts of design category A are equipped with a device connecting the boards together when not in use.	6.3.4	[Yes / NA ?]	
14 Any opening appliance has a locking device, operable at least from inside. Excluded are deadlights.	6.3.5	[Yes / NA ?]	
15 Minimum clearing characteristics of escape hatches according to ISO 12217?	6.3.7	[Yes / NA ?]	

The following questions shall be filled in by the watercraft manufacturer and appropriate documentation shall be submitted to the inspector for verification.

Subject to check		Requirements	Checked ?
16 All appliances are designed and fixed to prevent substantial ingress of water when closed.	4.4	[Yes ?]	
17 All types of fastening ensure watertightness of the plate or frame, and resistance to loads due to normal operating pressure.	6.2.1	[Yes ?]	
18 Glued joints are resistant to sunlight, environmental effects or cleaning chemicals.	6.2.3	[Yes / NA ?]	

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



19	Glued joints fulfil at least one of the following requirements of this standard: -inside pressure test; -seperation test; -manufacturers gluing procedure and conditions are followed and the band strength was checked through calculation.	6.2.3	[Yes / NA ?]	
20	Deadlights installed in area I are permanently attached to the appliance or the craft structure. They are only operative in the case of rupture. Of the opening part of the window.	6.3.6	[Yes / NA ?]	
21	Calculation worksheet and/or test report(s) are submitted.		[Yes ?]	

Comments:
