



CHECKLIST

SMALL CRAFT - BILGE-PUMPING SYSTEMS

Ref.: EN ISO 15083:2020/A1:2022/A11:2023

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



Subject to check

Clause Requirements Checked ?

Note: the following requirements are applicable to all boats which require a bilge-pump system. See Table 2.

1	Bilge-pumping system(s) is capable of removing water from all separate bilge water compartments.	5.1	[Yes ?]	
2	If fore and aft peaks have a combined volume of more than 10% of the displacement they are linked to the bilge-pumping system.	5.1	[Yes / NA ?]	
3	If trapped water in fore and aft peaks can be emptied into the main bilges by a valve or drained by other means, fore and aft peaks need not be linked to the bilge-pumping system.	5.1	[Yes / NA ?]	
4	Bilge water compartments not readily accessible have a bilge pump installed.	5.1	[Yes / NA ?]	
5	Type(s), number(s) and location(s) of bilge pumps as required by table 2.	5.1	[Yes ?]	
6	Check documented pumps to have capacity of each bilge pump, as stated. This shall be according to 5.1.2/5.1.3 not be less than (see table 2): - 600 l/h for boats with LH less than or equal to 6 m, - 900 l/h for boats with LH greater than 6 m and less than 12 m, or - 1800 l/h for boats with LH greater than or equal to 12 m.	5.3	[Yes ?]	
7	The capacity for manual bilge pumps shall be rated for 45 strokes per minute or less.	5.3	[Yes / NA ?]	
8	Pump handle is secured unless pump is permanently fitted.	6.1.3	[Yes / NA ?]	
9	Discharge of bilge pump into cockpit only if this is open aft to sea.	6.1.4	[Yes / NA ?]	
10	Bilge pumps systems shall not discharge into a recess nor be connected to recess drains.	6.1.4	[Yes ?]	
11	If a switch is subjected to spray, it is water resistant to IP56.	6.2.3	[Yes / NA ?]	
12	Bilge pump mounted in an accessible location.	7.1	[Yes ?]	
13	Water inlet prevents ingestion of debris, e.g. by strainer.	7.2	[Yes ?]	
14	Outlet above maximum heeled waterline unless a seacock is installed and backflow into the boat is prevent.	7.5	[Yes / NA ?]	
15	Hose connections secured with non-corrosive clamps or mechanically fastened.	7.7	[Yes / NA ?]	
16	Non-submersible bilge pump motor is mounted above bilge water level.	7.8	[Yes / NA ?]	
17	Individual electrical bilge pump has a manual power supply switch.	7.9	[Yes / NA ?]	
18	Automatic bilge pump control has manual power supply switch.	7.10	[Yes / NA ?]	

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



19	Automatic bilge pump control has visual indication to show power supply (switch position or a light).	7.11	[Yes / NA ?]	
20	Manual bilge pumps can be operated to their capacity.	7.12	[Yes / NA ?]	

The following questions shall be filled in by the watercraft manufacturer and appropriate documentation shall be submitted to the inspector for verification.

Subject to check	Clause	Requirements	Checked ?
21 Bilge pumps shall be operable within temperature limits ranging from 0 °C to + 60 °C and shall withstand storage temperatures, without operation, of –40 °C to +60 °C when in the dry condition.	6.1.1	[Yes ?]	
22 Electrical bilge pumps complies with ISO 8849.	6.2.1	[Yes / NA ?]	
23 Intake hose does not collapses under maximum suction.	7.3	[Yes ?]	
24 Pump discharge lines non-restrictive.	7.4	[Yes ?]	
25 Simultaneous operation of several pumps at time does not diminishes the capacity of the entire system.	7.6	[Yes / NA ?]	
26 Accidental discharge of pollutants overboard in the upright or heeled waterline position is not possible.	7.13	[Yes ?]	

Instructions/Warnings to be included in the owner's manual

27 Means of bailing shall be specified for craft, not requiring a bilge pumping system (e.g. non fully enclosed boats).	5.1.2	[Yes / NA ?]	
28 For craft in design category D and Lh less than or equal 6 m, manual bilge pump or other means of bailing shall be specified.	5.1.3.2	[Yes / NA ?]	
29 Bilge-pumping system: -type, capacity and location of each bilge pump; -operating instructions; -requirements for servicing.	8	[Yes ?]	
30 "It is the responsibility of the owner/operator to have at least one means of bailing on board, secured against accidental loss."	8	[Yes ?]	
31 CAUTION - Check the function of all bilge pumps at regular intervals. Clear debris from the pump inlets.	8	[Yes ?]	
32 CAUTION - The seacocks in the fore and aft peak bulkheads shall be kept closed and shall only be opened to let water drain into the main bilges.	8	[Yes / NA ?]	
33 WARNING - The combined capacity of the system is not intended to drain the craft in the case of damage.	8	[Yes / NA ?]	
34 Additional information: -replacement of bilge pumping system filtes (when required); -maintanance; -visual inspection of drip trays (when installed); -visual inspection of bilge; - position of automatic bilge pump switch.	8	[Yes / NA ?]	

Comments:

compliant: Yes or V

not applicable: NA

follow up on variation report: Rpt or X