

CHECKLIST
SMALL CRAFT- Protection from falling overboard and means of reboarding
Ref.: EN ISO 15085:2024 (ISO 15085:2024)
 Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



Subject to check	Clause	Requirements	Checked ?
1 Craft provides safe access to the areas necessary for the safe operation of the boat, as well as their use. According to the type of the craft, the intended use and the design category, there are:	4.1	[Yes ?]	
2 - deck zones assigned according to 4.2	4.1	[Yes ?]	
3 - safety devices installed to these deck zones according to 4.3	4.1	[Yes ?]	
4 Areas which are not intended to accommodate persons during normal operation and therefore not considered to be part of the deck zones are described in the craft owner's manual	4.1	[Yes ?]	
5 The watercraft is able to accommodate the maximum recommended number of persons in a combination of deck area Z1 and the interior of the watercraft. Where different maximum recommended number of persons are assigned to different design categories for the craft, it is ensured the requirements of ISO 15085:2024 are met for each of these design categories.	4.2	[Yes ?]	
6 The areas of the craft are divided into deck zones as described in Table 1:	4.2	[Yes ?]	
7 - Zone Z1 includes all areas that require <u>access at all times</u> , at least the following: helm position; emergency steering position; emergency controls; manual bilge pump(s); sail setting equipment; primary controls areas for furling, unfurling, hoisting, dropping sails; main companionway(s); areas within the zone where persons stand, lean, lay or sit	4.2 table 1	[Yes ?]	
8 - Zone Z2 includes all areas that require <u>access at a speed of 4 knots and below</u> , at least the following: engine space; emergency steering installation; tow points; sail hoist, drop areas for non-furling sails; life raft stowage; areas within the zone where persons stand, lean, lay or sit	4.2 table 1	[Yes ?]	
9 - Zone Z3 includes all areas that require <u>access when nearly stationary</u> , at least the following: mooring strong points; means of reboarding; boarding area; areas within the zone where persons stand, lean, lay or sit	4.2 table 1	[Yes ?]	
10 For each option related to a design category and craft length (L _H) the requirements of the relevant clause for the corresponding safety devices of table 3 and table 4 are fulfilled	4.3	[Yes ?]	
11 For non-sailing boats, the safety devices requirements of table 3 are fulfilled	4.3	[Yes / NA ?]	

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



12	For sailing boats, the safety devices requirements of table 4 are fulfilled	4.3	[Yes / NA ?]	
13	There are deck zone Z3 areas where persons do not have an activity as specified in Table 1 and only stand, lean, lay or sit without handholds	4.3	[Yes; No ?]	
14	General requirements for deck zones:	4.4		
15	Connection between areas of the deck zones; either directly or by passage through the interior is provided	4.4.1	[Yes ?]	
16	Within any deck zone, openings leading directly to water and not provided with a hatch or other protective covering are either: - surrounded by barriers to falling overboard as required in Clause 8; or - fitted with trampolines or nets	4.4.1	[Yes ?]	
17	Steps shall not be higher than 500 mm and obstacles shall not be higher or longer than 500 mm	4.4.1 fig.1	[Yes / NA ?]	
18	The outer periphery areas of deck zones Z1 and Z2, is angled transversally less than 15° to the horizontal, when the craft is upright	4.4.2	[Yes ?]	
19	The outer periphery areas of deck zones Z1 and Z2 have a minimum width of - 150 mm for categories A and B - 120 mm for category C - 100 mm for design category D	4.4.2	[Yes ?]	
20	All deck zones where people can stand or walk shall be fitted with slip-resistant surfaces with the exemptions of clause 5.1 (transition zones; glazed appliances not larger than 500mm x 500mm)	5.1	[Yes ?]	
21	Trampolines and nets which are part of the deck zones shall have slip-resistant characteristics	5.2	[Yes ?]	
22	The junction between the trampolines or nets and the craft minimize the risk of foot trapping	5.2	[Yes ?]	
23	Foot-stops as required by clause 4.3 are installed continuously at the outer periphery of the deck zones with the exception of item 23-27	6.2	[Yes ?]	
24	Foot-stops are be omitted on the following:			
25	- capsize-recoverable craft	6.2	[Yes / NA ?]	
26	- where the crew is not intended to walk but only sit when the craft is underway (e.g. a sailing-boat deck edge where the crew hikes)	6.2	[Yes / NA ?]	
27	- the aft limit (perpendicular to the longitudinal axis) of deck zones (e.g. top of transoms)	6.2	[Yes / NA ?]	
28	- front and aft structural beams (perpendicular to the longitudinal axis) of multihulls	6.2	[Yes / NA ?]	
29	The upper edge of the foot-stop is not less than 25mm for non-sailing boats in design cat A and B or 20mm of design cat C	6.3	[Yes / NA ?]	
30	The upper edge of the foot-stop is not less than 30mm for sailing boats in design cat A and B or 25mm of design cat C	6.3	[Yes / NA ?]	
31	The height of the foot-stop is measured according to clause 6.3 [see Figure 2 a) - 2 b) - 2 c)]	6.3 fig.2	[Yes / NA ?]	
32	Angled surface foot-stops are only be used on non-sailing boats of design categories C and D, they have an inclination of not less than 20° from the horizontal and their surfaces are slip-resistant [see Figure 2 d)].	6.4 fig.2	[Yes / NA ?]	
33	Vertical clearances between deck and foot-stop level, the open spaces between the deck level and the bottom of the lowest point of foot-stopping shall not be greater than 40mm[see Figure 2 e)].	6.5 fig. 2	[Yes / NA ?]	

compliant: Yes or V

not applicable: NA

follow up on variation report: Rpt or X

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



34	Where a bulwark provides the foot-stop function, vertical gap between the deck surface and the bulwark shall not be higher than 100 mm.	6.5	[Yes / NA ?]	
35	Steps in the deck within 100mm of the foot-stop are not be higher than 15mm [see in Figure 2 a)].	6.6 fig 2	[Yes / NA ?]	
36	Gaps in the foot-stop rail measured between foot-stops and/or fittings, shall be less than - 150 mm distance for craft of 8,5 m and less - 250 mm distance for craft greater than 8,5 m Fittings providing an effective foot-stop are considered as a foot-stop.	6.7	[Yes / NA ?]	
37	Handholds, as installed, are capable of being grasped by an entire hand without additional action by the user	7.1	[Yes / NA ?]	
38	Handholds, as installed, provide efficient access and use	7.1	[Yes / NA ?]	
39	Handholds in all deck areas are located in the inboard vicinity of the outer deck edge	7.2	[Yes ?]	
40	The maximum distance between two adjacent handholds does not exceed 1,5 m	7.2	[Yes ?]	
41	The maximum transverse distance between the outer deck edge and the handhold does not exceed 1,0m	7.2	[Yes ?]	
42	Where the handhold is located inboard of the side deck and where deck zones of 300 mm width or less with an adjacent superstructure higher than 450 mm, handholds are placed at a minimum height of 450 mm above deck level	7.2	[Yes / NA ?]	
43	Where the handhold is located inboard of the side deck, handholds fitted less than 300 mm inboard from the outer deck edge are placed at least 450 mm above deck level (but may be lower than the adjacent superstructure)	7.2	[Yes / NA ?]	
44	Where the handhold is located inboard of the side deck, handholds fitted more than 300 mm inboard from the outer deck zone edge are placed at any height but no more than 1,80 m above deck level.	7.2	[Yes / NA ?]	
45	Where the handhold is located outboard of the side deck, handholds are placed at least 450 mm above deck level	7.2	[Yes / NA ?]	
46	Where the handhold is located outboard of the side deck, where stairs, ladders or companionways are located within a distance of 1,0 m to the outer deck edge, handholds are installed in their vicinity	7.2	[Yes / NA ?]	
47	On non-sailing boats with LH < 6 m, on the outer deck edge, the max. distance between two adjacent handholds does not exceed 1,2 m	7.2	[Yes / NA ?]	
48	Barriers to falling overboard are installed continuously at the outer periphery of the deck zones	8.1	[Yes / NA ?]	
49	If glass is used as part of the barrier to falling overboard, only high impact resistance glass is used	8.1	[Yes / NA ?]	
50	The minimum height of barriers to falling overboard is as specified in Table 5.	8.2.1 table 5	[Yes / NA ?]	
51	Sailing boats are fitted with an intermediate guard-rail or guard-wire if it has a high barrier to falling overboard consisting of a guard-rail or guard-wire. The vertical gap between this intermediate line and the deck, foot-stop, bulwark, etc., whichever is higher, shall not exceed that stated in Table 5.	8.2.1 table 5	[Yes / NA ?]	

compliant: Yes or V

not applicable: NA

follow up on variation report: Rpt or X

Checklist_Evaluation_Module B_G en260703



Watercraft manufacturer:	
Watercraft model name:	

52	If the deck zone has a change of height in way of the barriers to falling overboard, the lower gap increases to that stated in Table 5 for no longer than 500 mm measured along the line of the barrier	8.2.1 table 5	[Yes / NA ?]	
53	If there are permanent openings in barriers to falling overboard, the gap does not exceed 150mm	8.2.2	[Yes / NA ?]	
54	Permanently fixed and quickly operable mobile sections are fitted in vicinity of openings to facilitate boarding or reboarding of crew or equipment	8.2.2	[Yes / NA ?]	
55	For sailing boats: Bow pulpits may be open but the opening between the pulpit and any part of the craft is not greater than 380mm.	8.3.1	[Yes / NA ?]	
56	For sailing boats: Transom barriers to falling overboard for sailing boats fulfill the requirements of clause 8.1 and 8.2	8.3.2	[Yes / No / NA ?]	
57	If question 57 is answered with 'No', where the transverse aft part of the deck zone is a seat, the minimum height of a barrier to falling overboard is 450mm for high barriers or 300mm for low barriers	8.3.2	[Yes / NA ?]	
58	If question 57 is answered with 'No', where the transverse aft part of the deck zone is a cockpit floor, the minimum height requirement for a barrier to falling overboard is 800mm for high barriers and 650mm for low barriers	8.3.2 fig 5	[Yes / NA ?]	
59	The exemptions for forward cross beams of sailing catamarans of cl. 8.3.3 are taken into account	8.3.3	[Yes / NA ?]	
60	For sailing trimarans: In the areas where a person falling from the deck zone would land on a trampoline or net with a minimum width of 700mm, barriers to falling overboard are omitted on the central hull	8.3.4	[Yes / NA ?]	
61	Elevated deck zones are provided with protection to minimize the risk of falling overboard, according to the requirements of Table 6.	8.4 table 6	[Yes / NA ?]	
62	H1 and H2 values are defined according to Table 7 and function of the barrier to falling overboard type fitted at lower deck edge.	8.4 table 7	[Yes / NA ?]	
63	As installed, the barrier to falling overboard system withstand an 1820 N static load applied over a contact length which shall not exceed 100 mm at any location, in an outboard horizontal direction, without failure such that it no longer performs its intended purpose	8.5.1	[Yes / NA ?]	
64	Guard-rails are capable of supporting, at any point along their top a horizontal force of 280 N (perpendicularly to the guard-rail local direction) with a deflection at the force level not greater than 50 mm measured at the top of the device. If the fitting has play, the deflection shall be measured from the end of movement. There is no permanent deformation of the guard-rail or support after the force has been taken off. Where there is play in the assembly, it shall not be more than 40 mm measured between its extremes.	8.5.2	[Yes / NA ?]	
65	Conformity with the requirements of 8.5.2 are either demonstrated by calculation or test. The calculation or the test report are submitted.	8.5.2	[Yes / NA ?]	

compliant: Yes or V

not applicable: NA

follow up on variation report: Rpt or X

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



66	If a synthetic line is used, it is chafe resistant or protected against chafing, particularly in bearing areas on stanchions and pulpits.	8.5.3	[Yes / NA ?]	
68	Where a material type permits a diameter smaller than 3,5 mm, sheathing is fitted on the guard-line to increase its diameter to 3,5 mm or greater.	8.5.3	[Yes / NA ?]	
69	Guard-lines are tightened to provide a firm support. Devices are fitted to tension the guard-line.	8.5.3	[Yes / NA ?]	
70	Stanchions or guard-line supports are designed and installed such that the distance between two supports, measured along the line, is not greater than 2,20 m.	8.5.4.1	[Yes / NA ?]	
71	The requirements of 8.5.4.2 are verified by calculation or test, for at least one sample of the device (stanchion or guard-line support, base, fixture system). In the case of a test, to measure the deflection and strength, the stanchion and its support are installed either on the craft or on a test jig.	8.5.4.2	[Yes / NA ?]	
72	Stanchions/line supports are mechanically secured in their supports (the tension of the guard-lines is not considered to satisfy this requirement)	8.5.4.3	[Yes / NA ?]	
73	Stanchions/line supports are angled outboard less or equal to 10° from the vertical, at all points 50 mm above the deck	8.5.4.3	[Yes / NA ?]	
74	Hooking points are located within 1 m of the edge of the main companionway hatch/door.	9.2	[Yes / NA ?]	
75	Hooking points are located within 2 m of all-weather deck steering positions.	9.2	[Yes / NA ?]	
76	Hooking points are located within 2 m of the mast of sailing boats.	9.2	[Yes / NA ?]	
77	Hooking points are located within 2 m of the winch positions of sailing boats.	9.2	[Yes / NA ?]	
78	Hooking points are located within 2 m of the windlass or towing strong points.	9.2	[Yes / NA ?]	
79	Hooking points are located within 2 m of the life-raft stowage.	9.2	[Yes / NA ?]	
80	Hooking points are not more than 3 m apart.	9.2	[Yes / NA ?]	
81	Habitable boats susceptible to inversion are fitted with hooking points accessible when inverted: - within 1 m of each escape hatch - within 2 m to life-raft stowage point(s) - no more than 3 m apart from each other	9.3	[Yes / NA ?]	
82	Hooking point eyes that are designed to accept a harness shall be inscribed within a circle of 15 mm. The cross-section of the material to which the harness may be clipped is no larger than 12,5 mm	9.4	[Yes / NA ?]	
83	Attachment points for jack-lines are fitted port and starboard on deck, to provide secure fixing of jack-lines.	10.2	[Yes / NA ?]	
84	The jack-lines are long enough to allow movement on deck for boat operation.	10.2	[Yes / NA ?]	
85	Each section of jack-lines are as long as practicable. Attachment points are fitted at the ends of each section.	10.2	[Yes / NA ?]	

compliant: Yes or V

not applicable: NA

follow up on variation report: Rpt or X

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



86	If a high-speed boat: Craft is fitted with means of support for each of its occupants to maintain upright posture, when the craft is underway, minimizing the possibilities of occupants being thrown overboard in case of sharp turns, strong acceleration or movements in the sea.	11.1	[Yes / NA ?]	
87	Support is provided by one handhold according to clause 7 and body support as in clause 11.3. or one or two handholds, as required in clause 7, allowing simultaneous gripping of both hands	11.1	[Yes / NA ?]	
88	If an occupant position requires simultaneous gripping of both hands, the handhold device(s) allow a minimum separation of 200 mm between hands	11.2	[Yes / NA ?]	
89	Where round tubing is used as a handhold designated for high-speed craft body support, the diameter shall be in the range 19 mm to 38 mm.	11.2	[Yes / NA ?]	
90	The body support has a height of ≥ 120 mm above the rigid bottom of the seat with compressed cushion.	11.3	[Yes / NA ?]	
91	When standing or leaning, the body support provides support for back and torso.	11.3	[Yes / NA ?]	
92	When sitting riding astride a seat, body support is provided by action of the knees.	11.3	[Yes / NA ?]	
93	Where a seat structure is permanently fitted to the craft by means of an attachment system, the seat and the attachment system shall conform to the strength requirements given in Annex A.	11.4	[Yes / NA ?]	
94	As an alternative to options XI and XII handhold requirements in deck zone Z1 (see 4.3), sailing boats are fitted with toe straps.	12	[Yes / NA ?]	
95	The location of the toe straps allow the intended crew to hike safely at the intended position	12	[Yes / NA ?]	
96	Propeller propulsion is not used as means of reboarding.	13	[Yes ?]	
97	The boat is provided with a means of reboarding by a person in the water unaided, by either:	13		
98	- a rigid ladder according to 13.2, or	13.1	[Yes / NA ?]	
99	- a non-rigid ladder according to 13.3, or	13.1	[Yes / NA ?]	
100	- another dedicated device, or	13.1	[Yes / NA ?]	
101	- a design of the watercraft which enables reboarding without a dedicated device.	13.1	[Yes / NA ?]	
102	Any device for activation of a deployable device is located not higher than 500 mm above waterline.	13.1	[Yes / NA ?]	
103	Any flexible activation device, e.g. a rope, is fixed not higher than 500 mm above the waterline.	13.1	[Yes / NA ?]	
104	A deployable device can be activated even if engine is stopped with any primary energy fault.	13.1	[Yes / NA ?]	
105	Attention has been paid to the location of the means of reboarding relative to possible danger from propeller(s).	13.1	[Yes ?]	
106	The reboarding means leads directly to a deck zone (Z3, Z2 or Z1)	13.2	[Yes / NA ?]	
107	If reboarding means is rigid ladder, following requirements are met:	13.2		
108	- it does not swing away in the water under load, and	13.2	[Yes / NA ?]	
109	- it is not angled beyond vertical as installed, and	13.2	[Yes / NA ?]	

compliant: Yes or V

not applicable: NA

follow up on variation report: Rpt or X

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



110	- steps or rungs have a treading depth of 25 mm being slip resistant, and	13.2	[Yes / NA ?]	
111	- steps or rungs have a maximum spacing of 305 mm, and	13.2	[Yes / NA ?]	
112	- a minimum rung width of 100 mm per foot or a minimum total width of 200 mm for two foot [figure a)], and	13.2	[Yes / NA ?]	
113	- a horizontal tread clearance of at least 100 mm from adjacent structure, and	13.2	[Yes / NA ?]	
114	- the bottom step is at least 560 mm below the waterline in m _{LC} condition, and	13.2	[Yes / NA ?]	
115	- allows a grip clearance from adjacent structures of at least 32 mm, and	13.2	[Yes / NA ?]	
116	- a handhold that can be reached on the ladder or its vicinity not more than 500 mm away from the upper step or rung, and	13.2	[Yes / NA ?]	
117	- the highest step or rung is located not more than 500 mm below the adjacent area leading to a Z3 deck zone, and	13.2	[Yes / NA ?]	
118	- the ladder fulfils its purpose if subjected to a vertical force of 1800 N applied at any point.	13.2	[Yes / NA ?]	
119	If reboarding means is a non-rigid ladder, following requirements are met:	13.3		
120	- steps or rungs have a treading depth of 25 mm being slip resistant, and	13.3	[Yes / NA ?]	
121	- steps or rungs have a maximum spacing of 305 mm, and	13.3	[Yes / NA ?]	
122	- the bottom step is at least 1200 mm below the waterline in m _{LC} condition and	13.3	[Yes / NA ?]	
123	- the highest step or rung is located not more than 500 mm below the adjacent area leading to a Z3 deck zone, and	13.3	[Yes / NA ?]	
124	- rigid rungs have a width of 250 mm, and	13.3	[Yes / NA ?]	
125	- the ladder is attached by at least two separate points spaced not less than the rung width, and	13.3	[Yes / NA ?]	
126	- the submerged steps or rungs have negative buoyancy, and	13.3	[Yes / NA ?]	
127	- the ladder fulfils its purpose if subjected to a vertical force of 1800 N applied at any point the ladder.	13.3	[Yes / NA ?]	

The following questions shall be filled in by the watercraft manufacturer and appropriate documentation shall be submitted to the inspector for verification.

		Clause	Requirements	Checked ?
128	Plastic materials used in safety devices shall be capable of operation in ambient temperature of -20 °C to +60 °C	4.5.1	[Yes / NA ?]	
129	Plastic materials used in safety devices shall be capable of withstanding storage at ambient temperature of -30 °C to +60 °C	4.5.2	[Yes / NA ?]	
130	The connection of trampoline and nets to the craft support, without failure such that they no longer perform their intended purpose, a uniform load over the area of the trampoline or net, of 3 000 N/m ² or 50% of the maximum recommended number of persons, whichever is less	5.2	[Yes / NA ?]	
131	Handholds, as built and installed, withstand a load of 1 500 N, in any direction, at any point, along their length without failure such that they no longer perform their intended purpose	7.3	[Yes / NA ?]	

compliant: Yes or V

not applicable: NA

follow up on variation report: Rpt or X

Checklist_Evaluation_Module B_G en260703



Watercraft manufacturer:	
Watercraft model name:	

132	A handhold dedicated to more than one person shall, in addition to the point load above, be designed to withstand an equally distributed load equal to 1 500 N multiplied by the number of people designated to hold at the same time.	7.3	[Yes / NA ?]	
133	Guard-rails are capable of supporting, at any point along their top a horizontal force of 280 N (perpendicularly to the guard-rail local direction) with a deflection at the force level not greater than 50 mm measured at the top of the device. If the fitting has play, the deflection shall be measured from the end of movement. There is no permanent deformation of the guard-rail or support after the force has been taken off. Where there is play in the assembly, it shall not be more than 40 mm measured between its extremes.	8.5.2	[Yes / NA ?]	
134	Guard-rails are capable of supporting, at any point along their top, a horizontal force of 560 N without breaking	8.5.2	[Yes / NA ?]	
135	The strength of the high guard-lines, low guard-lines and intermediate guard-lines fulfil the requirements of Table 8.	8.5.3 table 8	[Yes / NA ?]	
136	Any device forming part of the guard-lines beyond its attachment point withstand, as installed, the ultimate loads defined in Table 8. These requirements are verified by test or calculation	8.5.3	[Yes / NA ?]	
137	Stanchions or guard-line supports are capable of supporting, at their top, the following outboard forces applied perpendicular to the guard-line local direction: - a horizontal force of 280 N with a deflection under load of the stanchion or support not greater than 50 mm at the force level measured at the top of the device. If the fitting has play, the deflection is measured from the end of movement - horizontal force of 560 N without breaking Assessment of the stanchions for the above requirements are made without installed lines	8.5.4.2	[Yes / NA ?]	
138	If boat is in Cat. C: Hooking points withstand a horizontal force of 3600 N.	9.5	[Yes / NA ?]	
139	If boat is in Cat. A and B: Hooking points withstand a horizontal force of 6000 N.	9.5	[Yes / NA ?]	
140	Attachment points for jack-lines withstand a horizontal force of 20000 N in the direction of, and up to an angle of 30° from a line connecting them.	10.3	[Yes / NA ?]	
141	If used as an alternative to options XI and XII handhold requirements in deck zone Z1, each section of a toe strap (i.e. between attachments) shall, as installed, withstand a vertical load of 1 000 N per number of crew that will use that section.	12	[Yes / NA ?]	
142	If a deployable device is provided as means of reboarding, the work force required for activation is maximum 100 N.	13.1	[Yes / NA ?]	
143	A test according to 13.4 has been conducted by a person wearing a flotation device according to Table 1, if the device is: - non-rigid ladder, or - any other dedicated device, or - reboarding by design of the craft.	13.4	[Yes / NA ?]	

Instructions/Warnings to be included in the owner's manual

compliant: Yes or V

not applicable: NA

follow up on variation report: Rpt or X

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



144	Deck zone area(s) explained as text or sketch.	4.1	[Yes / NA ?]	
145	Due to ageing, ultraviolet rays or chafe, the synthetic line shall be periodically inspected or replaced. The period between inspections or maintenance, and the actions to be performed, are indicated in the owner's manual.	8.5.3	[Yes / NA ?]	
146	If option X is used, a sentence shall indicate that the boat is only intended for daytime sailing and not at night.	4.3, table 4	[Yes / NA ?]	
147	Description of re-boarding and how to deploy it, with a recommendation that it shall ne kept readily deployable and usable at all times.	13	[Yes ?]	

Comments:
