



CHECKLIST

SMALL CRAFT- MAN-OVERBOARD PREVENTION AND RECOVERY

Ref.: EN ISO 15085:2003/A2:2018 (ISO 15085:2003/Amd 2:2017)

Withdrawal date OJ: 2027-08-13

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



Subject to check	Clause	Requirements	Checked ?
1 Safe access is provided either via the working deck, the interior of the boat or combination thereof to boat steering including emergency steering, strong points, sail handling and trimming, interior and engine room compartment.	4.1	[Yes ?]	
2 The working deck area is free, continuous and not angled more than 15° from the horizontal.	4.3	[Yes ?]	
3 The working deck area has a width of ≥ 100 mm for Design Cat. D, 120 mm for Cat. C, and 150 mm for Cat. A and B, measured according to 4.3.	4.3	[Yes ?]	
4 All working decks are connected.	4.4	[Yes ?]	
5 Steps and obstacles higher or longer than 500 mm are avoided.	4.4	[Yes ?]	
6 For non-sailing boats: the requirements of Table 3 are fulfilled.	6.2	[Yes / NA ?]	
7 For sailing boats: The requirements of Table 4 are fulfilled.	6.3	[Yes / NA ?]	
8 Working deck areas are slip resistant.	7.1	[Yes ?]	
9 The slip resistant surfaces have no spacing greater than 75 mm for non-glazed areas, and 500 mm for glazed areas.	7.1	[Yes ?]	
10 Sailing dinghies have at least slip resistant surfaces on locations where people are supposed to tread.	7.1	[Yes / NA ?]	
11 Trampolines and nets part of the working deck, have slip-resistant characteristics.	7.2	[Yes / NA ?]	
12 Openings in the working deck area having a depth > 1m, and not provided with a lid or hatch, are surrounded by guard-rails according to clause 9.	7.2	[Yes / NA ?]	
13 Openings in the working deck area having a depth > 1m, and not provided with a lid or hatch, are provided with nets or trampolines.	7.2	[Yes / NA ?]	
14 The junction between trampoline or net and the boat does not involve any risk of foot trapping.	7.2	[Yes / NA ?]	
15 The connection of trampoline and nets withstands a uniform load of 3000 N/mm ² or 50% of the crew limit, whichever is smaller.	7.2	[Yes / NA ?]	
16 Footstops are as close as practical to the outboard edges of the working deck with regard to the exceptions in 8.2.	8.2	[Yes ?]	
17 For Cat. C sailing boats: the footstop height is 25 mm.	8.3	[Yes / NA ?]	
18 For Cat. C non-sailing boats: the footstop height is 20 mm.	8.3	[Yes / NA ?]	
19 For Cat. A and B sailing boats: the footstop height is 30 mm.	8.3	[Yes / NA ?]	
20 For Cat. A and B non-sailing boats: the footstop height is 25 mm.	8.3	[Yes / NA ?]	

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



21	The footstop height is measured according to the requirements of 8.3.	8.3	[Yes / NA ?]	
22	The footstop angle to the vertical is $\leq 30^\circ$.	8.3	[Yes / NA ?]	
23	If angled surfaces foot-stops on non-sailing boats of design categories C and D: Surfaces shall have an inclination $\geq 20^\circ$ from the horizontal and a height according to 8.3 being slip-resistant.	8.4	[Yes / NA ?]	
24	The vertical clearance between deck and foot-stop the open spaces to the lowest foot-stopping point is ≤ 40 mm. See figure 2e.	8.5	[Yes / NA ?]	
25	Within 100 mm from the footstop there is no step in the working deck level > 15 mm.	8.6	[Yes / NA ?]	
26	Gaps in footstop rails are ≤ 100 mm to the edge of the adjacent fitting or footstop rail.	8.7	[Yes / NA ?]	
27	Handholds fitted < 300 mm inboard from the outer working deck edge are placed ≥ 500 mm above deck level, but not higher than the adjacent superstructure.	9.2	[Yes / NA ?]	
28	Handholds fitted > 300 mm inboard from the outer working deck edge are placed at any height.	9.2	[Yes / NA ?]	
29	On route along the outer edges of the working deck, the maximum distance between two handholds is $\leq 1,5$ m.	9.2	[Yes / NA ?]	
30	Low guard-rails have a height of at least 450 mm.	10.2	[Yes / NA ?]	
31	High guard-rails have a height of at least 600 mm.	10.2	[Yes / NA ?]	
32	For low guard-rail: if discontinuities in working deck level, the vertical gap between the lowest guard-rail/line and the deck or foot-stop, coaming etc, is not greater than 560 mm.	10.2	[Yes / NA ?]	
33	For high guard-rail: if discontinuities in working deck level, the vertical gap between the lowest or intermediate guard-rail/line and the deck or foot-stop, coaming etc, is not greater than 380 mm.	10.2	[Yes / NA ?]	
34	The maximum length of these discontinuities is ≤ 600 mm.	10.2	[Yes / NA ?]	
35	If sailing craft: If high guard-rail/guard-lines are installed, an intermediate guard-rail is fitted with the gap between this intermediate line and the deck, foot, stop, bulwark, etc, whichever is higher, ≤ 300 mm.	10.3	[Yes / NA ?]	
36	The gap between this intermediate guard-rail and the deck, foot-stop, coaming etc., is ≤ 300 mm.	10.3	[Yes / NA ?]	
37	Alternatively, the intermediate line is replaced by a device limiting the gap between two adjacent protections below 380 mm, in any direction.	10.3	[Yes / NA ?]	
38	Any part of the working deck higher than H1 in Table 5 from the adjacent part of the working deck is equipped with a footstop according to clause 8.	10.4	[Yes / NA ?]	
39	Any part of the working deck higher than H2 in Table 5 from the adjacent part of the working deck is equipped with a footstop according to clause 8, and guard-rails having the same height as at the outer periphery of the deck.	10.4	[Yes / NA ?]	
40	If openings in the guard-rail/guard-lines: Permanently fixed and quickly operable mobile sections are fitted in way of these openings. These sections shall be designed not to open inadvertently.	10.5	[Yes / NA ?]	

compliant: Yes or V

not applicable: NA

follow up on variation report: Rpt or X

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



41	Openings in guard-rails for passage of sails have no gap transversally and the space between the rails is ≤ 150 mm.	10.5	[Yes / NA ?]	
42	The bow pulpit opening between pulpit and any part of the boat is ≤ 360 mm.	10.6	[Yes / NA ?]	
43	If high guard-rails are required: Aft pulpits are ≥ 600 mm height.	10.7.1	[Yes / NA ?]	
44	If high guard-rails are required: The transversal lines do not meet the requirements of 10.1, 10.2, 10.3 and 12.2.1 since they meet the requirements of 10.7.1.	10.7.1	[Yes / NA ?]	
45	If low guard-rails are required: Aft pulpits are ≥ 450 mm height.	10.7.2	[Yes / NA ?]	
46	If low guard-rails are required: The transversal lines do not meet the requirements of 10.1, 10.2, 10.3 and 12.2.1 since they meet the requirements of 10.7.2.	10.7.2	[Yes / NA ?]	
47	If a sailing catamaran, the wire/rod and stanchion bracing on the forward cross beam is regarded as guard-rail. The minimum height is according to Table 4.	10.8	[Yes / NA ?]	
48	If a sailing catamaran, the longitudinal guard-rail height on outer edges diminishes to zero at forward beam. The greatest distance between handhold points on transverse and longitudinal guard-rails is $\leq 0,75$ m.	10.8	[Yes / NA ?]	
49	If a sailing catamaran, guard-rails are omitted on the central hull in areas where a person falling from working deck would land on a trampoline. The width of this trampoline is at least 700 mm.	10.9	[Yes / NA ?]	
50	Guard-lines are firmly supported. Means is provided to tension the line.	12.1	[Yes / NA ?]	
51	The spacing between stanchions or guard-line supports is $\leq 2,2$ m.	12.2.1	[Yes / NA ?]	
52	Stanchions/line supports are mechanically secured in their supports, not taken into consideration the tension of the guard-lines.	12.2.3	[Yes / NA ?]	
53	Guard-lines are held horizontally and vertically by the stanchion/line support.	12.2.3	[Yes / NA ?]	
54	Stanchions/line supports are not angled outboard more than 10° from the vertical, at any point above 50 mm from the deck.	12.2.3	[Yes / NA ?]	
55	Hooking points are located within 1 m of the edge of the main access hatch/door.	13.2	[Yes / NA ?]	
56	Hooking points are located within 2 m of all outside steering positions.	13.2	[Yes / NA ?]	
57	Hooking points are located within 2 m of the mast of sailing boats.	13.2	[Yes / NA ?]	
58	Hooking points are located within 2 m of the winch positions of sailing boats.	13.2	[Yes / NA ?]	
59	Hooking points are located within 2 m of the windlass or towing strong points.	13.2	[Yes / NA ?]	
60	Hooking points are not more than 3 m apart.	13.2	[Yes / NA ?]	
61	If a habitable sailing multihull of Cat. A and B: At least one hooking point is in the vicinity of each escape hatch to be used in inverted position.	13.2	[Yes / NA ?]	

compliant: Yes or V

not applicable: NA

follow up on variation report: Rpt or X

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



62	Any hooking point is inscribed within a circle of 15 mm diameter.	13.3	[Yes / NA ?]	
63	Attachment points for jack-lines are fitted port and starboard on deck, to provide secure fixing of jack-lines.	14.2	[Yes / NA ?]	
64	The jack-lines are long enough to allow movement on deck for boat operation.	14.2	[Yes / NA ?]	
65	Jack-lines are as long as practicable. Attachment points are fitted at the ends of each section.	14.2	[Yes / NA ?]	
66	If a high-speed boat: Each occupant has a body support limiting the risk of being thrown overboard in case of sharp turns, acceleration or movements in sea.	15.1	[Yes / NA ?]	
67	Support is provided by one handhold according to clause 9 and body support.	15.1	[Yes / NA ?]	
68	Support is provided by two handholds according to clause 9, allowing simultaneous gripping of two hands.	15.1	[Yes / NA ?]	
69	The body support has a height of ≥ 120 mm above the rigid bottom of the seat with compressed cushion.	15.1	[Yes / NA ?]	
70	When standing or leaning, the body support provides support for back and torso.	15.2	[Yes / NA ?]	
71	When sitting riding astride a seat, body support is provided by action of the knees.	15.2	[Yes / NA ?]	
72	Propeller propulsion is not used as means of reboarding.	16	[Yes ?]	
73	The boat is provided with a means of reboarding by a person in the water unaided, by either:	16		
74	- a rigid ladder according to 16.2, or	16.1	[Yes / NA ?]	
75	- a non-rigid ladder according to 16.3, or	16.1	[Yes / NA ?]	
76	- another dedicated device, or	16.1	[Yes / NA ?]	
77	- a design of the watercraft which enables reboarding without a dedicated device.	16.1	[Yes / NA ?]	
78	Any device for activation of a deployable device is located not higher than 500 mm above waterline.	16.1	[Yes / NA ?]	
79	Any flexible activation device, e.g. a rope, is fixed not higher than 500 mm above the waterline.	16.1	[Yes / NA ?]	
80	A deployable device can be activated even if engine is stopped with any primary energy fault.	16.1	[Yes / NA ?]	
81	Attention has been paid to the location of the means of reboarding relative to possible danger from propeller(s).	16.1	[Yes ?]	
82	The reboarding means leads directly to the working deck.	16.1	[Yes / NA ?]	
83	The reboarding means leads to a part outside of the working deck with slip resistance surface and fitted with handholds on its way leading to the working deck.	16.1	[Yes / NA ?]	
84	If reboarding means is rigid ladder, following requirements are met:	16.2		
85	- it does not swing away in the water under load, and	16.2	[Yes / NA ?]	
86	- it is not angled beyond vertical as installed, and	16.2	[Yes / NA ?]	
87	- steps or rungs have a treading depth of 25 mm being slip resistant, and	16.2	[Yes / NA ?]	
88	- steps or rungs have a maximum spacing of 305 mm, and	16.2	[Yes / NA ?]	

compliant: Yes or V

not applicable: NA

follow up on variation report: Rpt or X

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



89	- a minimum rung width of 100 mm per foot or a minimum total width of 200 mm for two foot [figure a)], and	16.2	[Yes / NA ?]	
90	- a horizontal tread clearance of at least 100 mm from adjacent structure, and	16.2	[Yes / NA ?]	
91	- the bottom step is at least 560 mm below the waterline in m _{LC} condition, and	16.2	[Yes / NA ?]	
92	- allows a grip clearance from adjacent structures of at least 32 mm, and	16.2	[Yes / NA ?]	
93	- a handhold that can be reached on the ladder or its vicinity not more than 500 mm away from the upper step or rung, and	16.2	[Yes / NA ?]	
94	- the highest step or rung is located not more than 500 mm below the adjacent area leading to the working deck, and	16.2	[Yes / NA ?]	
95	- the ladder fulfils its purpose if subjected to a vertical force of 1800 N applied at any point.	16.2	[Yes / NA ?]	
96	If reboarding means is a non-rigid ladder, following requirements are met:	16.3		
97	- steps or rungs have a treading depth of 25 mm being slip resistant, and	16.3	[Yes / NA ?]	
98	- steps or rungs have a maximum spacing of 305 mm, and	16.3	[Yes / NA ?]	
99	- the bottom step is at least 1200 mm below the waterline in m _{LC} condition and	16.3	[Yes / NA ?]	
100	- the highest step or rung is located not more than 500 mm below the adjacent area leading to the working deck, and	16.3	[Yes / NA ?]	
101	- rigid rungs have a width of 250 mm, and	16.3	[Yes / NA ?]	
102	- the ladder is attached by at least two separate points spaced not less than the rung width, and	16.3	[Yes / NA ?]	
103	- the submerged steps or rungs have negative buoyancy, and	16.3	[Yes / NA ?]	
104	- the ladder fulfils its purpose if subjected to a vertical force of 1800 N applied at any point the ladder.	16.3	[Yes / NA ?]	

The following questions shall be filled in by the watercraft manufacturer and appropriate documentation shall be submitted to the inspector for verification.

Subject to check	Clause	Requirements	Checked ?
105 Handholds withstand, as installed, a horizontal force of 1500 N without rupture.	9.3	[Yes / NA ?]	
106 Guard-rails withstand a horizontal force of 280 N with a deflection at the force level of ≤ 50 mm.	11	[Yes / NA ?]	
107 Guard-rails withstand a horizontal force of 560 N without breaking.	11	[Yes / NA ?]	
108 Guard-lines have a strength according to Table 6.	12.1	[Yes / NA ?]	
109 Any device forming a part of guard-lines withstand the loads defined in Table 5.	12.1	[Yes / NA ?]	
110 Stanchions or guard-line supports withstand a horizontal force of 280 N with a deflection at the force level of ≤ 50 mm, assessed with no lines on.	12.2.2	[Yes / NA ?]	
111 Stanchions or guard-line supports withstand a horizontal force of 560 N without breaking, assessed with no lines on.	12.2.2	[Yes / NA ?]	

compliant: Yes or V

not applicable: NA

follow up on variation report: Rpt or X

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



112	If boat is in Cat. C: Hooking points withstand a horizontal force of 3600 N .	13.3	[Yes / NA ?]	
113	If boat is in Cat. A and B: Hooking points withstand a horizontal force of 6000 N.	13.3	[Yes / NA ?]	
114	Attachment points for jack-lines withstand a horizontal force of 20000 N in the direction of, and up to an angle of 30° from a line connecting them.	14.3	[Yes / NA ?]	
115	If a deployable device is provided as means of reboarding, the work force required for activation is maximum 100 N.	16.1	[Yes / NA ?]	
116	A test according to 16.4 has been conducted by a person wearing a flotation device according to Table 1, if the device is: - non-rigid ladder, or - any other dedicated device, or - reboarding by design of the craft.	16.4	[Yes / NA ?]	

Instructions/Warnings to be included in the owner's manual

117	Working deck area(s) explained as text or sketch.	4.1	[Yes / NA ?]	
118	If periodical inspection of guard-lines or replacement of the synthetic line is needed, the period between inspection or maintenance, and the actions to be performed are explained.	12.1	[Yes / NA ?]	
119	If option 4 is used, a sentence shall indicate that the boat is only intended for daytime sailing and not at night.	6.3	[Yes / NA ?]	
120	Description of re-boarding and how to deploy it, with a recommendation that it shall be kept readily deployable and usable at all times.	16	[Yes ?]	

Comments:
