

CHECKLIST

SMALL CRAFT - PERMANENTLY INSTALLED PETROL AND DIESEL FUEL TANKS

Ref.: EN ISO 21487:2018 (ISO 21487:2012/A1:2014/A2:2015)

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



Subject to check	Clause	Requirements	Checked ?
1 Fuel type.	3.1/3.2	[Petrol / Diesel]	
2 Provisions are made for determination of fuel level or quantity.	4.3.1	[Yes ?]	
3 Metal tanks shall be designed/installed that no exterior surface will trap water.	4.3.2	[Yes / NA ?]	
4 Non-integral tank supports, chocks or hangers shall be separated from the surface of metal tanks by a non-abrasive material, or welded to the tank.	4.3.4	[Yes / NA ?]	
5 The fuel fill pipe has a minimum diameter of 28,5 mm.	4.3.7	[Yes ?]	
6 Diesel tank equipped with inspection hatch(es), at least 120 mm diameter.	4.3.10	[Yes / NA ?]	
7 If petrol tank, not integral with hull.	5.1.1	[Yes / NA ?]	
8 If petrol tank, all fittings and openings on top. Metallic fill and ventilation pipes may be connected to the sides or ends if welded to the tank and reach above the tank top.	5.1.2	[Yes / NA ?]	
9 If petrol tank, no tank drains are permitted.	5.1.3	[Yes / NA ?]	
10 Label: Fuel tank information: -manufacturer's name/trademark, city or equivalent, and country; -year of manufacture; -design capacity, expressed in litres; -maximum temperature to which the tank may be exposed (for non-metallic tanks only); -fuel or fuels for which the tank is suitable, in symbols (as specified in ISO 11192) or in words; -maximum fill-up height above tank top, expressed in metres, and allowable test pressure, expressed in kilopascals; -"ISO 21487" marking or label if the tank is a non-metallic petrol fuel tank fire tested in accordance with this International Standard. Affixed: on the tank, visible during inspection.	8	[Yes ?]	

The following questions shall be filled in by the watercraft manufacturer and appropriate documentation shall be submitted to the inspector for verification.

Subject to check	Clause	Requirements	Checked ?
11 All seals such as gaskets, o-rings and joint-rings shall be of non-wicking, i.e. non-fuel absorbent, material.	4.1.1	[Yes ?]	

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



12	All materials are resistant to deterioration by the fuel and to other liquids (e.g. grease, lubricating oil, bilge solvents and sea water).	4.1.2	[Yes ?]	
13	Copper-based alloys for fittings are acceptable for direct coupling with all tank materials specified in Table 1, except aluminium.	4.2	[Yes / NA ?]	
14	Copper-based alloy fittings are used for aluminium tanks only if a galvanic barrier is arranged between fitting and tank.	4.2	[Yes / NA ?]	
15	Rigid fuel suction tubes and fill pipes which extend to the tank bottom have sufficient clearance to prevent contact with the bottom during normal operation.	4.3.3	[Yes / NA ?]	
16	If baffles are provided, the open area of the baffle is not greater than 30% of the tank cross-section in the plane of the baffle.	4.3.5	[Yes / NA ?]	
17	Baffle openings do not prevent fuel flow across the bottom or trap vapour.	4.3.6	[Yes / NA ?]	
18	The ventilation pipes have a minimum inside diameter of 11 mm (95 mm ²) or a ventilation opening preventing tank pressure exceeding 80% of the marked.	4.3.8	[Yes ?]	
19	The tank material and thicknesses comply with the requirements of Table 1.	4.3.9	[Yes ?]	
20	Non-integral tank installed to introduce loads into the structure.	4.4.1	[Yes / NA ?]	
21	If petrol tank, the pressure-impulse test requirements in 7.3 are met.	5.2.2	[Yes / NA ?]	
22	Alternatively, a metallic petrol tank may be tested in accordance to 7.2 with enhanced pressure but fulfils requirements for plating thickness, construction and welding.	5.2.2	[Yes / NA ?]	
23	If a non-metallic petrol tank, the fire test requirements in 7.4 and/or 7.5 are met.	5.2.3	[Yes / NA ?]	
24	If integral and cored hull, the core does not deteriorate from exposure.	6.1.1	[Yes / NA ?]	
25	Diesel integral fuel tanks are in accordance with ISO 12215-5.	6.1.3	[Yes / NA ?]	
26	Diesel tanks meet the leakage test requirements according to 7.1.2.	6.2.1	[Yes / NA ?]	
27	If diesel tank is non-metallic, non-integral and installed in engine compartment, the tank is fire tested according to 7.4 or 7.5.	6.2.3	[Yes / NA ?]	
28	Petrol and/or diesel fuel tank has been type tested with hydraulic pressure/strength test by fuel tank manufacturer.	7.2.1	[Yes / NA ?]	
29	Individual fuel tank has been leakage tested by fuel tank manufacturer.	7.2.2	[Yes ?]	

Comments:

compliant: Yes or V

not applicable: NA

follow up on variation report: Rpt or X