



CHECKLIST

SMALL CRAFT - WASTE SYSTEMS - PART 2: SEWAGE TREATMENT SYSTEMS

Ref.: EN ISO 8099-2:2021 (ISO 8099-2:2020)

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



Subject to check	Clause	Requirements	Checked ?
1 Toilets are connected solely to a sewage holding tank system or a waste treatment system.	4.1	[Yes ?]	
2 The sewage treatment system prevents the emission of vapour and liquids within the craft.	4.2	[Yes ?]	
3 The sewage treatment unit include a visible or audible alarm from within the habitable space notify.	4.8	[Yes ?]	
4 A readily accessible means to disable discharge is capable of being secured in the closed position to avoid accidental discharge.	4.9	[Yes ?]	
5 Each part to be serviced routinely accessible in the as installed position of the unit.	4.10	[Yes ?]	
6 Hoses and piping are securely fastened in position.	6.1	[Yes ?]	
7 All hoses, pipes and fittings are safely accessible for visible inspection.	6.1	[Yes ?]	
8 Piping and hose between toilet and sewage treatment are as short as practicable.	6.1	[Yes ?]	
9 The inner surface of pipe/hoses between toilet and sewage treatment unit is: -smooth and without convolutions to permit free flow of sewage; -have an inside diameter of 38 mm or in accordance with manufacturers recommendations.	6.1	[Yes ?]	
10 Vent system equipped with a means to minimise odour.	7	[Yes ?]	
11 Vent system is self-draining.	7	[Yes ?]	
12 Vent system terminate on the exterior of the craft and outside of weather enclosures.	7	[Yes ?]	
13 Vent system prevent water ingress.	7	[Yes ?]	
14 Sewage units marked clearly visible with the following, if applicable; Label: -name/trademark of manufacturer; -name, model, serial number; -date of manufacture; -ISO 8099-2; -power supply, characteristics; -system treatment capacity [Litres]; -system flow rate [l/min]; -maximum allowable unit pressure; -maximum allowable head of water; -maximum accumulated biological charge in 24h; -maximum accumulated hydraulic charge in 24h; Affixed: Clearly visible after the sewage treatment system has been fitted. Note: a supplementary label may be used.	10	[Yes ?]	

Watercraft manufacturer:	
Watercraft model name:	



The following questions shall be filled in by the watercraft manufacturer and appropriate documentation shall be submitted to the inspector for verification.

Subject to check	Clause	Requirements	Checked ?
15 The sewage treatment system is capable of operation throughout an temperature range of +1°C and +50°C.	4.3	[Yes ?]	
16 The system withstand an temperature of -40°C to +60°C for storage.	4.3	[Yes ?]	
17 The system is capable of operation when the craft is heeled at angles up to 20° for monohull sailing craft and 7° for other craft.	4.4	[Yes ?]	
18 Back siphoning is prevented from raw water intakes and discharge outlets up to a heel angle to either side of at least 30° for monohull sailing craft, 20° for other craft and a trimmed condition at the bow or stern of at least 10°.	4.5	[Yes ?]	
19 Back siphoning of the contents and escape of gas from the treatment system back through the toilet fixture shall be prevented when the boat is heeled at all angles up to 30° for monohull sailing craft, 20° for other craft and a trimmed condition at the bow or stern of at least 10°.	4.5	[Yes ?]	
20 Back siphoning from the escape of sewage from the treatment system to the exterior of the craft shall be prevented when the boat is heeled at all angles up to 30° for monohull sailing craft, 20° for other craft and a trimmed condition at the bow or stern of at least 10°.	4.5	[Yes ?]	
21 The sewage treatment system withstand a pressure of 20 kPa for 5 min without leakage.	4.7	[Yes ?]	
22 Sewage treatment unit is tested by a recognized laboratory against the discharged limits.	4.11	[Yes ?]	
23 The materials used are in accordance with the standard.	5	[Yes ?]	
24 Vent system is installed as per sewage treatment unit manufacturers requirements.	7	[Yes ?]	
25 The sewage treatment unit installation, operation and maintenance manual is in accordance with the standard.	11	[Yes ?]	

Instructions/Warnings to be included in the owner's manual

26 Location of the overcurrent protection device for the power supply.	12	[Yes ?]	
27 Location of by-pass valves in the plumbing system.	12	[Yes ?]	
28 Location of all thru-hull fittings.	12	[Yes ?]	
29 Warning labels, if applicable.	12	[Yes / NA ?]	
30 Location of the sewage treatment units control panel.	12	[Yes ?]	
31 Installation, operation and maintenance manual		[Yes ?]	

Comments:
