

CHECKLIST
SMALL CRAFT - REMOTE MECHANICAL STEERING SYSTEMS
Ref.: EN ISO 8848:2022

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



	Subject to check	Clause	Requirements	Checked ?
1	Is a standard duty steering system installed?	1	[Yes / NA ?]	
2	Is a light duty steering system installed?	1	[Yes / NA ?]	
3	Is a mini-jet steering system installed?	1	[Yes / NA ?]	
4	Craft suitable and designated for twin outboard engines.	4.3	[Yes / NA ?]	
5	Threaded fastener with locking means.	4.5	[Yes ?]	
6	No loose lock-washers, distorting threads or seperately applied adhesive.	4.6.1	[Yes ?]	
7	Jam nuts are prohibited except if no failure occurs if loose.	4.6.2	[Yes ?]	
8	Locking devices visible or can be felt.	4.6.3	[Yes ?]	
9	No connections relying on spring.	4.7	[Yes ?]	
10	All applicable dimensional requirements for the outboard engine steering system are met.	5.2	[Yes / NA ?]	
11	The steering system is capable of unobstructed movement throughout ist full range of intended cable travel without interference.	6.2.4	[Yes ?]	
12	Ball joints used to connect the steering system to the rudder, sterndrive, outboard and water jet drives are installed so that total loss of steering does not occur if the ball separates axially from its socket.	6.2.5	[Yes / NA ?]	
13	The ball joints used in mini-jet craft installations have redundancy such that axial failure of the ball-to-socket connection does not result in total loss of steering.	6.2.5	[Yes / NA ?]	
14	Label: Steering cables permanently marked with steering system length from steering wheel shaft centre to the hole centre in the steering output ram at the mid-travel position Affixed: At the output end.	6.3.1	[Yes ?]	
15	The cable or steering output device for standard duty and light duty steering systems amout 100 mm to 115 mm on each side of mid-travel.	6.3.2	[Yes / NA ?]	
16	The cable or steering output device for mini-jet steering systems amout 98 mm to 95,4 mm on each side of mid-travel.	6.3.2	[Yes / NA ?]	
17	Label: Steering cable for light duty steering systems permanently marked that the maximum power permissible is 40 kW. Affixed: At the steering cable.	6.3.3	[Yes / NA ?]	
18	Label: Steering mechanisms that use a steering wheel are permanently marked with manufacturer's recommendation of the largest steering wheel diameter and deepest steering wheel dish that may be used. Affixed: On the helm assembly, visible when steering wheel is removed.	6.4.2	[Yes / NA ?]	

compliant: Yes or V

not applicable: NA

follow up on variation report: Rpt or X

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



19	Label: Steering mechanisms that are intended for a handlebar are permanently marked with largest handlebar width and greatest effective offset that may be used. Affixed: At the steering mechanism.	6.4.3	[Yes / NA ?]	
20	Label: Steering mechanisms that are intended for a joystick are permanently marked with the largest stick allowed. Affixed: At the steering mechanism.	6.4.4	[Yes / NA ?]	
21	Steering mechanisms for mini-jet craft incorporate travel stops to eliminate overloading of the steering cable.	6.4.6	[Yes / NA ?]	
22	Label: Helm assemblies for light duty steering systems are permanently marked stating that the maximum power permissible is 40 kW. Affixed: At the helm assemblies.	6.4.7	[Yes / NA ?]	
23	Declaration of conformity for the steering system checked and submitted?	8.3	[Yes ?]	
24	Label: Steering system marked with the following: -ISO 8848; -name of manufacturer; -model type; Affixed: At the steering system.	9.1	[Yes ?]	
25	Installation manual provided.	9.3	[Yes ?]	

The following questions shall be filled in by the watercraft manufacturer and appropriate documentation shall be submitted to the inspector for verification.

	Subject to check	Clause	Requirements	Checked ?
26	Components are resistant to corrosion and galvanically compatible with adjoining components	4.4	[Yes ?]	
27	Steering stops of outboard engine(s) permit at least 30° of angular movement to either side of the centerline.	5.1	[Yes / NA ?]	
28	Outboard engines ensure a static load of 3300 N for a standard duty steering system.	5.6	[Yes / NA ?]	
29	Outboard engines ensure a static load of 2200 N for a light duty steering system.	5.6	[Yes / NA ?]	
30	Sterndrives designed for remote mechanical steering systems ensure a torque of 680 Nm.	5.8	[Yes / NA ?]	
31	Plastics and elastomers which can be exposed to sunlight shall be chosen to resist degradation by ultraviolet radiation.	6.2.7	[Yes / NA ?]	
32	Plastics and elastomers which can be installed in engine compartments shall be chosen to resist degradation by saline atmospheres, fuel, oil, ozone and heat.	6.2.8	[Yes / NA ?]	
33	The output of a mini-jet craft steering system follow the requirements of figure 5.	6.3.4	[Yes / NA ?]	
34	Light duty and standard duty steering cables are not interchangeable with steering cables for mini-jet craft steering systems.	6.3.5	[Yes / NA ?]	
35	Ferrous metals used for the core of a steering cable, installed below the maximum load waterline, are corrosion-resistant and equivalent to 300 series stainless steel.	6.3.6	[Yes / NA ?]	
36	For engine-mounted steering system in outboard engine-craft, the output ram or equivalent connection point reach at least 270 mm beyond the engine centerline.	7.2	[Yes / NA ?]	

compliant: Yes or V

not applicable: NA

follow up on variation report: Rpt or X

Checklist_Evaluation_Module B_G en260703

Watercraft manufacturer:	
Watercraft model name:	



37	For craft-mounted steering systems in outboard engine-craft, the output ram or equivalent connection pint reaches at least to the engine centerline.	7.3	[Yes / NA ?]	
38	Steering system installed to avoid damaging with any part of the craft steering system.	7.4	[Yes ?]	
39	Minimum steering manufacturer's recommendation for the cable radius is take into account.	7.5	[Yes ?]	
40	Steering wheel hubs and helm shafts fit each other.	7.6	[Yes ?]	
41	At least 65 mm of clearance between the shift and throttle control levers and control element under all possible positions.	7.7	[Yes ?]	
42	If cable passes through the side of an outboard engine well below the downflooding height, the cable opening meet the right degree of watertightness according to ISO 12217.	7.8	[Yes / NA ?]	
43	Steering system meet the as-installed tests, test report attached to this document.	8.2	[Yes ?]	
Instructions/Warnings to be included in the owner's manual				
44	Type of steering system(s) used with installation instruction.	5.4	[Yes ?]	
45	General description of the principle of operation and identification of major components.	9.2	[Yes ?]	
46	Exploded or sectioned diagram showing parts with identification numbers and description.	9.2	[Yes ?]	
47	Maintenance procedures and permissible adjustments.	9.2	[Yes ?]	
48	Specific precautions critical for correct operation.	9.2	[Yes ?]	
49	Reference of the model type.	9.2	[Yes ?]	

Comments:
