

Type	Interval (s)	CAN Device Identifier (11-bit)		Data (8-byte)	
		Device Identifier (6-bit)	Message Identifier (5-bit)	Lower Datum (4-byte)	Higher Datum (4-byte)
Cell voltages	1	48	0	Cell 0.0 voltage (float)	Cell 0.1 voltage (float)
			1	Cell 0.2 voltage (float)	Cell 0.3 voltage (float)
			2	Cell 0.4 voltage (float)	Cell 0.5 voltage (float)
			3	Cell 1.0 voltage (float)	Cell 1.1 voltage (float)
			4	Cell 1.2 voltage (float)	Cell 1.3 voltage (float)
			5	Cell 1.4 voltage (float)	Cell 1.5 voltage (float)
			6	Cell 2.0 voltage (float)	Cell 2.1 voltage (float)
			7	Cell 2.2 voltage (float)	Cell 2.3 voltage (float)
			8	Cell 2.4 voltage (float)	Cell 2.5 voltage (float)
			9	Cell 3.0 voltage (float)	Cell 3.1 voltage (float)
			10	Cell 3.2 voltage (float)	Cell 3.3 voltage (float)
			11	Cell 3.4 voltage (float)	Cell 3.5 voltage (float)
			12	Cell 4.0 voltage (float)	Cell 4.1 voltage (float)
			13	Cell 4.2 voltage (float)	Cell 4.3 voltage (float)
			14	Cell 4.4 voltage (float)	Cell 4.5 voltage (float)
			15	Cell 5.0 voltage (float)	Cell 5.1 voltage (float)
			16	Cell 5.2 voltage (float)	Cell 5.3 voltage (float)
Thermistor temperatures	1	48	17	Cell 5.4 voltage (float)	Cell 5.5 voltage (float)
			18	Thermistor 0.0 temperature (float)	Thermistor 0.1 temperature (float)
			19	Thermistor 0.2 temperature (float)	Thermistor 1.0 temperature (float)
			20	Thermistor 1.1 temperature (float)	Thermistor 1.2 temperature (float)
			21	Thermistor 2.0 temperature (float)	Thermistor 2.1 temperature (float)
			22	Thermistor 2.2 temperature (float)	Thermistor 3.0 temperature (float)
			23	Thermistor 3.1 temperature (float)	Thermistor 3.2 temperature (float)
			24	Thermistor 4.0 temperature (float)	Thermistor 4.1 temperature (float)
			25	Thermistor 4.2 temperature (float)	Thermistor 5.0 temperature (float)
			26	Thermistor 5.1 temperature (float)	Thermistor 5.2 temperature (float)
High Voltage Bus voltage and current	0.1	48	27	HV Bus voltage (float)	HV Current (float)
Statuses			28	[0: relay status][1: electric safe discharge status][2: discharge status][3-31: reserved]	Supplementary battery voltage (float)
Overvoltage/temperature/current flags			29	[0-35: Cell 0.0, 0.1, ..., 5.5 overvoltage flags][36-53: Thermistor 0.0, 0.1, ..., 5.2 overtemperature flags][54: overcurrent flag][55-63: reserved]	
Undervoltage/temperature flags			30	[0-35: Cell 0.0, 0.1, ..., 5.5 undervoltage flags][36-53: Thermistor 0.0, 0.1, ..., 5.2 undertemperature flags][54: undercurrent flag][55-63: reserved]	
Low Voltage Bus voltage and current	1	48	31	LV Bus voltage (float)	LV Current (float)