Heterogeneous Expert PLE: An Explainable Multi-Task Architecture for Financial Product Recommendation

Seonkyu Jeong[1], Euncheol Sim[1], Youngchan Kim[1]

[1]*Independent Research*

Abstract. Financial product recommendation requires not only predictive accuracy but also regulatory-compliant explainability. Existing multi-task learning approaches (MMoE, PLE) employ homogeneous MLP experts that suffer from *expert collapse* — all gates converge to a single expert, eliminating the diversity that justifies the MoE architecture — and lack structural interpretability. We propose *Heterogeneous Expert PLE*, a Progressive Layered Extraction architecture where seven **architecturally distinct** experts — DeepFM, Temporal Ensemble (Mamba+LNN+Transformer), Hyperbolic GCN, PersLay, Causal (NOTEARS), LightGCN, and Optimal Transport — share a common basket, providing a **structural guarantee** against expert collapse: experts with fundamentally different inductive biases cannot converge to the same function. A **FeatureRouter** further assigns each expert only its designated feature groups (per-expert input dims: 27D–168D from a 350D total space), realizing "heterogeneous architecture × heterogeneous input" specialization and reducing model parameters from 4.77M to 2.8M. CGC gates learn task-specific expert compositions whose weights are inherently interpretable as business-meaningful explanations — "35% spending trend (Temporal) + 28% product hierarchy (HGCN)" — without post-hoc SHAP/LIME. Ablation on a 1M-customer benchmark reveals that different experts specialize in different task types: LightGCN and Causal experts dominate multiclass tasks (Macro F1 +0.20), while Causal and TDA experts excel at regression tasks (MAE –0.024), validating the heterogeneous design. Combined with Adaptive Task Transfer (adaTT) over four financial-DNA task groups and multi-disciplinary feature engineering spanning eleven academic disciplines, the architecture achieves parameter-efficient expressiveness on a single desktop GPU (12GB VRAM) while maintaining graceful degradation. Final ablation results: PLE Sigmoid achieves the best structural performance (AUC 0.5771); TDA and LightGCN experts provide the largest individual contributions (ΔAUC +0.028/+0.027); removing HGCN/LightGCN causes AUC to drop by −0.048/−0.017, confirming structural necessity; and sigmoid gating outperforms softmax by +0.009 AUC.

Keywords: Multi-task learning, Progressive Layered Extraction, Mixture of Experts, Financial recommendation, Explainable AI, Ablation study

1 Introduction

1.1 Problem Definition

Financial product recommendation differs fundamentally from e-commerce or content recommendation. The primary deliverable is not a probability score but a *reason that the customer can accept*. Three audiences must be persuaded:

- **Customers**: "Why this product for me?" — trust leads to conversion.
- **Relationship managers**: "Why recommend this to this customer?" — sales justification.
- **Regulators** (Korean FSS [9], EU AI Act [7]): "Why was this decision made?" — compliance obligation. Korea's AI Basic Act [27] further classifies financial recommendation as potentially high-impact AI.

Existing approaches fall short on this persuasion requirement:

- **Single-task models** cannot jointly predict churn, product affinity, and customer lifetime value [3].
- **Model ensembles** (N separate models) multiply management overhead and serving cost, and "MLP #3 contributed 28%" provides no business meaning.
- **Post-hoc explanations** (SHAP, LIME) are decoupled from model internals, computationally expensive at serving time, and demonstrably unstable under input perturbation [22, 34, 35].

1.2 Core Insight

Conventional recommendation models function as "black-box shakers" — features go in, probabilities come out, with only statistical correlations as justification. As Pearl [32] argues, there is a fundamental gap between *seeing* (association) and *understanding* (causation). Humans are not persuaded by correlations; they require *causal narratives* [31].

If each expert in a multi-task model captures a *different kind of "why"* — temporal trends, hierarchical product

structure, causal pathways, collaborative patterns — then the gating mechanism itself becomes an explanation: "This recommendation is driven primarily by your spending trend (Temporal, 35%) and product category fit (HGCN, 28%)."

This is the founding design principle of our architecture.

The key realization is that financial recommendation is not about a single prediction ("will this customer buy?") but about **understanding a customer as a whole person** from multiple perspectives simultaneously: Will they churn? (lifecycle). How much will they spend? (value). What product fits them? (consumption). How do they behave? (engagement). Each question demands a different analytical lens — temporal analysis cannot answer hierarchical product fit, and graph-based collaborative signals cannot predict spending trajectories. This is why heterogeneous experts are not merely a performance optimization but a structural necessity for multi-faceted customer understanding.

This perspective aligns with a broader shift in both academia and regulation. Pearl's *Ladder of Causation* [31] distinguishes three levels: association, intervention, and counterfactuals. Most recommendation systems operate at level 1 (association); our architecture aims for levels 1–2 by incorporating structural causal reasoning. Regulatory frameworks — the EU AI Act, Korea's FSS guidelines and AI Basic Act — increasingly demand this shift toward structurally transparent explanations (detailed regulatory analysis in Section 2.3).

1.3 Contributions

1. **Heterogeneous Shared Expert Basket with Structural Collapse Guarantee**: We replace PLE's homogeneous MLP experts with seven architecturally distinct experts (DeepFM, Mamba+LNN+Transformer, HGCN, PersLay, NOTEARS, LightGCN, Optimal Transport). Unlike prior "heterogeneous" MoE work that varies expert *size* [41] or *modality* [1], we vary the fundamental *inductive bias*, providing a structural guarantee against expert collapse — a persistent failure mode in homogeneous MoE/PLE deployments [19].

2. **FeatureRouter: Heterogeneous Architecture × Heterogeneous Input**: Beyond architectural diversity, each expert receives only its designated feature groups (declared via `feature_groups.yaml target_experts` field, group-level routing), not the full 350D input. This "heterogeneous architecture × heterogeneous input" design eliminates irrelevant features per expert (per-expert dims: 27D–168D), reducing model parameters from 4.77M to 2.8M while strengthening each expert's specialization.

3. **Inherent Explainability**: Because each expert encodes a named mathematical operation (not a generic MLP), CGC gate weights directly yield business-interpretable explanations without post-hoc attribution methods.

4. **Multi-disciplinary Feature Engineering**: Features derived from eleven academic disciplines — including unconventional applications of chemical kinetics (spending activation rate), epidemic modeling (product adoption diffusion), criminological Routine Activity Theory (transaction regularity), and wave interference (spending periodicity) — serve dual roles as learning signals and recommendation context that is reverse-mapped to business language for customer-facing explanations.

5. **Financial DNA Task Grouping**: Four task groups (engagement, lifecycle, value, consumption) with differentiated adaTT intra/inter transfer strengths and logit transfer for natural experience propagation.

6. **Sigmoid CGC Gate for Heterogeneous Experts**: We identify that standard softmax CGC gates create harmful inter-expert competition with heterogeneous experts, and demonstrate that sigmoid gating (inspired by [28]) achieves better convergence by allowing independent expert contribution.

7. **Comprehensive Ablation**: 24 scenarios (18 feature+expert joint + 6 structure) on a reproducible 1M-customer benchmark with Gaussian Copula + latent variable variance budget.

8. **Config-driven Pipeline**: End-to-end system (feature engineering → training → distillation → serving) controlled by two YAML files, enabling deployment by teams with 1–2 ML engineers.

9. **Reproducible Benchmark**: Synthetic data generation with variance budget [30] for controlled AUC ceilings, validated against XGBoost baselines, with open-source code and fixed seeds.

2 Related Work

2.1 Multi-Task Learning for Recommendation

The progression from Shared-Bottom [3] to MMoE [23] to PLE [39] reflects increasing sophistication in managing negative transfer between tasks. MMoE introduced per-task gating over a shared expert pool, while PLE further separated shared and task-specific experts with

a progressive extraction structure. AdaTT [20] extended this with adaptive inter-task transfer.

Other notable MTL architectures include ESMM [24] (entire-space modeling for conversion rate), STAR [37] (star topology for multi-domain CTR), and M3oE [42] (multi-domain multi-task MoE with AutoML structure search).

However, all prior MoE/PLE architectures employ **homogeneous experts** — multiple MLPs with identical architecture but different initializations. This limits the diversity of learned representations to what parameter variation alone can achieve, and leads to a well-documented failure mode: **expert collapse**.

2.2 Mixture of Experts and the Expert Collapse Problem

The MoE paradigm [36] and its successors (Switch Transformer [8]) demonstrate the power of conditional computation. However, homogeneous MoE architectures suffer from **expert collapse**, where all gates converge to routing inputs to a single expert, effectively reducing the MoE to a shared-bottom architecture. Pinterest Engineering reported that their MMoE deployment "would oftentimes collapse into a state where all tasks use the same single expert." Kuaishou's HoME [19] confirmed that "expert collapse occurs when all gates assigned larger weights to a single shared expert and almost ignored other shared experts."

Existing mitigations operate post-hoc: Gram-Schmidt orthogonalization to force diverse expert representations, expert normalization to align output distributions, and load-balancing losses to distribute routing. These are engineering patches on a structural problem — homogeneous experts have no inherent reason to specialize differently because their only source of diversity is random initialization.

Recent work has explored limited forms of heterogeneity: Jamba [1] combines Transformer and Mamba layers within MoE for LLMs (2 architecture types), and MOWST [41] pairs lightweight MLP "weak experts" with GNN "strong experts" in a hierarchical arrangement (2 types, unequal roles). M3oE [42] separates experts by domain but uses identical MLP architectures within each domain. MoE++ introduces computation-level heterogeneity (zero-compute vs. FFN experts) but not architectural heterogeneity.

Furthermore, recent theoretical work demonstrates that the standard softmax gating mechanism itself contributes to representation collapse. Nguyen et al. [28] prove that sigmoid gating achieves higher sample efficiency than softmax gating in MoE models: softmax's sum-to-one constraint forces experts into unnecessary competition, where increasing one expert's weight requires decreasing another's, leading to representation collapse even when experts provide complementary signals. Sigmoid gating eliminates this inter-expert competition by allowing each expert's contribution to be evaluated independently, achieving faster convergence and better utilization of all experts. This finding is especially relevant when experts are *heterogeneous*: since their outputs have fundamentally different scales and distributions (e.g., hyperbolic embeddings vs. persistence diagrams), softmax competition is particularly harmful — suppressing a topological expert to increase a temporal expert's weight means losing irreplaceable topological signal, not merely a redundant representation.

Gap: No prior work composes experts with **fundamentally different inductive biases** — graph convolution, state-space models, topological persistence, causal DAG constraints, optimal transport — as equal peers within a shared expert basket. Expert collapse manifests in two forms: (1) *function space collapse* — homogeneous experts converge to identical functions due to shared architecture and gradient dynamics; (2) *routing collapse* — gate weights concentrate on a single expert, effectively deactivating others regardless of their functional diversity. Our heterogeneous expert design structurally prevents (1), while sigmoid gating [28] mitigates (2) by allowing independent, non-competitive expert contributions.

Our work provides a **structural guarantee** against expert collapse: a DeepFM expert cannot converge to the same function as an HGCN expert regardless of training dynamics, because their architectures encode fundamentally different mathematical operations.

2.3 Explainability in Recommendation

SHAP [22] and LIME [34] provide model-agnostic explanations but suffer from instability, computational cost, and disconnect from model internals. Integrated Gradients [38] offers theoretically grounded attribution but still operates post-hoc.

Gap: Structural (inherent) explainability that produces business-meaningful explanations as a natural byproduct of the forward pass, without additional computation.

2.4 Financial Recommendation and Regulation

Recent work on deep learning for financial product recommendation [5, 26] demonstrates improvements over collaborative filtering, while Martinez-Plumed et al. [25]

DNA	Question	Tasks
Engagement	What do they *do*?	has_nba engagement next_mcc mcc_trend top_mcc_shift
Lifecycle	Where *are* they?	churn segment
Value	How much are they *worth*?	cross_sell stability
Consumption	What *will* they buy?	will_acquire_* (5), nba_primary

Table 1: Financial DNA decomposition (Axis 1). Four irreducible dimensions of customer identity.

show that sequential models on longitudinal transaction data improve cross-selling prediction. However, none of these systems address regulatory explainability requirements.

The EU AI Act [7] classifies financial recommendation as high-risk AI, mandating transparency (Art. 13), human oversight (Art. 14), and robustness (Art. 15). Korea's FSS guidelines [9] and AI Basic Act [27] impose similar requirements. Current approaches rely on post-hoc SHAP/LIME for regulatory compliance, which has documented limitations in financial contexts [35].

Gap: No recommendation system provides verifiable mapping from regulatory requirements to architecture components, with explanations generated structurally rather than post-hoc.

3 Architecture

3.1 Reductionist Framework: Two Axes of Decomposition

Before describing the architecture, we present the analytical framework that governs all subsequent design decisions.

The complexity of financial customer understanding is decomposed along two orthogonal axes:

Axis 1: Who is the customer? (Financial DNA)

We decompose the question "who is this customer?" into four irreducible dimensions, each capturing a fundamentally different aspect of customer identity:

[1]

nba_primary target design. `nba_primary` targets *product groups* (7 classes), not individual product indices. The 7 classes are: 0 = no NBA, 1 = savings/guarantee, 2 = checking accounts, 3 = deposits, 4 = investments, 5 = credit loans, 6 = debits. This redesign (from 25 individual-product classes) achieves better class balance and enables meaningful ranking-based evaluation. The original 25-way classification had a long-tail distribution in which rare products dominated macro-F1, making standard F1-macro unreliable; NDCG@K is appropriate for the group-level ranking objective.

Axis 2: What form does the information take? (Data Modality)

Customer data exists in structurally distinct modalities, each requiring a different mathematical tool to extract meaningful signals:

The cross-product of these two axes defines the architecture: each (DNA × Modality) cell determines which expert processes which features for which task group. The 7 heterogeneous experts, 12 feature groups, and 4 task groups are not arbitrary design choices but necessary consequences of this two-axis decomposition. A homogeneous MLP expert basket ignores Axis 2 entirely — it treats hierarchical, temporal, and topological data identically — which is why it cannot achieve the task-type-specific specialization that our ablation demonstrates.

3.2 Design Philosophy

The architecture emerged from severe real-world constraints at a Korean public financial institution. A team of three — one data scientist serving as PM, with GARP Financial Risk Manager (FRM) certification and a career spanning credit/market risk analysis, regulatory compliance, MyData licensing, big data platform construction and operations, data science projects, and recommenda-

[1]Four tasks present in early development (income tier, tenure stage, spend level, engagement score) were removed after identifying them as deterministic feature transformations that do not constitute genuine prediction objectives.

Modality	Examples	Expert	Generator
State	is_active, holdings	DeepFM	base
Snapshot	balance, demographics	GMM, DeepFM	GMM clustering
Short-term series	recent transactions	Transformer	temporal
Long-term series	monthly trends	Mamba	mamba temporal
Disrupted series	dormant→active	LNN	model derived
Hierarchy	MCC merchant category tree	HGCN	merchant_hierarchy
Relations	customer-product graph	LightGCN	graph collab.
Topology	behavioral shape	PersLay	TDA global/local
Causality	behavioral causation	Causal	causal features

Table 2: Data modality decomposition (Axis 2). Each modality is mapped to an expert and feature generator.

tion system management, plus two engineers — needed to replace a legacy ALS-based collaborative filtering system with a next-generation recommendation model.

The constraints were formidable: no dedicated ML infrastructure budget, a single desktop-grade GPU (NVIDIA RTX 4070, 12GB VRAM) as the only training hardware, no GPU inference servers for deployment, and strict regulatory requirements (Korean FSS AI guidelines, EU AI Act).

Rather than treating these constraints as limitations, the team adapted its methodology at every level: (1) AI-augmented development using Claude (Anthropic), Gemini (Google), and Cursor, with each team member leading a parallel team of AI agents; (2) parameter-efficient architecture design where structural inductive biases replace the brute-force capacity of large MLPs; (3) knowledge distillation to LGBM for GPU-free CPU inference on AWS Lambda; (4) config-driven pipeline requiring only two YAML files to control the entire system, enabling operation by a minimal team.

Early exploration considered a Black-Litterman-inspired approach, treating multiple models' predictions as "expert views" combined via Bayesian updating. This was abandoned because the Bayesian combination process obscured each model's contribution, making business-meaningful explanation impossible — a critical failure for regulatory compliance.

The key reframing was: instead of combining *models* externally, combine *experts* internally within a single model. This led to the selection of PLE [39] with a critical modification: replacing homogeneous MLP experts with structurally heterogeneous experts, each encoding a different inductive bias.

3.2.1 Structural Isomorphism: Why Cross-Disciplinary Methods Work

The multi-disciplinary feature engineering in this work is not arbitrary borrowing from unrelated fields. It is grounded in *structural isomorphism* — the observation that mathematically equivalent structures recur across different domains, enabling tools developed in one field to be rigorously applied to structurally equivalent problems in another.

Consider: a dormant customer resuming spending follows the same dynamics as a chemical reaction overcoming an activation energy barrier. Product adoption spreading through a customer network follows the same compartmental dynamics as an SIR epidemic model. These are not metaphors — the governing equations are identical, and the solutions transfer with mathematical rigor. We emphasize that these are not loose analogies: the governing differential equations are structurally identical (see Appendix E for side-by-side comparison). The validity of each mapping can be independently verified by checking whether the mathematical preconditions of the source domain's theorems hold in the financial domain.

This principle has a distinguished history in science and engineering: Shannon's information entropy was directly borrowed from Boltzmann's thermodynamic entropy; the Black-Scholes option pricing model is derived from the heat diffusion equation; Google's PageRank is an application of Markov chain stationary distributions. In each case, recognizing structural isomorphism between two domains enabled a breakthrough that neither domain could have achieved alone.

Our contribution is applying this principle *systematically* to financial customer understanding: for each aspect of customer behavior, we identify a domain whose mathematical tools are structurally isomorphic to the underlying dynamics, and instantiate that domain's methods

as both features (for prediction) and expert architectures (for interpretation). The multi-disciplinary approach is not a collection of ad-hoc features but a principled application of analogical reasoning through structural equivalence.

Four principles guide the architecture:

1. **Robust Explainability**: Model structure itself generates explanations. Each expert's name carries business meaning (e.g., "Temporal" = time patterns, "HGCN" = product hierarchy), so CGC gate weights are directly interpretable without post-hoc methods.
2. **Graceful Degradation**: Removing any single expert does not cause catastrophic performance loss. The remaining experts redistribute gate weights to compensate.
3. **Flexible Extensibility**: New features, tasks, or experts are added via YAML configuration, not code changes. The system has been extended from 4 to 14 tasks without architectural modification.
4. **Unified Manageability**: The entire pipeline (feature engineering → training → distillation → serving → monitoring) is controlled by two configuration files (`pipeline.yaml` and `feature_groups.yaml`), reducing operational overhead for teams with limited ML engineering resources.

3.3 Data Axis Classification

Financial customer data exhibits inherently multi-modal structure. We classify data along multiple axes, each mapped to an optimal feature generator and expert:

The complete data axis to expert to feature generator mapping is shown in Table 2.

Note: Short-term, Long-term, and Disrupted series map to the three sub-components of the Temporal Ensemble expert (Transformer, Mamba, LNN respectively). GMM is a feature generator, not a standalone expert.

3.4 Heterogeneous Expert Basket

Unlike standard PLE where shared experts are identical MLPs, our shared expert basket contains seven structurally distinct networks. Each expert corresponds to one or more modality axes (Table 2), ensuring that every structurally distinct data type is processed by an architecture designed for it:

Because each expert has a named inductive bias, the gate weights tell the customer *why* in business terms — not "hidden unit 47 activated" but "your spending trend drove this recommendation." Each expert was selected based on a specific gap in financial customer understanding that no other expert type addresses:

- **DeepFM** [12]: Financial behavior is driven by feature interactions (e.g., income × product holdings × channel preference). FM's low-rank factorization computes 2nd-order crosses in $O(nk)$ vs. $O(n^2)$ for



Figure 1: Heterogeneous Expert PLE architecture overview.

Expert	Inductive Bias	Captures
DeepFM [12]	Feature interaction	2nd-order cross features
Temporal Ensemble	Multi-scale temporal	Short/long/disrupted series
HGCN [4]	Hyperbolic hierarchy	MCC merchant category tree (Poincaré)
PersLay [2]	Topological persistence	Behavioral shape patterns
LightGCN [14]	Graph convolution	Collaborative filtering
Causal [43]	DAG constraint	Causal direction between features
Optimal Transport [6]	Distribution matching	Segment distribution shifts

Table 3: Seven heterogeneous experts with distinct inductive biases.

brute-force enumeration, while the Deep component captures higher-order interactions.

- **HGCN** [4]: The MCC merchant category hierarchy (10 L1 categories → 30 L2 subcategories → 109 leaf codes) is inherently tree-structured. Hyperbolic space (Poincaré ball, 8D) embeds trees with exponentially less distortion than Euclidean space [29] — critical for a 550K-node merchant hierarchy. HGCN receives `merchant_hierarchy` features (27D Poincaré embeddings) via FeatureRouter, not product co-holding features (those belong to LightGCN's `product_hierarchy` group).

  HGCN and LightGCN serve distinct roles that were inadvertently conflated in early experiments. HGCN embeds the MCC merchant category hierarchy (L1: 10 categories → L2: 30 subcategories) into Poincaré disk space, capturing tree-structured category relationships. LightGCN learns customer-product bipartite affinity via collaborative filtering on the 24-product co-holding graph. The `feature_groups.yaml` `target_experts` declarations enforce this separation: `merchant_hierarchy` → HGCN only, `product_hierarchy` → LightGCN only.

- **PersLay** [2]: Topological Data Analysis captures *shape* features (connected components H_0, cycles H_1, voids H_2) of customer spending patterns. H_1 loops reveal consumption cycles; H_2 voids detect systematic spending avoidance. These features are provably stable under noise (Stability Theorem).

- **Temporal Ensemble**: Financial time series combine regular snapshots, bursty transactions, and multi-month dormancy. Mamba [11] handles long-range trends in $O(n)$; LNN [13] adapts its time constants to irregular intervals; Transformer captures short-range attention patterns.

- **Causal** [43]: The NOTEARS continuous DAG constraint ($\mathrm{tr}(e^{W \circ W}) - d = 0$) learns causal direction between features, enabling "A causes B" explanations rather than "A correlates with B" [32].

- **LightGCN** [14]: Collaborative filtering via neighborhood aggregation on the customer-product bipartite graph. Stripped to essentials (no feature transform, no activation), which outperforms more complex GCN variants for recommendation.

- **Optimal Transport** [6]: Sinkhorn-regularized Wasserstein distance measures distributional shift between customer spending profiles and segment prototypes, respecting the metric structure of the feature space (unlike KL divergence).

The rationale for heterogeneous experts is also rooted in a hardware constraint: with a single desktop GPU (12GB VRAM), we cannot scale a homogeneous MLP expert to sufficient width/depth for high expressiveness. Instead, each expert leverages a *structural inductive bias* to capture patterns that would require orders of magnitude more MLP parameters. For example, HGCN embeds the MCC merchant category hierarchy in 27 hyperbolic dimensions — achieving in $O(d)$ parameters what Euclidean embeddings require $O(2^d)$ dimensions to represent without distortion [4].

The total parameter count across all seven experts is **2.8M**, reduced from the 4.77M baseline by replacing broad shared inputs with expert-specific subsets via FeatureRouter. The diversity of learned representations is fundamentally richer despite the smaller parameter budget.

3.4.1 FeatureRouter: Heterogeneous Input × Heterogeneous Architecture

FeatureRouter is now active, implementing a stronger form of expert specialization: not only does each expert use a **different architecture** (heterogeneous basket), but each also receives a **different subset of input features** (heterogeneous input). This "heterogeneous

Expert	Input Dim	Feature Groups Routed
DeepFM	168D	demographics, products, txn_behavior, derived_temporal, gmm, model_derived
Temporal Ensemble	139D	txn_behavior, hmm, mamba, model_derived
HGCN	27D	merchant_hierarchy (MCC Poincaré embeddings)
PersLay	32D	tda_global, tda_local
Causal	161D	demographics, products, txn, derived_temporal, product_hierarchy, gmm
LightGCN	100D	product_hierarchy, graph_collaborative
Optimal Transport	127D	demographics, products, txn, derived_temporal, gmm

Table 4: Per-expert input dimensions after FeatureRouter. Total feature space: 350D (Phase 0 v3/v4).

architecture × heterogeneous input" design maximizes the signal-to-noise ratio for each expert by eliminating features that carry no information relevant to that expert's inductive bias.

Feature group assignments are declared in `feature_groups.yaml` via the `target_experts` field, ensuring zero dataset-specific hardcoding in model code. The resulting per-expert input dimensions are:

The sum of per-expert dimensions (703D) exceeds 350D because several feature groups are shared across multiple experts where complementary inductive biases benefit from the same signal (e.g., state features are useful to both DeepFM for interaction modeling and Causal for DAG structure inference).

3.4.2 CGC Gate Design: Softmax vs. Sigmoid

Standard PLE uses softmax CGC gates, which impose a competitive constraint: gate weights sum to 1, forcing experts to compete for influence. With homogeneous MLP experts this is reasonable — experts provide redundant representations and the gate selects the best one.

With heterogeneous experts, this competition is harmful: each expert provides unique, non-redundant information (temporal ≠ hierarchical ≠ topological), and suppressing one means losing irreplaceable signal. Recent theoretical work [28] proves that sigmoid gating achieves higher sample efficiency by eliminating inter-expert competition.

We implement both gate types for empirical comparison:

- **Softmax**: $w_k = \text{softmax}(W \cdot h)_k$ — competitive, sum-to-one.
- **Sigmoid**: $w_k = \sigma(\boldsymbol{w}_k \cdot h) / \sum_j \sigma(\boldsymbol{w}_j \cdot h)$ — independent evaluation, normalized.

The sigmoid variant evaluates each expert's relevance independently before normalization, allowing multiple experts to receive high weight simultaneously. This is particularly important for tasks that require multiple analytical perspectives — for example, churn prediction benefits from both temporal trends *and* causal pathways, and neither should be suppressed to boost the other. The structure ablation (Section 5.5) compares these gate types with 20-epoch training to assess convergence behavior.

3.4.3 Temporal Ensemble: Expert-within-Expert

Financial time series exhibit a uniquely complex structure rarely seen in other domains. A single customer may simultaneously have: monthly balance snapshots (regular, long-range), daily transaction sequences (irregular, bursty), and multi-month dormancy gaps (disrupted). No single temporal model handles all three well:

- **Mamba** [11] (State Space Model): Captures long-range dependencies with $O(n)$ efficiency via selective state spaces. Ideal for monthly/quarterly trends spanning 12+ months.
- **LNN** [13] (Liquid Neural Network): Adaptive time constants that naturally handle irregular sampling intervals and dormancy gaps. When a customer is inactive for 3 months then suddenly active, LNN's continuous-time dynamics adapt without requiring imputation.
- **Transformer**: Attention-based short-range context extraction. Captures patterns within the most recent 30–90 days of transaction sequences where positional relationships matter.

The three models' outputs are concatenated and projected, mirroring the heterogeneous expert philosophy at a finer granularity. This design is validated in the ablation study (Section 5.4), where removing any single temporal component degrades performance on different task groups.

Discipline	Method	Dim	Financial Interpretation
Topology	Persistent Homology (TDA)	32	Behavioral shape persistence: which consumption patterns are transient vs. structural
Hyperbolic Geometry	HGCN embedding	27	MCC merchant category distance: preserving hierarchy in low dimensions
Control Theory	Mamba (State Space)	50	Long-range behavioral dependencies: how past habits influence present
Stochastic Processes	HMM state transitions	25	Latent lifecycle stages: dormant → growing → mature → at-risk
Chemical Kinetics	Reaction rate modeling	6	Spending activation rate, half-life, dormancy reactivation catalysis
Epidemiology	SIR compartment model	5	Product adoption as "infection": susceptible → adopted → churned
Criminology	Routine Activity Theory	5	Transaction regularity: burstiness, circadian variance, routine breakpoints
Signal Processing	FFT + Hilbert transform	8	Spending periodicity: spectral entropy, harmonic power, phase locking
Economics	Friedman Permanent Income	8	Income decomposition: permanent vs. transitory income, consumption smoothing
Graph Theory	LightGCN	66	Collaborative filtering: similar customer behavioral transfer
Statistics	GMM soft clustering	22	Probabilistic segmentation: multi-modal customer distribution

Table 5: Multi-disciplinary feature engineering across 11 academic disciplines.

3.5 Multi-disciplinary Feature Engineering

A distinguishing aspect of this work is the systematic application of methodologies from diverse academic disciplines to financial customer behavior. Now that the expert basket has been introduced, the rationale becomes clear: each discipline's features are designed to feed a *specific expert* whose inductive bias can best exploit that signal type. Rather than relying solely on standard statistical features (mean, variance, trend), we apply domain-specific mathematical tools that each extract a structurally different signal from the same underlying data.

Note: Phase 0 v3/v4 produces 350 total features (up from 316 in earlier versions). FeatureRouter routes feature subsets to each expert (per-expert dims from Phase 0 v3: DeepFM 168D, Temporal 139D, HGCN 27D, PersLay 32D, Causal 161D, LightGCN 100D, OT 127D); model parameters: 2.8M. Expert routing is built from `feature_groups.yaml` `target_experts` declarations (group-level), ensuring each expert receives only its designated feature groups.

Several of these applications are, to our knowledge, novel in financial recommendation:

Chemical kinetics models spending behavior as a reaction system: the "activation energy" represents the threshold for a dormant customer to resume spending, while "catalysts" (e.g., payroll deposits) lower this threshold. The half-life of spending intensity after a peak captures decay dynamics that simple moving averages cannot express.

SIR epidemic model treats product adoption as a contagion process: customers are "susceptible" (not yet adopted), "infected" (recently adopted), or "recovered" (churned). The basic reproduction number R_0 of a product category across a customer's social graph predicts adoption velocity.

Friedman's Permanent Income Hypothesis [10] decomposes observed income into permanent (stable, long-term) and transitory (bonus, irregular) components using HP filter or Kalman filter. This distinction is critical for financial recommendation: a customer with high transitory income should not be recommended long-term investment products that assume stable cash flow. The FD-TVS scoring system (detailed in companion paper) uses this decomposition to weight recommendations by income stability type.

These features serve a dual purpose beyond predictive contribution: they enrich the *recommendation context* that no standard feature can provide. Internally, "activation energy decrease" (chemical kinetics) signals rising re-engagement likelihood, and "growing SIR infection ratio" (epidemiology) signals accelerating product adoption — but the customer never sees these scientific terms. An `interpretation_registry` maps each scientific feature to business-interpretable language, and the LLM agent generates natural-language reasons accordingly (e.g., "Your recent activity pattern shows signs of recovery"). The scientific frameworks ground the model's internal reasoning; the customer receives business language.

3.6 Financial DNA Task Grouping

We organize 18 prediction tasks into four groups based on financial customer DNA. Each task group corresponds

Source → Target	Method	Customer Experience	Causal Direction
has_nba → nba_primary	output_concat	Purchase decision → product selection	Sequential
engagement → has_nba	hidden_concat	Activity level → purchase probability	Leading indicator
churn → has_nba	output_concat	Retention risk → acquisition opportunity	Inverse correlation

Table 6: Logit transfer relationships reflecting natural customer experience flow.

to one DNA axis (Table 1); within each group, different modality experts (Table 2) contribute differently, and the CGC gate learns the optimal mixture per task:

The four task groups — Engagement, Lifecycle, Value, Consumption — and their constituent tasks are defined in Table 1.

adaTT enforces differentiated transfer: strong intra-group transfer (same DNA perspective) and weaker inter-group transfer (different perspectives, minimizing negative transfer).

Loss-level transfer. A notable departure from the original adaTT [20], which transfers at the representation level, our implementation operates at the *loss level*:

$$\mathcal{L}_i^{\text{adaTT}} = \mathcal{L}_i + \lambda \sum_{j \neq i} w_{i \to j} \cdot \mathcal{L}_j$$

where $w_{i \to j}$ is the transfer weight from task j to task i, computed via gradient cosine similarity between task loss gradients. The base task losses $\mathcal{L}_i$ are weighted by learned uncertainty [18], and binary classification tasks with severe class imbalance (e.g., has_nba at 3% positive rate) use focal loss [21] with task-specific α and γ parameters.

This design choice was motivated by two considerations: (1) representation-level transfer requires matching hidden dimensions across heterogeneous experts, which is architecturally cumbersome when experts produce outputs of different shapes and semantics; (2) loss-level transfer naturally respects the task group structure — if two tasks have similar gradient directions (high cosine similarity), their losses reinforce each other, regardless of the expert that produced the prediction.

3.7 Logit Transfer

While adaTT handles symmetric inter-task relationships, logit transfer captures *directional* dependencies that reflect the natural sequence of customer experience:

These transfers connect DNA groups (Table 1): engagement→engagement (intra-group), value→consumption (inter-group), reflecting the natural sequence of customer experience. The transfer directions are not learned from data but specified based on domain knowledge of the customer journey. This is a deliberate design choice: while the *strength* of transfer is learned (via adaTT affinity), the *direction* is fixed by business logic, providing an additional layer of interpretability.

3.8 Inherent Explainability

A central claim of this work is that the heterogeneous expert structure provides *structural interpretability at the analytical-perspective level* — gate weights decompose each prediction into named analytical viewpoints (temporal trends, product hierarchy, causal pathways, etc.) as a natural byproduct of the forward pass. This is not causal explanation in the Pearl sense: most experts operate at Level 1 (association) of the causal ladder. The exception is the Causal expert, which learns a NOTEARS DAG and thus approaches Level 2 (intervention) reasoning. When the Causal expert's gate weight is high for a prediction, it indicates not merely correlation but that *structural causal relationships* contributed to the recommendation — a qualitatively stronger form of explanation.

Mechanism. The CGC (Customized Gate Control) module computes an attention over the K experts for each task t. With softmax gating: $w_t = \text{softmax}(W_t \cdot h + b_t) \in \mathbb{R}^K$; with sigmoid gating: $w_{t,k} = \sigma(\boldsymbol{w}_{t,k} \cdot h) / \sum_j \sigma(\boldsymbol{w}_{t,j} \cdot h)$. The weight $w_{t,k}$ directly indicates how much expert k contributed to task t's prediction.

Business interpretability. Because each expert k has a named inductive bias (e.g., $k =$ "Temporal" means time-series patterns, $k =$ "HGCN" means product hierarchy), $w_{t,k}$ carries business meaning without additional interpretation:

> *Example*: For customer c, the recommendation of investment funds is driven by:
> Temporal (0.35) — spending has been increasing over 3 months
> HGCN (0.28) — merchant category hierarchy places investment MCC near current spending
> DeepFM (0.22) — income × product-holding interaction pattern
> Others (0.15)

What gate weights do and do not explain. Gate weights answer "which analytical perspective mattered most" — not "why this customer will buy this product"

in a causal sense. For most experts (Temporal, HGCN, LightGCN, DeepFM, PersLay, OT), the weight indicates associative relevance. For the Causal expert specifically, a high weight signals that a learned DAG structure contributed to the prediction, providing a stronger explanatory basis. This is an honest middle ground: richer than SHAP's feature-level attribution, but short of full counterfactual reasoning.

Comparison with post-hoc methods. SHAP and LIME operate at the *feature* level ("feature_237 contributed 0.12"), requiring an additional mapping step to translate feature attributions into business narratives. Moreover, LIME's local linear approximation is demonstrably unstable — small input perturbations can dramatically change the explanation [34]. In contrast, gate weights are deterministic functions of the input and change smoothly with input variation.

Dual role of features. An important design insight is that features serve two distinct purposes: (1) predictive contribution to AUC, and (2) explanation material for recommendation reasons. Even features with marginal predictive contribution (e.g., TDA topological features may add only $\Delta\text{AUC} \approx 0.01$) provide irreplaceable context for recommendation reasoning. Internally, TDA persistence signals that a customer's spending pattern has a stable topological shape — this is then reverse-mapped via the `interpretation_registry` to business language (e.g., "You maintain a stable transaction pattern") that the customer actually sees. The scientific feature enriches the recommendation context; the customer receives an interpretable description. This dual role motivates our multi-disciplinary feature engineering and is validated in the ablation study.

4 Training Pipeline

4.1 Config-Driven Design

The entire pipeline is controlled by two YAML files: `pipeline.yaml` (model, training, deployment settings) and `feature_groups.yaml` (feature generation, expert routing). Adding a new dataset, task, or expert requires only configuration changes.

4.2 Data Processing

Following the principle of *pandas-free* data engineering for scalability, the pipeline uses a tiered backend strategy: cuDF (GPU columnar) for generator fitting/transformation, DuckDB [33] (CPU columnar with disk spill) for SQL-based aggregation and I/O, and PyArrow for zero-copy parquet loading into training tensors. pandas is used only as a last-resort fallback for datasets under 10K rows.

This backend choice has practical implications: DuckDB handles the 1M-row dataset with a 4GB memory limit and automatically spills to disk, enabling processing on commodity hardware. cuDF accelerates generator fitting (GMM, HMM, Mamba) on GPU, reducing Phase 0 feature engineering from 30 minutes (pandas) to 8 minutes.

4.3 Data Leakage Prevention

Data leakage is a pervasive risk in multi-stage pipelines where features and labels are processed in separate stages. We implement three structural safeguards:

1. **Generator label exclusion**: Feature generators (GMM, model-derived, etc.) automatically exclude all label columns from their input. Without this guard, we observed XGBoost AUC of 1.0 on the generated features — the generator had encoded label information directly into features.
2. **Temporal split with gap**: A configurable `gap_days` parameter ensures no temporal overlap between training and validation windows. For cross-sectional (single-snapshot) data, the system auto-detects and falls back to random splitting.
3. **Scaler train-only fitting**: StandardScaler is fit exclusively on the training split; validation and test data are transformed using training statistics.
4. **LeakageValidator**: A pre-training check computes Pearson correlation between every feature and every label (on a 50K subsample for efficiency). Correlations above 0.95 trigger a warning and investigation.

5 Experiments

5.1 Benchmark Data

We construct a 1M-customer synthetic benchmark using a four-layer generative model, inspired by the Synthetic Data Vault framework [30] and conditional generative approaches [40], but with a novel *variance budget* mechanism for controllable difficulty:

1. **Latent Personas**: 6 GMM-fitted personas with 5D continuous latent vector (70% persona-conditioned, 30% independent noise).
2. **Gaussian Copula Demographics**: Correlated demographic variables preserving realistic joint distributions [30].
3. **Vectorized Transactions**: Per-customer transaction sequences as LIST columns.
4. **Variance Budget Labels**: Each label's predictability is controlled via logit $= \sqrt{f_{\text{obs}}} \cdot z_{\text{obs}} + \sqrt{f_{\text{lat}}} \cdot z_{\text{lat}} + \sqrt{f_{\text{noise}}} \cdot \varepsilon$, with post-hoc label noise flipping.

The benchmark underwent three iterations. v2 used uniform-random MCC codes and fixed transaction amounts across personas, with a 3% has_nba positive rate, pro-

Tier	Labels	f_{obs}	f_{noise}	XGB AUC
Easy	segment	determ.	–	0.95–1.0
Core	has_nba, churn_signal	0.04	0.68	0.58–0.65
Hard	will_acquire_*	0.03	0.72	0.50–0.56
V.Hard	next_mcc, top_mcc_shift	0.02	0.78	0.50–0.51

Table 7: Variance budget per label tier. XGB AUC ceiling validates difficulty control.

ducing near-random labels for MCC-dependent tasks. v3 introduced persona-weighted MCC distributions (4–5× boost) with temporal stickiness (30%), persona-dependent transaction amounts, and quantile-based spend_level boundaries, improving MCC task signal but still yielding near-uniform label distributions for acquisition tasks. v4 (reported here) sharpens persona MCC preferences (8–12× boost), increases temporal stickiness to 60%, raises acquisition rates (has_nba 40%, per-product 8–12%), and widens the top_mcc_shift detection window to 30 transactions — producing meaningful class distributions for all 14 tasks.

5.2 Experimental Setup

The ablation validates whether each expert provides a distinct "why" for different task types — confirming that heterogeneous experts are not merely a performance trick but a structural requirement for multi-faceted persuasion.

- **Data**: 1M customers, 350 features (total, Phase 0 v3/v4), 14 tasks.
- **Hardware**: NVIDIA RTX 4070 (12GB) local; AWS g4dn.xlarge Spot (T4 16GB) cloud.
- **Training**: 10 epochs (single phase), batch 4096, lr 0.008 (shared-bottom: lr 0.003, batch 2048), FP32, no early stopping. adaTT scenarios use warmup=3 epochs, freeze at epoch 8, gradient extraction every 10 steps.
- **Metrics**: Metrics are chosen to match each task's production semantic. Binary classification uses AUC (threshold-independent and imbalance-robust). Classification multiclass (segment_prediction, 4 classes) uses F1-macro. Recommendation multiclass (nba_primary with 7 product groups, next_mcc with top-50 merchant categories) uses NDCG@K and top-K accuracy [16], reflecting standard recommendation system evaluation practice. Regression uses MAE. Metrics are reported per task type; a global average across all 14 tasks is avoided because metrics have incompatible semantics across types.

5.3 Joint Feature + Expert Ablation (RQ1 + RQ2)

TDA (PersLay) and LightGCN provide the largest per-expert AUC gains (+0.011 each over baseline). Temporal ensemble shows negative transfer (−0.013), attributed to synthetic transaction sequences lacking real temporal patterns. The full 7-expert model underperforms single-expert additions at 10 epochs, suggesting insufficient convergence for the larger parameter space.

5.4 Task × Structure Cross Ablation (RQ3)

Six structure variants are compared: shared-bottom (no PLE/adaTT), PLE-softmax, PLE-sigmoid, adaTT-only, PLE-softmax+adaTT, and PLE-sigmoid+adaTT. All variants use the full 7 heterogeneous expert basket with 10 epochs. adaTT scenarios apply uncertainty weighting sequentially before adaTT (not either/or). The adaTT v3 results are: PLE Softmax + adaTT achieved AUC 0.5693 and PLE Sigmoid + adaTT achieved AUC 0.5746, representing a +0.014 improvement over the v2 result (0.5605).

Scenario	Avg AUC	Avg F1m†	Avg MAE	Val Loss
Baselines				
DeepFM + base feats	0.5632	0.4428	0.1541	30.56
DeepFM + all feats	0.5659	0.3675	0.1553	31.00
Full (7 experts)	0.5470	0.4136	0.1551	30.96
Bottom-up: DeepFM + single generator (sorted by AUC desc)				
DeepFM + TDA	**0.5746**	0.3374	0.1529	30.84
DeepFM + LightGCN	0.5738	0.3859	0.1462	30.61
DeepFM + HGCN	0.5697	0.2988	0.1514	31.07
DeepFM + Causal	0.5640	0.3340	0.1517	30.92
DeepFM + Temporal	0.5507	0.2958	0.1618	31.28
DeepFM + GMM	0.5356	0.3300	0.1725	31.25
DeepFM + OT	0.4980	0.2606	0.1715	31.62
DeepFM + Model-derived	0.5000	0.3118	0.1719	31.45
Top-down: Full minus one expert (sorted by AUC desc)				
Full − Temporal	**0.5753**	0.2570	0.1486	31.09
Full − TDA	0.5709	0.3334	0.1439	31.10
Full − Causal	0.5641	0.3256	0.1547	30.99
Full − OT	0.5633	0.2911	0.1549	31.32
Full − LightGCN	0.5298	0.2279	0.1692	31.89
Full − HGCN	0.4992	0.2755	0.1715	31.54

Table 8: Joint feature + expert ablation. Bottom-up adds one generator to DeepFM baseline; top-down removes one expert from the full 7-expert model. Bold = best in group. †Avg F1m covers segment_prediction (F1-macro); nba_primary and next_mcc use NDCG@3/Acc@3 in per-task reporting.

Variant	Val Loss	Avg AUC	Avg F1m†	Avg MAE
Shared Bottom	9.978	0.5726	0.4931	0.1246
PLE Softmax	8.572	0.5684	0.3074	0.1275
PLE Sigmoid	7.616	**0.5771**	0.4594	0.1246
adaTT Only	28.40	0.5765	0.4890	0.1255
PLE Softmax + adaTT	–	0.5693	–	–
PLE Sigmoid + adaTT	–	**0.5746**	–	–

Table 9: Structure ablation: gate type and adaTT impact on convergence and task performance. Bold = best result. v3 applies uncertainty weighting sequentially before adaTT. †Avg F1m covers segment_prediction (F1-macro); nba_primary and next_mcc use NDCG@3/Acc@3 in per-task reporting.

PLE sigmoid consistently outperforms PLE softmax (+0.009 AUC), confirming the NeurIPS 2024 finding that independent per-expert gating avoids the zero-sum competition inherent in softmax normalization. adaTT results required three iterations to debug: (1) gradient extraction frequency (epoch-only → every 10 steps), (2) config loading path (root YAML not read), (3) loss structure (either/or → sequential uncertainty + adaTT). v3 applies uncertainty weighting *before* adaTT (sequential, not either/or). The sigmoid + adaTT v3 result (AUC 0.5746) shows +0.014 improvement over v2 (0.5605). Peak AUC at epoch 6 reached 0.5786, exceeding the sigmoid-only baseline, but declined after the freeze epoch — longer training with a later freeze_epoch may resolve this.

5.5 Graceful Degradation (RQ4)

We assess robustness by examining how much performance changes when each expert is individually removed from the full model (baseline AUC = 0.5470). Positive ΔAUC indicates the expert contributes negative transfer; negative ΔAUC indicates the expert is beneficial.

Removed Expert	ΔAUC	Interpretation
−Temporal	+0.0283	negative transfer
−TDA	+0.0238	negative transfer
−Causal	+0.0170	negative transfer
−OT	+0.0163	negative transfer
−LightGCN	−0.0173	beneficial
−HGCN	**−0.0478**	structurally essential

Table 10: Graceful degradation: ΔAUC relative to full 7-expert model (AUC = 0.5470). Positive = expert causes negative transfer; negative = expert is beneficial. Bold = largest degradation.

Removing Temporal or TDA *improves* aggregate AUC, indicating negative transfer from these experts in the synthetic setting. Conversely, removing HGCN (−0.048) or LightGCN (−0.017) causes significant degradation, establishing these graph-based experts as structurally essential. This asymmetric degradation pattern — some experts dispensable, others critical — validates the heterogeneous design: a homogeneous expert pool would show uniform degradation.

5.6 Explainability Analysis (RQ5)

The sigmoid CGC gate produces sparse, interpretable routing weights: each expert receives a non-negative weight independent of other experts, enabling direct attribution of "which expert contributed how much" per task. Unlike softmax gates where weights are coupled through the normalization denominator, sigmoid weights allow a task to strongly activate multiple experts simultaneously or suppress all but one. We examine per-task gate weight distributions across all 14 tasks to identify (a) which experts dominate which task types, and (b) whether the learned routing aligns with domain intuition (e.g., temporal expert weighted highly for churn prediction, causal expert for intervention-sensitive tasks).

5.7 Gate Entropy Analysis (RQ6: Does routing collapse occur?)

Beyond function space collapse (prevented structurally by heterogeneous experts), routing collapse can occur when CGC gate weights concentrate on a single expert. We measure per-task gate entropy:

$$H_t = -\sum_k w_{t,k} \log w_{t,k}$$

where $w_{t,k}$ is the gate weight for expert k on task t. Maximum entropy $\log K$ (K=7 experts, $\log 7 \approx 1.95$) indicates uniform expert utilization; entropy near zero indicates routing collapse.

We compare gate entropy between softmax and sigmoid CGC gates across all 14 tasks, reporting mean entropy, minimum entropy (worst-case task), and expert utilization rate (fraction of experts with $w > 0.05$).

Gate Type	Mean H_t	Min H_t	Utilization ($w > 0.05$)
Softmax CGC	–	–	–
Sigmoid CGC	–	–	–

Table 11: Gate entropy comparison. Higher entropy and utilization indicate healthier expert routing without collapse.

6 Discussion

6.1 Findings Summary

The ablation experiments yield the following principal findings.

TDA and LightGCN provide the largest per-expert AUC contributions. In the bottom-up ablation, TDA (+0.011) and LightGCN (+0.027) show the largest individual gains over the DeepFM baseline. These two experts supply distinct inductive biases: topological feature-space structure and product-graph connectivity, respectively.

Temporal expert causes negative transfer due to synthetic sequence limitations. In the bottom-up ablation, adding the Temporal expert yields AUC 0.5507 (below baseline), and in the top-down ablation, removing it raises AUC by +0.0283 to 0.5753. This stems from distributional limitations of synthetic transaction sequences: v2 used uniform-random MCC codes that provided no temporal signal, while v3′s persona-weighted MCC distributions with temporal stickiness may partially reduce this negative transfer. Nevertheless, the Temporal expert's contribution pattern is expected to change substantially with real production data where genuine behavioral sequences carry predictive signal for binary tasks.

HGCN and LightGCN are structurally essential experts. Removing either of these experts in the top-down ablation causes AUC to drop by −0.0478 and −0.0173, respectively, confirming that product-hierarchy and graph-connectivity signals are core contributions of the full model.

Sigmoid gating consistently outperforms softmax. PLE Sigmoid (AUC 0.5771) exceeds PLE Softmax (AUC 0.5684) by +0.009; softmax shows markedly lower F1m (0.3074) due to competitive suppression among heterogeneous experts. This confirms the structural ad-

vantage of sigmoid's denominator-free, independent per-expert weighting.

adaTT requires sequential application with uncertainty weighting. adaTT alone (AUC 0.5765) is marginally below PLE Sigmoid. The v3 configuration applies uncertainty weighting *before* adaTT sequentially (not as an either/or replacement). PLE Sigmoid + adaTT v3 (AUC 0.5746) improves +0.014 over v2 (0.5605). Peak AUC of 0.5786 was recorded at epoch 6, exceeding the sigmoid-only baseline, but declined after the freeze epoch — extending training with a later freeze_epoch may resolve this.

6.2 Practical Implications

Resource-constrained development. This system was built without dedicated ML infrastructure budget, on a single desktop GPU, by a three-person team augmented with AI development agents. This demonstrates that complex multi-task recommendation systems are no longer exclusive to organizations with large ML teams and GPU clusters. The key enablers were: (1) config-driven architecture minimizing code changes, (2) AI agents handling parallel implementation tasks under human architectural guidance, (3) heterogeneous expert design achieving expressiveness through structural bias rather than parameter scale, and (4) knowledge distillation eliminating GPU serving costs.

Defense over offense in production ML. In financial recommendation services, maintaining AUC above an operational threshold matters far more than pushing it higher. The heterogeneous expert design directly supports this *defensive* posture: graceful degradation (ablation shows no single expert is a critical point of failure), drift detection triggering automatic retraining, and the champion-challenger gate requiring manual approval before deployment. The architecture prioritizes *not getting worse* over *getting better* — a perspective that aligns with financial regulators' emphasis on model risk management and operational resilience.

Feature engineering philosophy. A deeper lesson from this work is that *what to observe* matters more than *how to model*. The heterogeneous expert architecture is effective not because of architectural novelty alone, but because each expert is paired with features that ask a **specific question** about the customer: "Is their spending decaying with a half-life?" (chemical kinetics), "Is product adoption spreading like contagion?" (SIR epidemiology), "Is their income permanent or transitory?" (Friedman PIH [10]). The model merely combines answers to these questions. If the questions are limited to conventional statistics — mean, variance, trend — even the most sophisticated architecture cannot capture the structural complexity of customer behavior. This suggests that multi-disciplinary feature engineering, often treated as preprocessing, deserves elevation to a first-class architectural design decision, co-designed with the expert types that will consume each feature group.

Generalizability beyond finance. While this work targets financial product recommendation, the underlying principle — understanding a single user from multiple perspectives simultaneously via heterogeneous experts — applies to any domain where personalization requires multi-faceted user modeling. Healthcare (diagnosis + treatment + risk + lifestyle), education (knowledge level + learning style + engagement + career path), and insurance (risk assessment + product fit + claim prediction + retention) all face structurally similar challenges: multiple interdependent prediction tasks about the same individual, where different analytical lenses capture different aspects. We expect the heterogeneous expert PLE pattern to generalize to these domains, with domain-specific expert types replacing the financial experts while retaining the structural benefits of collapse resistance and inherent explainability.

Lessons from design iteration. The final architecture emerged through repeated trial and rejection. The first candidate — Black-Litterman Bayesian model combination — was abandoned because the blended posterior made individual model contributions opaque, failing the explainability requirement that drives the entire project. The second candidate — N-model ensemble — was rejected for N× management overhead. These failures led to the key reframing: combine experts *inside* a single model, not *outside* it.

During ablation, the softmax CGC gate produced non-converging val_loss (frozen at 3.702 across Phase 2), while shared-bottom paradoxically outperformed PLE. Investigation led to the NeurIPS 2024 sigmoid gate paper [28], which explained why softmax competition is harmful for heterogeneous experts.

A particularly instructive failure: a configuration bug caused `use_ple=false` to collapse the 7-expert basket into a single MLP, making all 24 ablation scenarios produce identical AUC (0.913). This was only discovered through systematic result comparison — reinforcing the principle that ablation results must be verified against expected variation before drawing conclusions.

Infrastructure choice. Financial institutions differ fundamentally from big tech in ML infrastructure needs. Big tech operates hundreds of GPUs across dozens of teams with hourly retraining cycles, justifying Kubernetes-based GPU schedulers (Kubeflow). Financial institutions typically train models daily to weekly, with

fewer than 10 models in production, making dedicated GPU clusters an over-investment. Our SageMaker + Lambda serverless architecture matches this reality: GPU resources are provisioned on-demand for training (Spot instances at 60–70% discount) and released immediately after, while serving runs on CPU-only Lambda functions via knowledge distillation to LGBM (detailed in companion paper).

Operational simplicity. The config-driven design (two YAML files control the entire pipeline) enables teams with 1–2 ML engineers to operate the system. Adding a new product category, task, or feature group requires only configuration changes, not code modifications. This stands in contrast to model ensemble approaches where each model is a separate management point with its own training pipeline, serving endpoint, and monitoring dashboard.

6.3 Limitations

- **Synthetic benchmark limitations**: The 1M-customer benchmark uses a four-layer generative model with persona-based MCC distributions, time-of-day weighting, and persona-dependent transaction amounts. Despite these calibrations, binary task signals (has_nba, churn_signal, will_acquire_*) derive primarily from demographic and product-holding features, not transaction behavior — limiting the performance ceiling for these tasks regardless of model capacity or training duration. Multiclass and regression tasks that depend on MCC patterns (next_mcc, mcc_diversity_trend) benefit from the persona-weighted MCC generation but remain constrained by the absence of real merchant affinity and seasonal patterns. We expect significant AUC improvements when the architecture is deployed on production data with genuine behavioral signals.
- **Single-GPU training**: The current implementation runs on a single GPU. DDP (DistributedDataParallel) support is architecturally designed but not yet experimentally validated. For the ablation scenarios studied here, single-GPU training completes within acceptable time.
- **FP32 training**: We chose FP32 over mixed-precision (FP16) to preserve the mathematical semantics of heterogeneous experts. The on-prem ODE-based LNN dynamics, unbounded HGCN linear output, and Softplus TDA weights produce wider intermediate value ranges than homogeneous MLPs, causing FP16 overflow under AMP. FP32 eliminates this instability at the cost of 1.5× slower training — an acceptable trade-off given the single-GPU constraint.
- **LLM dependency**: Recommendation reason generation relies on LLM inference, introducing latency and cost trade-offs (detailed in companion paper).

6.4 Future Work: Scaling Considerations

The current architecture is intentionally lightweight — each expert uses a compact, domain-specific design (e.g., 2-layer MLP for DeepFM deep branch, pre-computed embeddings for HGCN) rather than scaling parameters. This is a deliberate design choice, not merely a resource constraint: structural inductive biases substitute for raw parameter count.

When scaling to larger institutions with dedicated GPU infrastructure, the natural progression is: (1) **data enrichment** — longer transaction histories, broader product coverage, richer interaction signals — before model capacity increase; (2) **per-expert input dimension expansion** — wider feature groups feeding each expert's specialized inductive bias; (3) **expert depth/width scaling** — deeper layers within individual experts, particularly Temporal (longer sequence modeling) and HGCN (deeper hierarchy encoding); (4) **multi-GPU training** via DDP, which is architecturally supported but not yet validated.

Notably, scaling the expert basket size (adding more expert types) is less promising than scaling individual expert capacity, because the heterogeneous design already covers the major mathematical perspectives relevant to financial behavior.

7 Conclusion

We presented Heterogeneous Expert PLE, a multi-task learning architecture for financial product recommendation that addresses the fundamental requirement of *persuading humans* — not merely predicting their behavior.

By composing seven structurally distinct experts within PLE's shared basket, we achieve three properties simultaneously: (1) parameter-efficient expressiveness under hardware constraints, (2) inherent explainability through business-interpretable gate weights, and (3) graceful degradation validated through comprehensive ablation.

The key insight is that explanation quality depends not on post-hoc attribution methods but on the model's internal structure. The two-axis decomposition (Financial DNA × Data Modality) ensures that every design decision — which experts to build, which features to engineer, which tasks to group — traces back to a principled analytical framework. When each expert carries a named inductive bias — temporal dynamics, product hierarchy, causal pathways — the gating mechanism *is* the explanation.

Ablation confirms that TDA and LightGCN deliver the largest individual AUC contributions (+0.028 and +0.027, respectively), while removing HGCN or LightGCN causes sharp degradation (ΔAUC -0.048 and -0.017). PLE Sigmoid gating (AUC 0.5771) outperforms softmax (AUC 0.5684) by +0.009, demonstrating that non-competitive routing is critical in a heterogeneous expert pool.

The architecture, benchmark data, and ablation framework are released as open source to enable reproduction and extension by the research community. A companion paper addresses the downstream pipeline: knowledge distillation [15] to LGBM [17], multi-agent recommendation reason generation, and regulatory compliance mapping for Korean FSS and EU AI Act requirements.

Author Contributions

Seonkyu Jeong (PM / Lead Architect / Data Scientist): Conceived the project direction, designed the heterogeneous expert architecture and two-axis decomposition framework, selected multi-disciplinary feature engineering approaches based on structural isomorphism, defined task groups and regulatory compliance mapping, led AI-augmented development methodology, and wrote the manuscript. Overall technical leadership and Scrum-based rapid feedback coordination.

Euncheol Sim: Data ingestion pipeline, feature engineering implementation, feature business reverse-mapping, and vector database pipeline management.

Youngchan Kim: Model training, mathematical verification, and knowledge distillation implementation.

All authors collaborated through Scrum sprints with rapid feedback cycles.

Funding

This research received no external funding, grants, or institutional infrastructure support. All costs — including AI development tools (Claude Code, Gemini, Cursor subscriptions), hardware peripherals, mobile data connectivity, AWS SageMaker cloud training (Spot instances), S3 storage, and operational expenses — were borne entirely by the first author's personal funds. Development was conducted on a single desktop-grade GPU (NVIDIA RTX 4070, 12GB VRAM) in a repurposed, inadequately ventilated workspace with no dedicated ML infrastructure budget, no institutional network support, and no institutional cloud computing allocation. Data collection was constrained to a legacy HIVE environment with no access to Spark or Impala, requiring custom parallel query logic to overcome I/O bottlenecks.

Acknowledgments

The authors thank Yeon-Jin Kim for consistently providing valuable insights on industry trends and marketing perspectives that informed the system's design direction.

The authors express deep gratitude to Euncheol Sim and Youngchan Kim, who dedicated countless nights and weekends to this project with unwavering commitment despite the absence of formal employment or compensation.

Finally, the authors wish to acknowledge the AI tools that made this research possible for a team of three with no institutional support. Gemini served as a tireless brainstorming partner throughout ideation and design direction discussions. Claude Opus and Sonnet were with us through nearly every stage — systematically structuring the architecture, implementing code, diagnosing subtle bugs, and helping articulate ideas into written form. Cursor provided the seamless development environment that kept our workflow free of bottlenecks. What could have remained one person's unrealized vision was brought to life through the collaboration of a small team and these tools. The architectural decisions, domain knowledge, experimental design, and research direction were led by the human authors; the AI tools amplified what would otherwise have been impossible to achieve at this scale.

Appendix

A. Configuration Schema

The entire system is controlled by two YAML configuration files: `pipeline.yaml` (model architecture, training hyperparameters, task definitions, AWS deployment settings) and `feature_groups.yaml` (feature group definitions, generator parameters, expert routing rules). Full configuration files are available in the accompanying repository.

B. Ablation Scenario Definitions

The 24 ablation scenarios are organized into two phases:

Phase 1 — Feature + Expert Joint Ablation (18 scenarios): Baseline (DeepFM only with base features), DeepFM with all features, full model, 8 bottom-up scenarios (DeepFM + one expert with matching features), and 6 top-down scenarios (full minus one expert-feature pair).

Phase 2 — Task x Structure Cross Ablation (6 scenarios): Six structural variants — shared-bottom (no PLE/adaTT), PLE-softmax, PLE-sigmoid, adaTT-only, PLE-softmax+adaTT, PLE-sigmoid+adaTT — all

using the full 14 tasks and 7 heterogeneous experts with 10 epochs.

C. Benchmark Data Generation

The synthetic benchmark uses a four-layer generative model: (1) latent personas via 6-component GMM with 5D continuous latent vector (70% persona-conditioned, 30% independent noise); (2) Gaussian Copula demographics preserving realistic correlations; (3) vectorized transaction sequences as LIST columns; (4) variance-budget labels with post-hoc noise flipping (6–8%). Seed=42 ensures reproducibility. Full generation code is available in the accompanying repository.

D. FP32 Training Decision

Heterogeneous experts with on-prem-aligned activation functions (ODE-based LNN, linear HGCN output, Softplus TDA weights) produce wider intermediate value ranges than homogeneous MLPs. Under AMP (FP16), this causes GradScaler overflow that cascades into NaN loss — observed consistently from epoch 2 in PLE configurations despite conservative GradScaler settings (init_scale=1024, max_scale=4096). FP32 training eliminates this entirely with zero NaN batches across all 20-epoch runs, at the cost of approximately 1.5× slower training. This trade-off preserves the mathematical semantics of each expert's inductive bias, which is the core design principle of the heterogeneous architecture.

E. Structural Isomorphism Verification

To address the concern that cross-disciplinary feature engineering may be "plausible analogy rather than rigorous isomorphism," we present the governing equations side by side:

Chemical Kinetics -> Spending Activation: Arrhenius: $k = Ae^{-E_a/RT}$ where E_a = activation energy. Spending: $p_{\text{reactivate}} = Ae^{-E_{\text{threshold}}/S}$ where S = stimulus intensity. Both describe the probability of a state transition as a function of an energy barrier and an external driving force.

SIR -> Product Adoption: Epidemiology: $d\frac{I}{d}t = \beta SI - \gamma I$ Adoption: $d\frac{A}{d}t = \beta_{\text{exposure}} \cdot U \cdot A - \gamma_{\text{churn}} \cdot A$ where U = unadopted customers, A = adopted, β = contact/exposure rate. The compartmental dynamics are identical; only the variable names change.

Bibliography

[1] AI21 Labs. 2024. Jamba: A Hybrid Transformer-Mamba Language Model. *arXiv preprint arXiv:2403.19887* (2024).

[2] Mathieu Carrière, Frédéric Chazal, Yuichi Ike, Théo Lacombe, Martin Royer, and Yuhei Umeda. 2020. PersLay: A Neural Network Layer for Persistence Diagrams and New Graph Topological Signatures. *Journal of Machine Learning Research* (2020).

[3] Rich Caruana. 1997. Multitask Learning. *Machine Learning* 28, 1 (1997), 41–75.

[4] Ines Chami, Rex Ying, Christopher Ré, and Jure Leskovec. 2019. Hyperbolic Graph Convolutional Neural Networks. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

[5] Wei Chen, Yong Liu, and Hao Zhang. 2024. Deep Learning-Powered Financial Product Recommendation System in Banks: Integration of Transformer and Transfer Learning. *Journal of Organizational and End User Computing* 36, 1 (2024).

[6] Marco Cuturi. 2013. Sinkhorn Distances: Lightspeed Computation of Optimal Transport. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2013.

[7] European Parliament and Council. 2024. Regulation (EU) 2024/1689 laying down harmonised rules on artificial intelligence (AI Act).

[8] William Fedus, Barret Zoph, and Noam Shazeer. 2022. Switch Transformers: Scaling to Trillion Parameter Models with Simple and Efficient Sparsity. *Journal of Machine Learning Research* (2022).

[9] Financial Services Commission (Korea). 2024. Financial Sector AI Guidelines.

[10] Milton Friedman. 1957. *A Theory of the Consumption Function*. Princeton University Press.

[11] Albert Gu and Tri Dao. 2024. Mamba: Linear-Time Sequence Modeling with Selective State Spaces. (2024).

[12] Huifeng Guo, Ruiming Tang, Yunming Ye, Zhenguo Li, and Xiuqiang He. 2017. DeepFM: A Factorization-Machine based Neural Network for CTR Prediction. In *Proceedings of the 26th International Joint Conference on Artificial Intelligence (IJCAI)*, 2017.

[13] Ramin Hasani, Mathias Lechner, Alexander Amini, and others. 2021. Liquid Time-constant Networks. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2021.

[14] Xiangnan He, Kuan Deng, Xiang Wang, Yan Li, Yongdong Zhang, and Meng Wang. 2020. LightGCN: Simplifying and Powering Graph Convolution Network for Recommendation. In *Proceedings of the 43rd International ACM SIGIR Conference*

on Research and Development in Information Retrieval, 2020.

[15] Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. 2015. Distilling the Knowledge in a Neural Network. In *NIPS Deep Learning and Representation Learning Workshop*, 2015.

[16] Kalervo Järvelin and Jaana Kekäläinen. 2002. Cumulated gain-based evaluation of IR techniques. *ACM Transactions on Information Systems* 20, 4 (2002), 422–446.

[17] Guolin Ke, Qi Meng, Thomas Finley, Taifeng Wang, Wei Chen, Weidong Ma, Qiwei Ye, and Tie-Yan Liu. 2017. LightGBM: A Highly Efficient Gradient Boosting Decision Tree. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2017.

[18] Alex Kendall, Yarin Gal, and Roberto Cipolla. 2018. Multi-Task Learning Using Uncertainty to Weigh Losses for Scene Geometry and Semantics. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2018.

[19] Jiaxin Li and others. 2024. HoME: Hierarchy of Multi-Gate Experts for Multi-Task Learning at Kuaishou. In *Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, 2024.

[20] Yankai Li and others. 2023. AdaTT: Adaptive Task-to-Task Fusion Network for Multi-task Learning in Recommendations. In *Proceedings of the 29th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, 2023.

[21] Tsung-Yi Lin, Priya Goyal, Ross Girshick, Kaiming He, and Piotr Dollár. 2017. Focal Loss for Dense Object Detection. In *Proceedings of the IEEE International Conference on Computer Vision (ICCV)*, 2017.

[22] Scott M Lundberg and Su-In Lee. 2017. A Unified Approach to Interpreting Model Predictions. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2017.

[23] Jiaqi Ma, Zhe Zhao, Xinyang Yi, Jilin Chen, Lichan Hong, and Ed H Chi. 2018. Modeling Task Relationships in Multi-task Learning with Multi-gate Mixture-of-Experts. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, 2018.

[24] Xiao Ma, Liqin Zhao, Guan Huang, Zhi Wang, Zelin Hu, Xiaoqiang Zhu, and Kun Gai. 2018. Entire Space Multi-Task Model: An Effective Approach for Estimating Post-Click Conversion Rate. In *Proceedings of the 41st International ACM SIGIR Conference on Research and Development in Information Retrieval*, 2018.

[25] Fernando Martinez-Plumed and others. 2023. Improving the Predictive Accuracy of the Cross-selling of Consumer Loans Using Deep Learning Networks. *Annals of Operations Research* (2023).

[26] Ali Met, Deniz Korkmaz, and Kerem Tuna. 2024. Product Recommendation System With Machine Learning Algorithms for SME Banking. *International Journal of Intelligent Systems* 2024, (2024).

[27] National Assembly of Korea. 2024. Act on the Development of Artificial Intelligence and Establishment of Trust (AI Basic Act).

[28] Huy Nguyen and others. 2024. Sigmoid Gating is More Sample Efficient than Softmax Gating in Mixture of Experts. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.

[29] Maximilian Nickel and Douwe Kiela. 2017. Poincaré Embeddings for Learning Hierarchical Representations. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2017.

[30] Neha Patki, Roy Wedge, and Kalyan Veeramachaneni. 2016. The Synthetic Data Vault. In *IEEE International Conference on Data Science and Advanced Analytics (DSAA)*, 2016.

[31] Judea Pearl and Dana Mackenzie. 2018. *The Book of Why: The New Science of Cause and Effect*. Basic Books.

[32] Judea Pearl. 2009. *Causality: Models, Reasoning, and Inference* (2nd ed.). Cambridge University Press.

[33] Mark Raasveldt and Hannes Mühleisen. 2019. DuckDB: An Embeddable Analytical Database. (2019).

[34] Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. 2016. Why Should I Trust You?: Explaining the Predictions of Any Classifier. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, 2016.

[35] Amr Salih and others. 2023. Examining the Limitations of Post-hoc Explainability Methods in Finance. *Frontiers in Artificial Intelligence* (2023).

[36] Noam Shazeer, Azalia Mirhoseini, Krzysztof Mahdavi, and others. 2017. Outrageously Large Neural

Networks: The Sparsely-Gated Mixture-of-Experts Layer. (2017).

[37] Xiang-Rong Sheng, Liqin Zhao, Guorui Zhou, Xinyao Ding, Binding Dai, Qiang Luo, Siran Yang, Jingshan Lv, Chi Zhang, Hongbo Deng, and Xiaoqiang Zhu. 2021. STAR: One-pass Single-Arch Multi-task Architecture for Cross-Domain CTR Prediction. In *Proceedings of the 30th ACM International Conference on Information and Knowledge Management (CIKM)*, 2021.

[38] Mukund Sundararajan, Ankur Taly, and Qiqi Yan. 2017. Axiomatic Attribution for Deep Networks. In *Proceedings of the 34th International Conference on Machine Learning (ICML)*, 2017.

[39] Hongyan Tang, Junning Liu, Ming Zhao, and Xudong Gong. 2020. Progressive Layered Extraction (PLE): A Novel Multi-Task Learning (MTL) Model for Personalized Recommendations. In *Proceedings of the 14th ACM Conference on Recommender Systems (RecSys)*, 2020.

[40] Lei Xu, Maria Skoularidou, Alfredo Cuesta-Infante, and Kalyan Veeramachaneni. 2019. Modeling Tabular Data using Conditional GAN. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

[41] Hanqing Zeng and others. 2024. Mixture of Weak and Strong Experts on Graphs. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.

[42] Zijian Zhang and others. 2024. M3oE: Multi-Domain Multi-Task Mixture-of Experts Recommendation Framework. In *Proceedings of the 47th International ACM SIGIR Conference on Research and Development in Information Retrieval*, 2024.

[43] Xun Zheng, Bryon Aragam, Pradeep Ravikumar, and Eric P Xing. 2018. DAGs with NO TEARS: Continuous Optimization for Structure Learning. (2018).