AIOps PLE Platform

Architecture Design Document

PLE + adaTT-Based Financial Product Recommendation System
Technical Design Document (Internal Reference)

Version 1.0 — 2026-04-01
Target Audience: Developers, Architects, Code Reviewers

Design vs Implementation Note

This document describes the **design intent and target architecture**. The current implementation may be a subset of the design, and some components described herein may not yet be implemented. Refer to the codebase and `pipeline_state.json` for implementation status.

Table of Contents

1. System Overview 4
   1.1. System Purpose 4
   1.2. Target Users and Operating Environment 4
   1.3. On-Prem vs AWS Comparison 4
2. Design Philosophy 5
   2.1. Principle 1: Inherent Explainability 5
   2.2. Principle 2: Graceful Degradation 5
   2.3. Principle 3: Extensibility 5
   2.4. Principle 4: Manageability 5
3. Architecture Decision History 6
   3.1. From ALS to Black-Litterman 6
   3.2. Black-Litterman Drop Rationale 6
   3.3. PLE + adaTT Selection Process 6
   3.4. Decision Flow Summary 6
4. PLE + Heterogeneous Expert Basket 8
   4.1. Limitations of Original PLE and Introduction of Heterogeneous Experts 8
   4.2. Pool / Basket / Runtime 3-Tier 8
   4.3. Expert Pool — 11 Registered Types 8
   4.4. 7-Expert Selection Rationale 8
      4.4.1. Temporal Ensemble: Intra-Expert Ensemble 9
   4.5. CGC Layer + Attention 9
   4.6. Dual-Registry Architecture 9
5. adaTT + Task Group 10
   5.1. 4 Financial DNA Groups 10
   5.2. Adaptive Task Transfer (adaTT) 10
   5.3. Loss-Level Transfer: Logit Transfer (3-Method Dispatch) 10
   5.4. HMM Triple-Mode Projection 10
   5.5. Multidisciplinary Per-Task Routing 10
6. Feature Pipeline 12
   6.1. 5-Axis Feature Classification 12
   6.2. 12 Feature Groups (316D) 12
      6.2.1. 4 Base Groups (transform type) 12
      6.2.2. 8 Generated Groups (generate type) 12
   6.3. 11 Academic Disciplines (Multidisciplinary Feature Design) 12
   6.4. Dual Role of Features: Training + Recommendation Rationale 13
   6.5. 3-Stage Normalization Pipeline 13
7. Training Pipeline 14
   7.1. Phase 0: Data Preparation 14
      7.1.1. 4-Layer Data Leakage Prevention 14
      7.1.2. Data Processing Backend Policy 14
   7.2. Phase 1–3: Ablation Study (48 Scenarios) 14
   7.3. Model Training (Common to Phase 1–3) 14

7.3.1. Per-Task Loss Dispatch . . . 14
7.3.2. Uncertainty Weighting (Kendall et al.) . . . 14
7.3.3. Evidential Deep Learning (Config-Gated) . . . 15
7.3.4. SAE Regularization (Detached, Config-Gated) . . . 15
8. Distillation + Serving . . . 16
8.1. Phase 4: Knowledge Distillation (PLE -> LGBM) . . . 16
8.2. Phase 5: Serverless Serving (Lambda) . . . 16
8.2.1. Serving Architecture . . . 16
8.2.2. FD-TVS Composite Scoring . . . 16
8.2.3. DNA Modifier . . . 16
8.2.4. Constraint Engine . . . 16
8.2.5. Recommendation Rationale Generation Pipeline . . . 16
9. Monitoring + Compliance . . . 17
9.1. Pipeline Tracking . . . 17
9.2. Per-Stage Checkpoints . . . 17
9.3. Audit Artifacts . . . 17
9.4. Interpretability Pipeline (Stage 8.5) . . . 17
9.5. Encryption Pipeline (Stage 3) . . . 17
10. End-to-End Data Flow . . . 18
10.1. Full Data Flow Diagram . . . 18
10.2. Internal Model Data Flow . . . 19
10.3. GPU/CPU Acceleration Mapping . . . 19
11. Appendix: PLEModel Build Automation . . . 21
11.0.1. PLEInput Data Container . . . 21
12. Appendix: Config File Structure . . . 21

1. System Overview

1.1. System Purpose

AIOps PLE Platform is an end-to-end multi-task learning platform for **financial product recommendation**. It targets banks, card companies, and financial holding companies, generating personalized recommendations for comprehensive financial products—deposits, cards, loans, investments—along with **explainable rationale** simultaneously.

The final deliverable of AI recommendation is not a probability (0.73) but a **reason the customer can accept**. The persuasion target is always a person, and three levels of explanation are required:

Audience	Question	Expected Level
Customer	"Why this product?"	Trust -> Conversion
Banker	"Why recommend this to this customer?"	Sales rationale
Regulator	"Why was this decision made?"	Regulatory compliance (EU AI Act, FSS Guidelines)

1.2. Target Users and Operating Environment

- **Financial ML Operations Staff**: Realistically 1–2 people. N models x explanation modules x ensemble logic = N management points. A single config system must enable unified management.
- **Hardware**: 1–4 GPU scale. Since MLP parameter scaling is infeasible, structural inductive bias is used to secure expressiveness.
- **Infrastructure**: On-Prem (Airflow + DuckDB) or AWS (SageMaker + S3). The architectural philosophy remains identical; only the infrastructure layer changes.

1.3. On-Prem vs AWS Comparison

Aspect	On-Prem (Current)	AWS (Target)	Migration Rationale
Orchestration	Airflow 86 DAGs ($300/mo)	Step Functions 5 ($0/mo)	Pay-per-execution
Training	Local GPU	SageMaker Spot (70% savings)	Parallel ablation
Storage	DuckDB files	S3 Parquet	Durability, IAM
Serving	FastAPI + Docker	Lambda / ECS Fargate	Auto-switch by scale
Experiment Mgmt	MLflow (Docker)	SageMaker Experiments	Eliminate server maintenance cost
Monitoring	Custom drift_monitor	SageMaker Model Monitor	Managed service

2. Design Philosophy

Four core design principles serve as the starting point for all technical decisions.

2.1. Principle 1: Inherent Explainability

The system pursues **structural explanation** rather than post-hoc explanation (SHAP/LIME).

- **SHAP/LIME limitations**: Separated from the model, so explanations diverge from internal behavior. Explanations change drastically with slight input changes. Separate computation per inference multiplies serving latency.
- **Structural approach**: Explanations are derived from the model structure itself (gate, evidential, contrastive). A single forward pass produces both inference and explanation simultaneously.

The Heterogeneous Expert architecture makes this possible:

- CGC gate weights themselves serve as explanations: "Temporal(0.35), DeepFM(0.28), HGCN(0.22)"
- Expert names directly map to business context: "Time-series pattern contributed 35%, feature interaction 28%, product hierarchy 22%"
- With homogeneous MLP experts, "MLP 3 contributed" carries no business meaning

2.2. Principle 2: Graceful Degradation

Even if one expert becomes useless, the remaining experts naturally compensate through gate redistribution.

- Ablation proves "removing any expert does not cause catastrophic performance degradation"
- Financial sector characteristics: Unlike big tech's aggressive "AUC +0.01 = N billion in revenue" experimentation, financial firms face "regulatory sanctions for model malfunction" -> conservative operations, stability first

2.3. Principle 3: Extensibility

Adding new features/tasks requires only config changes. adaTT automatically learns new relationships without modifying existing structures.

- **Pool/Basket/Runtime 3-tier**: Code(Pool) -> Config(Basket) -> Training(Runtime) separation
- Zero code changes for domain switching: simply replace config files from `configs/financial/` to `configs/ecommerce/`

2.4. Principle 4: Manageability

The entire pipeline (feature generation -> training -> distillation -> serving -> recommendation rationale) is managed through a unified config system (`pipeline.yaml` + `feature_groups.yaml`).

- **Config-Driven**: A single YAML defines data/tasks/model/infrastructure. New problems without code changes.
- **Registry Pattern**: Expert, Task, Feature, Model, Tower are all registered via plug-in pattern.
- **Schema-First**: The data schema determines the entire pipeline.

3. Architecture Decision History

3.1. From ALS to Black-Litterman

The existing financial product recommendation system was based on ALS (Alternating Least Squares) collaborative filtering. When the decision to adopt MLOps was made, next-generation model evaluation began.

Initial candidates:
1. DL model family (DeepFM, Wide&Deep, AutoInt)
2. GBM model family (XGBoost, LightGBM, CatBoost)
3. DL + GBM ensemble

During ensemble evaluation, there was an attempt to apply the financial portfolio optimization **Black-Litterman model** to recommendations. The idea was to treat each model's prediction as an "expert view" and integrate them via Bayesian updating weighted by uncertainty (risk).

3.2. Black-Litterman Drop Rationale

Critical limitations were identified at the design stage:

Limitation	Details
Business interpretation impossible	Each model's contribution is blended during Bayesian updating -> "Why was this product recommended?" becomes hard to explain. Fatal in the regulatory environment.
Structural mismatch	Fundamental difference between financial portfolios (continuous weight allocation) and product recommendation (discrete selection)
View matrix automation difficulty	Uncertainty estimation for each model is subjective and hard to automate
Multi-task limitation	Insufficient means to express inter-task relationships when integrating churn/recommendation/segment/value into a single BL framework

3.3. PLE + adaTT Selection Process

The question was reframed: "How to blend multiple models well?" (ensemble) -> "Is there a structure where multiple experts collaborate within a single model?" (MoE/PLE).

MTL (Multi-Task Learning) family evaluation:

Architecture	Characteristics	Limitation
Shared-Bottom	Single expert shared across all tasks	Severe negative transfer
MMoE	N experts + per-task gate	All experts exposed to all tasks -> insufficient specialization
PLE	Shared + task-specific expert separation, CGC gate	Selected

Why PLE was selected:
- Expert network = internal ensemble (per-expert specialization)
- CGC gate = per-task expert weighting -> explainability
- Single model training/deployment -> 1 management point, fixed serving cost
- What Black-Litterman tried externally (uncertainty-based integration of expert opinions) is solved internally, data-driven, within the model structure

3.4. Decision Flow Summary

```
ALS (existing)
  | "MLOps adoption, next-gen model needed"
DL + GBM ensemble evaluation
  | "Simple ensemble insufficient for multi-task integration"
Black-Litterman attempt
  | "Financial portfolio != product recommendation, dropped at design stage"
PLE + adaTT selected
  | "Prototype validated on-premises"
AWS migration
  | "Parallel ablation + end-to-end serving needed"
Benchmark data + Ablation execution
```

```
  | (planned)
Distillation + Lambda serving
```

4. PLE + Heterogeneous Expert Basket

4.1. Limitations of Original PLE and Introduction of Heterogeneous Experts

The original PLE (Tencent, 2020) shared experts consist of **homogeneous MLP x N** (same structure, different initialization). Expressiveness increases only by adding parameters, so lightweight models lack representational power.

Our approach: shared expert = **7 heterogeneous experts**. Each expert processes the same data from a different perspective with a different inductive bias, and the CGC gate learns "which perspective is useful for this task." Lighter than a single large MLP yet more expressive.

4.2. Pool / Basket / Runtime 3-Tier

```
Pool (Registry)           Basket (Config Selection)     Runtime (Weighted Execution)
+-----------------+      +------------------+          +------------------+
| All components  |      | YAML config      |          | At execution     |
| registered in   |----->| selects a subset |--------->| weight-based     |
| Registry        |      | (per domain)     |          | combination      |
| (plug-in)       |      |                  |          | (train/infer)    |
+-----------------+      +------------------+          +------------------+
     Code domain              Config domain               Model domain
```

Tier	Role	Change Agent
Pool	Register all available components in Registry	Developer (code addition)
Basket	Select subset for a specific pipeline via YAML	Operator (config swap)
Runtime	Weighted combination of selected components during execution	Model (automatic during training)

4.3. Expert Pool — 11 Registered Types

#	Registry Name	Class	Primary Axis	Basket
1	`deepfm`	DeepFM Expert	State (feature interaction)	O
2	`temporal_ensemble`	Temporal Ensemble	Timeseries (Mamba+LNN+Transformer)	O
3	`hgcn`	Unified HGCN	Hierarchy (hyperbolic graph)	O
4	`perslay`	PersLay Expert	Snapshot (TDA global)	O
5	`causal`	Causal Expert	Snapshot (NOTEARS DAG)	O
6	`lightgcn`	LightGCN Expert	Item (graph collaborative filtering)	O
7	`optimal_transport`	OT Expert	Snapshot (Sinkhorn)	O
8	`mlp`	MLP Expert	State (basic)	—
9	`mamba`	Mamba Expert	Timeseries (SSM)	—
10	`autoint`	AutoInt Expert	State (Self-Attention)	—
11	`xdeepfm`	XDeepFM Expert	State (CIN + Deep)	—

4.4. 7-Expert Selection Rationale

Each expert possesses a non-overlapping inductive bias:

Expert	Inductive Bias	Pattern Captured with Fewer Parameters
DeepFM	Feature interaction	2nd-order cross effects between features
Temporal Ensemble	Composite time series (Mamba+LNN+Transformer)	Long/short-term/discontinuous time-series integration
HGCN	Hierarchical structure (hyperbolic space)	Product category tree

Expert	Inductive Bias	Pattern Captured with Fewer Parameters
PersLay	Topological structure	TDA persistence shapes
LightGCN	Graph relationships	Customer-product collaborative filtering
Causal	Causal relationships	Causal direction (DAG constraint)
Optimal Transport	Distribution matching	Distribution differences across customer segments

4.4.1. Temporal Ensemble: Intra-Expert Ensemble

Financial time series have compound structures that no single model can capture. The Temporal Expert itself is designed as an internal ensemble of 3 models:

Model	Strength	Weakness
Mamba (SSM)	Long-range dependency, O(n) efficiency	Weak on irregular intervals
LNN (Liquid NN)	Adapts to discontinuous/irregular data	Poor at long-context summarization
Transformer	Short-context extraction	$O(n^2)$, inefficient for long sequences

4.5. CGC Layer + Attention

`CGCLayer` is the core building block of PLE. For each task, a gating network combines shared + task-specific expert outputs.

- **dim_normalize=True**: When expert output dimensions differ, `sqrt(mean_dim/dim)` scaling corrects dimensional imbalance
- **bias_high/bias_low**: Injects initial bias toward domain-relevant experts
- **entropy regularization**: Prevents expert collapse

Stacked PLE: 3 CGC layers. Layer 0 uses the heterogeneous Expert Basket + FeatureRouter, while Layers 1–2 use homogeneous MLP experts for abstraction.

4.6. Dual-Registry Architecture

```
Expert Pool Registry (core.model.experts.registry.ExpertRegistry)
    +-- AbstractExpert(input_dim, config)
    +-- 11 types registered

Expert PLE Registry (core.model.ple.experts.ExpertRegistry)
    +-- BaseExpert(input_dim, output_dim, dropout)
    +-- For CGCLayer default expert creation

Expert Basket (core.model.ple.experts.ExpertBasket)
    +-- Pool Registry -> Basket selection -> Inject into CGCLayer.shared_experts
```

5. adaTT + Task Group

5.1. 4 Financial DNA Groups

The initial design considered per-GMM-cluster task sub-heads, but with K=20, T=18, this would produce 360 sub-heads -> unmanageable, high overfitting risk. The direction was shifted to **grouping tasks by financial DNA perspective**:

Group	Financial DNA	Included Tasks	intra	inter
engagement	Does the customer respond?	has_nba, engagement_score, next_mcc, top_mcc_shift	0.8	0.3
lifecycle	Where is the customer?	churn_signal, product_stability, tenure_stage, segment_prediction	0.7	0.3
value	How valuable is the customer?	spend_level, income_tier, mcc_diversity_trend	0.6	0.3
consumption	What will the customer buy?	nba_primary, cross_sell_count, will_acquire_* (5)	0.7	0.3

A total of **18 tasks** organized into 4 semantic groups.

5.2. Adaptive Task Transfer (adaTT)

- **Intra-group**: Strong transfer between tasks in the same group (0.6–0.8)
- **Inter-group**: Weak transfer between different groups (0.3) — minimizing interference
- **Negative transfer threshold**: Automatically blocks transfer when performance degrades
- **EMA decay**: Stabilizes transfer weights
- **Warmup/freeze epochs**: Initial stabilization

5.3. Loss-Level Transfer: Logit Transfer (3-Method Dispatch)

Explicit causal relationships between tasks are modeled through 5 edges:

Source	Target	Method	Meaning
engagement_score	has_nba	output_concat	Activity -> Subscription (leading indicator)
has_nba	nba_primary	output_concat	Subscription status -> Which product
churn_signal	product_stability	output_concat	Churn -> Product stability
spend_level	cross_sell_count	output_concat	Spending level -> Cross-sell
next_mcc	nba_primary	hidden_concat	Next merchant category -> Next product (feature sharing)

Three transfer methods:

- **residual**: source output -> Linear -> tower_dim, residual addition
- **output_concat**: source output concatenated with tower input -> Linear -> tower_dim
- **hidden_concat**: source pre-tower hidden concatenated with tower input -> Linear -> tower_dim

`logit_transfer_strength: 0.5` — transfer ratio.

5.4. HMM Triple-Mode Projection

Three HMM modes are routed to task groups:

Task Group	HMM Mode	Meaning
engagement	behavior	Behavior mode -> Response/activity
lifecycle	lifecycle	Lifecycle mode -> Churn/retention
value	journey	Journey mode -> Value/spending
consumption	journey	Journey mode -> Consumption pattern

Per-mode 16D -> `task_expert_output_dim` projection, followed by additive fusion into tower input.

5.5. Multidisciplinary Per-Task Routing

24D multidisciplinary features are routed as 6D slices to 4 task groups:

Task Group	Discipline	Dimension
engagement	chemical_kinetics	[0:6]
lifecycle	epidemic_diffusion	[6:12]
value	crime_pattern	[12:18]
consumption	interference	[18:24]

6. Feature Pipeline

6.1. 5-Axis Feature Classification

All features are classified along 5 axes, and each axis is mapped to a corresponding Feature Generator and Expert.

Axis	Temporal Dependency	Rate of Change	Representative Data	Processing Method
State	None (static)	Nearly invariant	Age, gender, enrollment date	Feature interaction (FM)
Snapshot	Long-term (monthly/quarterly)	Slow	12-month transaction topology, HMM states	Long-term pattern extraction
Timeseries	Short-term (daily/weekly)	Fast	Recent 90-day transaction sequence	Sequence modeling (SSM)
Hierarchy	None (structural)	Slow	MCC code hierarchy, product categories	Hyperbolic embedding
Item	None (relational)	Medium	Customer-product interactions	Graph collaborative filtering

6.2. 12 Feature Groups (316D)

6.2.1. 4 Base Groups (transform type)

Generated by transforming existing raw columns. No Generator required.

- `base_rfm`: RFM-based features (quantile transform)
- `base_demographics`: Demographic features
- `base_product`: Product holding status
- `base_activity`: Activity metrics

6.2.2. 8 Generated Groups (generate type)

Dedicated Feature Generators produce features.

Group	Generator	Output D	Description
tda_topology	tda_extractor	70D	Topological analysis based on Persistence Diagrams
hmm_states	hmm_triple_mode	48D	Journey/lifecycle/behavior state estimation
hyperbolic_embedding	hyperbolic_embedding	20D	Hyperbolic space hierarchical structure embedding
temporal_pattern	temporal_pattern	variable	Time-series aggregation + periodic encoding
multidisciplinary	multidisciplinary	24D	Chemical kinetics, epidemic diffusion, interference, crime patterns
gmm_clustering	gmm	variable	Soft posterior probabilities
economics	economics_extractor	17D	MPC, income elasticity, permanent income
model_derived	model_feature_extractor	27D	Leveraging prior model outputs

6.3. 11 Academic Disciplines (Multidisciplinary Feature Design)

Discipline	Adopted Element	Meaning for Financial Customers
Topology	TDA Persistent Homology	Structural shape of consumption patterns
Hyperbolic Geometry	Hyperbolic GCN	Distortion-free embedding of product hierarchy
Stochastic Processes	HMM State Transitions	Customer lifecycle stage tracking
Control Theory	Mamba (State Space Model)	Long-range behavioral dependency
Economics	Permanent/transitory income, marginal utility	Structural decomposition of spending capacity

Discipline	Adopted Element	Meaning for Financial Customers
Financial Engineering	Risk metrics, Bandit explore/exploit	Product exploration propensity
Graph Theory	LightGCN	Behavioral transfer among similar customer groups
Statistics	GMM Clustering	Soft segmentation
Causal Inference	Causal DAG (NOTEARS)	Causal direction between behaviors
Optimal Transport	Sinkhorn Optimal Transport	Distribution shift across segments
Neural ODE	Liquid Neural Network	Adaptation to irregular time intervals

Key insight: These perspectives are non-overlapping. Topology's "shape" and economics' "utility" are entirely different aspects of the same customer, each contributing independently (proven by ablation).

6.4. Dual Role of Features: Training + Recommendation Rationale

The value of multidisciplinary features is not just training performance (AUC contribution). Even if removing TDA features only drops AUC by 0.01, the explanation "Your consumption pattern has been consistently showing a stable shape" is impossible to generate without TDA.

Business context reverse mapping is built for all features:

- `hmm_lifecycle_prob_growing` -> "Growth-stage customer"
- `mamba_temporal_d3` -> "Spending increase trend over the last 3 months"
- `hgcn_hierarchy_d5` -> "Position close to investment product category"

6.5. 3-Stage Normalization Pipeline

```
Stage 1: Power-law detection (skew+kurt -> log-log R^2) + log1p copy generation
Stage 2: StandardScaler (continuous columns only, binary excluded, TRAIN fit only)
Stage 3: Power-law _log copies are not scaled (raw magnitude preserved)
```

- Scaler is **fit on TRAIN split only**. val/test are transform-only with the train-fitted scaler.
- Binary columns are excluded from scaling.

7. Training Pipeline

7.1. Phase 0: Data Preparation

A 10+ stage PipelineRunner transforms raw data into training-ready tensors.

Stage	Name	Description	GPU
1	DataAdapter	DuckDB-native raw data load, AdapterRegistry-based	—
1.5	TemporalPrep	Sequence truncation (drop last month), prod_* recalculation	—
2	SchemaClassifier	Classify all columns into 5-Axis	—
3	EncryptionPipeline	PII -> SHA256 -> INT32 (domain-specific salt)	—
4	FeatureGroupPipeline	Run 8 Generators + PowerLawAwareScaler	cuDF
5	LabelDeriver	Config-driven 18-label generation	—
5.5	LeakageValidator	Sequence/correlation/product/temporal 4-way leakage check	—
6	SequenceBuilder	flat -> 3D tensor (event_seq, session_seq)	—

Phase 0 runs on **CPU instances**. GPU instances are not wasted on Phase 0.

7.1.1. 4-Layer Data Leakage Prevention

1. **Sequence truncation**: 17 months -> 16 months (drop last month)
2. **Product recalculation**: Recalculate prod_* based on month 16 state
3. **Temporal split**: temporal split + gap_days (minimum 7 days)
4. **LeakageValidator**: Sequence/correlation/product/temporal verification, auto-remove features with >0.95 correlation

7.1.2. Data Processing Backend Policy

Priority: cuDF (GPU) -> DuckDB (CPU columnar) -> pandas (last resort fallback, only for fewer than 10K records). Direct use of `pd.read_parquet()`, `pd.concat()`, `df.apply()` and similar pandas calls is avoided.

7.2. Phase 1–3: Ablation Study (48 Scenarios)

Systematic experiments across 4 dimensions x multiple scenarios:

Phase	Dimension	Content	Job Count
1	Feature Group	full + base_only + bottom-up + top-down	16
2	Expert	deepfm baseline + bottom-up + top-down + mlp_only	16
3	Task x Structure	4 tiers x 4 structures (shared_bottom / ple_only / adatt_only / full)	16

- **Bottom-up**: base + X -> measures independent contribution
- **Top-down**: full − X -> measures irreplaceability

7.3. Model Training (Common to Phase 1–3)

7.3.1. Per-Task Loss Dispatch

Loss Type	Module	Usage	Task Type
focal	FocalLoss(alpha, gamma)	Imbalanced binary classification (calibrated alpha)	binary
huber	SmoothL1Loss	Outlier-robust regression	regression
mse	MSELoss	Basic regression	regression
ce	CrossEntropyLoss(weight)	Multi-class (auto class_weights)	multiclass
infonce	InfoNCELoss(temperature)	Contrastive learning	contrastive

In AMP (Mixed Precision) environments, tower output is cast to FP32 before loss computation (overflow prevention).

7.3.2. Uncertainty Weighting (Kendall et al.)

$$L_{\text{total}} = \sum_k \left[\exp(-s_k) \cdot L_k + \frac{s_k}{2} \right]$$

s_k: learnable log-variance for task k. Tasks with higher uncertainty -> automatic weight reduction.

7.3.3. Evidential Deep Learning (Config-Gated)

Task Type	**Distribution**	**Parameters**	**Uncertainty**
Binary	Beta(alpha, beta)	alpha, beta	1/(alpha+beta)
Multiclass	Dirichlet(alpha)	alpha_1..K	K/sum(alpha)
Regression	Normal-Inverse-Gamma	mu, v, alpha, beta	beta/(v*(alpha-1))

7.3.4. SAE Regularization (Detached, Config-Gated)

Anthropic-style Sparse Autoencoder. Applied to the shared expert concatenated output. **Detached** so it does not affect main model gradients (analysis-only sidecar). Tied weights, pre-bias centering, ReLU activation.

8. Distillation + Serving

8.1. Phase 4: Knowledge Distillation (PLE -> LGBM)

```
PLE Teacher (GPU training)
    | Soft label generation (temperature=5.0)
    | Store in S3
LGBM Student (CPU training)
    | alpha=0.3 (30% hard + 70% soft)
    | IG-based feature selection (top-k features)
    | Save lightweight model
Serving (real-time: LGBM ~5ms, batch: PLE)
```

- **Temperature**: 5.0 — maximizes information content of soft labels
- **Alpha**: 0.3 — 30% hard label + 70% soft label blend
- **Fidelity validation**: Teacher-student prediction agreement verification

8.2. Phase 5: Serverless Serving (Lambda)

8.2.1. Serving Architecture

- **Real-time**: LGBM student -> Lambda (5ms latency)
- **Batch**: PLE teacher -> SageMaker Batch Transform
- **Scale switching**: Lambda (default) ECS Fargate (large scale) automatic switching

8.2.2. FD-TVS Composite Scoring

Task-level predictions are integrated into a single recommendation score:

Task	Weight
has_nba	0.20
nba_primary	0.30
cross_sell_count	0.15
churn_signal	0.15
product_stability	0.10
engagement_score	0.10

8.2.3. DNA Modifier

Segment-level weight adjustment: TOP(1.3), PARTICULARES(1.0), UNIVERSITARIO(0.8), UNKNOWN(0.7).

8.2.4. Constraint Engine

Constraint	Description
Fatigue	Maximum 5 messages within 7 days
Eligibility	min_score > 0.05, max_churn_prob < 0.6
Owned Product	Exclude already-owned products via prod_* prefix
Product Tier	Minimum tenure: standard 3 months, growth 6 months, premium 12 months
Top-K Diversity	Ensure diversity via MMR (lambda=0.5)

8.2.5. Recommendation Rationale Generation Pipeline

```
[Model Inference] -> [IG Attribution: Top Features] -> [Business Reverse Mapping]
-> [LLM Agent: Context Composition -> Natural Language Recommendation Rationale]
```

Four levels of explanation are provided simultaneously:

1. **gate weight**: "Which perspective contributed" (expert-level)
2. **contrastive**: "Why this and not that" (contrastive)
3. **evidential**: "How confident is this" (uncertainty quantification)
4. **SAE**: "Which internal concepts were activated" (neuron-level)

9. Monitoring + Compliance

9.1. Pipeline Tracking

Artifact	Location	Purpose
`pipeline_manifest.json`	output_dir/	Full pipeline config snapshot
`pipeline_state.json`	output_dir/	Per-stage completion/failure status, resume support
`feature_stats.json`	output_dir/	Zero-variance, NaN ratio, feature column count
`label_stats.json`	output_dir/	Class balance, positive rate

9.2. Per-Stage Checkpoints

Stage	Artifact	Format
Feature	`features.parquet`	Parquet
Label	`labels.parquet`	Parquet
Sequence	`sequences.npy`, `seq_lengths.npy`	NumPy
Scaler	`scaler_params.json`	JSON
Leakage	`leakage_report.json`	JSON

9.3. Audit Artifacts

```
audit/
+-- schema/          <- Schema validation results
+-- encryption/      <- PII processing audit log
+-- scaler/          <- scaler_params.json
+-- labels/          <- label_transforms.json
+-- leakage/         <- LeakageValidator results
+-- fidelity/        <- Distillation fidelity verification
```

9.4. Interpretability Pipeline (Stage 8.5)

Analysis	Purpose	Output
Integrated Gradients (IG)	Feature attribution measurement	attribution scores
Expert Redundancy CCA	Inter-expert redundancy detection	CCA correlation matrix
CGC Gate Analysis	Per-task expert weight analysis	attention heatmap
HGCN Interpretable	Hierarchical structure explanation	hierarchy paths
Multi Interpreter	Multidisciplinary interpretation integration	structured reasons
Template Reason Engine	Natural language recommendation rationale	text templates
XAI Quality Evaluator	Explanation quality evaluation	quality scores
Model Card	Auto-generated model documentation	model_card.json

9.5. Encryption Pipeline (Stage 3)

```
Schema (pii: true)
    | derive_from_schema()
EncryptionPolicy (per source, per column)
    |
EncryptionPipeline.process_source()
    +-- Step 1: Drop (phone, email, SSN, etc.)
    +-- Step 2: SHA256 Hash (domain-specific salt)
    +-- Step 3: Integer Index (hash -> INT32)
    +-- Step 4: Audit report
```

16 PII domains defined (CUSTOMER, ACCOUNT, CARD, MERCHANT, etc.). SaltManager manages per-domain salts from AWS Secrets Manager or local storage.

10. End-to-End Data Flow

10.1. Full Data Flow Diagram

```
+-------------------------------------------------------------+
|                    Phase 0: Data Preparation                    |
|                                                                 |
|  S3 Raw Parquet                                                 |
|       |                                                         |
|       v                                                         |
|  Stage 1: DataAdapter (DuckDB-native load)                      |
|       |                                                         |
|       v                                                         |
|  Stage 1.5: TemporalPrep (sequence truncation, prod recalc)    |
|       |                                                         |
|       v                                                         |
|  Stage 2: SchemaClassifier (5-Axis classification)              |
|       |                                                         |
|       v                                                         |
|  Stage 3: EncryptionPipeline (PII -> SHA256 -> INT32)           |
|       |                                                         |
|       v                                                         |
|  Stage 4: FeatureGroupPipeline (8 Generators + Normalization)   |
|       |         output: features.parquet (316D)                 |
|       v                                                         |
|  Stage 5: LabelDeriver (18 tasks, config-driven)                |
|       |         output: labels.parquet                          |
|       v                                                         |
|  Stage 5.5: LeakageValidator (4-check, auto-drop)              |
|       |                                                         |
|       v                                                         |
|  Stage 6: SequenceBuilder (flat -> 3D tensors)                  |
|               output: event_seq.npy, session_seq.npy            |
+----------------------------+-----------------------------------+
                             |
                             v
+-------------------------------------------------------------+
|                Phase 1-3: Ablation Training                     |
|                                                                 |
|  Stage 7: DataLoader (temporal split, gap_days)                 |
|       |                                                         |
|       v                                                         |
|  Stage 8: PLETrainer                                            |
|       |   PLE (3-layer CGC, 7 shared + 1 task expert)           |
|       |   adaTT (4 groups, intra/inter transfer)                |
|       |   Logit Transfer (5 edges, 3 methods)                   |
|       |   HMM Triple-Mode + Multidisciplinary Routing           |
|       |   Evidential + SAE (config-gated)                       |
|       |   Per-task Loss + Uncertainty Weighting                 |
|       |   AMP FP16 forward + FP32 loss                          |
|       |                                                         |
|       v                                                         |
|  Stage 8.5: Model Analysis                                      |
|       |   IG, CCA, Gate, HGCN, Multi Interpreter                |
|       |   Template Engine, XAI Quality, Model Card              |
+----------------------------+-----------------------------------+
                             |
                             v
+-------------------------------------------------------------+
|                Phase 4: Distillation                            |
|                                                                 |
```

```
|  Stage 9: StudentTrainer                                        |
|       |   PLE teacher -> LGBM students                          |
|       |   Soft label (T=5.0, alpha=0.3)                         |
|       |   IG-based feature selection + fidelity validation      |
+----------------------------+-----------------------------------+
                             |
                             v
+-------------------------------------------------------------+
|                Phase 5: Serving                                 |
|                                                                 |
|  Stage 9.5: Context Vector Store (RAG embedding)                |
|       |                                                         |
|       v                                                         |
|  Stage 10: CPE + Agentic Reason Orchestrator                    |
|       |   FD-TVS scoring + DNA modifier                         |
|       |   Constraint Engine (fatigue, eligibility, diversity)    |
|       |   L1+L2a+L2b inference chain                            |
|       |                                                         |
|       v                                                         |
|  Lambda / ECS Fargate (serverless serving)                      |
|       output: Recommended products + NL rationale + uncertainty |
+-------------------------------------------------------------+
```

10.2. Internal Model Data Flow

```
5-Axis Features (316D)
    |
    v FeatureRouter (per-axis distribution)
+----------------------------------+
|  Expert Basket (7 shared)        |
|  DeepFM <- State axis            |
|  Temporal <- Timeseries axis     |
|  HGCN <- Hierarchy axis          |
|  PersLay <- Snapshot axis        |
|  Causal <- Snapshot axis         |
|  LightGCN <- Item axis           |
|  OT <- Snapshot axis             |
+----------+-----------------------+
           |
           v CGC Layer x 3 (dim_normalize, entropy reg.)
           |
           v HMM Triple-Mode Projection (16D x 3 modes)
           |
           v Multidisciplinary Routing (24D -> 4 x 6D)
           |
           v adaTT (intra 0.6-0.8, inter 0.3)
           |
           v Logit Transfer (5 edges, strength=0.5)
           |
           v Task Towers x 18 (TowerRegistry)
           |
           +-- Evidential Layer (regression tasks)
           +-- SAE Regularization (detached sidecar)
           +-- Per-task Loss + Uncertainty Weighting
```

10.3. GPU/CPU Acceleration Mapping

Stage	Target	CPU Path	GPU Path
1	Data loading	DuckDB (primary)	cuDF (optional)
4	Generator execution	pandas fallback	cuDF primary (cuML for GMM)
4	TDA persistence	ripser (NumPy)	cuPY + ripser (5–10x)

Stage	Target	CPU Path	GPU Path
4	StandardScaler	NumPy	cuPY (3–5x on 100M+ rows)
7	Training data loading	PyArrow (zero-copy)	—
8	Model training	PyTorch CPU	PyTorch CUDA + AMP

GPU acceleration is optional; CPU paths are used as automatic fallback when cuDF/cuPY is not installed.

11. Appendix: PLEModel Build Automation

When `PLEModel.__init__(config: PLEConfig)` is called, the following are built automatically in order:

1. `_build_extraction_layers()` — Stacked CGC + FeatureRouter
2. `_build_cgc_attention()` — Per-task attention (dim_normalize)
3. `_build_task_experts()` — GroupTaskExpertBasket or MLP fallback
4. `_build_hmm_projectors()` — 3 modes x projection
5. `_build_adatt()` — Adaptive Task Transfer
6. `_build_logit_transfer()` — 3-method dispatch, 5 edges
7. `_build_multidisciplinary_routing()` — 24D -> 4 x 6D
8. `_build_task_towers()` — TowerRegistry (standard/contrastive)
9. `_build_evidential_layers()` — NIG for regression (config-gated)
10. `_build_sae()` — Sparse Autoencoder (config-gated)
11. `_build_task_loss_fns()` — `build_loss()` per task
12. `_build_loss_weighting()` — Uncertainty / GradNorm / DWA / Fixed

11.0.1. PLEInput Data Container

```
@dataclass
class PLEInput:
    features: Tensor                      # (batch, input_dim)
    feature_group_ranges: Optional[Dict] # group->(start,end) for routing
    cluster_ids: Optional[Tensor]        # (batch,) cluster assignment
    cluster_probs: Optional[Tensor]      # (batch, n_clusters) soft probs
    targets: Optional[Dict[str, Tensor]] # {task_name: label}
    hyperbolic_features: Optional[Tensor]   # (batch, 20)
    tda_features: Optional[Tensor]          # (batch, 70)
    collaborative_features: Optional[Tensor]# (batch, 64)
    hmm_journey: Optional[Tensor]           # (batch, 16)
    hmm_lifecycle: Optional[Tensor]         # (batch, 16)
    hmm_behavior: Optional[Tensor]          # (batch, 16)
    event_sequences: Optional[Tensor]       # (batch, seq_len, feat_dim)
    multidisciplinary_features: Optional[Tensor]  # (batch, 24)
    sample_weights: Optional[Tensor]        # (batch,)
```

12. Appendix: Config File Structure

All system parameters are managed through 2 YAML files:

`pipeline.yaml`: Task definitions, model structure, training parameters, AWS infrastructure settings

- `tasks`: 18 tasks (name, type, loss, loss_weight, label_col)
- `model.ple`: num_layers, extraction_dim, expert_basket
- `model.adatt`: task_groups, intra/inter strength
- `model.logit_transfers`: 5 transfer edges
- `training`: batch_size, epochs, learning_rate, amp
- `aws`: instance_type, spot, budget_limit

`feature_groups.yaml`: 12 feature group definitions

- `group_type`: transform (existing column transformation) | generate (Generator invocation)
- `generator`: Reference to Pool's Generator name
- `generator_params`: input_filter (dtype, exclude_binary, min_nunique, etc.)
- `target_experts`: List of experts that receive this group's features
- `output_dim`: Output dimension

When switching domains, replacing only these 2 files configures an entirely different recommendation system without any code changes.