



Eidgenössische Technische Hochschule Zürich
Swiss Federal Institute of Technology Zurich

Lecture with Computer Exercises:
Modelling and Simulating Social Systems with MATLAB

Project Report

**Zombie Outbreak:
The Effect of Inter-State Collaboration
on the Survival of Humanity**

by

Matthieu G. MOTTET
Basile I. M. WICKY

Zurich
December 2012

Agreement for free-download

We hereby agree to make our source code for this project freely available for download from the web pages of the SOMS chair. Furthermore, we assure that all source code is written by ourselves and is not violating any copyright restrictions.

Matthieu G. MOTTET

Basile I. M. WICKY

Declaration of Originality

This sheet must be signed and enclosed with every piece of written work submitted at ETH.

I hereby declare that the written work I have submitted entitled

Zombie Outbreak: The Effect of Inter-State Collaboration on the Survival of Humanity

is original work which I alone have authored and which is written in my own words.*

Author(s)

Last name

Mottet

Basile

First name

Matthieu

Basile

Supervising lecturer

Last name

Baliotti

Donnay

First name

Stefano

Karsten

With the signature I declare that I have been informed regarding normal academic citation rules and that I have read and understood the information on 'Citation etiquette' (http://www.ethz.ch/students/exams/plagiarism_s_en.pdf). The citation conventions usual to the discipline in question here have been respected.

The above written work may be tested electronically for plagiarism.

Zurich, 14.12.2012

Place and date

Signature

Contents

1	Abstract	5
2	Individual contributions	5
3	Acknowledgments	5
4	Introduction and Motivations	6
5	Description of the Model	8
6	Implementation	10
6.1	The outbreak function	10
6.2	The update function	11
6.3	The sweep function	11
7	Simulation Results and Discussion	11
8	Summary and Outlook	12
9	References	12
10	Appendix	12
10.1	outbreak.m	12
10.2	update.m	18
10.3	plotResults.m	21
10.4	sweep.m	23

1 Abstract

This part needs updating once the rest of the report will be finished

Investigation of the application of the SIR model to a zombie outbreak has already been studied, raising the fear of dark days for humanity. However, we would like to deepen this investigation to a multi-state system to see how interactions between subpopulation may brighten the future of the human race. Moreover, we are interested in seeing to what extent the different paradigms of international politics, Realpolitik, Liberalism and Neoconservatism as defined by Daniel W. Drezner in Theories of International Politics and zombies may lead to different outcomes.

2 Individual contributions

M.G.M. and B.I.M.W. formulated the question in mathematical terms and discussed the implementation in MATLAB. M.G.M. wrote the code. M.G.M. and B.I.M.W. analysed and discussed the results and B.I.M.W. wrote the report.

3 Acknowledgments

We wish to thank Karsten Donnay and Stefano Balietti for their support in our work, fruitful discussions and an open mind to accept such a project. We would also like to thank the Chair of Sociology for the computational support provided with simulation time on the ETH cluster Brutus.

4 Introduction and Motivations

While models of international relationship have already been studied under different pressure components, the effect of a zombie outbreak on international collaboration and equilibrium is a question that has been underestimated and was never addressed to the best of our knowledge. It is remarkable that the effect of such an intense event has not been looked at, although the fear of zombies and the threat they represent is vivid for many of us as reflected by the importance of the zombie culture. Zombies, compared to other unnatural creatures such as vampires or aliens, have the very peculiar property not to be a minority inside the human civilization but rather to be in a way a part of it, just not quite as it was, i.e. zombified. Accordingly, zombies cause a much more deep-rooted fear as they not only threaten our lives but also our very sense of identity as it questions our notion of what humanity is. The psychological effect of such a non-standard threat as well as the repercussion on the behaviour of large population systems such as states should be far from trivial. Accordingly, we decided to simulate an inter-state collaboration models in order to see the outcome on a large scale of such an extreme event. While some people might question the validity of such a study (no zombie has been observed so far), we think that the applicability of such a reasoning could extend to a more probable large-scale epidemiological disaster or simply, give a line of reasoning to cope with what former U.S. Secretary of Defense Donald Rumsfeld referred as the "unknown unknowns" of international security. Zombies might not be real, but the threat and stress they could impose on current world politics is.

Epidemiological models have been widely studied to see the evolution dynamics and spread of a disease in a population [REFERENCE](#). They are based on a mass action model where interaction between susceptibles and infected together with an infection constant define the rate of infection. In the simplest case of such models, infected people can move to the immunized category also following a mass action law. These models have been shown to work in numerous cases and when corrections are added [REFERENCE](#), they can very well represent the evolution and spread of an infectious disease in a population. However, an epidemiological model of communicating population has not been tested to the best of our knowledge.

The origin of the word "zombie" as well as its initial meaning is quite remote from modern pop culture description. The word itself is said to have originated in the voodoo language in the Caribbean [1]. The original description is that of a ritual where the wizard of a tribe would start controlling another person. The fact that this person doesn't have a soul anymore and that it is no longer under the control of another human being, i.e. it has no longer a free-will, makes it a zombie [1].

Some studies suggest that those "zombified" members of the tribe were actually administered a cocktail of two natural drugs, one being a neurotoxin and the other a hallucinogenic drug [REFERENCE](#). In fact, the neurotoxin damages the brain and turns the person into a vegetative state.

Zombies in popular culture differ a lot from this original etymological definition. The canon of the zombie literature have had numerous description and hypothesis on how they may emerge in a human population, as well as what might characterize them. Since Romero's "night of the living dead" [REFERENCE](#), where zombies were said to have raised from some pseudo-magical event, the depiction and origin of zombies has considerably evolved. Recent zombie stories usually describe the genesis of flesh-eating monsters in an epidemiological sense, typically some sort of virus. Recent examples in the zombie culture are numerous and include (non-exhaustively) "Resident Evil", "28 Days Later". For simplicity, we will treat the emergence and zombification events as linked to an infectious disease of some sort, allowing the treatment of the problem with a modified epidemiological model. The big difference with a standard infectious disease where people usually get immunized, being transformed into a zombie is a on way process. The only way out is death and therefore, humans (susceptibles) can only decrease in our system.

It is interesting to notice that most zombie canon predict a very bleak outcome concerning the fate of humanity. Indeed, most movies/film describe an almost total disappearance of humans and the few survivors are rarely in a position that seem to be about to brighten up. While some might argue that the disappearance of humanity might not be such regretful event and might actually benefit our planet [REFERENCE](#), we decided to see if the usual outcome and fate of the human race in case of a zombie outbreak might differ from those classical scenarios, and if so, under which set of particular conditions.

Mathematical modeling of a zombie outbreak in a single population has previously been simulated [2] but showed very little hope for humans in the case of such an unlikely event. The primary reason for the annihilation of humans in all of the presented scenarios lies in their models. In contrast to "classical" epidemiological models where infected people can recover and although having changed population statues (going from susceptible to removed in a immunized sense of the term), they do not actually die. This is very different for the zombie scenario, where now "removed" is no longer synonym of "immunized", but is actually a very nice way of putting "dead". Accordingly, under the considerations of the model presented, humans can only day and this eventually happens in every case (some set of parameters can give reprieve the inevitable fate).

We rationalized that a more state-based description of the world population

might actually help in brightening the outcome of a zombie outbreak. In fact, the world is divided into states and nations that apply their own laws and restrictions in terms of immigration. If immigration applies to humans, it might as well apply to zombies. In such a case, one might envision that in a given state under the threat of a zombie epidemiological disaster, flux of incoming susceptibles to help them kill the zombies or on the other hand the emigration of the survivors to a non-infected state might lead various outcome. For example, it is imaginable to see the emergence of a zombie-only state where all the remaining survivor would have found shelter in another state. Or even better, that the help of susceptible from another state might help eradicate the new-coming zombie threat.

For those reason we decided to simulate a model of interacting sub-populations, each under an epidemiological-like treatment. The inner-state epidemiological model describes the emergences of zombies from a spreading disease point of view, while the populations fluxes between states would represent immigration/emigration of the populations under concern (humans and/or zombies).

5 Description of the Model

$$\Delta S_i^{micro} = -\alpha S_i Z_i - \gamma S_i Z_i = -(\alpha + \gamma) S_i Z_i \quad (1)$$

$$\Delta Z_i^{micro} = +\alpha S_i Z_i - \beta S_i Z_i = (\alpha - \beta) S_i Z_i \quad (2)$$

$$\Delta R_i^{micro} = +\beta S_i Z_i + \gamma S_i Z_i = (\beta + \gamma) S_i Z_i \quad (3)$$

$$\Delta S_i^{macro} = -\nu S_i \Delta S_i + \sum_{j \neq i} \nu S_j \Delta S_j \quad (4)$$

$$\Delta Z_i^{macro} = -\eta Z_i \tanh\left(\frac{Z_i}{S_i}\right) + \sum_{j \neq i} \eta Z_j \tanh\left(\frac{Z_j}{S_j}\right) \quad (5)$$

For each state (microstate), we define a SZR model that evaluates the evolution of the different populations under studies: susceptibles (S), zombies (Z) and removed (R). Epidemiological-like transfer of populations between the states (at the macrostate level) also occurs as defined above and models the refugees and zombie transfer across states. Those transfers are parameters dependants, which depend on the cost-hypothesis as defined by the Game-Theoretical paradigm implemented. The apparition of zombies in one state will start the game. Each state will then evolve on the domestic and international level. The domestic level will follow a standard SZR model, whereas the international level will introduce exchange in the population of susceptible and zombie between the states. These

on future action, for example the effectiveness of a military attack. This effect will be made as to converge after a certain time to model the wearing out of the psychological effect over time. The system will be implemented as a step-based update. This implies the ignorance of the actors (the states) of the action of the other actors. This rationalisation comes as the idea that the outbreak would occur over a short period of time, forcing for rapid decision-making and therefore not allow a reaction-based decision-making process.

6 Implementation

Research Methods

We would like to tackle this question by using a two-level model. Intra-state populations would be modelled by a standard SIR (Kermack-McKendrick) model or an evolution of it that might include quarantined populations and more evolved parameters. On the next level, the inter-state relationships would be modelled using Game-Theory under different cost-hypothesis related to the main paradigms of international relationships as previously defined. Other

The material necessary for defining our models of zombies and 'zombification' parameters will be extracted from the canon of the zombie popular culture such as World War Z (Brooks, 2006), 28 Days Later (Boyle, 2002), The Night of the Living Dead (Romero, 1968), Zombieland (Fleischer, 2009), Resident Evil (Capcom, 1996), etc.

The implementation in MatLab works on two levels: one taking care of the simulation of the epidemiological model, the other one taking care of the sweeping of the epidemiological parameters. We will discuss the key parts of the implementation as well as some of the interesting details that had to ensure the coherence of the model.

6.1 The outbreak function

The outbreak function is the wrapping function of the epidemiological model. It first takes care of the evaluation of the different parameters, initialize the different matrices used throughout the simulation, calls the update function of our model and is finally responsible of the validation of the new data. The validation of the data allows the simulation to keep on running. We implemented three exit policy in the simulation loop. The two obvious first occurred when either the susceptible or the zombie population reaches zero. The third one is triggered when the simulation's evolution becomes too slow, indicating a relative steady state. This last control is defined as follows:

$$\langle |\Delta S| \rangle < x \ \&\& \ \langle |\Delta Z| \rangle < x \quad (6)$$

The mean of the absolute variation of susceptibles and zombies on the last 100 steps is calculated and compared to a threshold $x = 0.1$. If the values are smaller than the threshold, we assume a steady state and exit the simulation. Furthermore, a maximum number of step can be defined (default: 10^8 steps) as last exit condition.

6.2 The update function

The update function takes care of the evolution of the model. It applies the different equations of the models and use safeguards to avoid unphysical results. The first constraint is applied during the computation of the flux exiting each states. Due to the structure of the program, negatives population values can arise. Though these populations will be extremely small ($> -10^{-4}$), resulting in small negative exiting flux, they will lead to negative entering flux in the other states. These flux being considered as positive into the next control procedure, negative values have to be avoided.

The second constraint is applied after the computation of all flux. There is the possibility for the negative flux (death, contamination, emigration) to be bigger than the population plus the positive flux (immigration). In such case, we apply a simple algorithm to avoid the negative population:

1. the negative flux are normalized and multiplied by the population plus the positive flux,
2. the incoming flux of the two other states are corrected to fit the values,
3. the validation is applied to the two other states.

This algorithm is applied until all discrepancy is removed. Note that negative values up to 10^{-4} are allowed and that during the first step of the algorithm, in the case where the sum of the population and incoming flux is negative, this value is zeroed. This method allows a relatively fast convergence of the values.

6.3 The sweep function

The sweep function acts as a wrapper function for the sweeping of each parameters between two values using defined steps. The results of each individual simulation is stored in a dedicated folder. It also assigns a id string to the sweep. This id allows to resume the sweep with the first non completed simulation, this feature was added due to the duration of the sweep with sufficient resolution.

7 Simulation Results and Discussion

Fundamental Questions

Investigation of the application of the SIR model to a zombie outbreak has already been studied, raising the fear of dark days for humanity. However, we would like to deepen this investigation to a multi-state system to see how interactions between subpopulation may brighten the future of the human race. Moreover, we are interested in seeing to what extent the different paradigms of international politics, Realpolitik, Liberalism and Neoconservatism as defined by Daniel W. Drezner in *Theories of International Politics* and zombies may lead to different outcomes.

Expected Results
As describe in Drezner’s book, we except different equilibrium outcomes depending on the paradigm under consideration. He postulates the possible appearance of zombie states under Realpolitik and Liberalism paradigms while Neoconservatism would not allow such an outcome.

8 Summary and Outlook

blablabla[3]

9 References

- [1] D.W. Drezner. *Theories of international politics and zombies*. Princeton University Press, 2011.
- [2] P. Munz, I. Hudea, J. Imad, and R.J. Smith. When zombies attack!: mathematical modelling of an outbreak of zombie infection. *Infectious Disease Modelling Research Progress. Hauppauge NY: Nova Science Publishers*, pages 133–150, 2009.
- [3] T.C. Reluga. An sis epidemiology game with two subpopulations. *Journal of Biological Dynamics*, 3(5):515–531, 2009.
- [4] P.G. Bennett. Modelling decisions in international relations: game theory and beyond. *Mershon International Studies Review*, pages 19–52, 1995.
- [5] D. Balcan and A. Vespignani. Phase transitions in contagion processes mediated by recurrent mobility patterns. *Nature physics*, 7(7):581–586, 2011.
- [6] S. Funk, M. Salathé, and V.A.A. Jansen. Modelling the influence of human behaviour on the spread of infectious diseases: a review. *Journal of The Royal Society Interface*, 7(50):1247–1256, 2010.
- [7] T.C. Reluga. Game theory of social distancing in response to an epidemic. *PLoS computational biology*, 6(5):e1000793, 2010.

10 Appendix

10.1 outbreak.m

```
1 function dump = outbreak( varargin )
2
3 %
4 % OUTBREAK runs the simulation of a zombie outbreak in a 3 states
5 % system.
6 %
7 % DUMP = OUTBREAK( ARGS )
8 %     ARGS are name-value pairs. Possible arguments are :
9 %     params: structure containing rate parameters (alpha, beta,
10 %            gamma, eta, nu) as arrays (3x1 for alpha, beta and
11 %            gamma or 3x2 for eta and nu).
12 %     paramfile: path to a mat-file storing the parameter
13 %                structure.
14 %     zombies: 3x1 array containing the number of initial zombie
15 %              per state (default: 0, 0, 0).
16 %     population: 3x1 array containing the number of initial
17 %                 susceptible population per state (default: 1000,
18 %                 1000, 1000).
19 %     steps: maximal number of steps for the simulation (default:
20 %            1e8).
21 %     silent: level of output for the simulation:
22 %              0 = all outputs
23 %              1 = all outputs excepts graphs
24 %              2 = no outputs
25 %     dslength: size of the sliding window used for the
26 %               calculation of the mean of dS (used as weight
27 %               factor for the inter-state susceptible transfer).
28 %
29 %     DUMP is a structure containing the following fields:
30 %     S: 4xn array containing the evolution of the susceptible
31 %        population.
32 %     dS: 4xn array containing the evolution of the susceptible
33 %         population's variation.
34 %     Z: 4xn array containing the evolution of the zombie
35 %        population.
36 %     dZ: 4xn array containing the evolution of the zombie
37 %         population's variation.
38 %     R: 4xn array containing the evolution of the removed
39 %        population.
40 %     dR: 4xn array containing the evolution of the removed
41 %         population's variation.
42 %     step: number of steps performed.
43 %     alpha, beta, gamma, eta, nu: transfer rate parameters.
44 %     time: simulation time.
45 %
46
47
```

```

48 %% Variable initialization
49 silent = 0;
50 dslength = 10;
51 maxSteps = 1e8;
52 rates = struct( 'alpha', [ 0.00095 ; 0.00095 ; 0.00095 ], 'beta', ...
    [0.00025 ; 0.00025 ; 0.00025 ], 'gamma', [ 0.00005 ; 0.00005 ; ...
    0.00005 ], 'mu', [ 0.00000005 , 0.00000005 ; 0.00000005 , ...
    0.00000005 ; 0.00000005 , 0.00000005 ], 'nu', [ 0.00000005 , ...
    0.00000005 ; 0.00000005 , 0.00000005 ; 0.00000005 , 0.00000005 ], ...
    'eta', [ 0.00000005 , 0.00000005 ; 0.00000005 , 0.00000005 ; ...
    0.00000005 , 0.00000005 ] );
53 zombies = [ 0 ; 0 ; 0 ; 0 ];
54 populations = [ 1e3 ; 1e3 ; 1e3 ; 3e3 ];
55
56 % Structure storing populations and populations variation
57 states = struct( 'pop', zeros( 4, 3 ), 'dpop', zeros( 4, 3 ) );
58
59 % See exit condition at the end of the loop.
60 exitThreshold = 1e-1;
61
62 p = [ 'alpha' ; 'beta ' ; 'gamma' ; 'eta ' ; 'mu ' ; 'nu ' ];
63 reverseStr = '';
64
65
66 %% Argument parsing
67 % All argument are optional.
68 for i = 1:2:nargin
69
70     % Argument are passed in name-value pairs. If i + 1 does not exist,
71     % then the value is absent and the program stops.
72     if( nargin < i + 1 )
73
74         error( [ 'Missing argument for parameter "' varargin{ i } ...
75             '","' ] );
76     end
77
78     switch varargin{ i }
79
80         % params excepts a structure containing the rates values for the
81         % epidemiologic model. Not all fields have to be present. If a
82         % field is missing, the default value is used.
83         case 'params'
84             for j = 1:6
85
86                 if isfield( varargin{ i + 1 }, strtrim( p( j, : ) ) )
87
88                     rates.( strtrim( p( j, : ) ) ) = varargin{ i + 1 ...
89                         }.( strtrim( p( j, : ) ) );
90
91                     end
92
93             end
94
95         % paramfile excepts the path to a mat-file containing a
96         % parameter structure (refer to parms).

```

```

93     case 'paramfile'
94         pfile = load( varargin{ i + 1 }, '-mat' );
95         for j = 1:6
96
97             if isfield( pfile{ i + 1 }, strtrim( p( j, : ) ) )
98
99                 rates.( strtrim( p( j ) ) ) = pfile{ i + 1 }. ( ...
100                     strtrim( p( j ) ) );
101             end
102         end
103
104         % zombies excepts an array containing the initial zombie
105         % populations in each state.
106         case 'zombies'
107             temp = varargin{ i + 1 };
108             for j = 1:3
109
110                 zombies( j ) = temp( j );
111                 zombies( 4 ) = zombies( 4 ) + temp( j );
112             end
113
114         % zombies excepts an array containing the initial susceptible
115         % population in each state.
116         case 'population'
117             temp = varargin{ i + 1 };
118             populations( 4 ) = 0;
119             for j = 1:3
120
121                 populations( j ) = temp( j );
122                 populations( 4 ) = populations( 4 ) + populations( j );
123             end
124
125         % steps excepts the maximum number of steps allowed for the
126         % simulation.
127         case 'steps'
128             maxSteps = varargin{ i + 1 };
129
130         % silent except a int defining the output type :
131         % 2 : No output
132         % 1 : All outputs but the graphs
133         % 0 : Normal output
134         case 'silent'
135             silent = varargin{ i + 1 };
136
137         % dslength excepts the size of the sliding window used for the
138         % calculation of the mean of dS (used as weight factor for the
139         % inter-state susceptible transfer).
140         case 'dslength'
141             dslength = varargin{ i + 1 };
142
143         otherwise
144             error( [ 'Unknown parameter "', varargin{ i }, "'. ' ] );
145     end

```

```

145     end
146
147
148
149     %% Initialization of simulation
150
151     % Setting the initial populations.
152     states.pop( :, 1 ) = populations;
153     states.pop( :, 2 ) = zombies;
154
155     % Initialization of the sliding window for inter-state population
156     % transfer.
157     dshistory = zeros( 3, dslength );
158
159     % Setting up the initial dump structure. Large matrices are used to
160     % avoid the need of dynamic memory allocation to improve code
161     % efficiency.
162     d = zeros( 4, max( 200, .0001 * maxSteps ) );
163     dump = struct( 'S', d, 'dS', d, 'Z', d, 'dZ', d, 'R', d, 'dR', d, ...
        'step', 1, 'alpha', mean( rates.alpha ), 'beta', mean( rates.beta ...
        ), 'gamma', mean( rates.gamma ), 'eta', mean( mean( rates.eta ) ...
        ), 'nu', mean( mean( rates.nu ) ), 'time', 0 );
164     dump.S( :, 1 ) = states.pop( 1:4, 1 );
165     dump.Z( :, 1 ) = states.pop( 1:4, 2 );
166     dump.R( :, 1 ) = states.pop( 1:4, 3 );
167
168     % Initialize timer.
169     tic;
170
171     %% Update loop.
172     for i = 1:maxSteps
173
174         % Output of step # and current population count.
175         if silent < 2
176
177             msg = sprintf('Processing step %d... Human population %d, ...
                Zombie population %d\n', i, dump.S( 4, dump.step ), ...
                dump.Z( 4, dump.step ) );
178             fprintf([ reverseStr, msg]);
179
180             reverseStr = repmat(sprintf('\b'), 1, length(msg));
181         end
182
183         % Update function (see update.m for details).
184         [ states, rates, dshistory ] = update( states, rates, dshistory );
185
186         % Dumping of the latest state of the simulation.
187         % Update of the step number.
188         dump.step = i + 1;
189
190         % Dumping of the various population and population variation.
191         dump.S( :, dump.step ) = states.pop( :, 1 );
192         dump.dS( :, dump.step ) = states.dpop( :, 1 );

```



```

193     dump.Z( :, dump.step ) = states.pop( :, 2 );
194     dump.dZ( :, dump.step ) = states.dpop( :, 2 );
195     dump.R( :, dump.step ) = states.pop( :, 3 );
196     dump.dR( :, dump.step ) = states.dpop( :, 3 );
197
198     % Stops simulation if S is equal to 0.
199     if states.pop( 4, 1 ) == 0
200
201         if silent < 2
202
203             disp( ' ' );
204             disp( 'End of the human race.' );
205         end
206         break;
207     end
208
209     % Stops simulation if Z is equal to 0.
210     if states.pop( 4, 2 ) == 0
211
212         if silent < 2
213
214             disp( ' ' );
215             disp( 'Humanity survived.' );
216         end
217         break;
218     end
219
220     % Stops simulation if the average fluctuation of both dS and dZ
221     % over a sliding window is lower than the threshold (simulation
222     % reached equilibrium in the limit of our time frame).
223     if i > 100 && mean( abs( dump.dS( 4, ( i - 100 ):i ) ) ) < ...
        exitThreshold && mean( abs( dump.dZ( 4, ( i - 100 ):i ) ) ) < ...
        exitThreshold
224
225
226         if silent < 2
227
228             disp( ' ' );
229             disp( 'Equilibrium reached.' );
230         end
231         break;
232     end
233 end
234
235 % Store simulation time.
236 dump.time = toc;
237
238 % Resizing of the dump matrices before plotting.
239 dump.S = dump.S( :, 1:dump.step );
240 dump.dS = dump.dS( :, 1:dump.step );
241 dump.Z = dump.Z( :, 1:dump.step );
242 dump.dZ = dump.dZ( :, 1:dump.step );
243 dump.R = dump.R( :, 1:dump.step );

```

```

244     dump.dR = dump.dR( :, 1:dump.step );
245
246     if ~silent
247
248         % Plot the simulation history (see plotResults.m for details).
249         plotResults( dump );
250     end
251 end

```

10.2 update.m

```

1     function [ states, rates, dshistory ] = update( states, rates, ...
2         dshistory )
3
4     %
5     % UPDATE compute the population evolution for one step of the
6     % epidemiological model.
7     %
8     % [ STATES, RATES, DSHISTORY, DUMP ] = UPDATE( STATES, RATES, ...
9     % DSHISTORY, DUMP )
10    %
11    % STATES is the structure storing the populations and population
12    % variations as defined in the OUTBREAK function.
13    % RATES is the structure containing the epidemiological transfer
14    % rates as defined in the OUTBREAK function.
15    % DSHISTORY is the array containing the sliding window for
16    % inter-state susceptible transfer.
17    %
18    %% Initialization of parameters :
19
20    s = states.pop( 1:3, 1 );
21    z = states.pop( 1:3, 2 );
22
23    alpha = rates.alpha;
24    beta = rates.beta;
25    gamma = rates.gamma;
26    nu = rates.nu;
27    eta = rates.eta;
28
29    % Permutation matrix used to set the input inter-state flux from the
30    % inter-state output flux to avoid redundant calculations. See flux
31    % update.
32    permutation = [ 0 0 1 ; 1 0 0 ; 0 1 0 ];
33
34    % Matrix containing the coordinates of the input inter-state flux from
35    % each state (line) to the other two (block of two colons). See flux
36    % correction.
37    iFluxCoor = [ 2 2 3 1 ; 3 2 1 1 ; 1 2 2 1 ];

```

```

37 %% Update of the susceptible population.
38
39 % Depletion of the susceptible population goes according to :
40 %
41 %   S  -> Z  = - alpha * s * z
42 %   S  -> R  = - gamma * s * z
43 %   S1 -> S2 = nu * dSmean
44 %   S1 -> S3 = nu * dSmean
45 %
46 % Immigration is the only source of susceptible population.
47 %
48 % dS is a 3x6 matrix containing for each state :
49 %
50 %   Row 1 : n( S  -> Z  )
51 %   Row 2 : n( S  -> R  )
52 %   Row 3 : n( S1 -> S2 ) | n( S2 -> S3 ) | n( S3 -> S1 )
53 %   Row 4 : n( S1 -> S3 ) | n( S2 -> S1 ) | n( S3 -> S2 )
54 %   Row 5 : n( S2 -> S1 ) | n( S3 -> S2 ) | n( S1 -> S3 )
55 %   Row 6 : n( S3 -> S1 ) | n( S1 -> S2 ) | n( S2 -> S3 )
56 %
57 % The sum of each line gives the population variation for the state.
58
59 % Mean variation of the susceptible in the sliding window.
60 dsmean = min( mean( dshistory, 2 ), 0 );
61
62 dS = zeros( 3, 6 );
63 dS( :, 1 ) = min( - alpha .* s .* z, 0 );
64 dS( :, 2 ) = min( - gamma .* s .* z, 0 );
65 dS( :, 3 ) = nu( :, 1 ) .* dsmean;
66 dS( :, 4 ) = nu( :, 2 ) .* dsmean;
67 dS( :, 5 ) = - permutation * permutation * dS( :, 4 );
68 dS( :, 6 ) = - permutation * dS( :, 3 );
69
70
71 % There is the possibility that any of the |-dSi| is larger than the
72 % actual population in the state (negative population fluctuation larger
73 % than the actual population). If so, a correction is applied to
74 % avoid negative population.
75 % As long as any state falls into this category:
76 while sum( sum( dS( :, 1:4 ), 2 ) + s + sum( dS( :, 5:6 ), 2 ) < ...
77         -1e-6 )
78     for i = 1:3
79
80         % Correct the state that falls into this category:
81         if( sum( dS( i, 1:4 ), 2 ) + ( s( i ) + sum( dS( i, 5:6 ), 2 ...
82             ) ) < -1e-6 )
83
84             % Population is considered equal to the sum of previous
85             % population and the inter-state input transfer. The
86             % negative contributions to the dS are reduced so that it
87             % equals this population.
88             dS( i, 1:4 ) = dS( i, 1:4 ) / abs( sum( dS( i, 1:4 ) ) ) ...

```

```

88         * max( sum( dS( i, 5:6 ) ) + s( i ), 0 );
89
90         % The effect of the correction on the output flux is
91         % applied to the other state input flux.
92         dS( iFluxCoor( i, 1 ), 4 + iFluxCoor( i, 2 ) ) = - dS( i, ...
93             3 );
94         dS( iFluxCoor( i, 3 ), 4 + iFluxCoor( i, 4 ) ) = - dS( i, ...
95             4 );
96     end
97 end
98
99 % Note that the output flux can only be lower than the original flux.
100 % Therefore, the input flux for the two other states can only
101 % be smaller than before the correction. Accordingly, the
102 % process has to be repeated until all states have a population
103 % differential such that it doesn't lead to a negative population.
104 end
105
106 %% Update of the zombie population.
107
108 % Depletion of the zombie populations goes according to :
109 %
110 % S -> Z = alpha * s * z
111 % Z -> R = - beta * s * z
112 % Z1 -> Z2 = - eta * z * tanh( z / s )
113 % Z1 -> Z3 = - eta * z * tanh( z / s )
114 %
115 % Conversion from susceptible and "immigration" are the two sources of
116 % zombies.
117 %
118 % dZ is a 3x6 matrix containing for each states :
119 %
120 % Row 1 : n( S -> Z )
121 % Row 2 : n( Z -> R )
122 % Row 3 : n( Z1 -> Z2 ) | n( Z2 -> Z3 ) | n( Z3 -> Z1 )
123 % Row 4 : n( Z1 -> Z3 ) | n( Z2 -> Z1 ) | n( Z3 -> Z2 )
124 % Row 5 : n( Z2 -> Z1 ) | n( Z3 -> Z2 ) | n( Z1 -> Z3 )
125 % Row 6 : n( Z3 -> Z1 ) | n( Z1 -> Z2 ) | n( Z2 -> Z3 )
126 %
127
128 dZ = zeros( 3, 6 );
129 dZ( :, 1 ) = max( - dS( :, 1 ), 0 );
130 dZ( :, 2 ) = min( - beta .* s .* z, 0 );
131 dZ( :, 3 ) = min( - eta( :, 1 ) .* z .* tanh( z ./ s ), 0 );
132 dZ( :, 4 ) = min( - eta( :, 2 ) .* z .* tanh( z ./ s ), 0 );
133 dZ( :, 5 ) = - permutation * permutation * dZ( :, 4 );
134 dZ( :, 6 ) = - permutation * dZ( :, 3 );
135
136 % The same control procedure as for the susceptible population is
137 % applied to avoid negative population of zombies. See susceptible
138 % correction for details on the procedure.
139 while sum( ( dZ( :, 1 ) + sum( dZ( :, 5:6 ), 2 ) + z ) + sum( dZ( :, ...
140     2:4 ), 2 ) < - 1e-6 )

```

```

137
138     for i = 1:3
139
140         if( ( dZ( i, 1 ) + sum( dZ( i, 5:6 ), 2 ) + z( i ) ) + sum( ...
141             dZ( i, 2:4 ) ) < - 1e-6 )
142
143             dZ( i, 2:4 ) = dZ( i, 2:4 ) * max( sum( dZ( i, 5:6 ) ) + ...
144                 dZ( i, 1 ) + z( i ), 0 ) / abs( sum( dZ( i, 2:4 ) ) );
145
146             dZ( iFluxCoor( i, 1 ), 4 + iFluxCoor( i, 2 ) ) = - dZ( i, ...
147                 3 );
148             dZ( iFluxCoor( i, 3 ), 4 + iFluxCoor( i, 4 ) ) = - dZ( i, ...
149                 4 );
150         end
151     end
152 end
153
154 %% Update of the removed population
155
156 % Variation in the removed population is strictly positive and comes
157 % from both the susceptible and zombie population:
158 %
159 %   S -> R = alpha * s * z
160 %   Z -> R = beta * s * z
161 %
162 % The value obtained for dS and dZ are used:
163
164 dR = - [ dS( :, 2 ), dZ( :, 2 ) ];
165
166 %% Update each population
167
168 % Compilation of the populations variations
169 states.dpop( 1:3, : ) = [ sum( dS, 2 ), sum( dZ, 2 ), sum( dR, 2 ) ];
170
171 % Update of the sliding window matrix for the susceptible.
172 [ ~, dsSize ] = size( dshistory );
173 dshistory( :, 2:dsSize ) = dshistory( :, 1:( dsSize - 1 ) );
174 dshistory( :, 1 ) = states.dpop( 1:3, 1 );
175
176 % Update of the current populations
177 states.pop( 1:3, : ) = states.pop( 1:3, : ) + states.dpop( 1:3, : );
178
179 % Update of the total populations
180 states.pop( 4, : ) = sum( states.pop( 1:3, : ) );
181 states.dpop( 4, : ) = sum( states.dpop( 1:3, : ) );
182 end

```

10.3 plotResults.m

```

1 function plotResults( dump )

```

```

2
3 % PLOTRESULTS plots the populations' evolution during the simulation. It
4 % plots the different populations (S, Z, R) for each state as well as
5 % the population variation. Furthermore the global populations and
6 % population variations are also displayed.
7 %
8 % PLOTRESULTS( DUMP )
9 % DUMP is the dumping structure as defined in the OUTBREAK function.
10 %
11
12 x = 0:( length( dump.S ) - 1 );
13
14 % For each of the three states, plot the populations and
15 % populations' variations.
16 for i = 1:3
17
18     subplot( 4, 4, ( i * 4 - 3 ):( i * 4 - 2 ) );
19     plot( x, dump.S( i, : ), 'g', x, dump.Z( i, : ), 'r', x, dump.R( ...
20         i, : ), 'k' );
21     ylim( [ 0 dump.S( 4 ) ] );
22     xlabel( 'Step' );
23     ylabel( 'Population' );
24     title( [ 'State ', int2str( i ) ], 'fontweight', 'b' );
25     if i == 1
26
27         legend( 'Susceptibles', 'Zombies', 'Removed' );
28     end
29
30     subplot( 4, 4, ( i * 4 - 1 ):( i * 4 ) );
31     plot( x, dump.dS( i, : ), 'g', x, dump.dZ( i, : ), 'r', x, ...
32         dump.dR( i, : ), 'k' );
33     xlabel( 'Step' );
34     ylabel( 'Population Variation' );
35     title( [ 'State ', int2str( i ) ], 'fontweight', 'b' );
36
37 end
38
39 % Plot the total populations and total populations' variations.
40 subplot( 4, 4, 13:14 );
41 plot( x, dump.S( 4, : ), 'g', x, dump.Z( 4, : ), 'r', x, dump.R( 4, : ...
42     ), 'k' );
43 ylim( [ 0 dump.S( 4 ) ] );
44 xlabel( 'Step' );
45 ylabel( 'Population' );
46 title( 'World population', 'fontweight', 'b' );
47
48 subplot( 4, 4, 15:16 );
49 plot( x, dump.dS( 4, : ), 'g', x, dump.dZ( 4, : ), 'r', x, dump.dR( ...
50     4, : ), 'k' );
51 xlabel( 'Step' );
52 ylabel( 'Population Variation' );
53 title( 'World population', 'fontweight', 'b' );

```

```

51
52 end

```

10.4 sweep.m

```

1 function params = sweep( params )
2
3 %
4 % SWEEP allows to run multiple simulation sequentially varying the
5 % parameters in a defined range with defined steps.
6 %
7 % PARAMS = SWEEP( PARAMS )
8 %     PARAMS is a structure storing for each parameter alpha, beta,
9 %     gamma, eta and nu a 1x3 matrix with the minimal value, the
10 %     step and the maximal value for the parameter.
11 %     The return value also contains the ID of the sweep as well
12 %     as the number of simulations done.
13 %
14 % PARAMS = SWEEP( ID )
15 %     ID is the ID string of a previous sweep. The sweep will start
16 %     over where the sweep stopped the last time.
17 %
18
19
20 %% Parsing of the argument
21 switch class( params )
22
23     case 'struct'
24         % If the parameter set has never been employed, the restart
25         % fields are created.
26         if length( params.alpha ) == 3
27
28             params.alpha( 4 ) = params.alpha( 1 );
29             params.beta( 4 ) = params.beta( 1 );
30             params.gamma( 4 ) = params.gamma( 1 );
31             params.eta( 4 ) = params.eta( 1 );
32             params.nu( 4 ) = params.nu( 1 );
33
34         else
35             if ~isfield( params, 'step' )
36
37                 params.alpha( 4 ) = params.alpha( 1 );
38                 params.beta( 4 ) = params.beta( 1 );
39                 params.gamma( 4 ) = params.gamma( 1 );
40                 params.eta( 4 ) = params.eta( 1 );
41                 params.nu( 4 ) = params.nu( 1 );
42             end
43         end
44

```

```

45         % Initialization of the number of simulation ran
46         if ~isfield( params, 'step' )
47
48             params.step = 1;
49         end
50
51         % If an ID is assigned, the restart file is loaded, otherwise,
52         % an ID is created as well as a folder for the simulation
53         % results.
54         if isfield( params, 'id' )
55
56             if exist( [ params.id '.restart' ], 'file' )
57
58                 params = load( [ id '.restart' ], '-mat' );
59             end
60         else
61
62             params.id = num2hex( ceil( 1e20*rand ) );
63             mkdir( [ '../results/' params.id ] );
64         end
65
66         case 'char'
67             % If an ID is provided, the restart file is loaded.
68             params = load( [ params '.restart' ], '-mat' );
69     end
70
71     %% Display of the simulation details
72     disp( [ 'Id : ' params.id '.' ] );
73     disp( 'Use the id as parameter to resume the sweep anytime.' );
74     disp( '_____' );
75     disp( params );
76     disp( '_____' );
77
78     %% Variables initialization
79     cParams = struct( 'alpha', zeros( 3, 1 ), 'beta', zeros( 3, 1 ), ...
80         'gamma', zeros( 3, 1 ), 'eta', zeros( 3, 2 ), 'nu', zeros( 3, 2 ) );
81     output = struct( 'S', 0, 'Z', 0, 'R', 0, 'alpha', 0, 'beta', 0, ...
82         'gamma', 0, 'eta', 0, 'nu', 0, 'e', 0, 'step', 0 );
83     reverseStr = '';
84     step = 1;
85
86     %% Parameter sweeping
87     for nu = params.nu( 1 ):params.nu( 2 ):params.nu( 3 )
88
89         for eta = params.eta( 1 ):params.eta( 2 ):params.eta( 3 )
90
91             for gamma = params.gamma( 1 ):params.gamma( 2 ):params.gamma( ...
92                 3 )
93
94                 for beta = params.beta( 1 ):params.beta( 2 ):params.beta( ...
95                     3 )

```



```

94         for alpha = params.alpha( 1 ):params.alpha( 2 ...
95             ):params.alpha( 3 )
96
97             % If the current step number is larger than the
98             % step number in the parameter file, the simulation
99             % has already be done and can be skipped.
100             if step > params.step
101
102                 % Update of the current process status.
103                 msg = sprintf('Step %d.\nAlpha = %f, Beta = ...
104                     %f,\nGamma = %f, Eta = %f, Nu = %f.', ...
105                     step, alpha, beta, gamma, eta, nu );
106                 fprintf([ reverseStr, msg]);
107                 reverseStr = repmat(sprintf('\b'), 1, ...
108                     length(msg));
109
110                 % Preparation of the simulation parameters
111                 cParams.alpha = alpha * ones( 3, 1 );
112                 cParams.beta = beta * ones( 3, 1 );
113                 cParams.gamma = gamma * ones( 3, 1 );
114                 cParams.eta = eta * ones( 3, 2 );
115                 cParams.nu = nu * ones(3, 2 );
116
117                 % Simulation
118                 dump = outbreak( 'silent', 2, 'params', ...
119                     cParams, 'zombies', [ 1 0 0 ] );
120
121                 % Preparation of the output structure
122                 output.S = dump.S;
123                 output.R = dump.R;
124                 output.Z = dump.Z;
125                 output.step = dump.step;
126                 output.alpha = alpha;
127                 output.beta = beta;
128                 output.gamma = gamma;
129                 output.eta = eta;
130                 output.nu = nu;
131
132                 % Saving of the results of the simulation
133                 save( [ '../results/' params.id '/output.' ...
134                     int2str( params.step ) '.mat' ], ...
135                     '-struct', 'output' );
136
137                 % Update of the parameter structure and saving
138                 % of the restart file.
139                 params.step = params.step + 1;
140                 params.alpha( 4 ) = alpha + params.alpha( 2 );
141                 save( [ params.id '.restart' ], '-struct', ...
142                     'params' );
143             end
144
145             % Update of the current step.
146             step = step + 1;

```

```

139         end
140
141         % Parameters update
142         params.alpha( 4 ) = params.alpha( 1 );
143
144         params.beta( 4 ) = beta + params.beta( 2 );
145     end
146
147     params.beta( 4 ) = params.beta( 1 );
148
149     params.gamma( 4 ) = gamma + params.gamma( 2 );
150 end
151
152     params.gamma( 4 ) = params.gamma( 1 );
153
154     params.eta( 4 ) = eta + params.eta( 2 );
155 end
156
157     params.eta( 4 ) = params.eta( 1 );
158
159     params.nu( 4 ) = nu + params.nu( 2 );
160 end
161 end

```