Traffic Sign Classifier (TSC) Project Submission Writeup Report For the Udacity Self-Driving Car Program – Term 1

Submitted by:

Stewart Teaze

May 26, 2017

Project Goals

The goals / steps of this project are:

- Load the provided German Traffic Signs data set
- Explore, summarize and visualize the data set
- Design, train and test a model architecture
- Use the model to make predictions on new images
- Analyze the softmax probabilities of the new images
- Summarize the results with a written report

Rubric Points

The following sections of this document relate to each of the project's rubric points (project requirements), and provide details of how each requirement was addressed in the project implementation.

Writeup

1. This file is the Writeup itself, and is provided in .pdf format. The project code can be found at: https://github.com/blunderbuss9/CarND-TSC-StewartTeaze.html

Data Set Summary & Exploration

1. Following are basic summary statistics of the provided German Traffic Signs data set:

- The size of (original) training set is 34799
- The size of the validation set is 8699 (1/4 * 34799)
- The size of test set is 26100 (3/4 * 34799)
- The shape of a traffic sign image is (32,32,3)
- The number of unique classes/labels in the data set is 43

2. Exploratory visualization of the dataset.

Table 1 below provides an exploratory visualization of the provided German Traffic Signs data set, and includes additional summary statistics. In the project code itself, this analysis and visualization was performed and rendered using python, with the numpy and matplotlib libraries. The table provides one representative image from the training set file, corresponding to each Traffic Sign type that was found in the training set file.

The title text above each image is X:Y, where X is the Traffic Sign Class label/type, & Y is the number of occurrences of that label/type that were encountered in the training set file:



TABLE 1

Design and Test of the Model Architecture

1. Image Data Preprocessing.

The images that were provided in the German Traffic Sign dataset file train.p (a subset of the German Traffic Sign Recognition Benchmark dataset of more than 50,000 traffic sign images [Stallkamp][AnsBach]), are read in, and then split into two parts: 75% training data, and 25% validation data; by doing this, validation set accuracy measurements of between 0.944 and 0.961 were achieved, during various test runs against the created validation set - all of these measurements were above the 0.93 minimum requirement for a successful project submission, and a significant increase over the roughly .88 accuracy achieved during initial runs made with the provided validation dataset (whose size was only roughly 15% of the training set).

The training data is shuffled randomly for each epoch processed during each run – it is important to randomly shuffle the training data, otherwise the order of the data could have a huge effect on how well the network model trains.

1. Model Architecture Description.

The machine learning network model architecture implementation is a multi-layer (Deep Learning) Convolutional Neural Network (CNN), that is based on and adapted from the LeNet-5 5-Layer architecture [LeCun98]. The following table provides the details for the stages (steps/techniques) implemented, within each layer of this project's machine learning network model's architecture implementation:

		STAGES / LAYER		
LAYER 1	Convolutional Stride: 1x1 Padding: VALID Input: 32x32x3(RGB) Output: 28x28x6	Activation Type: ReLU	Max Pooling Stride: 2x2 Padding: VALID Input: 28x28x6 Output: 14x14x6	
LAYER 2	Convolutional Stride: 1x1 Padding: VALID Input: 14x14x6 Output: 10x10x16	Activation Type: ReLU	Max Pooling Stride: 2x2 Padding: VALID Input: 10x10x16 Output: 5x5x16	Flatten Input: 5x5x16 Output: 400
LAYER 3	Fully Connected Input: 400 Output: 120	Activation Type: ReLU		
LAYER 4	Fully Connected Input: 120 Output: 84	Activation Type: ReLU		
LAYER 5	Fully Connected Input: 84 Output: 43 (Logits)			

2. Model Training Description

The last output (logits), described in the table above, is then softmax cross-entropy one-hot encoded, for later use by the AdamOptimizer loss minimization functional step in each epoch pass in the training pipeline.

A batch size of 128 per epoch was used; and the training pipeline used 10 epochs (passes). The learning rate hyperparameter was set to .001. Mean and standard deviation parameters within all layers of the model were set to 0 and .1, respectively.

3. Solution Approach used for Achieving Validation Accuracy > 0.93

The well-known LeNet-5 5-Layer CNN architecture was used, as it has been shown to yield good results on image recognition type problems, and has been well-studied, with numerous support resources readily available on The Internet; for example, the LeNet and CNN approaches are the core of the Stanford Computer Vision course CS231n, which has generated huge interest throughout the Artificial Intelligence machine learning community, and whose resources are accessible via The Internet to those interested [CS231n17].

The main approach used, to achieve validation accuracy was to split the provided German Traffic Sign dataset file train.p, into two parts: 75% training data, and 25% validation data; by doing this, validation set accuracy measurements of between 0.943 and 0.961 were achieved, during numerous test runs against this increased-size validation set. These measurements were a significant improvement over the roughly .88 accuracy achieved during initial runs I had made with the provided validation dataset file valid.p (whose size was only roughly 15% of the training set). This approach was used, because numerous research results have shown the validation dataset should be a "substantial fraction" of the training dataset size, to achieve optimal results... "In most cases a single validation set of respectable size substantially simplifies the code base, without the need for cross-validation with multiple folds. You'll hear people say they "cross-validated" a parameter, but many times it is assumed that they still only used a single validation set" [CS231n17].

My final model results were:

- validation set accuracies of between .0943-.0961
- test set accuracy of .866

Model Test Results using Web-based Images

Following are five sample German traffic signs that I found on the web, and used for the test evaluation run.

1. Sample Traffic Sign Images

a. This image, of an 100 km/h speed limit sign, found at http://media.istockphoto.com/vectors/german-road-sign-speed-limit-100-kmh-vector-id472360055 was cropped to 512x512 pixels using MS Paint; while it has some watermark artifacts, it can be seen that the effects on classification should be minimal, once the image is re-sized to 32x32 pixels in the project code during the evaluation run (NOTE: for comparison purposes, the 32x32 re-sized images, produced and output during the project code evaluation section run, are included next to each of the original-sized images presented here).





b. This image, of a Traffic Signal Ahead sign, found at

https://thumb10.shutterstock.com/display_pic_with_logo/2535709/4562684 47/stock-vector-germany-traffic-signals-sign-456268447.jpg

was originally cropped to 492x488 pixels; while there are some watermark overlay artifacts, it can be seen that the effects on classification should be minimal, once the image is re-sized to 32x32 pixels in the project code during the evaluation run (see 2^{nd} image below-right).



c. This image, of a Priority Road sign, found at

https://www.shutterstock.com/image-photo/german-priority-road-sign-yellow-white-595318625?src=FQkuNDJD74L7Ee1vpiMlvQ-1-29

was originally cropped at 427x390 pixels; while there are some watermark artifacts, it can be seen that the effects on classification should be minimal, once the image is re-sized to 32x32 pixels in the project code during the evaluation run (see 2^{nd} image below-right).





d. This image, of a German Yield Sign, found at

http://www.gettyimages.com/detail/illustration/yield-german-road-sign-royaltyfree-illustration/176430515

was originally cropped to 392x335 pixels; while not square(leading to some aspect ratio issues when re-sized to 32x32), and while there are some watermark artifacts, it can be seen that the effects of these issues on classification should be minimal, once the image is re-sized to 32x32 pixels in the project code during the evaluation run (see 2nd image below).





e. This image, of a German Warning Sign, found at

http://www.gettyimages.com/detail/illustration/dangerous-area-risk-of-ice-german-warning-royalty-free-illustration/472360059

was originally cropped at 570x491 pixels; there are some watermark artifacts, but it can be seen that the effects on classification of these artifacts should be minimal, once the image is re-sized to 32x32 pixels in the project code during the evaluation run(see 2^{nd} image below-right).



2. Trained Model's Prediction Accuracy on New Dataset.

Here are the results of the predictions on the 5 web sample images:

Image	Prediction
100 km/h	80 km/h
Signal Ahead	Signal Ahead
Priority Road	Priority Road
Yield	Yield
Danger	Signal Ahead

The trained model was able to correctly guess 3 of the 5 traffic signs, which gives an accuracy of 60%. This compares to the accuracy of 86% against the test set of images.

3. Top 5 Softmax Probabilities for Each of the 5 Sample Images.

The code for making predictions for each of the 5 sample images, with the final version of this project submission's model, is located in the 12^{th} (last) code cell of the submitted Jupyter notebook.

For the first image, the model is somewhat sure that this is an 80 km/h sign (probability of 0.094), however, the image is a 100 km/h sign, which was the model's 4^{th} prediction in this case. The top five soft max probabilities were:

Probability	Prediction
.094	80 km/h
.087	60 km/h
.067	Priority Road
.056	100 km/h
.053	120 km/h

For the second image, the model is somewhat sure that this is a Traffic Signal Ahead sign (probability of 0.113); and indeed the image is a Traffic Signal Ahead sign. The top five soft max probabilities were:

Probability	Prediction
.113	Traffic Signal Ahead
.091	Danger
.082	Priority Road
.068	Deer Warning
.053	Main Street has Right-of- Way

For the third image, the model is relatively sure that this is a Priority Road sign (probability of 0.169); and indeed the image is a Priority sign. The top five soft max probabilities were:

Probability	Prediction
.169	Priority Road
.079	Yield
.065	No Passing for Trucks
.061	Traffic Signal Ahead
.045	80 km/h

For the fourth image, the model is relatively sure that this is a Yield sign (probability of 0.136); and indeed the image is a Yield sign. The top five soft max probabilities were:

Probability	Prediction
.136	Yield
.101	Priority Road
.068	Traffic Signal Ahead
.048	Construction Site
.047	No Passing for Trucks

For the fifth image, the model is somewhat sure that this is a Traffic Signal Ahead sign (probability of 0.097); yet the actual sign in the image is the somewhat-similar Danger sign, with was the model's second prediction. The top five soft max probabilities were:

Probability		Prediction
	.097	Traffic Signal Ahead
	.092	Danger
	.082	Priority Road
	.054	Deer Warning
	.050	Yield

REFERENCES

Stallkamp, I., Schlipsing, M., Salmen, J., Igel, C. (2011). The German Traffic Sign Recognition Benchmark: A multi-class classification competition; The 2011 International Joint Conference on Neural Networks (IJCNN). http://ieeexplore.ieee.org/document/6033395/

[Ansbach] US Army Garrison Ansbach; "FOR SAFETY You must KNOW German Traffic Signs" Pamphlet. USAREUR POSTER 190-34-12, Jan, 2001; http://www.ansbach.army.mil/documents/EuropeanRoadSignsPamphlet.pdf

[LeCun98] LeCun, Y., Bottou, L., Bengio, Y., and Haffner, P. (1998d). Gradient-based learning applied to document recognition. Proceedings of the IEEE, 86(11), 2278–2324.

[CS231n17] Karpathy, A., Li, F. (2017) http://cs231n.stanford.edu/ Convolutional Neural Networks for Visual Recognition; Stanford University, Spring 2017.