

```

! This version of the program models a gaussian pulse travelling along the
string
program wave
    real :: string_length, time_end, x_step, t_step, phase_vel ,lambda
    real :: init_pos, width
    !Here string_length is the ending point of string i.e. the length of
string
    !time_end is the final time
    !x_step is the step size of x
    !t_step is the step size of t
    !phase_vel is the constant in the 1D wave equation
    integer :: nt, nx
    !nt and nx are the number of steps in t and x respectively
    real, dimension(:, :), allocatable :: y
    !y will be containing the the displacement of the x at time t

    integer :: i, j
    !just two variable to move through the matrix

    write(*, '("The following program is to calculate the position of a wave
generated by a streched string is space-time)")')
    write(*, '("Using 1-D Wave Equation", /, 15X, "u_tt = phase_vel^2 u_xx",
/, /)')
    write(*, '("Enter the length of the string : ")', advance = "no")
    read *, string_length
    write(*, '("Enter the final time t : ")', advance = "no")
    read *, time_end
    write(*, '("Enter the step size in x : ")', advance = "no")
    read *, x_step
    write(*, '("Enter the step size in t : ")', advance = "no")
    read *, t_step
    write(*, '("Enter the constant A : ")', advance = "no")
    read *, phase_vel
    ! Calculate the number of time and distance points
    nt = time_end/t_step + 0.5
    nx = string_length/x_step + 0.5
    print *, "nx = ", nx, ", nt = ", nt
    !Make the sure the value is 1 or less than 1 otherwise it will shoot to
infinity
    lambda = phase_vel*phase_vel*t_step*t_step/(x_step*x_step)
    print *, "Lambda = ", lambda
    ! Now the numerical calculation
    allocate(y(0:nx, 0:nt))
    ! The ends have to be at 0 or all times
    do j = 0, nt
        y(0, j) = 0
        y(nx, j) = 0
    end do
    ! Set the 1st initial values:  $y(x, 0) = \exp(-(x - x_0)^2/a^2)$ 
    ! We will start with  $x_0 = L/2$  i.e. halfway along the string
    init_pos = string_length/2
    width = string_length/5
    do i = 1, nx - 1
        y(i, 0) = exp(-(i*x_step - init_pos)**2/width**2)
    end do
    ! For the second initial values the pulse has moved a distance v dt along
the string
    init_pos = init_pos + phase_vel*t_step

```

```

do i = 1, nx-1
    y(i,1) = exp(-(i*x_step - init_pos)**2/width**2)
end do
! Now do the calculation
do j = 1, nt-1
    do i = 1, nx-1
        y(i,j+1) = 2*y(i,j) + lambda*(y(i+1,j) - 2*y(i,j) + y(i-1,j)) -
y(i,j-1)
    end do
end do
open(19, file = "wavepulse.txt")
do j = 0, nt
    do i = 0, nx
        write(19,'(F0.4, 1X, F0.4, 1x, F0.4)') x_step*i, y(i,j)
    end do
    write(19, '/')
end do
! All finished so free the arrays we allocated
deallocate(y)
end program wave

```