→ Member-only story

7 Pandas DataFrame Tricks I Wish I Knew in My Last Job



Brent Fischer · Follow

Published in Python in Plain English $\,\cdot\,\,4$ min read $\,\cdot\,\,$ Jan 2, 2025



5









•••
















Pandas for Experts

Pandas is one of the most popular Python libraries for data manipulation and analysis, but it can be overwhelming when you're starting out or under time pressure at work. Learning these tricks would have saved me a lot of frustration and time in my last job, and I'm here to share them with you so you can work smarter, not harder.

1. Use .at and .iat for Faster Access to Single Values

Accessing or modifying individual values in a DataFrame is something you'll do often. While .loc and .iloc are the most common methods, they aren't always the fastest. For single-value access, .at (label-based) and .iat (integer position-based) are optimized for speed. This can make a big difference in large datasets.

```
import pandas as pd

df = pd.DataFrame({'A': [1, 2, 3], 'B': [4, 5, 6]})

# Accessing a value
value = df.at[0, 'A'] # Faster than df.loc[0, 'A']

# Modifying a value
df.iat[1, 1] = 10 # Faster than df.iloc[1, 1] = 10
```

In simple terms: Use .at when you know the column and row labels, and .iat when you're working with index positions.

2. Use query for Cleaner Filtering

Filtering rows with conditions is a daily task. While traditional boolean indexing works, it can get messy, especially with multiple conditions. Enter the query method, which lets you filter rows using SQL-like syntax for readability.

```
df = pd.DataFrame({'A': [1, 2, 3], 'B': [4, 5, 6]})

# Instead of this
filtered = df[(df['A'] > 1) & (df['B'] < 6)]

# Use query for cleaner code
filtered = df.query('A > 1 & B < 6')</pre>
```

When your filtering logic gets more complex, query makes your code much easier to read and maintain.

3. Vectorized Operations Instead of Loops

Loops feel natural to use, but they're inefficient when working with Pandas. The library is built for vectorized operations, which are faster because they're executed in C under the hood. If you're using for loops or apply for simple column-wise calculations, you're doing it the hard way.

```
# Slow loop
df['C'] = [a + b for a, b in zip(df['A'], df['B'])]
# Fast vectorized operation
df['C'] = df['A'] + df['B']
```

Not only is the vectorized approach faster, but it's also more readable. Think of your DataFrame as a single entity rather than individual rows and columns.

4. Use .assign to Chain Transformations

Data cleaning often involves multiple transformations. Instead of performing one operation, assigning it back to the DataFrame, and repeating, you can use <code>.assign</code> to chain them together. This makes your code more elegant and less error-prone.

```
df = pd.DataFrame({'A': [1, 2, 3], 'B': [4, 5, 6]})

# Add or modify columns in one step
df = df.assign(
    D=df['A'] * 2,
    E=lambda x: x['B'] + 3
)
```

Now you can add or modify multiple columns without interrupting the workflow. This is especially useful when chaining multiple operations together.

5. Replace apply with .map or .applymap for Simpler Tasks

If you're transforming a single column, use .map instead of apply. It's faster and more concise. For element-wise transformations across an entire DataFrame, use .applymap. Reserve apply for row-wise or column-wise operations.

```
# Use map for single columns
df['A'] = df['A'].map(lambda x: x * 2)

# Use applymap for element-wise operations across the DataFrame
df = df.applymap(lambda x: x * 2)
```

This keeps your code focused and avoids unnecessary complexity.

6. Convert DataFrames to Dictionaries Efficiently

When working with APIs or exporting data, you'll often need to convert a DataFrame to a dictionary. Instead of writing custom code, use Pandas' built-in to_dict method. Choosing the correct orient argument can save you a lot of headaches.

```
# Convert rows to a list of dictionaries
data_dict = df.to_dict(orient='records')
```

This method is perfect for JSON-style outputs, where each dictionary represents a row. It's a lifesaver when integrating with external systems.

7. Use . groupby with Custom Aggregations

The .groupby function is a powerhouse for summarizing data, but did you know you can combine it with .agg to perform multiple custom aggregations at once? This makes it easy to produce complex summaries in just a few lines.

```
df = pd.DataFrame({'A': ['foo', 'foo', 'bar'], 'B': [1, 2, 3], 'C': [4, 5, 6]})


# Group by column 'A' and compute custom aggregations
result = df.groupby('A').agg(
    sum_B=('B', 'sum'), # Sum of column B
    mean_C=('C', 'mean') # Mean of column C
)
```

Instead of chaining multiple .groupby and aggregation calls, this allows you to calculate everything at once, making your code concise and efficient.

Thank you for being a part of the community

Before you go:

- Be sure to **clap** and **follow** the writer
- Follow us: X | LinkedIn | YouTube | Newsletter | Podcast
- Check out CoFeed, the smart way to stay up-to-date with the latest in tech
- Start your own free AI-powered blog on Differ



• For more content, visit <u>plainenglish.io</u> + <u>stackademic.com</u>





Published in Python in Plain English



36K Followers · Last published 13 hours ago

New Python content every day. Follow to join our 3.5M+ monthly readers.



Written by Brent Fischer



24 Followers · 12 Following

Python Developer, Python Trainer, Geek, RPGs, Pizza, Traveller. Loves Rust, C, Linux. Drop by at <u>friendlybytes.net</u>

No responses yet



What are your thoughts?

Respond

More from Brent Fischer and Python in Plain English





Linux for Pythonistas: Advanced File Monitoring and Automation...

In Linux, inotify (inotify stands for "inode notify") is a powerful kernel subsystem that...

Dec 12, 2024 🔌 95



In Python in Plain English by Kiran Maan

Can Mojo Really Replace Python? Let's Test It

A few days ago, I got to know about Mojo on Medium. I just made a pause and read: "Mojo...

→ Dec 19, 2024 W 697 ■ 14





In Python in Plain English by Afsalkh

Why Does round(6.5) Return 6 While round(7.5) Returns 8 in...

Pythonistas, Can You Explain This Rounding Oddity?

Dec 3, 2024 **3** 697 **1** 13



In Python in Plain English by Brent Fischer

Python Advanced: The Beginner's **Guide to Ruff**

As Python projects grow in size and complexity, maintaining clean and consisten...

Dec 9, 2024 **3** 20

See all from Brent Fischer

See all from Python in Plain English

Recommended from Medium









10 Ways to Work with Large Files in **Python: Effortlessly Handle...**

Handling large text files in Python can feel overwhelming. When files grow into...

Dec 1, 2024 3 304 3

Pandas Read Excel 18 Times Faster

Yesterday, I had to process around 750 Excel files with approximately 165,000 rows each....

Jul 11, 2024 👋 164

Lists



Coding & Development

11 stories · 964 saves



Practical Guides to Machine Learning

10 stories · 2138 saves



Predictive Modeling w/ **Python**

20 stories · 1765 saves



ChatGPT

21 stories · 938 saves







Python 3.14 Released — Top 5 Features You Must Know

Faster Annotations & Mind-Blowing Updates You NEED to Know!

→ Dec 31, 2024 → 62

···

Lorenzo Uriel

Starting a Python Project

This guide documents the steps I take to set up the foundation of any Python project, wit...

Nov 19, 2024 **№** 200 **Q** 1



In Towards Data Engineering by Sandun Lakshan

vs. 13 475 last period 200 150 100 50

In Towards Data Science by Vladimir Zhyvov

10 Best Python Text User Interface (TUI) Libraries for 2025

Text-based user interfaces (TUIs) are a simple way to create interactive applications that ru...

vay to create interactive applications that ru.

From Default Python Line Chart to Journal-Quality Infographics

Transform boring default Matplotlib line charts into stunning, customized...

Dec 30, 2024 🔌 1.1K 🗨 18

See more recommendations