

alvin alexander



## Different ways to create and populate Lists in Scala

By Alvin Alexander. Last updated: Jun 6, 2015

This is an excerpt from the *Scala Cookbook* (partially modified for the internet). This is Recipe 11.1, “Different Ways to Create and Populate a List in Scala”

### Problem

You want to create and populate a `List`.

### Solution

There are many ways to create and initially populate a `List`:

```
// 1
scala> val list = 1 :: 2 :: 3 :: Nil
list: List[Int] = List(1, 2, 3)

// 2
scala> val list = List(1, 2, 3)
x: List[Int] = List(1, 2, 3)

// 3a
scala> val x = List(1, 2.0, 33D, 4000L)
x: List[Double] = List(1.0, 2.0, 33.0, 4000.0)

// 3b
scala> val x = List[Number](1, 2.0, 33D, 4000L)
x: List[java.lang.Number] = List(1, 2.0, 33.0, 4000)

// 4
scala> val x = List.range(1, 10)
x: List[Int] = List(1, 2, 3, 4, 5, 6, 7, 8, 9)

scala> val x = List.range(0, 10, 2)
x: List[Int] = List(0, 2, 4, 6, 8)

// 5
scala> val x = List.fill(3)("foo")
x: List[String] = List(foo, foo, foo)

// 6
scala> val x = List.tabulate(5)(n => n * n)
x: List[Int] = List(0, 1, 4, 9, 16)

// 7
scala> val x = collection.mutable.ListBuffer(1, 2, 3).toList
x: List[Int] = List(1, 2, 3)

// 8
scala> "foo".toList
res0: List[Char] = List(f, o, o)
```



### more scala

#### general

extension examples  
using match like switch  
current date/time  
if/then/else  
ternary operation  
for loop and yield

The first two approaches shown are the most common and straightforward ways to create a `List`. Examples 3a and 3b show how you can manually control the `List` type when your collection has mixed types. When the type isn’t manually set in Example 3a, it ends up as a `List[Double]`, and in 3b it’s manually set to be a `List[Number]`.

Examples 4 through 6 show different ways to create and populate a `List` with data.

Examples 7 and 8 show that many collection types also have a `toList` method that converts their data

early linker packaging  
and methods to existing  
classes.

spring framework  
dependency injection

#### classes and methods

creating java beans  
implementing java scala  
multiple constructors  
named and default  
parameters  
calling methods  
class casting  
equivalent of java class  
semantic classes on import  
private primary constructor

#### try/catch/finally

try, catch, and finally syntax  
declare a null var before  
try/catch

#### collections

mutable arrays  
string arrays  
convert array to string  
data types  
convert java collections to  
scala  
multidimensional arrays  
(2D array)  
Iterating over lists (foreach,  
for)  
Iterating over maps  
convert array to string with  
toString

#### list

list, foreach, and for  
merging lists  
creating lists  
list examples  
add elements to a list  
the filter method

#### map

map class examples  
Iterating over maps

#### tuple

tuple examples  
map tuples in anonymous  
function

#### strings

mutable strings  
string arrays  
string formatting  
convert array to string  
split string example

to a List.

Going back to the first example, it shows the `::` method for creating a List, which will be new to Java developers. As shown, the `::` method (called “cons”) takes two arguments: a head element, which is a single element, and a tail, which is another List. When a List is constructed like this, it must end with a Nil element.

It’s important to know that the Scala List class is not like Java List classes, such as the Java ArrayList. For example, Recipe 17.1, “Going to and from Java Collections” shows that a *java.util.List* converts to a Scala Buffer or Seq, not a Scala List.

The following quote from the Scala List Scaladoc discusses the important properties of the List class:

“This class is optimal for last-in-first-out (LIFO), stack-like access patterns. If you need another access pattern, for example, random access or FIFO, consider using a collection more suited to this than List. List has O(1) prepend and head/tail access. Most other operations are O(n) on the number of elements in the list.”

See Recipe 10.4, “Understanding the Performance of Collections” for more information on the List performance characteristics.

### See Also

- The List class
- Recipe 3.15, “Working with a List in a Match Expression” shows how to handle a List in a match expression, especially the Nil element
- Recipe 10.4, “Understanding the Performance of Collections” discusses List class performance
- Recipe 17.1, “Going to and from Java Collections” demonstrates how to convert back and forth between Scala and Java collections

### The Scala Cookbook

This tutorial is sponsored by the *Scala Cookbook*, which I wrote for O’Reilly:



You can find the Scala Cookbook at these locations:

- [Here on the O’Reilly website](#), and
- [Here on Amazon.com](#)

tags: collection cons create declare fill list nil populate range scala scala scala cookbook tabulate

### related

- [How to merge \(concatenate\) Lists in Scala](#)

concat string to int

compare strings with ==

a 'thump' method

find regex in string

functions and functional programming

named and default parameters

pass one function to another

pass a function to a function (twice)

files

open and read files

shell script example

command line and scripts

read command line arguments

execute fixed system commands

prompting a user, reading input

make scripts run faster

show more methods in repl

show more info on classes/objects in repl

paste multiline commands in repl

database

jdbc connection, select

actors and concurrency

akka 'hello world'

akka ping-pong example

stop/start an actor

stop actor and shut down

akka futures

akka ask, future, await, timeout

parallel collections, .par, and performance

akka remote example

akka remote - objects as messages

idioms

using option, some, and none

methods should have no side effects

prefer immutable state

email

imap client using v1 and imap2

imap client with search

play framework




play framework resgen

deploy to production

join method in controller

- [How to merge Scala Lists](#)
- [How to use a Range in Scala \(Range class examples\)](#)
- [How to populate Scala collections with a Range](#)
- [How to add elements to a List in Scala](#)
- [How to create a mutable List in Scala \(ListBuffer\)](#)

books i've written



new

- [How to use multiple generators in Scala 'for' expressions \(loops\)](#)
- [When you want to store static text in an Android file](#)
- [A Java FIFO queue class](#)
- [A Java tuple class](#)
- [A Java method to calculate the NFL Passer Rating](#)
- [An Android method to center text when using Canvas drawText](#)
- [An Android cheat sheet \(my notes, main concepts\)](#)
- [How to show an HTML WebView in an Android AlertDialog](#)
- [A Java method to determine if an integer is between a range](#)
- [How do I round a float or double to an integer in Java?](#)

[more](#)

[alvin's blog](#)

Post new comment

Your name:

E-mail:

The content of this field is kept private and will not be shown publicly.

Homepage:

Subject:

Comment: \*

creating read forms  
@extends rows and columns  
convert objects to json  
run play on different port  
populate data on startup  
using map in template  
template comments  
template functions  
404 and 500 errors  
mapping field validators  
web service request with  
literal  
play console commands/help  
testing web services with curl  
logout, destroy session  
read cookies

#### web services

test client using apache  
httpclient  
twitter client example  
json parsing using lift-json  
json array parsing using  
lift-json  
lift framework form examples

#### xml

create xml literal  
generate dynamic xml  
xml - pretty printing  
xml - save to file  
xml - serialize, deserialize  
xml - load a file  
xml - load a url  
xml - xpath searching  
searching xmlns namespaces,  
xpath  
xml - extract data from  
nodes  
xml - extract data from  
arrays  
xml - parsing, tags  
xml - using match  
expressions  
xml - many examples

#### build, testing, and debugging

sbt documentation (pdf)  
show sbt history  
scalatest - installing  
scalatest - writing fdd tests  
scalatest - writing fdd tests  
scalatest - given/when/then  
with fdd  
scalatest - test suite  
scalatest - expected, actual  
scalatest - mark test as  
pending  
scalatest - testing exceptions  
scalatest - logging tests

☒ Notify me when new comments are posted

☒ All comments ☐ Replies to my comment

Preview

scalatest - dividing tests

scalatest - mock objects

scalatest - running in eclipse

categories

android (45)  
best practices (63)  
cmm (50)  
cvs (27)  
design (13)  
drupal (91)  
eclipse (6)  
furry (3)  
gadgets (108)  
git (15)  
intellij (4)  
java (429)  
jboss (26)  
swing (74)  
jvc (9)  
latex (26)  
linux/unix (289)  
mac os x (115)  
mysql (16)  
osx/osul (11)  
perl (156)  
php (97)  
postgresql (17)  
ruby (56)  
scala (336)  
sencha (23)  
servlets (10)  
svn (6)  
technology (84)  
testing (13)  
uml (24)

java	unix	misc	other
java applets	man (help) pages	privacy policy	mobile website
java faqs	unix by example	terms & conditions	rss feed
misc content	tutorials	subscribe	my photos
java source code	source code	unsubscribe	life in alaska
test projects	warehouse	wincvs tutorial	how i sold my business
lejos	java examples	function point	living in talkeetna, alaska
perl	drupal examples	analysis (fpa)	my bookmarks
perl faqs		fpa tutorial	inspirational quotes
programs			source code snippets
perl recipes			
perl tutorials			