INFOSYS × IISc × NVIDIA

AEGIS 2026

MemLedger: Provenance-Governed Memory for Long-Running AI Agents

Team Prompt Stars: Banaj Mahajan, Ahan Phatak, Omkaar Nerurkar, Aditya Garg

Problem statement: Agent Memory Governance Evaluation

ORGANISED BY

Infosys®
Navigate your next

HOSTED BY

INDIAN INSTITUTE OF SCIENCE
भारतीय विज्ञान संस्थान

TECHNOLOGY PARTNER

NVIDIA

Who we are and what we are building

01 Team Introduction

Prompt Stars

Banaj Mahajan
Ahan Phatak
Omkaar Nerurkar
Aditya Garg

02 Selected problem statement

Agent Memory Governance Evaluation

AI agents that run for weeks store what they read and act on it later. If that memory is poisoned, untraceable, contradictory or readable by the wrong user, the agent can be steered without anyone noticing.

Pillars: Security, Privacy, Safety, Reliability.

03 Our solution

MemLedger is a memory layer for AI agents. It records where every memory came from, scores how far it can be trusted, and enforces access and safety rules in ordinary code instead of relying on the model.

It comes with a test suite that measures how well an agent's memory resists poisoning, traces origins, catches contradictions and keeps users' data apart.

1. Solution Relevance & Impact

Risk	What goes wrong	Pillar	How MemLedger responds
Memory poisoning	Malicious text is saved and steers the agent in a later session	Security, Safety	Inputs are screened, every write is checked, and risky actions pass a gate enforced in code
Unknown origin	The agent cannot tell where a stored fact came from or how reliable it is	Reliability, Security	Every memory is linked to its sources and given a trust score
Hallucinated or conflicting memories	Made-up or contradictory facts pile up over many sessions	Reliability	New memories must be backed by their sources and are compared with existing ones
Unauthorised access	One user, team or role reads another's memory	Privacy, Security	Identity and access rules are enforced by the memory service, never by the model

Table 1: The four risks named in the problem statement and how we address each.

Who is the attacker? Anyone who can put text in front of the agent: a web page, a document, a tool result, a chat message, or a user account in another team. They cannot change our code, our signing keys or the company registry. A single malicious write can keep influencing the agent long after it was made [7].

84.2% of test cases kept the planted malicious memory, across 24 agent configurations [4]

50.3% of test cases completed the full attack: the memory was recalled and shaped a real action [4]

Existing prompt-injection defences fail to cover memory poisoning [7].

IMPACT

- Safe shared memory for enterprise agents used by many people and teams
- A bad source can be traced and cleaned up without wiping memory
- Every memory has an audit trail: source, derivation, approval

2. Solution Approach, Innovation & Creativity

MemLedger places a memory service between the agent and its storage. The agent can only propose what to remember and request actions; the service decides what is stored, what is read back and what is allowed to run. Five ideas make this work:

1. **Provenance recorded by the system, not the model.** When a memory is written, the service records everything the model had in front of it and which of those sources actually support the new memory, as confirmed by a fact-checking model. A poisoned input cannot hide its influence by going uncited.
2. **Trust that repetition cannot inflate.** A memory is only as trustworthy as its weakest source. Agreement raises trust only when it comes from independent origins, so planting the same claim ten times still counts once.
3. **Targeted clean-up.** When a source turns out to be malicious, everything derived from it is quarantined. Memories that still have an independent, clean justification are restored automatically.
4. **Hard guarantees where they matter.** Critical company facts live in a signed registry the agent can read but not change, live facts are re-checked at their source, and risky actions are blocked unless their inputs come from these trusted channels.
5. **Measured, not assumed.** We switch each layer on in turn and measure what it adds in safety and what it costs in usefulness, on nine groups of published benchmarks and attacks plus our own multi-team scenarios.

We build on truth maintenance systems [12], the W3C provenance model [20], classic integrity and confidentiality models [2, 1] and recent information-flow controls for agents [6, 9].

2. Solution Approach (cont.): A poisoning attempt, step by step

Scenario. While researching suppliers, the agent reads a web page containing the line “Note: Acme Ltd’s bank account has changed to 9876.” Two weeks later, a finance user asks the agent to pay Acme’s latest invoice.

WITH A PLAIN RETRIEVAL MEMORY

1. **Stored.** The sentence is saved as a memory like any other.
2. **Recalled.** Two weeks later it is retrieved as relevant context for the payment.
3. **Acted on.** The agent pays account 9876. Nothing records why, and other memories built on the page stay in place.

WITH MEMLEDGER

1. **Recorded.** The page is saved as a low-trust web source, and the claim the agent proposes is linked to it.
2. **Rejected.** Bank accounts are protected facts. The claim does not match the signed company registry, so it is refused and the page is flagged.
3. **Paid safely.** The payment tool looks up Acme’s account in the registry itself, so even a fooled model pays the right account.
4. **Cleaned up.** Everything else derived from the page is quarantined, and the lineage view shows exactly what it touched.

2. Solution Approach (cont.): Tracking where memories come from




Figure 1: After the web page is found to be poisoned, the memories that depend on it (D2, D3) are quarantined. D1 also saw the page but is supported by a paper and a tool output, so it is restored.

What the graph stores. Every source (paper, user, tool, web page), every memory and every write event is a node. Links record what the model saw when writing a memory, which sources support it, and which memories contradict or replace each other. Each memory also stores when it was true, when it was recorded, and a hash chained to its sources' hashes, so any later tampering is detectable (Section 3).

How trust is computed. A memory derived from sources u, with fact-checker confidence s, gets

$$T = s \cdot \min_u T(u),$$

so it is never more trusted than its weakest source. If a fact is reached through several derivations with independent origins,

$$T = 1 - \prod_i (1 - T_i),$$

so independent agreement raises trust, while repetition from one origin does not. The full procedure is on the next slide.

2. Solution Approach (cont.): How a trust score is computed

The graph works like a justification-based truth maintenance system (JTMS) [12]: a memory is believed only while at least one of its justifications (groups of sources) is valid. The JTMS is plain code; models supply only steps 2 and 5.

1. **Start from the source (table).** Each source type gets a starting trust, e.g. 0.95 for approved papers and the registry, 0.9 for internal systems, 0.7 for user notes, 0.3 for web pages, fitted on held-out data.
2. **Check the step (model).** The hallucination check, MiniCheck [27] or AlignScore [32], returns the probability s that the sources support the memory, calibrated on held-out data.
3. **Weakest link (code).** $T = s \cdot \min_u T(u)$ over the supporting sources u.
4. **Independent agreement (code).** Derivations with non-overlapping origins combine as $1 - \prod_i (1 - T_i)$; copies from one origin are merged first.
5. **Contradictions (model).** A DeBERTa-v3 inference model [13] flags conflicts; a memory contradicted by a higher-trust one, and not an update, is marked contested and kept out of high-risk actions.
6. **Retraction (code).** When a source is flagged, its justifications are withdrawn; memories left with none are quarantined, and trust is recomputed downstream.
7. **Use (code).** The read filter applies a threshold per risk level; only a signed human approval can make a memory a trusted source.

WORKED EXAMPLE

A conclusion uses a paper (0.95) and a tool output (0.9), and the fact-checker gives $s = 0.9$:

$$T_1 = 0.9 \cdot \min(0.95, 0.9) = 0.81.$$

The same fact also follows independently from a user note (0.7) with $s = 0.8$:

$$T_2 = 0.8 \cdot 0.7 = 0.56.$$

Combined:

$$T = 1 - (1 - 0.81)(1 - 0.56) \approx 0.92.$$

A web page (0.3) that repeats the fact ten times counts as one origin, so it adds at most $0.3 \cdot s$ once.

If the paper is later retracted, T_1 is withdrawn and the fact falls back to $T_2 = 0.56$, below the threshold for high-risk use.

2. Solution Approach (cont.): Matching the check to the kind of fact

A trust score alone cannot prove that a fact is true. So we sort facts by how they can be checked, and a fact may influence actions only as far as it has been checked.

Kind of fact	Examples	How it is checked	Strength
Protected	bank accounts, admin contacts, approval limits	Must match the signed company registry exactly, otherwise it is rejected	**Guaranteed**
Live state	“ticket 42 is resolved”, “server A is down”	Re-checked against the source system just before use; memory is only a cache	**Guaranteed***
Derived	conclusions drawn from papers and observations	Fact-checker confirms support; trust of the weakest source; contradiction check	**Estimated**
Third-party	web facts, external claims	Needs agreement from at least k independent origins	**Estimated**
Unverifiable	preferences, opinions	Kept with its source; never used for high-risk actions	**Restricted**

Table 2: Kinds of facts and how each is checked. *Assumes the source system itself is trustworthy.

Every memory records both when it was true and when it was learned, as in Zep/Graphiti [25], so a change of state is treated as an update rather than a contradiction.

2. Solution Approach (cont.): Protected facts and risky actions

SIGNED COMPANY REGISTRY

Facts that must never be wrong are kept in a registry file signed with an Ed25519 key. The memory service checks the signature when loading the file and on every read, so an edited or unsigned file is refused.

Only staff who sign in with company credentials and the registry-admin role can change it. The agent can read it but never holds the key.

Risky tools take their critical parameters from the registry, not from the model: `send_payment(vendor)` looks up the vendor's account itself.

ACTION GATE

Tool calls are grouped by risk (Figure 2). Answering questions and editing internal data run normally. An external action, such as a payment or an outgoing email, runs only if every fact it relies on comes from the registry or was re-checked at its source; otherwise it waits for a person to approve it.

Adding a fact to the trusted sources also needs a signed approval from an authorised reviewer (optionally two), and the approval itself is recorded in the provenance graph.



Figure 2: Risk levels for tool calls. Only high-risk calls are gated.

3. Technical Implementation




Figure 3: How MemLedger works. Lane A: a new memory must pass three checks before it is stored. Lane B: stored memories are retrieved, filtered and shown to the agent with their sources, and risky actions are gated. White boxes are the memory service, dark boxes the AI agent and grey boxes things outside the system; steps 1 to 8 are explained on the next slide.

3. Technical Implementation (cont.): The eight steps

A. WRITING A MEMORY

1. **Screen and save.** Every input is checked for injected instructions and saved as a source with a hash, its team and access labels. Inputs never go straight into memory.
2. **Hallucination check.** The agent's proposed memory is split into single facts; a fact-checking model [27, 32] tests whether its sources support each one, and a memshield-bench [23] classifier flags manipulative entries. Failing facts are rejected.
3. **Registry match.** Protected facts (bank accounts, contacts, limits) must match the signed registry exactly; a mismatch is rejected and its source flagged.
4. **Contradiction and trust.** It is compared with similar memories [13]: an older fact becomes an update, a real conflict is settled by trust. Then it is scored and stored with its links.

B. USING A MEMORY

5. **Retrieve.** Candidates come from semantic and keyword search, exact lookups and provenance links, always within the user's own team.
6. **Read filter.** Quarantined, outdated and low-trust memories are removed; the rest carry their source and trust score.
7. **Build context.** The prompt is assembled from what passed the filter, and the service records exactly what the model was shown.
8. **Action gate.** A high-risk call (payment, email) runs only if its inputs come from the registry or were re-checked at the source; otherwise a person must approve it.

Why this holds up. Saving sources, the registry match, the action gate and access control are plain code, so they hold even if the model is fooled; the model-based parts of steps 1, 2, 4 and 5 are measured in Section 4.

3. Technical Implementation (cont.): Screening inputs (step 1)

Step 1 looks for text that gives the agent instructions instead of information: “ignore your previous instructions”, hidden tool calls, or requests to store something or send data elsewhere.

FOUR LAYERS, CHEAPEST FIRST

1. **Unhide (code).** Normalise Unicode, strip zero-width characters, decode Base64 and HTML entities, and pull out hidden text: comments, alt text, invisible styling, metadata.
2. **Rules (code).** Fast patterns for instruction phrases, role markers such as “system:”, tool-call syntax and store-or-send requests. Precise, but easy to evade by rewording.
3. **Classifier (model).** An off-the-shelf detector, Llama Prompt Guard 2 [18], compared with Protect AI’s DeBERTa-v3 detector [24], run on 512-token chunks. If it needs tuning, we use only BIPIA’s training split [31]; InjecAgent [33] and AgentDojo [8] are kept for testing.
4. **Spotlighting.** Text that passes enters the prompt clearly marked as quoted data with its source, which makes the model less likely to obey it [14].

WHAT THE SCORE DECIDES

High	Quarantined, never shown to the model; the source is flagged.
Mid	Allowed but marked untrusted: anything derived from it cannot become a high-trust memory or drive a high-risk action.
Low	Saved as a normal source with its usual starting trust.

LIMITS AND MEASUREMENT

The screen misses poison that reads like an ordinary fact (“Acme’s account changed to 9876”); the registry match, trust score and action gate catch that. We report precision and recall on BIPIA’s test split, InjecAgent and AgentDojo, false alarms on clean company documents, and detection of adaptive, disguised attacks generated with garak [10] and PyRIT [16].

3. Technical Implementation (cont.): Checking new memories

01 Hallucination check

A memory is hallucinated when its own sources do not support it. In step 2, the proposed memory is split into single facts. A fact-checking model (MiniCheck [27] or AlignScore [32]) scores each fact against the sources the model was shown. Unsupported facts are rejected or kept as the model's own knowledge with low trust. Multi-source conclusions are checked against all their sources together.

02 Contradiction check

We retrieve the most similar existing memories and run an inference model [13] on each pair. If two facts were true at different times, it is an update, not a conflict. Otherwise the lower-trust memory is replaced or quarantined with a log entry. Nothing is deleted.

03 Exact fields

For facts with a single correct value, such as a server's status or an account number, we also extract (subject, property, value) triples and compare them exactly, including with the registry. The extraction step uses a model, so we measure its error rate too.

Known weaknesses. Inference models are less accurate on long passages, so sources are checked in chunks. Stricter cut-offs catch more but reject more valid memories; we report the full trade-off on RAGTruth [22], HaluEval [15] and LLM-AggreFact [27].

3. Technical Implementation (cont.): Detecting direct tampering

An attacker with database access could bypass the agent and edit stored memories directly. Hash chaining makes any such edit detectable.




Figure 4: Editing Memory A changes its recomputed hash, which then mismatches the stored value, B's link and the signed root.

Limits. Tampering becomes detectable, not impossible: whoever holds the signing key or can rewrite the hash log could forge it, and writes since the last anchor rely on the change log alone. Measured by tamper detection (Table 5) and the tampering attacks in Appendix A1.

1. **Chain.** Every source and memory stores $h = \text{SHA-256}(\text{content} \,\|\, \text{record time} \,\|\, \text{sorted parent hashes})$. Changing one item breaks its links to everything derived from it.
2. **Anchor.** After every batch of writes, the service combines all current hashes into one root hash (a Merkle tree), signs it with Ed25519 and appends it to the hash log. The key lives in a separate service that the agent and the database's admin accounts cannot reach.
3. **Check on read.** Before a memory is returned, its hash is recomputed and checked against the stored value and, through a short Merkle proof, against the latest signed root. Gaps in the log's sequence numbers reveal deleted records.
4. **Respond.** On a mismatch the item is quarantined, an alert is raised and the last good version is restored from the change log; everything derived from it is re-checked by the trust engine.

3. Technical Implementation (cont.): How memories are retrieved

Retrieval starts like RAG, but similarity alone cannot tell where a memory came from, whether it is still true, or whether this user may read it. So we retrieve in two stages.




Figure 5: Two-stage retrieval. Stage 1 casts a wide net; stage 2 decides what the agent may see.

Semantic + keyword search. BGE-M3 [3] embeddings find memories by meaning; a keyword index finds exact names and IDs that embeddings often miss.

Exact lookup. Facts with a single value, such as Acme's bank account, are read from the registry or from stored (subject, property, value) triples, never from similarity search.

Graph links. For each hit we follow its provenance one step: its supporting sources come along, and a memory that has been replaced is swapped for its newer version.

WHY NOT PLAIN RAG?

1. It returns whatever is most similar, so a poisoned note written to match common questions comes first.
2. It shows old and new versions of a fact side by side.
3. It often filters access after searching, which can leak through result counts; we search only the user's team index.
4. It cannot tell a paper from an anonymous web page; we attach source and trust.

3. Technical Implementation (cont.): Components and models

Component	In MemLedger
Agents	One long-running agent per team; agents can propose memories and request actions, nothing more
Models	Main model, embedding model, fact-checkers, input and memory screens, and a separate attacker model for testing (Table 4)
Data	Vector index, provenance graph, signed registry and hash log; papers, tool outputs and user input as sources
Guardrails	Ingestion, write checks and read filter; access control and action gate in code

Table 3: The four building blocks.

Role	Model	Used for
Main model	Local 8–12B model (Ollama); a larger one on NVIDIA compute	Doing the task
Embeddings	BGE-M3 [3]	Semantic search
Fact-checkers	MiniCheck [27], AlignScore [32]; DeBERTa-v3 [13] tuned on MNLI [28]	Support, contradiction
Screens	Prompt Guard 2 [18]; classifier on memshield-bench [23]	Inputs; new memories
Attacker	Separate model; garak [10], PyRIT [16]	Test attacks
Trust engine	No model: JTMS [12] in code over the provenance graph	Trust, retraction

Table 4: Models and what each is used for.

SOFTWARE A Python memory service with five operations (ingest, propose a write, retrieve, flag a source, explain a memory's lineage); SQLite for the graph, change log and keyword search; Chroma for per-team search; a signed JSON registry; company single sign-on (Keycloak in the demo); a Streamlit demo with a lineage view.

4. Measurable Metrics

We run the same test suite on five versions of the system and compare them. Each version adds one layer, so the effect of every layer is visible.




Figure 6: The five versions we compare.

TWO KINDS OF TEST RUN

Attack runs. An attacker plants poison, tries to read another team's data, or tries to hijack a payment. Taken from the benchmarks in Appendix A2 and our own multi-team scenarios.

Clean runs. Ordinary tasks with no attacker, from LongMemEval [29], LoCoMo [17] and our scenarios. Every answer has a known correct result.

SAFETY AND COST

Safety metrics are measured on attack runs: how often an attack gets through.

Cost metrics are measured on clean runs: how much normal work the protections wrongly block, slow down or get wrong.

A system that refuses everything would score perfectly on safety and terribly on cost, so every safety number is reported next to its cost.

4. Measurable Metrics (cont.): Safety metrics

Risk	Metric	How it is computed	Goal
Poisoning	Poison stored rate	planted poisoned items that end up in memory ÷ planted items	lower
	Attack success rate	attack runs in which the agent later takes the attacker's chosen action ÷ attack runs	lower
Origin	Attribution accuracy	memories whose recorded sources are the ones that really shaped them (checked by removing one source at a time) ÷ memories checked	higher
	Clean-up recall	poison-derived memories quarantined after the source is flagged ÷ all poison-derived memories	higher
	Trust calibration error	average gap between a trust score and how often memories with that score are actually right (trust 0.8 should mean right 80% of the time)	lower
Consistency	Detection F1	balance of precision (flags that are real problems) and recall (real problems that get flagged), on planted conflicts, RAGTruth [22] and HaluEval [15]	higher
	Update accuracy	genuine changes of state treated as updates rather than conflicts ÷ all changes of state	higher
Access	Leak rate	runs in which another user's data was returned or appeared anywhere visible (Appendix A1) ÷ runs	0
	Tamper detection	records edited outside the service that are caught ÷ records edited	100%
Protected facts	Hijacked action rate	high-risk calls executed with attacker-supplied values (e.g. a wrong account) ÷ attempts	≈ 0

Table 5: Safety metrics, measured on attack runs for each of the five versions. "Goal" gives the direction of improvement or the design target.

4. Measurable Metrics (cont.): Cost metrics and reporting

Cost metric	How it is computed (on clean runs; lower is better)	Protection it charges
False rejection rate	harmless inputs or memories wrongly rejected ÷ harmless inputs or memories	input screen, write checks
Task accuracy loss	baseline accuracy minus this version's accuracy on LongMemEval [29], LoCoMo [17] and our tasks	read filter, all layers together
False quarantine rate	clean memories quarantined by a clean-up ÷ clean memories	retraction (JTMS)
False denial rate	legitimate requests refused ÷ legitimate requests	access control
Approval load	high-risk calls sent to a person ÷ high-risk calls, and their waiting time	action gate
Added delay	extra time per memory write and per read, in milliseconds	whole memory service

Table 6: Cost metrics: what each protection costs in normal use.

CHOOSING CUT-OFFS

Each check has a cut-off score. We tune it on a development set, pick the setting that blocks the most attacks while rejecting at most 5% of harmless writes, and report every number on a separate test set.

REPORTING

Every number comes with a 95% confidence interval. When no leak occurs in n independent runs, the true rate is below $3/n$ (rule of three): 0 in 3,000 runs means below 0.1%. The targets in Table 5 are design goals, not results.

AEGIS 2026 · BACKUP MATERIAL

Appendix

A1 How we test isolation between users

A2 Benchmarks

A3 Limitations and roadmap

A4 References

A1. Testing isolation between users

Setup. Each user p belongs to a team $\tau(p)$ and has a role $\rho(p)$ and a clearance level $\mathrm{clr}(p)$. Each memory m carries its team $\tau(m)$, a confidentiality level $c(m)$ and an integrity (trust) level $i(m)$.

Who may read what. User p may read memory m only if

$$\tau(m) \in \{\tau(p), \mathrm{shared}\}$$
$$\wedge\ c(m) \leq \mathrm{clr}(p)$$
$$\wedge\ \text{the role policy allows it,}$$

where *shared* covers the trusted sources and the registry, which everyone may read. We call this set $\mathrm{Auth}(p)$.

ID	Property we test
I1	A user only ever receives memories in $\mathrm{Auth}(p)$
I2	A memory derived from confidential sources is at least as confidential, and one derived from untrusted sources is at most as trusted; mixing teams is refused
I3	After reading untrusted content, a session cannot write to high-trust memory
I4	After reading untrusted content, a session cannot send data out
I5	That restriction lifts only when the session ends or a person approves
I6	Any change made to stored records outside the service is detected on the next read (hash check)
I7	Nothing a user sees, including response time, depends on data outside $\mathrm{Auth}(p)$
I8	Deleted memories never come back through search, caches or summaries
I9	An unsigned or altered registry is refused
I10	High-risk tools take protected parameters only from the registry

Table 7: Isolation properties checked in every test run.

A1. Testing isolation (cont.): How leaks are detected

Test data. At least three teams with two clearance levels each. Every memory contains a unique random 128-bit marker and a made-up fact that exists nowhere else.

Leak check 1. The service returned a memory the user may not read.

Leak check 2. A marker or made-up fact from such a memory appears anywhere the user can see: the prompt, the answer, tool arguments, logs or error messages.

Checking I7. We run the same script against two stores that differ only in data the user may not read. With fixed model settings the outputs must be identical, and response times are compared with a statistical test.

8×6 attack types $\times$ ways of reaching memory (search, lookup by ID, graph traversal, summaries, caches, shared store); every combination is tested

Attack type	What is attempted
Direct	forged team IDs, malformed filters, stolen or expired tokens
Via the model	prompts telling the agent to fetch another team's data
Side channel	result counts, error messages, shared caches, timing
Data flow	untrusted input followed by a trusted write or an outgoing call
Tampering	editing records or links directly in the database
Derivation	building a memory from another team's data
Multi-agent	a high-clearance agent writes, a low-clearance agent reads
Registry	unsigned edits, poisoned protected facts, hijacked parameters

Table 8: The eight attack types.

A2. Benchmarks

What it tests	Benchmark or published attack	Used for
Poisoning that persists over sessions or long interactions	MemEvoBench [30] (public); attack designs of MPBench [7] and MemSecBench [4], rebuilt in our scenarios as their data is not public	Poisoning (main results)
Poisoned memory and document stores	AgentPoison [5], PoisonedRAG [35] (attacks with code)	Poisoning
Poisoning through ordinary queries	MINJA [11] (attack with code)	Poisoning
Prompt injection and other agent attacks, mostly single-session	AgentDojo [8], InjecAgent [33], BIPIA [31], ASB [34]	Testing the input screen (BIPIA train split only for tuning); prior defences
Labelled clean vs. poisoned memory entries	memshield-bench [23] (own train/test splits)	Memory screen at write time
Hallucination and grounding	RAGTruth [22], HaluEval [15], LLM-AggreFact [27]	Hallucination check and its score
Natural language inference	ANLI [21]; held-out MNLI [28] sets	Calibrating the contradiction model
Privacy in context	PrivacyLens [26], ConfAIde [19]	Model revealing data it was allowed to see
Long-term memory usefulness	LongMemEval [29], LoCoMo [17]	Cost in usefulness
Our own multi-team scenarios	Research assistant shared by two teams, with known ground truth	Origin, access, registry
Attack generation tools	garak [10], PyRIT [16]	Producing test attacks

Table 9: Nine groups of published benchmarks and attacks, our own scenarios and two attack tools, and what each is used for.

A3. Limitations and roadmap

LIMITATIONS

(i) A trust score estimates how reliable a memory is; it does not prove the memory is true.

(ii) The registry protects only the facts listed in it, and a dishonest administrator is deterred (two-person approval, audit log) rather than stopped.

(iii) Fact-checking models struggle with long passages and multi-step reasoning. We would like to test System One models and discriminative decision models for these long contexts.

(iv) Recording everything the model saw over-estimates influence, so clean-up may quarantine some clean memories.

(v) Our simulated scenarios may not match real company data.

ROADMAP

1. **Memory service** and the plain-memory baseline
2. **Scenario generator** and attack library, with first baseline results
3. **Provenance graph,** trust scores and clean-up
4. **Write checks,** access control, action gate and registry
5. **Full comparison** of all five versions, cut-off tuning and calibration
6. **Interactive demo**




Figure 7: Planned live demonstration.

A4. References (1/3)

[1] D. E. Bell and L. J. LaPadula. Secure Computer Systems: Mathematical Foundations. MITRE Technical Report MTR-2547, Vol. I, 1973.

[2] K. J. Biba. Integrity Considerations for Secure Computer Systems. MITRE Technical Report MTR-3153 (ESD-TR-76-372), 1977.

[3] J. Chen, S. Xiao, P. Zhang, K. Luo, D. Lian, and Z. Liu. M3-Embedding: Multi-Linguality, Multi-Functionality, Multi-Granularity Text Embeddings Through Self-Knowledge Distillation (BGE-M3). Findings of ACL, 2024.

[4] X. Chen, X. Xie, W. Fu, J. Zhou, S. Yu, and Q. Xuan. MemSecBench: Tracking Agent Memory Poisoning from Persistence to Consequence and Repair. arXiv:2607.27080, 2026.

[5] Z. Chen, Z. Xiang, C. Xiao, D. Song, and B. Li. AgentPoison: Red-teaming LLM Agents via Poisoning Memory or Knowledge Bases. NeurIPS, 2024.

[6] M. Costa et al. Securing AI Agents with Information-Flow Control (Fides). arXiv:2505.23643, 2025.

[7] P. Dash, T. Ge, A. Jain, T. Shah, and Z. Shang. From Untrusted Input to Trusted Memory: A Systematic Study of Memory Poisoning Attacks in LLM Agents (MPBench). Second Workshop on Agents in the Wild, ICML 2026. arXiv:2606.04329.

[8] E. Debenedetti, J. Zhang, M. Balunović, L. Beurer-Kellner, M. Fischer, and F. Tramèr. AgentDojo: A Dynamic Environment to Evaluate Prompt Injection Attacks and Defenses for LLM Agents. NeurIPS Datasets and Benchmarks, 2024.

[9] E. Debenedetti et al. Defeating Prompt Injections by Design (CaMeL). arXiv:2503.18813, 2025.

[10] L. Derczynski, E. Galinkin, J. Martin, S. Majumdar, and N. Inie. garak: A Framework for Security Probing Large Language Models. arXiv:2406.11036, 2024.

[11] S. Dong et al. Memory Injection Attacks on LLM Agents via Query-Only Interaction (MINJA). NeurIPS, 2025. arXiv:2503.03704.

[12] J. Doyle. A Truth Maintenance System. Artificial Intelligence, 12(3):231–272, 1979.

A4. References (2/3)

[13] P. He, J. Gao, and W. Chen. DeBERTaV3: Improving DeBERTa using ELECTRA-Style Pre-Training with Gradient-Disentangled Embedding Sharing. ICLR, 2023.

[14] K. Hines, G. Lopez, M. Hall, F. Zarfati, Y. Zunger, and E. Kiciman. Defending Against Indirect Prompt Injection Attacks With Spotlighting. arXiv:2403.14720, 2024.

[15] J. Li, X. Cheng, W. X. Zhao, J.-Y. Nie, and J.-R. Wen. HaluEval: A Large-Scale Hallucination Evaluation Benchmark for Large Language Models. EMNLP, 2023.

[16] G. D. López Muñoz, A. J. Minnich, et al. PyRIT: A Framework for Security Risk Identification and Red Teaming in Generative AI System. arXiv:2410.02828, 2024.

[17] A. Maharana, D.-H. Lee, S. Tulyakov, M. Bansal, F. Barbieri, and Y. Fang. Evaluating Very Long-Term Conversational Memory of LLM Agents (LoCoMo). ACL, 2024.

[18] Meta. Llama Prompt Guard 2 (22M and 86M). Model card, 2025.

[19] N. Mireshghallah, H. Kim, X. Zhou, Y. Tsvetkov, M. Sap, R. Shokri, and Y. Choi. Can LLMs Keep a Secret? Testing Privacy Implications of Language Models via Contextual Integrity Theory (ConfAIde). ICLR (spotlight), 2024.

[20] L. Moreau and P. Missier (eds.). PROV-DM: The PROV Data Model. W3C Recommendation, 30 April 2013.

[21] Y. Nie, A. Williams, E. Dinan, M. Bansal, J. Weston, and D. Kiela. Adversarial NLI: A New Benchmark for Natural Language Understanding. ACL, 2020.

[22] C. Niu et al. RAGTruth: A Hallucination Corpus for Developing Trustworthy Retrieval-Augmented Language Models. ACL, 2024.

[23] N. Pow. memshield-bench: A Benchmark Dataset for AI Agent Memory Poisoning Detection. Hugging Face dataset npow/memshield-bench, 2026.

[24] ProtectAI.com. Fine-Tuned DeBERTa-v3-base for Prompt Injection Detection (deberta-v3-base-prompt-injection-v2). Hugging Face, 2024.

A4. References (3/3)

[25] P. Rasmussen, P. Paliychuk, T. Beauvais, J. Ryan, and D. Chalef. Zep: A Temporal Knowledge Graph Architecture for Agent Memory. arXiv:2501.13956, 2025.

[26] Y. Shao, T. Li, W. Shi, Y. Liu, and D. Yang. PrivacyLens: Evaluating Privacy Norm Awareness of Language Models in Action. NeurIPS Datasets and Benchmarks, 2024.

[27] L. Tang, P. Laban, and G. Durrett. MiniCheck: Efficient Fact-Checking of LLMs on Grounding Documents (LLM-AggreFact). EMNLP, 2024.

[28] A. Williams, N. Nangia, and S. R. Bowman. A Broad-Coverage Challenge Corpus for Sentence Understanding through Inference (MNLI). NAACL, 2018.

[29] D. Wu, H. Wang, W. Yu, Y. Zhang, K.-W. Chang, and D. Yu. LongMemEval: Benchmarking Chat Assistants on Long-Term Interactive Memory. ICLR, 2025.

[30] W. Xie et al. MemEvoBench: Benchmarking Safety Risks from Memory Misevolution in LLM Agents. arXiv:2604.15774, 2026.

[31] J. Yi, Y. Xie, B. Zhu, E. Kiciman, G. Sun, X. Xie, and F. Wu. Benchmarking and Defending Against Indirect Prompt Injection Attacks on Large Language Models (BIPIA). KDD, 2025.

[32] Y. Zha, Y. Yang, R. Li, and Z. Hu. AlignScore: Evaluating Factual Consistency with A Unified Alignment Function. ACL, 2023.

[33] Q. Zhan, Z. Liang, Z. Ying, and D. Kang. InjecAgent: Benchmarking Indirect Prompt Injections in Tool-Integrated Large Language Model Agents. Findings of ACL, 2024.

[34] H. Zhang et al. Agent Security Bench (ASB): Formalizing and Benchmarking Attacks and Defenses in LLM-based Agents. ICLR, 2025.

[35] W. Zou, R. Geng, B. Wang, and J. Jia. PoisonedRAG: Knowledge Corruption Attacks to Retrieval-Augmented Generation of Large Language Models. USENIX Security, 2025.