INFOSYS × IISc × NVIDIA

AEGIS 2026

MemLedger: Provenance-Governed Memory for Long-Running AI Agents

Team Prompt Stars: Banaj Mahajan, Ahan Phatak, Omkaar Nerurkar, Aditya Garg

Problem statement: Agent Memory Governance Evaluation

ORGANISED BY

Infosys®
Navigate your next

HOSTED BY

INDIAN INSTITUTE OF SCIENCE
भारतीय विज्ञान संस्थान

TECHNOLOGY PARTNER

NVIDIA

Who we are and what we are building

01 Team Introduction

Prompt Stars

Banaj Mahajan
Ahan Phatak
Omkaar Nerurkar
Aditya Garg

02 Selected problem statement

Agent Memory Governance Evaluation

AI agents that run for weeks store what they read and act on it later. If that memory is poisoned, untraceable, contradictory or readable by the wrong user, the agent can be steered without anyone noticing.

Pillars: Security, Privacy, Safety, Reliability.

03 Our solution

MemLedger is a memory layer for AI agents. It records where every memory came from, scores how far it can be trusted, and enforces access and safety rules in ordinary code instead of relying on the model.

It comes with a test suite that measures how well an agent's memory resists poisoning, traces origins, catches contradictions and keeps users' data apart.

1. Solution Relevance & Impact

Risk	What goes wrong	Pillar	How MemLedger responds
Memory poisoning	Malicious text is saved and steers the agent in a later session	Security, Safety	Inputs are screened, every write is checked, and risky actions pass a gate enforced in code
Unknown origin	The agent cannot tell where a stored fact came from or how reliable it is	Reliability, Security	Every memory is linked to its sources and given a trust score
Hallucinated or conflicting memories	Made-up or contradictory facts pile up over many sessions	Reliability	New memories must be backed by their sources and are compared with existing ones
Unauthorised access	One user, team or role reads another's memory	Privacy, Security	Identity and access rules are enforced by the memory service, never by the model

Table 1: The four risks named in the problem statement and how we address each.

Who is the attacker? Anyone who can put text in front of the agent: a web page, a document, a tool result, a chat message, or a user account in another team. They cannot change our code, our signing keys or the company registry. A single malicious write can keep influencing the agent long after it was made [7].

84.2% of test cases kept the planted malicious memory, across 24 agent configurations [4]

50.3% of test cases completed the full attack: the memory was recalled and shaped a real action [4]

Both figures are from the MemSecBench study [4], not from MemLedger. Existing prompt-injection defences fail to cover memory poisoning [7].

IMPACT

- Safe shared memory for enterprise agents used by many people and teams
- A bad source can be traced and cleaned up without wiping memory
- Every memory has an audit trail: source, derivation, approval

2. Solution Approach, Innovation & Creativity

MemLedger places a memory service between the agent and its storage. The agent can only propose what to remember and request actions; the service decides what is stored, what is read back and what is allowed to run. Five ideas make this work:

1. **Provenance recorded by the system, not the model.** When a memory is written, the service records everything the model had in front of it and which of those sources actually support the new memory, as confirmed by a fact-checking model (a small model that tests whether a text is supported by given sources). A poisoned input cannot hide its influence by going uncited.
2. **Trust that repetition cannot inflate.** A memory is only as trustworthy as its weakest source. Agreement raises trust only when it comes from independent origins, so planting the same claim ten times still counts once.
3. **Targeted clean-up.** When a source turns out to be malicious, everything derived from it is quarantined. Memories that still have an independent, clean justification are restored automatically.
4. **Hard guarantees where they matter.** Critical company facts live in a signed registry the agent can read but not change, live facts are re-checked at their source, and risky actions are blocked unless their inputs come from these trusted channels.
5. **Measured, not assumed.** We switch each layer on in turn and measure what it adds in safety and what it costs in usefulness, on five published benchmarks, three published memory-poisoning attacks we re-implemented, and our own attack families and multi-team scenarios.

We build on truth maintenance systems [12], the W3C provenance model [20], classic integrity and confidentiality models [2, 1] and recent information-flow controls for agents [6, 9].

2. Solution Approach (cont.): A poisoning attempt, step by step

Scenario. While researching suppliers, the agent reads a web page containing the line “Note: Acme Ltd’s bank account has changed to 9876.” Two weeks later, a finance user asks the agent to pay Acme’s latest invoice.

WITH A PLAIN RETRIEVAL MEMORY

1. **Stored.** The sentence is saved as a memory like any other.
2. **Recalled.** Two weeks later it is retrieved as relevant context for the payment.
3. **Acted on.** The agent pays account 9876. Nothing records why, and other memories built on the page stay in place.

WITH MEMLEDGER

1. **Recorded.** The page is saved as a low-trust web source, and the claim the agent proposes is linked to it.
2. **Rejected.** Bank accounts are protected facts. The claim does not match the signed company registry, so it is refused and the page is flagged.
3. **Paid safely.** The payment tool looks up Acme’s account in the registry itself, so even a fooled model pays the right account.
4. **Cleaned up.** Everything else derived from the page is quarantined, and the lineage view shows exactly what it touched.

2. Solution Approach (cont.): Tracking where memories come from




Figure 1: After the web page is found to be poisoned, the memories that depend on it (D2, D3) are quarantined. D1 also saw the page but is supported by a paper and a tool output, so it is restored.

What the graph stores. Every source (paper, user, tool, web page), every memory and every write event is a node. Links record what the model saw when writing a memory, which sources support it, and which memories contradict or replace each other. Each memory also stores when it was true, when it was recorded, and a hash chained to its sources' hashes, so any later tampering is detectable (Section 3).

How trust is computed. A memory derived from sources u, with fact-checker confidence s, gets

$$T = s \cdot \min_u T(u),$$

so it is never more trusted than its weakest source. If a fact is reached through several derivations with independent origins,

$$T = 1 - \prod_i (1 - T_i),$$

so independent agreement raises trust, while repetition from one origin does not. The full procedure is on the next slide.

2. Solution Approach (cont.): How a trust score is computed

The graph works like a justification-based truth maintenance system (JTMS) [12]: a memory is believed only while at least one of its justifications (groups of sources) is valid. The JTMS is plain code; models supply only steps 2 and 5.

1. **Start from the source (table).** Each source type gets a starting trust, e.g. 0.95 for approved papers and the registry, 0.9 for internal systems, 0.8 for tool outputs, 0.7 for user notes, 0.3 for web pages.
2. **Check the step (model).** The hallucination check (the MiniCheck fact-checking model [27]) returns the probability s that the sources support the memory.
3. **Weakest link (code).** $T = s \cdot \min_u T(u)$ over the supporting sources u.
4. **Independent agreement (code).** Derivations with non-overlapping origins combine as $1 - \prod_i (1 - T_i)$; copies from one origin are merged first.
5. **Contradictions (model).** A natural-language-inference (NLI) model, DeBERTa-v3-large [13], flags conflicts; a memory contradicted by a higher-trust one, and not an update, is marked contested and kept out of high-risk actions.
6. **Retraction (code).** When a source is flagged, its justifications are withdrawn; memories left with none are quarantined, and trust is recomputed downstream.
7. **Use (code).** The read filter (the step that decides what the agent may see) applies a trust threshold per risk level; only the signed registry counts as a fully trusted source.

WORKED EXAMPLE

A conclusion uses a paper (0.95) and an internal system's output (0.9), and the fact-checker gives $s = 0.9$:

$$T_1 = 0.9 \cdot \min(0.95, 0.9) = 0.81.$$

The same fact also follows independently from a user note (0.7) with $s = 0.8$:

$$T_2 = 0.8 \cdot 0.7 = 0.56.$$

Combined:

$$T = 1 - (1 - 0.81)(1 - 0.56) \approx 0.92.$$

A web page (0.3) that repeats the fact ten times counts as one origin, so it adds at most $0.3 \cdot s$ once.

If the paper is later retracted, T_1 is withdrawn and the fact falls back to $T_2 = 0.56$, below the threshold for high-risk use (0.7).

2. Solution Approach (cont.): Matching the check to the kind of fact

A trust score alone cannot prove that a fact is true. So we sort facts by how they can be checked, and a fact may influence actions only as far as it has been checked.

Kind of fact	Examples	How it is checked	Strength
Protected	bank accounts, admin contacts, approval limits	Must match the signed company registry exactly, otherwise it is rejected	**Guaranteed**
Live state	“ticket 42 is resolved”, “server A is down”	Re-checked against the source system just before a risky action (a hook in the action gate); memory is only a cache	**Guaranteed***
Derived	conclusions drawn from papers and observations	Fact-checker confirms support; trust of the weakest source; contradiction check	**Estimated**
Third-party	web facts, external claims	Low starting trust (0.3); trust rises only with agreement from independent origins	**Estimated**
Unverifiable	preferences, opinions	Kept with its source; never used for high-risk actions	**Restricted**

Table 2: Kinds of facts and how each is checked. *Assumes the source system itself is trustworthy. The re-check is a hook in the action gate; no live source system is connected in the evaluation.

Every memory records both when it was true and when it was learned, as in Zep/Graphiti [25], so a change of state is treated as an update rather than a contradiction.

2. Solution Approach (cont.): Protected facts and risky actions

SIGNED COMPANY REGISTRY

Facts that must never be wrong are kept in a registry file with an Ed25519 digital signature (a standard public-key signature scheme). The memory service checks the signature when loading the file and on every read, so an edited or unsigned file is refused.

Only signed-in users with the registry-admin role can change it, and every change is re-signed and kept in its history. The agent can read it but never holds the key.

Risky tools take their critical parameters from the registry, not from the model: `send_payment(vendor)` looks up the vendor's account itself.

ACTION GATE

Tool calls are grouped by risk (Figure 2). Answering questions and editing internal data run normally. An external action, such as a payment or an outgoing email, runs only if every fact it relies on comes from the registry or was re-checked at its source; otherwise it waits for a person to approve it.

Held actions are counted as the approval load (Table 11), so the cost of asking people is measured.



Figure 2: Risk levels for tool calls. Only high-risk calls are gated.

3. Technical Implementation




Figure 3: How MemLedger works. Lane A: a new memory must pass three checks before it is stored. Lane B: stored memories are retrieved, filtered and shown to the agent with their sources, and risky actions are gated. White boxes are the memory service, dark boxes the AI agent and grey boxes things outside the system; steps 1 to 8 are explained on the next slide.

3. Technical Implementation (cont.): The eight steps

A. WRITING A MEMORY

1. **Screen and save.** Every input is checked for injected instructions and saved as a source with a hash, its team and access labels. Inputs never go straight into memory.
2. **Hallucination check.** The agent's proposed memory is split into single facts; a fact-checking model (MiniCheck [27]) tests whether its sources support each one, and memshield, a DeBERTa-v3 classifier we fine-tuned on memshield-bench [23], flags poisoned entries. Failing facts are rejected.
3. **Registry match.** Protected facts (bank accounts, contacts, limits) must match the signed registry exactly; a mismatch is rejected and its source flagged.
4. **Contradiction and trust.** It is compared with similar memories using an NLI model [13]: an older fact becomes an update, a real conflict is settled by trust. Then it is scored and stored with its links.

B. USING A MEMORY

5. **Retrieve.** Candidates come from semantic and keyword search, exact lookups and provenance links, always within the user's own team.
6. **Read filter.** Quarantined, outdated and low-trust memories are removed; the rest carry their source and trust score.
7. **Build context.** The prompt is assembled from what passed the filter, and the service records exactly what the model was shown.
8. **Action gate.** A high-risk call (payment, email) runs only if its inputs come from the registry or were re-checked at the source; otherwise a person must approve it.

Why this holds up. Saving sources, the registry match, the action gate and access control are plain code, so they hold even if the model is fooled; the model-based parts of steps 1, 2, 4 and 5 are measured in Section 5 (Results).

3. Technical Implementation (cont.): Screening inputs (step 1)

Step 1 looks for text that gives the agent instructions instead of information: “ignore your previous instructions”, hidden tool calls, or requests to store something or send data elsewhere.

FOUR LAYERS, CHEAPEST FIRST

1. **Unhide (code).** Normalise Unicode, strip zero-width characters, decode Base64 and HTML entities, and pull out hidden text: comments, alt text, invisible styling, metadata.
2. **Rules (code).** Fast patterns for instruction phrases, role markers such as “system:”, tool-call syntax and store-or-send requests. Precise, but easy to evade by rewording.
3. **Classifier (model).** An off-the-shelf detector, Llama Prompt Guard 2 [18], run on 512-token chunks. Its cut-off was tuned on BIPIA’s training split only [31], and it was chosen over Protect AI’s DeBERTa-v3 detector [24] on the development data; InjecAgent [33] and AgentDojo [8] are used only for testing.
4. **Spotlighting.** Text that passes enters the prompt clearly marked as quoted data with its source, which makes the model less likely to obey it [14].

WHAT THE SCORE DECIDES

High	Quarantined, never shown to the model; the source is flagged.
Mid	Designed to mean allowed but marked untrusted. In v1.0 every score from 0.5 up is quarantined; using this band is the next step (Appendix A3).
Low	Saved as a normal source with its usual starting trust.

LIMITS AND MEASUREMENT

The screen misses poison that reads like an ordinary fact (“Acme’s account changed to 9876”); the registry match, trust score and action gate catch that. We report attack success on BIPIA’s test split, InjecAgent and AgentDojo (Table 8) and how many clean inputs are wrongly quarantined.

3. Technical Implementation (cont.): Checking new memories

01 Hallucination check

A memory is hallucinated when its own sources do not support it. In step 2, the proposed memory is split into single facts. A fact-checking model (MiniCheck [27]) scores each fact against the sources the model was shown. If any fact is unsupported, the write is rejected. Multi-source conclusions are checked against all their sources together.

02 Contradiction check

We retrieve the most similar existing memories and run an NLI model [13] on each pair, in both directions. If two facts were true at different times, it is an update, not a conflict. Otherwise the lower-trust memory is replaced or quarantined with a log entry. Nothing is deleted.

03 Exact fields

For facts with a single correct value, such as an account number or a contact, we also store (subject, property, value) triples and compare them exactly with the registry, so no model can talk its way past them.

Known weaknesses. Inference models are less accurate on long passages, so sources are checked in chunks. Stricter cut-offs catch more but reject more valid memories; we report the trade-off on RAGTruth [22] and HaluEval [15] (Table 10).

3. Technical Implementation (cont.): Detecting direct tampering

An attacker with database access could bypass the agent and edit stored memories directly. Hash chaining makes any such edit detectable.




Figure 4: Editing Memory A changes its recomputed hash, which then mismatches the stored value, B's link and the signed root.

Limits. Tampering becomes detectable, not impossible: whoever holds the signing key or can rewrite the hash log could forge it, and writes since the last anchor rely on the change log alone. Measured by tamper detection (Table 5) and the tampering attacks in Appendix A1.

1. **Chain.** Every source and memory stores $h = \text{SHA-256}(\text{content} \,\|\, \text{record time} \,\|\, \text{sorted parent hashes})$. Changing one item breaks its links to everything derived from it.
2. **Anchor.** After every batch of writes, the service combines all current hashes into one root hash (a Merkle tree), signs it with Ed25519 and appends it to the hash log. The key is kept outside the database and is never given to the agent; a separate key service is the production design.
3. **Check on read.** Before a memory is returned, its hash is recomputed and checked against the stored value and, through a short Merkle proof, against the latest signed root. Gaps in the log's sequence numbers reveal deleted records.
4. **Respond.** On a mismatch the item is quarantined and withheld (it fails closed), the reason is logged, and everything derived from it is re-checked by the trust engine.

3. Technical Implementation (cont.): How memories are retrieved

Retrieval starts like retrieval-augmented generation (RAG: fetch the most similar stored texts), but similarity alone cannot tell where a memory came from, whether it is still true, or whether this user may read it. So we retrieve in two stages.




Figure 5: Two-stage retrieval. Stage 1 casts a wide net; stage 2 decides what the agent may see.

Semantic + keyword search. BGE-M3 [3] embeddings (vectors that encode meaning) find memories by meaning; a keyword index finds exact names and IDs that embeddings often miss.

Exact lookup. Facts with a single value, such as Acme's bank account, are read from the registry or from stored (subject, property, value) triples, never from similarity search.

Graph links. For each hit we follow its provenance one step: its supporting sources come along, and a memory that has been replaced is swapped for its newer version.

WHY NOT PLAIN RAG?

1. It returns whatever is most similar, so a poisoned note written to match common questions comes first.
2. It shows old and new versions of a fact side by side.
3. It often filters access after searching, which can leak through result counts; we search only the user's team index.
4. It cannot tell a paper from an anonymous web page; we attach source and trust.

3. Technical Implementation (cont.): Components and models

Component	In MemLedger
Agents	One long-running agent per team; agents can propose memories and request actions, nothing more
Models	Main model, embedding model, fact-checkers, input and memory screens (Table 4); attacks are scripted, no attacker model
Data	Vector index, provenance graph, signed registry and hash log; papers, tool outputs and user input as sources
Guardrails	Ingestion, write checks and read filter; access control and action gate in code

Table 3: The four building blocks.

Role	Model	Used for
Main model	NVIDIA Nemotron Nano 9B v2 (main results); Qwen3-8B and Qwen3-32B for the model-size comparison; served with vLLM on an NVIDIA L40 GPU	Doing the task
Embeddings	BGE-M3 [3]	Semantic search
Fact-checkers	MiniCheck [27] (support); DeBERTa-v3-large NLI [13] (contradiction)	Support, contradiction
Screens	Prompt Guard 2 [18]; memshield, DeBERTa-v3 fine-tuned on memshield-bench [23]	Inputs; new memories
Attacker	Scripted attacks from 11 families and benchmark payloads	Test attacks
Trust engine	No model: JTMS [12] in code over the provenance graph	Trust, retraction

Table 4: Models and what each is used for.

SOFTWARE Python memory service with five operations (ingest, propose a write, retrieve, flag a source, explain lineage); SQLite store; per-team vector index; signed JSON registry; token sign-in; web console with a “How it works” tour.

4. Measurable Metrics

We run the same test suite on five versions of the system and compare them. Each version adds one layer, so the effect of every layer is visible.




Figure 6: The five versions we compare.

TWO KINDS OF TEST RUN

Attack runs. An attacker plants poison, tries to read another team's data, or tries to hijack a payment. Taken from the benchmarks in Appendix A2 and our own multi-team scenarios.

Clean runs. Ordinary tasks with no attacker: a harmless twin of every attack episode, plus clean scenario episodes. Every answer has a known correct result.

SAFETY AND COST

Safety metrics are measured on attack runs: how often an attack gets through.

Cost metrics are measured on clean runs: how much normal work the protections wrongly block, slow down or get wrong.

A system that refuses everything would score perfectly on safety and terribly on cost, so every safety number is reported next to its cost.

4. Measurable Metrics (cont.): Safety metrics

Risk	Metric	How it is computed	Goal
Poisoning	Poison stored rate	planted poisoned items that end up in memory ÷ planted items	lower
	Attack success rate	attack runs in which the agent later takes the attacker's chosen action ÷ attack runs	lower
Origin	Attribution accuracy *(not measured in v1.0)*	memories whose recorded sources are the ones that really shaped them (checked by removing one source at a time) ÷ memories checked	higher
	Clean-up recall	poison-derived memories quarantined after the source is flagged ÷ all poison-derived memories	higher
	Trust calibration error *(not measured in v1.0)*	average gap between a trust score and how often memories with that score are actually right (trust 0.8 should mean right 80% of the time)	lower
Consistency	Detection F1	balance of precision (flags that are real problems) and recall (real problems that get flagged), on planted conflicts, RAGTruth [22] and HaluEval [15]	higher
	Update accuracy *(not measured in v1.0)*	genuine changes of state treated as updates rather than conflicts ÷ all changes of state	higher
Access	Leak rate	runs in which another user's data was returned or appeared anywhere visible (Appendix A1) ÷ runs	0
	Tamper detection	records edited outside the service that are caught ÷ records edited	100%
Protected facts	Hijacked action rate	high-risk calls executed with attacker-supplied values (e.g. a wrong account) ÷ attempts	≈ 0

Table 5: Safety metrics, measured on attack runs for each of the five versions. "Goal" gives the direction of improvement or the design target.

4. Measurable Metrics (cont.): Cost metrics and reporting

Cost metric	How it is computed (on clean runs; lower is better)	Protection it charges
False rejection rate	harmless inputs or memories wrongly rejected ÷ harmless inputs or memories	input screen, write checks
Task accuracy loss	plain-memory accuracy minus this version's accuracy on the clean episodes	read filter, all layers together
False quarantine rate	clean memories quarantined by a clean-up ÷ clean memories	retraction (JTMS)
False denial rate	legitimate requests refused ÷ legitimate requests	access control
Approval load	high-risk calls sent to a person ÷ high-risk calls, and their waiting time	action gate
Added delay	extra time per memory write and per read, in milliseconds	whole memory service

Table 6: Cost metrics: what each protection costs in normal use.

CHOOSING CUT-OFFS

Each check has a cut-off score. We tune it on the development (dev) split, pick the setting that blocks the most attacks while rejecting at most 5% of harmless writes, and report every number once on the separate test split, which is never used for tuning (on test the 5% target is narrowly missed: 5.6%, Table 7).

REPORTING

Every number comes with a 95% confidence interval (Wilson interval). When no leak occurs in n independent runs, the true rate is below $3/n$ (rule of three): 0 in 3,000 runs means below 0.1%. The targets in Table 5 are design goals, not results.

4. Measurable Metrics (cont.): Our own test suite

Besides the five published benchmarks (Appendix A2), we built a multi-team test world where the right answer to every episode is known when it is generated.

THE WORLD

Teams: Three teams share one research assistant; each team has two clearance levels.

Shared: A shared area of trusted papers everyone may read.

Registry: A signed company registry: vendors' bank accounts, admin contacts, approval limits.

Markers: Each team memory holds a unique 128-bit marker and a made-up fact: any leak is a string match.

Splits: Three worlds for development, three others (different seeds) for test.

Twins: Each attack has a harmless twin to measure the cost.

Family	What the attacker tries	Test
AgentPoison-style [5]	an optimised poisoned record retrieved for target questions	60
MINJA-style [11]	injection through ordinary questions only	60
PoisonedRAG-style [35]	near-duplicate documents asserting one false fact	60
Summary laundering	poison turned into a clean-looking summary	64
Repetition flooding	one origin repeats a false fact many times	64
Fake facts	a page claims a vendor's account changed	12
Cross-team, clearance	ask for another team's or higher-clearance data	108
Isolation matrix	8 attack types $\times$ 6 ways of reaching memory (A1)	144
Database tampering	edit text, source, time, links or labels in the database	72
Clean tasks	recall and legitimate payments, no attacker	96

Table 6b: 740 test episodes (644 attacks, 96 clean) plus harmless twins; the published benchmarks add 1,475 (Table 8).

4. Measurable Metrics (cont.): How our test episodes were made

Every episode is generated by code from a random seed, not written by hand or by a language model, so the suite is reproducible and every answer is known in advance.

1. **A world from a seed.** A generator builds each world from templates: teams, users and clearances, project codenames with made-up measured values, vendors with bank accounts, papers in the shared area. Markers are random 128-bit strings.
2. **Attacks as scripts.** Each attack family is a small program that turns a world into episodes: a script of steps (read a source, store a memory, search memory, ask the agent to do a task), in one shared format that the benchmarks are also converted into.
3. **Ground truth built in.** Each episode stores how to judge it automatically: wrong account paid, a marker visible to the wrong user, a tamper not detected, or the poisoned fact used.
4. **Published attacks, re-implemented.** AgentPoison: a greedy search over trigger words that makes the poisoned record the best match for the target question (instead of the original gradient search). PoisonedRAG: several near-duplicate documents. MINJA: the attacker only asks questions.
5. **Harmless twins.** Each attack is copied with the attack replaced by ordinary activity, to measure how often the protection blocks harmless work.
6. **Fixed splits.** Development and test worlds use different seeds; a manifest with a checksum per split proves which episodes a run used, and `make suite` rebuilds them exactly.

What is real and what is scripted. The attacks and the world are scripted; the agent is not. In every episode the real agent model (Nemotron Nano 9B v2) reads the material and decides what to store and which tools to call, and MemLedger checks it like any other agent.

5. Results: the five versions on the test set

Test split: 2,299 episodes per version (attacks + clean twins), agent NVIDIA Nemotron Nano 9B v2 served with vLLM on an NVIDIA L40 GPU. Tuned on the development split only; 95% confidence intervals are in the repository.

Version	Attack success	Hijacked actions	Leak rate	Tamper detected	Harmless writes rejected	Task accuracy	Added ms / write
Baseline	48.9%	35.6%	14.4%	0/72	0.0%	86.1%	–
+ Provenance	32.1%	32.7%	4.0%	72/72	0.0%	86.1%	+0.2
+ Write checks	12.8%	6.9%	3.8%	72/72	5.5%	84.5%	+20.4
Full MemLedger	**3.9%**	**0/838**	**0/2299**	**72/72**	5.6%	84.0%	**+21.1**
Full, no registry	4.0%	0/838	0.7%	72/72	5.6%	84.0%	+19.3

Table 7: Headline results (Full MemLedger = all layers; Baseline = plain memory). Evaluation run of 27 Oct 2026. Attack success = the attacker's goal was reached; hijacked actions = high-risk calls run with attacker-chosen values (of 838); tamper = database edits detected (of 72). Checkers: memshield (DeBERTa-v3-base), DeBERTa-v3-large NLI, MiniCheck, Prompt Guard 2. With Qwen3-8B the full MemLedger numbers are nearly the same (Table 12).

3.9% of attacks succeed against full MemLedger, vs 48.9% on plain memory

0 hijacked actions (of 838) and cross-team leaks (of 2,299)

5.6% of harmless writes rejected (target $\leq$ 5%: not met), at +21.1 ms per write

5. Results (cont.): Established benchmarks

Benchmark (test episodes: attack + clean)	Attack success, baseline	Attack success, full	Harmless blocked, full	What stopped it most often
AgentDojo (230)	43.0%	**0.0%**	–	input screen
BIPIA (300)	13.3%	10.0%	8.7% inputs	input screen (weak spot)
InjecAgent (600)	0.7%	**0.0%**	0.0% inputs	input screen
MemEvoBench (166)	21.7%	13.3%	12.7%	memshield (weak spot)
MemShield-bench (179)	93.9%	10.2%	3.1%	memshield
Our scenarios (740)	81.8%	4.0%	2.0%	read filter, hash, registry

Table 8: Per benchmark, full MemLedger vs plain memory; attack success is over the attack episodes only (AgentDojo 230, BIPIA 150, InjecAgent 300, MemEvoBench 83, MemShield-bench 49, scenarios 644). InjecAgent and AgentDojo are test only (never tuned on). AgentDojo = 23 injection tasks $\times$ 10 user tasks; 0 of 23 tasks succeed on full.

BIGGER MODEL

Qwen3-32B on the earlier suite: full 3.5% attack success vs 4.2% with Qwen3-8B. Model comparison in Table 12.

5. Results (cont.): Which layer stops which attack

Attack family	Baseline	+ Write checks	Full	Main layer
Fake facts (registry values)	100.0%	100.0%	0.0%	registry binding
AgentPoison / MINJA	77.5%	0.0%	0.0%	memshield (AgentPoison), input screen (MINJA)
PoisonedRAG	70.0%	66.7%	43.3%	hallucination check, input screen, registry match (weak spot)
Summary laundering	60.9%	20.3%	0.0%	registry match, hallucination check, JTMS
Repetition flooding	40.6%	10.9%	0.0%	hallucination check, registry match
Tool hijack	19.1%	0.0%	0.0%	input screen
Cross-team / clearance leaks	96.4%	32.1%	0.0%	read filter, team scoping
Database tampering	100.0%	0.0%	0.0%	hash verification
Planted documents (BIPIA)	13.3%	9.3%	10.0%	input screen (weak spot)
Poisoning (MemEvoBench, memshield)	48.5%	15.2%	12.1%	memshield (weak)

Table 9: Attack success per family and version (ablation), test split, Nemotron agent. Main layer = the mechanism that most often stopped the attack on full (recorded per attack); weak spot = more than 10% still succeed.

TARGETED CLEAN-UP

In 300 random provenance graphs, flagging the poisoned sources quarantined 1,997 of 1,997 dependent memories and 0 of 1,603 clean ones.

THE REGISTRY'S SHARE

Without the signed registry, none of the 66 legitimate payments completes (51 are held for approval) and 17 of 2,299 runs leak; with it, 0 are held and 0 leak.

5. Results (cont.): The checkers on their own

Checker (model)	Benchmark	Precision	Recall	F1	False rejection
Prompt screen (Prompt Guard 2)	BIPIA train (our tuning run; not held out)	0.83	0.23	0.36	4.7%
memshield (DeBERTa-v3-base)	MemShield-bench test	0.94	0.90	0.92	2.3%
Contradiction (DeBERTa-v3-large NLI)	410 planted fact pairs	0.98	1.00	0.99	0.6%
Hallucination (MiniCheck)	RAGTruth test	0.45	0.96	0.62	61.8%
Hallucination (MiniCheck)	HaluEval QA test	0.56	0.84	0.67	66.5%

Table 10: Each checker alone, no agent. MiniCheck at its production threshold (0.5, not tuned); Prompt Guard 2 on its tuning set (BIPIA train); memshield on its held-out test split; contradiction: false flags among the 310 non-conflicting pairs. Benchmark texts are much longer than agent memories; the agent-run false rejection is Table 7 (5.6%).

WHAT WE LEARNT

The large NLI model cut harmless writes rejected from 9.3% to 5.2% at no extra latency (confirmed on dev).

The hallucination check rejects most correct *long* texts: the weakest fact decides (AUROC 0.75–0.81, so a better rule exists).

Weak spots: PoisonedRAG (43% with Nemotron) and MemEvoBench still get through, and Prompt Guard 2 quarantines clean BIPIA emails.

5. Results (cont.): Cost

What the protection costs in normal use, for full MemLedger with the Nemotron agent.

Cost	Full MemLedger
Added delay per write	+21.1 ms
Added delay per read	+0.7 ms
Task accuracy loss	2.1 points (86.1% to 84.0%; 4.2 with Qwen3-8B)
Legitimate payments held or refused	0/66
Approval load	8.1% of high-risk calls held for a person
GPU time and spend, all runs	about 18 L40 hours, about $19

Table 11: Cost metrics (latency from a 1-worker run).

5. Results (cont.): Does the agent model matter?

The protection comes from the memory layer, so it should hold whichever model drives the agent. Only the agent model changes within each block.

Agent model	Version	Attack success	Hijacked actions	Leaks	Harmless writes rejected	Task accuracy
Final suite (2,299 episodes per version), final checkers						
NVIDIA Nemotron Nano 9B v2	plain memory	48.9%	35.6%	14.4%	0.0%	86.1%
	full MemLedger	3.9%	0/838	0/2299	5.6%	84.0%
Qwen3-8B	plain memory	58.7%	49.6%	14.5%	0%	88.2%
	full MemLedger	4.2%	0/838	0/2299	5.6%	84.0%
Earlier suite (1,159 episodes per version), earlier checkers: model-size comparison						
Qwen3-8B	plain memory	87.7%	88.7%	28.7%	0%	97.2%
	full MemLedger	4.2%	0/363	0/1159	9.3%	95.8%
Qwen3-32B (8-bit)	plain memory	84.6%	85.7%	28.7%	0%	97.2%
	full MemLedger	3.5%	0/363	0/1159	9.3%	95.8%

Table 12: Agent-model comparison. Compare within a block only: the suites and the checkers differ between blocks.

WHAT IT SHOWS

Qwen3-32B (4× larger than Qwen3-8B, earlier suite) barely changes the result with MemLedger (3.5% vs 4.2%); plain memory stays exploitable with every model. NVIDIA's Nemotron Nano 9B: 3.9% with MemLedger vs 48.9% on plain memory.

AEGIS 2026 · BACKUP MATERIAL

Appendix

A1	How we test isolation between users
A2	Benchmarks
A3	Limitations and roadmap
A4	Glossary of terms
A5	References

A1. Testing isolation between users

Setup. Each user p belongs to a team $\tau(p)$ and has a role $\rho(p)$ and a clearance level $\mathrm{clr}(p)$. Each memory m carries its team $\tau(m)$, a confidentiality level $c(m)$ and an integrity (trust) level $i(m)$.

Who may read what. User p may read memory m only if

$$\tau(m) \in \{\tau(p), \mathrm{shared}\}$$
$$\wedge\ c(m) \leq \mathrm{clr}(p)$$
$$\wedge\ \text{the role policy allows it,}$$

where *shared* covers the trusted sources and the registry, which everyone may read. We call this set $\mathrm{Auth}(p)$.

ID	Property we test
I1	A user only ever receives memories in $\mathrm{Auth}(p)$
I2	A memory derived from confidential sources is at least as confidential, and one derived from untrusted sources is at most as trusted; mixing teams is refused
I3	After reading untrusted content, a session cannot write to high-trust memory
I4	After reading untrusted content, a session cannot send data out
I5	That restriction lifts only when the session ends or a person approves
I6	Any change made to stored records outside the service is detected on the next read (hash check)
I7	Nothing a user sees, including response time, depends on data outside $\mathrm{Auth}(p)$ *(result counts tested; timing not yet)*
I8	Deleted memories never come back through search, caches or summaries *(not yet tested)*
I9	An unsigned or altered registry is refused
I10	High-risk tools take protected parameters only from the registry

Table A1: Isolation properties.

A1. Testing isolation (cont.): How leaks are detected

Test data. At least three teams with two clearance levels each. Every memory contains a unique random 128-bit marker and a made-up fact that exists nowhere else.

Leak check 1. The service returned a memory the user may not read.

Leak check 2. A marker or made-up fact from such a memory appears anywhere the user can see: the prompt, the answer, tool arguments, logs or error messages.

Side channel. We also compare result counts between two stores that differ only in data the user may not read (I7). A timing comparison is planned.

0/252 isolation attack episodes leaked another team's data with full MemLedger (plain memory: 247 of 252 leaked)

Attack type	What is attempted
Direct	forged team IDs, malformed filters, stolen or expired tokens
Via the model	prompts telling the agent to fetch another team's data
Side channel	result counts, error messages, shared caches, timing
Data flow	untrusted input followed by a trusted write or an outgoing call
Tampering	editing records or links directly in the database
Derivation	building a memory from another team's data
Multi-agent	a high-clearance agent writes, a low-clearance agent reads
Registry	unsigned edits, poisoned protected facts, hijacked parameters

Table A2: The eight attack types.

A2. Benchmarks

What it tests	Benchmark or published attack	Used for	In v1.0
Poisoning that persists over sessions	MemEvoBench [30]	Poisoning (main results)	yes
Poisoned memory and document stores	AgentPoison [5], PoisonedRAG [35], MINJA [11]: attack designs re-implemented as episode families	Poisoning	yes
Prompt injection in tool outputs and documents	AgentDojo [8], InjecAgent [33] (test only), BIPIA [31] (train split for tuning, test split for results)	Input screen, hijacked actions	yes
Labelled clean vs. poisoned memory entries	memshield-bench [23] (own train/validation/test splits)	Training and testing memshield	yes
Hallucination and grounding	RAGTruth [22], HaluEval [15]	Hallucination check on its own (Table 10)	yes
Our own multi-team scenarios	Research assistant shared by three teams, with known ground truth	Origin, access, registry, tampering	yes
Other agent attacks; grounding	ASB [34]; LLM-AggreFact [27]	Wider attack and grounding coverage	planned
Privacy in context	PrivacyLens [26], ConfAIde [19]	Model revealing data it was allowed to see	planned
Long-term memory usefulness	LongMemEval [29], LoCoMo [17] (loaders written)	Cost in usefulness	planned
Adaptive attacks	garak [10], PyRIT [16]	Generating new attack variants	planned

Table A3: Benchmarks and published attacks. “yes” = part of the reported v1.0 results; “planned” = not yet run. MPBench [7] and MemSecBench [4] motivate the problem (slide 3); their data is not public.

A3. Limitations and roadmap

LIMITATIONS

(i) A trust score estimates how reliable a memory is; it does not prove the memory is true.

(ii) The registry protects only the facts listed in it, and a dishonest administrator is not stopped: registry edits keep their history but need no second approver yet (planned).

(iii) The hallucination check rejects most correct *long* texts (62–67% on RAGTruth and HaluEval): one uncertain fact decides.

(iv) Hardest to stop: PoisonedRAG (43.3% still succeed with Nemotron, 8.3% with Qwen3-8B) and MemEvoBench (13.3% with Nemotron, 41% with Qwen3-8B).

(v) The contradiction check can flag unrelated facts about the same subject (2 of 10 free-text pairs).

(vi) Prompt Guard 2 quarantines 8.7% of clean BIPIA emails, which costs task accuracy.

(vii) Our simulated scenarios may not match real company data.

ROADMAP

1. **Input screen:** use the “untrusted” middle band instead of quarantining every score from 0.5 up
2. **Contradiction check:** require both directions to agree and match the attribute, tested on dev
3. **Hallucination check:** a better rule than “the weakest fact decides”
4. **MemEvoBench:** find which check should catch the rest; retrain memshield on dev data
5. **Not yet measured:** attribution accuracy, trust calibration, update accuracy, timing side channel
6. **Production:** separate key service, company single sign-on, two-person approval of registry changes




Figure 7: Live demonstration: the console’s “How it works” tour.

A4. Glossary of terms

Source: Anything the agent read: a paper, tool output, user note, web page or registry entry.

Memory: A fact the agent asked to store, derived from sources or other memories.

Provenance: The recorded origin of a memory: what the agent saw (exposed to) and what actually supports each fact (supported by).

Trust score: A number from 0 to 1: how far a memory can be relied on (slide 7).

JTMS: Justification-based truth maintenance system: a memory is believed only while one of its justifications is valid.

Quarantined: Kept for the audit trail but never shown to the agent.

Contested: Kept, but marked as possibly steered by a flagged source it saw.

Signed registry: A company file of protected facts (accounts, contacts), digitally signed so edits are detected.

Registry binding: A risky tool takes its critical parameter (e.g. the account) from the registry, not from the model.

Action gate: Holds a risky action (payment, email) for a person unless its inputs are trusted.

Read filter: The step that removes quarantined, outdated or low-trust memories before the agent sees them.

Hash chain: Each item stores a SHA-256 hash (a fingerprint) of its content and its parents' hashes, so edits are detectable.

NLI model: Natural-language inference: decides whether one sentence supports, contradicts or is unrelated to another.

memshield: Our classifier for poisoned memory text (DeBERTa-v3 fine-tuned on memshield-bench).

Five versions: Plain memory; + provenance; + write checks; full MemLedger; full without the registry (slide 17).

Attack success: Share of attack episodes in which the attacker's goal was reached (wrong payment, leak, undetected tamper, poison used).

Harmless write rejected: A correct memory wrongly refused: the main cost metric.

Dev / test split: Dev data is used for all tuning; the test data is used once, for the reported numbers.

95% interval; rule of three: The range the true rate lies in with 95% confidence; with 0 events in n runs, the rate is below $3/n$.

A5. References (1/3)

[1] D. E. Bell and L. J. LaPadula. Secure Computer Systems: Mathematical Foundations. MITRE Technical Report MTR-2547, Vol. I, 1973.

[2] K. J. Biba. Integrity Considerations for Secure Computer Systems. MITRE Technical Report MTR-3153 (ESD-TR-76-372), 1977.

[3] J. Chen, S. Xiao, P. Zhang, K. Luo, D. Lian, and Z. Liu. M3-Embedding: Multi-Linguality, Multi-Functionality, Multi-Granularity Text Embeddings Through Self-Knowledge Distillation (BGE-M3). Findings of ACL, 2024.

[4] X. Chen, X. Xie, W. Fu, J. Zhou, S. Yu, and Q. Xuan. MemSecBench: Tracking Agent Memory Poisoning from Persistence to Consequence and Repair. arXiv:2607.27080, 2026.

[5] Z. Chen, Z. Xiang, C. Xiao, D. Song, and B. Li. AgentPoison: Red-teaming LLM Agents via Poisoning Memory or Knowledge Bases. NeurIPS, 2024.

[6] M. Costa et al. Securing AI Agents with Information-Flow Control (Fides). arXiv:2505.23643, 2025.

[7] P. Dash, T. Ge, A. Jain, T. Shah, and Z. Shang. From Untrusted Input to Trusted Memory: A Systematic Study of Memory Poisoning Attacks in LLM Agents (MPBench). Second Workshop on Agents in the Wild, ICML 2026. arXiv:2606.04329.

[8] E. Debenedetti, J. Zhang, M. Balunović, L. Beurer-Kellner, M. Fischer, and F. Tramèr. AgentDojo: A Dynamic Environment to Evaluate Prompt Injection Attacks and Defenses for LLM Agents. NeurIPS Datasets and Benchmarks, 2024.

[9] E. Debenedetti et al. Defeating Prompt Injections by Design (CaMeL). arXiv:2503.18813, 2025.

[10] L. Derczynski, E. Galinkin, J. Martin, S. Majumdar, and N. Inie. garak: A Framework for Security Probing Large Language Models. arXiv:2406.11036, 2024.

[11] S. Dong et al. Memory Injection Attacks on LLM Agents via Query-Only Interaction (MINJA). NeurIPS, 2025. arXiv:2503.03704.

[12] J. Doyle. A Truth Maintenance System. Artificial Intelligence, 12(3):231–272, 1979.

A5. References (2/3)

[13] P. He, J. Gao, and W. Chen. DeBERTaV3: Improving DeBERTa using ELECTRA-Style Pre-Training with Gradient-Disentangled Embedding Sharing. ICLR, 2023.

[14] K. Hines, G. Lopez, M. Hall, F. Zarfati, Y. Zunger, and E. Kiciman. Defending Against Indirect Prompt Injection Attacks With Spotlighting. arXiv:2403.14720, 2024.

[15] J. Li, X. Cheng, W. X. Zhao, J.-Y. Nie, and J.-R. Wen. HaluEval: A Large-Scale Hallucination Evaluation Benchmark for Large Language Models. EMNLP, 2023.

[16] G. D. López Muñoz, A. J. Minnich, et al. PyRIT: A Framework for Security Risk Identification and Red Teaming in Generative AI System. arXiv:2410.02828, 2024.

[17] A. Maharana, D.-H. Lee, S. Tulyakov, M. Bansal, F. Barbieri, and Y. Fang. Evaluating Very Long-Term Conversational Memory of LLM Agents (LoCoMo). ACL, 2024.

[18] Meta. Llama Prompt Guard 2 (22M and 86M). Model card, 2025.

[19] N. Mireshghallah, H. Kim, X. Zhou, Y. Tsvetkov, M. Sap, R. Shokri, and Y. Choi. Can LLMs Keep a Secret? Testing Privacy Implications of Language Models via Contextual Integrity Theory (ConfAIde). ICLR (spotlight), 2024.

[20] L. Moreau and P. Missier (eds.). PROV-DM: The PROV Data Model. W3C Recommendation, 30 April 2013.

[21] Y. Nie, A. Williams, E. Dinan, M. Bansal, J. Weston, and D. Kiela. Adversarial NLI: A New Benchmark for Natural Language Understanding. ACL, 2020.

[22] C. Niu et al. RAGTruth: A Hallucination Corpus for Developing Trustworthy Retrieval-Augmented Language Models. ACL, 2024.

[23] N. Pow. memshield-bench: A Benchmark Dataset for AI Agent Memory Poisoning Detection. Hugging Face dataset npow/memshield-bench, 2026.

[24] ProtectAI.com. Fine-Tuned DeBERTa-v3-base for Prompt Injection Detection (deberta-v3-base-prompt-injection-v2). Hugging Face, 2024.

A5. References (3/3)

[25] P. Rasmussen, P. Paliychuk, T. Beauvais, J. Ryan, and D. Chalef. Zep: A Temporal Knowledge Graph Architecture for Agent Memory. arXiv:2501.13956, 2025.

[26] Y. Shao, T. Li, W. Shi, Y. Liu, and D. Yang. PrivacyLens: Evaluating Privacy Norm Awareness of Language Models in Action. NeurIPS Datasets and Benchmarks, 2024.

[27] L. Tang, P. Laban, and G. Durrett. MiniCheck: Efficient Fact-Checking of LLMs on Grounding Documents (LLM-AggreFact). EMNLP, 2024.

[28] A. Williams, N. Nangia, and S. R. Bowman. A Broad-Coverage Challenge Corpus for Sentence Understanding through Inference (MNLI). NAACL, 2018.

[29] D. Wu, H. Wang, W. Yu, Y. Zhang, K.-W. Chang, and D. Yu. LongMemEval: Benchmarking Chat Assistants on Long-Term Interactive Memory. ICLR, 2025.

[30] W. Xie et al. MemEvoBench: Benchmarking Safety Risks from Memory Misevolution in LLM Agents. arXiv:2604.15774, 2026.

[31] J. Yi, Y. Xie, B. Zhu, E. Kiciman, G. Sun, X. Xie, and F. Wu. Benchmarking and Defending Against Indirect Prompt Injection Attacks on Large Language Models (BIPIA). KDD, 2025.

[32] Y. Zha, Y. Yang, R. Li, and Z. Hu. AlignScore: Evaluating Factual Consistency with A Unified Alignment Function. ACL, 2023.

[33] Q. Zhan, Z. Liang, Z. Ying, and D. Kang. InjecAgent: Benchmarking Indirect Prompt Injections in Tool-Integrated Large Language Model Agents. Findings of ACL, 2024.

[34] H. Zhang et al. Agent Security Bench (ASB): Formalizing and Benchmarking Attacks and Defenses in LLM-based Agents. ICLR, 2025.

[35] W. Zou, R. Geng, B. Wang, and J. Jia. PoisonedRAG: Knowledge Corruption Attacks to Retrieval-Augmented Generation of Large Language Models. USENIX Security, 2025.