Grammar for Language Describing Game Structures

Brooks MacLachlan

March 21, 2019

Pretty-printed EBNF grammar:

```
\langle qame \rangle ::= \text{`Players:'} \langle teamList \rangle \text{`Rounds:'} \langle roundList \rangle \text{`Win:'} \langle winConditionList \rangle
\langle teamList \rangle ::= (\langle team \rangle \{`, `\langle team \rangle\} | \langle playerList \rangle | `randomly divide' \langle playerList \rangle
        'into' \langle nameList \rangle) ['having' \langle attributeList \rangle]
\langle team \rangle ::= \text{`team'} \langle name \rangle \text{ ':'} \langle playerList \rangle
\langle playerList \rangle ::= \langle player \rangle \{`, `\langle player \rangle \}
\langle player \rangle ::= \langle name \rangle [\langle attributeList \rangle]
\langle attributeList \rangle ::= \langle attribute \rangle \{`,`\langle attribute \rangle \}
\langle attribute \rangle ::= 'affiliation with' \langle name \rangle | ('score' | 'resource' | 'counter')
        \langle name \rangle [\langle number \rangle]
\langle roundList \rangle ::= \langle round \rangle \{`, `\langle round \rangle\} [\langle modifierList \rangle]
\langle modifierList \rangle ::= \langle modifier \rangle \{ `, ` \langle modifier \rangle \}
\langle modifier \rangle ::= ['just' | 'from'] (\langle roundReference \rangle ('before' | 'after') \langle phaseReference \rangle
        'insert' \langle phase \rangle \mid \langle roundReference \rangle 'replace' \langle phaseReference \rangle 'with' \langle phase \rangle)
\langle roundReference \rangle ::= \text{`round'} [\langle number \rangle]
\langle phaseReference \rangle ::= 'phase' [\langle number \rangle]
\langle round \rangle ::= \langle phaseList \rangle ['repeated' \langle number \rangle 'times']
\langle phase \rangle ::= \langle action \rangle \mid \langle progression \rangle
\langle phaseList \rangle ::= \langle phase \rangle \{`>` \langle phase \rangle \}
```

```
\langle action \rangle ::= \langle competition \rangle \mid \langle decision \rangle
\langle competition \rangle ::= [\text{`scored'}] [\text{`team'}] \text{`competition between'} \langle idList \rangle
\langle decision \rangle ::= [\text{`self-included'}] \text{`vote by'} \langle idList \rangle \text{`between'} \langle idList \rangle [\text{'tiebroken by'}]
            (\langle competition \rangle \mid \langle decision \rangle \mid \langle identifier \rangle)] \mid [\text{`self-included'}] \text{ 'nomination of'}
            \langle number \rangle 'by' \langle identifier \rangle 'between' \langle idList \rangle | 'allocate' \langle name \rangle | ['self-included']
            'directed vote by \langle idList \rangle 'between' \langle idList \rangle | 'uses?' \langle identifier \rangle 'then'
             '(' \langle phaseList \rangle ')' ['otherwise' '(' \langle phaseList \rangle ')']
\langle progression \rangle ::= (\langle affiliationUpdate \rangle \mid \langle counterUpdate \rangle) 'for' \langle idList \rangle
\langle affiliationUpdate \rangle ::= \text{`elimination'} | (\text{`add'} | \text{`remove'}) \langle name \rangle | [\text{`number preserving'}]
             'swap' \langle nameList \rangle ['adding' \langle nameList \rangle] | 'change' \langle name \rangle 'to' \langle name \rangle |
            'merge' \langle nameList \rangle \ [\langle name \rangle]
\langle counterUpdate \rangle ::= ('increase' | 'decrease') \langle name \rangle 'by' \langle value \rangle | 'set' \langle name \rangle
            'to' \langle value \rangle
\langle value \rangle ::= \langle number \rangle \mid \langle name \rangle \mid \langle \langle resultReference \rangle \mid \langle allocateReference \rangle \mid \langle voteReference \rangle
            'results'
\langle idList \rangle ::= \langle identifier \rangle \{ ', ' \langle identifier \rangle \} [ 'except' \langle idList \rangle ]
\langle identifier \rangle ::= (\text{`everyone'} | \langle name \rangle | \text{`chance'} | \text{`nominated'} | \text{`tied'} | \text{`eliminated'})
            |\langle compReference \rangle ('winner' | 'loser') |\langle voteReference \rangle ('majority' | 'minority')
            | ('highest' | 'lowest' | 'most' | 'least') \langle name \rangle ) ['*' \langle value \rangle]
\langle compReference \rangle ::= \text{`competition'} [\langle number \rangle]
\langle allocateReference \rangle ::= 'allocation' [\langle number \rangle]
\langle voteReference \rangle ::= \text{`vote'} [\langle number \rangle]
\langle name \rangle ::= ('a' \mid ... \mid 'z' \mid 'A' \mid ... \mid 'Z') \{ (a' \mid ... \mid 'z' \mid 'A' \mid ... \mid 'Z' \mid '0' \mid ... \mid '9' \}
\langle nameList \rangle ::= \langle name \rangle \{`, `\langle name \rangle \}
\langle number \rangle ::= (`0` \mid ... \mid `9`) +
\langle winCondition \rangle ::= [\text{'team'}] \text{ 'achieving' } \langle name \rangle \text{ 'of' } \langle number \rangle | [\text{'team'}] \text{ 'competition'}
            | \text{['team'] ('highest' | 'lowest' | 'most' | 'least')} \langle name \rangle | \langle number \rangle 'member jury vote' | 'lowest' | 'number | 'num
\langle winConditionList \rangle ::= \langle winCondition \rangle \{`,` \langle winCondition \rangle \}
```

Notes:

- make grammar unambiguous
- should allocate be a decision and progression or just progression? Both, but decision will automatically also do the progression. The progression exists for non-decision related resource updates, such as awarding a player more of a resource for winning a competition.
- $\bullet\,$ chance as itself or as a random player