CARBON ZAPP

INNOVATION DRIVEN

Engineering Forward
Mobility Solutions!

GDR „X

Workshop Injector Test Benches



OVERVIEW

DSR-X | GDR-X

Workshop Injector Test Benches

One Platform, Two Systems

The **DSR-X** and **GDR-X** share a single air-driven bench-top platform. The **DSR-X** tests diesel common-rail injectors to 2,200 bar; the **GDR-X** tests gasoline direct injectors to 450 bar. Same chassis, same software, same footprint, you choose the system your workshop actually services.

Air-driven high-pressure pump
runs from standard workshop air; no three-phase installation

6,500+ part numbers
in the factory database, updated online





THE SHARED PLATFORM

- **Compact bench-top chassis:** 510 × 780 × 780 mm @40Kg;
- **AZO v3 operating system** on a 10" Android HMI, guided test procedures, live response-time measurement
- **CloudX connected:** results encrypted and cloud-stored, GDPR-compliant
- **Spring-loaded injector holder** with fully adjustable height and fast clamping
- **Universal fittings and adapters** · 2-year full warranty worldwide

WHERE THEY FIT

Built for the workshop that services passenger cars and light-duty vehicles daily and needs measured, professional results without the investment of a specialist or flagship bench.

- **These benches test.** Full injector servicing, coding, heavy-duty systems and multi-injector throughput are handled by the specialist ranges.
- **Upgrade path:** CTBR-X / ITBR-X for diesel CRDi coding GTBR-X for 4-injector GDi.

Database continuously updated to new EU6 applications.

One platform. Diesel or Gasoline. Professional injector testing at workshop investment.



FEATURES

DSR-X: Diesel Common-Rail Injectors

- **All CRi brands and types:** Bosch CRi1/2/3, Denso G2/G3/G4, Delphi DFI, Schaeffler / Continental, plus CRIN light-duty
- **Up to 2,200 bar:** passenger car and light-duty common-rail envelope
- **EU6 technologies supported:** VCC, NCC, iART, PCRS5
- **6 – 12 minutes per injector**

TESTS PERFORMED

• Electrical (coil / piezo) • Insulation • Back-leak (static / dynamic) • Volumetric flow (all conditions) • Nozzle opening pressure (aNOP) • Nozzle response time (RSP) • EU6 technology testing • NLT / LKT nozzle leak • Spray pattern & atomization

FEATURES

GDR-X: Gasoline Direct Injectors

- **All GDi brands and types:** Bosch HDEV, Denso, Delphi, Schaeffler / Continental, Hitachi-HTC, Magneti Marelli
- **Up to 450 bar:** passenger car and light-duty GDi envelope
- **GDi Piezo capable:** Energy-Controlled signal support
- **Integrated cleaning:** pressurized reverse flush at 35 bar and optimized ultrasonic-cleaning actuation
- **5 – 7 minutes per injector**

TESTS PERFORMED

• Electrical (coil / piezo) • Insulation • Volumetric flow (all conditions) • Back-leak (static / dynamic) • Nozzle Leak Test (NLT) • Nozzle response time (RSP) • Spray pattern & atomization • Reverse flushing at 35 bar

Built to Move the Industry Forward.

From advanced testing equipment and connected intelligence to technical expertise and global support, Carbon Zapp brings every solution together in one complete ecosystem.

Let's Connect and Discover Future Opportunities.

Scan the QR Code and easily download the Product Catalog to your phone.

CARBON ZAPP

Headquarters & Production
Isiodou 18 (Industrial Park)
194 00 Koropi, Greece

German Branch
A.I.S. GmbH
75438 Knittlingen, Germany

email contact@carbonzapp.com
tel +30 210 9856110
carbonzapp.com

Scan and Explore
Complete CZ Solutions