

CFBD endpoint field reference

Auto-generated from the vendored `cfbd-python` client (spec version pinned in `cfbd-python/README.md`) by `scripts/gen_endpoint_field_reference.py`. Every field description below is authored by us — CFBD's OpenAPI spec ships descriptions for request *parameters* only (see `cfbd/api/*.py`), never for response fields, so nothing here is copied from upstream docs. Regenerate after bumping the vendored client; verify names against the model source under `cfbd-python/cfbd/models/` if in doubt.

Endpoint list mirrors the `ENDPOINTS` registry in `cfb_system_maker/scrapers.py` — see `docs/data-coverage.md` for which endpoints are actually scraped, on what cadence, and known data floors/gaps.

Glossary

- **EPA / PPA** — Expected Points Added / Predicted Points Added: value of a play in expected-points terms. CFBD calls its own implementation PPA; EPA appears on a few adjusted-metrics models.
- **SP+** — Bill Connelly's predictive team-strength rating.
- **FPI** — ESPN's Football Power Index.
- **SRS** — Simple Rating System (margin of victory, strength-of-schedule adjusted).
- **Elo** — Chess-style rating updated after each game result.
- **Havoc rate** — share of defensive plays with a TFL, forced fumble, pass breakup, or interception.
- **Success rate** — share of plays gaining enough yardage to stay "on schedule" (Football Outsiders rules: 50% of yards to go on 1st down, 70% on 2nd, 100% on 3rd/4th).
- **Line yards / second-level yards / open-field yards** — run yardage split by how far past the line of scrimmage it was gained (offensive-line credit vs. runner credit).
- **excludeGarbageTime (`_ngt` endpoints)** — drops blowout garbage-time plays before aggregating, so values differ from the unfiltered endpoint rather than being a strict subset.

Adjusted metrics (EPA, weighted, opponent-adjusted)

adjusted_player_passing

- **CFBD method:** `AdjustedMetricsApi.get_adjusted_player_passing_stats`
- **Scrape mode:** per season

Player EPA weighted by game importance/leverage.

Field	Type	Description
<code>year</code>	int	Season year.
<code>athleteId</code>	str	Player identifier.
<code>athleteName</code>	str	Player name.
<code>position</code>	str	Position abbreviation.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>wepa</code>	float	Weighted EPA — EPA contribution weighted by the game's leverage/importance.
<code>plays</code>	int	Number of plays.

adjusted_player_rushing

- **CFBD method:** `AdjustedMetricsApi.get_adjusted_player_rushing_stats`
- **Scrape mode:** per season

Player EPA weighted by game importance/leverage.

Field	Type	Description
<code>year</code>	int	Season year.
<code>athleteId</code>	str	Player identifier.
<code>athleteName</code>	str	Player name.
<code>position</code>	str	Position abbreviation.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>wepa</code>	float	Weighted EPA — EPA contribution weighted by the game's leverage/importance.
<code>plays</code>	int	Number of plays.

adjusted_team_season

- **CFBD method:** `AdjustedMetricsApi.get_adjusted_team_season_stats`
- **Scrape mode:** per season

Opponent-adjusted EPA/success-rate metrics at the team-season level.

Field	Type	Description
<code>year</code>	int	Season year.
<code>teamId</code>	int	Team identifier.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>epa</code>	<code>AdjustedTeamMetricsEpa</code>	Expected Points Added — value of a play/drive/game in expected-points terms. — see AdjustedTeamMetricsEpa
<code>epaAllowed</code>	<code>AdjustedTeamMetricsEpa</code>	Expected Points Added allowed (defensive perspective). — see AdjustedTeamMetricsEpa
<code>successRate</code>	<code>AdjustedTeamMetricsSuccessRate</code>	Success rate. — see AdjustedTeamMetricsSuccessRate
<code>successRateAllowed</code>	<code>AdjustedTeamMetricsSuccessRate</code>	Success rate allowed. — see AdjustedTeamMetricsSuccessRate
<code>rushing</code>	<code>AdjustedTeamMetricsRushing</code>	Rushing. — see AdjustedTeamMetricsRushing
<code>rushingAllowed</code>	<code>AdjustedTeamMetricsRushing</code>	Rushing allowed. — see AdjustedTeamMetricsRushing

Field	Type	Description
<code>explosiveness</code>	float	Average PPA on successful plays — a measure of big-play ability.
<code>explosivenessAllowed</code>	float	Explosiveness allowed.

kicker_paar

- **CFBD method:** `AdjustedMetricsApi.get_kicker_paar`
- **Scrape mode:** per season

Points Above Average Replacement for kickers on field goals.

Field	Type	Description
<code>year</code>	int	Season year.
<code>athleteId</code>	str	Player identifier.
<code>athleteName</code>	str	Player name.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>paar</code>	float	Points Above Average Replacement on field goal attempts.
<code>attempts</code>	int	Attempts.

Betting lines

lines

- **CFBD method:** `BettingApi.get_lines`
- **Scrape mode:** per season

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.
<code>season</code>	int	Season year.
<code>seasonType</code>	SeasonType	<code>regular</code> or <code>postseason</code> . (<code>regular</code> , <code>postseason</code> , <code>both</code> , <code>allstar</code> , <code>spring_regular</code> , <code>spring_postseason</code>)
<code>week</code>	int	Week number within the season.
<code>startDate</code>	datetime	Kickoff date/time (UTC).
<code>homeTeamId</code>	int	Home team ID.
<code>homeTeam</code>	str	Home team name.
<code>homeConference</code>	str	Home team's conference at the time of the game.
<code>homeClassification</code>	DivisionClassification	Home team's division (FBS/FCS/etc). (<code>fbs</code> , <code>fcs</code> , <code>ii</code> , <code>ii/iii</code> , <code>iii</code>)
<code>homeScore</code>	int	Home score.

Field	Type	Description
awayTeamId	int	Away team ID.
awayTeam	str	Away team name.
awayConference	str	Away team's conference at the time of the game.
awayClassification	DivisionClassification	Away team's division (FBS/FCS/etc). (fbs , fcs , ii , ii/iii , iii)
awayScore	int	Away score.
lines	List[GameLine]	Lines.

Coaches

[coaches](#)

- **CFBD method:** [CoachesApi.get_coaches](#)
- **Scrape mode:** per season

Field	Type	Description
id	int	Unique identifier for the record.
firstName	str	First name.
lastName	str	Last name.
hireDate	datetime	Date the coach was hired.
seasons	List[CoachSeason]	Seasons.

[coach_seasons](#)

- **CFBD method:** [CoachesApi.get_coach_seasons](#)
- **Scrape mode:** per season

Field	Type	Description
games	int	Games coached.
wins	int	Win count.
losses	int	Loss count.
ties	int	Tie count.
winPercentage	float	Win percentage.
coach	CoachReference	Coach name. — see CoachReference
team	CoachSeasonTeamReference	Team name. — see CoachSeasonTeamReference
year	int	Season year.
preseasonRank	int	Preseason poll rank.
postseasonRank	int	Final/postseason poll rank.
srs	float	SRS.

Field	Type	Description
<code>spOverall</code>	float	SP+ overall.
<code>spOffense</code>	float	SP+ offense.
<code>spDefense</code>	float	SP+ defense.
<code>teamMetrics</code>	CoachRatingContext	Team metrics. — see CoachRatingContext
<code>recruiting</code>	CoachRecruitingContext	Recruiting. — see CoachRecruitingContext
<code>pollResume</code>	CoachPollResume	Poll resume. — see CoachPollResume
<code>attributionComplete</code>	bool	Attribution complete.
<code>recordSplits</code>	CoachRecordSplits	Record splits. — see CoachRecordSplits
<code>scoring</code>	CoachScoring	True if the play resulted in points. — see CoachScoring
<code>cfp</code>	CoachCfpContext	Cfp. — see CoachCfpContext
<code>draftFollowingSeason</code>	CoachDraftContext	Draft following season. — see CoachDraftContext

coach_profile

- **CFBD method:** `CoachesApi.get_coach_profile`
- **Scrape mode:** on-demand (not bulk-scraped)

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.
<code>firstName</code>	str	First name.
<code>lastName</code>	str	Last name.
<code>displayName</code>	str	Full display name.
<code>currentTeam</code>	CoachSeasonTeamReference	Current team. — see CoachSeasonTeamReference
<code>career</code>	CoachCareer	Career. — see CoachCareer
<code>birthDate</code>	str	Birth date.
<code>almaMater</code>	CoachAlmaMater	Alma mater. — see CoachAlmaMater
<code>graduationYear</code>	int	Graduation year.
<code>wikidataId</code>	str	Wikidata ID.
<code>hallOfFameYear</code>	int	Hall of fame year.

coach_tenures

- **CFBD method:** `CoachesApi.get_coach_tenures`
- **Scrape mode:** on-demand (not bulk-scraped)

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.

Field	Type	Description
<code>coach</code>	CoachReference	Coach name. — see CoachReference
<code>team</code>	CoachTeamReference	Team name. — see CoachTeamReference
<code>hireDate</code>	str	Date the coach was hired.
<code>startYear</code>	int	Start year.
<code>endYear</code>	int	End year.
<code>effectiveStart</code>	datetime	Effective start.
<code>effectiveEnd</code>	datetime	Effective end.
<code>isInterim</code>	bool	Is interim.
<code>active</code>	bool	Active.
<code>seasons</code>	int	Seasons.
<code>record</code>	CoachRecord	Record. — see CoachRecord
<code>attributionComplete</code>	bool	Attribution complete.

Conferences

`conferences`

- **CFBD method:** `ConferencesApi.get_conferences`
- **Scrape mode:** once (no params)

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.
<code>name</code>	str	Name.
<code>shortName</code>	str	Short name.
<code>abbreviation</code>	str	Short abbreviation.
<code>classification</code>	ConferenceClassification	Division classification (FBS/FCS/II/III). (<code>fbs</code> , <code>fcs</code> , <code>ii</code> , <code>ii/iii</code> , <code>iii</code>)
<code>memberCount</code>	int	Member count.

`conference_affiliations`

- **CFBD method:** `ConferencesApi.get_team_conference_affiliations`
- **Scrape mode:** once (no params)

Field	Type	Description
<code>teamId</code>	int	Team identifier.
<code>team</code>	str	Team name.
<code>conferenceId</code>	int	Conference identifier, joins to the conferences endpoint.
<code>conference</code>	str	Conference name.

Field	Type	Description
conferenceAbbreviation	str	Conference abbreviation.
classification	ConferenceClassification	Division classification (FBS/FCS/II/III). (fbs , fcs , ii , ii/iii , iii)
conferenceDivision	str	Conference division.
startYear	int	Start year.
endYear	int	End year.

conference_changes

- **CFBD method:** [ConferencesApi.get_team_conference_changes](#)
- **Scrape mode:** per season

Field	Type	Description
teamId	int	Team identifier.
team	str	Team name.
fromConferenceId	int	From conference ID.
fromConference	str	From conference.
fromConferenceAbbreviation	str	From conference abbreviation.
fromClassification	ConferenceClassification	From classification. (fbs , fcs , ii , ii/iii , iii)
toConferenceId	int	To conference ID.
toConference	str	To conference.
toConferenceAbbreviation	str	To conference abbreviation.
toClassification	ConferenceClassification	To classification. (fbs , fcs , ii , ii/iii , iii)
effectiveYear	int	Effective year.

NFL draft

draft_picks

- **CFBD method:** [DraftApi.get_draft_picks](#)
- **Scrape mode:** per season

Field	Type	Description
collegeAthleteId	int	College player identifier.
nflAthleteId	int	NFL.com player identifier.
collegeId	int	College ID.
collegeTeam	str	College the player was drafted from.
collegeConference	str	College conference the player was drafted from.

Field	Type	Description
<code>nflTeamId</code>	int	Nfl team ID.
<code>nflTeam</code>	str	NFL team that drafted the player.
<code>year</code>	int	Season year.
<code>overall</code>	int	Overall (combined) rating.
<code>round</code>	int	Round.
<code>pick</code>	int	Overall draft pick number.
<code>name</code>	str	Name.
<code>position</code>	str	Position abbreviation.
<code>height</code>	float	Height in inches.
<code>weight</code>	int	Weight in pounds.
<code>preDraftRanking</code>	int	Pre draft ranking.
<code>preDraftPositionRanking</code>	int	Pre draft position ranking.
<code>preDraftGrade</code>	int	Pre draft grade.
<code>hometownInfo</code>	DraftPickHometownInfo	Recruit's hometown details. — see DraftPickHometownInfo

draft_positions

- **CFBD method:** `DraftApi.get_draft_positions`
- **Scrape mode:** once (no params)

Field	Type	Description
<code>name</code>	str	Name.
<code>abbreviation</code>	str	Short abbreviation.

draft_teams

- **CFBD method:** `DraftApi.get_draft_teams`
- **Scrape mode:** once (no params)

Field	Type	Description
<code>location</code>	str	Location details (city/state/lat/lon).
<code>nickname</code>	str	Nickname.
<code>displayName</code>	str	Full display name.
<code>logo</code>	str	Logo.

Drives

drives

- **CFBD method:** `DrivesApi.get_drives`
- **Scrape mode:** per season

Field	Type	Description
<code>offense</code>	str	Offensive-side breakdown.
<code>offenseConference</code>	str	Offense team's conference.
<code>defense</code>	str	Defensive-side breakdown.
<code>defenseConference</code>	str	Defense team's conference.
<code>gameId</code>	int	Game identifier, joins to the games endpoint.
<code>id</code>	str	Unique identifier for the record.
<code>driveNumber</code>	int	Drive number.
<code>scoring</code>	bool	True if the play resulted in points.
<code>startPeriod</code>	int	Start period.
<code>startYardline</code>	int	Start yardline.
<code>startYardsToGoal</code>	int	Start yards to goal.
<code>startTime</code>	PlayClock	Start time. — see PlayClock
<code>endPeriod</code>	int	End period.
<code>endYardline</code>	int	End yardline.
<code>endYardsToGoal</code>	int	End yards to goal.
<code>endTime</code>	PlayClock	End time. — see PlayClock
<code>elapsed</code>	PlayClock	Elapsed. — see PlayClock
<code>plays</code>	int	Number of plays.
<code>yards</code>	int	Yards.
<code>driveResult</code>	str	Drive result.
<code>isHomeOffense</code>	bool	Is home offense.
<code>startOffenseScore</code>	int	Start offense score.
<code>startDefenseScore</code>	int	Start defense score.
<code>endOffenseScore</code>	int	End offense score.
<code>endDefenseScore</code>	int	End defense score.

Games

`advanced_box_score`

- **CFBD method:** `GamesApi.get_advanced_box_score`
- **Scrape mode:** per game (fan-out, opt-in)

Field	Type	Description
<code>gameInfo</code>	<code>AdvancedBoxScoreGameInfo</code>	Game info. — see AdvancedBoxScoreGameInfo
<code>teams</code>	<code>AdvancedBoxScoreTeams</code>	Teams. — see AdvancedBoxScoreTeams
<code>players</code>	<code>AdvancedBoxScorePlayers</code>	Players. — see AdvancedBoxScorePlayers

calendar

- **CFBD method:** `GamesApi.get_calendar`
- **Scrape mode:** per season

Field	Type	Description
<code>season</code>	<code>int</code>	Season year.
<code>week</code>	<code>int</code>	Week number within the season.
<code>seasonType</code>	<code>SeasonType</code>	<code>regular</code> or <code>postseason</code> . (<code>regular</code> , <code>postseason</code> , <code>both</code> , <code>allstar</code> , <code>spring_regular</code> , <code>spring_postseason</code>)
<code>startDate</code>	<code>datetime</code>	Kickoff date/time (UTC).
<code>endDate</code>	<code>datetime</code>	End date.
<code>firstGameStart</code>	<code>datetime</code>	First game start.
<code>lastGameStart</code>	<code>datetime</code>	Last game start.

game_player_stats

- **CFBD method:** `GamesApi.get_game_player_stats`
- **Scrape mode:** per season x week

Field	Type	Description
<code>id</code>	<code>int</code>	Unique identifier for the record.
<code>teams</code>	<code>List[GamePlayerStatsTeam]</code>	Teams.

game_team_stats

- **CFBD method:** `GamesApi.get_game_team_stats`
- **Scrape mode:** per season x week

Field	Type	Description
<code>id</code>	<code>int</code>	Unique identifier for the record.
<code>teams</code>	<code>List[GameTeamStatsTeam]</code>	Teams.

games

- **CFBD method:** `GamesApi.get_games`
- **Scrape mode:** per season

Field	Type	Description
id	int	Unique identifier for the record.
season	int	Season year.
week	int	Week number within the season.
seasonType	SeasonType	regular or postseason. (regular, postseason, both, allstar, spring_regular, spring_postseason)
startDate	datetime	Kickoff date/time (UTC).
startTimeTBD	bool	True if kickoff time was not yet announced.
completed	bool	True once the game has finished.
neutralSite	bool	True if played at a neutral (non-home) site.
conferenceGame	bool	True if both teams share a conference.
attendance	int	Reported attendance.
venueId	int	Venue identifier, joins to the venues endpoint.
venue	str	Venue name.
homeId	int	Home team identifier.
homeTeam	str	Home team name.
homeConference	str	Home team's conference at the time of the game.
homeClassification	DivisionClassification	Home team's division (FBS/FCS/etc). (fbs, fcs, ii, ii/iii, iii)
homePoints	int	Home team's final score.
homeLineScores	List[Union[float]	Home team's score by quarter/period.
homePostgameWinProbability	float	Model-estimated home win probability after the game.
homePregameElo	int	Home team's Elo rating entering the game.
homePostgameElo	int	Home team's Elo rating after the game.
awayId	int	Away team identifier.
awayTeam	str	Away team name.
awayConference	str	Away team's conference at the time of the game.
awayClassification	DivisionClassification	Away team's division (FBS/FCS/etc). (fbs, fcs, ii, ii/iii, iii)
awayPoints	int	Away team's final score.
awayLineScores	List[Union[float]	Away team's score by quarter/period.
awayPostgameWinProbability	float	Model-estimated away win probability after the game.
awayPregameElo	int	Away team's Elo rating entering the game.

Field	Type	Description
<code>awayPostgameElo</code>	int	Away team's Elo rating after the game.
<code>excitementIndex</code>	float	CFBD's game-excitement metric, derived from win-probability swings.
<code>highlights</code>	str	Highlight video URL, if available.
<code>notes</code>	str	Free-text notes about the game (e.g. bowl name).
<code>playoff</code>	GamePlayoff	Playoff context for the game (round/bracket), if applicable. — see GamePlayoff

media

- **CFBD method:** `GamesApi.get_media`
- **Scrape mode:** per season

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.
<code>season</code>	int	Season year.
<code>week</code>	int	Week number within the season.
<code>seasonType</code>	SeasonType	<code>regular</code> or <code>postseason</code> . (<code>regular</code> , <code>postseason</code> , <code>both</code> , <code>allstar</code> , <code>spring_regular</code> , <code>spring_postseason</code>)
<code>startTime</code>	datetime	Start time.
<code>isStartTimeTBD</code>	bool	Is start time t b d.
<code>homeTeam</code>	str	Home team name.
<code>homeConference</code>	str	Home team's conference at the time of the game.
<code>awayTeam</code>	str	Away team name.
<code>awayConference</code>	str	Away team's conference at the time of the game.
<code>mediaType</code>	MediaType	Media type. (<code>tv</code> , <code>radio</code> , <code>web</code> , <code>ppv</code> , <code>mobile</code>)
<code>outlet</code>	str	Outlet.

records

- **CFBD method:** `GamesApi.get_records`
- **Scrape mode:** per season

Field	Type	Description
<code>year</code>	int	Season year.
<code>teamId</code>	int	Team identifier.
<code>team</code>	str	Team name.
<code>classification</code>	DivisionClassification	Division classification (FBS/FCS/II/III). (<code>fbs</code> , <code>fcs</code> , <code>ii</code> , <code>ii/iii</code> , <code>iii</code>)

Field	Type	Description
<code>conference</code>	str	Conference name.
<code>division</code>	str	Conference division (e.g. East/West), if applicable.
<code>expectedWins</code>	float	Expected wins.
<code>total</code>	TeamRecord	Total. — see TeamRecord
<code>conferenceGames</code>	TeamRecord	Conference games. — see TeamRecord
<code>homeGames</code>	TeamRecord	Home games. — see TeamRecord
<code>awayGames</code>	TeamRecord	Away games. — see TeamRecord
<code>neutralSiteGames</code>	TeamRecord	Neutral site games. — see TeamRecord
<code>regularSeason</code>	TeamRecord	Regular season. — see TeamRecord
<code>postseason</code>	TeamRecord	Postseason. — see TeamRecord

scoreboard

- **CFBD method:** `GamesApi.get_scoreboard`
- **Scrape mode:** on-demand (not bulk-scraped)

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.
<code>startDate</code>	datetime	Kickoff date/time (UTC).
<code>startTimeTBD</code>	bool	True if kickoff time was not yet announced.
<code>tv</code>	str	Tv.
<code>neutralSite</code>	bool	True if played at a neutral (non-home) site.
<code>conferenceGame</code>	bool	True if both teams share a conference.
<code>status</code>	GameStatus	Status. (scheduled , in_progress , completed)
<code>period</code>	int	Quarter/period number.
<code>clock</code>	str	Game clock at the time of the play/event.
<code>situation</code>	str	Situation.
<code>possession</code>	str	Possession.
<code>lastPlay</code>	str	Last play.
<code>venue</code>	ScoreboardGameVenue	Venue name. — see ScoreboardGameVenue
<code>homeTeam</code>	ScoreboardGameHomeTeam	Home team name. — see ScoreboardGameHomeTeam
<code>awayTeam</code>	ScoreboardGameHomeTeam	Away team name. — see ScoreboardGameHomeTeam
<code>weather</code>	ScoreboardGameWeather	Weather. — see ScoreboardGameWeather
<code>betting</code>	ScoreboardGameBetting	Betting. — see ScoreboardGameBetting

weather

- **CFBD method:** `GamesApi.get_weather`
- **Scrape mode:** per season

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.
<code>season</code>	int	Season year.
<code>week</code>	int	Week number within the season.
<code>seasonType</code>	SeasonType	<code>regular</code> or <code>postseason</code> . (<code>regular</code> , <code>postseason</code> , <code>both</code> , <code>allstar</code> , <code>spring_regular</code> , <code>spring_postseason</code>)
<code>startTime</code>	datetime	Start time.
<code>gameIndoors</code>	bool	Game indoors.
<code>homeTeam</code>	str	Home team name.
<code>homeConference</code>	str	Home team's conference at the time of the game.
<code>awayTeam</code>	str	Away team name.
<code>awayConference</code>	str	Away team's conference at the time of the game.
<code>venueId</code>	int	Venue identifier, joins to the venues endpoint.
<code>venue</code>	str	Venue name.
<code>temperature</code>	float	Temperature.
<code>dewPoint</code>	float	Dew point.
<code>humidity</code>	float	Humidity.
<code>precipitation</code>	float	Precipitation.
<code>snowfall</code>	float	Snowfall.
<code>windDirection</code>	float	Wind direction.
<code>windSpeed</code>	float	Wind speed.
<code>pressure</code>	float	Pressure.
<code>weatherConditionCode</code>	float	Weather condition code.
<code>weatherCondition</code>	str	Weather condition.

Info / account

user_info

- **CFBD method:** `InfoApi.get_user_info`
- **Scrape mode:** once (no params)

Field	Type	Description
<code>patronLevel</code>	float	Patron level.

Field	Type	Description
<code>tierName</code>	str	Tier name.
<code>monthlyLimit</code>	float	Monthly limit.
<code>remainingCalls</code>	float	Remaining calls.
<code>usedCalls</code>	float	Used calls.
<code>resetAt</code>	str	Reset at.
<code>sharedPool</code>	bool	Shared pool.
<code>products</code>	List[str]	Products.
<code>features</code>	UserFeatureAccess	Features. — see UserFeatureAccess

Advanced metrics (PPA, win probability, predicted points)

`field_goal_ep`

- **CFBD method:** `MetricsApi.get_field_goal_expected_points`
- **Scrape mode:** once (no params)

Expected points value of attempting a field goal, by distance.

Field	Type	Description
<code>yardsToGoal</code>	int	Yards remaining to the opponent's goal line.
<code>distance</code>	int	Yards to go for a first down.
<code>expectedPoints</code>	float	Expected points.

`predicted_points`

- **CFBD method:** `MetricsApi.get_predicted_points`
- **Scrape mode:** down x distance grid

Expected points value for a given down/distance (predicted-points model lookup table).

Field	Type	Description
<code>yardLine</code>	int	Yard line (0-100, own end zone to opponent's).
<code>predictedPoints</code>	float	Predicted points.

`ppa_games`

- **CFBD method:** `MetricsApi.get_predicted_points_added_by_game`
- **Scrape mode:** per season

PPA aggregated to team-game level, split offense/defense.

Field	Type	Description
<code>gameId</code>	int	Game identifier, joins to the games endpoint.

Field	Type	Description
<code>season</code>	int	Season year.
<code>week</code>	int	Week number within the season.
<code>seasonType</code>	SeasonType	<code>regular</code> or <code>postseason</code> . (<code>regular</code> , <code>postseason</code> , <code>both</code> , <code>allstar</code> , <code>spring_regular</code> , <code>spring_postseason</code>)
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>opponent</code>	str	Opponent team name.
<code>offense</code>	TeamGamePredictedPointsAddedOffense	Offensive-side breakdown. — see TeamGamePredictedPointsAddedOffense
<code>defense</code>	TeamGamePredictedPointsAddedOffense	Defensive-side breakdown. — see TeamGamePredictedPointsAddedOffense

ppa_players_games

- **CFBD method:** `MetricsApi.get_predicted_points_added_by_player_game`
- **Scrape mode:** per season x week

PPA aggregated to player-game level.

Field	Type	Description
<code>season</code>	int	Season year.
<code>week</code>	int	Week number within the season.
<code>seasonType</code>	SeasonType	<code>regular</code> or <code>postseason</code> . (<code>regular</code> , <code>postseason</code> , <code>both</code> , <code>allstar</code> , <code>spring_regular</code> , <code>spring_postseason</code>)
<code>id</code>	str	Unique identifier for the record.
<code>name</code>	str	Name.
<code>position</code>	str	Position abbreviation.
<code>team</code>	str	Team name.
<code>opponent</code>	str	Opponent team name.
<code>averagePPA</code>	PlayerGamePredictedPointsAddedAveragePPA	Average p p a. — see PlayerGamePredictedPointsAddedAveragePPA

ppa_players_season

- **CFBD method:** `MetricsApi.get_predicted_points_added_by_player_season`
- **Scrape mode:** per season

PPA aggregated to player-season level.

Field	Type	Description
<code>season</code>	int	Season year.
<code>id</code>	str	Unique identifier for the record.
<code>name</code>	str	Name.
<code>position</code>	str	Position abbreviation.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>averagePPA</code>	PlayerSeasonOverviewPPAAverage	Average p p a. — see PlayerSeasonOverviewPPAAverage
<code>totalPPA</code>	PlayerSeasonOverviewPPAAverage	Sum of PPA across plays. — see PlayerSeasonOverviewPPAAverage

ppa_teams

- **CFBD method:** `MetricsApi.get_predicted_points_added_by_team`
- **Scrape mode:** per season

PPA aggregated to team-season level, split offense/defense.

Field	Type	Description
<code>season</code>	int	Season year.
<code>conference</code>	str	Conference name.
<code>team</code>	str	Team name.
<code>offense</code>	TeamSeasonPredictedPointsAddedOffense	Offensive-side breakdown. — see TeamSeasonPredictedPointsAddedOffense
<code>defense</code>	TeamSeasonPredictedPointsAddedOffense	Defensive-side breakdown. — see TeamSeasonPredictedPointsAddedOffense

pregame_win_prob

- **CFBD method:** `MetricsApi.get_pregame_win_probabilities`
- **Scrape mode:** per season

Pregame win-probability model output for a game.

Field	Type	Description
<code>season</code>	int	Season year.
<code>seasonType</code>	SeasonType	<code>regular</code> or <code>postseason</code> . (<code>regular</code> , <code>postseason</code> , <code>both</code> , <code>allstar</code> , <code>spring_regular</code> , <code>spring_postseason</code>)
<code>week</code>	int	Week number within the season.
<code>gameId</code>	int	Game identifier, joins to the games endpoint.
<code>homeTeam</code>	str	Home team name.

Field	Type	Description
<code>awayTeam</code>	str	Away team name.
<code>spread</code>	float	Closing point spread (negative = favorite by that many points), home-team perspective unless noted.
<code>homeWinProbability</code>	float	Home win probability.

`win_probability`

- **CFBD method:** `MetricsApi.get_win_probability`
- **Scrape mode:** per game (fan-out, opt-in)

Live win probability after each play in a game.

Field	Type	Description
<code>gameId</code>	int	Game identifier, joins to the games endpoint.
<code>playId</code>	str	Play ID.
<code>playText</code>	str	Human-readable play description.
<code>homeId</code>	int	Home team identifier.
<code>home</code>	str	Home.
<code>awayId</code>	int	Away team identifier.
<code>away</code>	str	Away.
<code>spread</code>	float	Closing point spread (negative = favorite by that many points), home-team perspective unless noted.
<code>homeBall</code>	bool	Home ball.
<code>homeScore</code>	int	Home score.
<code>awayScore</code>	int	Away score.
<code>yardLine</code>	int	Yard line (0-100, own end zone to opponent's).
<code>down</code>	int	Down number (1-4).
<code>distance</code>	int	Yards to go for a first down.
<code>homeWinProbability</code>	float	Home win probability.
<code>playNumber</code>	int	Play number.

`ppa_games_ngt`

- **CFBD method:** `MetricsApi.get_predicted_points_added_by_game`
- **Scrape mode:** per season

Same schema as its base endpoint above. `excludeGarbageTime=true` — drops garbage-time plays before aggregating, so values differ from the unfiltered twin.

`ppa_teams_ngt`

- **CFBD method:** `MetricsApi.get_predicted_points_added_by_team`
- **Scrape mode:** per season

Same schema as its base endpoint above. `excludeGarbageTime=true` — drops garbage-time plays before aggregating, so values differ from the unfiltered twin.

ppa_players_season_ngt

- **CFBD method:** `MetricsApi.get_predicted_points_added_by_player_season`
- **Scrape mode:** per season

Same schema as its base endpoint above. `excludeGarbageTime=true` — drops garbage-time plays before aggregating, so values differ from the unfiltered twin.

ppa_players_games_ngt

- **CFBD method:** `MetricsApi.get_predicted_points_added_by_player_game`
- **Scrape mode:** per season x week

Same schema as its base endpoint above. `excludeGarbageTime=true` — drops garbage-time plays before aggregating, so values differ from the unfiltered twin.

Passing charting (air yards, aDOT, yards after catch)

passing_plays

- **CFBD method:** `PassingApi.get_passing_plays`
- **Scrape mode:** per season x week
- **Data floor:** no data before 2025

Field	Type	Description
gameId	int	Game identifier, joins to the games endpoint.
playId	str	Play ID.
driveId	str	Drive ID.
season	int	Season year.
week	int	Week number within the season.
seasonType	SeasonType	regular or postseason. (regular, postseason, both, allstar, spring_regular, spring_postseason)
offenseId	int	Offense ID.
offense	str	Offensive-side breakdown.
offenseConference	str	Offense team's conference.
defenseId	int	Defense ID.
defense	str	Defensive-side breakdown.
defenseConference	str	Defense team's conference.
period	int	Quarter/period number.

Field	Type	Description
clock	PassingPlayClock	Game clock at the time of the play/event. — see PassingPlayClock
down	int	Down number (1-4).
distance	int	Yards to go for a first down.
playText	str	Human-readable play description.
passerId	str	Passer ID.
passer	str	Passer.
targetId	str	Target ID.
target	str	Target.
outcome	PassOutcome	Outcome. (completion , incompletion , interception)
airYards	int	Air yards.
passDepth	PassDepth	Pass depth. (short , deep)
passDirection	PassDirection	Pass direction. (left , middle , right)
passLocation	PassLocation	Pass location. (short left , short middle , short right , deep left , deep middle , deep right)
totalYards	int	Total yards.
yardsAfterCatch	int	Yards after catch.
startYardline	int	Start yardline.
startYardsToGoal	int	Start yards to goal.
targetYardsToGoal	int	Target yards to goal.
isSpike	bool	Is spike.
isThrowaway	bool	Is throwaway.
isIntentionalGrounding	bool	Is intentional grounding.
parseStatus	PassParseStatus	Parse status. (complete , partial , invalid)

passing_players_games

- **CFBD method:** [PassingApi.get_player_passing_by_game](#)
- **Scrape mode:** per season x week
- **Data floor:** no data before 2025

Field	Type	Description
attempts	int	Attempts.
completions	int	Completions.
incompletions	int	Incompletions.

Field	Type	Description
<code>interceptions</code>	int	Interceptions.
<code>completionRate</code>	float	Completion rate.
<code>airYardsAttemptsAvailable</code>	int	Air yards attempts available.
<code>totalAirYards</code>	int	Total air yards.
<code>averageDepthOfTarget</code>	float	Average depth of target.
<code>totalYardsAttemptsAvailable</code>	int	Total yards attempts available.
<code>totalYards</code>	int	Total yards.
<code>yardsAfterCatchAttemptsAvailable</code>	int	Yards after catch attempts available.
<code>totalYardsAfterCatch</code>	int	Total yards after catch.
<code>averageYardsAfterCatch</code>	float	Average yards after catch.
<code>gameId</code>	int	Game identifier, joins to the games endpoint.
<code>season</code>	int	Season year.
<code>week</code>	int	Week number within the season.
<code>seasonType</code>	SeasonType	<code>regular</code> or <code>postseason</code> . (<code>regular</code> , <code>postseason</code> , <code>both</code> , <code>allstar</code> , <code>spring_regular</code> , <code>spring_postseason</code>)
<code>playerId</code>	str	Player ID.
<code>player</code>	str	Player.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>opponent</code>	str	Opponent team name.

passing_players_season

- **CFBD method:** `PassingApi.get_player_passing_by_season`
- **Scrape mode:** per season
- **Data floor:** no data before 2025

Field	Type	Description
<code>attempts</code>	int	Attempts.
<code>completions</code>	int	Completions.
<code>incompletions</code>	int	Incompletions.
<code>interceptions</code>	int	Interceptions.
<code>completionRate</code>	float	Completion rate.
<code>airYardsAttemptsAvailable</code>	int	Air yards attempts available.
<code>totalAirYards</code>	int	Total air yards.

Field	Type	Description
<code>averageDepthOfTarget</code>	float	Average depth of target.
<code>totalYardsAttemptsAvailable</code>	int	Total yards attempts available.
<code>totalYards</code>	int	Total yards.
<code>yardsAfterCatchAttemptsAvailable</code>	int	Yards after catch attempts available.
<code>totalYardsAfterCatch</code>	int	Total yards after catch.
<code>averageYardsAfterCatch</code>	float	Average yards after catch.
<code>season</code>	int	Season year.
<code>playerId</code>	str	Player ID.
<code>player</code>	str	Player.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.

passing_teams_games

- **CFBD method:** `PassingApi.get_team_passing_by_game`
- **Scrape mode:** per season x week
- **Data floor:** no data before 2025

Field	Type	Description
<code>gameId</code>	int	Game identifier, joins to the games endpoint.
<code>season</code>	int	Season year.
<code>week</code>	int	Week number within the season.
<code>seasonType</code>	SeasonType	<code>regular</code> or <code>postseason</code> . (<code>regular</code> , <code>postseason</code> , <code>both</code> , <code>allstar</code> , <code>spring_regular</code> , <code>spring_postseason</code>)
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>opponent</code>	str	Opponent team name.
<code>offense</code>	PassingProduction	Offensive-side breakdown. — see PassingProduction
<code>defense</code>	PassingProduction	Defensive-side breakdown. — see PassingProduction

passing_teams_season

- **CFBD method:** `PassingApi.get_team_passing_by_season`
- **Scrape mode:** per season
- **Data floor:** no data before 2025

Field	Type	Description
<code>season</code>	int	Season year.

Field	Type	Description
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>offense</code>	PassingProduction	Offensive-side breakdown. — see PassingProduction
<code>defense</code>	PassingProduction	Defensive-side breakdown. — see PassingProduction

Players

`player_season_overview`

- **CFBD method:** `PlayersApi.get_player_season_overview`
- **Scrape mode:** per player (fan-out, opt-in)

Field	Type	Description
<code>season</code>	int	Season year.
<code>id</code>	str	Unique identifier for the record.
<code>name</code>	str	Name.
<code>position</code>	str	Position abbreviation.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>games</code>	int	Games coached.
<code>boxScoreStats</code>	PlayerSeasonOverviewBoxScoreStats	Box score stats. — see PlayerSeasonOverviewBoxScoreStats

`player_usage`

- **CFBD method:** `PlayersApi.get_player_usage`
- **Scrape mode:** per season

Field	Type	Description
<code>season</code>	int	Season year.
<code>id</code>	str	Unique identifier for the record.
<code>name</code>	str	Name.
<code>position</code>	str	Position abbreviation.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>usage</code>	PlayerUsageUsage	Share of team plays/snaps the player was involved in, by situation. — see PlayerUsageUsage

`returning_production`

- **CFBD method:** `PlayersApi.get_returning_production`
- **Scrape mode:** per season

Field	Type	Description
<code>season</code>	int	Season year.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>totalPPA</code>	float	Sum of PPA across plays.
<code>totalPassingPPA</code>	float	Total passing p p a.
<code>totalReceivingPPA</code>	float	Total receiving p p a.
<code>totalRushingPPA</code>	float	Total rushing p p a.
<code>percentPPA</code>	float	Percent p p a.
<code>percentPassingPPA</code>	float	Percent passing p p a.
<code>percentReceivingPPA</code>	float	Percent receiving p p a.
<code>percentRushingPPA</code>	float	Percent rushing p p a.
<code>usage</code>	float	Share of team plays/snaps the player was involved in, by situation.
<code>passingUsage</code>	float	Passing usage.
<code>receivingUsage</code>	float	Receiving usage.
<code>rushingUsage</code>	float	Rushing usage.

transfer_portal

- **CFBD method:** `PlayersApi.get_transfer_portal`
- **Scrape mode:** per season

Field	Type	Description
<code>season</code>	int	Season year.
<code>firstName</code>	str	First name.
<code>lastName</code>	str	Last name.
<code>position</code>	str	Position abbreviation.
<code>origin</code>	str	Origin.
<code>destination</code>	str	Destination.
<code>transferDate</code>	datetime	Transfer date.
<code>rating</code>	float	Composite rating score.
<code>stars</code>	int	Recruit star rating (1-5).
<code>eligibility</code>	TransferEligibility	Player eligibility/class status. (<code>Withdrawn</code> , <code>TBD</code> , <code>PendingAppeal</code> , <code>SittingOne</code> , <code>Immediate</code>)

player_search

- **CFBD method:** `PlayersApi.search_players`
- **Scrape mode:** on-demand (not bulk-scraped)

Field	Type	Description
<code>id</code>	str	Unique identifier for the record.
<code>team</code>	str	Team name.
<code>name</code>	str	Name.
<code>firstName</code>	str	First name.
<code>lastName</code>	str	Last name.
<code>weight</code>	int	Weight in pounds.
<code>height</code>	float	Height in inches.
<code>jersey</code>	int	Jersey number.
<code>position</code>	str	Position abbreviation.
<code>hometown</code>	str	Hometown.
<code>teamColor</code>	str	Team color.
<code>teamColorSecondary</code>	str	Team color secondary.
<code>activeStartYear</code>	int	Active start year.
<code>activeEndYear</code>	int	Active end year.
<code>teamStints</code>	List[PlayerSearchTeamStint]	Team stints.

player_usage_ngt

- **CFBD method:** `PlayersApi.get_player_usage`
- **Scrape mode:** per season

Same schema as its base endpoint above. `excludeGarbageTime=true` — drops garbage-time plays before aggregating, so values differ from the unfiltered twin.

Plays

live_plays

- **CFBD method:** `PlaysApi.get_live_plays`
- **Scrape mode:** on-demand (not bulk-scraped)

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.
<code>status</code>	str	Status.
<code>period</code>	int	Quarter/period number.
<code>clock</code>	str	Game clock at the time of the play/event.

Field	Type	Description
<code>possession</code>	str	Possession.
<code>down</code>	int	Down number (1-4).
<code>distance</code>	int	Yards to go for a first down.
<code>yardsToGoal</code>	int	Yards remaining to the opponent's goal line.
<code>teams</code>	List[LiveGameTeam]	Teams.
<code>drives</code>	List[LiveGameDrive]	Number of drives.

play_stat_types

- **CFBD method:** `PlaysApi.get_play_stat_types`
- **Scrape mode:** once (no params)

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.
<code>name</code>	str	Name.

play_stats

- **CFBD method:** `PlaysApi.get_play_stats`
- **Scrape mode:** per season x week

Field	Type	Description
<code>gameId</code>	float	Game identifier, joins to the games endpoint.
<code>season</code>	float	Season year.
<code>week</code>	float	Week number within the season.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>opponent</code>	str	Opponent team name.
<code>teamScore</code>	float	Team score.
<code>opponentScore</code>	float	Opponent score.
<code>driveId</code>	str	Drive ID.
<code>playId</code>	str	Play ID.
<code>period</code>	float	Quarter/period number.
<code>clock</code>	PlayStatClock	Game clock at the time of the play/event. — see PlayStatClock
<code>yardsToGoal</code>	float	Yards remaining to the opponent's goal line.
<code>down</code>	float	Down number (1-4).
<code>distance</code>	float	Yards to go for a first down.

Field	Type	Description
athleteId	str	Player identifier.
athleteName	str	Player name.
statType	str	Category of statistic being recorded.
stat	float	Statistic value.

play_types

- **CFBD method:** [PlaysApi.get_play_types](#)
- **Scrape mode:** once (no params)

Field	Type	Description
id	int	Unique identifier for the record.
text	str	Text.
abbreviation	str	Short abbreviation.

plays

- **CFBD method:** [PlaysApi.get_plays](#)
- **Scrape mode:** per season x week

Field	Type	Description
id	str	Unique identifier for the record.
driveId	str	Drive ID.
gameId	int	Game identifier, joins to the games endpoint.
driveNumber	int	Drive number.
playNumber	int	Play number.
offense	str	Offensive-side breakdown.
offenseConference	str	Offense team's conference.
offenseScore	int	Offense team's score at the time of the play.
defense	str	Defensive-side breakdown.
home	str	Home.
away	str	Away.
defenseConference	str	Defense team's conference.
defenseScore	int	Defense team's score at the time of the play.
period	int	Quarter/period number.
clock	PlayClock	Game clock at the time of the play/event. — see PlayClock
offenseTimeouts	int	Offense timeouts.

Field	Type	Description
<code>defenseTimeouts</code>	int	Defense timeouts.
<code>yardline</code>	int	Yardline.
<code>yardsToGoal</code>	int	Yards remaining to the opponent's goal line.
<code>down</code>	int	Down number (1-4).
<code>distance</code>	int	Yards to go for a first down.
<code>yardsGained</code>	int	Yards gained on the play.
<code>scoring</code>	bool	True if the play resulted in points.
<code>playType</code>	str	Play type (run/pass/punt/etc).
<code>playText</code>	str	Human-readable play description.
<code>ppa</code>	float	Predicted Points Added — CFBD's play-value metric, similar to EPA.
<code>wallclock</code>	str	Real-world timestamp of the event.

College Football Playoff (CFP)

`cfp_playoff`

- **CFBD method:** `PlayoffsApi.get_cfp_playoff`
- **Scrape mode:** per season
- **Data floor:** no data before 2014

Field	Type	Description
<code>season</code>	int	Season year.
<code>competition</code>	PlayoffCompetitionCfp	Competition. (<code>cfp</code>)
<code>format</code>	str	Format.
<code>teamCount</code>	int	Team count.
<code>status</code>	PlayoffStatus	Status. (<code>scheduled</code> , <code>selected</code> , <code>in_progress</code> , <code>completed</code>)
<code>participants</code>	List[PlayoffParticipant]	Participants.
<code>rounds</code>	List[PlayoffRoundRecord]	Rounds.
<code>champion</code>	PlayoffTeam	Champion. — see PlayoffTeam

`cfp_games`

- **CFBD method:** `PlayoffsApi.get_cfp_games`
- **Scrape mode:** per season
- **Data floor:** no data before 2014

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.
<code>bracketSlot</code>	str	Bracket slot.

Field	Type	Description
<code>round</code>	PlayoffRound	Round. (<code>first_round</code> , <code>quarterfinal</code> , <code>semifinal</code> , <code>championship</code>)
<code>roundName</code>	str	Round name.
<code>roundOrder</code>	int	Round order.
<code>matchupOrder</code>	int	Matchup order.
<code>startDate</code>	datetime	Kickoff date/time (UTC).
<code>bowlName</code>	str	Bowl name.
<code>slots</code>	List[PlayoffMatchupSlot]	Slots.
<code>game</code>	PlayoffLinkedGame	Game. — see PlayoffLinkedGame
<code>advancesTo</code>	PlayoffAdvancement	Advances to. — see PlayoffAdvancement

cfp_participants

- **CFBD method:** `PlayoffsApi.get_cfp_participants`
- **Scrape mode:** per season
- **Data floor:** no data before 2014

Field	Type	Description
<code>team</code>	PlayoffTeam	Team name. — see PlayoffTeam
<code>committeeRank</code>	int	Committee rank.
<code>seed</code>	int	Seed.
<code>bidType</code>	PlayoffBidType	Bid type. (<code>automatic</code> , <code>at_large</code>)
<code>qualificationReason</code>	str	Qualification reason.
<code>conferenceChampion</code>	bool	Conference champion.
<code>qualifyingConference</code>	str	Qualifying conference.
<code>firstRoundBye</code>	bool	First round bye.
<code>outcome</code>	PlayoffOutcome	Outcome. (<code>active</code> , <code>eliminated</code> , <code>champion</code>)
<code>eliminatedRound</code>	PlayoffRound	Eliminated round. (<code>first_round</code> , <code>quarterfinal</code> , <code>semifinal</code> , <code>championship</code>)

Rankings / polls

rankings

- **CFBD method:** `RankingsApi.get_rankings`
- **Scrape mode:** per season

Field	Type	Description
<code>season</code>	int	Season year.

Field	Type	Description
<code>seasonType</code>	SeasonType	<code>regular</code> or <code>postseason</code> . (<code>regular</code> , <code>postseason</code> , <code>both</code> , <code>allstar</code> , <code>spring_regular</code> , <code>spring_postseason</code>)
<code>week</code>	int	Week number within the season.
<code>polls</code>	List[Poll]	Polls.

Ratings (SP+, FPI, Elo, SRS)

conference_sp

- **CFBD method:** `RatingsApi.get_conference_sp`
- **Scrape mode:** per season

SP+ averaged to the conference level.

Field	Type	Description
<code>year</code>	int	Season year.
<code>conference</code>	str	Conference name.
<code>rating</code>	float	Composite rating score.
<code>secondOrderWins</code>	float	Second-order (efficiency-based expected) win total.
<code>sos</code>	float	Strength of schedule rating.
<code>offense</code>	ConferenceSPOffense	Offensive-side breakdown. — see ConferenceSPOffense
<code>defense</code>	ConferenceSPDefense	Defensive-side breakdown. — see ConferenceSPDefense
<code>specialTeams</code>	TeamSPSpecialTeams	Special-teams breakdown. — see TeamSPSpecialTeams

elo

- **CFBD method:** `RatingsApi.get_elo`
- **Scrape mode:** per season

Elo rating (chess-style rating updated after each game).

Field	Type	Description
<code>year</code>	int	Season year.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>elo</code>	int	Elo.

fpi

- **CFBD method:** `RatingsApi.get_fpi`
- **Scrape mode:** per season

ESPN's Football Power Index rating.

Field	Type	Description
<code>year</code>	int	Season year.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>fpi</code>	float	FPI.
<code>resumeRanks</code>	TeamFPIResumeRanks	Resume ranks. — see TeamFPIResumeRanks
<code>efficiencies</code>	TeamFPIEfficiencies	Efficiencies. — see TeamFPIEfficiencies

sp

- **CFBD method:** `RatingsApi.get_sp`
- **Scrape mode:** per season

Bill Connelly's SP+ rating: predictive team strength on a scale where 0 is average.

Field	Type	Description
<code>year</code>	int	Season year.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>rating</code>	float	Composite rating score.
<code>ranking</code>	int	Rank (1 = best) within the given scope.
<code>secondOrderWins</code>	float	Second-order (efficiency-based expected) win total.
<code>sos</code>	float	Strength of schedule rating.
<code>offense</code>	TeamSPOffense	Offensive-side breakdown. — see TeamSPOffense
<code>defense</code>	TeamSPDefense	Defensive-side breakdown. — see TeamSPDefense
<code>specialTeams</code>	TeamSPSpecialTeams	Special-teams breakdown. — see TeamSPSpecialTeams

srs

- **CFBD method:** `RatingsApi.get_srs`
- **Scrape mode:** per season

Simple Rating System: margin-of-victory rating adjusted for strength of schedule.

Field	Type	Description
<code>year</code>	int	Season year.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>division</code>	str	Conference division (e.g. East/West), if applicable.
<code>rating</code>	float	Composite rating score.

Field	Type	Description
<code>ranking</code>	int	Rank (1 = best) within the given scope.

core_ratings

- **CFBD method:** `RatingsApi.get_core`
- **Scrape mode:** per season

CFBD's blended "core" rating combining multiple underlying models.

Field	Type	Description
<code>year</code>	int	Season year.
<code>throughSeasonType</code>	CoreRatingSeasonType	Through season type. (<code>regular</code> , <code>postseason</code>)
<code>throughWeek</code>	int	Through week.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>overall</code>	float	Overall (combined) rating.
<code>offense</code>	float	Offensive-side breakdown.
<code>defense</code>	float	Defensive-side breakdown.
<code>offensePlays</code>	int	Offense plays.
<code>defensePlays</code>	int	Defense plays.
<code>modelVersion</code>	str	Model version.

srs_expanded

- **CFBD method:** `RatingsApi.get_expanded_srs`
- **Scrape mode:** per season

SRS including FCS opponents, with additional sub-components.

Field	Type	Description
<code>year</code>	int	Season year.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>division</code>	str	Conference division (e.g. East/West), if applicable.
<code>rating</code>	float	Composite rating score.
<code>ranking</code>	int	Rank (1 = best) within the given scope.
<code>classification</code>	DivisionClassification	Division classification (FBS/FCS/II/III). (<code>fbs</code> , <code>fcs</code> , <code>ii</code> , <code>ii/iii</code> , <code>iii</code>)

Recruiting

recruiting_groups

- **CFBD method:** `RecruitingApi.get_aggregated_team_recruiting_ratings`
- **Scrape mode:** once (no params)

Field	Type	Description
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>positionGroup</code>	str	Position group.
<code>averageRating</code>	float	Average rating.
<code>totalRating</code>	float	Total rating.
<code>commits</code>	int	Commits.
<code>averageStars</code>	float	Average stars.

recruits

- **CFBD method:** `RecruitingApi.get_recruits`
- **Scrape mode:** per season

Field	Type	Description
<code>id</code>	str	Unique identifier for the record.
<code>athleteId</code>	str	Player identifier.
<code>recruitType</code>	RecruitClassification	Recruit type (HighSchool/JUCO/PrepSchool/Transfer). (JUCO , PrepSchool , HighSchool)
<code>year</code>	int	Season year.
<code>ranking</code>	int	Rank (1 = best) within the given scope.
<code>name</code>	str	Name.
<code>school</code>	str	School/team name.
<code>committedTo</code>	str	School the recruit committed to.
<code>position</code>	str	Position abbreviation.
<code>height</code>	float	Height in inches.
<code>weight</code>	int	Weight in pounds.
<code>stars</code>	int	Recruit star rating (1-5).
<code>rating</code>	float	Composite rating score.
<code>city</code>	str	City name.
<code>stateProvince</code>	str	State province.
<code>country</code>	str	Country.
<code>hometownInfo</code>	RecruitHometownInfo	Recruit's hometown details. — see RecruitHometownInfo

recruiting_teams

- **CFBD method:** `RecruitingApi.get_team_recruiting_rankings`
- **Scrape mode:** per season

Field	Type	Description
<code>year</code>	int	Season year.
<code>rank</code>	int	Rank (1 = best) within the given scope.
<code>team</code>	str	Team name.
<code>points</code>	float	Points value for this rating component.

Stats

`advanced_game_stats`

- **CFBD method:** `StatsApi.get_advanced_game_stats`
- **Scrape mode:** per season

Per-game advanced efficiency stats (PPA, success rate, explosiveness, line yards, havoc) split by offense/defense and situation (standard downs / passing downs / rushing / passing).

Field	Type	Description
<code>gameId</code>	int	Game identifier, joins to the games endpoint.
<code>season</code>	int	Season year.
<code>seasonType</code>	SeasonTypeDB	<code>regular</code> or <code>postseason</code> . (<code>allstar</code> , <code>postseason</code> , <code>preseason</code> , <code>regular</code> , <code>spring_postseason</code> , <code>spring_regular</code>)
<code>week</code>	int	Week number within the season.
<code>team</code>	str	Team name.
<code>opponent</code>	str	Opponent team name.
<code>offense</code>	AdvancedGameStatOffense	Offensive-side breakdown. — see AdvancedGameStatOffense
<code>defense</code>	AdvancedGameStatDefense	Defensive-side breakdown. — see AdvancedGameStatDefense

`advanced_season_stats`

- **CFBD method:** `StatsApi.get_advanced_season_stats`
- **Scrape mode:** per season

Season-aggregated version of `AdvancedGameStat`.

Field	Type	Description
<code>season</code>	int	Season year.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>offense</code>	AdvancedSeasonStatOffense	Offensive-side breakdown. — see AdvancedSeasonStatOffense
<code>defense</code>	AdvancedSeasonStatDefense	Defensive-side breakdown. — see AdvancedSeasonStatDefense

stat_categories

- **CFBD method:** `StatsApi.get_categories`
- **Scrape mode:** once (no params)

Returns `List[str]` — a plain list of values, no object fields.

game_havoc_stats

- **CFBD method:** `StatsApi.get_game_havoc_stats`
- **Scrape mode:** per season

Havoc-rate breakdown (TFL/FF/PBU/INT share) for a game.

Field	Type	Description
<code>gameId</code>	int	Game identifier, joins to the games endpoint.
<code>season</code>	int	Season year.
<code>seasonType</code>	SeasonTypeDB	<code>regular</code> or <code>postseason</code> . (<code>allstar</code> , <code>postseason</code> , <code>preseason</code> , <code>regular</code> , <code>spring_postseason</code> , <code>spring_regular</code>)
<code>week</code>	int	Week number within the season.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>opponent</code>	str	Opponent team name.
<code>opponentConference</code>	str	Opponent conference.
<code>offense</code>	GameHavocStatsOffense	Offensive-side breakdown. — see GameHavocStatsOffense
<code>defense</code>	GameHavocStatsOffense	Defensive-side breakdown. — see GameHavocStatsOffense

player_season_stats

- **CFBD method:** `StatsApi.get_player_season_stats`
- **Scrape mode:** per season

Field	Type	Description
<code>season</code>	int	Season year.
<code>playerId</code>	str	Player ID.
<code>player</code>	str	Player.
<code>position</code>	str	Position abbreviation.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>category</code>	str	Statistic category/group.
<code>statType</code>	str	Category of statistic being recorded.

Field	Type	Description
<code>stat</code>	str	Statistic value.

player_success_season

- **CFBD method:** `StatsApi.get_player_season_success_rates`
- **Scrape mode:** per season

Field	Type	Description
<code>season</code>	int	Season year.
<code>id</code>	str	Unique identifier for the record.
<code>name</code>	str	Name.
<code>position</code>	str	Position abbreviation.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>passing</code>	PlayerSuccessRateSplit	Passing. — see PlayerSuccessRateSplit
<code>rushing</code>	PlayerSuccessRateSplit	Rushing. — see PlayerSuccessRateSplit

player_success_game

- **CFBD method:** `StatsApi.get_player_game_success_rates`
- **Scrape mode:** per season x week

Field	Type	Description
<code>season</code>	int	Season year.
<code>seasonType</code>	SeasonTypeDB	<code>regular</code> or <code>postseason</code> . (<code>allstar</code> , <code>postseason</code> , <code>preseason</code> , <code>regular</code> , <code>spring_postseason</code> , <code>spring_regular</code>)
<code>week</code>	int	Week number within the season.
<code>gameId</code>	int	Game identifier, joins to the games endpoint.
<code>id</code>	str	Unique identifier for the record.
<code>name</code>	str	Name.
<code>position</code>	str	Position abbreviation.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>opponent</code>	str	Opponent team name.
<code>passing</code>	PlayerSuccessRateSplit	Passing. — see PlayerSuccessRateSplit
<code>rushing</code>	PlayerSuccessRateSplit	Rushing. — see PlayerSuccessRateSplit

team_stats

- **CFBD method:** `StatsApi.get_team_stats`
- **Scrape mode:** per season

Field	Type	Description
<code>season</code>	int	Season year.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>statName</code>	str	Stat name.
<code>statValue</code>	TeamStatStatValue	Stat value. — see TeamStatStatValue

`advanced_game_stats_ngt`

- **CFBD method:** `StatsApi.get_advanced_game_stats`
- **Scrape mode:** per season

Same schema as its base endpoint above. `excludeGarbageTime=true` — drops garbage-time plays before aggregating, so values differ from the unfiltered twin.

`advanced_season_stats_ngt`

- **CFBD method:** `StatsApi.get_advanced_season_stats`
- **Scrape mode:** per season

Same schema as its base endpoint above. `excludeGarbageTime=true` — drops garbage-time plays before aggregating, so values differ from the unfiltered twin.

`player_success_season_ngt`

- **CFBD method:** `StatsApi.get_player_season_success_rates`
- **Scrape mode:** per season

Same schema as its base endpoint above. `excludeGarbageTime=true` — drops garbage-time plays before aggregating, so values differ from the unfiltered twin.

`player_success_game_ngt`

- **CFBD method:** `StatsApi.get_player_game_success_rates`
- **Scrape mode:** per season x week

Same schema as its base endpoint above. `excludeGarbageTime=true` — drops garbage-time plays before aggregating, so values differ from the unfiltered twin.

Teams

`fbs_teams`

- **CFBD method:** `TeamsApi.get_fbs_teams`
- **Scrape mode:** per season

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.
<code>school</code>	str	School/team name.
<code>mascot</code>	str	Team mascot name.
<code>abbreviation</code>	str	Short abbreviation.
<code>alternateNames</code>	List[str]	Alternate names.
<code>conference</code>	str	Conference name.
<code>division</code>	str	Conference division (e.g. East/West), if applicable.
<code>classification</code>	str	Division classification (FBS/FCS/II/III).
<code>color</code>	str	Primary brand color (hex).
<code>alternateColor</code>	str	Alternate color.
<code>logos</code>	List[str]	Logo image URLs.
<code>twitter</code>	str	Twitter/X handle.
<code>location</code>	Venue	Location details (city/state/lat/lon). — see Venue

matchup

- **CFBD method:** `TeamsApi.get_matchup`
- **Scrape mode:** on-demand (not bulk-scraped)

Field	Type	Description
<code>team1</code>	str	Team1.
<code>team2</code>	str	Team2.
<code>startYear</code>	int	Start year.
<code>endYear</code>	int	End year.
<code>team1Wins</code>	int	Team1 wins.
<code>team2Wins</code>	int	Team2 wins.
<code>ties</code>	int	Tie count.
<code>games</code>	List[MatchupGame]	Games coached.

roster

- **CFBD method:** `TeamsApi.get_roster`
- **Scrape mode:** per season

Field	Type	Description
<code>id</code>	str	Unique identifier for the record.
<code>firstName</code>	str	First name.

Field	Type	Description
lastName	str	Last name.
team	str	Team name.
height	float	Height in inches.
weight	int	Weight in pounds.
jersey	int	Jersey number.
year	int	Season year.
position	str	Position abbreviation.
homeCity	str	Home city.
homeState	str	Home state.
homeCountry	str	Home country.
homeLatitude	float	Home latitude.
homeLongitude	float	Home longitude.
homeCountyFIPS	str	Home county f i p s.
recruitIds	List[str]	Recruit IDs.

talent

- **CFBD method:** `TeamsApi.get_talent`
- **Scrape mode:** per season

Field	Type	Description
year	int	Season year.
team	str	Team name.
talent	float	Talent.

teams

- **CFBD method:** `TeamsApi.get_teams`
- **Scrape mode:** per season

Field	Type	Description
id	int	Unique identifier for the record.
school	str	School/team name.
mascot	str	Team mascot name.
abbreviation	str	Short abbreviation.
alternateNames	List[str]	Alternate names.
conference	str	Conference name.

Field	Type	Description
<code>division</code>	str	Conference division (e.g. East/West), if applicable.
<code>classification</code>	str	Division classification (FBS/FCS/II/III).
<code>color</code>	str	Primary brand color (hex).
<code>alternateColor</code>	str	Alternate color.
<code>logos</code>	List[str]	Logo image URLs.
<code>twitter</code>	str	Twitter/X handle.
<code>location</code>	Venue	Location details (city/state/lat/lon). — see Venue

teams_ats

- **CFBD method:** `TeamsApi.get_teams_ats`
- **Scrape mode:** per season

Field	Type	Description
<code>year</code>	int	Season year.
<code>teamId</code>	int	Team identifier.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>games</code>	int	Games coached.
<code>atsWins</code>	int	Ats wins.
<code>atsLosses</code>	int	Ats losses.
<code>atsPushes</code>	int	Ats pushes.
<code>avgCoverMargin</code>	float	Avg cover margin.

Venues

venues

- **CFBD method:** `VenuesApi.get_venues`
- **Scrape mode:** once (no params)

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.
<code>name</code>	str	Name.
<code>city</code>	str	City name.
<code>state</code>	str	State/province abbreviation.
<code>zip</code>	str	Postal code.
<code>countryCode</code>	str	ISO country code.

Field	Type	Description
<code>timezone</code>	str	IANA timezone name.
<code>latitude</code>	float	Latitude in decimal degrees.
<code>longitude</code>	float	Longitude in decimal degrees.
<code>elevation</code>	str	Elevation in feet.
<code>capacity</code>	int	Stadium capacity.
<code>constructionYear</code>	int	Year the venue was built.

Not bulk-scraped

`/info/usage` (`InfoApi.get_usage`) is registered in the live spec but has no scraper entry — it reports API account metering (request counts), not football data. See [docs/data-coverage.md](#) for the full rationale.

Nested / shared types

Object and enum types referenced by the response fields above, expanded once here instead of repeating inline.

AdjustedTeamMetrics

Field	Type	Description
<code>year</code>	int	Season year.
<code>teamId</code>	int	Team identifier.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>epa</code>	AdjustedTeamMetricsEpa	Expected Points Added — value of a play/drive/game in expected-points terms. — see AdjustedTeamMetricsEpa
<code>epaAllowed</code>	AdjustedTeamMetricsEpa	Expected Points Added allowed (defensive perspective). — see AdjustedTeamMetricsEpa
<code>successRate</code>	AdjustedTeamMetricsSuccessRate	Success rate. — see AdjustedTeamMetricsSuccessRate
<code>successRateAllowed</code>	AdjustedTeamMetricsSuccessRate	Success rate allowed. — see AdjustedTeamMetricsSuccessRate
<code>rushing</code>	AdjustedTeamMetricsRushing	Rushing. — see AdjustedTeamMetricsRushing
<code>rushingAllowed</code>	AdjustedTeamMetricsRushing	Rushing allowed. — see AdjustedTeamMetricsRushing
<code>explosiveness</code>	float	Average PPA on successful plays — a measure of big-play ability.
<code>explosivenessAllowed</code>	float	Explosiveness allowed.

AdjustedTeamMetricsEpa

Field	Type	Description
<code>rushing</code>	float	Rushing.
<code>passing</code>	float	Passing.
<code>total</code>	float	Total.

AdjustedTeamMetricsRushing

Field	Type	Description
<code>highlightYards</code>	float	Highlight yards.
<code>openFieldYards</code>	float	Run yards gained 10+ yards past the line of scrimmage.
<code>secondLevelYards</code>	float	Run yards gained 5-10 yards past the line of scrimmage.
<code>lineYards</code>	float	Yards attributable to the offensive line on run plays (Football Outsiders-style stat).

AdjustedTeamMetricsSuccessRate

Field	Type	Description
<code>passingDowns</code>	float	Passing downs.
<code>standardDowns</code>	float	Standard downs.
<code>total</code>	float	Total.

AdvancedBoxScore

Field	Type	Description
<code>gameInfo</code>	<code>AdvancedBoxScoreGameInfo</code>	Game info. — see AdvancedBoxScoreGameInfo
<code>teams</code>	<code>AdvancedBoxScoreTeams</code>	Teams. — see AdvancedBoxScoreTeams
<code>players</code>	<code>AdvancedBoxScorePlayers</code>	Players. — see AdvancedBoxScorePlayers

AdvancedBoxScoreGameInfo

Field	Type	Description
<code>excitement</code>	float	Excitement.
<code>homeWinner</code>	bool	Home winner.
<code>awayWinProb</code>	float	Away win prob.
<code>awayPoints</code>	int	Away team's final score.
<code>awayTeam</code>	str	Away team name.
<code>homeWinProb</code>	float	Home win prob.
<code>homePoints</code>	int	Home team's final score.
<code>homeTeam</code>	str	Home team name.

AdvancedBoxScorePlayers

Field	Type	Description
<code>ppa</code>	List[PlayerPPA]	Predicted Points Added — CFBD's play-value metric, similar to EPA.
<code>usage</code>	List[PlayerGameUsage]	Share of team plays/snaps the player was involved in, by situation.

AdvancedBoxScoreTeams

Field	Type	Description
<code>fieldPosition</code>	List[TeamFieldPosition]	Field position.
<code>scoringOpportunities</code>	List[TeamScoringOpportunities]	Scoring opportunities.
<code>havoc</code>	List[TeamHavoc]	Havoc rate — share of defensive plays with a TFL, forced fumble, pass breakup, or interception.
<code>rushing</code>	List[TeamRushingStats]	Rushing.
<code>explosiveness</code>	List[TeamExplosiveness]	Average PPA on successful plays — a measure of big-play ability.
<code>successRates</code>	List[TeamSuccessRates]	Success rates.
<code>cumulativePpa</code>	List[TeamPPA]	Cumulative PPA.
<code>ppa</code>	List[TeamPPA]	Predicted Points Added — CFBD's play-value metric, similar to EPA.

AdvancedGameStat

Field	Type	Description
<code>gameId</code>	int	Game identifier, joins to the games endpoint.
<code>season</code>	int	Season year.
<code>seasonType</code>	SeasonTypeDB	<code>regular</code> or <code>postseason</code> . (<code>allstar</code> , <code>postseason</code> , <code>preseason</code> , <code>regular</code> , <code>spring_postseason</code> , <code>spring_regular</code>)
<code>week</code>	int	Week number within the season.
<code>team</code>	str	Team name.
<code>opponent</code>	str	Opponent team name.
<code>offense</code>	AdvancedGameStatOffense	Offensive-side breakdown. — see AdvancedGameStatOffense
<code>defense</code>	AdvancedGameStatDefense	Defensive-side breakdown. — see AdvancedGameStatDefense

AdvancedGameStatDefense

Field	Type	Description
<code>passingPlays</code>	AdvancedGameStatOffensePassingPlays	Passing plays. — see AdvancedGameStatOffensePassingPlays

Field	Type	Description
rushingPlays	AdvancedGameStatOffensePassingPlays	Rushing plays. — see AdvancedGameStatOffensePassingPlays
passingDowns	AdvancedGameStatOffensePassingDowns	Passing downs. — see AdvancedGameStatOffensePassingDowns
standardDowns	AdvancedGameStatOffensePassingDowns	Standard downs. — see AdvancedGameStatOffensePassingDowns
openFieldYardsTotal	int	Open field yards total.
openFieldYards	float	Run yards gained 10+ yards past the line of scrimmage.
secondLevelYardsTotal	int	Second level yards total.
secondLevelYards	float	Run yards gained 5-10 yards past the line of scrimmage.
lineYardsTotal	int	Line yards total.
lineYards	float	Yards attributable to the offensive line on run plays (Football Outsiders-style stat).
stuffRate	float	Share of opponent run plays stopped at or behind the line of scrimmage.
powerSuccess	float	Power success.
explosiveness	float	Average PPA on successful plays — a measure of big-play ability.
successRate	float	Success rate.
totalPPA	float	Sum of PPA across plays.
ppa	float	Predicted Points Added — CFBD's play-value metric, similar to EPA.
drives	int	Number of drives.
plays	int	Number of plays.

AdvancedGameStatOffense

Field	Type	Description
passingPlays	AdvancedGameStatOffensePassingPlays	Passing plays. — see AdvancedGameStatOffensePassingPlays
rushingPlays	AdvancedGameStatOffensePassingPlays	Rushing plays. — see AdvancedGameStatOffensePassingPlays
passingDowns	AdvancedGameStatOffensePassingDowns	Passing downs. — see AdvancedGameStatOffensePassingDowns
standardDowns	AdvancedGameStatOffensePassingDowns	Standard downs. — see AdvancedGameStatOffensePassingDowns

Field	Type	Description
<code>openFieldYardsTotal</code>	int	Open field yards total.
<code>openFieldYards</code>	float	Run yards gained 10+ yards past the line of scrimmage.
<code>secondLevelYardsTotal</code>	int	Second level yards total.
<code>secondLevelYards</code>	float	Run yards gained 5-10 yards past the line of scrimmage.
<code>lineYardsTotal</code>	int	Line yards total.
<code>lineYards</code>	float	Yards attributable to the offensive line on run plays (Football Outsiders-style stat).
<code>stuffRate</code>	float	Share of opponent run plays stopped at or behind the line of scrimmage.
<code>powerSuccess</code>	float	Power success.
<code>explosiveness</code>	float	Average PPA on successful plays — a measure of big-play ability.
<code>successRate</code>	float	Success rate.
<code>totalPPA</code>	float	Sum of PPA across plays.
<code>ppa</code>	float	Predicted Points Added — CFBD's play-value metric, similar to EPA.
<code>drives</code>	int	Number of drives.
<code>plays</code>	int	Number of plays.

AdvancedGameStatOffensePassingDowns

Field	Type	Description
<code>explosiveness</code>	float	Average PPA on successful plays — a measure of big-play ability.
<code>successRate</code>	float	Success rate.
<code>ppa</code>	float	Predicted Points Added — CFBD's play-value metric, similar to EPA.

AdvancedGameStatOffensePassingPlays

Field	Type	Description
<code>explosiveness</code>	float	Average PPA on successful plays — a measure of big-play ability.
<code>successRate</code>	float	Success rate.
<code>totalPPA</code>	float	Sum of PPA across plays.
<code>ppa</code>	float	Predicted Points Added — CFBD's play-value metric, similar to EPA.

AdvancedSeasonStat

Field	Type	Description
<code>season</code>	int	Season year.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>offense</code>	AdvancedSeasonStatOffense	Offensive-side breakdown. — see AdvancedSeasonStatOffense
<code>defense</code>	AdvancedSeasonStatDefense	Defensive-side breakdown. — see AdvancedSeasonStatDefense

AdvancedSeasonStatDefense

Field	Type	Description
<code>passingPlays</code>	AdvancedSeasonStatOffensePassingPlays	Passing plays. — see AdvancedSeasonStatOffensePassingPlays
<code>rushingPlays</code>	AdvancedSeasonStatOffensePassingPlays	Rushing plays. — see AdvancedSeasonStatOffensePassingPlays
<code>passingDowns</code>	AdvancedSeasonStatOffensePassingPlays	Passing downs. — see AdvancedSeasonStatOffensePassingPlays
<code>standardDowns</code>	AdvancedSeasonStatOffensePassingDowns	Standard downs. — see AdvancedSeasonStatOffensePassingDowns
<code>havoc</code>	AdvancedSeasonStatOffenseHavoc	Havoc rate — share of defensive plays with a TFL, forced fumble, pass breakup, or interception. — see AdvancedSeasonStatOffenseHavoc
<code>fieldPosition</code>	AdvancedSeasonStatOffenseFieldPosition	Field position. — see AdvancedSeasonStatOffenseFieldPosition
<code>pointsPerOpportunity</code>	float	Points per opportunity.
<code>totalOpportunities</code>	int	Total opportunities.
<code>openFieldYardsTotal</code>	int	Open field yards total.
<code>openFieldYards</code>	float	Run yards gained 10+ yards past the line of scrimmage.
<code>secondLevelYardsTotal</code>	int	Second level yards total.
<code>secondLevelYards</code>	float	Run yards gained 5-10 yards past the line of scrimmage.
<code>lineYardsTotal</code>	int	Line yards total.
<code>lineYards</code>	float	Yards attributable to the offensive line on run plays (Football Outsiders-style stat).
<code>stuffRate</code>	float	Share of opponent run plays stopped at or behind the line of scrimmage.
<code>powerSuccess</code>	float	Power success.

Field	Type	Description
<code>explosiveness</code>	float	Average PPA on successful plays — a measure of big-play ability.
<code>successRate</code>	float	Success rate.
<code>totalPPA</code>	float	Sum of PPA across plays.
<code>ppa</code>	float	Predicted Points Added — CFBD's play-value metric, similar to EPA.
<code>drives</code>	int	Number of drives.
<code>plays</code>	int	Number of plays.

AdvancedSeasonStatOffense

Field	Type	Description
<code>passingPlays</code>	AdvancedSeasonStatOffensePassingPlays	Passing plays. — see AdvancedSeasonStatOffensePassingPlays
<code>rushingPlays</code>	AdvancedSeasonStatOffensePassingPlays	Rushing plays. — see AdvancedSeasonStatOffensePassingPlays
<code>passingDowns</code>	AdvancedSeasonStatOffensePassingDowns	Passing downs. — see AdvancedSeasonStatOffensePassingDowns
<code>standardDowns</code>	AdvancedSeasonStatOffensePassingDowns	Standard downs. — see AdvancedSeasonStatOffensePassingDowns
<code>havoc</code>	AdvancedSeasonStatOffenseHavoc	Havoc rate — share of defensive plays with a TFL, forced fumble, pass breakup, or interception. — see AdvancedSeasonStatOffenseHavoc
<code>fieldPosition</code>	AdvancedSeasonStatOffenseFieldPosition	Field position. — see AdvancedSeasonStatOffenseFieldPosition
<code>pointsPerOpportunity</code>	float	Points per opportunity.
<code>totalOpportunities</code>	int	Total opportunities.
<code>openFieldYardsTotal</code>	int	Open field yards total.
<code>openFieldYards</code>	float	Run yards gained 10+ yards past the line of scrimmage.
<code>secondLevelYardsTotal</code>	int	Second level yards total.
<code>secondLevelYards</code>	float	Run yards gained 5-10 yards past the line of scrimmage.
<code>lineYardsTotal</code>	int	Line yards total.
<code>lineYards</code>	float	Yards attributable to the offensive line on run plays (Football Outsiders-style stat).

Field	Type	Description
stuffRate	float	Share of opponent run plays stopped at or behind the line of scrimmage.
powerSuccess	float	Power success.
explosiveness	float	Average PPA on successful plays — a measure of big-play ability.
successRate	float	Success rate.
totalPPA	float	Sum of PPA across plays.
ppa	float	Predicted Points Added — CFBD's play-value metric, similar to EPA.
drives	int	Number of drives.
plays	int	Number of plays.

AdvancedSeasonStatOffenseFieldPosition

Field	Type	Description
averagePredictedPoints	float	Average predicted points.
averageStart	float	Average start.

AdvancedSeasonStatOffenseHavoc

Field	Type	Description
db	float	Havoc rate credited to defensive backs specifically.
frontSeven	float	Front seven.
total	float	Total.

AdvancedSeasonStatOffensePassingDowns

Field	Type	Description
explosiveness	float	Average PPA on successful plays — a measure of big-play ability.
successRate	float	Success rate.
ppa	float	Predicted Points Added — CFBD's play-value metric, similar to EPA.
rate	float	Rate.

AdvancedSeasonStatOffensePassingPlays

Field	Type	Description
explosiveness	float	Average PPA on successful plays — a measure of big-play ability.
successRate	float	Success rate.

Field	Type	Description
<code>totalPPA</code>	float	Sum of PPA across plays.
<code>ppa</code>	float	Predicted Points Added — CFBD's play-value metric, similar to EPA.
<code>rate</code>	float	Rate.

AggregatedTeamRecruiting

Field	Type	Description
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>positionGroup</code>	str	Position group.
<code>averageRating</code>	float	Average rating.
<code>totalRating</code>	float	Total rating.
<code>commits</code>	int	Commits.
<code>averageStars</code>	float	Average stars.

BettingGame

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.
<code>season</code>	int	Season year.
<code>seasonType</code>	SeasonType	<code>regular</code> or <code>postseason</code> . (<code>regular</code> , <code>postseason</code> , <code>both</code> , <code>allstar</code> , <code>spring_regular</code> , <code>spring_postseason</code>)
<code>week</code>	int	Week number within the season.
<code>startDate</code>	datetime	Kickoff date/time (UTC).
<code>homeTeamId</code>	int	Home team ID.
<code>homeTeam</code>	str	Home team name.
<code>homeConference</code>	str	Home team's conference at the time of the game.
<code>homeClassification</code>	DivisionClassification	Home team's division (FBS/FCS/etc). (<code>fbs</code> , <code>fcs</code> , <code>ii</code> , <code>ii/iii</code> , <code>iii</code>)
<code>homeScore</code>	int	Home score.
<code>awayTeamId</code>	int	Away team ID.
<code>awayTeam</code>	str	Away team name.
<code>awayConference</code>	str	Away team's conference at the time of the game.
<code>awayClassification</code>	DivisionClassification	Away team's division (FBS/FCS/etc). (<code>fbs</code> , <code>fcs</code> , <code>ii</code> , <code>ii/iii</code> , <code>iii</code>)
<code>awayScore</code>	int	Away score.
<code>lines</code>	List[GameLine]	Lines.

CalendarWeek

Field	Type	Description
<code>season</code>	int	Season year.
<code>week</code>	int	Week number within the season.
<code>seasonType</code>	SeasonType	<code>regular</code> or <code>postseason</code> . (<code>regular</code> , <code>postseason</code> , <code>both</code> , <code>allstar</code> , <code>spring_regular</code> , <code>spring_postseason</code>)
<code>startDate</code>	datetime	Kickoff date/time (UTC).
<code>endDate</code>	datetime	End date.
<code>firstGameStart</code>	datetime	First game start.
<code>lastGameStart</code>	datetime	Last game start.

CfpCoachSeasonOutcome

Enum values: `active`, `eliminated`, `champion`

CfpPlayoff

Field	Type	Description
<code>season</code>	int	Season year.
<code>competition</code>	PlayoffCompetitionCfp	Competition. (<code>cfp</code>)
<code>format</code>	str	Format.
<code>teamCount</code>	int	Team count.
<code>status</code>	PlayoffStatus	Status. (<code>scheduled</code> , <code>selected</code> , <code>in_progress</code> , <code>completed</code>)
<code>participants</code>	List[PlayoffParticipant]	Participants.
<code>rounds</code>	List[PlayoffRoundRecord]	Rounds.
<code>champion</code>	PlayoffTeam	Champion. — see PlayoffTeam

Coach

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.
<code>firstName</code>	str	First name.
<code>lastName</code>	str	Last name.
<code>hireDate</code>	datetime	Date the coach was hired.
<code>seasons</code>	List[CoachSeason]	Seasons.

CoachAlmaMater

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.
<code>school</code>	str	School/team name.

CoachCareer

Field	Type	Description
<code>games</code>	int	Games coached.
<code>wins</code>	int	Win count.
<code>losses</code>	int	Loss count.
<code>ties</code>	int	Tie count.
<code>winPercentage</code>	float	Win percentage.
<code>seasons</code>	int	Seasons.
<code>teams</code>	int	Teams.
<code>firstYear</code>	int	First year.
<code>lastYear</code>	int	Last year.

CoachCfpContext

Field	Type	Description
<code>appeared</code>	bool	Appeared.
<code>seed</code>	int	Seed.
<code>outcome</code>	CfpCoachSeasonOutcome	Outcome. (<code>active</code> , <code>eliminated</code> , <code>champion</code>)

CoachDraftContext

Field	Type	Description
<code>year</code>	int	Season year.
<code>totalPicks</code>	int	Total picks.
<code>firstRoundPicks</code>	int	First round picks.

CoachPollResume

Field	Type	Description
<code>preseasonRank</code>	int	Preseason poll rank.
<code>postseasonRank</code>	int	Final/postseason poll rank.
<code>bestRank</code>	int	Best rank.
<code>weeksRanked</code>	int	Weeks ranked.

Field	Type	Description
<code>weeksTopTen</code>	int	Weeks top ten.

CoachProfile

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.
<code>firstName</code>	str	First name.
<code>lastName</code>	str	Last name.
<code>displayName</code>	str	Full display name.
<code>currentTeam</code>	CoachSeasonTeamReference	Current team. — see CoachSeasonTeamReference
<code>career</code>	CoachCareer	Career. — see CoachCareer
<code>birthDate</code>	str	Birth date.
<code>almaMater</code>	CoachAlmaMater	Alma mater. — see CoachAlmaMater
<code>graduationYear</code>	int	Graduation year.
<code>wikidataId</code>	str	Wikidata ID.
<code>hallOfFameYear</code>	int	Hall of fame year.

CoachRatingContext

Field	Type	Description
<code>spSpecialTeams</code>	float	SP+ special teams.
<code>strengthOfSchedule</code>	float	Strength of schedule.
<code>secondOrderWins</code>	float	Second-order (efficiency-based expected) win total.
<code>fpi</code>	float	FPI.
<code>yearOverYear</code>	CoachRatingContextYearOverYear	Year over year. — see CoachRatingContextYearOverYear

CoachRatingContextYearOverYear

Field	Type	Description
<code>spOverall</code>	float	SP+ overall.
<code>srs</code>	float	SRS.
<code>wins</code>	int	Win count.

CoachRecord

Field	Type	Description
<code>games</code>	int	Games coached.

Field	Type	Description
<code>wins</code>	int	Win count.
<code>losses</code>	int	Loss count.
<code>ties</code>	int	Tie count.
<code>winPercentage</code>	float	Win percentage.

CoachRecordSplits

Field	Type	Description
<code>conference</code>	CoachRecord	Conference name. — see CoachRecord
<code>postseason</code>	CoachRecord	Postseason. — see CoachRecord
<code>home</code>	CoachRecord	Home. — see CoachRecord
<code>away</code>	CoachRecord	Away. — see CoachRecord
<code>neutral</code>	CoachRecord	Neutral. — see CoachRecord

CoachRecruitingContext

Field	Type	Description
<code>rank</code>	int	Rank (1 = best) within the given scope.
<code>points</code>	float	Points value for this rating component.
<code>talent</code>	float	Talent.

CoachReference

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.
<code>firstName</code>	str	First name.
<code>lastName</code>	str	Last name.

CoachScoring

Field	Type	Description
<code>pointsFor</code>	int	Points for.
<code>pointsAgainst</code>	int	Points against.
<code>averagePointDifferential</code>	float	Average point differential.

CoachSeasonTeamReference

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.

Field	Type	Description
school	str	School/team name.
conference	str	Conference name.

CoachTeamReference

Field	Type	Description
id	int	Unique identifier for the record.
school	str	School/team name.

CoachTenure

Field	Type	Description
id	int	Unique identifier for the record.
coach	CoachReference	Coach name. — see CoachReference
team	CoachTeamReference	Team name. — see CoachTeamReference
hireDate	str	Date the coach was hired.
startYear	int	Start year.
endYear	int	End year.
effectiveStart	datetime	Effective start.
effectiveEnd	datetime	Effective end.
isInterim	bool	Is interim.
active	bool	Active.
seasons	int	Seasons.
record	CoachRecord	Record. — see CoachRecord
attributionComplete	bool	Attribution complete.

Conference

Field	Type	Description
id	int	Unique identifier for the record.
name	str	Name.
shortName	str	Short name.
abbreviation	str	Short abbreviation.
classification	ConferenceClassification	Division classification (FBS/FCS/II/III). (fbs , fcs , ii , ii/iii , iii)
memberCount	int	Member count.

ConferenceClassification

Enum values: [fbs](#), [fcs](#), [ii](#), [ii/iii](#), [iii](#)

ConferenceSP

Field	Type	Description
year	int	Season year.
conference	str	Conference name.
rating	float	Composite rating score.
secondOrderWins	float	Second-order (efficiency-based expected) win total.
sos	float	Strength of schedule rating.
offense	ConferenceSPOffense	Offensive-side breakdown. — see ConferenceSPOffense
defense	ConferenceSPDefense	Defensive-side breakdown. — see ConferenceSPDefense
specialTeams	TeamSPSpecialTeams	Special-teams breakdown. — see TeamSPSpecialTeams

ConferenceSPDefense

Field	Type	Description
havoc	AdvancedSeasonStatOffenseHavoc	Havoc rate — share of defensive plays with a TFL, forced fumble, pass breakup, or interception. — see AdvancedSeasonStatOffenseHavoc
passingDowns	float	Passing downs.
standardDowns	float	Standard downs.
passing	float	Passing.
rushing	float	Rushing.
explosiveness	float	Average PPA on successful plays — a measure of big-play ability.
success	float	Success rate — share of plays gaining enough yardage to be an on-schedule down (per Football Outsiders rules).
rating	float	Composite rating score.

ConferenceSPOffense

Field	Type	Description
pace	float	Plays run per minute of possession (tempo).
runRate	float	Run rate.
passingDowns	float	Passing downs.
standardDowns	float	Standard downs.
passing	float	Passing.
rushing	float	Rushing.

Field	Type	Description
explosiveness	float	Average PPA on successful plays — a measure of big-play ability.
success	float	Success rate — share of plays gaining enough yardage to be an on-schedule down (per Football Outsiders rules).
rating	float	Composite rating score.

CoreRatingSeasonType

Enum values: [regular](#), [postseason](#)

DetailedCoachSeason

Field	Type	Description
games	int	Games coached.
wins	int	Win count.
losses	int	Loss count.
ties	int	Tie count.
winPercentage	float	Win percentage.
coach	CoachReference	Coach name. — see CoachReference
team	CoachSeasonTeamReference	Team name. — see CoachSeasonTeamReference
year	int	Season year.
preseasonRank	int	Preseason poll rank.
postseasonRank	int	Final/postseason poll rank.
srs	float	SRS.
spOverall	float	SP+ overall.
spOffense	float	SP+ offense.
spDefense	float	SP+ defense.
teamMetrics	CoachRatingContext	Team metrics. — see CoachRatingContext
recruiting	CoachRecruitingContext	Recruiting. — see CoachRecruitingContext
pollResume	CoachPollResume	Poll resume. — see CoachPollResume
attributionComplete	bool	Attribution complete.
recordSplits	CoachRecordSplits	Record splits. — see CoachRecordSplits
scoring	CoachScoring	True if the play resulted in points. — see CoachScoring
cfp	CoachCfpContext	Cfp. — see CoachCfpContext
draftFollowingSeason	CoachDraftContext	Draft following season. — see CoachDraftContext

DivisionClassification

Enum values: `fbs`, `fcs`, `ii`, `ii/iii`, `iii`

DraftPick

Field	Type	Description
<code>collegeAthleteId</code>	int	College player identifier.
<code>nflAthleteId</code>	int	NFL.com player identifier.
<code>collegeId</code>	int	College ID.
<code>collegeTeam</code>	str	College the player was drafted from.
<code>collegeConference</code>	str	College conference the player was drafted from.
<code>nflTeamId</code>	int	Nfl team ID.
<code>nflTeam</code>	str	NFL team that drafted the player.
<code>year</code>	int	Season year.
<code>overall</code>	int	Overall (combined) rating.
<code>round</code>	int	Round.
<code>pick</code>	int	Overall draft pick number.
<code>name</code>	str	Name.
<code>position</code>	str	Position abbreviation.
<code>height</code>	float	Height in inches.
<code>weight</code>	int	Weight in pounds.
<code>preDraftRanking</code>	int	Pre draft ranking.
<code>preDraftPositionRanking</code>	int	Pre draft position ranking.
<code>preDraftGrade</code>	int	Pre draft grade.
<code>hometownInfo</code>	DraftPickHometownInfo	Recruit's hometown details. — see DraftPickHometownInfo

DraftPickHometownInfo

Field	Type	Description
<code>countyFips</code>	str	County fips.
<code>longitude</code>	str	Longitude in decimal degrees.
<code>latitude</code>	str	Latitude in decimal degrees.
<code>country</code>	str	Country.
<code>state</code>	str	State/province abbreviation.
<code>city</code>	str	City name.

DraftPosition

Field	Type	Description
<code>name</code>	str	Name.
<code>abbreviation</code>	str	Short abbreviation.

DraftTeam

Field	Type	Description
<code>location</code>	str	Location details (city/state/lat/lon).
<code>nickname</code>	str	Nickname.
<code>displayName</code>	str	Full display name.
<code>logo</code>	str	Logo.

Drive

Field	Type	Description
<code>offense</code>	str	Offensive-side breakdown.
<code>offenseConference</code>	str	Offense team's conference.
<code>defense</code>	str	Defensive-side breakdown.
<code>defenseConference</code>	str	Defense team's conference.
<code>gameId</code>	int	Game identifier, joins to the games endpoint.
<code>id</code>	str	Unique identifier for the record.
<code>driveNumber</code>	int	Drive number.
<code>scoring</code>	bool	True if the play resulted in points.
<code>startPeriod</code>	int	Start period.
<code>startYardline</code>	int	Start yardline.
<code>startYardsToGoal</code>	int	Start yards to goal.
<code>startTime</code>	PlayClock	Start time. — see PlayClock
<code>endPeriod</code>	int	End period.
<code>endYardline</code>	int	End yardline.
<code>endYardsToGoal</code>	int	End yards to goal.
<code>endTime</code>	PlayClock	End time. — see PlayClock
<code>elapsed</code>	PlayClock	Elapsed. — see PlayClock
<code>plays</code>	int	Number of plays.
<code>yards</code>	int	Yards.
<code>driveResult</code>	str	Drive result.
<code>isHomeOffense</code>	bool	Is home offense.

Field	Type	Description
<code>startOffenseScore</code>	int	Start offense score.
<code>startDefenseScore</code>	int	Start defense score.
<code>endOffenseScore</code>	int	End offense score.
<code>endDefenseScore</code>	int	End defense score.

ExpandedTeamSRS

Field	Type	Description
<code>year</code>	int	Season year.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>division</code>	str	Conference division (e.g. East/West), if applicable.
<code>rating</code>	float	Composite rating score.
<code>ranking</code>	int	Rank (1 = best) within the given scope.
<code>classification</code>	DivisionClassification	Division classification (FBS/FCS/II/III). (<code>fbs</code> , <code>fcs</code> , <code>ii</code> , <code>ii/iii</code> , <code>iii</code>)

FieldGoalEP

Field	Type	Description
<code>yardsToGoal</code>	int	Yards remaining to the opponent's goal line.
<code>distance</code>	int	Yards to go for a first down.
<code>expectedPoints</code>	float	Expected points.

Game

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.
<code>season</code>	int	Season year.
<code>week</code>	int	Week number within the season.
<code>seasonType</code>	SeasonType	<code>regular</code> or <code>postseason</code> . (<code>regular</code> , <code>postseason</code> , <code>both</code> , <code>allstar</code> , <code>spring_regular</code> , <code>spring_postseason</code>)
<code>startDate</code>	datetime	Kickoff date/time (UTC).
<code>startTimeTBD</code>	bool	True if kickoff time was not yet announced.
<code>completed</code>	bool	True once the game has finished.
<code>neutralSite</code>	bool	True if played at a neutral (non-home) site.
<code>conferenceGame</code>	bool	True if both teams share a conference.

Field	Type	Description
attendance	int	Reported attendance.
venueId	int	Venue identifier, joins to the venues endpoint.
venue	str	Venue name.
homeId	int	Home team identifier.
homeTeam	str	Home team name.
homeConference	str	Home team's conference at the time of the game.
homeClassification	DivisionClassification	Home team's division (FBS/FCS/etc). (fbs , fcs , ii , ii/iii , iii)
homePoints	int	Home team's final score.
homeLineScores	List[Union[float]]	Home team's score by quarter/period.
homePostgameWinProbability	float	Model-estimated home win probability after the game.
homePregameElo	int	Home team's Elo rating entering the game.
homePostgameElo	int	Home team's Elo rating after the game.
awayId	int	Away team identifier.
awayTeam	str	Away team name.
awayConference	str	Away team's conference at the time of the game.
awayClassification	DivisionClassification	Away team's division (FBS/FCS/etc). (fbs , fcs , ii , ii/iii , iii)
awayPoints	int	Away team's final score.
awayLineScores	List[Union[float]]	Away team's score by quarter/period.
awayPostgameWinProbability	float	Model-estimated away win probability after the game.
awayPregameElo	int	Away team's Elo rating entering the game.
awayPostgameElo	int	Away team's Elo rating after the game.
excitementIndex	float	CFBD's game-excitement metric, derived from win-probability swings.
highlights	str	Highlight video URL, if available.
notes	str	Free-text notes about the game (e.g. bowl name).
playoff	GamePlayoff	Playoff context for the game (round/bracket), if applicable. — see GamePlayoff

GameHavocStats

Field	Type	Description
gameId	int	Game identifier, joins to the games endpoint.
season	int	Season year.

Field	Type	Description
seasonType	SeasonTypeDB	regular or postseason . (allstar , postseason , preseason , regular , spring_postseason , spring_regular)
week	int	Week number within the season.
team	str	Team name.
conference	str	Conference name.
opponent	str	Opponent team name.
opponentConference	str	Opponent conference.
offense	GameHavocStatsOffense	Offensive-side breakdown. — see GameHavocStatsOffense
defense	GameHavocStatsOffense	Defensive-side breakdown. — see GameHavocStatsOffense

GameHavocStatsOffense

Field	Type	Description
dbHavocRate	float	Db havoc rate.
frontSevenHavocRate	float	Front seven havoc rate.
havocRate	float	Havoc rate.
dbHavocEvents	float	Db havoc events.
frontSevenHavocEvents	float	Front seven havoc events.
totalHavocEvents	float	Total havoc events.
totalPlays	float	Total plays.

GameMedia

Field	Type	Description
id	int	Unique identifier for the record.
season	int	Season year.
week	int	Week number within the season.
seasonType	SeasonType	regular or postseason . (regular , postseason , both , allstar , spring_regular , spring_postseason)
startTime	datetime	Start time.
isStartTimeTBD	bool	Is start time t b d.
homeTeam	str	Home team name.
homeConference	str	Home team's conference at the time of the game.
awayTeam	str	Away team name.
awayConference	str	Away team's conference at the time of the game.

Field	Type	Description
<code>mediaType</code>	MediaType	Media type. (<code>tv</code> , <code>radio</code> , <code>web</code> , <code>ppv</code> , <code>mobile</code>)
<code>outlet</code>	str	Outlet.

GamePlayerStats

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.
<code>teams</code>	List[GamePlayerStatsTeam]	Teams.

GamePlayoff

Field	Type	Description
<code>competition</code>	PlayoffCompetition	Competition. (<code>cfp</code>)
<code>format</code>	str	Format.
<code>round</code>	PlayoffRound	Round. (<code>first_round</code> , <code>quarterfinal</code> , <code>semifinal</code> , <code>championship</code>)
<code>roundName</code>	str	Round name.
<code>bracketSlot</code>	str	Bracket slot.
<code>homeSeed</code>	int	Home seed.
<code>awaySeed</code>	int	Away seed.
<code>bowlName</code>	str	Bowl name.

GameStatus

Enum values: `scheduled`, `in_progress`, `completed`

GameTeamStats

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.
<code>teams</code>	List[GameTeamStatsTeam]	Teams.

GameWeather

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.
<code>season</code>	int	Season year.
<code>week</code>	int	Week number within the season.
<code>seasonType</code>	SeasonType	<code>regular</code> or <code>postseason</code> . (<code>regular</code> , <code>postseason</code> , <code>both</code> , <code>allstar</code> , <code>spring_regular</code> , <code>spring_postseason</code>)

Field	Type	Description
startTime	datetime	Start time.
gameIndoors	bool	Game indoors.
homeTeam	str	Home team name.
homeConference	str	Home team's conference at the time of the game.
awayTeam	str	Away team name.
awayConference	str	Away team's conference at the time of the game.
venueId	int	Venue identifier, joins to the venues endpoint.
venue	str	Venue name.
temperature	float	Temperature.
dewPoint	float	Dew point.
humidity	float	Humidity.
precipitation	float	Precipitation.
snowfall	float	Snowfall.
windDirection	float	Wind direction.
windSpeed	float	Wind speed.
pressure	float	Pressure.
weatherConditionCode	float	Weather condition code.
weatherCondition	str	Weather condition.

KickerPAAR

Field	Type	Description
year	int	Season year.
athleteId	str	Player identifier.
athleteName	str	Player name.
team	str	Team name.
conference	str	Conference name.
paar	float	Points Above Average Replacement on field goal attempts.
attempts	int	Attempts.

LiveGame

Field	Type	Description
id	int	Unique identifier for the record.
status	str	Status.

Field	Type	Description
<code>period</code>	int	Quarter/period number.
<code>clock</code>	str	Game clock at the time of the play/event.
<code>possession</code>	str	Possession.
<code>down</code>	int	Down number (1-4).
<code>distance</code>	int	Yards to go for a first down.
<code>yardsToGoal</code>	int	Yards remaining to the opponent's goal line.
<code>teams</code>	List[LiveGameTeam]	Teams.
<code>drives</code>	List[LiveGameDrive]	Number of drives.

Matchup

Field	Type	Description
<code>team1</code>	str	Team1.
<code>team2</code>	str	Team2.
<code>startYear</code>	int	Start year.
<code>endYear</code>	int	End year.
<code>team1Wins</code>	int	Team1 wins.
<code>team2Wins</code>	int	Team2 wins.
<code>ties</code>	int	Tie count.
<code>games</code>	List[MatchupGame]	Games coached.

MediaType

Enum values: `tv`, `radio`, `web`, `ppv`, `mobile`

PassDepth

Enum values: `short`, `deep`

PassDirection

Enum values: `left`, `middle`, `right`

PassLocation

Enum values: `short left`, `short middle`, `short right`, `deep left`, `deep middle`, `deep right`

PassOutcome

Enum values: `completion`, `incompletion`, `interception`

PassParseStatus

Enum values: `complete`, `partial`, `invalid`

PassingPlay

Field	Type	Description
<code>gameId</code>	int	Game identifier, joins to the games endpoint.
<code>playId</code>	str	Play ID.
<code>driveId</code>	str	Drive ID.
<code>season</code>	int	Season year.
<code>week</code>	int	Week number within the season.
<code>seasonType</code>	SeasonType	<code>regular</code> or <code>postseason</code> . (<code>regular</code> , <code>postseason</code> , <code>both</code> , <code>allstar</code> , <code>spring_regular</code> , <code>spring_postseason</code>)
<code>offenseId</code>	int	Offense ID.
<code>offense</code>	str	Offensive-side breakdown.
<code>offenseConference</code>	str	Offense team's conference.
<code>defenseId</code>	int	Defense ID.
<code>defense</code>	str	Defensive-side breakdown.
<code>defenseConference</code>	str	Defense team's conference.
<code>period</code>	int	Quarter/period number.
<code>clock</code>	PassingPlayClock	Game clock at the time of the play/event. — see PassingPlayClock
<code>down</code>	int	Down number (1-4).
<code>distance</code>	int	Yards to go for a first down.
<code>playText</code>	str	Human-readable play description.
<code>passerId</code>	str	Passer ID.
<code>passer</code>	str	Passer.
<code>targetId</code>	str	Target ID.
<code>target</code>	str	Target.
<code>outcome</code>	PassOutcome	Outcome. (<code>completion</code> , <code>incompletion</code> , <code>interception</code>)
<code>airYards</code>	int	Air yards.
<code>passDepth</code>	PassDepth	Pass depth. (<code>short</code> , <code>deep</code>)
<code>passDirection</code>	PassDirection	Pass direction. (<code>left</code> , <code>middle</code> , <code>right</code>)
<code>passLocation</code>	PassLocation	Pass location. (<code>short left</code> , <code>short middle</code> , <code>short right</code> , <code>deep left</code> , <code>deep middle</code> , <code>deep right</code>)
<code>totalYards</code>	int	Total yards.
<code>yardsAfterCatch</code>	int	Yards after catch.

Field	Type	Description
<code>startYardline</code>	int	Start yardline.
<code>startYardsToGoal</code>	int	Start yards to goal.
<code>targetYardsToGoal</code>	int	Target yards to goal.
<code>isSpike</code>	bool	Is spike.
<code>isThrowaway</code>	bool	Is throwaway.
<code>isIntentionalGrounding</code>	bool	Is intentional grounding.
<code>parseStatus</code>	PassParseStatus	Parse status. (<code>complete</code> , <code>partial</code> , <code>invalid</code>)

PassingPlayClock

Field	Type	Description
<code>minutes</code>	int	Minutes.
<code>seconds</code>	int	Seconds.

PassingProduction

Field	Type	Description
<code>attempts</code>	int	Attempts.
<code>completions</code>	int	Completions.
<code>incompletions</code>	int	Incompletions.
<code>interceptions</code>	int	Interceptions.
<code>completionRate</code>	float	Completion rate.
<code>airYardsAttemptsAvailable</code>	int	Air yards attempts available.
<code>totalAirYards</code>	int	Total air yards.
<code>averageDepthOfTarget</code>	float	Average depth of target.
<code>totalYardsAttemptsAvailable</code>	int	Total yards attempts available.
<code>totalYards</code>	int	Total yards.
<code>yardsAfterCatchAttemptsAvailable</code>	int	Yards after catch attempts available.
<code>totalYardsAfterCatch</code>	int	Total yards after catch.
<code>averageYardsAfterCatch</code>	float	Average yards after catch.

Play

Field	Type	Description
<code>id</code>	str	Unique identifier for the record.
<code>driveId</code>	str	Drive ID.

Field	Type	Description
<code>gameId</code>	int	Game identifier, joins to the games endpoint.
<code>driveNumber</code>	int	Drive number.
<code>playNumber</code>	int	Play number.
<code>offense</code>	str	Offensive-side breakdown.
<code>offenseConference</code>	str	Offense team's conference.
<code>offenseScore</code>	int	Offense team's score at the time of the play.
<code>defense</code>	str	Defensive-side breakdown.
<code>home</code>	str	Home.
<code>away</code>	str	Away.
<code>defenseConference</code>	str	Defense team's conference.
<code>defenseScore</code>	int	Defense team's score at the time of the play.
<code>period</code>	int	Quarter/period number.
<code>clock</code>	PlayClock	Game clock at the time of the play/event. — see PlayClock
<code>offenseTimeouts</code>	int	Offense timeouts.
<code>defenseTimeouts</code>	int	Defense timeouts.
<code>yardline</code>	int	Yardline.
<code>yardsToGoal</code>	int	Yards remaining to the opponent's goal line.
<code>down</code>	int	Down number (1-4).
<code>distance</code>	int	Yards to go for a first down.
<code>yardsGained</code>	int	Yards gained on the play.
<code>scoring</code>	bool	True if the play resulted in points.
<code>playType</code>	str	Play type (run/pass/punt/etc).
<code>playText</code>	str	Human-readable play description.
<code>ppa</code>	float	Predicted Points Added — CFBD's play-value metric, similar to EPA.
<code>wallclock</code>	str	Real-world timestamp of the event.

PlayClock

Field	Type	Description
<code>seconds</code>	int	Seconds.
<code>minutes</code>	int	Minutes.

PlayStat

Field	Type	Description
<code>gameId</code>	float	Game identifier, joins to the games endpoint.
<code>season</code>	float	Season year.
<code>week</code>	float	Week number within the season.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>opponent</code>	str	Opponent team name.
<code>teamScore</code>	float	Team score.
<code>opponentScore</code>	float	Opponent score.
<code>driveId</code>	str	Drive ID.
<code>playId</code>	str	Play ID.
<code>period</code>	float	Quarter/period number.
<code>clock</code>	PlayStatClock	Game clock at the time of the play/event. — see PlayStatClock
<code>yardsToGoal</code>	float	Yards remaining to the opponent's goal line.
<code>down</code>	float	Down number (1-4).
<code>distance</code>	float	Yards to go for a first down.
<code>athleteId</code>	str	Player identifier.
<code>athleteName</code>	str	Player name.
<code>statType</code>	str	Category of statistic being recorded.
<code>stat</code>	float	Statistic value.

PlayStatClock

Field	Type	Description
<code>seconds</code>	float	Seconds.
<code>minutes</code>	float	Minutes.

PlayStatType

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.
<code>name</code>	str	Name.

PlayType

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.

Field	Type	Description
text	str	Text.
abbreviation	str	Short abbreviation.

PlayWinProbability

Field	Type	Description
gameId	int	Game identifier, joins to the games endpoint.
playId	str	Play ID.
playText	str	Human-readable play description.
homeId	int	Home team identifier.
home	str	Home.
awayId	int	Away team identifier.
away	str	Away.
spread	float	Closing point spread (negative = favorite by that many points), home-team perspective unless noted.
homeBall	bool	Home ball.
homeScore	int	Home score.
awayScore	int	Away score.
yardLine	int	Yard line (0-100, own end zone to opponent's).
down	int	Down number (1-4).
distance	int	Yards to go for a first down.
homeWinProbability	float	Home win probability.
playNumber	int	Play number.

PlayerGamePredictedPointsAdded

Field	Type	Description
season	int	Season year.
week	int	Week number within the season.
seasonType	SeasonType	regular or postseason. (regular, postseason, both, allstar, spring_regular, spring_postseason)
id	str	Unique identifier for the record.
name	str	Name.
position	str	Position abbreviation.
team	str	Team name.

Field	Type	Description
opponent	str	Opponent team name.
averagePPA	PlayerGamePredictedPointsAddedAveragePPA	Average p p a. — see PlayerGamePredictedPointsAddedAveragePPA

PlayerGamePredictedPointsAddedAveragePPA

Field	Type	Description
pass	float	Pass.
all	float	All.

PlayerGameSuccessRate

Field	Type	Description
season	int	Season year.
seasonType	SeasonTypeDB	regular or postseason . (allstar , postseason , preseason , regular , spring_postseason , spring_regular)
week	int	Week number within the season.
gameId	int	Game identifier, joins to the games endpoint.
id	str	Unique identifier for the record.
name	str	Name.
position	str	Position abbreviation.
team	str	Team name.
conference	str	Conference name.
opponent	str	Opponent team name.
passing	PlayerSuccessRateSplit	Passing. — see PlayerSuccessRateSplit
rushing	PlayerSuccessRateSplit	Rushing. — see PlayerSuccessRateSplit

PlayerPassingGame

Field	Type	Description
attempts	int	Attempts.
completions	int	Completions.
incompletions	int	Incompletions.
interceptions	int	Interceptions.
completionRate	float	Completion rate.
airYardsAttemptsAvailable	int	Air yards attempts available.
totalAirYards	int	Total air yards.

Field	Type	Description
averageDepthOfTarget	float	Average depth of target.
totalYardsAttemptsAvailable	int	Total yards attempts available.
totalYards	int	Total yards.
yardsAfterCatchAttemptsAvailable	int	Yards after catch attempts available.
totalYardsAfterCatch	int	Total yards after catch.
averageYardsAfterCatch	float	Average yards after catch.
gameId	int	Game identifier, joins to the games endpoint.
season	int	Season year.
week	int	Week number within the season.
seasonType	SeasonType	regular or postseason. (regular, postseason, both, allstar, spring_regular, spring_postseason)
playerId	str	Player ID.
player	str	Player.
team	str	Team name.
conference	str	Conference name.
opponent	str	Opponent team name.

PlayerPassingSeason

Field	Type	Description
attempts	int	Attempts.
completions	int	Completions.
incompletions	int	Incompletions.
interceptions	int	Interceptions.
completionRate	float	Completion rate.
airYardsAttemptsAvailable	int	Air yards attempts available.
totalAirYards	int	Total air yards.
averageDepthOfTarget	float	Average depth of target.
totalYardsAttemptsAvailable	int	Total yards attempts available.
totalYards	int	Total yards.
yardsAfterCatchAttemptsAvailable	int	Yards after catch attempts available.
totalYardsAfterCatch	int	Total yards after catch.
averageYardsAfterCatch	float	Average yards after catch.
season	int	Season year.

Field	Type	Description
playerId	str	Player ID.
player	str	Player.
team	str	Team name.
conference	str	Conference name.

PlayerSearchResult

Field	Type	Description
id	str	Unique identifier for the record.
team	str	Team name.
name	str	Name.
firstName	str	First name.
lastName	str	Last name.
weight	int	Weight in pounds.
height	float	Height in inches.
jersey	int	Jersey number.
position	str	Position abbreviation.
hometown	str	Hometown.
teamColor	str	Team color.
teamColorSecondary	str	Team color secondary.
activeStartYear	int	Active start year.
activeEndYear	int	Active end year.
teamStints	List[PlayerSearchTeamStint]	Team stints.

PlayerSeasonOverview

Field	Type	Description
season	int	Season year.
id	str	Unique identifier for the record.
name	str	Name.
position	str	Position abbreviation.
team	str	Team name.
conference	str	Conference name.
games	int	Games coached.

Field	Type	Description
boxScoreStats	PlayerSeasonOverviewBoxScoreStats	Box score stats. — see PlayerSeasonOverviewBoxScoreStats

PlayerSeasonOverviewBoxScoreStats

Field	Type	Description
categories	List[PlayerSeasonOverviewCategory]	Categories.

PlayerSeasonOverviewPPAAverage

Field	Type	Description
passingDowns	float	Passing downs.
standardDowns	float	Standard downs.
thirdDown	float	Third down.
secondDown	float	Second down.
firstDown	float	First down.
pass	float	Pass.
all	float	All.

PlayerSeasonPredictedPointsAdded

Field	Type	Description
season	int	Season year.
id	str	Unique identifier for the record.
name	str	Name.
position	str	Position abbreviation.
team	str	Team name.
conference	str	Conference name.
averagePPA	PlayerSeasonOverviewPPAAverage	Average p p a. — see PlayerSeasonOverviewPPAAverage
totalPPA	PlayerSeasonOverviewPPAAverage	Sum of PPA across plays. — see PlayerSeasonOverviewPPAAverage

PlayerSeasonSuccessRate

Field	Type	Description
season	int	Season year.
id	str	Unique identifier for the record.
name	str	Name.

Field	Type	Description
position	str	Position abbreviation.
team	str	Team name.
conference	str	Conference name.
passing	PlayerSuccessRateSplit	Passing. — see PlayerSuccessRateSplit
rushing	PlayerSuccessRateSplit	Rushing. — see PlayerSuccessRateSplit

PlayerStat

Field	Type	Description
season	int	Season year.
playerId	str	Player ID.
player	str	Player.
position	str	Position abbreviation.
team	str	Team name.
conference	str	Conference name.
category	str	Statistic category/group.
statType	str	Category of statistic being recorded.
stat	str	Statistic value.

PlayerSuccessRateSplit

Field	Type	Description
plays	int	Number of plays.
successes	int	Successes.
successRate	float	Success rate.

PlayerTransfer

Field	Type	Description
season	int	Season year.
firstName	str	First name.
lastName	str	Last name.
position	str	Position abbreviation.
origin	str	Origin.
destination	str	Destination.
transferDate	datetime	Transfer date.

Field	Type	Description
rating	float	Composite rating score.
stars	int	Recruit star rating (1-5).
eligibility	TransferEligibility	Player eligibility/class status. (Withdrawn , TBD , PendingAppeal , SittingOne , Immediate)

PlayerUsage

Field	Type	Description
season	int	Season year.
id	str	Unique identifier for the record.
name	str	Name.
position	str	Position abbreviation.
team	str	Team name.
conference	str	Conference name.
usage	PlayerUsageUsage	Share of team plays/snaps the player was involved in, by situation. — see PlayerUsageUsage

PlayerUsageUsage

Field	Type	Description
passingDowns	float	Passing downs.
standardDowns	float	Standard downs.
thirdDown	float	Third down.
secondDown	float	Second down.
firstDown	float	First down.
rush	float	Rush.
pass	float	Pass.
overall	float	Overall (combined) rating.

PlayerWeightedEPA

Field	Type	Description
year	int	Season year.
athleteId	str	Player identifier.
athleteName	str	Player name.
position	str	Position abbreviation.
team	str	Team name.

Field	Type	Description
<code>conference</code>	str	Conference name.
<code>wepa</code>	float	Weighted EPA — EPA contribution weighted by the game's leverage/importance.
<code>plays</code>	int	Number of plays.

PlayoffAdvancement

Field	Type	Description
<code>matchupId</code>	int	Matchup ID.
<code>bracketSlot</code>	str	Bracket slot.
<code>position</code>	int	Position abbreviation.

PlayoffBidType

Enum values: `automatic`, `at_large`

PlayoffCompetition

Enum values: `cfp`

PlayoffCompetitionCfp

Enum values: `cfp`

PlayoffLinkedGame

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.
<code>startDate</code>	datetime	Kickoff date/time (UTC).
<code>completed</code>	bool	True once the game has finished.
<code>homeTeam</code>	PlayoffTeam	Home team name. — see PlayoffTeam
<code>homePoints</code>	int	Home team's final score.
<code>awayTeam</code>	PlayoffTeam	Away team name. — see PlayoffTeam
<code>awayPoints</code>	int	Away team's final score.
<code>venueId</code>	int	Venue identifier, joins to the venues endpoint.
<code>venue</code>	str	Venue name.

PlayoffMatchup

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.
<code>bracketSlot</code>	str	Bracket slot.

Field	Type	Description
round	PlayoffRound	Round. (first_round , quarterfinal , semifinal , championship)
roundName	str	Round name.
roundOrder	int	Round order.
matchupOrder	int	Matchup order.
startDate	datetime	Kickoff date/time (UTC).
bowlName	str	Bowl name.
slots	List[PlayoffMatchupSlot]	Slots.
game	PlayoffLinkedGame	Game. — see PlayoffLinkedGame
advancesTo	PlayoffAdvancement	Advances to. — see PlayoffAdvancement

PlayoffOutcome

Enum values: [active](#), [eliminated](#), [champion](#)

PlayoffParticipant

Field	Type	Description
team	PlayoffTeam	Team name. — see PlayoffTeam
committeeRank	int	Committee rank.
seed	int	Seed.
bidType	PlayoffBidType	Bid type. (automatic , at_large)
qualificationReason	str	Qualification reason.
conferenceChampion	bool	Conference champion.
qualifyingConference	str	Qualifying conference.
firstRoundBye	bool	First round bye.
outcome	PlayoffOutcome	Outcome. (active , eliminated , champion)
eliminatedRound	PlayoffRound	Eliminated round. (first_round , quarterfinal , semifinal , championship)

PlayoffRound

Enum values: [first_round](#), [quarterfinal](#), [semifinal](#), [championship](#)

PlayoffStatus

Enum values: [scheduled](#), [selected](#), [in_progress](#), [completed](#)

PlayoffTeam

Field	Type	Description
id	int	Unique identifier for the record.
school	str	School/team name.
conference	str	Conference name.

PollWeek

Field	Type	Description
season	int	Season year.
seasonType	SeasonType	regular or postseason . (regular , postseason , both , allstar , spring_regular , spring_postseason)
week	int	Week number within the season.
polls	List[Poll]	Polls.

PredictedPointsValue

Field	Type	Description
yardLine	int	Yard line (0-100, own end zone to opponent's).
predictedPoints	float	Predicted points.

PregameWinProbability

Field	Type	Description
season	int	Season year.
seasonType	SeasonType	regular or postseason . (regular , postseason , both , allstar , spring_regular , spring_postseason)
week	int	Week number within the season.
gameId	int	Game identifier, joins to the games endpoint.
homeTeam	str	Home team name.
awayTeam	str	Away team name.
spread	float	Closing point spread (negative = favorite by that many points), home-team perspective unless noted.
homeWinProbability	float	Home win probability.

Recruit

Field	Type	Description
id	str	Unique identifier for the record.
athleteId	str	Player identifier.

Field	Type	Description
recruitType	RecruitClassification	Recruit type (HighSchool/JUCO/PrepSchool/Transfer). (JUCO , PrepSchool , HighSchool)
year	int	Season year.
ranking	int	Rank (1 = best) within the given scope.
name	str	Name.
school	str	School/team name.
committedTo	str	School the recruit committed to.
position	str	Position abbreviation.
height	float	Height in inches.
weight	int	Weight in pounds.
stars	int	Recruit star rating (1-5).
rating	float	Composite rating score.
city	str	City name.
stateProvince	str	State province.
country	str	Country.
hometownInfo	RecruitHometownInfo	Recruit's hometown details. — see RecruitHometownInfo

RecruitClassification

Enum values: [JUCO](#), [PrepSchool](#), [HighSchool](#)

RecruitHometownInfo

Field	Type	Description
fipsCode	str	Fips code.
longitude	float	Longitude in decimal degrees.
latitude	float	Latitude in decimal degrees.

ReturningProduction

Field	Type	Description
season	int	Season year.
team	str	Team name.
conference	str	Conference name.
totalPPA	float	Sum of PPA across plays.
totalPassingPPA	float	Total passing p p a.
totalReceivingPPA	float	Total receiving p p a.

Field	Type	Description
totalRushingPPA	float	Total rushing p p a.
percentPPA	float	Percent p p a.
percentPassingPPA	float	Percent passing p p a.
percentReceivingPPA	float	Percent receiving p p a.
percentRushingPPA	float	Percent rushing p p a.
usage	float	Share of team plays/snaps the player was involved in, by situation.
passingUsage	float	Passing usage.
receivingUsage	float	Receiving usage.
rushingUsage	float	Rushing usage.

RosterPlayer

Field	Type	Description
id	str	Unique identifier for the record.
firstName	str	First name.
lastName	str	Last name.
team	str	Team name.
height	float	Height in inches.
weight	int	Weight in pounds.
jersey	int	Jersey number.
year	int	Season year.
position	str	Position abbreviation.
homeCity	str	Home city.
homeState	str	Home state.
homeCountry	str	Home country.
homeLatitude	float	Home latitude.
homeLongitude	float	Home longitude.
homeCountyFIPS	str	Home county f i p s.
recruitIds	List[str]	Recruit IDs.

ScoreboardGame

Field	Type	Description
id	int	Unique identifier for the record.
startDate	datetime	Kickoff date/time (UTC).

Field	Type	Description
startTimeTBD	bool	True if kickoff time was not yet announced.
tv	str	Tv.
neutralSite	bool	True if played at a neutral (non-home) site.
conferenceGame	bool	True if both teams share a conference.
status	GameStatus	Status. (scheduled , in_progress , completed)
period	int	Quarter/period number.
clock	str	Game clock at the time of the play/event.
situation	str	Situation.
possession	str	Possession.
lastPlay	str	Last play.
venue	ScoreboardGameVenue	Venue name. — see ScoreboardGameVenue
homeTeam	ScoreboardGameHomeTeam	Home team name. — see ScoreboardGameHomeTeam
awayTeam	ScoreboardGameHomeTeam	Away team name. — see ScoreboardGameHomeTeam
weather	ScoreboardGameWeather	Weather. — see ScoreboardGameWeather
betting	ScoreboardGameBetting	Betting. — see ScoreboardGameBetting

ScoreboardGameBetting

Field	Type	Description
awayMoneyline	float	Away moneyline.
homeMoneyline	float	Home moneyline.
overUnder	float	Total (over/under) line.
spread	float	Closing point spread (negative = favorite by that many points), home-team perspective unless noted.

ScoreboardGameHomeTeam

Field	Type	Description
winProbability	float	Win probability.
lineScores	List[int]	Line scores.
points	int	Points value for this rating component.
classification	DivisionClassification	Division classification (FBS/FCS/II/III). (fbs , fcs , ii , ii/iii , iii)
conference	str	Conference name.
name	str	Name.
id	int	Unique identifier for the record.

ScoreboardGameVenue

Field	Type	Description
<code>state</code>	str	State/province abbreviation.
<code>city</code>	str	City name.
<code>name</code>	str	Name.

ScoreboardGameWeather

Field	Type	Description
<code>windDirection</code>	float	Wind direction.
<code>windSpeed</code>	float	Wind speed.
<code>description</code>	str	Description.
<code>temperature</code>	float	Temperature.

SeasonType

Enum values: `regular`, `postseason`, `both`, `allstar`, `spring_regular`, `spring_postseason`

SeasonTypeDB

Enum values: `allstar`, `postseason`, `preseason`, `regular`, `spring_postseason`, `spring_regular`

Team

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.
<code>school</code>	str	School/team name.
<code>mascot</code>	str	Team mascot name.
<code>abbreviation</code>	str	Short abbreviation.
<code>alternateNames</code>	List[str]	Alternate names.
<code>conference</code>	str	Conference name.
<code>division</code>	str	Conference division (e.g. East/West), if applicable.
<code>classification</code>	str	Division classification (FBS/FCS/II/III).
<code>color</code>	str	Primary brand color (hex).
<code>alternateColor</code>	str	Alternate color.
<code>logos</code>	List[str]	Logo image URLs.
<code>twitter</code>	str	Twitter/X handle.
<code>location</code>	Venue	Location details (city/state/lat/lon). — see Venue

TeamATS

Field	Type	Description
year	int	Season year.
teamId	int	Team identifier.
team	str	Team name.
conference	str	Conference name.
games	int	Games coached.
atsWins	int	Ats wins.
atsLosses	int	Ats losses.
atsPushes	int	Ats pushes.
avgCoverMargin	float	Avg cover margin.

TeamConferenceAffiliation

Field	Type	Description
teamId	int	Team identifier.
team	str	Team name.
conferenceId	int	Conference identifier, joins to the conferences endpoint.
conference	str	Conference name.
conferenceAbbreviation	str	Conference abbreviation.
classification	ConferenceClassification	Division classification (FBS/FCS/II/III). (fbs , fcs , ii , ii/iii , iii)
conferenceDivision	str	Conference division.
startYear	int	Start year.
endYear	int	End year.

TeamConferenceChange

Field	Type	Description
teamId	int	Team identifier.
team	str	Team name.
fromConferenceId	int	From conference ID.
fromConference	str	From conference.
fromConferenceAbbreviation	str	From conference abbreviation.
fromClassification	ConferenceClassification	From classification. (fbs , fcs , ii , ii/iii , iii)
toConferenceId	int	To conference ID.
toConference	str	To conference.

Field	Type	Description
toConferenceAbbreviation	str	To conference abbreviation.
toClassification	ConferenceClassification	To classification. (fbs , fcs , ii , ii/iii , iii)
effectiveYear	int	Effective year.

TeamCoreRating

Field	Type	Description
year	int	Season year.
throughSeasonType	CoreRatingSeasonType	Through season type. (regular , postseason)
throughWeek	int	Through week.
team	str	Team name.
conference	str	Conference name.
overall	float	Overall (combined) rating.
offense	float	Offensive-side breakdown.
defense	float	Defensive-side breakdown.
offensePlays	int	Offense plays.
defensePlays	int	Defense plays.
modelVersion	str	Model version.

TeamElo

Field	Type	Description
year	int	Season year.
team	str	Team name.
conference	str	Conference name.
elo	int	Elo.

TeamFPI

Field	Type	Description
year	int	Season year.
team	str	Team name.
conference	str	Conference name.
fpi	float	FPI.
resumeRanks	TeamFPIResumeRanks	Resume ranks. — see TeamFPIResumeRanks
efficiencies	TeamFPIEfficiencies	Efficiencies. — see TeamFPIEfficiencies

TeamFPIEfficiencies

Field	Type	Description
<code>specialTeams</code>	float	Special-teams breakdown.
<code>defense</code>	float	Defensive-side breakdown.
<code>offense</code>	float	Offensive-side breakdown.
<code>overall</code>	float	Overall (combined) rating.

TeamFPIResumeRanks

Field	Type	Description
<code>gameControl</code>	int	Game control.
<code>remainingStrengthOfSchedule</code>	int	Remaining strength of schedule.
<code>strengthOfSchedule</code>	int	Strength of schedule.
<code>averageWinProbability</code>	int	Average win probability.
<code>fpi</code>	int	FPI.
<code>strengthOfRecord</code>	int	Strength of record.

TeamGamePredictedPointsAdded

Field	Type	Description
<code>gameId</code>	int	Game identifier, joins to the games endpoint.
<code>season</code>	int	Season year.
<code>week</code>	int	Week number within the season.
<code>seasonType</code>	SeasonType	<code>regular</code> or <code>postseason</code> . (<code>regular</code> , <code>postseason</code> , <code>both</code> , <code>allstar</code> , <code>spring_regular</code> , <code>spring_postseason</code>)
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>opponent</code>	str	Opponent team name.
<code>offense</code>	TeamGamePredictedPointsAddedOffense	Offensive-side breakdown. — see TeamGamePredictedPointsAddedOffense
<code>defense</code>	TeamGamePredictedPointsAddedOffense	Defensive-side breakdown. — see TeamGamePredictedPointsAddedOffense

TeamGamePredictedPointsAddedOffense

Field	Type	Description
<code>thirdDown</code>	float	Third down.

Field	Type	Description
<code>secondDown</code>	float	Second down.
<code>firstDown</code>	float	First down.
<code>rushing</code>	float	Rushing.
<code>passing</code>	float	Passing.
<code>overall</code>	float	Overall (combined) rating.

TeamPassingGame

Field	Type	Description
<code>gameId</code>	int	Game identifier, joins to the games endpoint.
<code>season</code>	int	Season year.
<code>week</code>	int	Week number within the season.
<code>seasonType</code>	SeasonType	<code>regular</code> or <code>postseason</code> . (<code>regular</code> , <code>postseason</code> , <code>both</code> , <code>allstar</code> , <code>spring_regular</code> , <code>spring_postseason</code>)
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>opponent</code>	str	Opponent team name.
<code>offense</code>	PassingProduction	Offensive-side breakdown. — see PassingProduction
<code>defense</code>	PassingProduction	Defensive-side breakdown. — see PassingProduction

TeamPassingSeason

Field	Type	Description
<code>season</code>	int	Season year.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>offense</code>	PassingProduction	Offensive-side breakdown. — see PassingProduction
<code>defense</code>	PassingProduction	Defensive-side breakdown. — see PassingProduction

TeamRecord

Field	Type	Description
<code>games</code>	int	Games coached.
<code>wins</code>	int	Win count.
<code>losses</code>	int	Loss count.
<code>ties</code>	int	Tie count.

TeamRecords

Field	Type	Description
<code>year</code>	int	Season year.
<code>teamId</code>	int	Team identifier.
<code>team</code>	str	Team name.
<code>classification</code>	DivisionClassification	Division classification (FBS/FCS/II/III). (<code>fbs</code> , <code>fcs</code> , <code>ii</code> , <code>ii/iii</code> , <code>iii</code>)
<code>conference</code>	str	Conference name.
<code>division</code>	str	Conference division (e.g. East/West), if applicable.
<code>expectedWins</code>	float	Expected wins.
<code>total</code>	TeamRecord	Total. — see TeamRecord
<code>conferenceGames</code>	TeamRecord	Conference games. — see TeamRecord
<code>homeGames</code>	TeamRecord	Home games. — see TeamRecord
<code>awayGames</code>	TeamRecord	Away games. — see TeamRecord
<code>neutralSiteGames</code>	TeamRecord	Neutral site games. — see TeamRecord
<code>regularSeason</code>	TeamRecord	Regular season. — see TeamRecord
<code>postseason</code>	TeamRecord	Postseason. — see TeamRecord

TeamRecruitingRanking

Field	Type	Description
<code>year</code>	int	Season year.
<code>rank</code>	int	Rank (1 = best) within the given scope.
<code>team</code>	str	Team name.
<code>points</code>	float	Points value for this rating component.

TeamSP

Field	Type	Description
<code>year</code>	int	Season year.
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>rating</code>	float	Composite rating score.
<code>ranking</code>	int	Rank (1 = best) within the given scope.
<code>secondOrderWins</code>	float	Second-order (efficiency-based expected) win total.
<code>sos</code>	float	Strength of schedule rating.

Field	Type	Description
offense	TeamSPOffense	Offensive-side breakdown. — see TeamSPOffense
defense	TeamSPDefense	Defensive-side breakdown. — see TeamSPDefense
specialTeams	TeamSPSpecialTeams	Special-teams breakdown. — see TeamSPSpecialTeams

TeamSPDefense

Field	Type	Description
havoc	AdvancedSeasonStatOffenseHavoc	Havoc rate — share of defensive plays with a TFL, forced fumble, pass breakup, or interception. — see AdvancedSeasonStatOffenseHavoc
passingDowns	float	Passing downs.
standardDowns	float	Standard downs.
passing	float	Passing.
rushing	float	Rushing.
explosiveness	float	Average PPA on successful plays — a measure of big-play ability.
success	float	Success rate — share of plays gaining enough yardage to be an on-schedule down (per Football Outsiders rules).
rating	float	Composite rating score.
ranking	int	Rank (1 = best) within the given scope.

TeamSPOffense

Field	Type	Description
pace	float	Plays run per minute of possession (tempo).
runRate	float	Run rate.
passingDowns	float	Passing downs.
standardDowns	float	Standard downs.
passing	float	Passing.
rushing	float	Rushing.
explosiveness	float	Average PPA on successful plays — a measure of big-play ability.
success	float	Success rate — share of plays gaining enough yardage to be an on-schedule down (per Football Outsiders rules).
rating	float	Composite rating score.
ranking	int	Rank (1 = best) within the given scope.

TeamSPSpecialTeams

Field	Type	Description
rating	float	Composite rating score.

TeamSRS

Field	Type	Description
year	int	Season year.
team	str	Team name.
conference	str	Conference name.
division	str	Conference division (e.g. East/West), if applicable.
rating	float	Composite rating score.
ranking	int	Rank (1 = best) within the given scope.

TeamSeasonPredictedPointsAdded

Field	Type	Description
season	int	Season year.
conference	str	Conference name.
team	str	Team name.
offense	TeamSeasonPredictedPointsAddedOffense	Offensive-side breakdown. — see TeamSeasonPredictedPointsAddedOffense
defense	TeamSeasonPredictedPointsAddedOffense	Defensive-side breakdown. — see TeamSeasonPredictedPointsAddedOffense

TeamSeasonPredictedPointsAddedOffense

Field	Type	Description
cumulative	AdjustedTeamMetricsEpa	Cumulative. — see AdjustedTeamMetricsEpa
thirdDown	float	Third down.
secondDown	float	Second down.
firstDown	float	First down.
rushing	float	Rushing.
passing	float	Passing.
overall	float	Overall (combined) rating.

TeamStat

Field	Type	Description
season	int	Season year.

Field	Type	Description
<code>team</code>	str	Team name.
<code>conference</code>	str	Conference name.
<code>statName</code>	str	Stat name.
<code>statValue</code>	TeamStatStatValue	Stat value. — see TeamStatStatValue

TeamStatStatValue

Field	Type	Description
<code>any_of_schemas</code>	List[str]	Any of schemas.

TeamTalent

Field	Type	Description
<code>year</code>	int	Season year.
<code>team</code>	str	Team name.
<code>talent</code>	float	Talent.

TransferEligibility

Enum values: `Withdrawn`, `TBD`, `PendingAppeal`, `SittingOne`, `Immediate`

UserFeatureAccess

Field	Type	Description
<code>adjustedMetrics</code>	bool	Adjusted metrics.
<code>weather</code>	bool	Weather.
<code>scoreboard</code>	bool	Scoreboard.
<code>livePlayByPlay</code>	bool	Live play by play.
<code>graphql</code>	bool	Graph ql.

UserInfo

Field	Type	Description
<code>patronLevel</code>	float	Patron level.
<code>tierName</code>	str	Tier name.
<code>monthlyLimit</code>	float	Monthly limit.
<code>remainingCalls</code>	float	Remaining calls.
<code>usedCalls</code>	float	Used calls.
<code>resetAt</code>	str	Reset at.

Field	Type	Description
<code>sharedPool</code>	bool	Shared pool.
<code>products</code>	List[str]	Products.
<code>features</code>	UserFeatureAccess	Features. — see UserFeatureAccess

Venue

Field	Type	Description
<code>id</code>	int	Unique identifier for the record.
<code>name</code>	str	Name.
<code>city</code>	str	City name.
<code>state</code>	str	State/province abbreviation.
<code>zip</code>	str	Postal code.
<code>countryCode</code>	str	ISO country code.
<code>timezone</code>	str	IANA timezone name.
<code>latitude</code>	float	Latitude in decimal degrees.
<code>longitude</code>	float	Longitude in decimal degrees.
<code>elevation</code>	str	Elevation in feet.
<code>capacity</code>	int	Stadium capacity.
<code>constructionYear</code>	int	Year the venue was built.