

# Introductory Programming in Python

March 10, 2013

# Chapter 1

## Basic concepts

### 1.1 What is a Program?

Simply put, a program is a set of instructions on **how** to take some **input** data and produce **output** data. Programs can be written in many languages, such as PERL, Python, C, Ruby, Pascal, etc... Even a stylised form of natural languages such as English, known as pseudo code, can be used to describe a program effectively.

**Input -> Program -> Output**

It is important to realise that the **program** determines what input is satisfactory, and what input will cause error. Input cannot be used to change how a program works. Similarly, the program defines what output will be produced. If you need a program to handle input differently, you need to write a new program. Likewise, if the output isn't what you need, you will need to change the program too.

Ultimately a program, no matter what language it is written in, consists of a some atomic actions/instructions, each one an instruction that cannot be divided into a sequence of 'smaller' or 'less complex' instructions. These instructions are composed (as in mathematical composition) in various manners, usually by issuing them in sequential order, but also by defining the result of one instruction as the operand of another.

Instructions (or sets of composed instructions) can be divided into two groups, those that produce a result, and those that don't. For example, adding two numbers, 3 and 4, together has a result (7). More specifically, it has a **value**, i.e. some data the program can continue to work with. Contrast this with an instruction that puts a line of text on the screen. It produces no value as a result. Instructions which produce a value are called **expressions**, instructions which produce no value are called **statements**

In a similar manner to statements, expressions can be combined with other expressions, to form complex expressions. Expressions are combined using **operators** such as the mathematical functions sum, difference, product, quotient, etc... Thus  $1+1$  is also an expression that has a **single value** despite the fact that it is a composite of multiple sub-expressions.

Which we can compare to the much simpler version of the same thing in python

```
a = 12
b = 12
if a*b == 144:
    a = 1
```

The basic point is to illustrate that programs are made up of small, well defined, **easy to understand** steps in sequence. As in chess, where each individual piece can only move in a very limited number of ways, yielding a tiny number of potential moves per piece per turn, these moves can be combined in a near infinite number of ways and often grouped together into common techniques or strategies. So too can the simple statements of a programming language be combined in infinite ways to produce complex but meaningful results.

## 1.2 Everyone can program!

Believe it or not, you've programmed before. You've programmed your friends, and do so every time you give them directions. After all what is a set of directions but a sequence of instructions.

```
OUT OF Cape Town TAKE the N1
TAKE the Sable rd. Offramp
AT the fork VEER LEFT
AT the traffic lights TURN LEFT
AT the NEXT traffic lights TURN RIGHT
AT the traffic circle TURN LEFT
AT the NEXT traffic circle TURN RIGHT
AT the t-junction TURN LEFT
```

You will note that some (in fact a hell of a lot) of the words in the directions to my place are capitalised. In the language of giving directions, these are pretty much our most basic instructions. That is, they are the **atomic** instructions of the program. This means that each of these instructions cannot be divided into a combination of more basic instructions. For example, LEFT, on it's own doesn't make sense. Likewise, TURN alone is vague. Thus TURN LEFT would be considered an atomic instruction, which along with other atomic instructions could be used to build up a more complex program of instructions.

The portion of the directions left in lowercase are labels or names for things that are not common to all sets of directions, most often places specific to the set of directions being given. These have values, and would be our expressions.

Examining the directions we have

**OUT OF** meaning I must first be **in** a named place before performing the next instruction

**TAKE** meaning to drive along, or turn off onto a named offramp

**AT** continue until the named place or situation is reached **before** performing the next instruction

**VEER** meaning to stay in a particular lane as the road splits

**TURN LEFT, TURN RIGHT** self explanatory

**NEXT** meaning the next object of specified type encountered

At first the description of these concepts may seem obvious, but recall that computers, the machines executing your programming instructions, have an IQ of 0. They are not intelligent, fiendishly annoying at times perhaps, but never intelligent, never aware, never capable of the massive amounts of understanding and contextualization done by the human brain in order to draw logical conclusions. They are designed and built to understand and execute only specific very basic steps. So what is implicit in the instructions contained in a set of directions given to us, must be explicitly defined for a computer.

### 1.3 Data representation and translation of real world problems

Now that the concept of sequences of statements has been thoroughly flogged to death, to what do these statements apply? They apply to **data**! But data in a computer, like instructions, must be simple and well defined, or at the very least able to be broken down into multiple well defined simple pieces. In general computers work only with numbers. The pictures you see on screen, the text you are reading, the sound you hear when playing MP3s are all numbers. The actual physical devices attached to the computer are what are responsible for transforming the numbers with which the Central Processing Unit, or 'brain' of a computer, deals into humanly recognisable phenomena such as sound waves and images. Until the screen, or the speakers, are reached, everything is numbers. So it stands to reason that the most basic, atomic, unit of data in a computer is a number. Fortunately, modern programming languages are capable of dealing with numbers and sequences of numbers in a few different ways. Integers and Reals can be considered atomic data units in almost every modern computer language, as can text in the form of a string of characters in sequence.

As programs are usually written to solve problems occurring in the real world, it falls to the programmer to translate the problem being solved into something the computer can deal with, i.e. numbers. This is a bit like those annoying word problems we encountered in junior school mathematics.

Jane has seven apples, Mary has four, Bob has one. They pool their resources, and divide the apples equally. How many apples does each one receive?

The most difficult concept to grasp when learning to program is the ability to translate a problem expressed in words into a set of instructions that describe the solution to the problem. Learning a programming language doesn't teach one to program, it merely provides one with a specific set of tools with which one can solve a problem. Learning how to apply these tools is the true skill to programming, and this comes primarily with experience. The problem set out above is ridiculously simple, and you've already worked out the answer in your head, but **how did you do it?** Describe the process! But what if there were 1000 people involved, and many thousands of apples. Working it out in your head becomes a tedious task, but the basic process you followed in your head for three people applies equally well to the case of a thousand people. And so for our first exercise in programming let us translate the word

problem into the atomic (most basic) statements and atomic data units that can be used to provide us with the answer. Assume we are provided with only the following statements and expressions to work with, and that statements are numbered from 1 upwards in the order in which they appear in our program:

- **EXPRESSION** – `input()`: get a number from input
- **STATEMENT** – `labelname = #`: Assign the value of number to a label for storage
- **STATEMENT** – `labelname += #`: Addition of the second number to the number stored in `labelname`
- **STATEMENT** – `if # != # {}`: check if the two numbers are not equal. If they are not equal perform any instructions within the braces `{}`
- **STATEMENT** – `GOTO #`: Instead of executing the next statement, execute the statement numbered `#`
- **STATEMENT** – `labelname /= #`: Division of the number stored in `labelname` by `#`
- **STATEMENT** – `print(#)`: Output of a number to the screen

Note that `#` can be either an actual number, the name of a label storing a number, or the instruction `input()` which is the number received as input.

Each of a number of people has at least one apple. They pool their resources and divide the apples equally. For any given number of people and the number of apples each of these people has, how many apples will each person receive?

Given only the above statements and expressions to work with, there are some important questions that need answering

- Do we need to know who started with how many apples?
- How do we represent how many apples there are?
- How can one determine the total number of people?

```
1: apples = 0
2: people = 0
3: a = input()
4: people += 1
5: if a != 0 {
6:     apples += a
7:     GOTO 3
8: }
9: apples /= people
10: print(apples)
```

## 1.4 Exercises

1. What is a program?

2. What is the difference between an expression and a statement?

## Chapter 2

# Invocation

### 2.1 Starting the interactive shell

Starting Python is easy.

1. We will be using IDLE to get things started
2. On the Desktop you will see a link named "Python"
3. To open the Interpreter click on "**Run**" & "**Python Shell**"
4. The screen will open up and look similar to the following

```
Python 3.3.0 (v3.3.0:bd8afb90ebf2, Sep 29 2012,
01:25:11)
[GCC 4.2.1 (Apple Inc. build 5666) (dot 3)] on darwin
Type "copyright", "credits" or "license()" for more
information.
>>> WARNING: The version of Tcl/Tk (8.5.9) in use may
be unstable.
Visit http://www.python.org/download/mac/tcltk/ for
current information.
>>>
```

What you see now is known as the Python interactive shell. The first line tells you what version of Python you are running. The second line gives you some information about how this particular copy of Python was built, and on what system it is running. The third line lists some commands you can use to get more information. Whilst in the interactive shell, you can enter Python expressions and see their results immediately. Try it now, type in a simple mathematical expression such as `4 + 7`.

```
>>> 4 + 7
11
>>>
```

As you can see, the answer or result of the expression is printed out, and you are returned to the prompt `>>>`. Now try something different: type in `a = 2 + 7`. Then, on the next line, type just `a`.

```
>>> a = 2 + 7
>>> a
9
>>>
```

This should be somewhat familiar from the end of the basic concepts section, where we were assigning a value to a name. In this case the name is `a` and the value is the result of `2 + 7`. Note that no value is printed out immediately after the assignment. The interactive shell always prints out the value of expressions, but not of statements. This means however that the labels to which we assign values, more correctly called **variables**, are expressions that evaluate to a value, which is why it printed out `9` when we input `a`.

## 2.2 Running a saved Python Script

Whilst ideal as a calculator and for exploring new ideas quickly, it would be pretty tedious if we had to re-enter our program into the interactive shell every time we wanted to run it. So instead we can, and in fact most often will, save our program code to a file. Program source code is plain raw text. As such word processors like Microsoft Word, Wordperfect, Open Office etc... are not suitable to the task. We will look for Idle which is specifically geared towards creating Python programs, and comes with Python.

So now, instead of running the interactive shell, let's write our first Python program, this is also known as a script. Open up the first window again and do the following

1. Click on **File > Save**
2. Navigate to `/home/username/Desktop`
3. Save the file as **hello.py**
4. Type the following:

```
print "Hello World!"
```

Hit F5, or Click **Run > Run Module** to run your program.

```
>>>
Hello World!
>>>
```

This is a very simple program, but it should help you get the idea. The computer is only following the instructions you provided to it. Let's convert the test we did on the Interpreter to a program. Save it as **second.py**.

```
#My second Python program
4 + 7 #This should add two numbers and output the
      result
```



```
a = 2 + 7
a
```

Notice the first and second lines. They contain what are called **comments**. Any text following a hash character on a line in a Python program is a comment, including the hash itself. Comments are completely ignored by Python, and are there purely to annotate code and make things easier for humans reading the code. We use comments to place small reminders within the code for ourselves, or explain the logic behind particularly tricky sections. As we progress through the course, you will find the code examples used are sprinkled more and more liberally with comments explaining how they work.

Now it would be reasonable to expect that if we ran this program we would get the same results as given to us by the interactive shell. So, let's try it.

```
>>>
>>>
```

No output? Nothing? The Python interpreter (python), when called without a file name following, starts up in the interactive shell. Only then will it output the results of expressions entered. When invoked with a file name following, and that file contains Python code, Python will only produce output if explicitly told to do so. So let's use a trick from our first program. Modify the code so it looks like the following:

```
#My second Python program
4 + 7 #This should add two numbers and output the
    result
a = 2 + 7
print a
>>>
9
>>>
```

Ah, that's better. Again, you should recognise the print statement from the end of the basic concepts section. The print statement will be explained in greater detail the next section.

One more important consideration is that Python is **case sensitive**. A variable a and another variable A are not the same, as illustrated below ...

```
#This program illustrates how Python is case sensitive

a = 3 # assign a the value 3
A = "Hi" # assign A the value "Hi"

# Check whether assigning to A has changed a
print a

# Check that A and a are still different
print "A = ", A, " and a = ", a
```

Running this produces the output:

```
3
A = Hi  and  a = 3
```

## 2.3 Exercises

1. Start the Python interpreter
2. Try using the interpreter as a calculator
3. Write the Hello World program.
4. Write the second program.
5. Write a program that prints out your name.
6. Consider the following lines of code:

```
a = 9
b = 3
a/b
```

- (a) For each of these three lines, which are expressions and which are statements?
- (b) What will the output be if these lines are entered into the python interactive interpreter?
- (c) What will the output be if I run these lines from a file/script?
- (d) What changes need to be made to produce output when I run these lines from a file/script?

## Chapter 3

# Basic output

### 3.1 The `print()` Statement

The most basic statement in Python is `print()`. The `print()` statement causes whatever is between the brackets to be outputted to the screen. We've already encountered it previously, now it's time to understand how it works. Start up the python interactive shell, and let's explore. Type the following:

```
>>> print(1)
1
>>> print(173+92)
265
>>> print(173+92.0)
265.0
>>> print("hello")
hello
>>>
```

As one can see, the `print()` statement outputs the **value** of the expression immediately following it to the screen, and moves to the next line. Note that the third print statement produces slightly different output, namely the extra `'0'`. This is because `92.0` and `92` are different to a computer. `92` is an integer, whilst `92.0` is a real number, or in computing terms a **floating point number** or **float** for short. The differences will be covered later.

Also of importance is the expression `"hello"` (note the double quotes). The value of `"hello"` is *hello*, and this is what is outputted to the screen by the `print()` statement. *hello* is designated as a **string** by enclosing it in quotes. Try `print(hello)` without the quotes and see what happens.

```
>>> print(hello)
Traceback (most recent call last):
  File "<stdin>", line 1, in ?
NameError: name 'hello' is not defined
```

```
>>>
```

What's going on? Welcome to your first bug! We will soon learn to dissect and understand what all that means, but for the moment it is sufficient to understand that something has gone wrong. But what? Recall from basic concepts we were able to store values in *labels* or *variables*. Python consists of a limited set of key words that have special meaning. These key words form the list of basic (atomic) statements and expressions that python knows how to handle. Whenever python encounters a word it doesn't recognise, it treats this as a label name. It obviously doesn't recognise 'hello' as a statement, and thus treats it as a **variable**. Variables must have a value, because variables are expressions in and of themselves. But we haven't told Python what the value of hello is, hence it complains 'hello' is not defined.

The `print()` statement is not so plain and boring as it seems. It can do a few more things that are worth mentioning. Try entering `print("Jane has", 7, "apples.")`

```
>>> print("Jane has", 7, "apples")
Jane has 7 apples
>>>
```

Of course we could just as easily use `print("Jane has 7 apples")` and get the same result. However, separating the number 7 out illustrates two important things about the `print()` statement. Firstly, we can in fact output the values of any number of expressions in a comma separated list, and secondly the outputs of each of the expressions in the comma separated list are separated by a single space each.

Finally, you will notice that the `print()` statement always ends off the line, and starts a new one. Simply leaving a comma on the end prevents this, e.g. `print("Enter your name:",)`. In summary:

- The `print()` statement prints out the *values* between the brackets and then prints a new line
- An empty `textttprint()` statement ends the current line and starts a new one.
- The `print()` statement can print multiple expressions if they are given in a *comma separated* list. In this case, a space is included between each expression's outputted value.
- The automatic newline outputted by `textttprint()` can be avoided by putting a trailing comma in the expression list. This will print a trailing space instead.
- If a `textttprint()` statement with a trailing comma is followed by an *empty* `textttprint()` statement, the trailing space is suppressed.

## 3.2 Some String Basics

Python treats all text in units called **strings**. A **string** is formed by enclosing some text in quotes. Double quotes, or single quotes may be used. There is a small limitation to this however, being that a string cannot be broken across multiple lines.

```
'this is a string of text'
"this is also a string of text"
'this string will
    cause an error, because it spans multiple lines'
```

Trying to enter the third string into the interactive shell yields

```
>>> 'this string will
      File "<stdin>", line 1
        'this string will
            ^
SyntaxError: EOL while scanning single-quoted string
>>>
```

EOL meaning End Of Line. If we want to introduce line breaks into strings we can use two methods. The first, and simplest, is to use *triple quotes*, meaning three double or three single quotes to indicate both the beginning and the end of the string, as in

```
>>> """this string will not
...     cause an error
...     just because it is split over three lines"""
'this string will not\n    cause an error\n        just
    because it is split over three lines'
>>>
```

The immediately obvious disadvantage is that everything between the triple quotes is taken as-is, meaning the second and third lines of my string which I indented to line up with the beginning of the first line are indented in the string itself in the form of three spaces after those `\n` thingies. Speaking of which, what the hell are those things? Why does our string contain stuff we didn't put there? Well let's try to print the string out ...

```
>>> print("""this string will not
...     cause an error
...     just because it is split over three lines""")
this string will not
    cause an error
    just because it is split over three lines
>>>
```

Well the `\ns` are gone, but what were they? Strings are sequences of characters and are one dimensional. They have no **implicit** way to specify a line break, or relative position, or which characters are where relative to which other characters in the string in two dimensions, as displayed on a screen. Hence we get the second method of specifying line breaks within a string. There are special characters known as **escape characters** which mean special things inside strings. They all start with a backslash `\` which escapes the following character from the string, or in layman's terms means the following character in the string is not a 'normal' character and should be treated specially. Some important escape characters are

`\n` line break or New line (n from the n in new line)

`\t` tab

`\\` a plain backslash

You will see that because a backslash already has a special meaning, namely "treat the next character specially", we can't simply put a backslash into our string. So we escape the backslash with a second backslash, meaning we actually want a backslash and not a special character.

Finally, how do we actually put quotes inside a string since they indicate the **end** of a string. The easiest solution is to mix your quotes. If you want a single quote in a string, define the string with double quotes, e.g. `"I've got this escape thing all figured out!"`. Alternatively, you can actually escape quotes within strings, to give them the special meaning that they don't end the string, e.g. `'I\'ve got this escaped thing totally figured out!'`

### 3.3 Exercises

1. What does the `print()` statement do generally?
2. Start the Python interactive interpreter:
  - (a) Output your first name.
  - (b) Output your surname.
  - (c) Output your first name followed by a space followed by your surname.
  - (d) Create a variable called `firstname` and put your first name into it.
  - (e) Create a variable called `surname` and put your surname into it.
  - (f) Using only the variables you have created, print your first name and surname again, making sure there is exactly one space between your two names.

Quit the Python interactive interpreter.

3. Which special rules does the `print` statement adhere to regarding trailing spaces and newlines?
4. Consider the following code...

```
print("MUCH madness is divinest sense,")
print("To a discerning eye;")
print("Much sense the starkest madness.")
print("'T is the majority", "In this, as all,
    prevails")
print("Assent, and you are sane;")
print("Demur,-you're straightway dangerous",)
print()
print("And handled with a chain.")
```

- (a) What output, exactly, does the above code produce? Indicate spaces with underscores.
5. Write a program that prints "Hello".
  6. Write a program that outputs a favourite piece of poetry or other prose, over multiple lines.
  7. How can you print a value stored in the variable `x`?
  8. How can you print the values of multiple expressions on one line?
  9. Write a program that outputs your name, age, and height in metres in the following format. Make sure age is an integer, and height is a float, and not simply part of your string.  
`My name is James, I am 30 years old and 1.78 metres tall.`
  10. Explain three possible ways to print a string containing an apostrophe, for example the string  
`The cat's mat.`

## Chapter 4

# Basic Input

### 4.1 Literal Values

So far our programs have been pretty uninteresting. They consistently produce the same results because they consistently act on the same data, or input, which we have specified by *hard coding* values for our inputs in the form of **literals**. A constant or literal is sort of the opposite to a variable, in that its value does not change over the course of program execution, and more importantly, its value is specified *literally*, within the program code.

As mentioned before, Python understands a fairly limited set of key words and symbols as basic statements or operators. Previously, we said that Python treats unrecognised words (used in a very loose sense) as variable names, but this is not strictly true. Python treats unrecognised words as expressions, and attempts to determine their value. Now, the word can specify a value directly, in which case it is called a literal value, or simply *literal* for short.

```
#An example differentiating literals and variables
a = 3                #a is a variable name, 3 is an
                    integer literal
b = 'b'              #b is a variable name, 'b' is a
                    string literal
c = True              #c is a variable name, True is a
                    boolean literal
if 3*'b' == a*b:      #3 and 'b' are literals, a and b
                    are variables
    print(c)          #is c literal or variable?
else:
    print "False"     #is "False" a literal or a
                    variable?

#Are False and "False" the same?
```



## 4.2 The `input()` Function

It's not very helpful to us if we must change our programs every time we want to change the data they work with. So instead we want to be able to tell our program to get input from somewhere. The simplest place to get input from is the keyboard, in the form of text entered by the user. Python provides a **function** to do just this, called `input()`:

```
>>> name = input("What is your name? ")
What is your name? James
>>> print(name)
James
>>>
```

We've seen *input* before in the basic concepts section, and there really isn't much to it. Just a few things to note. Firstly, `input` is a function. A function is a defined collection of statements that produce or **return** a value when executed. You could think of them as a way of turning a small set of statements into an expression. We will learn how to define our own functions later on in the course, but Python provides quite a few basic built in ones which we are going to be using before that, so let's look briefly at how they work.

- `input` is the name of the function. Like variables, functions have names to identify them. Like a variable, a function name is a label that points to the collection of statements to be executed.
- To execute the statements in a function, better known as **calling a function** we write the function's name followed by round brackets. `input()`
- Using the name just by itself treats the function like a variable.
- "What is your name? " is a parameter to the function. Functions are like mini programs. They always do the same thing, but they can do the same thing to different data. We put the data we want a function to operate on in between the brackets when we call it. Expressions and variables **passed** to functions in this way are temporarily known as **parameters**. Multiple parameters can be passed to a function by separating them with commas, and in general any valid expression is a valid parameter; e.g. `minimum(6, 2, 3+4, 4**2, 8.3, 3*1)` has six parameters, some of which are not just simple expressions like plain numbers.
- Despite the fact that any valid expression is a valid parameter, functions are usually quite picky about the parameters they can work with. For example, we couldn't find them minimum of a collection of strings. That only really works with integers and floats. Functions usually specify the *number* of parameters they accept. Often functions may accept less parameters than they specifically ask for, by substituting default values for the parameters not provided.

Back to `input`! `input()` captures a single line of text from the keyboard, as entered by the user. It returns a string containing the captured text, leaving out the `\n` produced when the user hits the Enter key. In addition, it takes one optional parameter, which is displayed as

a prompt prior to accepting input from keyboard. If this parameter is left out, the default prompt is an empty string, so nothing is printed.

## 4.3 Exercises

1. If there is a function named *my\_function*, how do I call it?
2. Are functions expressions or statements? What about when they are called?
3. Start the python interactive interpreter:
  - (a) Assign what the user types to a variable called `s`.
  - (b) Print the value of the variable `s`.
  - (c) Print `s`.
  - (d) Use `input()` to prompt the user for a number, get that number, and assign it to a variable called `n`.
  - (e) Print double the value of the variable `n`.

Exit the Python interactive interpreter.

4. Write a program that asks the user for their name and stores it in a variable. Then output “Hello”, followed by the user’s name
5. Write a program that asks the user to enter two numbers, and prints the sum of those two numbers.
6. Write a program that asks the user to enter two numbers, and prints the difference of those two numbers.
7. Write a program that asks the user to enter two numbers, and prints the product of those two numbers. Are you sensing a pattern here?
8. Write a program that asks the user for some text, and a number. The program prints out the text a number of times equal to the number entered, without line breaks or spaces in between each repetition.

# Chapter 5

## Program state

### 5.1 The Concept of State

As we know, programs execute statements in sequential order. They flow through your code, left to right, top to bottom. As statements are executed, things happen: output is issued, calculations are done, and the **state** of your program changes. But what is state? Loosely put, state refers to all the data your program is dealing with and their **current** values at the point in time when a particular statement is about to be executed. Since the entire point of a program is to transform input data into some meaningful output data, it stands to reason that the program's state will change as it executes statements. We need a way to record the state of our program in manageable units. We shall call these units **variables**, since their values may vary as our program executes.

Variables each have a name, a type, and a value. A name is simply what we choose to call a particular piece of data. For example, we previously called the bit of data representing the total number of apples held by everyone 'apples'. We stored a number in 'apples', so this would be its type. The value of 'apples' started at 0. As more people were added to the problem, the number of apples increased. Accordingly, the value of our variable 'apples' changed.

**Type** refers to the type of value a variable can have. Text is not the same as a number, thus they are considered different types. One could not for example add "apples" to the number 7.

Python has five basic types:

**int** Integers, e.g. 1, 179835646, -3, 0

**string** Text strings, e.g. 'Alice', "The cat sat on the mat"

**float** Real numbers, e.g. 0.0, 48747.23501, -0.5

**bool** Boolean conditions, e.g. True, False

**None** None is used to specify a variable which has no type or actual value.

## 5.2 Assignment Statements

To create a new variable, we simply **assign** it a value, by giving it a name and setting the name equal to the value. We do this by using the **assignment statement** which takes the form `variable_name = expression`

```
>>> name = "James"  
>>>
```

Here we have created a new variable, whose name is `name`, and which has the value *James*. Note, we did not have to say that `name` was of type string. When assigning a value to a variable, Python automatically sets the type of variable being assigned to the type of the value being assigned. If we go on to assign `name` again, this time with a different value

```
>>> name = "Jimbo"  
>>>
```

the value of `name` will be changed. If we want to see what the value of a variable is we can simply print it:

```
>>> print(name)  
Jimbo  
>>>
```

James has disappeared. As far as the program is concerned James was never there. There is no James! Assigning a new value to a variable will obliterate the previous value of that variable. If you wish to keep the old value of a variable you need to save a copy, in a different variable.

```
>>> i = 1  
>>> j = i  
>>> i = 2  
>>> print("i =", i, "and j =", j)  
i = 2 and j = 1  
>>>
```

Let's look at what we've done, step by step.

1. `i = 1`

We create a new variable, called `i`, assign it a value of *1*, and Python sets it's type to `int`

2. `j = i`

We create another new variable, this time called `j`, assign it a value of ... well what exactly? `i` is not a string because it's not in quotes, and it's not a number, so it's being treated as a variable. But what is `i`? Variables are implicitly considered to be their current values. So `i` is implicitly considered to be *1* (it's current value)

3. `i = 2`

We assign a new value to `i`. The old value of `i` is discarded.

4. `print("i =", i, "and j =", j)`

We output the current values of `i` and `j` respectively.

Step 2 highlights a number of important points about assignment. The assignment statement does something very specific. It changes the current value of the variable being assigned to the value of the expression to the right of the equals. This means that the value of the expression is determined before actually changing the value of the variable. As you can see from the output produced by our little program, assignments do not behave in the same way as a similar statement in maths does. `j = i` does not mean that `j` and `i` are always equivalent. The only thing that can be certainly said about the relationship between `j` and `i` is that they will be equal directly after the assignment statement has been executed. Both before and after that point in time, all bets are off. An assignment is **not** a description of a relationship between two expressions.

It effects a **once off** change in the value of one variable.

Consider the assignment statement `x = x + 1`. For those of you with inner mathematicians that are screaming loudly to get out, prepare yourself! What we have is an assignment to a variable (`x`) the value of an expression (`x + 1`). Let us suppose that currently the value of `x` is 1. This assignment occurs as follows.

1. `x = x + 1`

The value of the expression `x + 1` is determined. Since `x` is 1, we can transform the expression into `1 + 1` since variables in expressions are considered to have their current value.

2. `x = 1 + 1`

This is obviously 2, hence the value of the expression overall is 2.

3. `x = 2`

2 is assigned as the **new** value of `x`.

## 5.3 Integers, Floats and Arithmetic Expressions

Obviously we want to be able do more than simply assign values to variables. We need to be able to manipulate and combine them in various ways. For integers and floats this leads directly to arithmetic notation, and its representations in Python. In general, basic arithmetic expressions can be formed in much the same way as one would express them mathematically. If `x` and `y` are either integers or floats then

- `x + y` yields Addition
- `x - y` yields Subtraction
- `x * y` yields Multiplication
- `x / y` yields Division
- `x % y` yields Modulo (or Remainder)
- `x ** y` yields Exponentiation (or raising to the power of)

The above list describes various **operators** that can be used to form arithmetic expressions. But, suppose we have the expression `2 + 3 * 4`. Which of the addition or the multiplication operators is applied first? One might think the operators are applied simply left to right, but as in maths, we have a well defined order of **precedence** specifying the order in which operators are applied. In general Python arithmetic operates exactly as it would in normal mathematics.

We know that variables have a type, and so does the value of expressions. The type of the value of an expression is generally determined by the types comprising the expression. For example, adding one integer to another in an expression always yields an integer, so the expression's type is integer. But what happens when you mix two, or more, types in an expression? In general, all participating sub-expressions have their type promoted to the most general type. By general, we mean *most capable of representing all types involved*. For example, the value 0.5 cannot be represented by an integer, but the value 3 can be represented by a float as 3.0. Hence adding a float to an integer means the integer gets promoted to a float and the type of the expression's value as a whole will be a float.

Python division allows us to do a number of things. We can divide two integers (say 5/2) and the result will be represented as a float (2.5). However, we often actually want the integer part of a division only (that is, we want the decimal part dropped), or the remainder. Python provides us with an operator to get both the integer division value and the remainder. Using `%` is called getting the modulo of two numbers:

```
>>> print(5 % 2)
1
>>> print("5 divided by 2 is ", 5 // 2, "remainder", 5
      % 2)
5 divided by 2 is 2 remainder 1
>>>
```

## 5.4 Strings and common operators

Strings can be manipulated too, but the operations we perform on them are fundamentally different. Assuming `s1` and `s2` are strings, and `i` and `j` are integers

- `s1 + s2` yields Concatenation  
This joining of two strings in the order they are listed as operands to form a single string; e.g. `"a" + "b"` yields `"ab"`
- `s1 * i` yields Repetition  
The creation of a new string repeated *i* times; e.g. `"a" * 3` yields `"aaa"`
- `s1[i]` yields Subscription (or indexing)  
The extraction of a single character at a specific position in the string, where the first character in the string is a position 0, the second and position 1, and so on; e.g. `"abc"[1]` yields `"b"`. *i* may be any expression evaluating to an integer. Negative numbers may be used, where `-i` means the *i*'th last position.

- `s1[i:j:k]` yields Slicing

The extraction of a series of characters from a string starting at the character in the *i*'th position and continuing until the character just prior to the *j*'th position, extracting only every *k*'th character, where positions are numbered from 0, and negative numbers mean distance from end of string. Any of *i*, *j*, or *k* may be omitted, in which case *i* is treated as 0, *j* as the string length, and *k* as 1. A *k* value of 1 means all characters in the specified range are extracted. If *j* is omitted, the extraction is from the *i*'th position to the end of the string. Examples:

`"The quick brown fox"[4:]` yields `"quick brown fox"`

`"The quick brown fox"[-4:]` yields `" fox"`

`"The quick brown fox"[:4]` yields `"The "`

`"The quick brown fox"[4:9]` yields `"quick".`

`"Thequickbrownfox"[:2]` yields `"Teqikbonfx"`

`"The quick brown fox"[4:15:3]` yields `"qcbw".`

- `s1[:]` yields Slicing of the entire string, essentially making a complete copy of the string.

## 5.5 Formalisation of the Concepts of Statements and Expressions

To recap:

1. Programs consist of sequences of statements
2. Statements perform actions but do not have value
3. Statements may act on expressions
4. Expressions have a value, and when used in statements, their value is determined and substituted in place of the expression
5. Expressions may be simple expressions such as numbers or variables whose values can be determined directly
6. Expressions may be composed of simpler expressions combined using appropriate operators

## 5.6 Exercises

1. What does the assignment statement do?
2. What are the five basic variable types in Python?
3. If the integer variable `i` has the value 7, then what is the value of the expression `7/4`. Why?

4. How does one calculate the remainder (modulo) of an integer when divided by another number?
5. Write a program that asks the user for a number from 1 to 31. Assume the first day of the month is a Sunday. Output the name of the weekday of the day of month the user entered.
6. Write a program that outputs the letter “x” 1000 times on a single line, without intervening spaces.
7. If `s` is a string variable with the value "Harry's Hippie Hoedown", then what is the value of  
`s + ": tickets only $5"`
8. If `s` is a string variable with the value "Harry's Hippie Hoedown", then what is the value of  
`s + ": tickets only $" + "5"*3`
9. What is the value of "ABBA was a Swedish band popular during the 80's"[0:4]?
10. What is the value of "ABBA was a Swedish band popular during the 80's"[-15:-7]?
11. If the string variable `s` has the value "ABBA was a Swedish band popular during the 80s", then what is the value of  
`"BAAB"+s[4:11]+"Danish"+s[18:24]+"un"+s[24:-4]+"90's"`
12. What is your favourite sport? Write a program that inputs the score units for this sport (e.g. for rugby: number of tries, conversions, penalties, time played) and works out some statistics (e.g. the total score, average points per minute, time remaining, expected final score).



## Chapter 6

# Conditionals

Up to now, our programs have been pretty straightforward. The computer has simply executed each statement, in order, one after the other. There has been no variation, no change in behaviour, no awesomeness. In life, we are able to change our behaviour based on our circumstances, i.e. we don't do **exactly** the same thing every day, day after day. Here are some everyday situations you might find yourself in, and some of the actions you might take as a result:

- If it's raining, or snowing for that matter, you won't go out, not without an umbrella at least.
- If it's dark and your lights are off, you'll turn them on, provided you're not trying to sleep.
- If you're hungry, and you have food at your disposal, or you have money to buy food, you'll eat something.

We are capable of using our reasoning and intuition, when deciding what to do. Computers however don't have intuition, and the only reasoning they have is the reasoning **you** provide them with. When analysing a situation we are capable of taking various complicated aspects into consideration. For example, when you are invited to a party you need to decide:

- How badly do I want to?
- How many people will be there?
- How wet will I get?
- How much trouble will I get into?

Computers on the other hand are not capable of this sort of reasoning. Whilst we can weigh up different pros and cons, are able to bend our own rules and are even capable of remaining unsure, a computer can only decide either yes or no. There are no in between feelings, doubts or possibilities for changing its mind. The logic computers use to make their decisions is called boolean logic. For a computer, something can only have two states, **True** or **False**. A computer will ask these questions instead:

- Do I want to?

- Will there be more than 5 people there?
- Will I get wet?
- Will I get into trouble?

A computer can analyse certain conditions, determine if they are true or false, and then act accordingly. There is no room for leeway, no randomness, the computer is always sure that what it's doing is correct. How does it know that it's correct? Because you told it it was.

In addition to computers only being aware of two conditions, programming languages generally have very few ways of determining what those conditions are and acting upon them. Lets have a look at that second example, “Will there be more than 5 people there”:

```
>>> numOfPeople=7
>>> numOfPeople>5
True
>>> numOfPeople=-3
>>> numOfPeople>5
False
>>> numOfPeople=5
>>> numOfPeople>5
False
>>>
```

In the above example, we set the `numOfPeople` first to 7, then to -3 then to 5. See how the expression `numOfPeople>5` only returns `True` when the value stored in the expression is **more** than 5, and returns `False` otherwise.

`True` and `False` are special words to Python, known as **reserved words**, meaning they have been reserved for a particular purpose. A reserved word we have already encountered is `if`. Reserved words in Python are:

<b>and</b>	<b>del</b>	<b>from</b>	<b>not</b>	<b>with</b>
<b>as</b>	<b>elif</b>	<b>global</b>	<b>or</b>	<b>yield</b>
<b>assert</b>	<b>else</b>	<b>if</b>	<b>pass</b>	
<b>break</b>	<b>except</b>	<b>import</b>	<b>raise</b>	
<b>class</b>	<b>exec</b>	<b>in</b>	<b>return</b>	
<b>continue</b>	<b>finally</b>	<b>is</b>	<b>try</b>	
<b>def</b>	<b>for</b>	<b>lambda</b>	<b>while</b>	

Note that when forming our proposition we used a specific operator, the greater than sign “`>`”. When forming propositions we can use a specific set of operators, called **comparison operators**. If both `a` and `b` are expressions of any type:

- `a == b` proposes Equivalence.  
Is `a` equal to `b`? **Note the double equals**. In Python `=` means assignment, and `==` means is one value equal to another?.
- `a != b` proposes Non-equivalence.  
Is `a` not equal to `b`?

- `a < b` proposes Less Than.  
Is `a` less than `b`?
- `a > b` proposes Greater Than.  
Is `a` greater than `b`?
- `a <= b` proposes Less Than OR Equal To.  
Is `a` less than or equal to `b`?
- `a >= b` proposes Greater Than OR Equal To.  
Is `a` greater than or equal to `b`?
- `a in b` proposes that the **string** `a` is a substring of, i.e. exists **inside**, the **string** `b`.  
This can also be used in lists as you will see in a later chapter.

Propositions, being expressions themselves, follow the usual rules for composition of expressions. This means that we can have an expression, `(x > 3) == (y < 4)`, in which we have two propositions `x > 3` and `y < 4` which have been composed into the total expression by using the third proposition which proposes that both sides have the same value. The entire proposition is true only if both the sub-propositions have the same truth value at the time the expression is evaluated.

So back to our program to decide if we want to go to the party, we don't want to go to lame parties with too few people. So we only go to the party if there are more than 5 people there, i.e. if `numOfPeople>5`. But what if we don't like crowded parties either? We could evaluate if `numOfPeople<40`, so as to avoid parties with more than 40 people. But if only there were a way to combine them, so that we only go to parties that have a couple people **AND** are not too crowded. Say hello to **logical operators**, also known as **boolean operators** (operators which apply to boolean expressions). There are only three logical operators, listed below. If `expr1` and `expr2` are both propositions:

- `expr1 and expr2` is True if both `expr1` **and** `expr2` are True when the proposition is evaluated.
- `expr1 or expr2` is True if either `expr1` **or** `expr2` are True when the proposition is evaluated.
- `not expr1` is True if `expr1` is False, and vice versa.

You can use boolean operators to string together multiple statements. e.g. to decide whether or not to go to a party you might use the following conditions

```
numOfPeople>5 and numOfPeople<40 and (day=='Friday' or day=='Saturday')
```

This will produce **True** if the party has between 5 and 40 people, and it is either a Friday or a Saturday. **Note the brackets around the parts next to the or.** Brackets are used here to define which expression to evaluate first. This is because the evaluation of boolean algebra also follows a hierarchy system, *BODMASNAO*. Your standard BODMAS operations on numbers and variables come first. Then comes your conditions (`>`, `==`, `not` then `and` and finally comes `or`. So if we left out the brackets and only had:

```
numOfPeople>5 and numOfPeople<40 and day=='Friday' or day=='Saturday'
```

This could be interpreted as yes if the party has between 5 and 40 people and its a Friday, or if its a Saturday (In which case the number of people doesn't matter). Hence its very important to get your BODMAS right else you're going to be going to lame parties with only 2 other people, just because its a Saturday. Lets look at some examples:

```
>>> 3>4 and 25==20
False
>>> a=2==1 or 4+2>=6 and not 5%2==0
>>> a
True
>>> b=True and 1==1 and (3!=3 or 14-2>5 and 5==2*2)
>>> b
False
>>> 'ell' in "Hello There"
True
>>> b or a and 4$<$=3
False
>>> a or b or 2!=2
True
>>>
```

*Note how in that example we stored the result of a boolean expression to a variable (variables a and b), and when we called them later they acted just like any other boolean expression.*

So now we know how to determine from a set of conditions whether or not something is true. We know whether or not to go to the party, but that isn't the end of the story: we have to actually use that information to do something about it.

Python specifically has three methods to act upon such information, the most prevalent of which is the `if` statement. The format that an `if` statement takes is the keyword `if` followed by an expression to be evaluated and a block of code to execute if (and only if) that expression evaluates to `True`. If the expression evaluates to `False` then the block of code will be completely skipped when the program is run and none of it will be executed. Put the following in a file called `second.py`:

```
x = input("Enter a number: ")
if x > '3':
    print ("You entered", x)
    print (" 'x' is larger than 3")
```

Now run your program using `python second.py` and enter 2 when prompted.

```
nyx@nyx-desktop:~/umonya_notes$ python second.py
Enter a number: 2
```

Hmmmm! Why didn't our print statements execute? If, as we believe, the program executes from top to bottom, the print statements should have been executed. Obviously, that `if x > '3':` is doing something we are unaware of, so let's experiment a little more. Run the program again, but this time enter 5 at the prompt.

```
nyx@nyx-desktop:~/umonya_notes$ python second.py
Enter a number: 5
You entered 5
'x' is larger than 3
```

Okay! Our program just acted differently based on the input we gave it, or rather, based on the conditions determined by the input. Looking back at the last three lines of our program, there's a lot of new stuff in there that needs explanation, so we'll break it down. The `if` statement takes the format:

```
if <expression>:
    statement
    statement
    ...
```

What `if` does, is check whether the expression provided has a value of `True`, and if so, the statement immediately following the `if` is executed, otherwise it is not executed. Taking our previously expressed English examples:

- *If* there are between 5 and 40 people, and it's either a Friday or a Saturday, then **go to the party**
- *If* you'll get wet, **don't go outside**
- *If* it's dark in your room, and the lights are off, **turn them on**

We can now express them in Python as follows

```
if numOfPeople>5 and numOfPeople<=$40 and (day=='Friday'
    ' or day=='Saturday'):
    whatYoureDoing="going to the party"
```

```
if weather=='Raining' and 'raincoat' not in
    thingsImWearing:
    pass #In other words, don't go outside
```

```
if dark and lightSwitch=='off':
    print("Go turn on your light")
```

Note the statement `pass`. `Pass` is another reserved word in Python, and means quite simply *do nothing*. We need it because `if` statements **require** a statement to execute if the expression they evaluate is `True`.

## Pitfalls in Translation

We need to be aware of some common pitfalls that we will encounter when translating English language logic (forgive the oxymoron) into mathematical or computer logic. Examine the following examples:

- English: If both first name and surname are not blank  
Wrong: `if firstname and surname != ''`  
Correct: `if (firstname != '') and (surname != '')`
- English: If the premises contain more than 3 persons and no children or pets (*This is actually a very ambiguous statement*)  
Wrong: `if adults > 3 and children or pets == 0`  
Correct: `if persons > 3 and (children == 0 and pets == 0)`
- English: If the type is not 5 or 6  
Wrong: `if type != 5 or 6`  
Correct: `if type != 5 and type != 6`  
Correct: `if not (type==5 or type==6)`

Why is this the case? Well, remember *BODMAS*? The boolean operations (`not`, `and`, `or`) have the lowest priority of all Python operations so they will happen last.

## 6.1 Executing Multiple Statements Conditionally

What `if` does, is check whether the expression provided has a value of `True`, and if so, the statement immediately following is executed, otherwise it is not executed.

Examining what we said previously, we notice nasty phrases like *the statement*, indicating one, singular, statement. However, most of the time we'll have a number of statements that we'll only want to execute when certain conditions have been met. Python, like most programming languages, provides us with the ability to group collections of statements into **blocks**, much like composition of expressions. Such blocks can be treated as a single statement for the purposes of `if` statements, and others we will encounter soon.

Unlike most other languages Python allows us to specify blocks using **indentation** (*spacing*). Lines of code that have the same indentation are considered to be members of the same block. Blocks can also be **nested** inside one another, such lines constituting inner blocks are also members of their encompassing outer blocks. This is best illustrated using an example. (line numbers are not part of the code)

```

1: #this program takes three numbers as input, and
   counts how many of
2: #those numbers is even, and how many even numbers
   are negative
3: #if an even number is entered, if it is negative,
   a message is printed
4:
5: #set the counts for even and negative to 0
6: even = 0
7: negative = 0
8:
9: #get the first number
10: first = int(input("Enter the first number: "))

```

```

11: if first % 2 == 0:
12:     print("The first number is even")
13:     even = even + 1
14:     if first < 0:
15:         print("The first number is negative")
16:         negative = negative + 1
17:
18: #get the second number
19: second = int(input("Enter the second number: "))
20: if second % 2 == 0:
21:     print("The second number is even")
22:     even = even + 1
23:     if second < 0:
24:         print("The second number is negative")
25:         negative = negative + 1
26:
27: #get the third number
28: third = int(input("Enter the third number: "))
29: if third % 2 == 0:
30:     print("The third number is even")
31:     even = even + 1
32:     if third < 0:
33:         print("The third number is negative")
34:         negative = negative + 1
35:
36: print("There were", even, "even numbers and",
       negative, "of those were negative")

```

Running this program and giving the numbers 2, -4, and 7 as input produces

```

nyx@nyx-desktop:~/umonya_notes$ python illus.py
Enter the first number: 2
The first number is even
Enter the second number: -4
The second number is even
The second number is negative
Enter the third number: -7
There were 2 even numbers and 1 of those were negative

```

Firstly, let's get the indentation and nesting thing out of the way. Looking at lines 12 through to 16 we see they are more indented than the `if` statement on line 11. Thus these lines form a block of statements. Since this block is immediately after an `if` statement, all the statements in the block will only be executed if the `if` statement's expression is `True`. For the first number we gave as input 2, this means the first `if` statement evaluates to `True`, so we start executing the block. When we get to line 14 we encounter a second `if` statement. This second `if` statement is **nested** inside the first, because it will only be executed if the outer `if` statement (line 11) has an expression that evaluates to `True`. Lines 15 and 16 form a **nested block**, but are not executed because 2 is not negative, or more specifically, because 2 is not

less than 0. Conversely, lines 24 and 25 will be executed because -4 is less than 0. Although -7 is negative, lines 33 and 34 won't be executed, because the `if` statement on line 32 is part of the block from 30-34 that never gets executed

Despite the fact that this example is an order of magnitude larger than any previous examples, there are only two new things. The first being indentation and nesting, the second being the use of `int()` around our input functions. Remember that `input()` returns a string. So even if the user types in 2, `input()` returns not 2 but the string '2'. Strings and numbers don't really play nice together, especially when they're being compared to one another, so we need to convert the string into an integer. This is known as **type casting** or **coercion**. We can do it for any basic Python type ...

```
>>> float("3.1415")
3.1415
>>> str(143)
'143'
>>> bool(None)
False
>>> bool(-1)
True
>>> int(1.4142)
1
>>>
```

## 6.2 Nested ifs vs complex boolean expressions

Lets re-examine our party scenario. We could use nested ifs to specify when to go to the party as such:

```
if numOfPeople>5:
    if numOfPeople<40:
        if day=='Friday':
            print("Go to party")
        if day=='Saturday':
            print("Go to party")
```

This method will work, but it is cumbersome. Too many nested ifs can lead to confusion, and if you wanted to change your program later so that it printed "You should go to the party", you might change it in one place but not the other. As such it would be much better to write that algorithm as follows:

```
if numOfPeople>5 and numOfPeople<40 and (day=='Friday'
or day=='Saturday'):
    print("Go to the party")
```

This is a much more elegant solution, and is preferable. You would only use nesting when you want to do slightly different things depending on the situation. When programming,



less is more. **You should almost always strive for less code** (so long as the program is understandable and still does what it should).

## 6.3 Specifying Execution Code for Alternate Conditions

So now we have a handle on basic `if` statements, we come up against the next hurdle. If our condition isn't met, our `if` block statements simply aren't executed. But what if we want something **else** executed instead of nothing when the condition isn't met. We could simply follow our first `if` with another `if` that has the opposite expression (using `not`), but this isn't a very elegant solution. Enter the `if ... else` statement.

```
1: first = int(input("Enter a number: "))
2: if first % 2 == 0:
3:     print(first, "is even")
4: else:
5:     print(first, "is odd")
```

Now, if `first` is not even, the program will print a message saying it is odd, instead of doing nothing. The indentation is of key importance here again. Note that **else** is at the same indentation level as the `if` and is also followed by a colon (`:`). The statement to be executed if `first` is not even, on line 5, is known as the **else clause**, as the statement on line 3 is known as the **if clause**.

Finally we have to deal with the case where things are not as clear cut, not so black and white.

```
1: colour = input("Enter the name of a colour: ")
2: if colour == "Red":
3:     print("Stop!")
4: elif colour == "Orange":
5:     print("Try to stop if possible.")
6: elif colour == "Green":
7:     print("Go! Go! GO!")
8: else:
9:     print(colour, "Stop! You're obviously drunk.")
```

Running this a couple of times with various inputs we get

```
nyx@nyx-desktop:~/umonya_notes$ python illus.py
Enter the name of a colour: Red
Stop!
nyx@nyx-desktop:~/umonya_notes$ python illus.py
Enter the name of a colour: Green
Go! Go! GO!
nyx@nyx-desktop:~/umonya_notes$ python illus.py
Enter the name of a colour: orange
Stop! You're obviously drunk.
nyx@nyx-desktop:~/umonya_notes$
```

The first run things happen as expected; We get to line 2, the value of colour is *Red*, the expression for the `if` statement is `True`, we execute line 3 ... and then the program finishes! This is because line 4 is not part of the block constituting line 2's `if` clause, because it has a lower indentation level. Also lines 4, 6 and 8 are all still part of the same `if` statement. Let's look at the second run a little more closely to see what happens.

We get to line 2, the value of colour is *Green*. *Green* is not equal to *Red*, so we don't execute line 3. Instead we jump to the `else ...` hang on! What is `elif`? `elif` is short for *else if* and allows one to set up alternate conditions if earlier conditions haven't been met. So we get to the `elif` on line 4. *Green* is not *Orange* so we don't execute line 5, instead we go onto line 6, which is still part of the same if-else group. *Green* is equal to *Green* so that will return true and we will run line 7.

The third run illustrates nicely that in fact strings in Python are case sensitive too. Not just the language, but the data we manipulate with it is considered case sensitive. *Orange* and *orange* are different strings, hence neither the `if`, nor any of the `elifs` execute. As a last resort, the block after the `else` executes.

## 6.4 Formal Summary

- Conditions are specified using propositions, i.e. expressions that have a value of either `True` or `False`.
- Propositions are expressions and can be composed using other expressions combined with logical operators.
- The `if` statement is used to execute certain statements only if certain conditions are true when the `if` statement is executed.
- `if` statements can specify alternative conditions and the code to execute under those conditions using `elif`.
- `if` statements can specify what to execute if none of the conditions specified are true using `else`.
- A collection of statements can be grouped together in the same code block, by indenting them
- The complete syntax of the `if` statement follows, where sections enclosed in square braces are optional.

```
if <expression>:
    statement
    statement
    ...
[ elif <expression>:
    statement
    statement
    ... ]
[ elif <expression>:
```

```

        statement
        statement
        ... ]
[ ... ]
[ else:
    statement
    statement
    ... ]

```

## 6.5 Exercises

1. Give a condition to check whether a number  $x$  is divisible by another number,  $y$ ?  
*Hint: what does the operator % do?*
2. Given the English phrase, “If you’re not on the VIP list or the staff list, you can’t come in.”, write down an equivalent Python/pseudo code condition.
3. Write a program that reads in a number and halves it, unless it’s an odd number, in which case it must print a suitable error message.
4. Do you think the following is True or False?

```
'Two'
```

Evaluate it. Is the answer what you expected? How are strings compared to each other?

5. Write a program with the below code. Run it and give it 1 as an input. Does the program do as you expected? Why not? Try and fix it.

```

a=1
b=input()
if a == b:
    print("You input 1!")

```

6. Write a program that asks the user to enter two numbers. If the second number is not zero, print the quotient (the one number divided by the other) of the two numbers, otherwise print a message to the effect of not being able to divide by zero.
7. What does the following equate to? Try figure it out for yourself before you code it up. If you’re still not sure why the answer is as it is, try breaking it up into smaller bits and evaluate them individually.

```

True and not True or (True or False and False) and
False == (not True or False)

```

8. Write a program that asks the user to enter 4 numbers, and prints the smallest number entered.
9. Write a program that asks the user to enter 3 numbers, and prints the largest even number entered, and displays a suitable error message if no even numbers are entered, or if there is no one largest number (i.e. if the two biggest numbers are the same)

10. Write a program that reads in a sentence and a keyword and tells you if that keyword is in that sentence.
11. Write a program that asks the user to enter a four digit year, and prints out whether that year is a leap year or not.  
*Hint: It's a leap year if the year is divisible by four, except if it's divisible by 100, in which case it's not, except if it's divisible by 400, in which case it is. ie. 1900 was not a leap year but 2000 was.*
12. Write a program that asks for the names, and the birthdays of two people. (Ask for year, month and then date of birth) The program must determine which of the two people is oldest.
13. Write a program that asks the user to enter 3 names, then outputs them sorted alphabetically.

```
import random
a=random.randrange(10)
print (a)
```

14. The above code prints a random number between 0 and 10. Use the above code in a program that asks the user to guess what number the computer is “thinking of”. Then tell the user if he was right, or wrong, and if so, whether his guess was too high or too low.
15. Write a program that asks the user to enter a number, then prints out all the numbers from 1 to 10 by which the entered number is divisible.
16. Think about that last program you wrote and how much of the code was repeated. Write a better version of the same program in your own pseudo-code.

## Chapter 7

# While loops

### 7.1 The while statement

The last program we wrote, to count the number of even and negative numbers entered by the user, was already getting pretty large if one measures program size in lines of code. And it only handled three inputs! What if we wanted a hundred inputs. Cutting and pasting would work, but making those small changes to each section of code dealing with a specific number would be tedious at best, and error prone at worst. Fortunately, computers excel at repetitive tasks. Enter the **while** statement:

The **while** statement executes a statement, or block of statements, repeatedly, as long as a given expression is **True**.

So let's rethink our previous problem. Previously, we would have described the problem as:

The user enters three integers. The program outputs how many of those integers were even, and how many were both even and negative. Also, if the number entered is even, a message stating the number entered is even is printed. Similarly a message is printed if the number is both even and negative, indicating the number is negative.

But we are not happy with just three numbers, so let's re-describe the behaviour we want from our program

The user may **enter** a number. **Until** the user enters a blank line, the program continues accepting numbers. After a blank line has been entered the program **outputs** the number of numbers entered by the user **which** were even, as well as the number of numbers **which** were **both** even **and** negative.

Much like how in junior school we were taught to look for key words in word problems to help us formulate the problem mathematically, we can and should do the same with descriptions of problems and their translation into program code. Everything in programming comes down to one of three *structures*...

- A sequence of steps

- A condition that selects which sequence of steps to execute
- A repetition of a sequence of steps

In the problem description above, we can identify some key words already hint at the structures we should use.

**enter** Relates to input – `input()`

**until** Indicates **repetition** based on the fulfilment of a **condition** – **while**

**output** Indicates **output** – `print()`

**which** Indicates a **condition without repetition** – **if**

**both ... and ...** Indicates a **composition of conditions** – **and**

We'll now step through the problem description, sentence by sentence and convert it into a Python program, using the keywords as hints, and the tools we have already come across. Also we'll introduce the syntax of the while statement.

The user may enter a number.

Looking at the keywords and their hints, we want to use the **input** function here. This is true of any input from the keyboard generally. Thus, our first line of code will be

```
number = input("Enter a number: ")
```

Until the user enters a blank line, the program continues accepting numbers.

Okay, from the hints we see we should be using a **while** statement, but **beware!** We don't have an 'until' statement in Python, and in English until and while are opposites, so we just need to transform the problem slightly so that we now have

**While** the user enters a line **that is not blank**, the program continues accepting numbers.

This translates directly into Python code which we append to what we've already got to produce

```
number = input("Enter a number: ")
while number != '':
    number = input("Enter another number (or nothing to
        finish): ")
```

Note the prompt has changed to tell the user what to do to exit the program, namely enter a blank line rather than a number. Also note the format, or syntax, of the **while** statement.

```
while <expression>:
    statement
    statement
    ...
```

See how we *indent* statements we want executed repetitively and conditionally under the **while** statement, in the same way as we do with **if** statements. The **while** statement checks the expression, and if it is **True**, will execute those indented statements once, after which it will check the expression again, and execute the statements again, etc ... If the expression is ever **False**, execution of the program continues at the first un-indented statement after the indented block.

There's a little more to the while loop than pure syntax. Every loop needs three things; A start point, an end point, and a way to get from one point to another. More importantly there needs to be a relationship between these three things, in the form of a variable. The start point takes the form of assigning a value (the starting value) to a variable, which we'll call the counter. The while loop's condition specifies the stop point of the loop, by specifying a condition under which the loop should terminate **in terms of the counter variable**. Finally, the loop needs a way to get from start to finish in a stepwise manner, i.e. a way to take a single step. This means the value of the counter variable must change **inside** the repeated block of statements, otherwise value of the loop condition won't change, and the loop will repeat forever. Commonly, the statement that changes the counter's value is placed at the *end* of the repeated block of statements, because this means it is changed immediately before the counter variable is checked in the loop condition again. This gives us the pattern:

```
counter = <start_value> #Initialise the counter
while <expression>: #<expression> specifies when the
    loop will stop in terms of counter
    statement
    statement
    ...
    counter = <new value of counter> #changes the value
        of counter
```

After a blank line has been entered the program outputs the total amount of numbers entered by the user which were even.

Now we haven't kept a record of the numbers entered so how can we tell how many were even? The solution is to keep a count as even numbers are entered. How do we store a value? **Variables!** We need to know **how many** numbers were even, indicating quantity, indicating a number, i.e. an integer. So let's create a new integer to use whilst counting, and call it **even**. But to create a new variable we have to give it a value! What value can we give even, if we don't know how many even numbers the user will enter? Well we do know how many even numbers there are before the user has entered any numbers; there are 0 even numbers. So let's put an assignment statement to that effect into our program in the right place (before a number is entered).

```
even = 0
number = input("Enter a number: ")
while number != '':
    number = input("Enter another number (or nothing to
        finish): ")
```

Now at the end of our program we still have 0 even numbers, because we haven't changed the value of `even`. We wish to count how many numbers that are entered are even, which means we need to increment (increase by one) every time an even number is entered. Firstly, how do we distinguish even numbers from odd? We use an `if` statement, because this is a condition. Secondly, where do we actually place the counting statements? Here's a suggestion:

```
even = 0
number = input("Enter a number: ")
while number != '':
    if int(number) % 2 == 0: #if number is even
        even = even + 1
    number = input("Enter another number (or nothing to
        finish): ")
```

A few things about our two new lines deserve mention. Firstly, as we are already familiar with, `input()` returns a string, so we need to **type cast** to an integer before we can test whether it is even. Then there's the condition itself. The definition of an even number is a number divisible exactly by 2, i.e. without remainder. The `'%'` operator returns the remainder of a division, and is thus perfectly suited to the job of testing whether a number is even or odd. If the remainder of the division is 0, the number is even. Also, we have nested the `if` statement within the `while` statement, so it may be executed multiple times, once each time a number is entered, to test the number. We have put it before the input function within the `while` statement because we don't want to test an empty string (blank line) for evenness in the case where the user has not entered a number and wishes to finish up. This way the `while` statement's expression tests whether the input is a blank line, before we convert to an integer and test for evenness.

as well as the number of numbers which were both even and negative.

The last piece of the problem description says we should also count how many of the input numbers are negative as well as even. And we need to put some output at the end once we've counted everything. Well, this is very similar to the previous segment, so let's recycle the idea and see what we get...

```
even = 0
negative = 0
number = input("Enter a number: ")
while number != '':
    if int(number) % 2 == 0: #if number is even
        even = even + 1
        if int(number) < 0:
            negative = negative + 1
    number = input("Enter another number (or nothing to
        finish): ")
print("There were", even, "even numbers, of which",
    negative, "were also negative")
```

So we've included a new variable, `negative`, which counts the number of negative entries, but only if those entries are even. Why is this? We haven't specified `( int(number) % 2`



`== 0 and int(number) < 0`). Instead we have nested the test for negativity inside the test for evenness. This means a number will only be tested, and thus potentially counted, for negativity if it has already been found to be even.

## 7.2 The break statement

Looking at the `while` statement, it seems that once we're in a block of statements to be executed repeatedly, known as a **loop**, we can't get out of the loop except when the expression after `while` (known as the **loop condition**) is `False`. Python provides us with a statement for breaking out of a loop, conveniently called **break**. Suppose we wanted our program for counting even numbers to end not only when a blank line was entered, but also if the user enters the string `'quit'`. We could simply add two lines ...

```
even = 0
negative = 0
number = input("Enter a number (or nothing or 'quit' to
quit): ")
while number != '':
    if number == 'quit':
        break
    if int(number) % 2 == 0: #if number is even
        even = even + 1
    if int(number) < 0:
        negative = negative + 1
    number = input("Enter another number (or nothing to
finish): ")
print("There were", even, "even numbers, of which",
negative, "were also negative")
```

Again we check what the user has entered, and if it is the string `'quit'`, we **break** out of the loop, meaning execution continues at the `print()` function.

## 7.3 The continue statement

If we wanted to get picky and consider 0 to not be even, we would have to modify our code so that it doesn't count a `'0'` entry as even or negative. We can't simply break out of the loop, because the user may want to enter more numbers after the `'0'`. We could enclose the entire test for evenness in an `if` statement that makes sure the number entered is not 0, but Python provides us with a more elegant solution, the **continue** statement. The **continue** statement jumps the flow of execution immediately back to the loop condition, at which point normal loop execution flow resumes.

```
even = 0
negative = 0
```

```

number = input("Enter a number (or nothing or 'quit' to
quit): ")
while number != '':
    if number == 'quit':
        break
    if number == '0':
        number = input("Enter another number (or
nothing or 'quit' to quit): ")
        continue
    if int(number) % 2 == 0: #if number is even
        even = even + 1
        if int(number) < 0:
            negative = negative + 1
        number = input("Enter another number (or nothing or
'quit' to quit): ")
print("There were", even, "even numbers, of which",
negative, "were also negative")

```

## 7.4 else clauses in while loops

**while** loop statements may also have an **else** clause, which is executed when the loop terminates when the condition becomes **False**, but not when the loop is terminated by a **break** statement.

```

while <expression>:
    <statement>
    [statement]
else:
    <statement>
    [statement]

```

## 7.5 Exercises

Given the code ...

```

i = 1
while i

```

1. How many lines of output will the above code produce?
2. What needs to be done to correct the program?
3. Write a program that outputs the word 'repeat' 100 times, each on a line of its own.
4. Write a program that prints the numbers from 1 to 10 on the screen, on a single line, ending with a new line.

5. Write a program that asks the user for a number and then prints the numbers from 1 to the number they entered.
6. Write a program that asks the user for a number and then prints the sum of numbers from 1 to the number they entered.
7. Write a program that asks the user for two numbers and then prints the sum of numbers from the lowest number entered to the highest number entered.
8. Write a program that asks the user to enter a sequence of numbers, ending with a blank line. Print out the smallest of those numbers.
9. Write a program that asks the user to enter a sequence of numbers, ending with a blank line. Print out the average of those numbers.
10. Write a program that prints the numbers from 1 to 100, 10 per each line.

# Chapter 8

## Lists

### 8.1 The Necessity of lists

Let us for the sake of originality work on a new problem.

A lecturer for an introductory programming course wants to record some information about his students. He wants to keep a record of each student's name, their primary field of study, and a brief description of their current research project. He would like to be able to print this out in a nicely formatted way. His class has 19 students.

For each student we need to record their name, field of study, and a description of their research project. This means three values we need to store for each student, or 38 variables in total. Surely there's a better way. There is, and Python yet again provides us with the perfect tool for job, the **list**!

A list is a **type** of variable. To create a new variable of type list in Python simply assign a variable to a list. Lists are formed using square brackets surrounding a comma separated sequence of the elements of the list. Example:

```
>>> mylist = [1, 2, 3]
>>> anotherlist = ["Alice", "Bob", "Carl", "Mallory"]
>>> mixed = ["a string", 143, [341]]
>>> empty = []
>>>
```

- Lists contain elements, e.g. `mylist` contains three elements, namely 1, 2, and 3.
- Lists have length, being the number of elements they contain, e.g. `mylist` has length 3, `anotherlist` has length 4
- We can determine the length of a list using Python's built in `len` function

```
>>> len([1, 2, 3])
3
```

- The elements of a list can be expressions of any type (including another list) and different elements in the same list can be of different types, e.g. `mixed` has three elements; the first element is a string ("`a string`"), the second element is an integer (`143`), and the third element is another list (`[341]`).
- Lists can contain no elements, in which case they are known as *empty*, e.g. `empty` contains no elements, but is still a list!
- Individual elements of a list are indexed according to their position in the list. The first position has an index of 0, the second position an index of 1, etc...
- We can access a specific element in a list by using a special operator in an expression with the format `list[index]`. This expression evaluates to the element in the index'th position of the list. e.g. `mylist[0]` is 1, `mylist[1]` is 2, `mixed[2]` is `[341]`.

Now that we know about lists, we could use a list to represent the students names, another to represent their fields of study, and a third to represent their project descriptions. So we might have

```
#a small program to record info about students

name = ["Ayanda", "Ben", "Carl", "Dumisani"]
field = ["Astronomy", "Biochemistry", "Cancer Research",
        , "Maths"]
description = [
    "The search for black holes",
    "Engineering a better yeast for brewing beer",
    "Better pain management in palliative care",
    "Finding a polynomial time solution for NP-complete
      problems"
]
```

## 8.2 Lists in Detail

We've already learnt a little about about lists, but there are many more features to lists, and sadly a few intricacies we need to know about. Firstly let's deal more explicitly with the operations that can be performed on lists. If both `a` and `b` are lists, `v` is any expression, and `i`, `j`, and `k` are integers then

- `a + b` concatenates (joins) two lists.  
It returns a new list that contains all the elements of list `a` and then list `b`.

```
>>> a = [1,2,3]
>>> a+[4,5]
[1, 2, 3, 4, 5]
>>>
>>> [4,5]+a
[4, 5, 1, 2, 3]
```

- `a * i` repeats a list.

It returns a new list with that has all the elements of `a` but repeated `i` times.

```
>>> a*2
[1, 2, 3, 1, 2, 3]
>>>
>>> [1]*2+2*[2]
[1, 1, 2, 2]
>>>
>>> [[1]*2,[2]*2]
[[1, 1], [2, 2]]
>>>
>>> [1]*2*3
[1, 1, 1, 1, 1, 1]
>>>
```

- `a[i]` retrieves the `i`'th element of `a`.

```
>>> a[0]
1
```

- `a[i:j:k]` slices the list.

It returns a copy of the list `a` from its `i`'th element to its `(j-1)`'th element, taking only every `k`'th element. If `k` is omitted (left out), every element in the range is taken. If `i` or `j` are omitted they default to beginning of list and end of list respectively.

```
>>> a[1:3]
[2, 3]
>>> a += [4, 5]
>>> a[0:6:2]
[1, 3, 5]
```

- `a[:i]` yields a slice from the beginning of `a` to the `(i-1)`'th element of `a`.

```
>>> a[:3]
[1, 2, 3]
```

- `a[i:]` yields a slice from the `i`'th element to the end of the list.

```
>>> a[3:]
[4, 5]
```

- `a[:]` yields a slice of the entire list. More importantly it yields a **copy** of the list!

```
>>> a[:]
[1, 2, 3, 4, 5]
>>>
```

Note that these operators each return newly created lists, and do not modify the *operand* lists (that is, the list that these operations are performed on) in any way.

## 8.3 Assignment to elements of a list

Lists can have their elements changed. This sounds a little weird, but consider it this way. The value of the integer 1 cannot change. We can change the value indicated by a variable `i` (which might be 1) to something else, but this doesn't change the value of the integer 1. Lists are different, because the value reflects a container of multiple other values, and we can remove, add, or replace those inner values, i.e. list elements. This changes the value of the list itself. Practically, this means we can assign values to specific elements of a list.

```
>>> a = [1, 2, 3]
>>> a[0]
1
>>> a[0] = 0
>>> a
[0, 2, 3]
>>>
```

Not only can we assign individual elements of a list a new value, but we can assign whole slices new values. The funky thing is, we can replace a specified slice of a list with a list of any length, effectively extending or shrinking the list in the process.

```
>>> a = [1, 2, 5]
>>> a[1:2] = [3]
>>> a
[1, 3, 5]
>>> a[1:2] = [2, 3, 4]
>>> a
[1, 2, 3, 4, 5]
>>> a[1:4] = [3]
>>> a
[1, 3, 5]
>>>
```

## 8.4 Comparing Lists

The comparison of lists to other lists, and other types is also slightly different to the comparison of simple types (int, float, bool). Specifically:

- `a == b` checks two lists are the same.  
It returns true if all the elements of `a` are the same as the elements of `b`.
- `a < b` yields Less Than.  
Note that lists are compared in sequence order, meaning that `a` is less than `b` if `a`'s first element is less than `b`'s first element. If `a`'s first element and `b`'s first element are equal, the second elements are checked, etc...
- `v in a` is True only if the list `a` contains an element whose value is that of the expression `v`.

- `a is b` is True only if `a` and `b` are the same list.

Note the final point, namely the `is` operator. This is one of those intricacies we mentioned earlier. The contents of a list can be changed. This is not true of an integer for example. One cannot change the contents of the integer 1. This introduces a slight complexity. If `a` is 1 and `b` is 1 then `a` and `b` are the same. But if `a = [1]`, and `b = [1]`, they **are not** the same. They may be equal, but are not the same list. They are different lists. Again, examples to the rescue

```
>>> a = [1,2]
>>> b = [1,2]
>>> a == b
True
>>> a is b
False
>>>
>>> b[0] = 3
>>> b
[3, 2]
>>> a
[1, 2]
>>>
```

```
>>> a = [1,2]
>>> b = a
>>> a == b
True
>>> a is b
True
>>> b[0] = 3
>>> b
[3, 2]
>>> a
[3, 2]
>>>
```

Note how the second line of the second example contradicts our basic idea of assignment, which was: The assignment statement assigns the value of the expression on the right to the variable on the left. But clearly, we are not just assigning the value (`[1,2]`), because later when we change the first element of `b` to 3, we also appear to change the first element of `a`. Weird. There is a technical explanation for this, but is really not worth knowing at this point as it is more likely to confuse than clarify. If you are interested, ask one of the tutors to explain this. What this does mean however is that we need to be aware of the special case of assignment to a single variable of types that can be changed! When, in an assignment statement `a = b`, if `b` is of **mutable type** (a type that can have its values changed), the assignment statement **makes `a` a synonym of `b`**, i.e. they become different names for the same variable.



Also note how we assigned a value to an element of the list, changing some of its contents. Python is quite advanced in terms of how it can handle assignments involving lists, so let's explore its features a bit. If `a` is the list `[1, 2, 3]`, `b` is some expression of any value, and `l` is some expression of type list.

- `a[0] = b` assigns the value of `b` to the 0'th element of `a`. (The mutable type special case applies)
- `a[0:2] = l` removes the slice range specified on the left and replaces the removed elements with the contents of `l`. This does **not** make `a` and `l` synonyms.

If we wish to make a copy of a list that is not a synonym, we assign to the slice of the full list, e.g. `a = b[:]` (where `b` is a list)

## 8.5 Lists as objects

In addition to the operators that can act on lists, lists are objects. An **object** is a term used in Computer Science to refer specifically to something which has both code and data associated with it directly. For now, a complete understanding of objects is not required, but in the meanwhile we need to be aware of some syntactical features they provide.

Objects have code associated with them in functions called **methods**. Methods are bound to every variable of an object type individually, meaning if two different variables, `a` and `b`, are of the same type which is an object type, then `a` and `b` both have the same set of methods but their methods are distinct from one another. When `a` calls a method, that method acts only on `a`, and when `b` calls that same method, the method will act only on `b`. Read it again, it makes sense. In fact examples will prove it's quite intuitive.

```
>>> a = [1, 2, 3]
>>> b = ["A", "B", "C"]
>>> a.index(2)
1
>>> b.index(2)
Traceback (most recent call last):
  File "", line 1, in
ValueError: 2 is not in list
>>> b.index("C")
2
```

Looking at the examples we notice there is some new notation, of the form `<list>.<method>()`. This *dot notation* indicates that we are obtaining a method of the list object (called `index` in the case of the example), and our use of brackets indicates we wish to call it. Methods are simply functions associated with a particular type.

Note that `a.index(2)` and `b.index(2)` return different results. In fact the `b.index` case produces an error. Obviously they are doing different things, despite being given the same parameter (2). What the `index` method does is search for a given value in the elements of **its** list. When called using `a.index` its list is `a`, when called using `b.index` its list is `b`. Since

the value 2 is an element of the list **a**, `index` returns its index position (1), meaning it can be found in the second position in the list. But the value 2 is not an element of the list **b**, hence `index` will cause an error.

That being said, let's round off our knowledge of lists by going through the list methods that will be useful to us.

- `<list>.append(<expression>)`

Appends the value of `<expression>` to the end of `<list>`.

```
>>> a = []
>>> a.append('one')
>>> a
['one']
>>>
```

- `<list>.count(<expression>)`

Returns the number of elements in `<list>` with same value as that of `<expression>`.

```
>>> a = ['a', 'c', 'g', 't', 't', 'a']
>>> a.count('a')
2
>>>
```

- `<list>.index(<expression>)`

Returns the index of the first element in `<list>` that has the same value as `<expression>`.

```
>>> a = ['a', 'c', 'g', 't', 't', 'a']
>>> a.index('t')
3
>>>
```

- `<list>.insert(<index expression>, <object expression>)`

Inserts the value of `<object expression>` **before** the element at the position indicated by `<index expression>`.

```
>>> a = ['a', 'c', 'g', 't', 't', 'a']
>>> a.insert(2, 'newitem')
>>> a
['a', 'c', 'newitem', 'g', 't', 't', 'a']
>>>
```

- `<list>.pop()`

Removes the last element from the end of the list, and returns its value.

```
>>> a = ['a', 'c', 'g', 't', 't', 'a']
>>> a.pop()
'a'
>>> a
['a', 'c', 'g', 't', 't']
>>>
```

- `<list>.remove(<expression>)`

Removes the first element in `<list>` that has the same value as `<expression>`.

```
>>> a = ['a', 'c', 'newitem', 'g', 't', 't', 'a']
>>> a.remove('newitem')
>>> a
['a', 'c', 'g', 't', 't', 'a']
>>>
```

- `<list>.reverse()`

Reverses the order of elements in `<list>`.

```
>>> a = ['alpha', 'beta', 'gamma', 'delta']
>>> a.reverse()
>>> a
['delta', 'gamma', 'beta', 'alpha']
>>>
```

- `<list>.sort()`

Sorts the elements of `<list>`.

```
>>> a = ['delta', 'gamma', 'beta', 'alpha']
>>> a.sort()
>>> a
['alpha', 'beta', 'delta', 'gamma']
>>>
```

## 8.6 Exercises

- Given the list `l = ['There', 'are', 9000000, 'bicycles', 'in', 'Beijing']`
  - How many elements does the list have? How would one find this out programmatically?
  - What is the index of the non-string element?
  - What is the output of `print(l[1:4])`?
- What is the value of `[1, 3] + [2, 4]`?
- What is the value of `[1, 3] + [[2, 4]]`?
- What is the difference between appending a value to a list and adding the same value within its own list using the concatenation operator?
- What is the slice notation to extract the word 'mickles' from the string 'How many mickles are there in a muckle?'
- Write a program that outputs the position of every 't' in the list `['a', 'c', 'g', 't', 't', 'a', 't']`. Use the index method, don't do it manually.

7. Write a program that asks the user to enter a sequence of up to 5 x:y coordinates with both x and y in the range 0 to 4, ending their sequence entry by providing a blank line for the x coordinate. Then display a five by five grid of '#' characters, with the points in the grid entered by the user left blank. Assume x increases from left to right, and y increases from top to bottom. Example input/output is given ...

```
Coordinates range from 0 to 4!
Please enter pair of coordinates (x:y), leave x
blank to terminate sequence.
X> 3
Y> 3
Please enter pair of coordinates (x:y), leave x
blank to terminate sequence.
X> 4
Y> 1
Please enter pair of coordinates (x:y), leave x
blank to terminate sequence.
X> 1
Y> 4
Please enter pair of coordinates (x:y), leave x
blank to terminate sequence.
X>
#####
####
#####
### #
#   ##
```

## Chapter 9

# Tuples

### 9.1 Tuples as immutable lists

In many ways tuples and lists are very similar. In fact tuples are basically immutable lists, that is, lists which cannot be changed. All the same operators work on them: concatenation, repetition, subscription, and slicing. All the comparison operators work in the same way: equivalence, less than, greater than, `is`. However, **assignments to tuples cannot be made** as they are immutable, or unchangeable. Once a tuple has been formed, it cannot be changed. New tuples can be formed from others using concatenation, repetition, etc... but the operand tuples remain unchanged by the operators.

### 9.2 Forming a tuple

Tuples are technically formed in Python using a comma, although most often they are found recorded in round braces. Tuples can be of any length, and have their elements indexed from 0 to `len(tuple)-1`.

```
>>> 1, 2
(1, 2)
>>> 1,
(1,)
>>> (1)
1
>>> (1, 2)
(1, 2)
>>> ("Tuples", "can", "have", "elements", "of", "more",
    "than", 1, "type")
('Tuples', 'can', 'have', 'elements', 'of', 'more', '
    than', 1, 'type')
>>>
```

## 9.3 Using tuples

Breaking it down we get to the old grind of operators, and in the case of tuples a few new ideas. Let's get the operators out of the way! If both **a** and **b** are tuples, **v** is any expression, and **i**, **j**, and **k** are integers then

- **a + b** concatenates two tuples.

```
>>> a = (1,2,3)
>>> a+(4,5)
(1, 2, 3, 4, 5)
>>>
>>> (4,5)+a
(4, 5, 1, 2, 3)
```

- **a \* i** repeats a tuple.

```
>>> a*2
(1, 2, 3, 1, 2, 3)
>>>
>>> (1,)*2+2*(2,)
(1, 1, 2, 2)
>>>
>>> ((1,)*2,(2,)*2)
((1, 1), (2, 2))
>>>
>>> (1,)*2*3
(1, 1, 1, 1, 1, 1)
>>>
```

- **a[i]** retrieves the **i**'th element of **a**.

```
>>> a[0]
1
```

- **a[i:j:k]** slices a tuples, or returns a copy of the tuple **a** from its **i**'th element to its **(j-1)**'th element, taking only every **k**'th element. If **k** is omitted, every element in the range is taken.

```
>>> a[1:3]
(2, 3)
>>> a = (1, 2, 3, 4, 5)
>>> a[0:6:2]
(1, 3, 5)
```

- **a[:i]** yields a slice from the beginning of the tuple to **(i-1)**'th element of **a**.

```
>>> a[:3]
(1, 2, 3)
```

- `a[i:]` yields a slice from the `i`'th element to the end of the tuple.

```
>>> a[3:]
(4, 5)
```

- `a[:]` yields a copy of the entire tuple.

```
>>> a[:]
(1, 2, 3, 4, 5)
```

The comparison of tuples to other tuples happens in the same way as lists to lists.

- `a == b` yields Equivalence
- `a < b` yields Less Than. Note that tuples are compared in sequence order, meaning that `a` is less than `b` if `a`'s first element is less than `b`'s first element. If `a`'s first element and `b`'s first element are equal, the second elements are checked, etc...
- `v in a` is True only if the tuple `a` contains an element whose value is that of the expression `v`.
- `a is b` is True only if `a` and `b` are the same tuple.

If tuples have a subset of the functionality of lists, why ever use them? What can they do that lists cannot. Well, actually they provide a very convenient way to package multiple variables together for passing to a function as a parameter, or more likely returning from a function. Technically speaking functions can only return one value, but since a tuple is a single 'value' no matter how many elements it contains, a tuple could be used in a function that returns a two-component piece of data, for example an x:y coordinate. Even better, is that Python *implicitly unpacks tuples*. By unpack we mean the assignment of multiple variables at once to their respective (based on position) elements in a tuple, for example

```
>>> t = (1, 2, 3)
>>> a, b, c = t
>>> a
1
>>> b
2
>>> c
3
>>>
```

And since tuples are formed by a comma, this provides us with a nifty little method to swap the values of two variables,

```
>>> a = 1
>>> b = 2
>>> b, a = a, b
>>> a
2
>>> b
1
```

## 9.4 Exercises

1. What is the difference between concatenation and addition of tuples? Why is the Python plus operator for tuples a concatenation operator instead of an addition operator?
2. The code `a, b = b, a` swaps the values of `a` and `b`. What would happen if added a third variable to the mix, `c`, as in `a, b, c = b, c, a`? What would happen if one repeated the statement indefinitely?
3. Given a variable with the value of the empty tuple ( `a = ()` ), how does one ‘append’ an element to `a`?
4. Write a program that accepts a list of numbers terminated by a blank line. Print out the entered numbers as elements of a tuple, in the order they were entered.
5. Given a list of tuples each specifying a subject name and a grade symbol (‘A’ - ‘F’) in the form `[('Maths', 'D'), ('Comp Sci', 'B'), ('English', 'C'), ('Xhosa', 'A'), ('Science', 'B'), ('History', 'E')]`:
  - (a) Write a program that prints out the subject with the highest mark.
  - (b) Write a program that outputs each subject and the grade symbol in the format ‘subject: symbol’, with each subject on a single line.
  - (c) Write a program that prints out a tab separated list of subjects on the first line, and the corresponding grades, also tab separated on the second line.
6. Write a program that accepts a list of numbers terminated by a blank line, and stores the result in a tuple, `a`. Repeat the process to form a second user inputted tuple, `b`, making sure there are the same number of elements in `b` as in `a`. Print out the result of the *mathematical addition* (not concatenation) of the two tuples as a tuple.
7. Write a program that reads a name and an age for a person, until the name is blank. As each name age pair is entered, store names in a list, and ages in another. Print a list of tuples of paired names and ages.
8. Write a program that reads a name and an age for a person, until the name is blank. Once all names have been entered, present the user with an option to list the entered people in alphabetical order, or in descending age order. For either choice, list each person’s name followed by their age on a single line. Make sure you output the correct age for the correct person.



# Chapter 10

## For loops

### 10.1 Loops over Lists

In lesson 8 we introduced the concept of lists.

A list is a type of variable that contains other elements. For instance we could create a shopping list.

```
>>> shopping=['Milk','Bread','Eggs','Motherboard','  
            Cheese','Jacket']
```

In order to view the individual contents of that list, we could refer to them by index

```
>>> shopping[0]  
'Milk'  
>>> shopping[3]  
'Motherboard'
```

In order to view all the items of our list, we could manually type in all the indexes, but what happens if you add more items later, or if you have 100 items? A better idea would be to use a **while** loop to change the index. We set the index to 0 to begin with, then while the index is less than length of the list, we print out the item in the list referenced by the index and increment the index.

```
>>> index=0  
>>> while (index < len(shopping)):  
...     print(shopping[index])  
...     index+=1  
...  
Milk  
Bread  
Eggs  
Motherboard  
Cheese  
Jacket
```

That works, but, once again Python provides us a better tool for the job in the form of the `for` statement.

The `for` statement is also a looping statement, like the `while` statement, except that it loops over the elements of a list rather than until a boolean expression is false. It looks like this

```
for <element> in <list>:
    statement
    statement
    ...
```

Where *element* is a variable name (not necessarily 'element'), which may be as yet unassigned (the `for` statement will assign a value to it), or may be an already existing variable, in which case a new value will be assigned to that variable by the `for` statement. `list` is an expression whose value is of type list.

What this does exactly is execute the indented statements **once for each element in the list**. Each time the statements are executed, the variable in the position of `element` is assigned the value of the next element in `list`, starting with the first.

So, for example, the following program

```
#a small program to display your shopping list
shopping=['Milk','Bread','Eggs','Motherboard','Cheese',
          'Jacket']
for i in shopping:
    print("Item:",i)
```

produces the following output

```
Item: Milk
Item: Bread
Item: Eggs
Item: Motherboard
Item: Cheese
Item: Jacket
```

Well, that's pretty cool. Notice how the variable `i` changes on every iteration (every repeat of the loop). But what if we wanted to number the list too, or have two lists, one with the item and one with the price. What we could do is have a list of indexes, and use the `for` loop to go through them, printing out both the index and the item in the shopping list that corresponds to that number. We could do that as follows:

```
#a small program to display a numbered shopping list
indexes=[0,1,2,3,4,5]
shopping=['Milk','Bread','Eggs','Motherboard','Cheese',
          'Jacket']
prices=['8','6','10','800','30','150']
for i in indexes:
```

```
print("Item number",i,"is",shopping[i],"and it
      costs R",prices[i])
```

produces the following output

```
Item number 0 is Milk and it costs R 8
Item number 1 is Bread and it costs R 6
Item number 2 is Eggs and it costs R 10
Item number 3 is Motherboard and it costs R 800
Item number 4 is Cheese and it costs R 30
Item number 5 is Jacket and it costs R 150
```

*Note that if you were printing this for your mother, she might not understand why milk is the 0th item and not the 1st, so you might want to `print(i+1)` so that it seems to start at 1.*

That works alright. But if we were dealing with larger lists, like of 19 items, or even thousands of items, we really don't want to have to type out the list of possible indexes ([0, 1, 2, ..., 19]) every time. Python again comes to the rescue with another built in function, `range`. `range` returns a list of numbers within a given range, and defined as follows

```
range([start,] stop [, step])
```

What it does is returns a list of integers, starting with the number given by *start* (or 0 if *start* is not given), up to but not including the number given by *stop*. If *step* is given, the list will only provide every *step*'th integer in the sequence. Examples probably illustrate this better ...

```
>>> range(5)
[0, 1, 2, 3, 4]
>>> range(4,10)
[4, 5, 6, 7, 8, 9]
>>> range(-3,3)
[-3, -2, -1, 0, 1, 2]
>>> range(0,10,2)
[0, 2, 4, 6, 8]
>>> range(10,20,3)
[10, 13, 16, 19]
>>>
```

So we can change our previous program slightly, as follows

```
#a small program to display a numbered shopping list
shopping=['Milk','Bread','Eggs','Motherboard','Cheese',
          'Jacket']
for i in range(len(shopping)):
    print("Item number",i,"is",shopping[i])
```

The `for` loop isn't only used with lists. The `for` loop can be used with any iterable structure, i.e. any structure which can be indexed. One such structure is the string, which you'll examine

in depth in the next chapter. As has been mentioned previously, the string is basically a list of characters, and hence you can use a `for` loop to iterate through those characters. So for example to print every letter of a word on a new line:

```
>>> for i in "Any Word":
...     print(i)
...
A
n
y

W
o
r
d
```

The `for` loop also works on parts sections of lists, and edited lists, here are some examples:

```
>>> for i in ["Ford","Mercedes","BMW","Audi","Toyota","Nissan"][2:5]:
...     print(i)
...
BMW
Audi
Toyota
>>> for i in "Experts Exchange"[6:10]:
...     print(i,)
...
s    E x
>>> for i in ["Animals",3,"blah"]+[2,True,"for you"]:
...     print(i, " | ",)
...
Animals | 3 | blah | 2 | True | for you |
>>> for i in "Hello how are you doing?":[::2]:
...     print(i,)
...
H l o h w a e y u d i g
```

## 10.2 else clauses in for loops

`for` loop statements may also have an `else` clause, which is executed when the list is finished, but not when the loop is terminated by a `break` statement.

```
for <variable> in <list>:
    <statement>
    [statement]
```

```
else:
    <statement>
    [statement]
```

## 10.3 Exercises

1. Write a program that asks the user to enter two (whole) numbers and outputs the product. However, do so without using `*` but rather by repeatedly adding.
2. Write a program that prints out the string `"repeat"` 100 times.
3. Write a program that asks the user for their name, and a number, then prints out the user's name, with some motivational comment, that many times.
4. What is an expression, using the `range` function, that yields a list of 10 consecutive integers starting at 0?
5. What is an expression, using the `range` function, that yields a list of 100 consecutive integers starting from 1?
6. What is an expression, using the `range` function, that yields a list of 100 consecutive *even* integers starting from 2?
7. Write a program that prints the *odd* numbers from 1 to 100 each on its own line.
8. The triangular numbers are the numbers 1, 3, 6, 10, 15... The  $n$ 'th triangular number is the sum of all the integers from 1 till  $n$ . e.g. the 4th triangular number is  $1+2+3+4=10$ . Write a program that accepts an integer value for  $n$  from the user, and prints the  $n$ 'th triangular number.
9. Write a program that accepts words from the user, storing them in a list, until the user enters the word "end". The program must then print out all the words in reverse order.
10. Modify your answer to question 10 from "Flow Control: Conditionals", i.e. print out the numbers from 1 to 10 by which a user entered number is divisible, to use a for loop instead of multiple if statements.
11. Write a program that asks the user for the height of a triangle. It must then print out a right handed triangle, with the right-angle on the bottom left, made of asterisks (`'*'`) of a height equal to the number entered. Example input/output follows ...

```
Enter triangle height: 3
*
**
***
```

```
Enter triangle height: 5
*
**
***
****
```

```
*****
```

12. Do the same as above, except now with the right-angle in the top right, and after you have printed the first triangle, you must start all over again until the user enters a blank line for input. Example ...

```
Enter triangle height: 3
***
**
*
Enter triangle height: 5
*****
****
***
**
*
Enter triangle height:
```

13. Write a program that prints out a 'Christmas' tree shape from asterisks. The program should ask the user for the height of the tree, in lines, and the tree should have a stalk of two lines regardless. If the user enters a height, the tree should be printed out, and the user should be prompted for another height until they enter a blank line.

```
Enter tree height: 4
*
***
*****
*****
*
*
Enter tree height: 6
*
***
*****
*****
*****
*****
*****
*
*
```