

Stage 1: Installing the Software

Note: Estimated time for installation is 15 minutes

Please note that the Freedom Fone v1.5 DVD will overwrite all data currently on the computer.

- Insert the Freedom Fone DVD and restart the computer
- Ensure that the computer's BIOS settings enable the computer to boot from the DVD. If the computer is not currently set to do this; restart the computer and look for the prompt to modify the BIOS settings and set the primary boot device to the CD/DVD player.
- When prompted, type install to begin the installation.
 Note that Freedom Fone will not work properly as a live CD.
- Step 1: Select the language you prefer for installation.
 Once selected, push the "forward" button.
- Step 2: Select the city in which you are running the server. Once selected, push the "forward" button.
- Step 3: Select keyboard layout. Check this setting by typing the following characters into the box provided: ~, @, |, / and ensuring the symbols displayed are correct. Once complete, push the "forward" button.
- Step 4: Prepare disk space. Select "Guided use entire disk" and then push the "forward" button.
- Step 5: Who are you. When it asks, "who are you", enter "lupinus". When it asks the password, enter "lupinus" twice and then push the "forward" button.
- Step 7 of 7: Click install. Once installation is complete, click "restart now"
- When prompted remove the DVD, close the tray and push enter.



Stage 2: Setting the Time

Date and time are important as they are used to log calls and manage polls. Make sure your settings are correct

- The computer should restart after the previous stage.
- For the computer login, the username and password is 'lupinus'.
- Check and ensure the computer system time is correct for your location.
- If you need to adjust the date and time, right click over the date and time icon in the top right hand corner.
- Select "adjust date and time"
- To unlock for any time adjustments, the password is 'lupinus'.



Stage 3: Connecting to the internet (Optional)

For those of you who are able and wish to connect to the internet, this is how you manually configure your connection.

- Don't forget to have your Ethernet cable plugged in!
- From the menus at the top of the screen, select System/Administration/Network.
- Click "unlock"
- Enter the password, 'lupinus'.
- Click on the "wired connection".
- Click on "properties"
- Unselect, "Enable roaming mode"
- Depending on how your network is administered either select, "automatic configuration (DHCP) or select the "static IP address" from the configuration drop down list.
- If you select "static IP address", ask your network administrator for an IP address, subnet mask and gateway address. Click DNS under the network settings and add DNS servers, as provided by your network administrator.



Stage 4: Getting the SIM card ready for use

For each SIM card you want to use with Freedom Fone, do the following:

- Ensure that the SIM card is activated.
- If you have a pre-paid SIM card ensure it is topped up with airtime and that it meets the pay-as-you-go operational requirements specific to your country.
- Insert the SIM card in a mobile phone and ensure the settings are modified to deactivate future pin requests; i.e. so that no pin is requested in the future.
- Ensure there is good network coverage in your work area
- Remove the SIM card from the mobile phone and place it in the telephony device i.e. the MobiGater or Voice Blue Lite.
- Make a note of the IMEI code associated with the MobiGater or Voice Blue Lite module bay into which the SIM card is inserted. Make a note of the phone number associated with the SIM card. This information will be useful when you test the system later.



Stage 6: Connecting computer to the Mobigater

If using more than one MobiGater, please connect one device at a time and test before adding any further devices.

- If it is on, switch the Freedom Fone server off before you add each MobiGater.
- Connect the MobiGater to the computer via a USB cable.
- Connect the MobiGater to the power.
- Switch the computer on.
- If all is correct, the LEDs on the MobiGater will light as follows: the LEDs under the power and USB icons will both light up red. The LED under the mobile phone icon will flicker red roughly every four seconds, as the SIM card polls the nearest mobile network tower.
- If the Freedom Fone user interface is not already open, click on the Freedom Fone shortcut on the desktop.
- Select Dashboard/GSM channels from the Freedom Fone menu
- The MobiGater you've just connected should be displayed

 check the IMEI number and compare it with the notes
 you took in Stage 5.



Stage 7a:
Testing
Telephony Device
with Leave-a
Message
Function

The first MobiGater connected to the Freedom Fone server will by default connect to the Leave-a-message voice menu (IVR).

- Click Dashboard/Call data records from the Freedom Fone menu
- The call data records page will be empty if there have been no previous calls to this system to date. You can click on the Refresh button at any time to view information associated with completed calls or calls in progress.
- Call the mobile number of the first MobiGater connected.
- If you have not yet modified the Leave-a-message voice menu using the Freedom Fone Leave-a-message/IVR menu screen, you will hear our default voice menu.
- Listen to the prompts and leave a message after the beep.
- If you are NOT using a registered copy of Cepestral, you
 will have an automated voice offering reminders to license
 the text to speech voice in-between the IVR prompts.
 See the Troubleshooting section to deal with the Cepstral
 nag!
- If you can successfully leave a voice message, select Leave-a-message/Inbox from the Freedom Fone menu to edit details associated with the voice message and to listen to it.

	-
	If you CANNOT leave a voice message because the selections you are making using your phone's key pad are being ignored, see the Troubleshooting section.
	Check to see if the SIM in the MobiGater is receiving ordinary text messages.
Stage 7b: Testing Telephony Device with SMS Function	 Send a message to the mobile number associated with the SIM card in the MobiGater. Select Poll/Other SMS from the Freedom Fone menu to view the SMS messages that have been received. Click the Refresh button repeatedly until your message can be seen, If your mobile network's message centre is operating efficiently you should see your message appear within seconds.
Stage 7c: Testing Telephony Device with Poll Function	 Set up a test Poll and experiment Select Poll/Manage polls from the Freedom Fone menu Create a new poll: Put in a question, give the poll a code, add 2 or more options Send test SMS messages to your mobile number. Remember each SMS must start with the poll's code as its first word, followed by one of the allowed options. Click the Refresh button on the Poll/Manage poll page and watch the votes add up. Click the poll question for more detailed information on the votes coming in.
Stage 7d: Modify the Leave-a-message IVR	 Edit the Leave-a-Message IVR by modifying the text to suit your needs or create and upload your own voice files. Select Leave-a-message/IVR Menu from the Freedom Fone menu If you create audio files for this menu, make sure to sample them as mono, 8Khz files less than 10MB in size. Either WAV or MP3 files can be used.



Stage 8: Adding more Mobigaters (Optional)

- If you want to add more MobiGaters, shut down the computer again; connect the next telephony device as per the steps in Stage 6.
- Please note that if more than one telephony device is connected, by default the:
 - o first and third devices are connected to the 'Leavea-Message' service
 - o second telephony device is connected to the default voice menu created and set using the Freedom Fone Voice menus/voice menus screen.