

Demo Doc - pipe interface

Contents

1 Data	2
2 Simple table	3
3 Annotate	4
4 Notes in minipage	5
5 Align	6
6 Units	7
7 Math	8
8 hline from column	9
9 hline anywhere	10
10 Remove duplicate values	11
11 Panel	12
12 Colspan	13
13 Colspan - multiple	14
14 Colspan - from cols	15
15 Handle wide columns	16
15.1 descr is taking over the table	16
15.2 Limit descr to 5 cm	16
16 Identify a summary row	17
17 Fontsize	18
18 Row space	19
19 Col space	20

1 Data

Mostly working with this data; but some others come in later to illustrate certain features.

```
library(pmtables)
library(yspec)
spec <- ys_help$spec()
```

```
pmdata <- readRDS("datasets/pmdata.RDS")
head(pmdata)
```

```
## # A tibble: 6 x 9
##   STUDYf      DOSEf FORMf   WT   CRCL AGE   N     ALB   SCR
##   <chr>      <chr> <chr>  <chr> <chr> <chr> <chr> <chr> <chr>
## 1 12-DEMO-001 100 mg tablet  71.4  104  33.7  80    4.20  1.06
## 2 12-DEMO-001 150 mg capsule 89.4  122  24.4  16    4.63  1.12
## 3 12-DEMO-001 150 mg tablet  81.7  104  34.4  48    3.83  0.910
## 4 12-DEMO-001 150 mg troche  94.0  93.2  27.4  16    4.94  1.25
## 5 12-DEMO-001 200 mg tablet  67.9  100  27.5  64    4.25  1.10
## 6 12-DEMO-001 200 mg troche  76.6  99.2  22.8  16    4.54  1.15
```

```
data <- select(pmdata, STUDY = STUDYf, DOSE = DOSEf, WT, AGE, CRCL, ALB, SCR)
```

2 Simple table

- Columns are in bold by default (can be turned off)

```
data %>% st_new() %>% st_make(.cat = TRUE)
```

STUDY	DOSE	WT	AGE	CRCL	ALB	SCR
12-DEMO-001	100 mg	71.4	33.7	104	4.20	1.06
12-DEMO-001	150 mg	89.4	24.4	122	4.63	1.12
12-DEMO-001	150 mg	81.7	34.4	104	3.83	0.910
12-DEMO-001	150 mg	94.0	27.4	93.2	4.94	1.25
12-DEMO-001	200 mg	67.9	27.5	100	4.25	1.10
12-DEMO-001	200 mg	76.6	22.8	99.2	4.54	1.15
12-DEMO-002	100 mg	61.3	38.3	113	4.04	1.28
12-DEMO-002	100 mg	77.6	29.9	106	4.31	0.981
12-DEMO-002	50 mg	74.1	37.1	112	4.44	0.900
12-DEMO-002	50 mg	71.2	34.1	106	4.63	0.868
12-DEMO-002	75 mg	72.4	38.2	105	3.89	0.900
12-DEMO-002	75 mg	71.6	34.2	98.9	4.49	0.991
12-DEMO-002	75 mg	73.6	49.2	103	4.52	0.930

3 Annotate

- Arguments to identify the name of the generating R script and the output file name
- The output file name is retained as an attribute to be used later when saving the table data
- Arbitrary notes are also allowed (encouraged)

```
data %>%  
  st_data() %>%  
  st_files(r = "foo.R", output = "foo.tex") %>%  
  st_notes(  
    "Data were analyzed in quadruplicate.",  
    "The results are very clear."  
  ) %>%  
  st_make(.cat = TRUE)
```

STUDY	DOSE	WT	AGE	CRCL	ALB	SCR
12-DEMO-001	100 mg	71.4	33.7	104	4.20	1.06
12-DEMO-001	150 mg	89.4	24.4	122	4.63	1.12
12-DEMO-001	150 mg	81.7	34.4	104	3.83	0.910
12-DEMO-001	150 mg	94.0	27.4	93.2	4.94	1.25
12-DEMO-001	200 mg	67.9	27.5	100	4.25	1.10
12-DEMO-001	200 mg	76.6	22.8	99.2	4.54	1.15
12-DEMO-002	100 mg	61.3	38.3	113	4.04	1.28
12-DEMO-002	100 mg	77.6	29.9	106	4.31	0.981
12-DEMO-002	50 mg	74.1	37.1	112	4.44	0.900
12-DEMO-002	50 mg	71.2	34.1	106	4.63	0.868
12-DEMO-002	75 mg	72.4	38.2	105	3.89	0.900
12-DEMO-002	75 mg	71.6	34.2	98.9	4.49	0.991
12-DEMO-002	75 mg	73.6	49.2	103	4.52	0.930

Data were analyzed in quadruplicate.

The results are very clear.

Source code: foo.R

Source file: foo.tex

4 Notes in minipage

- By default, notes are put in the 3rd part of threeparttable
- Alternatively, we can put them in a minipage just below the table

```
data %>%
  st_new() %>%
  st_files("foo.R", "foo.tex") %>%
  st_noteconf(type = "minipage", width = 0.65) %>%
  st_notes(
    "Data were analyzed in quadruplicate.",
    "The results are very clear."
  ) %>%
  st_make(.cat = TRUE)
```

STUDY	DOSE	WT	AGE	CRCL	ALB	SCR
12-DEMO-001	100 mg	71.4	33.7	104	4.20	1.06
12-DEMO-001	150 mg	89.4	24.4	122	4.63	1.12
12-DEMO-001	150 mg	81.7	34.4	104	3.83	0.910
12-DEMO-001	150 mg	94.0	27.4	93.2	4.94	1.25
12-DEMO-001	200 mg	67.9	27.5	100	4.25	1.10
12-DEMO-001	200 mg	76.6	22.8	99.2	4.54	1.15
12-DEMO-002	100 mg	61.3	38.3	113	4.04	1.28
12-DEMO-002	100 mg	77.6	29.9	106	4.31	0.981
12-DEMO-002	50 mg	74.1	37.1	112	4.44	0.900
12-DEMO-002	50 mg	71.2	34.1	106	4.63	0.868
12-DEMO-002	75 mg	72.4	38.2	105	3.89	0.900
12-DEMO-002	75 mg	71.6	34.2	98.9	4.49	0.991
12-DEMO-002	75 mg	73.6	49.2	103	4.52	0.930

Data were analyzed in quadruplicate.

The results are very clear.

Source code: foo.R

Source file: foo.tex

5 Align

- Center everything except for
- STUDY (left)
- DOSE and SCR (right)

```
data %>%  
  st_new() %>%  
  st_align("c", STUDY = 'l', .r = "DOSE,SCR") %>%  
  st_make(.cat = TRUE)
```

STUDY	DOSE	WT	AGE	CRCL	ALB	SCR
12-DEMO-001	100 mg	71.4	33.7	104	4.20	1.06
12-DEMO-001	150 mg	89.4	24.4	122	4.63	1.12
12-DEMO-001	150 mg	81.7	34.4	104	3.83	0.910
12-DEMO-001	150 mg	94.0	27.4	93.2	4.94	1.25
12-DEMO-001	200 mg	67.9	27.5	100	4.25	1.10
12-DEMO-001	200 mg	76.6	22.8	99.2	4.54	1.15
12-DEMO-002	100 mg	61.3	38.3	113	4.04	1.28
12-DEMO-002	100 mg	77.6	29.9	106	4.31	0.981
12-DEMO-002	50 mg	74.1	37.1	112	4.44	0.900
12-DEMO-002	50 mg	71.2	34.1	106	4.63	0.868
12-DEMO-002	75 mg	72.4	38.2	105	3.89	0.900
12-DEMO-002	75 mg	71.6	34.2	98.9	4.49	0.991
12-DEMO-002	75 mg	73.6	49.2	103	4.52	0.930

6 Units

- Automatically put units under the column name

```
units <- ys_get_unit(spec, parens = TRUE)

data %>%
  st_new() %>%
  st_center(STUDY = '1', .r = "DOSE,SCR") %>%
  st_args(units = units) %>%
  st_make(.cat = TRUE)
```

STUDY	DOSE	WT (kg)	AGE (years)	CRCL (ml/min)	ALB (g/dL)	SCR (mg/dL)
12-DEMO-001	100 mg	71.4	33.7	104	4.20	1.06
12-DEMO-001	150 mg	89.4	24.4	122	4.63	1.12
12-DEMO-001	150 mg	81.7	34.4	104	3.83	0.910
12-DEMO-001	150 mg	94.0	27.4	93.2	4.94	1.25
12-DEMO-001	200 mg	67.9	27.5	100	4.25	1.10
12-DEMO-001	200 mg	76.6	22.8	99.2	4.54	1.15
12-DEMO-002	100 mg	61.3	38.3	113	4.04	1.28
12-DEMO-002	100 mg	77.6	29.9	106	4.31	0.981
12-DEMO-002	50 mg	74.1	37.1	112	4.44	0.900
12-DEMO-002	50 mg	71.2	34.1	106	4.63	0.868
12-DEMO-002	75 mg	72.4	38.2	105	3.89	0.900
12-DEMO-002	75 mg	71.6	34.2	98.9	4.49	0.991
12-DEMO-002	75 mg	73.6	49.2	103	4.52	0.930

7 Math

- Columns with at least two \$ are “math” and will not be sanitized
- Otherwise they are functions to “prime” the data frame
- The default is to convert every column to character
- Then walk the columns, look for non-math columns and sanitize them

```
ptab <- readRDS("datasets/ptab.RDS")
ptab
```

```
## # A tibble: 4 x 6
##   .type      Parameter      Symbol  Math      Estimate    SE
##   <chr>      <chr>      <chr>   <chr>      <dbl> <dbl>
## 1 Fixed-effects Clearance    CL (L/h~ "$\\exp(\\thet~ 1.22 0.4
## 2 Fixed-effects Volume of distribu~ V2 (L)    "$\\exp(\\thet~ 5.87 0.89
## 3 Fixed-effects Absorption rate co~ KA (1/h~ "$\\theta_3$" 1.23 0.1
## 4 Unexplained varia~ Additive_error    RUV      "$\\sigma_1$" 0.02 0.01
```

```
ptab %>%
  st_data() %>%
  st_center(Parameter = col_ragged(3), .l = "Symbol") %>%
  st_panel(".type") %>%
  st_make(.cat = TRUE)
```

Parameter	Symbol	Math	Estimate	SE
Fixed-effects				
Clearance	CL (L/hr)	$\exp(\theta_1)$	1.22	0.4
Volume of distribution	V2 (L)	$\exp(\theta_2)$	5.87	0.89
Absorption rate constant	KA (1/hr)	θ_3	1.23	0.1
Unexplained variability				
Additive_error	RUV	σ_1	0.02	0.01

8 hline from column

- Use the column to determine where the hline should go

```
st_new(data) %>%  
  st_hline(from = "STUDY") %>%  
  st_make(.cat = TRUE)
```

STUDY	DOSE	WT	AGE	CRCL	ALB	SCR
12-DEMO-001	100 mg	71.4	33.7	104	4.20	1.06
12-DEMO-001	150 mg	89.4	24.4	122	4.63	1.12
12-DEMO-001	150 mg	81.7	34.4	104	3.83	0.910
12-DEMO-001	150 mg	94.0	27.4	93.2	4.94	1.25
12-DEMO-001	200 mg	67.9	27.5	100	4.25	1.10
12-DEMO-001	200 mg	76.6	22.8	99.2	4.54	1.15
12-DEMO-002	100 mg	61.3	38.3	113	4.04	1.28
12-DEMO-002	100 mg	77.6	29.9	106	4.31	0.981
12-DEMO-002	50 mg	74.1	37.1	112	4.44	0.900
12-DEMO-002	50 mg	71.2	34.1	106	4.63	0.868
12-DEMO-002	75 mg	72.4	38.2	105	3.89	0.900
12-DEMO-002	75 mg	71.6	34.2	98.9	4.49	0.991
12-DEMO-002	75 mg	73.6	49.2	103	4.52	0.930

9 hline anywhere

- Give row numbers for hline

```
st_new(data) %>%  
  st_hline(at = c(3,nrow(data))-1) %>%  
  st_make(.cat = TRUE)
```

STUDY	DOSE	WT	AGE	CRCL	ALB	SCR
12-DEMO-001	100 mg	71.4	33.7	104	4.20	1.06
12-DEMO-001	150 mg	89.4	24.4	122	4.63	1.12
12-DEMO-001	150 mg	81.7	34.4	104	3.83	0.910
12-DEMO-001	150 mg	94.0	27.4	93.2	4.94	1.25
12-DEMO-001	200 mg	67.9	27.5	100	4.25	1.10
12-DEMO-001	200 mg	76.6	22.8	99.2	4.54	1.15
12-DEMO-002	100 mg	61.3	38.3	113	4.04	1.28
12-DEMO-002	100 mg	77.6	29.9	106	4.31	0.981
12-DEMO-002	50 mg	74.1	37.1	112	4.44	0.900
12-DEMO-002	50 mg	71.2	34.1	106	4.63	0.868
12-DEMO-002	75 mg	72.4	38.2	105	3.89	0.900
12-DEMO-002	75 mg	71.6	34.2	98.9	4.49	0.991
12-DEMO-002	75 mg	73.6	49.2	103	4.52	0.930

10 Remove duplicate values

- Discard repeating values in a column

```
data %>%  
  st_new() %>%  
  st_hline(from = "STUDY") %>%  
  st_clear_reps("STUDY") %>%  
  st_make(.cat = TRUE)
```

```
## Warning in data[[dd$col]][dd$dup] <- rep("", dd$n): number of items to replace  
## is not a multiple of replacement length
```

STUDY	DOSE	WT	AGE	CRCL	ALB	SCR
12-DEMO-001	100 mg	71.4	33.7	104	4.20	1.06
	150 mg	89.4	24.4	122	4.63	1.12
	150 mg	81.7	34.4	104	3.83	0.910
	150 mg	94.0	27.4	93.2	4.94	1.25
	200 mg	67.9	27.5	100	4.25	1.10
	200 mg	76.6	22.8	99.2	4.54	1.15
12-DEMO-002	100 mg	61.3	38.3	113	4.04	1.28
	100 mg	77.6	29.9	106	4.31	0.981
	50 mg	74.1	37.1	112	4.44	0.900
	50 mg	71.2	34.1	106	4.63	0.868
	75 mg	72.4	38.2	105	3.89	0.900
	75 mg	71.6	34.2	98.9	4.49	0.991
	75 mg	73.6	49.2	103	4.52	0.930

11 Panel

- Divide the table using column contents
- there's a bug somewhere there

```
data %>%  
  st_new() %>%  
  st_center(DOSE = 'l', SCR = 'r') %>%  
  st_panel("STUDY", prefix = "Study number: ") %>%  
  st_make(.cat = TRUE)
```

DOSE	WT	AGE	CRCL	ALB	SCR
Study number: 12-DEMO-001					
100 mg	71.4	33.7	104	4.20	1.06
150 mg	89.4	24.4	122	4.63	1.12
150 mg	81.7	34.4	104	3.83	0.910
150 mg	94.0	27.4	93.2	4.94	1.25
200 mg	67.9	27.5	100	4.25	1.10
200 mg	76.6	22.8	99.2	4.54	1.15
Study number: 12-DEMO-002					
100 mg	61.3	38.3	113	4.04	1.28
100 mg	77.6	29.9	106	4.31	0.981
50 mg	74.1	37.1	112	4.44	0.900
50 mg	71.2	34.1	106	4.63	0.868
75 mg	72.4	38.2	105	3.89	0.900
75 mg	71.6	34.2	98.9	4.49	0.991
75 mg	73.6	49.2	103	4.52	0.930

12 Colspan

- Group columns

```
data %>%  
  st_new() %>%  
  st_left(.c = "WT,AGE,CRCL") %>%  
  st_span("In fonal model", WT:CRCL) %>%  
  st_make(.cat = TRUE)
```

STUDY	DOSE	In fonal model			ALB	SCR
		WT	AGE	CRCL		
12-DEMO-001	100 mg	71.4	33.7	104	4.20	1.06
12-DEMO-001	150 mg	89.4	24.4	122	4.63	1.12
12-DEMO-001	150 mg	81.7	34.4	104	3.83	0.910
12-DEMO-001	150 mg	94.0	27.4	93.2	4.94	1.25
12-DEMO-001	200 mg	67.9	27.5	100	4.25	1.10
12-DEMO-001	200 mg	76.6	22.8	99.2	4.54	1.15
12-DEMO-002	100 mg	61.3	38.3	113	4.04	1.28
12-DEMO-002	100 mg	77.6	29.9	106	4.31	0.981
12-DEMO-002	50 mg	74.1	37.1	112	4.44	0.900
12-DEMO-002	50 mg	71.2	34.1	106	4.63	0.868
12-DEMO-002	75 mg	72.4	38.2	105	3.89	0.900
12-DEMO-002	75 mg	71.6	34.2	98.9	4.49	0.991
12-DEMO-002	75 mg	73.6	49.2	103	4.52	0.930

13 Colspan - multiple

- Multiple groupings
- Multiple levels

```
data %>%
  st_new() %>%
  st_panel("STUDY", prefix = "Study ") %>%
  st_left(.c = "WT,AGE,CRCL") %>%
  st_files("foo.R", "foo.tex") %>%
  st_span("Meh", DOSE:WT) %>%
  st_span("Hrm", AGE:CRCL) %>%
  st_span("Huh", ALB:SCR) %>%
  st_span("Exper opinion", CRCL:SCR, level = 2) %>%
  st_make(.cat = TRUE)
```

		Exper opinion				
		Meh	Hrm		Huh	
DOSE	WT	AGE	CRCL	ALB	SCR	
Study 12-DEMO-001						
100 mg	71.4	33.7	104	4.20	1.06	
150 mg	89.4	24.4	122	4.63	1.12	
150 mg	81.7	34.4	104	3.83	0.910	
150 mg	94.0	27.4	93.2	4.94	1.25	
200 mg	67.9	27.5	100	4.25	1.10	
200 mg	76.6	22.8	99.2	4.54	1.15	
Study 12-DEMO-002						
100 mg	61.3	38.3	113	4.04	1.28	
100 mg	77.6	29.9	106	4.31	0.981	
50 mg	74.1	37.1	112	4.44	0.900	
50 mg	71.2	34.1	106	4.63	0.868	
75 mg	72.4	38.2	105	3.89	0.900	
75 mg	71.6	34.2	98.9	4.49	0.991	
75 mg	73.6	49.2	103	4.52	0.930	

Source code: foo.R

Source file: foo.tex

14 Colspan - from cols

- we have some columns of the form tag.name

```
dotdata <- readRDS("datasets/with-dots.RDS")
head(dotdata, n=2)
```

```
## # A tibble: 2 x 7
##   STUDY      Normal.WT Normal.CRCL Normal.ALB ESRD.WT ESRD.CRCL ESRD.ALB
##   <chr>      <chr>      <chr>      <chr>      <chr>      <chr>      <chr>
## 1 12-DEMO-001 71.4      104        4.20      78.5      26.0      2.10
## 2 12-DEMO-001 81.7      104        3.83      89.9      26.1      1.92
```

```
dotdata %>%
  st_new() %>%
  st_panel("STUDY", prefix = "Study") %>%
  st_span_split(sep = '.') %>%
  st_left(.c = "WT,AGE,CRCL") %>%
  st_files("foo.R", "foo.tex") %>%
  st_make(.cat = TRUE)
```

Normal			ESRD		
WT	CRCL	ALB	WT	CRCL	ALB
Study 12-DEMO-001					
71.4	104	4.20	78.5	26.0	2.10
81.7	104	3.83	89.9	26.1	1.92
89.4	122	4.63	98.4	30.6	2.32
94.0	93.2	4.94	103	23.3	2.47
67.9	100	4.25	74.7	25.1	2.13
76.6	99.2	4.54	84.2	24.8	2.27
Study 12-DEMO-002					
77.6	106	4.31	85.4	26.4	2.16
61.3	113	4.04	67.4	28.2	2.02
71.2	106	4.63	78.3	26.4	2.32
74.1	112	4.44	81.5	28.0	2.22
71.6	98.9	4.49	78.8	24.7	2.25
72.4	105	3.89	79.6	26.3	1.94
73.6	103	4.52	81.0	25.8	2.26

Source code: foo.R

Source file: foo.tex

15 Handle wide columns

15.1 descr is taking over the table

```
ptable <- readRDS("datasets/ptable.RDS")  
ptable %>% st_new() %>% st_make(.cat = TRUE)
```

symbol	descr	estimate	standard.error
CL (L)	Metabolic clearance in adults who graduated high school before 1973 and live in Muncie.	100	200

15.2 Limit descr to 5 cm

```
ptable %>%  
  st_new() %>%  
  st_align(descr = col_ragged(5)) %>%  
  st_make(.cat = TRUE)
```

symbol	descr	estimate	standard.error	rse
CL (L)	Metabolic clearance in adults who graduated high school before 1973 and live in Muncie.	100	200	2

16 Identify a summary row

We can point to one or more rows and style it up as a “summary row”

```
df.total <- readRDS(file = "datasets/with-total.RDS")
df.total

## # A tibble: 3 x 6
##   STUDY      WT    AGE  CRCL  ALB   SCR
##   <chr>    <chr> <chr> <chr> <chr> <chr>
## 1 12-DEMO-001 80.2  28.4  104   4.40  1.10
## 2 12-DEMO-002 71.7  37.3  106   4.33  0.979
## 3 all        75.9  32.8  105   4.37  1.04

st_new(df.total) %>%
  st_args(units = ys_get_unit(spec, parens = TRUE)) %>%
  st_center(STUDY = 'l') %>%
  st_files("foo.R", "output.tex") %>%
  st_rename("Protocol no." = "STUDY") %>%
  st_notes("WT: weight; CRCL: creatinine clearance") %>%
  st_sumrow(.$data$STUDY=="all", label = "All studies", bold = TRUE) %>%
  st_make(.cat = TRUE)
```

Protocol no.	WT (kg)	AGE (years)	CRCL (ml/min)	ALB (g/dL)	SCR (mg/dL)
12-DEMO-001	80.2	28.4	104	4.40	1.10
12-DEMO-002	71.7	37.3	106	4.33	0.979
All studies	75.9	32.8	105	4.37	1.04

WT: weight; CRCL: creatinine clearance

Source code: foo.R

Source file: output.tex

17 Fontsize

- Where's my glasses?

```
data %>% st_new() %>% st_args(fontsize = "tiny") %>% st_make(.cat = TRUE)
```

STUDY	DOSE	WT	AGE	CRCL	ALB	SCR
12-DEMO-001	100 mg	71.4	33.7	104	4.20	1.06
12-DEMO-001	150 mg	89.4	24.4	122	4.63	1.12
12-DEMO-001	150 mg	81.7	34.4	104	3.83	0.910
12-DEMO-001	150 mg	94.0	27.4	93.2	4.94	1.25
12-DEMO-001	200 mg	67.9	27.5	100	4.25	1.10
12-DEMO-001	200 mg	76.6	22.8	99.2	4.54	1.15
12-DEMO-002	100 mg	61.3	38.3	113	4.04	1.28
12-DEMO-002	100 mg	77.6	29.9	106	4.31	0.981
12-DEMO-002	50 mg	74.1	37.1	112	4.44	0.900
12-DEMO-002	50 mg	71.2	34.1	106	4.63	0.868
12-DEMO-002	75 mg	72.4	38.2	105	3.89	0.900
12-DEMO-002	75 mg	71.6	34.2	98.9	4.49	0.991
12-DEMO-002	75 mg	73.6	49.2	103	4.52	0.930

18 Row space

```
s1 <- data %>% slice(1:3)
s1 %>% st_new() %>% st_make(.cat = TRUE)
```

STUDY	DOSE	WT	AGE	CRCL	ALB	SCR
12-DEMO-001	100 mg	71.4	33.7	104	4.20	1.06
12-DEMO-001	150 mg	89.4	24.4	122	4.63	1.12
12-DEMO-001	150 mg	81.7	34.4	104	3.83	0.910

```
s1 %>% st_new() %>% st_space(0.9) %>% st_make(.cat = TRUE)
```

STUDY	DOSE	WT	AGE	CRCL	ALB	SCR
12-DEMO-001	100 mg	71.4	33.7	104	4.20	1.06
12-DEMO-001	150 mg	89.4	24.4	122	4.63	1.12
12-DEMO-001	150 mg	81.7	34.4	104	3.83	0.910

```
s1 %>% st_new() %>% st_space(2) %>% st_make(.cat = TRUE)
```

STUDY	DOSE	WT	AGE	CRCL	ALB	SCR
12-DEMO-001	100 mg	71.4	33.7	104	4.20	1.06
12-DEMO-001	150 mg	89.4	24.4	122	4.63	1.12
12-DEMO-001	150 mg	81.7	34.4	104	3.83	0.910

19 Col space

```
data %>% st_new() %>% st_space(col = 20) %>% st_make(.cat = TRUE)
```

STUDY	DOSE	WT	AGE	CRCL	ALB	SCR
12-DEMO-001	100 mg	71.4	33.7	104	4.20	1.06
12-DEMO-001	150 mg	89.4	24.4	122	4.63	1.12
12-DEMO-001	150 mg	81.7	34.4	104	3.83	0.910
12-DEMO-001	150 mg	94.0	27.4	93.2	4.94	1.25
12-DEMO-001	200 mg	67.9	27.5	100	4.25	1.10
12-DEMO-001	200 mg	76.6	22.8	99.2	4.54	1.15
12-DEMO-002	100 mg	61.3	38.3	113	4.04	1.28
12-DEMO-002	100 mg	77.6	29.9	106	4.31	0.981
12-DEMO-002	50 mg	74.1	37.1	112	4.44	0.900
12-DEMO-002	50 mg	71.2	34.1	106	4.63	0.868
12-DEMO-002	75 mg	72.4	38.2	105	3.89	0.900
12-DEMO-002	75 mg	71.6	34.2	98.9	4.49	0.991
12-DEMO-002	75 mg	73.6	49.2	103	4.52	0.930