

## Introduction to Two Pointers

①


- ↳ **Two Pointers pattern** is a technique used for solving problems involving sequential data structures (e.g., arrays, linked lists).
- ↳ It involves **maintaining two pointers** that traverse the structure in a coordinated way.
- ↳ The pointers typically start from **different positions** or move in **opposite directions**.
- ↳ They **dynamically adjust** based on conditions or criteria related to the problem.
- ↳ This pattern enables **efficient exploration** of data.
- ↳ It often leads to **optimal time and space complexity** solutions.
- ↳ Especially useful when trying to **find two elements** in an array that satisfy a specific condition.
- ↳ Should be **one of the first strategies** considered for such problems.

## Examples


2

↳ Reversing an Array: Given an array of integers, reverse it in place.


i) The input array




ii) Initialize two pointers,  $p1$  and  $p2$ , at the start and end of the array.



iii) Swap the values of the indexes pointed to by  $p1$  and  $p2$ .




iv) After swapping the values, move the pointers inwards, i.e., increment  $p1$  and decrement  $p2$ .




3


v) Swap the values of the indexes pointed to by  $p1$  and  $p2$ .




vi) After swapping the values, move the pointers inwards, i.e., increment  $p1$  and decrement  $p2$ .




vii) Swap the values of the indexes pointed to by  $p1$  and  $p2$ .



viii) After swapping the values, move the pointers inwards, i.e., increment  $p1$  and decrement  $p2$ .



ix) Because the pointers  $p1$  and  $p2$  have surpassed, the algorithm ends. The array has been reversed.



↳ Pair with Given Sum in a Sorted Array: Given a sorted array of integers, find a pair in the array that sums to a number  $T$ .

(4)

i) Given the following array, we need to find a pair that sums up to 14.

arr	2	3	5	7	11	13
-----	---	---	---	---	----	----

T	14
---	----

ii) Initialize two pointers,  $p1$  and  $p2$ , at the start and end of the array. Calculate the sum of the indexes pointed to by  $p1$  and  $p2$ . If the sum is equal to  $T$ , we've found the solution pair. If the sum is greater than  $T$ , decrement  $p2$ . Otherwise, increment  $p1$ .

	$p1$					$p2$
	↓					↓
arr	2	3	5	7	11	13

T	14
---	----


iii) Because the sum of the values pointed to by  $p1$  and  $p2$  is greater than  $T$ , decrement  $p2$  to move it inward towards the smaller values in the array.

	$p1$					$p2$
	↓					↓
arr	2	3	5	7	11	13


T	14
---	----

iv) Now, the sum of the values pointed to by  $p1$  and  $p2$  is less than  $T$ , increment  $p1$ .

⑤



v) The  $p1$  and  $p2$  are pointing to 3 and 11. Since they sum to  $T$ , i.e. 14, the solution pair is found.



## Does the Problem Match this Pattern?

⑥

↳ Yes, if all the following conditions are true:

- i) Linear Data Structure: The input data can be traversed in a linear fashion, such as an array, linked list, or string.
- ii) Process Pairs: Process data elements at two different positions simultaneously.
- iii) Dynamic Pointer Movement: Both pointers move independently of each other according to certain conditions or criteria. In addition, both pointers might move along the same or two different data structures.