Yes. **Shenandoah GC** is the next logical step after G1 in the evolution we've been discussing.

The key idea is:


> **G1 tries to keep GC pauses predictable by doing concurrent marking but performs evacuation during STW pauses. Shenandoah moves the evacuation and reference updating largely concurrently with the application.**

That is the major conceptual leap.

---

1. Where Shenandoah fits

A simplified evolution is:



The important distinction is:

```
G1:
    Mark concurrently
    Evacuate during STW

Shenandoah:
    Mark concurrently
    Evacuate concurrently
    Update references concurrently
```

---

2. Why was Shenandoah needed?

Imagine a 100 GB heap.


Suppose you have:

```
10 GB live objects
90 GB garbage
```

A collector wants to reclaim the garbage.

But there are millions/billions of references between objects.

If you need to stop the application while moving all those objects:



The pause could become significant.

Shenandoah asks:

> **Why can't we move objects while the application is running?**


That's the central idea.

---

3. Heap Layout

Like G1, Shenandoah divides the heap into regions.

For example:



Suppose:

```
R1 = mostly garbage
R2 = mostly garbage
R3 = mostly live
R4 = mostly garbage
```

Shenandoah wants to reclaim:


```
R1
R2
R4
```


by moving their live objects elsewhere.

---


4. Example Object Graph

Suppose:






Memory:



Suppose R1 needs to be evacuated.

Shenandoah wants:



The problem is:


> **The application may still access A, B, C, and D while they're being moved.**

That's where Shenandoah's key mechanisms come in.

---

5. Shenandoah's Core Trick: Forwarding

Suppose:



Shenandoah copies A:

```
A'
R10 / address 0x5000
```

Now we have:

```
Old location
0x1000 → A

New location
0x5000 → A'
```

The collector needs a way to say:

```
A → A'
```

This is called a **forwarding pointer/reference**.

Conceptually:

```
Old A
┌──────────────┐
│ forwarding ──────────→ New A
│ fields       │
└──────────────┘
```

This allows the JVM to redirect accesses to the new copy.

---

6. Brooks Pointer


Historically, Shenandoah used a technique commonly described using a **Brooks forwarding pointer**.


Conceptually:

```
Object A
┌──────────────────────┐
│ forwarding pointer ──┼──→ A
├──────────────────────┤
│ fields               │
```



After evacuation:





The exact implementation details have evolved across Shenandoah versions, so don't treat "Brooks pointer" as the only mechanism in modern Shenandoah.


The interview-level concept is:


> **Shenandoah maintains forwarding information so references can be resolved to an object's new location while evacuation happens concurrently.**

---

7. Shenandoah's Main Phases

A simplified lifecycle is:






There are implementation/version-specific nuances, but this is the right conceptual model.

---


8. Phase 1 — Initial Mark

Application threads briefly stop.



The collector identifies initial reachable objects from GC roots.

For example:




These become part of the marking process.

The pause is designed to be short.

---

9. Phase 2 — Concurrent Mark

Now application threads resume.



Both run simultaneously.

Shenandoah traverses the object graph and determines which objects are live.

This uses the same fundamental ideas we've already discussed:

- Tri-color marking
- Write barriers
- Concurrent graph traversal

---

10. Mutation During Marking

Suppose GC sees:

```
A → B
```

Then application changes it:

```
A → C
```

while marking is happening.

The collector uses barriers to maintain correctness.

This is conceptually similar to the **SATB** discussion from G1.


Instead of stopping every time the application changes an object graph, the GC records enough information to preserve the required marking semantics.

---

11. Phase 3 — Final Mark

Eventually the concurrent marking phase needs to finish.

There is a short STW pause:



The purpose is to finish outstanding marking work and establish the set of live objects.

This is one of the important answers to your earlier question:

> "Why can't GC eliminate STW entirely?"

Shenandoah dramatically minimizes STW, but still needs very short synchronization points for certain global state transitions.

---

12. Phase 4 — Identify Evacuation Candidates

Suppose:

Region	Live
R1	10%
R2	20%
R3	95%
R4	15%

Shenandoah wants to reclaim:

```
R1
R2
R4
```

because they contain mostly garbage.

This resembles G1's region selection.

But now comes the major difference.

---

13. G1 vs Shenandoah

G1:

```
STW
 │
 ├── Evacuate R1
 ├── Evacuate R2
 └── Evacuate R4
 │
 ▼
Resume
```

Shenandoah:

```
Application
████████████████████████████████

GC evacuation
        ████████████████
```

Evacuation happens concurrently.

This is Shenandoah's defining feature.

---

14. Concurrent Evacuation Example

Suppose:

```
R1:

A → B → C
    |
    └→ D
```

Shenandoah chooses R1 for evacuation.

It allocates destination space:


```
R10
```

and copies:

```
A → A'
B → B'
C → C'
D → D'
```

while application threads continue executing.

Conceptually:



If the application encounters an object whose old location has already been evacuated, the JVM can resolve the reference to the new copy.

---

15. The Interesting Race

Suppose two threads simultaneously try to evacuate A:

```
Thread GC1 → copy A → A1
Thread GC2 → copy A → A2
```

We don't want:

```
A → A1
A → A2
```

with inconsistent semantics.

The runtime uses synchronization/atomic operations around forwarding so that one copy becomes the authoritative destination and other attempts resolve appropriately.

The exact implementation details are more complicated, but the important idea is:

> **Object evacuation requires synchronization because multiple GC/application threads can encounter the same object concurrently**.

---

16. Phase 5 — Update References

Now suppose:

```
A → B
```

and both moved:

```
A' → B'
```

But somewhere else we still have:

```
X → A
```

Shenandoah must eventually turn this into:

```
X → A'
```

This is **concurrent reference updating**.

So:

```
Before:

X ──→ A ──→ B

After evacuation:

X ──→ A'
      │
      └──→ B'
```

The application can continue running during much of this process.

---

17. Load Barriers

This is an extremely important Shenandoah concept.

When the application loads a reference:

```
Object x = obj.child;
```

the JVM can execute a **load barrier**.

Conceptually:

```
obj.child
    │
    ▼
Load Barrier
    │
    ├── Is reference forwarded?
    │
    └── If yes → resolve new location
                 │
```

```
        ▼
       A'
```

This is fundamentally different from a simple write barrier.

Write barrier

Triggered when application modifies a reference:

```
A.child = B;
        ↑
    barrier
```

Load barrier

Triggered when application reads a reference:

```
B = A.child;
    ↑
 barrier
```

Shenandoah relies heavily on **load barriers** to support concurrent relocation.

---

18. Why Load Barriers Are So Powerful

Consider:

```
Old:

A @ 0x1000
```

GC moves it:

```
New:

A' @ 0x9000
```

Application still has:

```
reference → 0x1000
```

Instead of stopping the application and immediately updating every reference, the load barrier can effectively say:

```
"You're trying to access an evacuated object.
Let me resolve its current location."
```

Therefore:

```
Application
    |
    ▼
old reference
    |
    ▼
Load Barrier
    |
    ▼
forwarding information
    |
    ▼
new object
```

This is one of the key mechanisms that makes concurrent evacuation possible.

---

19. Complete Example

Let's put the whole process together.

Initial heap:

```
R1:

        A
       / \
      B   D
```

```
      |
      C
```

And:

```
R2 = mostly garbage
R3 = mostly garbage
R4 = mostly live
```

Step 1 — Initial Mark

```
STW
```

Identify:

```
A B C D = reachable
```

Resume application.

Step 2 — Concurrent Mark

```
Application ████████████████████
GC          ██████████████
```

GC finishes determining live objects.

Step 3 — Final Mark

Short:

```
STW → finalize marking → resume
```

Step 4 — Select regions

Suppose:

```
R1 = 30% live
R2 = 10% live
R3 = 15% live
R4 = 90% live
```


Select:

```
R1
R2
R3
```

for reclamation.

Step 5 — Concurrent Evacuation

Move live objects:



Application continues running.

Step 6 — References

Suppose another object X contains:

```
X → A
```

During/after relocation:

```
X → A'
```

Load/reference barriers help ensure application threads safely interact with the relocated objects.

Step 7 — Reclaim old regions

Eventually:

```
R1 → FREE
R2 → FREE
R3 → FREE
```

The heap now has reusable regions without requiring a large STW compaction pause.

---

20. Compare the Three Collectors

This is probably the most valuable table for interviews:

	Parallel GC	G1	Shenandoah
Generational	Yes	Yes	Yes in modern Shenandoah
Region based	No	Yes	Yes
STW Young GC	Yes	Yes	Some STW phases
Concurrent marking	No	Yes	Yes
Concurrent evacuation	No	No	**Yes**
Concurrent reference processing	No	Limited/different	**Yes**
Compaction	STW	Evacuation pauses	**Concurrent evacuation**
Main goal	Throughput	Balanced	**Low latency**
Barrier emphasis	Write/card barriers	SATB + remembered sets	**Load + write barriers**

---

21. The Most Important Difference

Think about the moment where objects are moved.

Parallel GC

```
STOP
 ↓
Move objects
 ↓
Update references
 ↓
RESUME
```

G1

```
STOP
 ↓
Evacuate selected regions
 ↓
Update references
 ↓
RESUME
```

Shenandoah

```
Application continues
        |
        ├──── GC moves objects
        |
        ├──── Application reads references
        |
        ├──── Load barriers resolve forwarding
        |
        └──── GC updates references
```

That's the fundamental architectural difference.


---

22. Why Doesn't Shenandoah Need a Huge STW Pause?


Because it shifts expensive work from:



to:



Only short synchronization phases remain:



The exact pause characteristics depend on workload, heap, CPU, configuration, and JVM version.

---


23. The Cost

Shenandoah isn't simply "better G1."

It pays for low latency.

① Barriers

Application reads/writes may require additional GC-related work.



```
      ↓
actual object
```

② CPU overhead

GC is running concurrently:

```
Application → CPU
GC          → CPU
```

Both compete for resources.

③ Memory overhead

Forwarding/reference metadata and evacuation require additional space and bookkeeping.

④ More complex implementation

The collector must correctly handle:

```
Application mutation
        +
Concurrent marking
        +
Concurrent evacuation
        +
Reference updating
```

That's substantially more complicated than Serial/Parallel GC.

---

24. Shenandoah and Your Earlier Optimistic-Locking Question

This is where your previous question becomes particularly interesting.

You asked:


> Why not use optimistic locking/versioning and retry?

Shenandoah is conceptually closer to that idea than traditional STW collectors—but it doesn't solve the problem by retrying the entire heap traversal.

Instead it uses:

```
Barriers
+
Forwarding information
+
Concurrent state transitions
```

For example:



So rather than:

> **"Detect conflict → restart everything"**

the approach is:

> **"Detect/handle the conflict locally and continue."**

That is much closer to the principle we discussed earlier: **avoid global retries; handle mutations incrementally**.

---

25. The Interview Answer


If an interviewer asks:

"Explain Shenandoah GC."

A strong answer is:

> **"Shenandoah is a low-latency, region-based garbage collector that performs concurrent marking, evacuation, and reference processing. Unlike G1, which performs region evacuation during stop-the-world pauses, Shenandoah can evacuate objects concurrently with application execution. It uses barriers and forwarding information to allow application threads to safely access objects while they are being relocated. There are still short STW phases for operations such as initial/final marking, but the expensive evacuation and reference-update work is largely concurrent."**

And the mental model to remember is:



If G1's defining feature is "Garbage First + region evacuation," Shenandoah's defining feature is "concurrent evacuation."