Yes. I reviewed the **current Elastic documentation**, rather than relying on the older "classic ELK" architecture. As of September 2026, the current Elastic Docs cover **Elastic Stack 9.x, with Elasticsearch 9.5.3 listed as the latest 9.0+ documentation version**. The modern architecture also puts considerably more emphasis on **Elastic Agent, Fleet, data streams, lifecycle management, ECS, ingest pipelines, and Elasticsearch as a general distributed search/analytics engine**, rather than treating Filebeat → Logstash → Elasticsearch → Kibana as the only architecture. (Elastic)

Current Elastic Documentation

Below is the architecture I would recommend learning for **MAANG+ system-design interviews**, followed by the algorithms, protocols, failure modes, trade-offs, and interview questions you should be able to reason about.


---


1. Executive view

The most useful mental model is:

> **Elastic Stack = distributed event-ingestion pipeline + distributed inverted-index/search engine + analytics engine + visualization/control plane.**

A production architecture looks roughly like this:





But there are **three different planes** hidden inside this diagram:

Data plane

```
events → collection → transformation → indexing → search/aggregation
```

Control plane

```
cluster membership
cluster state
shard allocation
node roles
Fleet policies
lifecycle policies
security configuration
```

Presentation/analysis plane

```
Kibana → queries → Elasticsearch → results → dashboards/alerts
```

This distinction is extremely important in a MAANG+ interview.

---

2. First correction: “ELK” is now broader than ELK

Historically:

```
Logstash → Elasticsearch → Kibana
```

was called ELK.

Today, Elastic recommends several ingestion architectures, and **Elastic Agent → Elasticsearch** is often the simplest architecture. Logstash becomes valuable when you need sophisticated transformation, buffering, multiple destinations, network bridging, or ingestion from sources not directly supported by Agent. (Elastic)

So I would learn the stack as:

Component	Primary responsibility
Elastic Agent	Edge collection
Fleet	Agent control plane
Logstash	Advanced ingestion / transformation / routing / buffering
Elasticsearch ingest nodes	Lightweight preprocessing
Elasticsearch	Distributed storage + search + analytics
Kibana	Visualization + operational/control UI
ECS	Common event schema
ILM/DLM	Data lifecycle
Kafka	Optional external durable event backbone

---

3. The core architecture

3.1 Collection layer


Applications produce:

```
application logs
access logs
audit logs
security events
metrics
traces
business events
```

Agents run close to the source.

For example:

```
Application
    |
    ├── stdout
```



The agent can collect, enrich and forward the events.

Fleet provides centralized management of agents and their policies. Elastic describes Fleet Server as a control-plane component that manages agent policies, status and actions. (Elastic)

---


4. Why an agent exists

A common interview question is:

> Why not have every application directly call Elasticsearch?

You can.

For simple environments:



is perfectly reasonable.

But direct application → Elasticsearch has drawbacks:

- application becomes coupled to storage
- Elasticsearch outages affect applications
- parsing logic becomes distributed
- credentials are distributed
- backpressure becomes application responsibility
- schema evolution becomes harder
- applications shouldn't generally know indexing topology

Therefore:

```
Application
    ↓
Agent
    ↓
Buffer / processing
    ↓
Elasticsearch
```

creates **decoupling**.

This is the same architectural reasoning behind Kafka, CDC pipelines and message brokers.

---


5. When Logstash enters the architecture


Logstash implements:

```
Input → Filter → Output
```

The current documentation describes this explicitly. (Elastic)

For example:





Logstash is particularly useful when:

- ingestion sources are heterogeneous
- you need conditional processing
- you need enrichment
- you need multiple outputs
- you need buffering
- you need network bridging
- you already operate Kafka
- you need sophisticated routing

Elastic explicitly recommends Logstash for advanced cases such as enrichment, buffering, proxying, routing to multiple Elasticsearch clusters and additional destinations. (Elastic)

---

6. Logstash's most important distributed-systems concept: backpressure

Suppose:

```
Agents → Logstash → Elasticsearch
```

and Elasticsearch suddenly slows down.


Without backpressure:

```
incoming rate = 500K events/sec
processing rate = 100K events/sec

queue → ∞
```

```
memory → exhausted
process → crash
```

Logstash supports **persistent queues**.



The current documentation describes PQ as a disk-backed queue that protects in-flight events during abnormal termination and can absorb bursts. When the queue fills, Logstash applies backpressure to inputs. (Elastic)

This is a classic:

> **producer-consumer + bounded queue + backpressure**

pattern.

---

7. Persistent Queue is NOT Kafka

This distinction is important.

Logstash PQ

```
one Logstash pipeline
        ↓
local disk
```

It protects against:

- process restart
- abnormal Logstash termination
- temporary Elasticsearch unavailability
- ingestion bursts

But it does **not** replicate the queue across machines. Elastic explicitly notes that PQ does not protect against disk/machine failure because its data isn't replicated. (Elastic)

Kafka

```
Producer
   ↓
Kafka topic
   ├── partition 0
   ├── partition 1
   ├── partition 2
   └── ...
        ↓
   multiple consumers
```

Kafka gives you:

- durable distributed buffering
- replay
- multiple independent consumers
- partition-based parallelism
- replication
- longer retention

Therefore:

```
Agent → Logstash PQ → ES
```

and

```
Agent → Kafka → Logstash → ES
```

solve different problems.

Elastic explicitly documents Kafka as appropriate when you already have Kafka or need an external data hub/replay capability. (Elastic)

---

8. Delivery semantics

This is a very important interview topic.

You should understand:

At-most-once

```
send → don't retry
```

Possible loss.

At-least-once

```
send
 ↓
ACK?
 ├─ yes → remove
 └─ no → retry
```

Possible duplicates.

Exactly-once

Hard in distributed systems because:

```
producer sends
      ↓
consumer processes
      ↓
consumer commits
      ↓
network fails
```

Did processing happen?

You don't know.

The Elastic Agent/Filebeat/Logstash architecture can provide **at-least-once delivery** in documented configurations. Elastic notes that Filebeat/Winlogbeat → Logstash and Logstash → Elasticsearch use acknowledgement-based synchronous communication in the relevant architecture. (Elastic)

Therefore your application should generally tolerate:

```
duplicate events
```

rather than assuming perfect exactly-once semantics.

---

9. ECS — schema normalization

At scale, the biggest problem isn't necessarily ingestion.

It's **semantic fragmentation**.

Imagine:

```
{
  "clientIp": "10.0.0.1"
}
```

another service:

```
{
  "client_ip": "10.0.0.1"
}
```

another:

```
{
  "sourceIP": "10.0.0.1"
}
```

Analytics becomes painful.

ECS provides common field definitions for events such as logs and metrics. (Elastic)

For example:

```
client.ip
host.name
http.request.method
http.response.status_code
log.level
event.action
event.dataset
@timestamp
```

The current ECS guidance requires `@timestamp` and recommends mapping as many fields as possible to ECS. (Elastic)

Think of ECS as:

> **A canonical event contract for observability/security/search data.**

That is a very useful system-design pattern beyond Elasticsearch.

---

10. Ingest pipelines

Elasticsearch itself can process documents before indexing:

```
document
   ↓
processor 1
   ↓
processor 2
   ↓
processor 3
   ↓
indexed document
```

Typical processors:

```
grok
dissect
rename
set
remove
date
```

```
geoip
script
json
user_agent
pipeline
```

For example:

```
raw Apache log
        ↓
      grok
        ↓
extract IP/status/path
        ↓
      ECS mapping
        ↓
      geoip
        ↓
Elasticsearch
```

This is useful when transformations are relatively straightforward.

Logstash remains preferable when processing is complex or when Elasticsearch shouldn't bear the entire ingestion workload.

---

11. Elasticsearch: the real heart of the architecture


The most important thing to understand is:

> Elasticsearch is not primarily a “log database.”

It is a **distributed document store built on Apache Lucene**, with powerful indexing, full-text search, filtering, aggregation and analytics capabilities. Elastic describes Elasticsearch as a distributed document store whose data is distributed across nodes. (Elastic)

The hierarchy is:

```
Cluster
   |
```



The most important chain is:


```
Cluster
  ↓
Index
  ↓
Shard
  ↓
Lucene index
  ↓
Segments
  ↓
Inverted index / doc values / BKD / etc.
```

---

12. Cluster

A cluster is a group of Elasticsearch nodes.

For example:



Every node knows the cluster state.

The master node maintains the authoritative cluster state, including:

- nodes
- settings
- mappings
- shard allocation
- index metadata

The current documentation emphasizes that Elasticsearch is peer-to-peer for high-throughput operations; normal indexing/search does **not** go through the master node. (Elastic)

This is a critical interview point.

---

13. Node roles


Modern Elasticsearch supports specialized roles.


Important ones:

```
master
data
data_content
data_hot
data_warm
data_cold
data_frozen
ingest
ml
transform
remote_cluster_client
```

Every node also has implicit coordinating behavior. (Elastic)

A production architecture might therefore be:





Don't automatically create every type of node.

For a small cluster:

```
3 mixed-role nodes
```

may be entirely appropriate.

For a large cluster:

```
dedicated master
+
data tiers
+
dedicated ingest
+
ML/transform
```

can isolate workloads.

---

14. Master election

This is where distributed-systems knowledge becomes important.

Elasticsearch maintains a **voting configuration** of master-eligible nodes.

Decisions require a majority.

For example:

```
M1
M2
M3
```

quorum:

```
majority = 2
```

Therefore:

```
M1 + M2 → cluster can elect master
M1 only → cannot
```

Elastic recommends at least three master-eligible nodes for HA, with at least two not voting-only, so that one failure doesn't prevent election. (Elastic)

This is conceptually similar to quorum-based consensus systems.

---

15. Cluster state publication

This is a particularly good MAANG+ interview topic.


Suppose an index is created.

The master:

1. receives cluster-state update
2. computes new state
3. publishes it
4. waits for sufficient acknowledgements
5. commits state
6. tells nodes to apply it

Elastic describes cluster-state publication as a two-stage acknowledgement/application process. (Elastic)

Think:



The high-throughput data path doesn't normally involve the master.

---

16. Index

An index is a logical collection of documents.

For example:

```
logs-web
logs-api
logs-payment
```

But in modern Elastic architectures, for append-only time-series data you generally want:

```
data stream
    ↓
backing indices
```

rather than an endlessly growing index.

---

17. Data streams

For logs and metrics:

```
logs-myapp
```

can be a data stream.

Internally:

```
logs-myapp
  │
  ├── backing-index-000001
  ├── backing-index-000002
  ├── backing-index-000003
  └── backing-index-000004 ← write index
```

Applications don't need to know the physical backing index.

They simply write to:

```
logs-myapp
```

This gives you:

- rollover
- lifecycle management
- retention
- better shard sizing
- easier operational management

Elastic recommends data streams for new time-series projects and append-only data. (Elastic)

---

18. Sharding

An index is divided into shards.

Example:

```
index
 │
 ├── shard 0
 ├── shard 1
 ├── shard 2
 └── shard 3
```

Each shard is an independent Lucene index.

Therefore:

```
large index
     ↓
multiple shards
     ↓
multiple nodes
     ↓
parallel indexing/search
```

Elastic explicitly describes each shard as a self-contained Lucene index containing a subset of the documents. (Elastic)

---

19. Primary and replica shards

Suppose:

```
4 primary shards
1 replica
```

You have:

```
P0 → R0
P1 → R1
P2 → R2
P3 → R3
```

which means:

```
8 shard copies
```

The replicas provide:

1. fault tolerance
2. read capacity

They are not merely backups.

---

20. Shard routing algorithm

This is one of the algorithms you absolutely should know.

The current Elasticsearch routing formula is:

```
shard_num = hash(_routing) % num_primary_shards
```

The default routing value is `_id`. (Elastic)

Therefore:

```
document ID
     ↓
   hash
     ↓
 modulo N
     ↓
primary shard
```

Example:

```
hash("customer-123") % 8 = 5
```

→ shard 5.

This is why Elasticsearch can determine the target shard without scanning the cluster.

---

21. Custom routing

You can route by:

```
tenant_id
customer_id
account_id
```

For example:

```
routing = customer_id
```

Then all documents for a customer can land on one shard.

Benefit:

```
customer query
      ↓
one shard
```

instead of:

```
customer query
      ↓
all 100 shards
```

But this creates the classic distributed-systems trade-off:

> **locality vs load distribution**

If one customer is huge:

```
customer A → 10 billion docs
customer B → 10K docs
```

you've created a hotspot.

Elastic explicitly documents this routing trade-off and also provides index partitioning to distribute a routing value across a subset of shards. (Elastic)

---

22. Shard sizing

A key system-design principle:

> Don't choose shard count arbitrarily.

Too few shards:

```
large shard
↓
slow recovery
slow queries
limited parallelism
```

Too many shards:

```
small shards
↓
cluster-state overhead
file descriptors
heap pressure
coordination overhead
```

For time-series workloads, Elastic currently describes **10–50 GB** as a useful shard-size range in its rollover guidance, while also noting a hard rollover trigger around 200 million documents per shard. (Elastic)

Treat that as a **starting guideline**, not a universal law.

---

23. Indexing pipeline

Now we get to the most important internal algorithmic flow.

Suppose:

```
{
  "message": "Payment failed",
  "status": 500,
```

```
    "service": "payments"
  }
```

is sent to Elasticsearch.

Conceptually:

```
HTTP request
      ↓
coordinating node
      ↓
routing
      ↓
primary shard
      ↓
mapping
      ↓
analysis/indexing
      ↓
Lucene segment
      ↓
replica
```

---

24. Mapping

Mapping tells Elasticsearch:

```
field → datatype + indexing behavior
```

Example:

```
status      → integer
service     → keyword
message     → text
timestamp   → date
```

This distinction is crucial:

`text`

Designed for full-text search.

```
"payment failed"
```

is analyzed into tokens.

`keyword`

Designed for exact matching:

```
service = "payments"
```

and:

- sorting
- aggregations
- filtering

This is a common interview question.

---

25. Analysis pipeline

For text:

```
raw text
    ↓
character filters
    ↓
tokenizer
    ↓
token filters
    ↓
tokens
```

Example:

```
"The Payment FAILED!"
```

might become:

```
the
payment
failed
```

depending on the analyzer.

Those tokens are then inserted into the inverted index.

---

26. Inverted index

This is perhaps the **single most important Elasticsearch data structure**.

Instead of:

```
Document → words
```

we build:

```
Word → documents
```

Example:

```
Documents

D1: "payment failed"
D2: "payment succeeded"
D3: "database failed"
```

Inverted index:

```
payment  → D1, D2
failed   → D1, D3
database → D3
succeeded → D2
```

Now:

```
query: failed
```

doesn't scan all documents.

It directly finds:

```
D1, D3
```

This is the fundamental reason search engines outperform naive document scanning.

---

27. Terms dictionary

The inverted index has additional structures for efficient term lookup.

Conceptually:

```
term dictionary
        ↓
posting list
        ↓
document IDs
```

Modern Lucene uses highly optimized structures such as finite-state representations for term dictionaries.

For an interview, the important abstraction is:

```
term → posting list
```

rather than the implementation minutiae.

---

28. Doc values

Inverted indexes answer:

```
term → documents
```

But aggregations and sorting frequently need:

```
document → value
```

That's what **doc values** help with.

Elastic describes doc values as an on-disk columnar structure designed for sorting, aggregations and field-value access. (Elastic)

Think:

```
Inverted index:

"error" → [D1,D5,D9]


Doc values:

D1 → "payments"
D2 → "orders"
D3 → "payments"
...
```

This is analogous to the difference between:

```
index-oriented access
```

and

```
column-oriented access
```

---

29. Numeric fields and BKD trees

Numeric/date/geo data needs range queries.

For example:

```
status >= 500
timestamp BETWEEN t1 AND t2
```

```
lat/lon within region
```

Elasticsearch/Lucene uses **BKD-tree-based structures** for many numeric and geo indexing operations.

Elastic's current numeric documentation explicitly describes numeric fields as indexed using BKD trees for range queries. (Elastic)

So remember:

```
text search        → inverted index
sorting/aggs       → doc values
numeric ranges     → BKD trees
vector search      → HNSW / related vector structures
```

That is a very good MAANG+ mental map.

---

30. Lucene segments

Documents aren't rewritten into one giant index after every write.

Instead:

```
memory buffer
      ↓
segment
      ↓
segment
      ↓
segment
      ↓
merge
```

A shard consists of multiple Lucene segments.

Segments are effectively immutable.

Deletes/updates therefore work conceptually as:

```
old document → marked deleted
new document → indexed
```

rather than modifying an existing Lucene document in place.

---

31. Refresh vs flush vs commit

This distinction is extremely important.

Refresh

Makes newly indexed documents searchable.

```
buffer
  ↓
new searchable segment
```

It does **not** mean durable disk commit.

Elastic calls Elasticsearch **near-real-time search** because refresh makes changes visible without requiring a full commit. The default periodic refresh behavior is roughly one second for active/searchable indices. (Elastic)

Flush/commit

Concerned with durable persistence and Lucene commit points.

Translog

Provides Elasticsearch's durability/recovery mechanism for operations that have been accepted but may not yet be represented in a committed Lucene segment.

Therefore:

```
INDEX
 ↓
translog / memory
 ↓
refresh
 ↓
searchable
 ↓
flush/commit
```

```
  ↓
durable Lucene commit
```

Do **not** say:

> "Elasticsearch writes directly to the final index and immediately searches it."

That is not how the engine works.

---

32. Why Elasticsearch is near-real-time

Suppose:

```
t = 0ms
index document
```

Immediately:

```
GET document
```

may see it.

But:

```
search "document contents"
```

may not yet see it.

After refresh:

```
search → visible
```

Hence:


> **near-real-time rather than strictly real-time.**

You can explicitly control refresh behavior when necessary. (Elastic)

---

33. Write path

The distributed write path is approximately:



The key principle:

> **The primary shard coordinates mutations for its shard**.

---

34. Replication and ordering

Suppose:

```
update A
update B
```

are generated rapidly.

Network delivery could become:

```
replica receives B
replica receives A
```

That creates an ordering problem.

Elasticsearch uses **sequence numbers** and **primary terms**.

Each operation receives a sequence number from the primary.

```
A → seq 100
B → seq 101
```

The replica can reject/stage operations that violate the expected ordering rather than allowing an older operation to overwrite a newer one.

Elastic explicitly documents sequence numbers as the mechanism ensuring newer operations cannot be overwritten by older operations. (Elastic)

---

35. Optimistic concurrency control

Suppose:

```
Client A GET document
version = seq 100, primary term 4
```

```
Client B updates document
seq = 101
```

Client A then attempts:

```
update using seq=100, primary_term=4
```

Elasticsearch detects:

```
expected seq=100
actual latest seq=101
```

and rejects the update.

This is **optimistic concurrency control**.

The important API fields are:

```
if_seq_no
if_primary_term
```

Elastic documents this mechanism directly. (Elastic)

This is analogous to:

```
compare-and-swap
```

in concurrency control.

---

36. Search architecture

This is the second most important Elasticsearch algorithm to understand.

Suppose:

```
index = 20 shards
```


and the user searches:


```
"payment failed"
```

The query may involve many shards.

The coordinating node performs a:

> **scatter-gather operation**





Elastic explicitly describes search as a two-phase process:

```
scatter → gather
```

where the coordinating node sends work to data nodes and reduces their results. (Elastic)

---

37. Search query phase

Conceptually:

```
Coordinator
     ↓
all relevant shards
     ↓
each shard:
    execute query
    find matching documents
    calculate scores
    keep top candidates
     ↓
Coordinator
```

The shard doesn't necessarily return every matching document.

It can return:

```
top K
```

candidate documents.

This greatly reduces network traffic.

---

38. Fetch phase

After identifying the global top hits:

```
Coordinator
      ↓
fetch requested _source fields
      ↓
documents
```

Conceptually:

```
Query phase
    ↓
top document IDs
    ↓
Fetch phase
    ↓
actual documents
```

This separation is fundamental to distributed search performance.

---

39. Adaptive replica selection

Suppose a shard has:

```
primary → N1
replica → N2
```

A search doesn't blindly choose one.

Elasticsearch can use **adaptive replica selection**, considering:

- previous response time
- previous search execution time
- search queue size

to choose an appropriate copy. (Elastic)

This is a good example of:

> **load-aware request routing**

rather than simple round-robin.

---

40. Query fan-out

Here's a major scalability problem.

Suppose:

```
1000 shards
```

and a search touches:

```
1000 shards
```

Every user request becomes:

```
1 → 1000
```

and then:

```
1000 → 1
```

That produces enormous coordination overhead.

Therefore:

> **Shard count is also a query fan-out problem.**

This is one reason shard design is more important than simply asking:

> "How much data do I have?"

---

41. Time-series search optimization

For logs:

```
timestamp = 2026-09-03
```

you shouldn't necessarily query:

```
10 years of indices
```

if the user only asks for:

```
last 15 minutes
```

Data streams and lifecycle management make temporal partitioning natural.

---

42. Aggregations

Elasticsearch is not just a search engine.

It is also a distributed analytics engine.

Example:

```
How many 500 errors per service?
```

Conceptually:

```
Shard 1:
payments → 100
orders   → 50

Shard 2:
payments → 80
orders   → 60

Shard 3:
payments → 120
orders   → 40
```

Coordinator reduces:

```
payments → 300
orders   → 150
```

This is another distributed map/reduce-like pattern.

---

43. Global ordinals

For keyword fields, Elasticsearch can use **ordinals**.

Conceptually:

```
payments → 0
orders   → 1
users    → 2
```

Instead of repeatedly processing strings:

```
"payments"
"payments"
"orders"
...
```

the aggregation can work with compact integer ordinals.

Elastic documents global ordinals as a structure built across segment-local ordinals to accelerate bucket aggregations such as `terms`. (Elastic)

---

44. Cardinality aggregation

Suppose you ask:

> How many unique users?

Naively:

```
hash set of all users
```

can require huge memory.

Elasticsearch's cardinality aggregation uses **HyperLogLog++**.

This gives:

```
approximate count
```

with bounded memory characteristics.

Elastic explicitly documents HyperLogLog++ for cardinality estimation and explains the memory/accuracy trade-off. (Elastic)

This is a fantastic MAANG+ algorithm to know.

---

45. Caching

There are several layers of caching.

OS filesystem cache

Elasticsearch heavily relies on the operating system filesystem cache for index files. (Elastic)

Think:

```
Lucene files
      ↓
OS page cache
      ↓
fast reads
```

Query cache

Filter-context query results can be cached per segment.

The current documentation describes an LRU-based node query cache and notes that segment merges can invalidate cached results. (Elastic)

Request/shard-level caching

Some repeated aggregation/search requests can benefit from shard request caching.

The important interview concept is:

```
CPU cache
JVM cache
query cache
filesystem cache
```

and the fact that:

> **Cache invalidation is closely coupled to Lucene segment lifecycle.**

---

46. Full-text relevance

Elasticsearch's default text similarity is:

> **BM25 — Okapi Best Matching 25**

Elastic explicitly identifies BM25 as the default similarity in current Elasticsearch. (Elastic)

The intuition:

```
more occurrences of query term
        → higher score

rare term
        → higher importance

very long document
        → normalized downward
```

BM25 balances:

- term frequency
- inverse document frequency
- document length

You should understand the basic formula, not memorize every implementation detail.

---

47. BM25 conceptual formula

A simplified form is:

$$
score(D,Q)

\sum_{t\in Q}
IDF(t)
\frac{f(t,D)(k_1+1)}
{f(t,D)+k_1(1-b+b\frac{|D|}{avgdl})}
$$

Where:

```
f(t,D)     = frequency of term t in document D
|D|        = document length
avgdl      = average document length
k1         = TF saturation parameter
b          = length normalization
```

Current Elastic documentation lists defaults of approximately:

```
k1 = 1.2
b  = 0.75
```

for the built-in BM25 similarity. (Elastic)

---

48. Vector search

This is increasingly important for modern MAANG+ interviews.

Elasticsearch is now also a vector database.

```
document
   ↓
embedding
   ↓
dense_vector
   ↓
vector index
```

Then:

```
query
 ↓
embedding
 ↓
nearest-neighbor search
 ↓
semantic results
```

Elastic supports approximate kNN using structures including **HNSW**, with current documentation also describing quantized vector indexing approaches such as BBQ variants. (Elastic)

---

49. HNSW

HNSW:


> Hierarchical Navigable Small World graph

Instead of comparing a query against every vector:

```
query
  ↓
N vectors
  ↓
calculate similarity N times
```

HNSW constructs a graph:

```
          A———B
         /     \
```



and navigates the graph toward nearby vectors.

The trade-off is:

```
exact search
     ↑
accuracy
     ↓
latency

approximate search
     ↑
speed
     ↓
potential recall
```

Elastic explicitly describes approximate kNN as an accuracy/performance trade-off and uses HNSW for efficient approximate search. (Elastic)

---


50. Hybrid search


Modern applications often combine:

```
BM25
+
vector similarity
+
filters
```

For example:

```
query:
"best laptop for software development"
```





Elastic explicitly supports combining kNN with normal queries, filters and aggregations. (Elastic)

For your MAANG+ preparation, I would therefore learn:

```
BM25
HNSW
hybrid retrieval
reranking
```

rather than treating Elasticsearch as only a log-search product.

---

51. Pagination

Do **not** use:

```
from = 900000
size = 100
```

for deep pagination.

This creates increasing work.

For deep pagination, Elasticsearch recommends:

```
search_after
```

and, where a consistent view across multiple requests is required:

```
Point In Time (PIT)
+
search_after
```

The current docs explicitly recommend this approach for deep pagination and no longer recommend scroll for ordinary deep-pagination use cases. (Elastic)

---

52. Why PIT matters

Without PIT:

```
Request 1
    ↓
refresh
    ↓
Request 2
```

the underlying visible index state can change.

Therefore:

```
page 1 ≠ same snapshot as page 2
```

PIT creates a stable logical view.

```
PIT
 │
 ├── page 1
 ├── page 2
 ├── page 3
 └── page 4
```

This is analogous to snapshot/cursor semantics in databases.

---

53. Lifecycle management

Logs are fundamentally different from product/catalog data.

Logs:

```
write-heavy
append-only
high volume
time-oriented
usually decreasing value with age
```

Therefore:

```
hot → warm → cold → frozen/archive → delete
```

is a natural architecture.

---

54. ILM

Index Lifecycle Management can automate:

```
rollover
allocation
read-only transition
shrink
force merge
downsampling
searchable snapshots
delete
```

Elastic's current ILM documentation describes these lifecycle actions explicitly. (Elastic)

---

55. Rollover

Instead of:

```
logs-2026
    ↓
10 TB
    ↓
20 TB
    ↓
50 TB
```

you use:

```
logs-000001
logs-000002
logs-000003
...
```

and roll over based on:

```
size
age
document count
```

Elastic recommends size/document-count/age-driven rollover over arbitrary time-based rotation because it avoids producing many unnecessarily small indices. (Elastic)

---

56. Downsampling

Suppose metrics arrive every:

```
10 seconds
```

Historical data might not need that resolution.

You can transform:

```
10-sec samples
      ↓
1-minute
```

```
      ↓
10-minute
      ↓
1-hour
```

For time-series data, Elasticsearch can store statistical summaries such as:

```
min
max
sum
value_count
```

for larger intervals. (Elastic)

This is essentially a **data-resolution compression strategy**.

---

57. Searchable snapshots

For old data:

```
expensive SSD
```

may not be economical.

You can use searchable snapshots and lower-cost storage.

The architectural principle is:

> **Separate data temperature from data availability.**


Old data can remain searchable without occupying expensive hot storage.

---

58. Modern data lifecycle architecture

A sophisticated production architecture can therefore be:

```
                NEW
                 |
```



This is one of the strongest patterns to understand for large-scale log systems.

---

59. Kibana architecture

Kibana sits above Elasticsearch.

```
Browser
   |
   ▼
Kibana
   |
   ▼
Elasticsearch
```

Kibana provides:

- Discover
- dashboards
- Lens
- visualizations
- alerts
- cases
- observability
- security
- management
- console/API access

Elastic describes Kibana as the UI and management layer for Elastic solutions and Elasticsearch data. (Elastic)

---

60. Kibana is not the database

This is another common interview misconception.

Kibana:

```
presentation/control
```

Elasticsearch:

```
data/search/analytics
```

Therefore:

```
Kibana failure
     ≠
Elasticsearch data loss
```

You can access Elasticsearch APIs without Kibana.

---


61. Kibana task manager

Kibana has distributed background work such as:

```
alerts
actions
reporting
```

Task Manager stores task state in Elasticsearch and allows multiple Kibana instances to distribute work. Elastic explicitly describes persistence, scaling and load balancing properties of Task Manager. (Elastic)

Conceptually:



Again:

> distributed work queue + persistent state + worker fleet.

---

62. Network protocols

For an interview, think in terms of three communication boundaries.

Client ⟶ Elasticsearch

Typically:

```
HTTPS
REST API
JSON / NDJSON
```

Examples:

```
GET /index/_search
POST /_bulk
PUT /index/_doc/id
```

Bulk ingestion uses **NDJSON**. (Elastic)

Agent → Logstash

For Beats/Elastic Agent integrations, acknowledgement-capable protocols are used in documented architectures.

Node → Node


Elasticsearch uses its internal transport layer.

For secure clusters, current Elastic documentation requires/uses **mutual TLS for inter-node transport communication**. (Elastic)

---

63. Security architecture

At minimum:



```
    ▼
  Elasticsearch
```

and internally:

```
  ES node ⟷ ES node
          mTLS
```

Elastic explicitly distinguishes:

```
  HTTP TLS
```

for client communication from:

```
  transport mTLS
```

for node-to-node communication. (Elastic)

---

64. Authentication and authorization

You should understand:

```
  authentication
        ↓
  who are you?
        ↓
  authorization
        ↓
  what can you access?
```

Modern Elastic supports API keys, roles and privileges.

For example:

```
  application A
      ↓
  API key
      ↓
```

```
read:
logs-prod-*
```


rather than giving it administrator privileges.

Elastic recommends appropriately scoped and preferably time-limited API keys for automated access. (Elastic)

---

65. Production security boundary

A robust deployment looks like:




Never expose the Elasticsearch transport layer directly to the public Internet.

---

66. High-availability architecture

For serious production workloads:



Distribute replicas across:

```
availability zones
racks
failure domains
```

using shard allocation awareness.

---

67. Failure scenario: data node dies

Suppose:

```
N1 contains P0
N2 contains R0
```

N1 dies.

The cluster detects:

```
P0 unavailable
```

Replica R0 can become the active primary.

Conceptually:

```
before:

P0(N1) → R0(N2)

after:

N1 ❌

R0(N2)
  ↓
P0
```

Then Elasticsearch can create another replica elsewhere.

This is:

> **automatic failover + replica promotion + rebalancing**

---

68. Failure scenario: master dies

Suppose:

```
M1 = current master
M2
M3
```

M1 dies.

The remaining master-eligible nodes:

```
M2 + M3
```

can elect another master through the cluster's voting mechanism.

The important distinction:

> **Master failure does not inherently mean data failure.**

Data is held on data nodes.

---

69. Failure scenario: Elasticsearch unavailable

The ingestion layer should absorb the failure:

```
Agent
  ↓
Logstash PQ / Kafka
  ↓
Elasticsearch unavailable
  ↓
buffer
```

When Elasticsearch recovers:

```
buffer
  ↓
replay
  ↓
Elasticsearch
```

This is why the ingestion architecture is part of the reliability design rather than merely a preprocessing detail.

---

70. Failure scenario: Logstash dies

With memory queue:

```
in-flight events → potentially lost
```

With persistent queue:

```
disk
 ↓
restart
 ↓
resume processing
```

Elastic explicitly documents this recovery behavior. (Elastic)

With Kafka:

```
Kafka
 ↓
new Logstash instance
 ↓
resume consumer position
```

and potentially replay historical data.

---

71. Failure scenario: Elasticsearch cluster overloaded

Symptoms:

```
CPU ↑
disk I/O ↑
heap ↑
GC ↑
search queue ↑
write queue ↑
429 responses
latency ↑
```

The correct response isn't:

> “Add more Elasticsearch nodes.”

You need to identify the bottleneck.

Possible bottlenecks:

```
CPU
disk
heap
network
shard count
hot shard
query fan-out
aggregation cardinality
ingestion rate
segment merging
```

---

72. 429 and backoff

When Elasticsearch can't accept more work, clients can see:

```
HTTP 429
```

Elastic recommends backing off and using randomized exponential backoff when indexing is rejected. (Elastic)

Classic distributed-systems pattern:

```
request fails
     ↓
wait
     ↓
retry
     ↓
randomized delay
     ↓
retry
```

Without jitter:

```
1000 clients retry simultaneously
        ↓
thundering herd
        ↓
cluster collapses again
```

---

73. Bulk indexing

Never assume:

```
1 HTTP request = 1 document
```

at high throughput.

Use:

```
Bulk API
```

Example:

```
POST /_bulk

index metadata
document
index metadata
document
index metadata
document
...
```

Bulk reduces request overhead and can substantially increase indexing throughput. (Elastic)

---


74. Bulk sizing

There is no universal:

```
"best bulk size"
```

Elastic recommends benchmarking progressively larger batches and warns against excessively large requests because concurrency can create memory pressure. (Elastic)

Therefore:



The sweet spot depends on:

- document size
- shard count
- CPU
- disk
- network
- concurrency
- mappings
- ingest processors

---

75. Indexing throughput optimization

Important techniques:

```
bulk requests
parallel producers
appropriate shard count
appropriate refresh interval
efficient mappings
avoid hotspots
fast storage
```

```
filesystem cache
backpressure
```

Elastic's current tuning guidance explicitly discusses bulk requests, worker concurrency, refresh intervals, indexing buffers, shard layout and hotspot avoidance. (Elastic)

---

76. Don't disable replicas casually

During a massive initial load you might temporarily use:

```
replicas = 0
```

to increase throughput.

But then:

```
node failure → data loss
```

unless the source data can be replayed.

Elastic documents this trade-off explicitly. (Elastic)

This is a classic:

> **performance vs durability**

trade-off.

---

77. Hot shards

One of the most important operational problems.

Suppose:

```
shard 0 → 90% of traffic
shard 1 → 2%
shard 2 → 2%
...
```

Adding nodes won't necessarily help.

Why?

Because the bottleneck is:

```
one shard
```

rather than total cluster capacity.

Possible causes:

```
bad custom routing
sequential IDs
tenant skew
time hotspot
poor partitioning
```

---

78. Custom routing trade-off

Routing by:

```
tenant_id
```

can make tenant queries very fast.

But:

```
tenant A = 80% traffic
```

can create a hotspot.

Possible solution:

```
tenant_id + hash(document_id)
```

or routing partitions.

This is a classic **locality vs load-balancing** trade-off.

---

79. Data modeling principle

For Elasticsearch:

> Model data around **query patterns**, not around normalized relational schemas.

Instead of:

```
users
orders
order_items
payments
```

you might create a search-oriented document:

```
{
  "order_id": "123",
  "customer": {...},
  "items": [...],
  "payment": {...},
  "status": "PAID"
}
```

if your dominant query is:

```
find order + customer + items
```

This avoids expensive distributed joins.

---

80. Denormalization trade-off

Advantages

```
fast reads
simple queries
```

```
fewer joins
distributed-friendly
```

Disadvantages

```
duplicate data
update amplification
larger storage
consistency complexity
```


This is the same trade-off you encounter in:


```
DynamoDB
Cassandra
MongoDB
distributed caches
```

---

81. Observability use case

The canonical architecture is:





This is where ECS becomes extremely important.

---

82. Distributed tracing

For a request:

```
User
 ↓
API Gateway
 ↓
Order Service
 ↓
Payment Service
 ↓
Database
```

you want:

```
trace_id
span_id
parent_span_id
```

throughout the request.

Then Elasticsearch becomes the searchable analytical substrate:

```
trace_id = abc123
```

→ retrieve all related events.

This enables:

```
logs ↔ traces ↔ metrics
```

correlation.


---


83. A powerful interview architecture

If asked:

> Design a centralized logging platform for 100,000 servers.

I would propose:





But I would **not automatically introduce Kafka**.

I would ask:

```
Do we need replay?
Do we have multiple downstream consumers?
Do we need durable distributed buffering?
Do we already operate Kafka?
```

If not:

```
Agent → Logstash PQ → Elasticsearch
```

may be substantially simpler.

---

84. Scale calculation

Suppose:

```
100,000 servers
10 KB/sec/server
```

Then:

$$

100,000 \times 10KB/s

1GB/s
$$

Raw ingestion:

```
≈ 1 GB/s
≈ 86.4 TB/day
```

Before:

```
replication
metadata
index overhead
compression
retention
```

At:

```
replication factor = 2
```

you are already around:

```
172.8 TB/day
```

of logical replicated storage before accounting for indexing/storage overhead.

This immediately tells you:

> **Lifecycle management is not optional**.

---

85. Retention calculation

Suppose:

```
86.4 TB/day raw
30 days
```

Then:

$$
86.4 \times 30 = 2592TB
$$

≈

```
2.6 PB
```

raw.

With replication and indexing overhead, your physical storage requirement can be substantially higher.

Therefore:

```
hot storage for everything forever
```

is usually a bad architecture.

You need:

```
hot → warm → cold → archive/delete
```

---

86. Availability vs consistency

Elasticsearch is not a relational database with:

```
SERIALIZABLE
```

transactions across arbitrary documents.

You should think in terms of:

```
per-shard primary ordering
replication
near-real-time visibility
optimistic concurrency
distributed search
```

rather than:

```
global ACID transaction
```

---

87. Read-after-write considerations

A common application requirement:

```
write document
↓
immediately search document
```

Because of refresh semantics, this is not automatically equivalent to:

```
write
↓
search
↓
guaranteed visible
```

If strict visibility is required, you can use appropriate refresh semantics, but that has a throughput cost.

Therefore:

> **freshness is a tunable consistency/performance dimension.**

---

88. Exactly-once is not your default assumption

For logging systems:

```
at-least-once
+
idempotency
+
deduplication where required
```

is often a better design than attempting global exactly-once processing.

If event identity matters:

```
event.id
```

can be used as an idempotency key.

For example:

```
event.id = UUID
```

and indexing semantics can be designed around that identity.

---

89. Backpressure architecture

The full pipeline should behave like:

```
Producer
   |
   ▼
Agent
   |
   ▼
Buffer
   |
   ▼
Processor
   |
   ▼
Elasticsearch
```

If:

```
ES capacity < incoming rate
```

then:

```
ES slows
  ↓
processor slows
  ↓
buffer fills
  ↓
agent slows
  ↓
producer is eventually throttled
```

This is **flow control**.

The alternative is:

```
ES slows
  ↓
memory grows
  ↓
OOM
  ↓
events lost
```

---

90. The most important bottlenecks

When debugging an Elasticsearch system, classify the bottleneck:

CPU-bound

Typical causes:

```
complex queries
script execution
heavy ingest processors
high aggregation load
vector search
```

Memory-bound

Typical causes:

- large aggregations
- high-cardinality fields
- fielddata
- global ordinals
- too many shards
- heap-heavy workloads

Disk I/O-bound

Typical causes:

- indexing
- segment merging
- random reads
- slow storage
- recovery

Network-bound

Typical causes:

- large search responses
- cross-node scatter/gather
- replication
- large bulk requests

Coordination-bound

Typical causes:

- too many shards
- large fan-out
- cluster-state pressure
- large aggregations

---

91. The Elasticsearch performance hierarchy

A useful mental model:

```
Application
    ↓
Query design
    ↓
Index/mapping design
    ↓
Shard design
    ↓
Node architecture
    ↓
Storage architecture
    ↓
Cluster architecture
```

Don't immediately solve:

```
slow query
```

with:

```
more nodes
```

First ask:

```
Why is the query slow?
```

---

92. The 80/20 of Elasticsearch performance

For interviews, remember these:

Search

```
avoid wildcard-heavy queries
avoid huge result sets
avoid deep from/size pagination
use search_after/PIT
limit shard fan-out
use filters appropriately
```

Indexing

```
bulk
parallelize
tune refresh
avoid hotspots
appropriate shard count
```

Aggregations

```
avoid unnecessary high-cardinality aggregations
use keyword rather than text for buckets
understand global ordinals
```

Storage

```
use appropriate data tiers
roll over
downsample
snapshot
delete
```

---

93. Deep pagination pattern

Bad:

```
page 1 → from=0
page 2 → from=100
```

```
page 10000 → from=999900
```

Better:

```
page 1
  ↓
last sort values
  ↓
search_after
  ↓
page 2
```

For stable pagination:

```
PIT
+
search_after
```

Elastic explicitly recommends this pattern. (Elastic)

---

94. Query design: filter vs query

A fundamental search-engine distinction:

Query context

Answers:

> How relevant is this document?

Example:

```
match
```

Filter context

Answers:

> Does this document satisfy the condition?

Example:

```
status = 500
service = payments
```


Filters are generally better suited to exact constraints and can participate in caching.

This distinction is fundamental to efficient Elasticsearch query design.

---

95. Search architecture summary

The whole flow is:




Memorize this.

---

96. Write architecture summary

Similarly:





Again, this is worth memorizing.


---

97. Complete production architecture

Putting everything together:




Applications
logs / metrics / traces
Elastic Agent
collect
batch
enrich
retry
Direct ES
Logstash
filter
enrich
route
PQ
optional
Kafka
durable
replay
fan-out
Elasticsearch
Coordinating


Master
Ingest
Hot Data
Warm Data
Cold Data
data streams
Hot data
Warm data
Cold data
searchable snapshots
archive
delete
SEARCH / ANALYTICS
Elasticsearch
BM25
Aggregations
kNN
Kibana
Dashboards
Alerts
Discover

98. The patterns you should know for MAANG+

I would explicitly study these patterns.

Distributed systems

Pattern	Where it appears
Partitioning	shards
Replication	primary/replica
Leader election	master election
Quorum	voting configuration
Scatter-gather	distributed search
Map/reduce	aggregations
Consistent routing	shard hashing
Backpressure	Agent/Logstash
Retry + exponential backoff	ingestion
Load balancing	coordinating/search routing
Failure detection	cluster membership
Failover	replica promotion
Eventual consistency	search visibility
Optimistic concurrency	seq_no + primary_term
Snapshotting	PIT / snapshots
Write-ahead logging	translog concept
Immutable segments	Lucene
Compaction	segment merging
Tiered storage	hot/warm/cold

Pattern	Where it appears
CQRS-like separation	ingestion vs search workloads
Denormalization	document modeling

---

99. Algorithms/data structures you should know

For your MAANG+ preparation, I'd put these in your **must-know** list:

Essential

1. Hashing
2. Consistent/distributed routing concepts
3. Inverted index
4. Posting lists
5. Tokenization/analyzers
6. BM25
7. Lucene segments
8. Segment merging
9. Doc values
10. BKD trees
11. Scatter-gather
12. Top-K selection
13. Distributed aggregation/reduction
14. Global ordinals
15. HyperLogLog++
16. LRU caching
17. Exponential backoff + jitter
18. Quorum
19. Leader election
20. Optimistic concurrency control

Increasingly important

21. HNSW
22. Approximate nearest-neighbor search

23. Vector quantization
24. Hybrid retrieval
25. Reranking

---

100. Protocols you should know

For interviews:

```
HTTP/HTTPS
REST
JSON
NDJSON
TCP
TLS
mTLS
HTTP connection pooling
compression
acknowledgement protocols
```

And conceptually:

```
request/response
streaming
batching
retry
timeout
backpressure
idempotency
```

---

101. Failure modes you should be able to explain

An interviewer could ask:

“What happens if Elasticsearch node dies?”

You should explain:

```
failure detection
→ replica promotion
→ shard recovery
→ rebalancing
```

“What happens if Elasticsearch is overloaded?”

```
queue growth
→ backpressure
→ 429
→ client retry/backoff
```

“What happens if Logstash dies?”

```
PQ recovery
```

or:

```
Kafka replay
```

“What happens if master dies?”

```
quorum
→ new election
→ cluster-state continuity
```

“What if one shard is hot?”

```
identify skew
→ fix routing/index design
→ repartition/reindex if necessary
```

---

102. The most important trade-offs

Memorize these pairs.

Throughput vs freshness

```
longer refresh interval
    → higher ingest throughput
    → less immediate search visibility
```

Replication vs write throughput

```
more replicas
    → higher durability/read capacity
    → more write/storage overhead
```

Shards vs coordination

```
more shards
    → more parallelism
    → more coordination/metadata overhead
```

Routing locality vs distribution

```
custom routing
    → fewer shards searched
    → possible hotspots
```

Exact cardinality vs memory

```
exact unique count
    → potentially huge memory
approximate HLL++
    → bounded memory + small error
```

Hot storage vs cost

```
SSD everywhere
    → fast
    → expensive

tiered storage
    → cheaper
    → slower historical queries
```

Logstash vs simplicity

```
Logstash
    → flexibility
    → operational complexity

Agent → ES
    → simplicity
    → less transformation flexibility
```

Kafka vs Logstash PQ

```
Kafka
    → distributed durable replayable buffer
    → more infrastructure

PQ
    → simple local buffering
    → not distributed
```

---

103. The architecture decision tree I recommend

When designing an Elastic system, reason in this order:

1. What data?
   - logs
   - metrics
   - traces
   - business documents
   - vectors
2. What access patterns?
   - full-text
   - exact filter
   - aggregation
   - time-range
   - semantic
   - hybrid
3. What ingestion rate?
4. What retention?
5. What freshness SLA?
6. What durability SLA?
7. What query latency SLA?
8. What failure model?
9. What scale?
10. Then choose:
    - mappings
    - shards
    - replicas
    - nodes
    - ingestion architecture
    - lifecycle
    - caching
    - storage tiers

This is much better than starting with:

> “Let's deploy an ELK cluster.”

---

104. What I would expect in a MAANG+ interview

If you're asked:

> **“Design a distributed logging system using Elasticsearch.”**

Your answer should proceed roughly like this:

Step 1 — Requirements

```
100K hosts
100 GB/s? 1 GB/s?
retention = 30/90/365 days
P99 search latency
freshness SLA
availability SLA
multi-tenancy
security
```

Step 2 — Ingestion

```
Agent
→ Logstash
→ optional Kafka
```

Step 3 — Durability

```
PQ
Kafka
at-least-once
retries
idempotency
```

Step 4 — Schema

ECS

Step 5 — Storage

data streams
→ rollover
→ ILM/DLM
→ hot/warm/cold

Step 6 — Elasticsearch

3+ master eligible
data nodes
replicas
shards
AZ awareness

Step 7 — Search

scatter-gather
query phase
fetch phase
adaptive replica selection

Step 8 — Relevance

BM25
filters
aggregations
optional vector search

Step 9 — Reliability

```
node failure
master failure
network partition
backpressure
retries
recovery
```

Step 10 — Performance

```
bulk
refresh tuning
shard sizing
hotspot detection
cache
filesystem cache
```

Step 11 — Security

```
TLS
mTLS
RBAC
API keys
tenant isolation
```

Step 12 — Cost


```
retention
downsampling
tiered storage
snapshots
```

That is the level of structure I would use in a Staff+/Principal-level system-design interview.


---

105. One-page mental model

If you remember nothing else, remember this:



And operationally:



---

106. Current Elastic concepts worth adding to your curriculum

Given your **Staff Software Engineer / Software Architect + MAANG+ preparation**, I would not stop at traditional ELK.

Your Elasticsearch mastery track should be:

Tier 1 — mandatory

```
Elasticsearch cluster architecture
nodes
shards
replicas
routing
Lucene
inverted indexes
mappings
analyzers
BM25
doc values
refresh
translog
bulk indexing
distributed search
```

query/fetch
aggregations
caching
ILM
data streams

Tier 2 — distributed-systems depth

master election
quorum
cluster state
shard allocation
recovery
replication
sequence numbers
primary terms
OCC
failure detection
backpressure
at-least-once delivery
idempotency
hot shards

Tier 3 — production architecture

Elastic Agent
Fleet
Logstash
PQ
Kafka integration
ECS
observability architecture
security
TLS/mTLS
RBAC/API keys
multi-AZ deployment
capacity planning
cost optimization

Tier 4 — modern search/AI

```
dense_vector
kNN
HNSW
vector quantization
semantic search
hybrid retrieval
reranking
RAG
```

Elastic's current documentation explicitly positions Elasticsearch as a vector database and search/RAG engine in addition to traditional full-text search. (Elastic)

---

107. The key conceptual connection to your broader system-design preparation

The most valuable thing about learning Elasticsearch isn't memorizing Elasticsearch APIs.

It is understanding **why these mechanisms exist**.

You can map them directly to general distributed-systems concepts:

Elasticsearch	General CS/System Design
Shard	Partition
Replica	Replication
Primary shard	Partition leader
Master	Cluster coordinator
Voting configuration	Quorum
Cluster state	Distributed metadata
Routing hash	Partitioning
Scatter/gather	Distributed query
Query/fetch	Two-phase distributed retrieval
Segment	Immutable data structure

Elasticsearch	General CS/System Design
Merge	Compaction
Translog	Write-ahead/recovery log concept
Sequence number	Operation ordering
Primary term	Leadership epoch
OCC	Compare-and-swap style concurrency
Refresh	Visibility boundary
Doc values	Columnar access
Inverted index	Secondary/search index
BM25	Relevance scoring
HLL++	Probabilistic algorithm
HNSW	ANN graph
PQ	Local durable queue
Kafka	Distributed durable log
ILM/DLM	Data lifecycle management
Data stream	Logical abstraction over partitions
ECS	Canonical schema
Kibana Task Manager	Distributed work queue

That is the level at which I recommend studying Elasticsearch for your MAANG+ interviews.

The official Elastic architecture documentation is especially useful for going deeper into distributed architecture, shards, cluster formation, node roles, lifecycle and Kibana task management. (Elastic)

Elastic Distributed Architecture Documentation

Elastic Ingest Architectures

Elasticsearch Reference

Final interview checklist

Before considering yourself **MAANG+ Elasticsearch-ready**, you should be able to whiteboard these **without documentation**:

```
[ ] Agent → Logstash → Elasticsearch
[ ] Agent → Kafka → Logstash → Elasticsearch
[ ] Logstash persistent queues
[ ] At-least-once delivery
[ ] Backpressure
[ ] Elasticsearch cluster
[ ] Master election/quorum
[ ] Cluster state
[ ] Primary/replica shards
[ ] Hash-based shard routing
[ ] Custom routing + hotspot problem
[ ] Write path
[ ] Translog
[ ] Refresh
[ ] Lucene segments
[ ] Segment merging
[ ] Inverted index
[ ] Doc values
[ ] BKD trees
[ ] Search scatter/gather
[ ] Query/fetch phases
[ ] Adaptive replica selection
[ ] BM25
[ ] Aggregations
[ ] Global ordinals
[ ] HyperLogLog++
[ ] Query/request/filesystem caching
[ ] search_after
[ ] PIT
[ ] Data streams
[ ] Rollover
[ ] ILM/DLM
[ ] Hot/warm/cold architecture
[ ] Downsampling
[ ] Searchable snapshots
[ ] Failure recovery
[ ] Multi-AZ shard allocation
[ ] Bulk indexing
```

```
[ ] 429/backoff/jitter
[ ] ECS
[ ] TLS/mTLS
[ ] RBAC/API keys
[ ] HNSW
[ ] Vector/hybrid search
```

If you can **explain the rationale and trade-offs behind each of these**, rather than merely define them, you'll have a strong Elasticsearch foundation for **Staff/Principal-level system design**, not just an "ELK administration" skill set.