

Erste Übung

```
2^8
2 * pi * 2
log10(1000)
round(pi, 4)
sqrt(25 + 3^2) / log2(8)
```

Zweite Übung

```
itsRaining <- TRUE
haveUmbrella <- FALSE
```

```
# 1
itsRaining & haveUmbrella
```

```
# 2
itsRaining | haveUmbrella
```

```
# 3
haveUmbrella | !itsRaining
```

Dritte Übung

```
# 1
help(floor)
```

```
# alternativ
?floor
```

```
# 2
round(pi^2, 4)
```

```
# 3
log(1000000000, base = 1000)
```

```
# Vierte Übung
myFunc <- function(x = 0, y = 0) {
  x + y
}
```

Beispiel globale Variablen

```
x <- 1
```

```
f <- function() {
  x <- 99
  print(x)
}
```

```
f()
print(x)
```

```
f1 <- function() {
  x <- 100
  print(x)
}
f1()
```

```
print(x)
```

```
x <- c(1.7, 3.8, 4.2, 5.7)
```

```
x[2]
x[1]
x[2:3]
x[c(4,4,1)]
```

```
x[-c(1,2)]
```

```
# Aufgabe Vektoren
```

```
x <- c(2, 4, -1, 7, 3, 0)
```

```
y <- c(1, -2, 5, 2, 1, 4)
```

```
# 1
```

```
x[x > 2]
```

```
# 2
```

```
which(x < 0)
```

```
# 3
```

```
x + y
```

```
# 4
```

```
x %*% y
```

```
# 5
```

```
c(x, y)
```

```
# 6
```

```
mean(x[x > 0])
```