


OPEN STUDIO PROJECT

TECHNICAL ENVIRONMENTAL SYSTEM

Group

TAFAZOLI, NASTARAN	10662943
JAFARI, FATEMEH	10663637
JABBARI BASIR, MEHRDAD	10695646
ABEDINI ARABANI,PEDRAM	10696406


Project information





Geometry:

Building type: office Number of floors: 1


Total Building Area: 75 m2 (15*5)










WEATHER DATA








Piacenza, Italy




	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Average Outdoor Air Dry Bulb (F)						66.8 F 19.3 C						33.7 F 0.9 C
Cooling Load (MBtu)	0.0	0.0	0.0	0.03	0.33	1.1	3.22	1.93	0.7	0.02	0.0	0.0
Heating Load (MBtu)	12.22	9.22	7.16	3.55	0.85	0.21	0.04	0.1	0.56	2.22	6.26	12.95

Oslo, Norway





	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Average Outdoor Air Dry Bulb (F)						58.5 F 14.7 C						29.1 F -1.6 C
Cooling Load (MBtu)	0.0	0.0	0.0	0.01	0.04	0.21	0.53	0.18	0.0	0.0	0.0	0.0
Heating Load (MBtu)	17.54	13.24	12.23	8.32	2.99	1.09	0.41	0.58	3.59	7.78	12.24	16.39

Isfahan, Iran




	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Average Outdoor Air Dry Bulb (F)						80.0 F 26.6 C						
Cooling Load (MBtu)	0.0	0.0	0.05	0.2	1.21	3.38	4.72	4.47	1.92	0.51	0.01	0.0
Heating Load (MBtu)	7.93	4.87	2.76	1.15	0.15	0.0	0.0	0.0	0.08	0.4	2.66	6.23







	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
PIACENZA 1												
Average Outdoor Air Dry Bulb (F)	34.8 F	37.9 F	43.3 F	50.6 F	60.5 F	66.8 F	73.8 F	70.6 F	63.8 F	56.4 F	47.2 F	33.7 F
	1.5 C	3.3 C	6.2 C	10.3 C	15.8 C	19.3 C	23.2 C	21.4 C	17.6 C	13.5 C	8.4 C	0.9 C
Cooling Load (MBtu)	0.0	0.0	0.0	0.03	0.33	1.1	3.22	1.93	0.7	0.02	0.0	0.0
Heating Load (MBtu)	12.22	9.22	7.16	3.55	0.85	0.21	0.04	0.1	0.56	2.22	6.26	12.95



	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
PIACENZA 2												
Average Outdoor Air Dry Bulb (F)	34.8 F	37.9 F	43.3 F	50.6 F	60.5 F	66.8 F	73.8 F	70.6 F	63.8 F	56.4 F	47.2 F	33.7 F
	1.5 C	3.3 C	6.2 C	10.3 C	15.8 C	19.3 C	23.2 C	21.4 C	17.6 C	13.5 C	8.4 C	0.9 C
Cooling Load (MBtu)	0.0	0.0	0.0	0.01	0.19	0.76	2.32	1.35	0.45	0.0	0.0	0.0
Heating Load (MBtu)	9.81	7.54	6.04	3.14	0.88	0.25	0.05	0.12	0.55	1.95	5.06	10.33



	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
PIACENZA 3												
Average Outdoor Air Dry Bulb (F)	34.8 F	37.9 F	43.3 F	50.6 F	60.5 F	66.8 F	73.8 F	70.6 F	63.8 F	56.4 F	47.2 F	33.7 F
	1.5 C	3.3 C	6.2 C	10.3 C	15.8 C	19.3 C	23.2 C	21.4 C	17.6 C	13.5 C	8.4 C	0.9 C
Cooling Load (MBtu)	0.0	0.0	0.0	0.01	0.23	0.91	2.76	1.63	0.53	0.0	0.0	0.0
Heating Load (MBtu)	11.31	8.57	6.74	3.34	0.78	0.19	0.03	0.08	0.48	2.07	5.8	11.9



Wall 2

C	0
=	≡
2	\ \ \
3	>

Construction	Net Area (ft^2)	Surface Count	R Value (ft^2*h*R/Btu)
ASHRAE 189.1-2009 ExtRoof IEAD ClimateZone 1	807	3	19.96
model ext wall	787	8	1.33

$$U = \frac{1}{R_{\text{total}}}$$
 U=0.75 Btu/ft^2*h*R U=4.25 w/m^2.k

 Construction
 Net Area (ft^2)
 Surface Count
 R Value (ft^2*h*R/Btu)

 ASHRAE 189.1-2009 ExtRoof IEAD ClimateZone 1
 807
 3
 19.96

 model ext wall 2
 787
 8
 7.75

$$U = \frac{1}{R_{\text{total}}}$$
 U=0.12 Btu/ft^2*h*R U=0.68 w/m^2.k

Construction	Net Area (ft^2)	Surface Count	R Value (ft^2*h*R/Btu)
ASHRAE 189.1-2009 ExtRoof IEAD ClimateZone 1	807	3	19.96
model ext wall 3	787	8	2.36

$$U = \frac{1}{R_{\text{total}}}$$
 U=2.38 Btu/ft^2*h*R U=2.38 w/m^2.k

CONCLUSION

As can be seen, the base wall is used in three cities, the building in Isfahan consumes the main energy for cooling but the Oslo which is located in the north of Europe and Piacenza consume the main energy for heating. The overall energy consumption between these three cities shows that Oslo uses main energy, after that is Piacenza and the last location where the building use least energy with the base wall characteristic is Isfahan.

Comparing the three walls in Piacenza show that the wall with insulation has a lowest U factor between the other walls which is shown less heat lost and also from the consumption chart it can be seen, the building with this characteristic use less energy.