INTRUSION DETECTION SYSTEM USING A NEURAL NETWORK

PHASE TWO PRESENTATION

BLAKE KNEDLER

AGENDA

- Action Items
- Project Vision and Plan Updates
- Formal Requirements Specification
- Architecture Design
- Test Plan
- Formal Technical Inspection Checklist
- Risks and Concerns
- Phase Three Plan
- Architecture Prototype Demonstration
- Questions and Comments

ACTION ITEMS

- Updated Vision Document for accuracy documentation
- Updated Project Plan for correct COCOMO chart
- Added risks for KDD99 Dataset

PROJECT VISION AND PLAN UPDATES

- Vision Document Updates
 - Updated to mention that I plan to achieve 85% accuracy.
 - Noted that all false negatives and false positives hurt that accuracy
- Project Plan Updates
 - Updated COCOMO chart show on the next slide


PROJECT VISION AND PLAN UPDATES

Cost Drivers	Ratings				Chosen		
Cost Drivers	Very Low	Low	Nominal	High	Very High	Extra High	Result
Product attributes							
Required software reliability	0.75	0.88	1	1.15	1.4		1.15
Size of application database		0.94	1	1.08	1.16		1
Complexity of the product	0.7	0.85	1	1.15	1.3	1.65	1.3
Hardware attributes							
Run-time performance constraints			1	1.11	1.3	1.66	1.3
Memory constraints			1	1.06	1.21	1.56	1
Volatility of the virtual machine environment		0.87	1	1.15	1.3		1
Required turnabout time		0.87	1	1.07	1.15		1.07
Personnel attributes							
Analyst capability	1.46	1.19	1	0.86	0.71		0.86
Applications experience	1.29	1.13	1	0.91	0.82		0.91
Software engineer capability	1.42	1.17	1	0.86	0.7		0.7
Virtual machine experience	1.21	1.1	1	0.9			1
Programming language experience	1.14	1.07	1	0.95			0.95
Project attributes							
Application of software engineering methods	1.24	1.1	1	0.91	0.82		1
Use of software tools	1.24	1.1	1	0.91	0.83		0.83
Required development schedule	0.82	0.96	1	1.04	1.1		1.04
TOTAL EAF	0.9342				TET V		177


FORMAL REQUIREMENTS SPECIFICATION

- Developed using USE
 - Four main classes:
 - Packet
 - PacketReader (Network Traffic Reader)
 - NeuralNetwork
 - Notifier (Recorder)
 - Operations for the PacketReader and NeuralNetwork include
 - readPacket
 - makeDecision


- Architecture is fairly simple from high level
- Diagram shows interactions
- Three main components
 - Network Traffic Reader
 - Neural Network
 - Input Layer
 - Hidden Layer
 - Output Layer
 - Recorder
- Three external nodes
 - Network Data
 - Notification Output
 - Log Output



- Package Design
- Four main packages:
 - Network Traffic Reader
 - Neural Network
 - Input Layer
 - Hidden Layer
 - Output Layer
 - Backpropogation Trainer
 - Recorder
- Three external nodes
 - Network Data
 - Notification Output
 - Log Output



- Class Design Diagram
 - Operations defined in following slides



Network Traffic Reader Class

Name:	send Current Packet Data
	This function will send the current packet data to
Purpose	the Neural Network.
Inputs:	None
Outputs:	currentPacketData string of data
Pre-Conditions:	The current packet data must be set.
Post-Conditions:	None

Name:	setCurrentPacketData
Purpose	This function will set the current packet data value.
Inputs:	currentPacketData string of data
Outputs:	None
	The current packet must be read off of the network
Pre-Conditions:	card.
Post-Conditions:	The current packet data will be set.

Name:	receivePacket
	This function will grab the newest packet off of the
Purpose	network card.
Inputs:	None
Outputs:	None
Pre-Conditions:	None
Post-Conditions:	The current packet will be set.

Name:	parsePacket
	This function will parse the data out of the current
Purpose	packet.
Inputs:	currentacket string of data
Outputs:	None
Pre-Conditions:	None
Post-Conditions:	The current packet data will be set.

Neural Network Class

Name:	setInputLayerSize
	This function will set the size for the number of the
Purpose	input layer nodes.
Inputs:	inputLayerSize integer
Outputs:	None
Pre-Conditions:	None
Post-Conditions:	The input layer size will exist.

Name:	setHiddenLayerSize
	This function will set the size for the number of the
Purpose	hidden layer nodes.
Inputs:	hiddenLayerSize integer
Outputs:	None
Pre-Conditions:	None
Post-Conditions:	The hidden layer size will exist.

Name:	setOutputLayerSize
	This function will set the size for the number of the
Purpose	output layer nodes.
Inputs:	outputLayerSize integer
Outputs:	None
Pre-Conditions:	None
Post-Conditions:	The output layer size will exist.

Name:	setSynapseWeights
	This function will set the synapse weights in the
Purpose	Neural Network.
Inputs:	synapseWeights matrix of integers
Outputs:	None
Pre-Conditions:	None
	The system will have weights and be considered
Post-Conditions:	trained.

Neural Network Class

Name:	getWeights
Purpose	This function will get the current synapse weights.
Inputs:	None
Outputs:	synapseWeights matrix of integers
Pre-Conditions:	The system must have weights currently.
Post-Conditions:	None

Name:	sigmoid
	This function will perform a sigmoid function on the
Purpose	data it is given.
Inputs:	data matrix of integers
Outputs:	data matrix of integers
Pre-Conditions:	None
Post-Conditions:	None

Name:	train
Purpose	This function will train the Neural Network.
	trainingData matrix of integers
	trainingAnswers matrix of integers
Inputs:	accuracy integer
Outputs:	data matrix of integers
	Training data must have been read into the Neural
Pre-Conditions:	Network.
Post-Conditions:	The Neural Network will be considered trained.

Name:	compute		
	This function will compute the decision for a signle		
Purpose	set of data.		
Inputs:	data matrix of integers		
Outputs:	answer integer		
Pre-Conditions:	The Neural Network must be trained.		
Post-Conditions:	None		

Name:	readTrainingDataFromFile		
	This function will read and parse all the training data		
Purpose	needed from the saved training file.		
Inputs:	None		
	trainingData matrix of integers		
Outputs:	trainingAnswers matrix of integers		
Pre-Conditions:	The training data file must exist.		
	The training data will be read into the Neural		
Post-Conditions:	Network.		

Recorder Class

Name:	initializeUI		
	This function will initialize the User Interface (UI)		
Purpose	portion of the system.		
Inputs:	None		
Outputs:	None		
Pre-Conditions:	None		
Post-Conditions:	The UI will be initialized and can be displayed.		

Name:	train		
	This function will tell the Neural Network class to		
Purpose	begin training using the saved training data.		
Inputs:	None		
Outputs:	None		
Pre-Conditions:	The UI is initialized.		
Post-Conditions:	The Neural Network will be trained.		

Name:	run		
Purpose	This function will tell the system to begin running.		
Inputs:	None		
Outputs:	None		
Pre-Conditions:	The Neural Network must be trained.		
Post-Conditions:	The system will be operating.		

Name:	notifyUser		
	The fuction will notify the user with descriptive		
Purpose	string indicating the data that was malicious.		
Inputs:	maliciousData A descriptive string of data		
Outputs:	None		
Pre-Conditions:	The UI is initialized.		
Post-Conditions:	A Notification will pop-up.		

Recorder Class


Name:	logData		
	The fuction will write log data to a log file with		
	descriptive string indicating the data that was		
Purpose	malicious.		
Inputs:	maliciousData A descriptive string of data		
Outputs:	None		
Pre-Conditions:	None		
Post-Conditions:	The log file will contain an additional item.		

Name:	loadWeights		
	The function will load the currently saved synapse		
Purpose	weights into the Neural Network.		
Inputs:	None		
Outputs:	None		
Pre-Conditions:	The UI is initialized and saved weights must exist.		
Post-Conditions:	The Neural Network will be trained.		


Name:	saveWeights		
Purpose	The function will save the current weights to a file.		
Inputs:	None		
Outputs:	None		
Pre-Conditions:	The UI is initialized.		
Post-Conditions:	There will be a save weights file.		

Name:	stop		
Purpose	This function will tell the system to stop running.		
Inputs:	None		
Outputs:	None		
Pre-Conditions:	The system must be operating.		
Post-Conditions:	The system must not be operating.		

Operating SequenceDiagram



Train SequenceDiagram



- SR1.1 [Critical Requirement]
 - The system shall be able to read data from the host system network card.
- SR2.1 [Critical Requirement]
 - The system shall be able to interpret the data from the received network traffic and store it in a usable format.
- SR3.1 [Critical Requirement]
 - The system shall be able to determine if the network data received by the host machine is malicious with at least 85% accuracy.
- SR3.2
 - The system shall determine what type of attack is being made to the host network when malicious network traffic is found.

- SR4.1 [Critical Requirement]
 - The system shall be able to train itself through backpropagation on known network traffic data.
- SR5.1 [Critical Requirement]
 - The system shall be able to notify the User of the host system when a malicious attack is encountered.
- SR6.1
 - The system shall be able to log all malicious attacks into a log file.

Test Case 1: Capturing Data

- Requirement(s): SR1.1; SR2.1
- This test will run the Data Traffic Reader and determine if it can capture the data by capturing the output of this package after it reads the data off the network card. The analysis will look at the format of the data to ensure that the data is formatted correctly.

Test Case 2: Correctness Accuracy

- Requirement(s): SR3.1
- This test will run the Neural Network package standalone. The test will consist of feeding the Neural Network with test data, capturing the decisions made, and determining that correctness by comparing the decisions made to the actual results.

Test Case 3: Attack Type

- Requirement(s): SR3.2
- This test will run the Neural Network package standalone. The test will consist of feeding the Neural Network with test data, capturing the decisions made, and determining that correctness by comparing the decisions made to the actual results. It will then check to determine if the correct attack type was reported compared to the expected outcome.

Test Case 4: Backpropagation Training

- Requirement(s): SR4.1
- This test will run the Neural Network package standalone. The test will consist of training the Neural Network with the saved training data. If the Neural Network can achieve a correctness similar to Test Case 2 then it will pass the test.

• Test Case 5: Notification

- Requirement(s): SR5.1
- This test will run the Recorder Package standalone. It
 will test that it creates a notification when the
 package receives an input notifying it of a malicious
 data packet. The notification must have some level
 of detail about the packet.

• Test Case 6: Logging

- Requirement(s): SR6.1
- This test will be similar to Test Case 5 but will check a log file instead of a notification.

• Test Case 7: System Test

- Requirement(s): N/A
- This test will be a full simulation test initializing and running the application. From a separate application I will inject malicious packets to fake malicious data into the system.

- Test Deliverables
 - Log file for each test
- Environment Needs
 - Only those needed to run the application

FORMAL TECHNICAL INSPECTION CHECKLIST


- Inspect Prototype Code
- Inspectors:
 - Tracy Marshall
 - Keith Moyer

Inspection Item	Pass/Fail	Comments
Does the code work and perform the intended task?		
Is the code easily readable?		
Is there duplicated code?		
Is the code modular?		
Are there unused variables or functions?		
Is there commented out code?		
Are all debugging statements removed?		
Are variable and function names meaningful?		

RISKS AND CONCERNS

- Loss of data points due to KDD99 expert system data captures
- Achieving the accuracy due to loss of data points

PHASE THREE PLAN



ARCHITECTURE PROTOTYPE DEMONSTRATION

- GitHub Repository Location:
 - https://github.com/bneedy/PyIDS
- All components of the system are working to some degree
- Not fully functional yet still a prototype
- Can read network traffic off network card and determine decision using neural network

