

Consolidated Deployment Plan Safe Families for Children Case Management Application

*Deploying to GoDaddy Shared Hosting at
<https://bruce-nekich.net>*

Prepared for: Bruce Nekich

Date: May 15, 2025

User ID: kiii85r0d56e

Contents

1	Introduction	2
2	Project Overview	2
3	Deployment Plan	2
3.1	Step 1: Verify Hosting Environment Compatibility	2
3.2	Step 2: Archive the Existing Website	3
3.3	Step 3: Prepare the Development Environment	4
3.4	Step 4: Build Vite Assets Locally	6
3.5	Step 5: Prepare Application for Deployment	6
3.6	Step 6: Deploy to GoDaddy	7
3.7	Step 7: Test the Deployed Application	8
3.8	Step 8: Finalize and Document	9
4	Rollback Plan	10
5	Troubleshooting Common Issues	10
6	Conclusion	11

1 Introduction

This document provides a consolidated, step-by-step plan to deploy the Safe Families for Children Case Management application to a GoDaddy shared hosting account at <https://bruce-nekich.net>. The application is built with Laravel 12, PHP 8.2, MariaDB 10.5, and uses Bootstrap 5, Livewire, Spatie Laravel-Permission, jQuery, Select2, and TypeScript via Vite. The deployment is for a test site, not production, and involves archiving the existing site, upgrading Laravel from 11 to 12, replacing MySQL with MariaDB, installing dependencies, and addressing GoDaddy-specific issues such as document root configuration and Vite build limitations.

2 Project Overview

The Safe Families for Children Case Management application has the following properties:

- **Programming Language:** PHP 8.2
- **Framework:** Laravel 12
- **Database:** MariaDB 10.5
- **Frontend:** Bootstrap 5, Blade templates
- **JavaScript Tools:** jQuery, Select2, TypeScript (via Vite)
- **IDE:** Visual Studio Code
- **Server Environment:** Ubuntu (production), Windows (development)
- **Additional Packages:** Spatie Laravel-Permission, Livewire
- **Other Tools:** DBeaver 25.03 (database management)

The application is hosted on GoDaddy's cPanel-based shared hosting, with the website files in the `public_html` directory and the URL <https://bruce-nekich.net>. The GoDaddy user ID is `kaii85r0d56e`.

3 Deployment Plan

3.1 Step 1: Verify Hosting Environment Compatibility

- **Objective:** Confirm GoDaddy supports PHP 8.2, MariaDB 10.5, and required tools.
- **Actions:**
 1. Log in to GoDaddy cPanel.
 2. Navigate to "Select PHP Version" or "MultiPHP Manager" and set PHP 8.2 for `public_html`.
 3. Go to "MySQL Databases" and verify MariaDB 10.5 (or compatible) is available.

4. Enable SSH in “Manage Shell” and retrieve credentials (host, port, username: kaii85r0d56e, password).
5. Run `node -v` and `composer -version` via SSH to confirm Node.js and Composer availability. If missing, use cPanel’s “Setup Node.js App” or contact support.

- **Notes:**

- If PHP 8.2 or MariaDB 10.5 is unavailable, contact GoDaddy to upgrade the hosting plan.
- Laravel 12 requires PHP 8.2+.

3.2 Step 2: Archive the Existing Website

- **Objective:** Safely back up the existing site at <https://bruce-nekich.net> and its database.

- **Actions:**

1. **Backup website files:**

- Via SSH:

```
1 tar -czvf bruce-nekich-backup-$(date +%F).tar.gz  
   public_html  
2 mv bruce-nekich-backup-$(date +%F).tar.gz ~/backups/
```

- Download the archive to your local machine via cPanel File Manager or SCP.

2. **Backup the database:**

- In cPanel, go to phpMyAdmin, select the database (check `public_html/.env` for the name), and export as SQL.
- Or via SSH:

```
1 mysqldump -u [db_username] -p [db_name] > bruce-nekich-db  
   -$(date +%F).sql
```

- Download the SQL file locally.

3. **Verify backups:**

- Ensure the `.tar.gz` file contains all `public_html` contents.
- Check the SQL file for valid schema and data.

4. **Move the old site to a subdirectory:**

```
1 mv public_html public_html_archive  
2 mkdir public_html
```

- **Notes:**

- Store backups securely (e.g., local machine, cloud storage).

- Keep the archived site until the new site is validated.

3.3 Step 3: Prepare the Development Environment

- **Objective:** Upgrade Laravel, install dependencies, and test locally.

- **Actions:**

1. **Set up local environment:**

- Install PHP 8.2, Composer, Node.js, and MariaDB 10.5 on your Windows machine.
- Use Visual Studio Code and DBeaver 25.03.

2. **Upgrade Laravel 11 to 12:**

- Update `composer.json`:

```
1 "require": {  
2     "laravel/framework": "^12.0",  
3     "spatie/laravel-permission": "^6.0",  
4     "livewire/livewire": "^3.0",  
5     "fakerphp/faker": "^1.23"  
6 }
```

- Run:

```
1 composer update
```

- Check the Laravel 12 upgrade guide for breaking changes (e.g., middleware, configs).

3. **Install dependencies:**

- PHP:

```
1 composer require spatie/laravel-permission livewire/  
   livewire fakerphp/faker
```

- JavaScript:

```
1 npm install bootstrap@5 jquery select2 vite typescript
```

- Configure Vite in `vite.config.js`:

```
1 import { defineConfig } from 'vite';  
2 import laravel from 'laravel-vite-plugin';  
3 import livewire from '@defstudio/vite-livewire-plugin';  
4  
5 export default defineConfig({  
6     plugins: [  
7         laravel({  
8             input: ['resources/css/app.css', 'resources/  
9                 js/app.ts'],  
10            refresh: true,
```

```

10         }),
11         livewire({
12             refresh: ['resources/views/**/*.blade.php'],
13         }),
14     ],
15 });

```

- Publish Spatie and Livewire assets:

```

1 php artisan vendor:publish --provider="Spatie\Permission\
  PermissionServiceProvider"
2 php artisan livewire:publish --config

```

4. Set up MariaDB locally:

- Create a database:

```

1 mysql -u root -p
2 CREATE DATABASE safe_families_test;

```

- Update .env:

```

1 DB_CONNECTION=mysql
2 DB_HOST=127.0.0.1
3 DB_PORT=3306
4 DB_DATABASE=safe_families_test
5 DB_USERNAME=[your_username]
6 DB_PASSWORD=[your_password]

```

- Run migrations and seeders:

```

1 php artisan migrate --seed

```

5. Test locally:

- Start the server:

```

1 php artisan serve

```

- Build assets:

```

1 npm run dev

```

- Visit <http://localhost:8000> and test authentication, Livewire, Spatie permissions, Select2, and TypeScript features.

- **Notes:**

- Fix any issues (e.g., TypeScript errors, deprecated methods) before deployment.
- Ensure .env is not committed to Git.

3.4 Step 4: Build Vite Assets Locally

- **Objective:** Generate production-ready assets locally to bypass GoDaddy's resource limits.

- **Actions:**

1. Install Node.js dependencies:

```
1 npm install
```

2. Run the production build:

```
1 npm run build
```

3. Verify `public/build/manifest.json` exists and contains entries for `app.ts` and `app.css`.

4. Test locally:

```
1 php artisan serve
```

5. Visit <http://localhost:8000> and confirm asset loading.

- **Notes:**

- GoDaddy's thread limits prevent server-side Vite builds.
- Ensure local Node.js version matches GoDaddy's (e.g., 18 or 20).

3.5 Step 5: Prepare Application for Deployment

- **Objective:** Optimize the application and create a deployment package.

- **Actions:**

1. Create `.env.testing`:

- Copy `.env` to `.env.testing` and set:

```
1 APP_ENV=testing
2 APP_DEBUG=true
```

2. Optimize:

```
1 php artisan config:clear
2 php artisan cache:clear
3 php artisan route:clear
4 php artisan view:clear
```

3. Temporarily modify `.gitignore` to include `public/build`:

```
1 # public/build # Commented for deployment
```

4. Create a deployment package:

```
1 git archive -o safe-families.zip HEAD
```

5. Restore .gitignore:

```
1 echo "public/build" >> .gitignore
2 git add .gitignore
3 git commit -m "Restore public/build in .gitignore"
```

- **Notes:**

- The package includes public/build with manifest.json.
- Ensure .env is excluded from the zip.

3.6 Step 6: Deploy to GoDaddy

- **Objective:** Deploy the application to public_html and configure the environment.
- **Actions:**

1. Upload the application:

- Connect via SSH:

```
1 ssh kaii85r0d56e@[server_host]
2 cd public_html
```

- Upload safe-families.zip via SCP or cPanel File Manager.

- Unzip:

```
1 unzip safe-families.zip
2 rm safe-families.zip
```

2. Install Composer dependencies:

```
1 composer install --optimize-autoloader --no-dev
```

3. Configure environment:

- Copy .env.testing to .env and update:

```
1 APP_URL=https://bruce-nekich.net
2 DB_CONNECTION=mysql
3 DB_HOST=localhost
4 DB_PORT=3306
5 DB_DATABASE=[cpanel_username]_safe_families_test
6 DB_USERNAME=[db_username]
7 DB_PASSWORD=[db_password]
```

- Set permissions:

```
1 chmod -R 755 storage bootstrap/cache public/build
2 chown -R kaii85r0d56e:kaii85r0d56e .
```

4. Set up MariaDB:

- In cPanel, create a database (e.g., [cpanel_*username*]*_safe_families_test*).Created
- Update .env with credentials.
- Run migrations:

```
1 php artisan migrate --seed
```

5. Configure document root:

- Create public_html/.htaccess:

```
1 <IfModule mod_rewrite.c>
2     RewriteEngine On
3     RewriteRule ^(.*)$ public/$1 [L]
4 </IfModule>
```

- Ensure public_html/public/.htaccess exists:

```
1 <IfModule mod_rewrite.c>
2     RewriteEngine On
3     RewriteBase /
4     RewriteRule ^index\.php$ - [L]
5     RewriteCond %{REQUEST_FILENAME} !-f
6     RewriteCond %{REQUEST_FILENAME} !-d
7     RewriteRule . /index.php [L]
8 </IfModule>
```

- Set permissions:

```
1 chmod 644 public_html/.htaccess public_html/public/.
   htaccess
2 chown kaii85r0d56e:kaii85r0d56e public_html/.htaccess
   public_html/public/.htaccess
```

• Notes:

- GoDaddy's primary domain root is fixed at public_html, so .htaccess redirects to public.
- Verify public/build/manifest.json exists after upload.

3.7 Step 7: Test the Deployed Application

- **Objective:** Confirm the application works at <https://bruce-nekich.net>.

• Actions:

1. Visit <https://bruce-nekich.net> and test:
 - Authentication
 - Livewire components
 - Spatie permissions
 - Select2 dropdowns

- TypeScript features
 - 2. Check browser Developer Tools (F12) for asset errors.
 - 3. Review `storage/logs/laravel.log`:
- ```
1 cat public_html/storage/logs/laravel.log
```
- 4. Verify database schema in phpMyAdmin or DBeaver.
  - 5. Run tests (if available):

```
1 php artisan test
```

- **Notes:**

- If errors occur, check `manifest.json` or `.htaccess`.
- Revert to the archived site if needed.

### 3.8 Step 8: Finalize and Document

- **Objective:** Optimize, secure, and document the deployment.

- **Actions:**

1. Optimize:

```
1 php artisan config:cache
2 php artisan route:cache
```

2. Secure:

- Update `.env`:

```
1 APP_DEBUG=false
```

- Generate a new key:

```
1 php artisan key:generate
```

3. Document:

- Save this plan.
- Note GoDaddy credentials, `.htaccess` setup, and Vite build process.
- List dependencies: `fakerphp/faker`, `spatie/laravel-permission`, `livewire`, `bootstrap@5`, `jquery`, `select2`, `typescript`.

4. Plan for production:

- Use a VPS for Ubuntu to avoid shared hosting limits.

- **Notes:**

- Keep backups until the test site is validated.
- Consider a subdomain for future testing.

## 4 Rollback Plan

- **Objective:** Revert to the original site if deployment fails.

- **Actions:**

1. Delete public\_html contents:

```
1 rm -rf public_html/*
```

2. Restore archived site:

```
1 mv public_html_archive public_html
```

3. Restore database:

- In phpMyAdmin, drop the test database.
- Import:

```
1 mysql -u [db_username] -p [cpanel_username]
_safe_families_test < bruce-nekich-db-2025-05-14.sql
```

4. Verify <https://bruce-nekich.net>.

- **Notes:**

- Test the restored site thoroughly.
- Contact GoDaddy support if issues persist.

## 5 Troubleshooting Common Issues

- **Vite Manifest Not Found:**

- Ensure public/build/manifest.json exists.
- Rebuild locally and upload public/build.
- Check @vite directive in Blade templates.

- **Database Connection Errors:**

- Clear caches:

```
1 php artisan config:clear
```

- Verify .env credentials match cPanel.

- Test connection:

```
1 mysql -u [db_username] -p -h localhost [cpanel_username]
_safe_families_test
```

- **FakerNot Found:**

- Ensure fakerphp/faker is in require in composer.json.

- Or remove Faker from seeders for production.
- **Document Root Issues:**
  - Verify `.htaccess` in `public_html` and `public_html/public`.
  - Contact GoDaddy if `mod_rewrite` fails.

## 6 Conclusion

This plan ensures a successful deployment of the Safe Families for Children Case Management application to <https://bruce-nekich.net> on GoDaddy shared hosting. By building Vite assets locally, using `.htaccess` to set the document root, and addressing dependency and database issues, the test site can be deployed reliably. For production, consider a VPS to avoid shared hosting limitations. Retain this document and backups for reference.