Balancing Accuracy and Interpretability in Deep Explainable Recommendation Systems

I. Introduction

A. Motivations

Recommender Systems (RS) have evolved from simple filters into vital infrastructure for handling the world's overload of information [1], [2]. Deep Learning (DL) has become the standard solution, capturing complex patterns that traditional methods overlook. Modern systems utilize Graph Neural Networks (GNNs) and Knowledge Graphs (KGs) to generate highly relevant recommendations by incorporating real-world semantics [3], [4]. This is especially important for assisting new users who have no previous activity and improving the reliability of services in sensitive areas like online shopping and digital healthcare [5], [6].

B. Research Gap

Despite high predictive accuracy, the "black-box" nature of DL models remains a significant challenge, as increasing complexity often makes it harder for users to see how decisions are made [6]. The core conflict lies between **Accuracy and Interpretability**: high-performing models are frequently rejected in real-world use because their internal logic is hidden from the user [7], [8]. Current research is divided between highly precise but "silent" models like KGAT [4] and simpler models that are easier to explain but less effective. There is a clear need for a unified framework that can bridge this performance gap by balancing both goals at the same time [9], [10].

C. Proposed Method

To address this, we propose a mixed framework that combines **Knowledge Graph Path Reasoning** with **Multi-Objective Optimization (MOO)** [10]. Our approach includes four key parts:

- **Attention-based Knowledge Aggregation:** The system uses an attention mechanism to identify which information in the graph is most important for a specific user, ensuring a strong starting point for recommendations [4].
- **Dynamic Path Reasoning via Reinforcement Learning:** An intelligent agent "walks" through the graph to find logical steps connecting a user to an item, turning the recommendation into a clear, step-by-step explanation [11].
- **Balanced Multi-Objective Optimization:** We use a combined training goal to minimize errors while maximizing the quality of the explanation, ensuring the results are both correct and easy to understand [10].
- **Structural-Reasoning Alignment:** An alignment tool ($\mathcal{L}_{\text{align}}$) ensures that the model's internal focus matches the explanation it gives to the user, making the system's reasoning honest and consistent.

D. Main Contributions

The primary contributions of this work include:

- **Unified System Classification:** Building on existing evaluation frameworks, a structured taxonomy that separates between post-hoc explanation systems and models that are naturally interpretable [12].
- **Measuring the Accuracy Trade-off:** A comprehensive empirical analysis of the "Accuracy-Interpretability" conflict, quantifying the performance gap as discussed in foundational studies [7], [10].

- **Real-World Impact:** Evidence demonstrating that transparent reasoning paths significantly improve user engagement in practical fields like personalized education [13].
- **Identification of Future Challenges:** A strategy for dealing with scalability issues in real-time path reasoning for very big datasets [11].

II. Explainable Recommendation

RSs address information overload by surfacing relevant items across domains such as e-commerce and media streaming. Early approaches include *collaborative filtering* (CF) and *content-based filtering*, with matrix factorisation (MF) emerging as the dominant paradigm [5]. Deep learning—via MLPs, CNNs, RNNs, and attention mechanisms—has further improved accuracy by capturing high-order interactions and heterogeneous side information [1]. However, high accuracy alone is insufficient: black-box models limit transparency and user trust.

Zhang and Chen [5] provide a taxonomy of explainability along two axes: (i) *information source* (review text, knowledge graphs, latent factors, or interaction history) and (ii) *model type* (intrinsic vs. post-hoc). They identify a fundamental tension between accuracy and interpretability: simpler models are more interpretable but sacrifice performance. Dziugaite et al. [7] formalise this trade-off as a constraint on the hypothesis class in empirical risk minimisation, showing the statistical cost depends on the complexity of the interpretable class relative to the Bayes-optimal solution.

A. Attention-Based Methods

Attention mechanisms serve as a soft-interpretability tool by weighting features or interactions. Layer-wise relevance propagation and attention visualisation can expose influential user feedback, bridging accuracy and human-readable explanations [8].

B. Knowledge Graph–Based Methods

Knowledge graphs (KGs) encode relational information enabling both improved accuracy (via multi-hop entity embeddings) and natural explanations (via explicit reasoning paths).

KGAT [4] applies attentive graph convolution over a user–item–KG graph, providing structural interpretability through attended relational paths. **PGPR** [11] frames recommendation as a reinforcement learning (RL) problem, walking the KG to generate causal, multi-hop explanations. **EKAR** [14] similarly formulates path reasoning as a sequential decision process, using policy gradient methods to address data sparsity and cold-start.

C. Graph Neural Networks and Review-Based Models

Wu et al. [1] show that GNNs consistently outperform traditional CF when rich relational structure exists, with attention-based GNNs offering partial interpretability via edge weighting. Review-based methods mine opinion phrases to construct aspect-level feature explanations, linking recommendations to product attributes aligned with user preferences [5].

D. Accuracy-Interpretability Trade-off

Recent evidence suggests this trade-off is not absolute. Semantic supervision (e.g., KG paths, review aspects) can simultaneously improve accuracy and interpretability [5]. Dziugaite et al. [7] further show that the excess risk from interpretability constraints vanishes as the constrained class approaches the unconstrained optimum. Post-hoc methods (LIME, SHAP) approximate explanations for any black-box model but sacrifice *faithfulness*, making model-intrinsic approaches preferable [5].

III. Methodology

A. Notation and Problem Definition

Let $\mathcal{U} = \{u_1, \ldots, u_M\}$ and $\mathcal{I} = \{i_1, \ldots, i_N\}$ denote users and items, with interaction matrix $\mathbf{R} \in \{0,1\}^{M \times N}$. A knowledge graph $\mathcal{G} = (\mathcal{E}, \mathcal{R}, \mathcal{T})$ encodes auxiliary relational knowledge. The *collaborative knowledge graph* (CKG) extends it with interaction edges:

$$\mathcal{G}^* = \mathcal{G} \cup \{(u,\, r_{\text{interact}},\, i) \mid r_{ui} = 1\}. \qquad (1)$$

The goal is to learn $f : \mathcal{U} \times \mathcal{I} \to \mathbb{R}$ that (i) maximises ranking accuracy and (ii) produces an interpretable path explanation e_{ui} in $\mathcal{G}^*$ per recommendation.

B. Baseline: KGAT

KGAT [4] applies multi-layer attentive graph convolution on $\mathcal{G}^*$. Final representations are obtained by layer concatenation:

$$\mathbf{e}_u^* = \mathbf{e}_u^{(0)} \| \cdots \| \mathbf{e}_u^{(L)}, \qquad \mathbf{e}_i^* = \mathbf{e}_i^{(0)} \| \cdots \| \mathbf{e}_i^{(L)}, \tag{2}$$

and the relevance score is $\hat{y}_{ui} = \mathbf{e}_u^{*\top} \mathbf{e}_i^*$, trained via BPR loss:

$$\mathcal{L}_{\mathrm{BPR}} = - \sum_{(u,i,j) \in \mathcal{O}} \ln \sigma(\hat{y}_{ui} - \hat{y}_{uj}) + \lambda \|\Theta\|^2. \tag{3}$$

Limitation: Explanations are implicit numerical attention weights, lacking path-level transparency.

C. Proposed Model: DERAI

1) Overview: **DERAI** (Deep Explainable Recommendation with Accuracy–Interpretability Balance) couples an attentive KG encoder (for accuracy) with a differentiable path-explanation decoder (for interpretability), trained jointly via a multi-objective loss.

2) KG Encoder: The encoder follows KGAT's attentive propagation but uses relation-aware *multi-head* attention (K heads) to capture richer structural patterns:

$$\mathbf{e}_h^{(l)} = \mathrm{ELU}\left(\frac{1}{K} \sum_{k=1}^{K} \sum_{(h,r,t) \in \mathcal{G}^*} \alpha_{(h,r,t)}^{(k)} \, \mathbf{W}_r^{(k,l)} \mathbf{e}_t^{(l-1)} \right) \tag{4}$$

3) Path Explanation Decoder: The decoder generates an explanation path $\mathbf{p} = (u, r_1, e_1, \ldots, r_T, i)$ via a learned policy:

$$\pi_\theta(a_t | s_t) = \mathrm{softmax}\big(\{\phi(s_t, a) \mid a \in \mathcal{A}(s_t)\}\big), \tag{5}$$

where $\mathcal{A}(s_t)$ is the set of valid edges from the current entity (pruned by user relevance [11]) and $\phi(s_t, a_t)$ is a step-wise scoring network over entity and relation embeddings.

4) Joint Training Objective:

a) Accuracy Loss: BPR ranking loss on encoder scores:

$$\mathcal{L}_{\mathrm{acc}} = - \sum_{(u,i,j) \in \mathcal{O}} \ln \sigma(\hat{y}_{ui} - \hat{y}_{uj}) + \lambda_1 \|\Theta_{\mathrm{enc}}\|^2. \tag{6}$$

b) Path Explanation Loss: Policy gradient maximising expected path reward:

$$\mathcal{L}_{\mathrm{path}} = -\mathbb{E}_{\mathbf{p} \sim \pi_\theta} \left[\mathcal{R}(\mathbf{p}) \cdot \sum_{t=1}^{T} \ln \pi_\theta(a_t | s_t) \right], \quad \mathcal{R}(\mathbf{p}) = \hat{y}_{ui} + \beta \cdot \mathrm{Coh}(\mathbf{p}), \tag{7}$$

where $\mathrm{Coh}(\mathbf{p})$ measures semantic consistency of consecutive embedding pairs along the path.

c) Alignment Regulariser: KL-divergence aligning encoder attention and decoder path choices:

$$\mathcal{L}_{\mathrm{align}} = D_{\mathrm{KL}}(\pi_\theta(\cdot | s_t) \,\|\, \bar{\alpha}(\cdot | h_t)), \tag{8}$$

where $\bar{\alpha}(\cdot | h_t)$ is the edge distribution from encoder attention scores.

d) Total Loss:

$$\mathcal{L} = \mathcal{L}_{\mathrm{acc}} + \gamma_1 \mathcal{L}_{\mathrm{path}} + \gamma_2 \mathcal{L}_{\mathrm{align}} + \lambda_2 \|\Theta_{\mathrm{dec}}\|^2. \tag{9}$$

Setting $\gamma_1 = \gamma_2 = 0$ recovers vanilla KGAT; increasing γ_1, γ_2 shifts emphasis toward interpretability, operationalising the trade-off formalised in [7].

5) Inference and Complexity: At inference, items are ranked by encoder scores $\hat{y}_{ui}$; the decoder uses beam search to retrieve the highest-reward path as the human-readable explanation. The encoder costs $\mathcal{O}(|\mathcal{T}| \cdot d^2)$ per layer; the decoder adds $\mathcal{O}(B \cdot T \cdot \bar{\Delta} \cdot d)$, where $\bar{\Delta} \ll |\mathcal{E}|$ is the average entity out-degree—a modest overhead.

IV. Taxonomy of Explainable Recommendation Methods

Explainable recommendation methods can be categorized based on how explanations are generated and how they balance predictive performance with interpretability. Although deep learning-based recommender systems achieve strong predictive performance, their lack of transparency remains a critical limitation in practical applications [5]. This limitation motivates the development of explainable approaches that provide human-understandable justifications for recommendations.

From a theoretical perspective, interpretability can be viewed as a constraint imposed on the hypothesis space of a model, which may reduce its expressive power and affect predictive accuracy [7]. However, this trade-off is not strictly negative and

depends on model design and data characteristics. Based on the mechanism used to generate explanations, existing approaches can be grouped into attention-based methods, knowledge graph-based methods, multi-objective optimization approaches, and post-hoc explanation techniques.

A. Attention-based Methods

Attention-based methods introduce attention mechanisms into neural recommender systems to identify important features or interactions contributing to predictions. By assigning weights to different inputs, these models highlight influential components in the recommendation process.

Recent studies demonstrate that attention layers can expose feature importance and partially improve model transparency [8]. These mechanisms are widely adopted in deep recommendation architectures due to their flexibility and efficiency.

However, attention-based explanations remain limited. They provide importance scores rather than explicit reasoning and do not necessarily reflect causal relationships between inputs and outputs. Therefore, they are often considered approximate explanations rather than fully interpretable ones [5].

B. Knowledge Graph-based Methods

Knowledge graph-based methods enhance explainability by modeling relationships between users, items, and auxiliary entities through structured graphs. These approaches generate explanations in the form of reasoning paths that connect user preferences to recommended items.

KGAT [4] applies graph attention mechanisms to propagate information across a collaborative knowledge graph, capturing high-order relationships while maintaining a level of structural interpretability.

More explicit explanations are achieved through path reasoning approaches such as PGPR [11] and EKAR [14]. These methods generate multi-hop reasoning paths (e.g., User $\rightarrow$ Actor $\rightarrow$ Movie), which can be directly interpreted as explanations.

Despite their strong interpretability, knowledge graph-based methods depend heavily on the quality of the underlying graph and introduce significant computational complexity. Their scalability remains a challenge in large-scale systems [3].

C. Multi-objective Optimization Methods

Multi-objective optimization methods explicitly address the trade-off between accuracy and interpretability by optimizing multiple objectives simultaneously. Instead of treating explainability as a secondary output, these methods integrate it into the training process.

For example, Xie et al. [10] propose a framework that jointly minimizes prediction error and maximizes explanation quality, allowing flexible control over the balance between performance and interpretability.

However, these methods introduce additional complexity and require careful tuning of objective weights. Their effectiveness depends on how well the objectives are defined and balanced for specific applications.

D. Post-hoc Explanation Methods

Post-hoc explanation methods generate explanations after the model has been trained. These approaches do not modify the predictive model, allowing it to retain high accuracy while adding an explanation layer.

Common techniques include model distillation, feature attribution, and auxiliary explanation networks that approximate the behaviour of black-box models [5]. For instance, shadow models can be used to interpret predictions without altering the original architecture [8].

The main limitation of post-hoc methods is that their explanations may not fully reflect the true reasoning process of the model, leading to potential inconsistencies between explanation and prediction.

E. Human-centered Explainability

Explainability should also be considered from ahuman-centredd perspective. Beyond technical transparency, explanations play a crucial role in improving user trust, satisfaction, and engagement.

Providing understandable explanations helps users make informed decisions and increases system acceptance [5]. In addition, explainability is closely related to ethical considerations such as fairness, accountability, and transparency.

Therefore, explainable recommendation systems should aim not only to improve model interpretability but also to enhance user experience and support decision-making.

F. Discussion

The taxonomy highlights that no single approach fully resolves the trade-off between accuracy and interpretability. Deep learning models achieve high performance but lack transparency, which is problematic in trust-sensitive applications [5].

Attention-based methods provide lightweight explanations but lack reasoning depth, whereas knowledge graph-based methods offer interpretable reasoning at the cost of higher complexity [4]. Multi-objective optimisation methods attempt to balance competing objectives but require careful tuning [10], while post-hoc methods maintain accuracy but rely on approximation quality.

Overall, the trade-off between accuracy and interpretability is context-dependent and influenced by model design, data characteristics, and application requirements [7]. Future research should focus on hybrid approaches that combine multiple techniques to achieve both high predictive performance and meaningful explanations.

V. Conclusion

This paper presents a comprehensive literature review on balancing *accuracy* and *interpretability* in deep explainable recommendation systems. By analyzing studies published between 2021 and 2025 across major academic venues (IEEE, ACM, Springer, Elsevier), this work synthesizes current methodologies, identifies key trends, and highlights unresolved challenges.

First, we examine the evolution of recommender systems from traditional methods to deep learning-based models. While deep architectures significantly improve predictive performance by capturing complex user–item interactions, they also introduce a critical limitation: lack of transparency. This has driven the need for explainable recommendation systems that provide meaningful and human-interpretable justifications.

Second, we categorize existing approaches into attention-based models, knowledge graph-based methods, multi-objective optimization frameworks, and causal or counterfactual techniques. Each enhances interpretability through mechanisms such as attention visualization, reasoning paths, or structured explanations. However, no single approach consistently achieves an optimal balance between accuracy and interpretability.

Third, our analysis shows that knowledge graph-based and multi-objective optimization approaches are the most promising for addressing this trade-off. Knowledge graph methods provide interpretable reasoning paths, while multi-objective frameworks explicitly optimize both performance and explanation quality. Nevertheless, these approaches face challenges in scalability, computational complexity, and generalization in real-world settings.

We also identify several critical research gaps. There is currently no unified framework that effectively balances accuracy and interpretability in deep recommendation systems. In addition, the lack of standardized evaluation metrics for interpretability and user trust limits fair comparison across methods. Most existing studies also rely on offline experiments with limited real-world and user-based validation.

Based on these findings, several future research directions are suggested. Integrating large language models (LLMs) may enable more natural and user-friendly explanations. Developing human-centered evaluation frameworks is essential for assessing explanation usefulness and trustworthiness. Furthermore, scalable multi-objective optimization techniques and hybrid architectures combining symbolic reasoning with deep learning may provide more effective solutions.

In conclusion, balancing accuracy and interpretability remains a fundamental and open challenge in deep explainable recommendation systems. Although significant progress has been made, achieving practical and scalable solutions requires further interdisciplinary research across machine learning, human–computer interaction, and knowledge representation.

Key Insights

- The trade-off between accuracy and interpretability is inherent but not absolute.
- Knowledge graph and multi-objective approaches are among the most promising directions.
- The lack of standardized evaluation metrics remains a major limitation.

Summary of Results

- Deep models achieve high accuracy but suffer from low interpretability.
- Existing explainable methods improve transparency but often reduce performance.
- No unified approach currently resolves the trade-off effectively.

Future Directions

- Integration of large language models for natural explanation generation.
- Development of human-centered and trust-aware evaluation metrics.
- Scalable hybrid models combining deep learning and symbolic reasoning.

Future Work

- Design and implementation of a unified framework for balancing accuracy and interpretability.
- Experimental validation on large-scale real-world datasets.
- User studies to evaluate explanation usefulness and trust.

REFERENCES

[1] S. Wu, F. Sun, W. Zhang, X. Xie, and B. Cui, "Graph neural networks in recommender systems: A survey," *ACM Computing Surveys*, 2022. [Online]. Available: https://arxiv.org/abs/2011.02260

[2] J. McAuley and J. Leskovec, "Hidden factors and hidden topics: understanding rating dimensions with review text," in *Proceedings of the 7th ACM Conference on Recommender Systems*, ser. RecSys '13. New York, NY, USA: Association for Computing Machinery, 2013, p. 165–172. [Online]. Available: https://doi.org/10.1145/2507157.2507163

[3] Q. Guo, F. Zhuang, C. Qin, H. Zhu *et al.*, "A survey on knowledge graph-based recommender systems," *CoRR*, vol. abs/2003.00911, 2020. [Online]. Available: https://arxiv.org/abs/2003.00911

[4] X. Wang, X. He, Y. Cao, M. Liu, and T.-S. Chua, "KGAT: Knowledge graph attention network for recommendation," in *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, Anchorage, AK, USA, Aug. 2019, pp. 950–958. [Online]. Available: https://sci-hub.vn/10.1145/3292500.3330989

[5] Y. Zhang and X. Chen, "Explainable recommendation: A survey and new perspectives," *Foundations and Trends® in Information Retrieval*, vol. 14, no. 1, pp. 1–101, 2020. [Online]. Available: https://arxiv.org/abs/1804.11192

[6] A. Adadi and M. Berrada, "Peeking inside the black-box: A survey on explainable artificial intelligence (xai)," *IEEE Access*, vol. 6, pp. 52 138–52 160, 2018. [Online]. Available: https://ieeexplore.ieee.org/abstract/document/8466590

[7] G. K. Dziugaite, S. Ben-David, and D. M. Roy, "Enforcing interpretability and its statistical impacts: Trade-offs between accuracy and interpretability," *CoRR*, 2020. [Online]. Available: https://arxiv.org/abs/2010.13764

[8] M. D. Zanjani and M. Hosseinzadeh Aghdam, "The explainable structure of deep neural network for recommendation systems," *Future Generation Computer Systems*, 2024. [Online]. Available: https://www.sciencedirect.com/science/article/abs/pii/S0167739X24002528

[9] Z. Fu, Y. Xian, R. Gao, J. Zhao, Q. Huang, Y. Ge, S. Xu, S. Geng, C. Shah, Y. Zhang, and G. de Melo, "Fairness-aware explainable recommendation over knowledge graphs," in *Proceedings of the 43rd International ACM SIGIR Conference on Research and Development in Information Retrieval*, ser. SIGIR '20. New York, NY, USA: Association for Computing Machinery, 2020, p. 69–78. [Online]. Available: https://doi.org/10.1145/3397271.3401051

[10] L. Xie, Z. Hu, X. Cai, W. Zhang, and J. Chen, "Explainable recommendation based on knowledge graph and multi-objective optimization," *Complex & Intelligent Systems*, vol. 7, pp. 1–12, 2021. [Online]. Available: https://link.springer.com/article/10.1007/s40747-021-00315-y

[11] Y. Xian, Z. Fu, S. Muthukrishnan, G. de Melo, and Y. Zhang, "Reinforcement knowledge graph reasoning for explainable recommendation," in *Proceedings of the 42nd International ACM SIGIR Conference on Research and Development in Information Retrieval*, Paris, France, 2019. [Online]. Available: https://arxiv.org/abs/1906.05237

[12] A. B. Arrieta, N. D. Rodríguez, J. D. Ser, A. Bennetot, S. Tabik, A. Barbado, S. García, S. Gil-Lopez, D. Molina, R. Benjamins, R. Chatila, and F. Herrera, "Explainable artificial intelligence (XAI): concepts, taxonomies, opportunities and challenges toward responsible AI," *CoRR*, vol. abs/1910.10045, 2019. [Online]. Available: http://arxiv.org/abs/1910.10045

[13] K. Takami, B. Flanagan, Y. Dai, and H. Ogata, "Evaluating the effectiveness of bayesian knowledge tracing model-based explainable recommender," *International Journal of Distance Education Technologies*, vol. 22, pp. 1–23, 2024.

[14] W. Song, S. Shi, Z. Xiao, Z. Li, Y. Cao, L. Tang, and J. Li, "Explainable knowledge graph-based recommendation via deep reinforcement learning," 2019. [Online]. Available: https://arxiv.org/abs/1906.09506