# Varianta 2 de pe site-ul modinfo

## Link varianta:

• https://www.modinfo.ro/bac/variante-test-2021/info/v2.pdf

### Rezolvare

#### Subjectul I

- 1. a
- 2. d
- 3. d
- 4. b
- 5. b

#### Subjectul II

1.

- a: -1 21
- b: 10123, 11234, 12345, etc
- c:

```
#include <iostream>
using namespace std;
void f (int x);
int main()
    int n, s = 1, c1, c2;
    cin >> n;
    c1 = n \% 10;
    n = n / 10;
    c2 = n \% 10;
    if (c1 == c2) {
        s = 0;
    } else if (c1 < c2) {</pre>
        s = -1;
    while ((c1 - c2) * s > 0 && n > 9) {
        c1 = n \% 10;
        n = n/10;
        c2 = n \% 10;
    }
```

```
cout << s << " " << n;
}
```

• d:

```
2. struct polinom {
    int grad;
    int coeficient[100];
} p
```

```
#include <iostream>
#include <string.h>

using namespace std;

int main()
{
    char s[21];
    cin>> s;
    char sirVocale[]= "aeiouAEIOU";
    for(int i = 0; i < strlen(sirVocale);i++) {
        if (strchr(s, sirVocale[i]) == NULL) {
            cout << sirVocale[i];
        }
    }
}</pre>
```

#### Subjectul III

1. Solutie

```
#include <iostream>
using namespace std;
int factori(int n, int m);
int primeDivizorHasSamePower(int divizor, int n, int m);
int main()
{
    int n, m;
    cin >> n >> m;
    int result = factori(n, m);
    cout << result;</pre>
}
int factori(int n, int m) {
    int contorNumerePrime = 0;
    for (int i = 2; i <= n && i <= m; i++) {
        if (n%i == 0 && m % i == 0) {
            int estePrim = 1;
            for (int j = 2; j*j <=i;j++) {
                if (i % j == 0) {
                    estePrim = 0;
                    break;
            }
            if (estePrim == 1 && primeDivizorHasSamePower(i, n, m)) {
                contorNumerePrime++;
        }
    return contorNumerePrime;
}
int primeDivizorHasSamePower(int divizor, int n, int m) {
    int counter1 = 0;
    int counter2 = 0;
    while(n % divizor == 0) {
        counter1++;
        n = n / divizor;
    while(m % divizor == 0) {
        counter2++;
        m = m / divizor;
   return counter1 == counter2;
}
```

#### 2. Solutie:

```
#include <iostream>
using namespace std;
```

```
int main()
{
    int n;
    cin >> n;
    int matrice[n][n];
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            if (j == (n-i-1)) {
                 matrice[i][j] = n;
             } else if ( j < (n-i-1)) {
            matrice[i][j] = n - (n-i-1-j);
            } else {
                 matrice[i][j] = n + (n-i-1-j);
        }
    }
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            cout << matrice[i][j] << " ";</pre>
        cout << endl;</pre>
    }
}
```

3.

- a. Limbaj natural
  - Un algoritm eficient pentru problema de fata ar fi urmatorul, numaram lungimea secventei pana la primul numar pozitiv si lungimea secventei care incepe dupa primul numar pozitiv (in ambele cazuri, si numarul pozitiv se va contoriza).
  - Eficienta algoritmului consta in faptul ca avem o singura parcurgere a fisierului.
- b. Solutie

```
#include <iostream>
#include <fstream>

using namespace std;

int main()
{
    ifstream fin("bac.in");
    int amGasitPrimulNumarPozitiv = 0;
    int maxLen = 0;
    int currentLength = 0;
    while (!fin.eof()) {
        int currentNumber;
        fin >> currentNumber;
    }
}
```

```
if (currentNumber >= 0 && !amGasitPrimulNumarPozitiv) {
            amGasitPrimulNumarPozitiv = 1;
            currentLength++;
            if (currentLength > maxLen) {
                maxLen = currentLength;
            }
            currentLength = 1;
        } else {
            currentLength++;
    }
    if (currentLength > maxLen) {
        maxLen = currentLength;
    }
    cout << maxLen;</pre>
   fin.close();
}
```