Nascom Documentation Library - Polyzap

1. Introduction to Polyzap
    1.1 Notations used in this manual
2. Coding assembly language programs
    2.1 Source statement format
        2.1.1 The label field
        2.1.2 The opcode field
        2.1.3 The operand field
        2.1.4 The comment field
    2.2 Symbols
    2.3 The location counter
    2.4 Constants
    2.5 Expressions
    2.6 Symbol table files
3. Pseudo operations
    3.1 ORG - Define origin
    3.2 IDNT - Define object file identity
    3.3 EQU - Equate symbol to a value
    3.4 SET - Set symbol value
    3.5 DEFL - Define label
    3.6 REFS - Reference file specify
    3.7 REF - Reference a symbol
    3.8 DB - Define byte(s)
    3.9 DC - Define character string
    3.10 DW - Define word(s)
    3.11 DS - Define storage
    3.12 DEFB - Define byte(s)
    3.13 DEFM - Define message
    3.14 DEFW - Define word(s)
    3.15 DEFS - Define storage
    3.16 END - End of source program
    3.17 Conditional assembly
        3.17.1 IF
        3.17.2 ELSE
        3.17.3 ENDIF
        3.17.4 COND
        3.17.5 ENDC
4. Operating Polyzap
    4.1 Assembly options
        4.1.1 The L option - Output an assembly listing
        4.1.2 The P option - Output sent to printer
        4.1.3 The S option - Output and alphabetically sorted symbol table
        4.1.4 The C option - Save symbol table to file

4.1.5 The G option - Print all object codes generated by DB, DC, DW etc., not just 1st 4 bytes
4.1.6 The D option - Do not print pseudo-op lines
4.1.7 The F option - Force 2nd pass, even if 1st pass failed
4.2 Assembler error handling