phase2

October 15, 2026

1 Phase 2: Exploratory Analysis and Preregistration

1.1 Part 1 — Data collection and exploratory analysis

1.1.1 1. Research question

How do U.S. monthly temperature and precipitation relate to the business's monthly hat sales, and does the relationship vary across different hat material?

For our project, we are measuring sales data from a family-owned hat business (link: https://angelawilliam.com/) and comparing it with historical weather data from the NOAA (National Oceanic and Atmospheric Administration). We want to see *whether* certain *weather* conditions (pun not intended, lol) are associated with higher or lower hat sales.

We will focus more so on monthly sales quantity and average temperature and precipitation across the contiguous United States.

1.1.2 2. Data collection and cleaning

2.1. Data sources and collection We are using sales and product data from William's family business. And we are using the historical weather data from NOAA.

The business data comes from an export of the accounting software and includes transaction records, descriptions of the product, and inventory information.

For the NOAA: we downloaded the weather data from the NOAA's monthly climate dataset which contains historical temperature and precipitation measurements.

We're using 5 files:

File	Use
`salesByCustomerDetail.CSV`	Invoice lines used to calculate monthly sales.
`itemData.CSV`	Product descriptions used to identify hats and materials.
`inventoryData.CSV`	Coverage checks only; adding its invoices could double-count sales.
`TempreatureData.CSV`	Monthly average US temperatures
`PrecipitationData.CSV`	Monthl US precipitation (rain)

2.1. Setup We first import Python libraries to use for cleaing, analyzing and visualizing the data. All the data is stored in the `csvs` folder.

[1]:
```
import pandas as pd
import matplotlib.pyplot as plt
from IPython.display import display

# All file paths are relative to the repository root.
plt.rcParams['figure.figsize'] = (10, 4)
```

2.2. Load the business files We load the three business datasets and check their sizes and transaction types. We read the columns as text initially so that product IDs and other values aren't accidentally changed when importing the files.

[2]:
```
sales_raw = pd.read_csv('csvs/salesByCustomerDetail.CSV', encoding='cp1252',␣
 ↪dtype=str).fillna('')
catalog = pd.read_csv('csvs/itemData.CSV', encoding='cp1252', dtype=str).
 ↪fillna('')
inventory = pd.read_csv('csvs/inventoryData.CSV', encoding='utf-8-sig',␣
 ↪dtype=str).fillna('')

print('Sales report rows:', len(sales_raw))
print('Catalog rows:', len(catalog))
print('Inventory report rows:', len(inventory))
print('Sales row types (blank = report heading or subtotal):')
display(sales_raw['Type'].value_counts())
print('Inventory row types:')
display(inventory['Type'].value_counts())
```

```
Sales report rows: 32768
Catalog rows: 7866
Inventory report rows: 32768
Sales row types (blank = report heading or subtotal):
```

```
Type
Invoice    31877
             891
Name: count, dtype: int64
```

```
Inventory row types:
```

```
Type
Invoice             29954
Item Receipt         1154
                      846
Inventory Adjust      700
Build Assembly         99
Bill                   15
Name: count, dtype: int64
```

2.3. Cleaning transactions and matching products The original sales file includes invoices, headings, and subtotal rows. Since we're interested in actual sales, we filter the data to keep invoice entries.

We then convert dates and numerical columns into usable formats, removing characters such as dollar signs and commas with `regex`. We also extract the product IDs and match them with the product information file so that we can identify what was sold.

We keep the original row numbers to help trace records back to the source data, and we don't automatically delete duplicate-looking transactions since some may be legitimate sales.

One concern is that both transaction exports contain exactly 32,768 rows and appear to end partway through the records. This might indicate an export limit, so we still need to verify whether the data is complete.

[3]:
```
# Keep invoice rows, rather than report headings and subtotals.
sales = sales_raw[sales_raw['Type'] == 'Invoice'].copy()
sales['source_csv_row'] = sales.index + 2
sales['date'] = pd.to_datetime(sales['Date'], format='%m/%d/%Y',␣
 ↪errors='coerce')

# Clean the three numeric columns. Parentheses mean a negative amount.
for column in ['Qty', 'Amount', 'Sales Price']:
    sales[column] = sales[column].str.replace(',', '', regex=False)
    sales[column] = sales[column].str.replace('$', '', regex=False)
    sales[column] = sales[column].str.replace('(', '-', regex=False)
    sales[column] = sales[column].str.replace(')', '', regex=False)
    sales[column] = pd.to_numeric(sales[column], errors='coerce')
sales = sales.rename(columns={'Qty': 'quantity', 'Amount': 'amount', 'Sales␣
 ↪Price': 'unit_price'})

# Sales item names contain an ID followed by a description in parentheses.
sales['item_id'] = sales['Item'].str.split(' (', n=1, regex=False).str[0].str.
 ↪strip()
catalog['item_id'] = catalog['Item'].str.strip()
products = catalog[['item_id', 'Type', 'Description']].copy()
products = products.rename(columns={'Type': 'catalog_type', 'Description':␣
 ↪'catalog_description'})

# many_to_one checks that each item ID matches no more than one catalog row.
sales = sales.merge(products, on='item_id', how='left', validate='many_to_one')
print('Invoice lines:', len(sales))
print('Unmatched catalog lines:', sales['catalog_type'].isna().sum())
print('First invoice date:', sales['date'].min())
print('Last invoice date:', sales['date'].max())
print('Missing numeric values:')
display(sales[['quantity', 'amount', 'unit_price']].isna().sum())
print('Zero or negative quantity lines:', (sales['quantity'] <= 0).sum())
```

```
print('Duplicate-looking source lines retained:', sales_raw[sales_raw['Type']␣
 ↪== 'Invoice'].duplicated().sum())
```

```
Invoice lines: 31877
Unmatched catalog lines: 1
First invoice date: 2006-10-01 00:00:00
Last invoice date: 2026-08-13 00:00:00
Missing numeric values:

quantity         0
amount         466
unit_price    1089
dtype: int64

Zero or negative quantity lines: 422
Duplicate-looking source lines retained: 1
```

2.4. Identifying hats and materials Next, we filter the transactions to focus on hats. We use product descriptions and keywords such as "hat," "fedora," "cap," and "beanie" to identify relevant products. We also exclude transactions that aren't merchandise, such as services or shipping charges which we aren't interested in.

We then try to classify the hats by material using words in their descriptions, including wool, cotton, straw, felt, and leather.

Not every product has a clear material listed. When we can't identify a material, we label it unknown. If multiple materials appear in the description, we label it `mixed_or_ambiguous`.

Finally, we keep transactions with valid dates and positive quantities. These are used for our initial analysis of sales, although they don't fully account for returns or refunds.

[4]:
```
# Combine descriptions and replace punctuation with spaces for word matching.
sales['description_text'] = sales['catalog_description'].fillna('') + ' ' +␣
 ↪sales['Item']
sales['description_text'] = sales['description_text'].str.lower()
sales['words'] = sales['description_text'].str.replace(r'[^a-z]+', ' ',␣
 ↪regex=True)
sales['words'] = ' ' + sales['words'] + ' '

# Flag common hat words.
hat_words = ['hat', 'hats', 'cap', 'caps', 'ivy', 'ivies', 'fedora', 'fedoras',
             'beanie', 'beanies', 'beret', 'berets', 'cloche', 'cloches',
             'fascinator', 'fascinators', 'visor', 'visors', 'bonnet',␣
 ↪'bonnets',
             'duckbill', 'newsboy', 'trilby', 'floppy', 'panama']
sales['candidate_hat'] = False
for word in hat_words:
    matches = sales['words'].str.contains(' ' + word + ' ', regex=False)
    sales.loc[matches, 'candidate_hat'] = True
```

```
# Exclude services, freight, and other non-merchandise catalog types.
merchandise_types = ['Inventory Part', 'Inventory Assembly', 'Non-inventory␣
 ↪Part']
sales['candidate_hat'] = sales['candidate_hat'] & sales['catalog_type'].
 ↪isin(merchandise_types)

# Assign a provisional material from explicit description words.
sales['material'] = 'unknown'
sales['material_matches'] = 0
for material in ['wool', 'straw', 'cotton', 'polyester', 'acrylic', 'leather',␣
 ↪'felt']:
    matches = sales['words'].str.contains(' ' + material + ' ', regex=False)
    if material == 'straw':
        matches = matches | sales['words'].str.contains(' raffia ', regex=False)
    sales.loc[matches, 'material'] = material
    sales.loc[matches, 'material_matches'] += 1
sales.loc[sales['material_matches'] > 1, 'material'] = 'mixed_or_ambiguous'

# Keep dated, positive-quantity candidate hats for preliminary gross-sales EDA.
keep = sales['candidate_hat'] & sales['date'].notna() & (sales['quantity'] > 0)
clean_sales = sales.loc[keep, ['source_csv_row', 'date', 'item_id', 'quantity',
                               'amount', 'unit_price', 'material']].copy()
clean_sales['month'] = clean_sales['date'].dt.to_period('M').dt.to_timestamp()
print('Retained candidate-hat invoice lines:', len(clean_sales))
display(clean_sales.groupby('material')['quantity'].sum().
 ↪sort_values(ascending=False))
```

```
Retained candidate-hat invoice lines: 23072
```

```
material
unknown               696515
cotton                 29182
felt                   12937
wool                   10912
straw                   6117
mixed_or_ambiguous      5867
leather                 2553
polyester                288
Name: quantity, dtype: int64
```

2.5. Monthly sales We group the cleaned transactions by month and material, then addition all the recorded sales quantities.

This gives us a dataset showing how much of each hat material was sold during each month. We also check for months without sales records. Rather than assuming sales were zero during those months, we leave them missing because we don't know whether the business had no sales or whether records are incomplete.

[5]:
```
# Sum quantities for each month and material.
monthly_sales = clean_sales.groupby(['month', 'material'])['quantity'].sum().
 ↪reset_index()
monthly_sales = monthly_sales.rename(columns={'quantity': 'recorded_quantity'})

# Make a calendar so gaps remain visible in the time-series plots.
month_range = pd.date_range(clean_sales['month'].min(), clean_sales['month'].
 ↪max(), freq='MS')
observed_month_count = clean_sales['month'].nunique()
print('Observed sales months:', observed_month_count)
print('Months without retained observations:', len(month_range) -␣
 ↪observed_month_count)
display(monthly_sales.head())
```

```
Observed sales months: 234
Months without retained observations: 5
```

	month	material	recorded_quantity
0	2006-10-01	unknown	15259
1	2006-11-01	unknown	25537
2	2006-12-01	unknown	22356
3	2007-01-01	unknown	10310
4	2007-02-01	unknown	6086

2.7 Loading weather data For our weather data, we use NOAA's historical monthly temperature and precipitation records for the contiguous United States.

The files contain one row per year, with separate columns for each month. We select the national temperature and precipitation records, rather than individual states or regions.

Both datasets cover 1895 through September 2026, but we only use the months corresponding to our sales data (October 2006 through August 2026).

Record format help from the NOAA: https://www.ncei.noaa.gov/monitoring-content/data/us/climdiv/monthly/current/state-readme.txt

[6]:
```
# Read the ID and 12 monthly values.
month_columns = ['01', '02', '03', '04', '05', '06',
                 '07', '08', '09', '10', '11', '12']
column_names = ['code'] + month_columns
temperature_raw = pd.read_csv('csvs/TempreatureData.CSV', sep=r'\s+',
                              header=None, names=column_names, dtype={'code':␣
 ↪str})
precipitation_raw = pd.read_csv('csvs/PrecipitationData.CSV', sep=r'\s+',
                                header=None, names=column_names, dtype={'code':␣
 ↪str})

# The six-character prefix selects region 110, division 0, and the variable.
```

```
temperature = temperature_raw[temperature_raw['code'].str[:6] == '110002'].
 ↪copy()
precipitation = precipitation_raw[precipitation_raw['code'].str[:6] ==␣
 ↪'110001'].copy()
temperature['year'] = temperature['code'].str[6:10]
precipitation['year'] = precipitation['code'].str[6:10]
print('National temperature years:', len(temperature))
print('National precipitation years:', len(precipitation))
display(temperature[['year'] + month_columns].tail(2))
```

```
National temperature years: 132
National precipitation years: 132
```

	year	01	02	03	04	05	06	07	08	09	\
7792	2025	29.16	34.74	46.83	53.56	61.70	71.20	75.42	73.38	67.95	
7793	2026	33.12	40.26	50.85	54.77	61.68	70.66	76.91	75.54	69.42	

	10	11	12
7792	56.95	46.69	37.83
7793	-99.90	-99.90	-99.90

2.7. (a) Cleaning temperature data We restructure the temperature data so that each row represents one month instead of one year. We also replace NOAA's missing-value codes with missing values in Python and convert temperatures from Fahrenheit to Celsius.

[7]:
```
# Reshape the national temperature rows into one row per month.
temperature_monthly = temperature.melt(id_vars='year', value_vars=month_columns,
                                       var_name='month_number',␣
 ↪value_name='temperature_f')
temperature_monthly['temperature_f'] = temperature_monthly['temperature_f'].
 ↪replace(-99.90, float('nan'))
temperature_monthly['month'] = pd.to_datetime(temperature_monthly['year'] + '-'␣
 ↪+ temperature_monthly['month_number'] + '-01')
temperature_monthly['temperature_c'] = (temperature_monthly['temperature_f'] -␣
 ↪32) * 5 / 9
temperature_monthly = temperature_monthly[['month', 'temperature_c']].
 ↪sort_values('month')
print('Missing national temperature months:',␣
 ↪temperature_monthly['temperature_c'].isna().sum())
display(temperature_monthly.tail())
```

```
Missing national temperature months: 3
```

	month	temperature_c
1055	2026-08-01	24.188889
1187	2026-09-01	20.788889
1319	2026-10-01	NaN
1451	2026-11-01	NaN
1583	2026-12-01	NaN

2.7. (b) Cleaning Precipitation Data And same thing for precipitation, converting the data into monthly observations and handling missing values. We also convert the measurements from inches to millimeters so that we're using metric units consistently.

[8]:
```
# Reshape the national precipitation rows into one row per month.
precipitation_monthly = precipitation.melt(id_vars='year',␣
 ↪value_vars=month_columns,
                                           var_name='month_number',␣
 ↪value_name='precipitation_in')
precipitation_monthly['precipitation_in'] =␣
 ↪precipitation_monthly['precipitation_in'].replace(-9.99, float('nan'))
precipitation_monthly['month'] = pd.to_datetime(precipitation_monthly['year'] +␣
 ↪'-' + precipitation_monthly['month_number'] + '-01')
precipitation_monthly['precipitation_mm'] =␣
 ↪precipitation_monthly['precipitation_in'] * 25.4
precipitation_monthly = precipitation_monthly[['month', 'precipitation_mm']].
 ↪sort_values('month')
print('Missing national precipitation months:',␣
 ↪precipitation_monthly['precipitation_mm'].isna().sum())
display(precipitation_monthly.tail())
```

```
Missing national precipitation months: 3
```

	month	precipitation_mm
1055	2026-08-01	58.674
1187	2026-09-01	68.326
1319	2026-10-01	NaN
1451	2026-11-01	NaN
1583	2026-12-01	NaN

2.8. Combining sales and weather data Once both datasets are cleaned, we merge temperature and precipitation into a single monthly weather dataset.

We then join this with our monthly hat sales data using the month as the matching variable. This gives us a dataset containing recorded sales quantities for each material, along with the temperature and precipitation for that month.

Our merged dataset contains 813 rows across 234 months with recorded sales. Every row successfully matches a temperature and precipitation value.

There are also five months in the overall time range without retained sales observations. We leave these missing rather than assuming there were zero sales.

[9]:
```
# Make one national weather row per month.
weather_monthly = temperature_monthly.merge(precipitation_monthly, on='month',
                                            how='outer', validate='one_to_one')
weather_monthly = weather_monthly.sort_values('month')
start_month = monthly_sales['month'].min()
end_month = monthly_sales['month'].max()
```

```
weather_monthly = weather_monthly[weather_monthly['month'].between(start_month,␣
↪end_month)].copy()

# Each weather month can match several sales material rows.
analysis_data = monthly_sales.merge(weather_monthly, on='month', how='left',␣
↪validate='many_to_one')
print('Sales month-material rows before merge:', len(monthly_sales))
print('Rows after merge:', len(analysis_data))
print('Missing weather values in merged data:')
display(analysis_data[['temperature_c', 'precipitation_mm']].isna().sum())
display(analysis_data.head())
```

```
Sales month-material rows before merge: 813
Rows after merge: 813
Missing weather values in merged data:
```

```
temperature_c       0
precipitation_mm    0
dtype: int64
```

	month	material	recorded_quantity	temperature_c	precipitation_mm
0	2006-10-01	unknown	15259	11.427778	73.660
1	2006-11-01	unknown	25537	6.711111	62.484
2	2006-12-01	unknown	22356	2.538889	65.278
3	2007-01-01	unknown	10310	-0.361111	56.388
4	2007-02-01	unknown	6086	0.227778	44.450

1.1.3 3. Data description

What does our dataset contain? Our final dataset, `analysis_data` contains 813 rows covering 234 months of sales records. Each row represents the total recorded sales quantity for a particular hat material in a given month.

There are 5 columns:

Column	Meaning
`month`	Month of the recorded sales (1st day of the month).
`material`	Hat material.
`recorded_quantity`	Total positive sales quantity for that material during the month.
`temperature_c`	Average monthly temperature across US in °C.
`precipitation_mm`	Average monthly precipitation across the US, in mm.

Why was this dataset created? The original sales and inventory data was collected by William's family business for accounting. NOAA collects weather data to monitor the history of climate conditions.

For this project, we combined these sources to investigate whether temperature and precipitation are related to hat sales, and whether this relatoinship differs between materials.

How was the dataset created? We started with sales/product inventory from the business accounting software, as well as monthly temp/precipitation data from NOAA.

We cleaned the sales record, converted dates and quantities, identified hats, assigned materials based on keywords, and grouped sales quantities by month and material.

For weather: we selected NOAA contiguous (continental) US observations, converted the measurements into metric units, and reorganized it into monthly rows.

(All these steps and details documented in the Section above, Section 2).

What factors might affect what was recorded? Our sales data only represents purchases recorded by the business, not necessarily all customer demand of all hats in the USA. For example, if an item was out of stock, the business may have lost potential sales that wouldn't appear in the data.

The accounting exports may also be incomplete, and some product descriptions don't specify the material of the hat. Additionally, the weather data represents national averages rather than the specific locations of customers.

What preprocessing was done? As stated in the section above, we filtered the sales records, standardized dates and values, and aggregated sales by month. Similarly for weather, we converted data into consistent units before merging the datasets.

Were people aware their data was being collected? The sales records were originally collected as part of normal business operations, rather than for this research project. We received the data through William's family business (who are OK with us using the data).

Our research does not need individual customer names or any identifying information.

The weather data comes from the official NOAA website and is public domain.

Where can the original data be found? The NOAA weather data is publicly available from the NOAA National Centers for Environmental Information. Here is a link

The original business data is private. Our group stores the project files in our GitHub repository (see `csvs` folder), but customer information and other sensitive business records should not be shared publicly.

1.1.4 4. Data limitations and implications

- **Incomplete sales records:** Both accounting exports contain exactly 32,768 rows, which suggests they may have been cut off. We also have five months without recorded sales, and August 2026 is incomplete. This could make our monthly sales totals inaccurate, especially when looking at long-term trends. For example, a decrease in recorded sales might actually reflect missing transactions rather than a decline in customer demand.

- **Missing material information:** Around 91.9% of our recorded sales quantity has an unknown or ambiguous material. Because we're identifying materials using product descriptions, we may be missing or incorrectly classifying certain products. This is especially important for our second hypothesis, since the cotton and wool products we can identify might not represent the business's actual sales mix. We also can't assume that missing material information is evenly distributed across different years or seasons.
- **Geographic differences:** Our weather data represents averages across the contiguous United States, but the business might sell more hats in certain regions. For example, customers in New York and Florida experience very different weather conditions. Using national averages could make it harder to identify relationships between weather and sales in specific markets.
- **Other factors affecting sales:** Hat sales could also be influenced by fashion trends, wholesale orders, promotions, inventory availability, or changes in the business over time. Some of these might follow seasonal patterns, making it difficult to separate their effects from weather.

1.1.5 5. Exploratory data analysis

Before running the analyzes, we wanted to get a better understanding of our data. We looked at overall sales quantities, differences between materials, and how both sales and weather change over time.

5.1. Summary statistics We looked at Mean/median/range to understand typical sales quantities. We also calculated how much of our sales quantity has unknown or ambigious material.

[10]:
```
# Summarize sales. Reindexing makes missing calendar months visible as NaN.
monthly_total = clean_sales.groupby('month')['quantity'].sum().
 ↪reindex(month_range)
print('Invoice-line quantity:')
display(clean_sales['quantity'].describe().round(2))
print('Observed monthly total quantity:')
display(monthly_total.describe().round(2))

uncertain = clean_sales['material'].isin(['unknown', 'mixed_or_ambiguous'])
unknown_share = clean_sales.loc[uncertain, 'quantity'].sum() /␣
 ↪clean_sales['quantity'].sum()
print('Percent of quantity with unknown/ambiguous material:', round(100 *␣
 ↪unknown_share, 1))
```

```
Invoice-line quantity:
```

```
count    23072.00
mean        33.13
std        107.98
min          1.00
25%          6.00
50%         12.00
75%         24.00
max       4260.00
Name: quantity, dtype: float64
```


```
Observed monthly total quantity:

count      234.00
mean      3266.54
std       4873.24
min         35.00
25%        650.00
50%       1528.50
75%       3884.75
max      45756.00
Name: quantity, dtype: float64

Percent of quantity with unknown/ambiguous material: 91.9
```

5.2. Sales over time We plot total monthly sales quantities to see how sales have changed over time.

[11]:
```
# Plot monthly quantities, leaving unknown months as gaps.
plt.figure(figsize=(10, 4))
plt.plot(monthly_total.index, monthly_total.values)
plt.title('Preliminary monthly hat quantity - available business records')
plt.xlabel('Month')
plt.ylabel('Recorded quantity (units unverified)')
plt.tight_layout()
plt.show()
```





5.3. Material composition and invoice quantities Next, we compare the total recorded sales quantity for each material category. This helps us understand which materials are most common in our dataset and how much information is missing.

We also plot the distribution of individual invoice quantities. We use a logarithmic scale because some orders are much larger than others, making it difficult to see the smaller orders on a regular scale.

[12]:
```
# Compare total recorded quantities by provisional material.
material_totals = clean_sales.groupby('material')['quantity'].sum().
 ↪sort_values()
material_totals.plot(kind='barh', figsize=(9, 4))
plt.title('Quantity by provisional material')
plt.xlabel('Recorded quantity')
plt.ylabel('Material')
plt.tight_layout()
plt.show()

# Use wider bins for larger orders and label the axis in original quantities.
plt.figure(figsize=(9, 4))
plt.hist(clean_sales['quantity'], bins=[1, 2, 5, 10, 20, 50, 100, 200, 500,␣
 ↪1000, 5000])
plt.xscale('log')
plt.title('Distribution of positive invoice quantities')
plt.xlabel('Recorded quantity (log scale; unequal bin widths)')
plt.ylabel('Invoice lines per bin')
plt.tight_layout()
plt.show()
```






5.4. Material sales over time We then compare monthly sales for cotton, felt, and wool, which are the three largest material categories that we could identify.

We want to see whether these materials follow similar sales patterns throughout the year or whether some materials appear to sell more during certain periods. However, these comparisons are limited by the large proportion of products without a clear material classification.

[13]:
```
# Find the three largest named material groups.
known = monthly_sales[~monthly_sales['material'].isin(['unknown',␣
 ↪'mixed_or_ambiguous'])]
material_totals = known.groupby('material')['recorded_quantity'].sum().
 ↪sort_values(ascending=False)
top_materials = material_totals.head(3).index

plt.figure(figsize=(10, 4))
for material in top_materials:
    material_data = known[known['material'] == material]
    quantities = material_data.set_index('month')['recorded_quantity'].
 ↪reindex(month_range)
    plt.plot(quantities.index, quantities.values, label=material)
plt.title('Monthly quantity for three largest provisional materials')
plt.xlabel('Month')
plt.ylabel('Recorded quantity')
plt.legend()
plt.tight_layout()
plt.show()
```




5.5 Weather over time And finally we look at monthly temperature and precipitation rates across the contiguous US over the same period as our sales data.


[14]:
```
# Describe the national weather series within the sales date range.
display(weather_monthly[['temperature_c', 'precipitation_mm']].describe().
  ↪round(2))

plt.figure(figsize=(10, 3))
plt.plot(weather_monthly['month'], weather_monthly['temperature_c'])
plt.title('CONUS monthly mean temperature')
plt.xlabel('Month')
plt.ylabel('Temperature (°C)')
plt.tight_layout()
plt.show()

plt.figure(figsize=(10, 3))
plt.plot(weather_monthly['month'], weather_monthly['precipitation_mm'])
plt.title('CONUS area average of monthly precipitation totals')
plt.xlabel('Month')
plt.ylabel('Precipitation (mm)')
plt.tight_layout()
plt.show()
```

	temperature_c	precipitation_mm
count	239.00	239.00
mean	12.10	65.62
std	8.42	14.80
min	-1.58	24.38
25%	4.59	56.39
50%	11.98	65.28
75%	20.31	75.06
max	24.95	113.54





5.6. Weather and Hat Sales Now that we've looked at sales and weather separately, we want to see how they relate to each other.

We plot monthly sales quantities against temperature and precipitation to look for any initial patterns. Each point represents one month of sales.

We exclude August 2026 because the sales records only cover part of that month. We're not running our proposed regression models yet; these plots are just to help us understand the data before the next phase.

[15]:
```
# Sum sales across all materials to get one total per month.

sales_totals = (
    monthly_sales.groupby('month', as_index=False)
    ['recorded_quantity'].sum()
)


# Match each sales month with its temperature and precipitation.
weather_sales = sales_totals.merge(
    weather_monthly,
    on='month',
    how='inner',
    validate='one_to_one'
```


```
)

# Exclude August 2026 because it is an incomplete sales month.
weather_sales = weather_sales[
    weather_sales['month'] < '2026-08-01'
].copy()

# Explore temperature versus sales.
plt.figure(figsize=(8, 5))
plt.scatter(
    weather_sales['temperature_c'],
    weather_sales['recorded_quantity'],
    alpha=0.5
)
plt.xlabel('Average monthly temperature (°C)')
plt.ylabel('Monthly recorded sales quantity')
plt.title('Monthly Hat Sales vs. Temperature')
plt.tight_layout()
plt.show()

# Explore precipitation versus sales.
plt.figure(figsize=(8, 5))
plt.scatter(
    weather_sales['precipitation_mm'],
    weather_sales['recorded_quantity'],
    alpha=0.5
)
plt.xlabel('Monthly precipitation (mm)')
plt.ylabel('Monthly recorded sales quantity')
plt.title('Monthly Hat Sales vs. Precipitation')
plt.tight_layout()
plt.show()
```





5.7. Interpretation of the EDA

- Sales quantities vary significantly. We have 23,072 retained invoice lines covering 234 months.

The median invoice quantity is 12, while the mean is 33.13, suggesting that some unusually large orders increase the average. Monthly totals also vary considerably, with a median of 1,528.5 and a mean of 3,266.54.

- Material information is limited. Around 91.9% of recorded sales quantity falls into the unknown or ambiguous material categories.
- Some sales records may be missing. There are five months in our overall time range without retained sales observations, which we will need to investigate.
- The weather data is complete for the months we're analyzing. All 813 month–material observations have corresponding temperature and precipitation measurements. Across the 239-month period, the average temperature was 12.10°C and average monthly precipitation was 65.62 mm.

Based on these findings, we're keeping our original research question but clarifying that we're using national weather averages rather than weather conditions for individual customers.

1.1.6 6. Questions for peer reviewers and project mentor — Part 1

1. Our sales exports appear to be cut off at 32,768 rows. Is there a good way to check whether we're missing transactions and how much this might affect our analysis?
2. Would using national average weather data be sufficient for our research question?
3. Many products don't have clearly identified materials. Would it make more sense to focus on fewer material categories, or is there a better approach to classifying them?
4. Are there any other variables we should consider before running our models, such as seasonal trends or changes in the business over time?

1.2 Part 2 — Preregistration of analyses

Preregistration Statement 1: Weather and total monthly sales

Hypothesis: We expect lower temperatures to be associated with higher monthly hat sales, even after accounting for seasonality and changes over time. We also expect precipitation to have a relationship with sales, although we don't have a strong prediction about its direction.

Proposed analysis: We will calculate the business's total recorded hat quantity for each month and use multiple linear regression to examine its relationship with temperature and precipitation. Our dependent variable will be the log of monthly sales quantity, and our independent variables will be temperature, precipitation, calendar month, and year.

We predict a negative coefficient for temperature (temperature < 0) and a nonzero coefficient for precipitation (precipitation 0). We will use calendar month to account for seasonality and year to account for longer-term trends. We will also exclude months with missing sales records and August 2026, since that month is incomplete.

We will report the results regardless of whether they support our hypothesis.

Preregistration Statement 2: Weather and cotton-wool sales mix

Hypothesis: Cotton hats make up a larger share of sales relative to wool hats during warmer months, even after accounting for precipitation, seasonal patterns, and changes over time.

Analysis: First, we will focus on sales classified as cotton or wool. For each month, we'll calculate the proportion of cotton quantity out of the combined cotton and wool quantity.

We will exclude months where neither material has recorded sales, since the proportion would be undefined. If only one material has recorded sales, its share will be 0 or 1 accordingly.

We will then use multiple linear regression, with cotton's share as the dependent variable and temperature, precipitation, calendar month, and year as independent variables.

We expect temperature to have a positive coefficient (temperature > 0). However, since many products have unknown materials, we'll need to be careful about interpreting the results. We will report them regardless of whether they support our hypothesis.

1.2.1 Questions for reviewers and project mentor — Part 2

1. Are these two analyses sufficiently distinct, and is the cotton–wool comparison defensible given the large amount of unknown material?
2. Is log-transformed quantity with seasonal controls appropriate?
3. Is there enough weather variation after seasonal adjustment?