







- ## NOTES

1. Drawn from the parameters of model/closetpit_glazing.py: zero contours of the glazing and mask signed-distance fields on the outer mould line of model/fuselage.py (sheet L1), projected. Never from the mesh. STA = m aft of datum (3000 mm ahead of the firewall); WL above the static ground line.
2. Every edge except the centre post is a plane normal to the plane of symmetry: straight in side projection (chain-dotted construction lines). Post |BL| = 23. Corners filleted (side projection).
3. PC-12 PRO: no direct vision window, the NGX starboard single pane is used on both sides (Pilatus PRO release; photos of s/n 3001, 3010, 3036, 3066).
4. Dark mask (filled): PRO livery item, one continuous area around all four panes - roof band, centre post, lower band with a ramp to the windshield's forward corner, straight leaning aft edge ahead of the airstair door. Drawn for the MSN 3008 scheme (edge 22.5°); the aft edges vary per airframe: model/livery.py MASK_SCHEMES; Mask corner tip: low-aft 60, top-aft 40, ramp 100.
5. Windshield roof edge: its own plane (11.0°, 9 mm above the side-window top plane at STA 4000) - our crown section at STA 3900 is 5.12 mm fuller than the drawing's; so plan and front cannot both match a single plane better than -11.7° mm.

LEGEND

	glass (pane outline)
	dark mask (PRO)
	construction plane (side projection)
	airstair door seam / max-breadth W
	design eye, sight line



vs PILATUS 190.10.40.432 SHEET 1 (mm)					
PANE	VIEW	REFERENCE	RMS	MAX	WORST AT
windshield	side	ws_port	2.6	5.4	3882 / 2514
side window	side	NGX_port DV+main	5.1	13.5	3654 / 2087
side window	side	ws_sbtd plan+OML *	8.8	20.7	3905 / 2066
windshield sbtd	plan	ws_sbtd	4.4	11.4	3905 / 243
windshield port	plan	ws_port	4.4	11.3	3894 / -244
side window port	plan	ws_sbtd	5.6	11.8	3814 / 590
side window port	plan	NGX_port DV+main	6.1	12.3	3810 / -578
windshield sbtd	front	ws_sbtd	3.5	6.7	226 / 2578
windshield port	front	ws_port	3.5	6.6	-197 / 2580
side window sbtd	front	sw_sbtd	4.9	10.4	589 / 2378
side window port	front	NGX_port DV+main	4.8	13.6	-766 / 2087

Symmetric point-to-outline distance, our OML contours vs the drawn loops. * starboard pane lifted onto our OML from the plan (sill ill-conditioned; information only).


vs PHOTOS (refs/photo_notes.md)				
ITEM	PHOTOS	OURS	DRAWING / NOTE	
pillar edge angle	32-39 deg	34.8 deg	dwg 3.4-1.3.4	
A-pillar width, side (horiz.)	0.05-0.06	0.044	dwg 0.038	
side-window at top	0.2-0.11	0.087	dwg 2.087 (DWG 2.073)	
side-window at extreme STA	-0.34	4.350	dwg 4.356	
glass height	0.40-0.45 (a)	0.451	dwg 0.448	
sil length / height	1.98-2.09 (a)	1.93	dwg 1.93	
top length / height	0.71-0.85 (a)	0.66	dwg 0.66	
B radius top / bottom	0.09-0.14 / 0.09-0.17	0.110 / 0.175	dwg 0.12 / 0.21 (b)	
D straight vertical	0.15-0.19	0.097	dwg 0.06 (b)	
side-window top rise (tw2)	2-6 (a)	9.5 deg	dwg 9.5 (b)	
windshield roof rise (tw2)	-25 deg (c)	11.0 deg	dwg 10.3 deg	
centre post; glass to glass	0.08-0.14 (d)	0.046	dwg 0.046	
mask below sil	0.06-0.08	0.070	photos only	
mask ramp angle	21-27 deg	25.0 deg	photos only	
mask fwd point STA / WL	3.17 / 2.21	3.169 / 2.218	ramp meets crown	
mask at edge lean (f)	3008: 22-26 deg	22.5 deg	MSM 3008, bottom fwd	
other airframes (f)	3000: 12-16, 30306: 0		curved: glass (d)	
mask at STA WL, 2.10 / 2.40	3008: 4.385 / 4.515	4.388 / 4.513	stbd_ground cam	
mask at margin low / top	0.015-0.20	0.040 / 0.210	mask at extrim low / top	
mask top margin	0.055-0.07 (c)	0.060	normal to top edge	
mask aft to door seam, top / low	3008: 0.10 / -0.27	0.090 / 0.296	STA 4650	
other airframes (f)	3036: -0.05, vertical	-	reaches the door	

- (a) perspective: ground-level cameras sit 10'-15" below the window; the tumblehome shortens the glass height and flattens the top edge (0.448 m > 0.40-0.41 m; 9.5° > $2-6^{\circ}$).
 - (b) drawing vs photos conflict: kept 0.175 (within 15 mm of the drawing) - owner to decide.
 - (c) the side-projection slope of the windshield's outboard roof corner, not the roof plane.
 - (d) indicative only (oblique views).
 - (e) ratio to the glass height on PRO s/n 3010 / 3036 and the long-lens NGX photo (photo notes: 0-0.05).
- the result/s/n edge is a very item and offers per frame (mod/very/y MASK, S/LMES; s/n 3008 photos rectified on the OEM, (rot'd, ground / prod_hangar_130 camera); this sheet and L5 carry s/n 3008.

VISION FROM THE DESIGN EYE (ESTIMATED)	
design eye STA / BL / WL	4080 / 335 / 2360
over the nose (eye BL, ahead)	8.9° down
abeam, over the side-window sill	29.5° down
abeam, to the side-window top	40.3° up
ahead, to the windshield roof edge	54.4° up

PILATUS PC-12 PRO

COCKPIT GLAZING & PRO MASK



DWG NO	REV	SCALE	SHEET	UNITS
PC12-L2	A	1:10	A2 · 1 OF 1	mm
DRAWN				DATE
Claude - loftkit parametric model				2026-09-24

RECONSTRUCTION FROM PUBLISHED DATA - NOT FOR CONSTRUCTION