

CREW STATION - OCCUPANTS AT THEIR SETTINGS (mm)						
LEFT SEAT	95TH M	50TH M	5TH M	5TH F	NOTE	
scale of the 95th-pct links	1.00	0.94	0.88	0.82	uniform scaling [E]	
seat notch / pedal crank	+18 / -50	0 / 0	-35 / +50	-70 / +50	each picks the knee angle -120°; crank - = fwd	
seat height (vertical travel)	-51	0	+51	+51	toward the design eye, ±51	
eye vs design eye, fwd / up	-12 / 0	0 / 0	+30 / 0	+60 / -51	0 up = on it	
over the nose (deg)	7.3	7.4	7.6	4.1	to the windshield lower edge	
knee angle (deg)	118	120	121	129	neutral pedals	
knee top WL	1765	1753	1745	1701	lower panel edge 1725; grip bottoms 1805	
knee to the lower panel	36	50	51	74	side view	
legs to the yoke, pitch ±90, wings level	+38	+50	+51	+84	criterion ≥ 25; 3-D, knees on the hip-to-pedal line (pedals ±125 [M]), 95th ±126	
... with roll ±70° [E]	-19	-13	-21	+5	pitch x roll sweep; - = contact	
roll keeping 25 / to contact (deg)	5 / 18	10 / 25	10 / 22	28 / 90	full pitch travel; 90 = no contact	
FULL RUDDER ±80: up-knee top WL	1814	1798	1783	1744	the pedal that comes aft lifts that knee [E travel]	
... legs to the yoke, wings level	-11	+5	+21	+57	up-knee on the worse leg, other leg extended; full pitch sweep	
... with roll ±70°	-55	-42	-39	-16	crosswind flare: full aft, roll, opposite rudder	
... roll to contact (deg)	0	0	8	25	0 = already wings level	
extended knee, pedal full fwd (deg)	139	145	146	169	! reach limit ≤ 165° [E]; ! = beyond it	
H-point to the pedal ball	949	899	837	808	neutral pedals	
headroom (head top to lining)	155	159	156	201	at the seat BL	
shoulder room	68	81	93	118	deltoid to the sidewall lining	
headrest lock (along the back)	832	784	760	760	six positions 760-880	
headrest rear to the divider	64	92	133	168	at the occupant's notch	

CREW STATION - GENERAL (mm)			
CREW STATION	VALUE	NOTE	
design eye STA / BL / WL	4120 / 375 / 2338	the 50th-pct eye on the neutral seat: SRP + 80 fwd / 799 up; L2 used 4080/335/2360	
neutral SRP STA / WL	4200 / 1539	280 above the floor; travel ± 70 / ± 51	
occupants at the design eye	5TH M - 95TH M	5th female -51 below it at full up (over-nose 4.1"): cushion	
eye to own PFD / to MFD	766 / 799	PFD centre 29° below horizontal	
over the nose / abeam down / up	7.4° / 29° / 44°	glareshield lip 11° down: clear of the view	
aft notch: headrest to divider	+28 / +14 / +1	lowest / 50th / top lock; divider fwd face 4546	
recline room to the divider	10.5° / 5.8° / 0.8°	fwd / centre / aft notch, 50th headrest ('reclining' [S])	
seat vs the tunnel plinth	15	trimmed inboard cushion (symmetric: -30; its top only 29 above the plinth at the lowest fwd seat); plates 50	
ingress: headrests / backs / cushions	470 / 310 / 380	95th hip 415: hips pass between the headrests, legs between the backs, then over the inboard cushion with the armrest up (stowed along the back, top 772 above the floor); divider opening 500	
room behind the seat back	84 / 154	neutral / fwd notch	
curtain to seat / track; extinguisher	+23 / +11 / +61	aft notch: the stowed curtain (LH, 60 deep [E]) to the seat back below its flare top and to the crew track's aft end; the bottle to the co-pilot seat's back / plate	

REACH FROM THE NEARER SHOULDER JOINT (mm)				
TARGET	KIND	5TH F: DIST / CLASS	95TH M: DIST / CLASS	
own PFD centre	TOUCH	669 LEAN		767 LOCKED
MFD centre	TOUCH	688 LEAN		767 LOCKED
SDU, own side	TOUCH	669 LEAN		747 LOCKED
SDU, far side	TOUCH	799 LEAN		777 LOCKED
GI 275 standby	TOUCH	667 LEAN		758 LOCKED
PCL knob	GRASP	474 LOCKED		520 LOCKED
flap lever	GRASP	564 LOCKED		602 LOCKED
CCD palm grip	GRASP	575 LOCKED		594 LOCKED
overhead panel, centre	TOUCH	532 LOCKED		525 LOCKED
overhead panel, far end	TOUCH	647 LOCKED		629 LOCKED
autoland button	TOUCH	668 LEAN		628 LOCKED
CB panel, own side	TOUCH	473 LOCKED		540 LOCKED

GRASP (levers, CCD palm grip): straight arm, shoulder joint to thumbtip 740 (95th; 5th F 607), from the thumbtip reach 870 less the back-wall offset.
TOUCH (touch screens, push-buttons, switches, breakers): + 70 to the index fingertip [E] (810 / 664). LOCKED: within it, harness locked; LEAN: within +200 with the inertia reel unlocked (normal in flight); NO: beyond.

KNEE vs YOKE - SENSITIVITY TO THE ESTIMATED INPUTS (OPEN POINT 1)								
INPUT (vs as set)	95TH NOTCH / CRANK	95 CONTACT	95 RUDDER mm / CONTACT	50TH NOTCH / CRANK	50 CONTACT	50 RUDDER mm / CONTACT	EXT. KNEE 95 / 50 / 5F	HEAD TO DIVIDER
as set	+18 / -50	18°	-11 / 0°	0 / 0	25°	+5 / 0°	139° / 145° / 169°!	+1
pedals +/-90 (rev B [E])	+18 / -50	18°	-7 / 0°	0 / 0	22°	+9 / 2°	139° / 145° / 169°!	+1
knees 30 wider (splay +30)	+18 / -50	79°	-4 / 0°	0 / 0	35°	+10 / 5°	139° / 145° / 169°!	+1
knee target 130 deg (120)	+53 / -50	80°	+8 / 2°	+18 / -25	none	+27 / 12°	154° / 173°! / 169°!	+1
SRP 35 alt	+18 / -25	22°	-6 / 0°	-18 / +25	22°	+2 / 0°	143° / 142° / 180°!	-34
SRP 70 alt	0 / 0	18°	-9 / 0°	-35 / +25	28°	+10 / 2°	140° / 149° / 180°!	-69
rudder travel +/-60 (80)	+18 / -50	18°	0 / 0°	0 / 0	25°	+15 / 5°	133° / 137° / 153°	+1
rudder travel +/-100 (80)	+18 / -50	18°	-20 / 0°	0 / 0	25°	-3 / 0°	147° / 154° / 180°!	+1
yoke hub 50 higher	+18 / -50	none	+39 / 18°	0 / 0	none	+55 / 30°	139° / 145° / 169°!	+1

Left seat. Each row changes one input from the as-set state; every occupant then re-picks notch and crank (knee ~120° rule, least travel). CONTACT: yoke roll (full pitch travel) at which a knee first touches a grip, neutral pedals. RUDDER: the up-knee on the pedal that came aft, other leg extended: wings-level clearance / roll to contact; none = no contact to 90°. EXT. KNEE: at full forward rudder, != beyond 165° [E]. HEAD TO DIVIDER: aft notch, top headrest lock.

NOTES (SHEET L6)

1. Sheet L6 is drawn from the parameter tables of model/interior.py and the fuselage, openings and glazing parameters (L1-L3), never from the mesh. Each value carries a source tag: [S] sourced, [M] measured from photos / renders, [E] estimated, [H] hard constraint.
2. Seat stations: POH NGX Report 02406 weight-and-balance occupant arms (POH datum = model datum). EX-6S-2 is the PRO standard 6-seat layout: aft-peco club pair, forward-facing club pair, staggered aft pair, forward RH lavatory.
3. Crew seat: iFLECO 3A318-type, travel ± 70 in 9 holes (POH), vertical ± 51 (est.). Design eye = the 50th-pct eye on the neutral seat = SRP + 80 fwd / 799 up; the 95th (seat down) and 5th male (seat up) reach it. Accommodated range at the design eye as drawn: 5th male - 95th male; the 5th female sits 51 below it (open point 2).
4. Manikins: 95TH-PCT MALE (ANSUR II) (stature 1870, sitting height 975, eye 850), scaled uniformly for the 50th / 5th male and 5th female. Crew: each sets seat height, notch and pedal crank (knee angle $\sim 120^\circ$); feet on the pedals, hands on the grips, knees on the hip-to-pedal line (pedals ± 125 [M]); full rudder moves one pedal 80 forward and the other as far aft. Cabin: upright, outboard (TTL), feet flat under the knees unless noted. Sections A-A / B-B draw what lies forward of the cut (legs, hands) in phantom.
5. Seat tracks: surface-mounted, 12 cabin / 18 crew [E], over the carry-through too; the seat heights include them.
6. Lining: headliner 40 below the OML at the crown, sidewall 85, giving the published 1.52×1.47 cabin; floor WL 1259 flush from the pedals to the baggage wall. The pedestal stands on a carpeted plinth over the nose-wheel tunnel (gear, hard).
7. Stage 2 only: the 3-D interior is still rev A and is rebuilt from these tables after the owner's review.

CABIN CHECKS (mm), 95TH-PCT MALE UNLESS NOTED			
CABIN (EX-6S-2)	VALUE	NOTE	
cabin length (divider -> aft wall)	5160	5160 published	
cabin width (lining, max breadth)	1518	1520 published	
cabin height (floor -> headliner, CL)	1470	1470 published (POH 1450)	
floor width (carpet) / between linings	1300 / 1382	1300 published	
floor length (divider -> FR34)	4679	4680 POH	
aisle between armrests / cushions	300 / 300	seats fully outboard (TTL); one arm per seat, inboard; cushion to the ledge 45	
club: cushion fronts / 95th knees	534 / 99	PAX 1 -> PAX 3; POH-mirror PAX 1: 642	
club: 95th toes pass each other	424	feet interleave: PAX 3 at CL ±105, PAX 1 ±225; outer foot -30 to the kick panel	
pitch PAX 3 -> 5, stagger 5 -> 6	1169 / 305	POH	
headroom 95th: outboard / inboard	40 / 85	seat slid inboard 91 [S]	
shoulder room 95th: out / in	+7 / +98	deltoid to the sidewall lining	
headrest (raised) top over head centre	-16 / +35	95th / 50th: the 95th's head centre is above the headrest; it supports the 50th	
seated eye WL 95th / 50th	2462 / 2412	window 1995-2380: eyes above the window top (no seated photo to test)	
club table underside vs the legs, 95 / 50 / 5M / 5F	-45 / -8 / +27 / +58	top 590 (20 under the ledge cap [M]), feet under the knees: the legs (CL ±105) are under the top; outboard leaf alone: -45 / -8 / +27 / +58	
table: shank angle for 25 / toes to the facing base	28° / +6	50th with the feet forward: fits; 95th needs 38° and his feet 125 under the facing seat's base: does not fit (decision + open point)	
recline reached PAX 1 / 2 / 3 / 4 / 5 / 6	45 / 42 / 33 / 45 / 45 / 38	deg from vertical, of 45 [E]; limits: 2: lavatory, 3: PAX 5, 6: FR34 partition	
PAX 6 back to FR34 / PAX 1 to cabinet	295 / 87	upright, at the floor	
exit hatch clear of the PAX 2 cushion	204	of 482; sill 622 above the floor	
lavatory: 95th knees past the door line	226	facing inboard on the toilet (back at the lid hinge); lav 624 x 492: doors cannot close	
lav: floor in front of the cabinet	72	cabinet 365 deep [E] to the bi-fold line (P1046411 shows carpet there)	
lav bi-folds to the entry zone	435	fold out <= 125; entry zone [BL] > 300	

DEVIATIONS & DECISIONS	
ITEM	DEVIATION / DECISION (vs the references and rev B)
yoke grips (r2)	built from the measured span 285: grips 140 long from -40 below the hub centre, tops 10° inboard (JTF key, P1046408); rev B: 15° outboard from the hub centre, span unused
DECISION: yoke vs knees	keep the measured hub, grips and pedals: the 95th's knee meets a grip from 18° roll (neutral pedals). The outcome depends on the estimated inputs more than on the measured ones (sensitivity table): the owner is asked which input to fix, open point 1
pedals (r3)	±125 centres, 125 pads, measured face-on (P1046408, MFD bezel scale + depth correction); rev B ±90 / 80 [E]. The crew knees sit on the hip-to-pedal line + 15 splay: 95th ±126 (rev B ±105)
crew SRP vs POH arm (r3)	SRP kept at 4200: the POH arm 4071 is the 50th's CG with the seat full aft (CG table); 60-85 further aft would put the aft-notch headrest as far into the divider and off the render's cushion front 3720 [M]
seat tracks (r3)	surface-mounted 12 [E] over the whole cabin floor (crew 18): over the carry-through the floor is <= 15 [H], too thin for a flush 20-25 track; local channels in the spar cap would need the structure (not modelled). The cabin seat heights [M] are read from the carpet and include the track; the seat bases stand on the tracks (B-B)
lavatory (r3)	cabinet 350 tall [M] (0.33 ring as scale; r2 450 [E]), niche 440-640 [M]; the lower seat puts the 95th's knees 226 past the door line
divider (r3)	curtain drawn: track at the headliner, bundle stowed LH (PRO 3001, orange; NGX 2281 stows a grey one RH); fire extinguisher on the RH divider's fwd face (plan); autoland cap (A-A)
SDUs (r2)	top -130 vs the MFD centre (10-20 under the MFD bezel), reclined 35° (JTF, camera-matched P1046406, P1046408); drawn 156 tall in view D; rev B -170 / 20°
cabin seat arms (r2)	one armrest, inboard: a deep side panel (base top to 435) with the seat control on its forward end; the 610 leg is the outboard armrest; rev B drew two arms
lavatory (r2)	cabinet wall to wall 4600-5165, bowl at the POH arm 4831, shelf + drawer aft of 5040, lit niche, TP holder (P1046411); depth 365 [E]; rev B 400 x 450 box
DECISION: club table	keep the measured table (top 590, outboard leaf + unfolding inboard leaf); up to the 50th fits (feet fwd 28"); the 95th does not (-45): open point 3
full rudder (r2)	pedal travel ±80 [E] and the toe brake added; the knee checks pose the up-knee on the aft pedal and the extended leg on the forward one
reach (r2)	grasp vs touch: touch targets get the 70 fingertip; the 95th reaches the PDUs and SDUs harness locked
crew armrest hinge (r2)	in the back's thickness, stowed along the back side; rev B hinged it 125 ahead of the back
PAX 1/2 aft-facing club PAX 5 (LH aft)	render footprint used: 108 aft of the POH-occupant mirror POH 1810 used; the marketing plan render shows it 180 fwd
LH cabinet	moved +56 aft of the render (5244) to clear the airstair opening
design eye	4120/375/2338 = the 50th eye on the neutral seat; replaces 3980 (info) and 4080/335/2360 (L2); over-nose 7.4° vs 8.7°
vs rev A (legacy 3-D)	crew seat BL 375 (335; yoke key 372), SRP 280 above the floor (300), vertical ±51 (+40), back 13° (11"), inboard cushion 185 (tunnel plinth); flight-deck floor flush 1259 (1240 + 19 step); MFD WL 2000 (1960; notes 1830; cabin-photo check 2010 ±50); hood closed onto the WS frame (plate 80-150 below); CB panels on the sidewall above the consoles (below them); FR34 pressure header + curtain (net), aft wall 9731 = divider + 5160 (FR36 9750, render 9744)

OPEN POINTS FOR THE OWNER

- KNEES vs YOKE: WHICH INPUT TO FIX? With the measured hub, grips and pedals (grip bottoms WL 1805, pedals ±125), the 95th's knee meets a grip from 18" roll with neutral pedals (50th 255"); with full rudder the 95th's touches it wings level (-11) and the 50th from 0°. The estimated inputs move this more than the measured ones (sensitivity table): knees 30 wider → 95th neutral-contradict 70°; a 130° knee target (seat further aft) → 80°, full rudder +8, but the 50th's forward rudder needs 173° (> 165°); the hub 50 higher → none, full-rudder contact from 18". Please choose what to pin down: the seat-setting rule (knee target), the knee spacing, the rudder travel, the hub height, or the roll travel / a roll limit. Wanted: the control-wheel roll and rudder travel (AMM / POH) and a side-on photo of a seated pilot at the yoke.
- 5TH-FEMALE ACCOMMODATION. At the forward notch, pedals cranked fully aft and the seat full up (+51, the travel limit [E]), her eye is 51 below the design eye: over the nose 4.1" along her BL (design eye 7.4"), 2.2" along BL 200; full forward rudder straightens her knee to 169° (limit 165° [E]); a 5 ft 2 in pilot, scale 0.84: 150"). As drawn the station accommodates 5th male - 95th male. Options: a booster cushion, more vertical travel (the IPECCO 3A1818 figure is wanted; ±51 is [E]), or state the range as 5M-95M.
- CLUB TABLE. Deployed (top 590, under the ledge cap), the 95th's knees are 45 into it and the 50th's 8 with the feet under the knees (the outboard leaf alone: the same, the outboard leg is under it). The 50th fits with the feet 28" forward (toes 6 short of the facing seat's base); the 95th would need 38" and put his feet 125 under it. Kept: the table serves up to about the 50th. Confirm, or re-measure the table / ledge height.
- Aft-facing club PAX 1/2: plan render (used) or POH-occupant mirror? The render leaves 204 of the 482 exit hatch clear of the PAX 2 cushion; the mirror gives a 642 club gap (render 534, 95th toes pass 424).
- Design eye 4120 / 375 / 2338 (over-nose 7.4") to replace cockpit_glazing.EYE (L2) and the viewer camera.
- Tunnel plinth (gear, 350 wide, 226 tall to STA 4120): the crew cushions are trimmed to 185 inboard to clear it; the photos show symmetric cushions and no step at the pedestal foot. Can the tunnel end or drop?
- Lavatory: cabinet wall to wall, 365 deep [E], leaves 72 of floor to the bi-fold line (BL 260); a seated 95th's knees still reach 226 past it. Door line / cabinet depth to confirm.
- Cabin seated eye above the window top (95th 2462, 50th 2412 vs 2380): a seated-passenger photo from 18" test the cushion 420 / SRP 360 (the windows are fixed by L3).
- Crew SRP 4200 vs the POH pilot arm 4071: the 50th's CG is -63 from it at the centre notch and -1 with the seat full aft, so the POH arm is read as a full-aft value and the SRP is kept (the aft-notch headset is already at the divider). Confirm the POH arm convention; crew seat vertical travel (±51 est.-alt), back / headset heights (side-on photo), MFO WL; interior scheme and cabin height 1.47 vs 1.45.

REVISIONS - PC12-L6		
REV	DATE	DESCRIPTION
A	-	first issue (legacy 3-D interior)
B	2026-09-24	Stage-2 parameter tables, checks; review r1
C	2026-09-26	review r2 + r3 (list on sheet 1): sensitivity, CG cross-check, 5th-female point
D	2026-09-26	Stage-3 review r2: sheepskin in the crew outline, yoke grips, curtain / track

KEY PARAMETERS ([S] SOURCED [M] MEASURED [E] ESTIMATED [H] HARD)			
PARAMETER	VALUE	SOURCE NOTE (model/interior.py)	
crew SRP STA (centre notch)	4200	[E] SRP, centre notch: render cushion front 3.72 / headrest rear 4.47 [M]; the divider bounds it aft. POH occupant arm 4.071 = the 50th's CG with the seat full aft (L6B cross-check)	
crew seat BL	375	[M] yoke centres +/-0.372 (Pilatus PRO cockpit key); plan render seat CL +/-0.37-0.39	
crew SRP above the floor	280	[E] SRP above the flight-deck floor, neutral height (notes: 0.28-0.30); puts the seat-back top corner on the cabin photo's 0.86-0.90 above the floor (P1046406)	
crew seat travel +/-	70	[S] POH Table 6-5-3: +/-4 holes x 0.69 in (0.018 m)	
crew seat vertical +/-	51	[E] vertical adjustment +/-2 in (POH 7-7-1.1 vertical leverage; IPECO travel not found); the 95th-pct male (full down) and the 5th-pct male (full up) both reach the design eye	
crew back angle	13°	[E] upright back angle from vertical: puts the headrest rear (50th position) on the render's 4.47 at the centre notch (notes: 13-15 deg)	
crew cushion inboard	185	[E] inboard half-width of pan + cushion: trimmed from 0.23 so the seat clears the nose-tunnel plinth (gear, hard) by 15 over the whole x / z travel; photos: symmetric	
crew armrest hinge	-30	[E] armrest hinge on the backrest side, this far behind the back line at the hinge height: between the back's front (+0.035) and rear (-0.10) faces (IPECO line art: the armrests hinge on the back and flip up along its side); rev B had it 0.16 AHEAD of the back line	
PDU glass STA	3500	[M] PDU glass 1.09-1.13 m ahead of the divider camera (PRO 3001 face-on photo, 12 mm lens)	
MFD centre WL	2000	[M] MFD centre: cabin-camera cross-check 2.01 +/- 0.05 (P1046406, camera 0.73 above the floor, MFD 3.5 m away); hood from the windshield frame to the lip 0.24-0.26 above it [M]	
SDU top vs MFD centre	-130	[M] SDU bezel top 10-20 below the MFD bezel foot (1.885); JTF p.18 elevation on MFD 2.00 gives 1.873-1.732, camera-matched P1046406 1.868-1.710, P1046408 agrees (rev B: -0.170)	
SDU recline	35°	[M] SDU face from vertical: a level camera (P1046406) sees 0.158 of the 0.19 bezel, the face-on camera (above the stack) -0.19 -> -35 deg (rev B: 20 [E])	
yoke hub vs MFD centre	-155	[M] hub centre 0.15-0.17 below the MFD centre	
yoke grips overall	285	[M] grips overall, outer edge to outer edge at their bottoms (JTF cockpit key, P1046408 with the 0.14 hub for scale); PC-24-style yoke [S]	
grip length / r / cant	140 / 16 / 10°	[M] grip length tip to tip, radius, cant from vertical with the TOPS INBOARD (JTF key: tops +/-0.10, bottoms +/-0.125 from the hub CL; P1046408 -8 deg); review r2 F2 (P1046408 pair: slim paddles 55 px against the render's 70 px, rising well above the hub); radius 0.020 -> 0.0155, length 0.125 -> 0.140 (the tops 15 mm higher)	
grip bottoms vs hub	-40	[M] grip bottoms 0.04 below the hub centre, near the hub bottom (JTF key: grips WL 1.80-1.93 on hub 1.79-1.90; P1046408 -0.05,-+0.09); tops -0.04 above the hub top (P1046408)	
yoke roll +/-	70°	[E] roll travel each way (PC-12 figure not found); the knee check sweeps it	
pedal heel point STA	3360	[M] heel point on the floor (plan render pedal gear 3.04-3.31, neutral crank)	
rudder pedal travel +/-	80	[E] rudder travel at the pad each way: full rudder pushes one pedal 0.08 forward and lets the other come 0.08 aft (PC-12 figure not found; typical 3-3.5 in)	
pedestal top above floor	300	[M] aft face -0.30-0.32 tall above the floor with FUEL / ACS T-handles (P1046406)	
divider aft face	4571	[S] POH seat charts 'divider aft surface' 179.95 in (render 4.571-4.583; FR16 4.590)	
cabin seat BL	400	[M] plan render seat CL +/-0.40 (fully outboard for TTL [S placard]; outer arm at the ledge)	
cabin seat length	705	[M] plan render, upright: back rear to cushion front	
cabin seat arm	60	[M] ONE armrest, on the aisle side (sliding [S]); no outboard arm: the 0.61 ledge is the outboard armrest (Pilatus plan + front renders, P1046402 / 05 / 06; legacy POH 7-28 'sidewall armrests')	
cabin SRP above floor	360	[E] SRP above the floor	
ledge top above the floor	610	[M] section render: ledge top above the floor (cup holders, USB, table slot)	
club table top	590	[M] slides out from under the ledge cap (0.61) and unfolds: top just below the ledge top (brochure p.18, P1046405, P1046406)	
club table outboard leaf	290	[M] the outboard leaf slides out of the ledge first (P1046404 / 05 show it alone); the inboard leaf unfolds over the aisle (brochure p.18)	
lav cabinet x0 x1 d h	4600 / 5165 / 365 / 350	[M] gloss-veneer cabinet wall to wall (P1046411): x0, x1 [M] (x1 = aft wall - 0.030); depth [E] 0.35-0.38 (carpet between its foot and the door jambs); height [M] 0.32-0.36, the 0.33 seat ring as scale (P1046411, lav teaser; r2 0.45)	
FR34 partition	9250	[S] FR34: POH floor length 4.68 from the divider; render 9.244	
sidewall lining	75	[H] OML - 0.085 gives the published 1.52 max width (L1 SIDE_ALLOW; render lining +/-0.755)	
touch reach allowance	80	[E] thumbtip (grasp) to index fingertip (touch): push-buttons and the G3000 PRIME touch screens are reached -0.07 further than a grasped lever	
extended-knee limit	165°	[E] extended leg at full forward rudder: knee angle <= 160-165 deg (reach limit)	
pedal centres +/-	125	[M] pedal-pad centres at seat CL +/- (P1046408 face-on: 0.24-0.26 apart, MFD-bezel scale + depth correction, the grip span checks it); rev B 0.09 [E]	
cabin seat track height	12	[E] cabin tracks surface-mounted (low profile, carpet butted) over the whole floor: over the carry-through the floor is <= 15 mm [H], too thin for a flush -20-25 track (L6B); the cabin seat heights [M] are read from the carpet and include it	

OTHER POH LAYOUTS (DATA ONLY)				
LAYOUT	SIDE	OCCUPANT ARMS (POH), FWD -> AFT		
EX-8S	LH	5899	7611	7824 8637
	RH	5899	7611	7824 8637
STD-9S	LH	5343	6181	7019 7857
	RH	5267	6105	6943 7781 8619

POH OCCUPANT ARMS vs THE OCCUPANT CG (mm)				
SEAT (50TH-PCT MALE)	POH ARM	SRP STA	CG STA	CG - POH
PILOT, centre notch	4071	4200	4008	-63
PILOT, full aft	4071	4270	4070	-1
PAX 1 (aft-facing)	5899	5827	5986	+87
PAX 2 (aft-facing)	5899	5827	5986	+87
PAX 3 (fwd-facing)	7011	7191	7032	+21
PAX 4 (fwd-facing)	7011	7191	7032	+21
PAX 5 (fwd-facing)	8180	8360	8201	+21
PAX 6 (fwd-facing)	8485	8665	8506	+21

Method: Dempster (1955) segment-mass fractions and segment CG locations (Winter's table) on the sheet's 50th-cpt poses, both limbs alike.
 Forward-facing cabin seats +21, +21: the method agrees with the POH to ~2 cm. Pilot: -63 at the centre notch but -1 with the seat full aft, so the POH crew arm reads as a full-aft value (conservative for the aft CG); the SRP stays at 4200 (the divider bounds it: open point 9). Aft-facing PAX 1/2: the plan-render footprint (open point 4).

PILATUS PC-12 PRO					
INTERIOR ARRANGEMENT - CHECKS & PARAMETERS					
DWG NO	REV	SCALE	SHEET	UNITS	
PC12-L6	D	-	A1 · 2 OF 2	mm	
DRAWN				DATE	
Claude - loftkit parametric model				2026-09-26	
RECONSTRUCTION FROM PUBLISHED DATA - NOT FOR CONSTRUCTION					