INTRODUCTION TO



Table of Contents

About the book	8
About the author	9
Sponsors	10
Ebook PDF Generation Tool	12
Book Cover	13
License	14
Databases	15
Tables and columns	16
MySQL	18
Installing MySQL	19
Accessing MySQL via CLI	21
Creating a database	22
Configuring .my.cnf	23
The mysqladmin command	24
GUI clients	25
Tables	26
Data types	27
Creating a database	28
Creating tables	30
Rename tables	32
Dropping tables	33
Allowing NULL values	34
Specifying a primary key	35

	Index Optimization for Database Queries	36
	Updating tables	38
	Truncate table	40
Pac	ic Syntay	41
Das	ic Syntax	
	INSERT	
	SELECT	
	UPDATE	
	DELETE	
	Comments	
	Conclusion	49
SEL	.ECT	50
	SELECT all columns	52
	Pattern matching	
	Formatting	
	SELECT specific columns only	
	SELECT with no FROM Clause	
	SELECT with Arithmetic Operations	
	LIMIT	
	COUNT	
	MIN, MAX, AVG, and SUM	
	DISTINCT	
	Conclusion	
	Conclusion	00
WH	ERE	67
	WHERE Clause example	68
	Operators	70
	AND keyword	71
	OR keyword	72

- y

LIKE operator	73
IN operator	74
IS operator	75
BETWEEN operator	76
Conclusion	77
Sorting with ORDER and GROUP BY	78
ORDER BY	79
GROUP BY	
HAVING Clause	83
INSERT	84
Inserting multiple records	86
Inserting multiple records using another table	87
UPDATE	88
Updating records using another table	91
DELETE	92
Delete from another table	94
JOIN	95
CROSS JOIN	98
INNER JOIN	100
LEFT JOIN	103
RIGHT JOIN	104
The Impact of Conditions in JOIN vs. WHERE Clauses	106
Equivalence of RIGHT and LEFT JOINs	108
Conclusion	109

SQL DDL, DQL, DML, DCL and TCL Commands 110
SQL Sub Queries
SQL - UNIONS CLAUSE
Relational Keys- Keys in a Relational Database 123
Types of Relational Keys 124
Logical Operator Keywords 127
HAVING Clause
Syntax 129
Description
Aggregate Functions
Aggregate Functions Examples
Having clause Examples13!
Essential MySQL Functions
Numeric Functions
STRING Functions
DATE Functions
Formatting Dates and Times
Calculating Dates and Times
Triggers In SQL
Example:

Transaction Control Language	151
TCL Commands	152
COMMIT	153
ROLLBACK	154
SAVEPOINT	155
Examples	156
Conclusion	160
Data Control Language	161
DCL Commands	162
GRANT	
REVOKE	164
Conclusion	168
The MySQL dump command	169
Exporting a Database	170
Exporting all databases	171
Automated backups	
Conclusion	175
Learn Materialize by running streaming SQL on your nginx lo	gs
	176
Prerequisites	177
What is Materialize	178
Installing Materialize	170

.

Installing mzcli	
Installing nginx	181
Adding a Materialize Source	182
Creating a Materialized View	184
Reading from the view	186
Conclusion	189
Conclusion	190
Other eBooks	191
SOI Injection A Paginner's Understanding	102
SQL Injection — A Beginner's Understanding	
☐ Table of Contents	
1. What is SQL Injection?	
2. Why it matters (risks & impact)	
3. High-level types of SQLi (conceptual)	
4. How SQLi happens — a conceptual example	197
5. Vulnerable vs. secure code (safe examples)	198
6. Top prevention techniques (practical, prioritized)	200
7. Detection, logging, and monitoring	202
8. Secure coding checklist (practical, copyable)	203
9. Responsible testing and legal/ethical notes	204
10. Learning resources & next steps	205
☐ Quick Takeaway	
☐ Additional Resources	

About the book

• This version was published on October 13,2021

This open-source introduction to SQL guide will help you learn the basics of SQL and start using relational databases for your SysOps, DevOps, and Dev projects. Whether you are a DevOps/SysOps engineer, developer, or just a Linux enthusiast, you will most likely have to use SQL at some point in your career.

The guide is suitable for anyone working as a developer, system administrator, or DevOps engineer who wants to learn the basics of SQL.

About the author

My name is Bobby Iliev, and I have been working as a Linux DevOps Engineer since 2014. I am an avid Linux lover and supporter of the open-source movement philosophy. I am always doing that which I cannot do in order that I may learn how to do it, and I believe in sharing knowledge.

I think it's essential always to keep professional and surround yourself with good people, work hard, and be nice to everyone. You have to perform at a consistently higher level than others. That's the mark of a true professional.

For more information, please visit my blog at https://bobbyiliev.com, follow me on Twitter obobbyiliev and YouTube.

Sponsors

This book is made possible thanks to these fantastic companies!

Materialize

The Streaming Database for Real-time Analytics.

<u>Materialize</u> is a reactive database that delivers incremental view updates. Materialize helps developers easily build with streaming data using standard SQL.

DigitalOcean

DigitalOcean is a cloud services platform delivering the simplicity developers love and businesses trust to run production applications at scale.

It provides highly available, secure, and scalable compute, storage, and networking solutions that help developers build great software faster.

Founded in 2012 with offices in New York and Cambridge, MA, DigitalOcean offers transparent and affordable pricing, an elegant user interface, and one of the largest libraries of open source resources available.

For more information, please visit https://www.digitalocean.com or follow @digitalocean on Twitter.

If you are new to DigitalOcean, you can get a free \$100 credit and spin up your own servers via this referral link here:

Free \$100 Credit For DigitalOcean

DevDojo

The DevDojo is a resource to learn all things web development and web design. Learn on your lunch break or wake up and enjoy a cup of coffee with us to learn something new.

Join this developer community, and we can all learn together, build together, and grow together.

<u>Join DevDojo</u>

For more information, please visit https://www.devdojo.com or follow othedevdojo on Twitter.

Ebook PDF Generation Tool

This ebook was generated by <u>Ibis</u> developed by <u>Mohamed Said</u>.

Ibis is a PHP tool that helps you write eBooks in markdown.

Book Cover

The cover for this ebook was created with <u>Canva.com</u>.

If you ever need to create a graphic, poster, invitation, logo, presentation – or anything that looks good — give Canva a go.

License

MIT License

Copyright (c) 2020 Bobby Iliev

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Databases

Before we dive deep into SQL, let's quickly define what a database is.

The definition of databases from Wikipedia is:

A database is an organized collection of data, generally stored and accessed electronically from a computer system.

In other words, a database is a collection of data stored and structured in different database tables.

Tables and columns

You've most likely worked with spreadsheet systems like Excel or Google Sheets. At the very basic, database tables are quite similar to spreadsheets.

Each table has different **columns** which could contain different types of data.

For example, if you have a todo list app, you would have a database, and in your database, you would have different tables storing different information like:

- Users In the users table, you would have some data for your users like: username, name, and active, for example.
- Tasks The tasks table would store all of the tasks that you are planning to do. The columns of the tasks table would be for example, task_name, status, due_date and priority.

The Users table will look like this:

Rundown of the table structure:

- We have 4 columns: id, username, name and active.
- We also have 3 entries/users.
- The id column is a unique identifier of each user and is autoincremented.

In the next chapter, we will learn how to install MySQL and create our first database.

MySQL

Now that you know what a database, table, and column are, the next thing that you would need to do is install a database service where you would be running your SQL queries on.

We will be using MySQL as it is free, open-source, and very widely used.

Installing MySQL

Depending on your operating system, to install MySQL run the following commands.

Install MySQL on Ubuntu

To install MySQL on a Linux or Ubuntu machine, run the following commands:

• First update your apt repository:

```
sudo apt update -y
```

• Then install MySQL:

```
sudo apt install mysql-server mysql-client
```

We are installing two packages, one is the actual MySQL server, and the other is the MySQL client, which would allow us to connect to the MySQL server and run our queries.

To check if MySQL is running, run the following command:

```
sudo systemctl status mysql.service
```

To secure your MySQL server, you could run the following command:

```
sudo mysql_secure_installation
```

Then follow the prompt and choose a secure password and save it in a secure place like a password manager.

With that, you would have MySQL installed on your Ubuntu server. The above should also work just fine on Debian.

Install MySQL on Mac

I would recommend installing MySQL using Homebrew:

brew install mysql

After that, start MySQL:

brew services start mysql

And finally, secure it:

mysql_secure_installation

In case that you ever need to stop the MySQL service, you could do so with the following command:

brew services stop mysql

Install MySQL on Windows

To install MySQL on Windows, I would recommend following the steps from the official documentation here:

https://dev.mysql.com/doc/refman/8.0/en/windows-installation.html

Accessing MySQL via CLI

To access MySQL run the mysql command followed by your user:

mysql -u root -p

Creating a database

After that, switch to the demo database that we created in the previous chapter:

```
USE demo;
```

To exit the just type the following:

```
exit;
```

Configuring .my.cnf

By configuring the ~/.my.cnf file in your user's home directory, MySQL would allow you to log in without prompting you for a password.

To make that change, what you need to do is first create a .my.cnf file in your user's home directory:

```
touch ~/.my.cnf
```

After that, set secure permissions so that other regular users could not read the file:

```
chmod 600 ~/.my.cnf
```

Then using your favourite text editor, open the file:

```
nano ~/.my.cnf
```

And add the following configuration:

```
[client]
user=Y0UR_MYSQL_USERNAME
password=Y0UR_MYSQL_PASSWORD
```

Make sure to update your MySQL credentials accordingly, then save the file and exit.

After that, if you run just mysql, you will be authenticated directly with the credentials that you've specified in the ~/.my.cnf file without being prompted for a password.

The mysqladmin command

As a quick test, you could check all of your open SQL connections by running the following command:

mysqladmin proc

The mysqladmin tool would also use the client details from the ~/.my.cnf file, and it would list your current MySQL process list.

Another cool thing that you could try doing is combining this with the watch command and kind of monitor your MySQL connections in almost real-time:

watch -n1 mysqladmin proc

To stop the watch command, just hit CTRL+C

GUI clients

If you prefer using GUI clients, you could take a look a the following ones and install them locally on your laptop:

- MySQL Workbench
- <u>Sequel Pro</u>
- TablePlus

This will allow you to connect to your database via a graphical interface rather than the mysql command-line tool.

If you want to have a production-ready MySQL database, I would recommend giving DigitalOcean a try:

Worry-free managed database hosting

Tables

Before we get started with SQL, let's learn how to create tables and columns.

As an example, we are going to create a users table with the following columns:

- id this is going to be the primary key of the table and would be the unique identifier of each user.
- username this column would hold the username of our users.
- name here, we will store the full name of users.
- status here, we will store the status of a user, which would indicate if a user is active or not.

You need to specify the data type of each column.

In our case it would be like this:

- id Integer
- username Varchar
- name Varchar
- status Number

Data types

The most common data types that you would come across are:

- CHAR(size): Fixed-length character string with a maximum length of 255 bytes.
- VARCHAR(size): Variable-length character string. Max size is specified in parenthesis.
- TEXT(size): A string with a maximum length of 65,535 bytes.
- INTEGER(size) or INT(size): A medium integer.
- BOOLEAN or BOOL: Holds a true or false value.
- DATE: Holds a date.

Let's have the following users table as an example:

- id: We would want to set the ID to INT.
- name: The name should fit in a VARCHAR column.
- about: As the about section could be longer, we could set the column data type to TEXT.
- birthday: For the birthday column of the user, we could use DATE.

For more information on all data types available, make sure to check out the official documentation <u>here</u>.

Creating a database

As we briefly covered in the previous chapter, before you could create tables, you would need to create a database by running the following:

• First access MySQL:

```
mysql -u root -p
```

• Then create a database called demo db:

```
CREATE DATABASE demo_db;
```

Note: the database name needs to be unique, if you already have a database named demo_db you would receive an error that the database already exists.

You can consider this database as the container where we would create all of the tables in.

Once you've created the database, you need to switch to that database:

```
USE demo_db;
```

You can think of this as accessing a directory in Linux with the cd command. With USE, we switch to a specific database.

Alternatively, if you do not want to 'switch' to the specific database, you would need to specify the so-called fully qualified table name. For example, if you had a users table in the demo_db, and you wanted to select all of the entries from that table, you could use one of the

following two approaches:

• Switch to the demo_db first and then run a select statement:

```
USE demo_db;
SELECT username FROM users;
```

 Alternatively, rather than using the USE command first, specify the database name followed by the table name separated with a dot: db_name.table_name:

```
SELECT username FROM demo_db.users;
```

We are going to cover the **SELECT** statement more in-depth in the following chapters.

Creating tables

In order to create a table, you need to use the CREATE TABLE statement followed by the columns that you want to have in that table and their data type.

Let's say that we wanted to create a users table with the following columns:

• id: An integer value

• username: A varchar value

about: A text typebirthday: Date

• active: True or false

The query that we would need to run to create that table would be:

```
CREATE TABLE users
(
    id INT,
    username VARCHAR(255),
    about TEXT,
    birthday DATE,
    active BOOL
);
```

Note: You need to select a database first with the USE command as mentioned above. Otherwise you will get the following error: `ERROR 1046 (3D000): No database selected.

To list the available tables, you could run the following command:

```
SHOW TABLES;
```

30

This is a sample from "Introduction to SQL" by Bobby Iliev.

For more information, <u>Click here</u>.