

Question 1 of 63



Choose 1 option.

Given the code below:

```
const copy = JSON.stringify([new String('false'), new Boolean(false), undefined]);
```

What is the value of `copy`?

- ☐ A. `'[false, {}]'`
- ☐ B. `'["false", false, undefined]'`
- ☒ C. `'["false", false, null]'`
- ☐ D. `'["false", {}]'`

Question 2 of 63



Choose 1 option.

A developer needs to debug a Node.js web server because a runtime error keeps occurring at one of the endpoints.

The developer wants to test the endpoint on a local machine and make the request against a local server to look at the behavior. In the source code, the `server.js` file will start the server. The developer wants to debug the Node.js server only using the terminal.

Which command can the developer use to open the CLI debugger in their current terminal window?

- ☒ A. `node inspect server.js`
- ☐ B. `node start inspect server.js`
- ☐ C. `node server.js --inspect`
- ☐ D. `node -i server.js`

Question 3 of 63



Choose 1 option.

A developer tries to retrieve all cookies, then sets a certain key value pair in the cookie. These statements are used:

```
01 document.cookie;  
02 document.cookie = 'key=John Smith';
```

What is the behavior?

- ☒ A. Cookies are read and the key value is set, the remaining cookies are unaffected.
- ☐ B. Cookies are read, but the key value is not set because the value is not URL encoded.
- ☐ C. Cookies are not read because line 01 should be `document.cookies`, but the key value is set and all cookies are wiped.
- ☐ D. Cookies are read and the key value is set, and all cookies are wiped.

Question 4 of 63

Choose 3 options.

Which three actions can be done using the JavaScript browser console?

- ☒ A. View and change the DOM of the page.
- ☒ B. Run code that is not related to the page.
- ☒ C. View, change, and debug the JavaScript code of the page.
- ☐ D. Display a report showing the performance of a page.
- ☐ E. View and change security cookies.

Question 5 of 63



Choose 2 options.

What are two unique features of functions defined with a fat arrow as compared to normal function definition?

- ☐ A. The function receives an argument that is always in scope, called `parentThis`, which is the enclosing lexical scope.
- ☒ B. If the function has a single expression in the function body, the expression will be evaluated and implicitly returned.
- ☐ C. The function uses the `this` from the enclosing scope.
- ☒ D. The function generates its own `this` making it useful for separating the function's scope from its enclosing scope.

Question 6 of 63

Choose 1 option.

Which statement parses successfully?

- ☐ A. `JSON.parse('foo');`
- ☐ B. `JSON.parse("'foo');`
- ☐ C. `JSON.parse("foo");`
- ☒ D. `JSON.parse('"foo"');`

Question 7 of 63

Choose 1 option.

```
04 const objA = {value: 10};  
05 const objB = objA;  
06  
07 changeValue(objB);  
08 const result = objA.value;
```

What is the value of `result` after the code executes?

- ☐ A. NaN
- ☐ B. undefined
- ☐ C. 10
- ☒ D. 5

Question 8 of 63



Choose 3 options.

Refer to the code below:

```
01 x = 3.14;  
02  
03 function myFunction() {  
04   'use strict';  
05   y = x;  
06 }  
07  
08 z = x;  
09 myFunction();
```

Considering the implications of 'use strict' on line 04, which three statements describe the execution of the code?

☐ A. 'use strict' is hoisted, so it has an effect on all lines.

Choose 3 options.

07

08 `z = x;`

09 `myFunction();`

Considering the implications of `'use strict'` on line 04, which three statements describe the execution of the

- ☐ A. `'use strict'` is hoisted, so it has an effect on all lines.
- ☒ B. `z` is equal to 3.14.
- ☒ C. Line 05 throws an error.
- ☒ D. `'use strict'` has an effect only on line 05.
- ☐ E. `'use strict'` has an effect between line 04 and the end of the file.

Question 9 of 63



Choose 1 option.

Which option is true about the strict mode in imported modules?

- ☐ A. Add the statement `use strict = false;` before any other statements in the module to enable not-strict mode.
- ☒ B. Imported modules are in strict mode whether you declare them as such or not.
- ☐ C. A developer can only reference `notStrict()` functions from the imported module.
- ☐ D. Add the statement `use non-strict;` before any other statements in the module to enable not-strict mode.

Question 10 of 63



Choose 1 option.

A developer wants to create an object from a function in the browser using the code below.

```
01 function Monster(){ this.name = 'hello' };  
02 const m = Monster();
```

What happens due to the lack of the `new` keyword on line 02?

- ☒ A. `window.name` is assigned to 'hello' and the variable `m` remains undefined.
- ☐ B. The `m` variable is assigned the correct object but `this.name` remains undefined.
- ☐ C. The `m` variable is assigned the correct object.
- ☐ D. `window.m` is assigned the correct object.

Question 11 of 63



Choose 1 option.

Refer to the code below:

```
01 const objBook = {  
02   title: 'JavaScript',  
03 };  
04 Object.preventExtensions(objBook);  
05 const newObjBook = objBook;  
06 newObjBook.author = 'Robert';
```

What are the values of `objBook` and `newObjBook` respectively?

- ☐ A. { author: "Robert" }
 { author: "Robert", title: "JavaScript" }
- ☐ B. { author: "Robert", title: "JavaScript" }
 undefined

Question 11 of 63

Choose 1 option.

```
06 newObjBook.author = 'Robert';
```

What are the values of objBook and newObjBook respectively?

- ☐ A. { author: "Robert" }
 { author: "Robert", title: "JavaScript" }
- ☐ B. { author: "Robert", title: "JavaScript" }
 undefined
- ☒ C. { title: "JavaScript" }
 { title: "JavaScript" }
- ☐ D. { author: "Robert", title: "JavaScript" }
 { author: "Robert", title: "JavaScript" }

Question 12 of 63

Choose 1 option.

Refer to the code below:

```
01 let sayHello = () => {  
02   console.log('Hello, World!');  
03 };
```

Which code executes `sayHello` once, two minutes from now?

- ☐ A. `setTimeout(sayHello(), 120000);`
- ☒ B. `setTimeout(sayHello, 120000);`
- ☐ C. `setInterval(sayHello, 120000);`
- ☐ D. `delay(sayHello, 120000);`

Question 13 of 63



Choose 3 options.

Given a value, which three options can a developer use to detect if the value is NaN?

- ☒ A. `Number.isNaN(value)`
- ☒ B. `Object.is(value, NaN)`
- ☐ C. `value == NaN`
- ☒ D. `value !== value`
- ☐ E. `value === Number.NaN`



Question 14 of 63

Choose 1 option.

A developer removes the HTML `class` attribute from the checkout button, so now it is simply:

```
<button>Checkout</button>
```

There is a test to verify the existence of the checkout button, however it looks for a button with `class="blue"`. The test fails because no such button is found.

Which type of test category describes this test?

- ☐ A. True negative
- ☒ B. False negative
- ☐ C. False positive
- ☐ D. True positive

Question 15 of 63



Choose 1 option.

```
let productSKU = '8675309';
```

A developer has a requirement to generate SKU numbers that are always 19 characters long, starting with 'sku', and padded with zeros.

Which statement assigns the value `sku00000000008675309`?

- ☐ A. `productSKU = productSKU.padStart(19, '0').padStart('sku');`
- ☐ B. `productSKU = productSKU.padEnd(16, '0').padStart(19, 'sku');`
- ☐ C. `productSKU = productSKU.padEnd(16, '0').padStart('sku');`
- ☒ D. `productSKU = productSKU.padStart(16, '0').padStart(19, 'sku');`

Question 16 of 63



Choose 1 option.

Refer to the following code block:

```
01 let array = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11];
02 let output = 0;
03
04 for (let num of array) {
05   if (output > 10) {
06     break;
07   }
08   if (num % 2 == 0) {
09     continue;
10   }
11   output += num;
12 }
```

What is the value of `output` after the code executes?

```
11     if (num > 10) {  
09         continue;  
10     }  
11     output += num;  
12 }
```

What is the value of `output` after the code executes?

☒ A. 16

☐ B. 11

☐ C. 25

☐ D. 36

Question 17 of 63

Choose 1 option.

Given the following code:

```
let x = ('15' + 10) * 2;
```

What is the value of x ?

- ☒ A. 1520
- ☐ B. 50
- ☐ C. 35
- ☐ D. 3020

Question 18 of 63



Choose 1 option.

Refer to the code below:

```
for (let number = 2; number <= 5; number += 1) {  
  // Insert code statement here  
}
```

The developer needs to insert a code statement in the location shown. The code statement has these requirements:

1. Does not require an import
2. Logs an error when the Boolean statement evaluates to false
3. Works in both the browser and Node.js

Which statement meets these requirements?

- ☒ A. `console.assert(number % 2 === 0);`
- ☐ B. `assert(number % 2 === 0);`

Question 19 of 63



Choose 1 option.

A class was written to represent items for purchase in an online store, and a second class representing items that are on sale at a discounted price. The constructor sets the name to the first value passed in. The pseudocode is below:

```
class Item {  
    constructor(name, price){  
        ... // Constructor Implementation  
    }  
}
```

```
class SaleItem extends Item {  
    constructor(name, price, discount){  
        ... // Constructor Implementation  
    }  
}
```

There is a new requirement for a developer to implement a `description` method that will return a brief description for `Item` and `SaleItem`.

Choose 1 option.

This is a discounted Shirt

☐ B. This is a Scarf

Uncaught TypeError: saleItem.description is not a function

This is a Scarf

This is a discounted Shirt

☐ C. This is a Scarf

Uncaught TypeError: saleItem.description is not a function

This is a Shirt

This is a discounted Shirt

☒ D. This is a Scarf

This is a Shirt

This is a Scarf

This is a discounted Shirt

Question 20 of 63



Choose 1 option.

Refer to the code below:

```
01 async function functionUnderTest(isOK) {  
02   if (isOK) return 'OK';  
03   throw new Error('not OK');  
04 }
```

Which assertion accurately tests the above code?

- ☒ A. `console.assert(await functionUnderTest(true), 'OK')`
- ☐ B. `console.assert(await functionUnderTest(true), 'not OK')`
- ☐ C. `console.assert(functionUnderTest(true), 'OK')`

Question 21 of 63



Choose 1 option.

A developer creates a simple webpage with an input field. When a user enters text in the input field and clicks the button, the actual value of the field must be displayed in the console.

Here is the HTML file content:

```
<input type="text" value="Hello" name="input">
<button type="button">Display</button>
```

The developer wrote the JavaScript code below:

```
01 const button = document.querySelector('button');
02 button.addEventListener('click', () => {
03   const input = document.querySelector('input');
04   console.log(input.getAttribute('value'));
05 });
```

When the user clicks the button, the output is always "Hello".

```
05 });
```

When the user clicks the button, the output is always "Hello".

What needs to be done to make this code work as expected?

- ☒ A. Replace line 04 with `console.log(input.value);`
- ☐ B. Replace line 02 with `button.addEventListener("onclick", function() {`
- ☐ C. Replace line 03 with `const input = document.getElementById('input');`
- ☐ D. Replace line 02 with `button.addCallback("click", function() {`

Question 22 of 63

Choose 1 option.

Refer to the code snippet:

```
01 let array = [1, 2, 3, 4, 4, 5, 4, 4];  
02 for (let i = 0; i < array.length; i++) {  
03   if (array[i] === 4) {  
04     array.splice(i, 1);  
05     i--;  
06   }  
07 }
```

What is the value of `array` after the code executes?

- ☐ A. [1, 2, 3, 5]
- ☐ B. [1, 2, 3, 4, 5, 4, 4]

```
05     1--1,  
06     }  
07 }
```

What is the value of array after the code executes?

- ☐ A. [1, 2, 3, 5]
- ☐ B. [1, 2, 3, 4, 5, 4, 4]
- ☒ C. [1, 2, 3, 4, 5, 4]
- ☐ D. [1, 2, 3, 4, 4, 5, 4]

Question 23 of 63

Choose 1 option.

Given the following code:

```
01 let x = null;  
02 console.log(typeof x);
```

What is the output of line 02?

- ☒ A. "object"
- ☐ B. "null"
- ☐ C. "x"
- ☐ D. "undefined"

Question 24 of 63



Choose 2 options.

Refer to the code below:

```
01 const event = new CustomEvent(  
02   //Missing code  
03 );  
04 obj.dispatchEvent(event);
```

A developer needs to dispatch a custom event called `update` to send information about `recordId`.

Which two options could a developer insert at the placeholder in line 02 to achieve this?

☐ A. `'update', '123abc'`

☒ B. `'update', {
 detail : {
 recordId : '123abc'
 }
}`

Choose 2 options.

Which two options could a developer insert at the placeholder in line 02 to achieve this?

☐ A. `'update', '123abc'`

☒ B. `'update', {
 detail : {
 recordId : '123abc'
 }
}`

☒ C. `'update', {
 recordId : '123abc'
}`

☐ D. `{type : 'update', recordId : '123abc'}`

Question 25 of 63



Choose 1 option.

Which statement accurately describes an aspect of promises?

- ☒ A. Arguments for the callback function passed to `.then()` are optional.
- ☐ B. In a `.then()` function, returning results is not necessary since callbacks will catch the result of a previous promise.
- ☐ C. `.then()` manipulates and returns the original promise.
- ☐ D. `.then()` cannot be added after a `catch`.

Question 26 of 63

Choose 2 options.

Refer to the string below:

```
const str = 'Salesforce';
```

Which two statements result in the word 'Sales'?

- ☒ A. `str.substr(0, 5);`
- ☐ B. `str.substring(1, 5);`
- ☒ C. `str.substring(0, 5);`
- ☐ D. `str.substr(1, 5);`

Question 27 of 63

Choose 1 option.

```
01 let country = {  
02   get capital() {  
03     let city = Number("London");  
04  
05     return {  
06       cityString: city.toString(),  
07     }  
08   }  
09 }
```

Which value can a developer expect when referencing `country.capital.cityString`?

- ☐ A. undefined
- ☒ B. NaN

Question 28 of 63



Choose 2 options.

```
01 function listen(event) {  
02  
03   alert('Hey! I am John Doe');  
04  
05 }  
06 button.addEventListener('click', listen);
```

Which two code lines make this code work as required?

- ☒ A. On line 04, use `button.removeEventListener('click', listen);`
- ☐ B. On line 02, use `event.first` to test if it is the first execution.
- ☒ C. On line 06, add an option called `once` to `button.addEventListener()`.
- ☐ D. On line 04, use `event.stopPropagation();`

Question 29 of 63



Choose 1 option.

A team at Universal Containers works on a big project and use `yarn` to deal with the project's dependencies.

A developer added a dependency to manipulate dates and pushed the updates to the remote repository. The rest of the team complains that the dependency does not get downloaded when they execute `yarn`.

What could be the reason for this?

- ☐ A. The developer missed the option `--add` when adding the dependency.
- ☐ B. The developer added the dependency as a dev dependency, and `YARN_ENV` is set to `production`.
- ☐ C. The developer missed the option `--save` when adding the dependency.
- ☒ D. The developer added the dependency as a dev dependency, and `NODE_ENV` is set to `production`.

Question 30 of 63

Choose 1 option.

Refer to the code below:

```
const pi = 3.1415926;
```

What is the data type of pi?

- ☐ A. Decimal
- ☒ B. Number
- ☐ C. Double
- ☐ D. Float

Question 31 of 63



Choose 1 option.

A developer creates a class that represents a news story based on the requirements that a Story should have a body, author, and view count. The code is shown below:

```
01 class Story {  
02   // Insert code here  
03   this.body = body;  
04   this.author = author;  
05   this.viewCount = viewCount;  
06 }  
07 }
```

Which statement should be inserted in the placeholder on line 02 to allow for a variable to be set to a new instance of a Story with the three attributes correctly populated?

☐ A. `function Story(body, author, viewCount) {`

```
01 }
```

Which statement should be inserted in the placeholder on line 02 to allow for a variable to be set to a new i with the three attributes correctly populated?

- ☐ A. `function Story(body, author, viewCount) {`
- ☐ B. `super (body, author, viewCount) {`
- ☐ C. `constructor() {`
- ☒ D. `constructor(body, author, viewCount) {`

Question 32 of 63

Choose 1 option.

Refer to the code below:

```
01 function myFunction(reassign) {  
02   let x = 1;  
03   var y = 1;  
04  
05   if(reassign) {  
06     let x = 2;  
07     var y = 2;  
08     console.log(x);  
09     console.log(y);  
10   }  
11  
12   console.log(x);  
13   console.log(y);  
14 }
```

What is displayed when `myFunction(true)` is called?

Choose 1 option.

```
10    }  
11  
12    console.log(x);  
13    console.log(y);  
14 }
```

What is displayed when `myFunction(true)` is called?

- ☒ A. 2 2 1 2
- ☐ B. 2 2 1 1
- ☐ C. 2 2 2 2
- ☐ D. 2 2 undefined undefined

Question 33 of 63



Choose 2 options.

Refer to the code below:

```
01 const exec = (item, delay) =>
02   new Promise(resolve => setTimeout(() => resolve(item), delay));
03
04 async function runParallel() {
05   const [result1, result2, result3] = await Promise.all(
06     [exec('x', '100'), exec('y', '500'), exec('z', '100')]
07   );
08   return `parallel is done: ${result1}${result2}${result3}`;
09 }
```

Which two statements correctly execute the `runParallel()` function?

☐ A. `async runParallel().then(data);`

☐ B. `runParallel().then(data);`

Which two statements correctly execute the `runParallel()` function?

- ☐ A. `async runParallel().then(data);`
- ☐ B. `runParallel().then(data);`
- ☒ C. `runParallel().then(function(data) {
 return data;
});`
- ☒ D. `runParallel().done(function(data) {
 return data;
});`

Question 34 of 63



Choose 1 option.

```
01 function filterDOM(searchString){
02   const parsedSearchString = searchString && searchString.toLowerCase();
03   document.querySelectorAll('.account').forEach(account => {
04     const accountName = account.innerHTML.toLowerCase();
05     account.style.display = accountName.includes(parsedSearchString) ? /* Insert code here */;
06   });
07 }
```

Which code should replace the placeholder comment on line 05 to hide accounts that do not match the search string?

- ☐ A. 'hidden' : 'visible'
- ☐ B. 'visible' : 'hidden'
- ☒ C. 'block' : 'none'

Question 35 of 63



Choose 1 option.

```
02 for (let i = 0; i < array.length; i++) {  
03   if (array[i] === 4) {  
04     array.splice(i, 1);  
05   }  
06 }
```

What is the value of array after the code executes?

- ☐ A. [1, 2, 3, 5]
- ☐ B. [1, 2, 3, 4, 5, 4, 4]
- ☐ C. [1, 2, 3, 4, 4, 5, 4]
- ☒ D. [1, 2, 3, 4, 5, 4]

Question 36 of 63



Choose 1 option.

A developer has an `isDog` function that takes one argument, `pet`. They want to schedule the function to run every minute.

What is the correct syntax for scheduling this function?

- ☐ A. `setTimeout(isDog('cat'), 60000);`
- ☐ B. `setTimeout(isDog, 60000, 'cat');`
- ☒ C. `setInterval(isDog, 60000, 'cat');`
- ☐ D. `setInterval(isDog('cat'), 60000);`

Question 37 of 63

Choose 1 option.

Refer to the code below:

```
01 console.log('Start');  
02 Promise.resolve('Success').then(function(value) {  
03   console.log('Success');  
04 });  
05 console.log('End');
```

What is the output after the code executes successfully?

- ☐ A. Start
Success
End
- ☒ B. Start
End
Success

Question 38 of 63

Choose 1 option.

Refer to the code below:

```
01 let o = {  
02   get js() {  
03     let city1 = String('St. Louis');  
04     let city2 = String('New York');  
05  
06     return {  
07       firstCity: city1.toLowerCase(),  
08       secondCity: city2.toLowerCase(),  
09     }  
10   }  
11 }
```

What value can a developer expect when referencing `o.js.secondCity`?


```
08      secondCity: city2.toLowerCase(),  
09    }  
10  }  
11 }
```

What value can a developer expect when referencing `o.js.secondCity`?

- ☐ A. An error
- ☐ B. undefined
- ☒ C. 'new york'
- ☐ D. 'New York'

Question 39 of 63



Choose 2 options.

After user acceptance testing, the developer is asked to change the webpage background based on user's location. This change was implemented and deployed for testing.

The tester reports that the background is not changing, however it works as required when viewing on the developer's computer.

Which two actions will help determine accurate results?

- ☒ A. The tester should disable their browser cache.
- ☐ B. The developer should rework the code.
- ☐ C. The developer should inspect their browser refresh settings.
- ☒ D. The tester should clear their browser cache.

Question 40 of 63



Choose 1 option.

The developer has a function that prints "Hello" to an input name. To test this, the developer created a function that returns "World". However, the following snippet does not print "Hello World".

```
01 const sayHello = (name) => {  
02   console.log('Hello ', name);  
03 };  
04  
05 const world = () => {  
06   return 'World';  
07 };  
08  
09 sayHello(world);
```

What can the developer do to change the code to print "Hello World"?

- ☐ A. Change line 7 to `) ()`;

```
05 const world = () => {  
06   return 'World';  
07 };  
08  
09 sayHello(world);
```

What can the developer do to change the code to print "Hello World"?

- ☐ A. Change line 7 to `) ();`
- ☐ B. Change line 5 to `function world() {`
- ☐ C. Change line 9 to `sayHello(world) ();`
- ☒ D. Change line 2 to `console.log('Hello', name());`

Question 41 of 63



Choose 1 option.

A developer wants to use a `try...catch` statement to catch any error that `countSheep()` may throw and pass it to a `handleError()` function.

What is the correct implementation of the `try...catch`?

- ☐ A.

```
setTimeout(function() {  
    try {  
        countSheep();  
    } catch (e) {  
        handleError(e);  
    }  
}, 1000);
```
- ☐ B.

```
try {  
    countSheep();  
} finally {
```

}

☐ C. try {

 countSheep();

 } handleError (e) {

 catch(e);

}

☒ D. try {

 setTimeout(function() {

 countSheep();

 }, 1000);

 } catch (e) {

 handleError(e);

}

Question 42 of 63



Choose 2 options.

A developer is leading the creation of a new browser application that will serve a single page application.

The team wants to use a new web framework Minimalist.js. The lead developer wants to advocate for a more seasoned web framework/library that already has a community around it.

Which two frameworks/libraries should the lead developer advocate for?

☒ A. React

☐ B. Express

☐ C. Koa

☒ D. Vue

Question 43 of 63

Choose 2 options.

Refer to the code below:

```
let inArray = [ [1,2] , [3,4,5] ];
```

Which two statements result in the array `[ 1, 2, 3, 4, 5 ]`?

☐ A. `[] .concat.apply([], inArray);`

☒ B. `[] .concat(...inArray);`

☐ C. `[] .concat([...inArray]);`

☒ D. `[] .concat.apply(inArray, []);`

Question 44 of 63



Choose 2 options.

A developer needs to test this function:

```
01 const sum3 = (arr) => {  
02   if (!arr.length) return 0;  
03   if (arr.length === 1) return arr[0];  
04   if (arr.length === 2) return arr[0] + arr[1];  
05   return arr[0] + arr[1] + arr[2];  
06 };
```

Which two assert statements are valid tests for this function?

- ☒ A. `console.assert(sum3([1, '2']) == 12);`
- ☐ B. `console.assert(sum3([0]) === 0);`
- ☐ C. `console.assert(sum3(['hello', 2, 3, 4]) === NaN);`

Which two assert statements are valid tests for this function?

- ☒ A. `console.assert(sum3([1, '2']) == 12);`
- ☐ B. `console.assert(sum3([0]) === 0);`
- ☐ C. `console.assert(sum3(['hello', 2, 3, 4]) === NaN);`
- ☒ D. `console.assert(sum3([-3, 2]) === -1);`

Question 45 of 63

Choose 1 option.

Which statement accurately describes the behavior of the `async/await` keywords?

- ☐ A. The associated function can only be called via asynchronous methods.
- ☐ B. The associated function is asynchronous, but acts like synchronous code.
- ☐ C. The associated class contains some asynchronous functions.
- ☒ D. The associated function sometimes returns a promise.

Question 46 of 63

Choose 1 option.

A developer has the function, shown below, that is called when a page loads.

```
function onLoad() {  
  console.log("Page has loaded!");  
}
```

Where can the developer see the log statement after loading the page in the browser?

- ☐ A. On the terminal console running the web server
- ☐ B. In the browser performance tools log
- ☐ C. On the webpage console log
- ☒ D. On the browser JavaScript console

Question 47 of 63



Choose 1 option.

Refer to the HTML below:

```
<p> The current status of an Order: <span id="status"> In Progress </span> </p>
```

Which JavaScript statement changes the text 'In Progress' to 'Completed' ?

- ☐ A. `document.getElementById("status").Value = 'Completed';`
- ☐ B. `document.getElementById(".status").innerHTML = 'Completed';`
- ☒ C. `document.getElementById("status").innerHTML = 'Completed';`
- ☐ D. `document.getElementById("#status").innerHTML = 'Completed';`

Question 48 of 63

Choose 1 option.

Refer to the code below:

```
01 let total = 10;  
02 const interval = setInterval(() => {  
03   total++;  
04   clearInterval(interval);  
05   total++;  
06 }, 0);  
07 total++;  
08 console.log(total);
```

Considering that JavaScript is single-threaded, what is the output of line 08 after the code executes?

☐ A. 13

☒ B. 11

Question 49 of 63



Choose 2 options.

A developer is asked to fix some bugs reported by users. To do that, the developer adds a breakpoint for debugging.

```
01 function Car(maxSpeed, color){  
02   this.maxSpeed = maxSpeed;  
03   this.color = color;  
04 }  
05 let carSpeed = document.getElementById('carSpeed');  
06 debugger;  
07 let fourWheels = new Car(carSpeed.value, 'red');
```

When the code execution stops at the breakpoint on line 06, which two types of information are available in the browser console?

☒ A. A variable displaying the number of instances created for the Car object

```
07 let fourWheels = new Car(carSpeed.value, 'red');
```

When the code execution stops at the breakpoint on line 06, which two types of information are available in the console?

- ☒ A. A variable displaying the number of instances created for the Car object
 - ☐ B. The values of the carSpeed and fourWheels variables
 - ☐ C. The information stored in the window.localStorage property
 - ☒ D. The style, event listeners and other attributes applied to the carSpeed DOM element
-

Question 50 of 63



Choose 1 option.

A developer wants to set up a secure web server with Node.js. The developer creates a directory locally called `app-server`, and the first file is `app-server/index.js`.

Without using any third-party libraries, what should the developer add to `index.js` to create the secure web server?

- ☒ A. `const https = require('https');`
- ☐ B. `const tls = require('tls');`
- ☐ C. `const http = require('http');`
- ☐ D. `const server = require('secure-server');`

Question 51 of 63

Choose 2 options.

Refer to the following code:

```
01 function Tiger() {  
02   this.type = 'Cat';  
03   this.size = 'large';  
04 }  
05  
06 let tony = new Tiger();  
07 tony.roar = () => {  
08   console.log('They\'re great!');  
09 };  
10  
11 function Lion() {  
12   this.type = 'Cat';  
13   this.size = 'large';  
14 }  
15
```

```
18 leo.roar();
```

Which two statements could be inserted at line 17 to enable the function call on line 18?

- ☒ A. `leo.roar = () => { console.log('They\'re pretty good!'); }`
- ☐ B. `Object.assign(leo, Tiger);`
- ☐ C. `leo.prototype.roar = () => { console.log('They\'re pretty good!'); }`
- ☒ D. `Object.assign(leo, tony);`

Question 52 of 63



Choose 1 option.

Given the code block below:

```
01 function GameConsole(name) {  
02     this.name = name;  
03 }  
04  
05 GameConsole.prototype.load = function(gamename) {  
06     console.log(`${this.name} is loading a game: ${gamename}...`);  
07 }  
08  
09 function Console16bit(name) {  
10     GameConsole.call(this, name);  
11 }  
12  
13 Console16bit.prototype = Object.create(GameConsole.prototype);  
14  
15 // insert code here  
16     console.log(`${this.name} is loading a cartridge game: ${gamename}...`);
```

```
20 console16bit.load('Super Monic 3x Force');
```

What should a developer insert at line 15 to output the following message using the load method?

```
> SNEGeneziz is loading a cartridge game: Super Monic 3x Force...
```

- ☐ A. `Console16bit.prototype.load(gamename) = function() {`
- ☐ B. `Console16bit.prototype.load(gamename) {`
- ☒ C. `Console16bit.prototype.load = function(gamename) {`
- ☐ D. `Console16bit = Object.create(GameConsole.prototype).load = function(gamename) {`

Question 53 of 63



Choose 1 option.

Refer to the code:

```
01 function Vehicle(name, price) {  
02   this.name = name;  
03   this.price = price;  
04 }  
05 Vehicle.prototype.priceInfo = function () {  
06   return `Cost of the ${this.name} is ${this.price}$`;  
07 }  
08 var ford = new Vehicle('Ford Fiesta', '20,000');
```

Given the requirement to refactor the code above to JavaScript class format, which class definition is correct?

- ☐ A. 01 class Vehicle {
02 vehicle(name, price) {
03 this.name = name;
04 this.price = price;

09 }

☒ B. 01 class Vehicle {
02 constructor(name, price) {
03 this.name = name;
04 this.price = price;
05 }
06 priceInfo() {
07 return `Cost of the \${this.name} is \${this.price}\$`;
08 }
09 }

☐ C. 01 class Vehicle {
02 constructor() {
03 this.name = name;
04 this.price = price;
05 }

Question 54 of 63



Choose 1 option.

A developer wants to use a module called `DatePrettyPrint`. This module exports one default function called `printDate()`.

How can a developer import and use the `printDate()` function?

- ☐ A. `import DatePrettyPrint() from '/path/DatePrettyPrint.js';`
`printDate();`
- ☐ B. `import printDate from '/path/DatePrettyPrint.js';`
`printDate();`
- ☒ C. `import printDate from '/path/DatePrettyPrint.js';`
`DatePrettyPrint.printDate();`
- ☐ D. `import DatePrettyPrint from '/path/DatePrettyPrint.js';`
`DatePrettyPrint.printDate();`

Question 55 of 63



Choose 1 option.

A developer wants to leverage a module to print a price in pretty format, and has imported a method as shown below:

```
import printPrice from '/path/PricePrettyPrint.js';
```

Based on the code, what must be true about the `printPrice` function of the `PricePrettyPrint` module for this import to work?

- ☐ A. `printPrice` must be an all export
- ☐ B. `printPrice` must be a multi export
- ☒ C. `printPrice` must be the default export
- ☐ D. `printPrice` must be a named export

Question 56 of 63



Choose 1 option.

A developer at Universal Containers is creating their new landing page based on HTML, CSS, and JavaScript.

To ensure that visitors have a good experience, a script named `personalizeWebsiteContent` needs to be executed when the webpage is fully loaded (HTML content and all related files), in order to do some custom initializations.

Which implementation should be used to call `personalizeWebsiteContent` based on the business requirement above?

- ☐ A. Add a listener to the `window` object to handle the `DOMContentLoaded` event
- ☒ B. Add a listener to the `window` object to handle the `load` event
- ☐ C. Add a handler to the `personalizeWebsiteContent` script to handle the `DOMContentLoaded` event
- ☐ D. Add a handler to the `personalizeWebsiteContent` script to handle the `load` event

Question 57 of 63



Choose 1 option.

Refer to the code below:

```
01 function execute() {  
02   return new Promise((resolve, reject) => reject());  
03 }  
04 let promise = execute();  
05  
06 promise  
07   .then(() => console.log('Resolved1'))  
08   .then(() => console.log('Resolved2'))  
09   .then(() => console.log('Resolved3'))  
10   .catch(() => console.log('Rejected'))  
11   .then(() => console.log('Resolved4'));
```

What is the result when the Promise in the execute function is rejected?

☐ A. Resolved1 Resolved2 Resolved3 Resolved4

```
11 .then(() => console.log('Resolved4'));
```

What is the result when the Promise in the `execute` function is rejected?

- ☐ A. Resolved1 Resolved2 Resolved3 Resolved4
 - ☒ B. Rejected Resolved4
 - ☐ C. Resolved1 Resolved2 Resolved3 Rejected Resolved4
 - ☐ D. Rejected
-

Question 58 of 63



Choose 1 option.

Refer to the code below:

```
01 let requestPromise = client.getRequest;  
02  
03 requestPromise().then((response) => {  
04   handleResponse(response);  
05 });
```

A developer uses a client that makes a GET request that uses a Promise to handle the request. `getRequest` returns a Promise.

Which code modification can the developer make to gracefully handle an error?

- ☒ A. 01 let requestPromise = client.getRequest;
02
03 requestPromise().then((response) => {
04 handleResponse(response);
05 }).catch((error) => {

Question 59 of 63



Choose 1 option.

Universal Containers recently launched its new landing page to host a crowd-funding campaign. The page uses an external library to display some third-party ads. Once the page is fully loaded, it creates more than 50 new HTML items placed randomly inside the DOM, like the one in the code below:

```
<!-- This is an ad -->
<div class="ad-library-item ad-hidden" onload="myFunction()" >
  
</div>
```

All the elements include the same `ad-library-item` class. They are hidden by default, and they are randomly displayed while the user navigates through the page.

Tired of all the ads, what can the developer do to temporarily and quickly remove them?

- ☐ A. Use the DOM inspector to remove all the elements containing the class `ad-library-item`.
- ☐ B. Use the browser console to execute a script that prevents the `load` event to be fired.

the user navigates through the page.

Tired of all the ads, what can the developer do to temporarily and quickly remove them?

- ☐ A. Use the DOM inspector to remove all the elements containing the class `ad-library-item`.
 - ☐ B. Use the browser console to execute a script that prevents the `load` event to be fired.
 - ☐ C. Use the DOM inspector to prevent the `load` event to be fired.
 - ☒ D. Use the browser console to execute a script that removes all the elements containing the class `ad-item`.
-

Question 60 of 63



Choose 1 option.

A developer creates a new web server that uses Node.js. It imports a server library that uses events and callbacks for handling server functionality.

The server library is imported with `require` and is made available to the code by a variable named `server`. The developer wants to log any issues that the server has while booting up.

Given the code and the information the developer has, which code logs an error at boot time with an event?

- ☐ A.

```
01 server.error((error) => {  
02   console.log('ERROR', error);  
03 });
```
- ☒ B.

```
01 server.on('error', (error) => {  
02   console.log('ERROR', error);  
03 });
```


Question 61 of 63



Choose 1 option.

Refer to the code below:

```
01 let car1 = new Promise( (_, reject) =>
02   setTimeout(reject, 2000, "Car 1 crashed in"));
03 let car2 = new Promise(resolve => setTimeout(resolve, 1500, "Car 2 completed"));
04 let car3 = new Promise(resolve => setTimeout(resolve, 3000, "Car 3 completed"));
05
06 Promise.race([car1, car2, car3])
07   .then(value => {
08     let result = `${value} the race.`;
09   })
10   .catch(err => {
11     console.log("Race is cancelled.", err);
12   });
```

What is the value of result when Promise.race executes?

```
08     let result = `${value} the race.`;  
09   })  
10   .catch(err => {  
11     console.log("Race is cancelled.", err);  
12   });
```

What is the value of `result` when `Promise.race` executes?

- ☒ A. Car 2 completed the race.
- ☐ B. Car 3 completed the race.
- ☐ C. Car 1 crashed in the race.
- ☐ D. Race is cancelled.

Question 62 of 63



Choose 1 option.

A developer wants to create a simple image upload in the browser using the File API. The HTML is below:

```
<input type="file" onchange="previewFile()">
<img src="" height="200" alt="Image preview..."/>
```

The JavaScript portion is:

```
01 function previewFile() {
02   const preview = document.querySelector('img');
03   const file = document.querySelector('input[type=file]').files[0];
04   // line 4 code
05   reader.addEventListener("load", () => {
06     preview.src = reader.result;
07   }, false);
08   //line 8 code
09 }
```

In lines 04 and 08, which code allows the user to select an image from their local computer, and to display the image in the

In lines 04 and 08, which code allows the user to select an image from their local computer, and to display it in the browser?

- ☒ A.

```
04 const reader = new FileReader();  
08 if (file) reader.readAsDataURL(file);
```
- ☐ B.

```
04 const reader = new File();  
08 if (file) URL.createObjectURL(file);
```
- ☐ C.

```
04 const reader = new File();  
08 if (file) reader.readAsDataURL(file);
```
- ☐ D.

```
04 const reader = new FileReader();  
08 if (file) URL.createObjectURL(file);
```

Question 63 of 63



Choose 2 options.

Refer to the code below:

```
01 const addBy = ?  
02 const addByEight = addBy(8);  
03 const sum = addByEight(50);
```

Which two functions can replace line 01 and return 58 to sum?

☒ A. `const addBy = function(num1) {
 return function(num2) {
 return num1 + num2;
 }
}`

☐ B. `const addBy = function(num1) {
 return num1 * num2;
}`

☒ A. `const addBy = function(num1){
 return function(num2){
 return num1 + num2;
 }
}`

☐ B. `const addBy = function(num1){
 return num1 * num2;
}`

☒ C. `const addBy = (num1) => (num2) => num1 + num2;`

☐ D. `const addBy = (num1) => num1 + num2;`

GRADE: Pass

The report below shows the percentage of questions in each section that you answered correctly for the Salesforce Certified JavaScript Developer - Multiple Choice exam. You will receive this information in your exam results email and can also access it via My Dashboard in Trailhead Academy.

SECTION NAME:	PERCENT CORRECT:
Variables, Types, and Collections	79%
Objects, Functions, and Classes	93%
Browser and Events	100%
Debugging and Error Handling	50%
Asynchronous Programming	75%
Server Side JavaScript	100%
Testing	75%