

Question 1 of 63



Choose 3 options.

Refer to the following code:

```
let codeName = 'Bond';  
let sampleText = `The name is ${codeName}, Jim ${codeName}!`;
```

A developer is trying to determine if a certain substring is part of a string.

Which three code statements return true?

- ☒ A. `sampleText.includes('Jim');`
- ☐ B. `sampleText.includes('The', 1);`
- ☒ C. `sampleText.includes('Jim', 4);`
- ☒ D. `sampleText.indexOf('Bond') !== -1;`
- ☐ E. `sampleText.substring('Jim');`

Question 2 of 65



Choose 1 option.

Refer to the code below:

```
01 let car1 = new Promise(_, reject) =>
02   setTimeout(reject, 2000, "Car 1 crashed in");
03 let car2 = new Promise(resolve => setTimeout(resolve, 1500, "Car 2 completed"));
04 let car3 = new Promise(resolve => setTimeout(resolve, 3000, "Car 3 completed"));
05
06 Promise.race([car1, car2, car3])
07   .then(value => {
08     let result = `${value} the race.`;
09   })
10   .catch(err => {
11     console.log("Race is cancelled.", err);
12   });
```

What is the value of `result` when `Promise.race` executes?

- ☐ A. Car 3 completed the race.
- ☒ B. Car 2 completed the race.
- ☐ C. Race is cancelled.
- ☐ D. Car 1 crashed in the race.



Choose 1 option.

Refer to the code below:

```
01 let car1 = new Promise((_ , reject) =>
02   setTimeout(reject, 2000, "Car 1 crashed in"));
03 let car2 = new Promise(resolve => setTimeout(resolve, 1500, "Car 2 completed"));
04 let car3 = new Promise(resolve => setTimeout(resolve, 3000, "Car 3 completed"));
05
06 Promise.race([car1, car2, car3])
07   .then(value => {
08     let result = `${value} the race.`;
09   })
10   .catch(err => {
11     console.log("Race is cancelled.", err);
12   });
```

What is the value of result when Promise.race executes?

- ☐ A. Car 3 completed the race.
- ☒ B. Car 2 completed the race.
- ☐ C. Race is cancelled.
- ☐ D. Car 1 crashed in the race.

Question 3 of 63



Choose 1 option.

Given the following code:

```
01 counter = 0;  
02 const logCounter = () => {  
03   console.log(counter);  
04 };  
05 logCounter();  
06 setTimeout(logCounter, 2100);  
07 setInterval(() => {  
08   counter++;  
09   logCounter();  
10 }, 1000);
```

What will be the first four numbers logged?

☒ A. 0 1 2 2

☐ B. 0 1 2 3

☐ C. 0 1 1 2

☐ D. 0 0 1 2

Question 4 of 63



Choose 3 options.

Which three actions can be done using the JavaScript browser console?

- ☒ A. View and change the DOM of the page.
- ☒ B. View, change, and debug the JavaScript code of the page.
- ☒ C. Run code that is not related to the page.
- ☐ D. Display a report showing the performance of a page.
- ☐ E. View and change security cookies.

Question 5 of 63



Choose 2 options.

A developer has a `fizzbuzz` function that, when passed in a number, returns the following:

- `'fizz'` if the number is divisible by 3.
- `'buzz'` if the number is divisible by 5.
- `'fizzbuzz'` if the number is divisible by both 3 and 5.
- empty string if the number is divisible by neither 3 or 5.

Which two test cases properly test scenarios for the `fizzbuzz` function?

- ☒ A. `let res = fizzbuzz(true);`
`console.assert(res === '');`
- ☐ B. `let res = fizzbuzz(3);`
`console.assert(res === '');`
- ☐ C. `let res = fizzbuzz(5);`
`console.assert(res === 'fizz');`
- ☒ D. `let res = fizzbuzz(15);`
`console.assert(res === 'fizzbuzz');`

Question 5 of 63



Choose 2 options.

A developer has a `fizzbuzz` function that, when passed in a number, returns the following:

- 'fizz' if the number is divisible by 3.
- 'buzz' if the number is divisible by 5.
- 'fizzbuzz' if the number is divisible by both 3 and 5.
- empty string if the number is divisible by neither 3 or 5.

Which two test cases properly test scenarios for the `fizzbuzz` function?

- ☒ A. `let res = fizzbuzz(true);`
`console.assert(res === '');`
- ☐ B. `let res = fizzbuzz(3);`
`console.assert(res === '');`
- ☐ C. `let res = fizzbuzz(5);`
`console.assert(res === 'fizz');`
- ☒ D. `let res = fizzbuzz(15);`
`console.assert(res === 'fizzbuzz');`

Question 6 of 63



Choose 1 option.

Refer to the following code:

```
01 let obj = {  
02   foo: 1,  
03   bar: 2  
04 }  
05 let output = [];  
06  
07 for (let something of obj) {  
08   output.push(something);  
09 }  
10  
11 console.log(output);
```

What is the value of output on line 11?

- ☐ A. An error will occur due to the incorrect usage of the for..of statement on line 07.
- ☐ B. [1, 2]
- ☒ C. ["foo", "bar"]
- ☐ D. ["foo:1", "bar:2"]

Choose 2 options.

Which two code snippets show working examples of a recursive function?

☐ A.

```
const sumToTen = numVar => {  
  if (numVar < 0)  
    return;  
  return sumToTen(numVar + 1);  
};
```

☐ B.

```
function factorial(numVar) {  
  if (numVar < 0) return;  
  if (numVar === 0) return 1;  
  return numVar - 1;  
}
```

☒ C.

```
const factorial = numVar => {  
  if (numVar < 0) return;  
  if (numVar === 0) return 1;  
  return numVar * factorial(numVar - 1);  
};
```

☒ D.

```
let countingDown = function(startNumber) {  
  if (startNumber > 0) {  
    console.log(startNumber);  
    return countingDown(startNumber - 1);  
  } else {
```

Choose 2 options.

Given two expressions `var1` and `var2`, what are two valid ways to return the concatenation of the two expressions and ensure it is data type `string`?

- ☒ A. `String(var1).concat(var2)`
- ☐ B. `String.concat(var1 + var2)`
- ☐ C. `var1 + var2`
- ☒ D. `var1.toString() + var2.toString()`

Question 9 of 63



Choose 1 option.

Refer to the code below:

```
01 const myFunction = arr => {  
02   return arr.reduce((result, current) => {  
03     return result + current;  
04   }, 10);  
05 }
```

What is the output of this function when called with an empty array?

- ☐ A. Returns 0
- ☐ B. Throws an error
- ☐ C. Returns NaN
- ☒ D. Returns 10

Question 9 of 63



Choose 1 option.

Refer to the code below:

```
01 const myFunction = arr => {  
02   return arr.reduce((result, current) => {  
03     return result + current;  
04   }, 10);  
05 }
```

What is the output of this function when called with an empty array?

- ☐ A. Returns 0
- ☐ B. Throws an error
- ☐ C. Returns NaN
- ☒ D. Returns 10

Question 10 of 63



Choose 1 option.

Given the code below:

```
01 function Person(name, email) {  
02   this.name = name;  
03   this.email = email;  
04 }  
05  
06 const john = new Person('John', 'john@email.com');  
07 const jane = new Person('Jane', 'jane@email.com');  
08 const emily = new Person('Emily', 'emily@email.com');  
09  
10 let usersList = [john, jane, emily];
```

Which method can be used to provide a visual representation of the list of users and to allow sorting by the name or email attribute?

- ☒ A. `console.table(usersList);`
- ☐ B. `console.group(usersList);`
- ☐ C. `console.groupCollapsed(usersList);`
- ☐ D. `console.info(usersList);`

Question 11 of 63



Choose 1 option.

Given the code below:

```
01 setTimeout(() => {  
02   console.log(1);  
03 }, 0);  
04 console.log(2);  
05 new Promise((resolve, reject) => {  
06   setTimeout(() => {  
07     reject(console.log(3));  
08   }, 1000);  
09 }).catch(() => {  
10   console.log(4);  
11 });  
12 console.log(5);
```

What is logged to the console?

☒ A. 2 5 1 3 4

☐ B. 1 2 4 3 5

☐ C. 1 2 5 3 4

☐ D. 2 1 4 3 5

Question 12 of 63



Choose 1 option.

Refer to the code below:

```
01 let timedFunction = () => {  
02   console.log('Timer called.');
```

```
03 };  
04  
05 let timerId = setInterval(timedFunction, 1000);
```

Which statement allows a developer to cancel the scheduled timed function?

- ☒ A. `clearInterval(timerId);`
- ☐ B. `removeInterval(timerId);`
- ☐ C. `removeInterval(timedFunction);`
- ☐ D. `clearInterval(timedFunction);`

Question 13 of 63



Choose 1 option.

A developer at Universal Containers creates a new landing page based on HTML, CSS, and JavaScript.

To ensure that visitors have a good experience, a script named `personalizeWebsiteContent` needs to be executed to do some custom initialization when the webpage is fully loaded with HTML content and all related files.

Which statement should be used to call `personalizeWebsiteContent` based on the above business requirement?

- ☐ A. `document.addEventListener('DOMContentLoaded', personalizeWebsiteContent);`
- ☐ B. `document.addEventListener('onDOMContentLoaded', personalizeWebsiteContent);`
- ☒ C. `window.addEventListener('load', personalizeWebsiteContent);`
- ☐ D. `window.addEventListener('onload', personalizeWebsiteContent);`

Question 14 of 63



Choose 1 option.

Refer to the code below:

```
for (let number = 2; number <= 5; number += 1) {  
  // Insert code statement here  
}
```

The developer needs to insert a code statement in the location shown. The code statement has these requirements:

1. Does not require an import
2. Logs an error when the Boolean statement evaluates to false
3. Works in both the browser and Node.js

Which statement meets these requirements?

- ☒ A. `console.assert(number % 2 === 0);`
- ☐ B. `assert(number % 2 === 0);`
- ☐ C. `console.error(number % 2 === 0);`
- ☐ D. `console.debug(number % 2 === 0);`

Choose 1 option.

Refer to the following code:

```
01 class Ship {
02   constructor(size) {
03     this.size = size;
04   }
05 }
06
07 class FishingBoat extends Ship {
08   constructor(size, capacity){
09     //Missing code
10     this.capacity = capacity;
11   }
12   displayCapacity() {
13     console.log('The boat has a capacity of ${this.capacity} people.');
```

Which statement should be added to line 09 for the code to display 'The boat has a capacity of 10 people?'

- ☒ A. `super(size);`
- ☐ B. `ship.size = size;`
- ☐ C. `super.size = size;`
- ☐ D. `this.size = size;`

Choose 1 option.

A developer initiates a server with the file `server.js` and adds dependencies in the source code's `package.json` that are required to run the server.

Which command should the developer run to start the server locally?

- ☐ A. `node start`
- ☒ B. `npm start`
- ☐ C. `npm start server.js`
- ☐ D. `start server.js`

Choose 1 option.

A developer has the function, shown below, that is called when a page loads.

```
function onLoad() {  
  console.log("Page has loaded!");  
}
```

Where can the developer see the log statement after loading the page in the browser?

- ☐ A. In the browser performance tools log
- ☐ B. On the terminal console running the web server
- ☐ C. On the webpage console log
- ☒ D. On the browser JavaScript console

Question 18 of 63



Choose 3 options.

Given the code below:

```
let numValue = 1982;
```

Which three code segments result in a correct conversion from number to string?

- ☐ A. `let strValue = numValue.toText();`
- ☒ B. `let strValue = String(numValue);`
- ☒ C. `let strValue = '' + numValue;`
- ☒ D. `let strValue = numValue.toString();`
- ☐ E. `let strValue = (String)numValue;`

Question 19 of 63



Choose 2 options.

Which two console logs output NaN?

- ☐ A. `console.log(10 / 0);`
- ☒ B. `console.log(parseInt('two'));`
- ☐ C. `console.log(10 / Number('5'));`
- ☒ D. `console.log(10 / 'five');`

Question 20 of 63



Choose 2 options.

A developer uses a parsed JSON string to work with user information as in the block below:

```
01 const userInformation = {  
02   "id" : "user-01",  
03   "email" : "user01@universalcontainers.demo",  
04   "age" : 25  
05 };
```

Which two options access the `email` attribute in the object?

- ☒ A. `userInformation.email`
- ☐ B. `userInformation.get("email")`
- ☒ C. `userInformation["email"]`
- ☐ D. `userInformation[email]`

Question 21 of 63



Choose 1 option.

Refer to the code below:

```
01 function execute() {  
02   return new Promise((resolve, reject) => reject());  
03 }  
04 let promise = execute();  
05  
06 promise  
07   .then(() => console.log('Resolved1'))  
08   .then(() => console.log('Resolved2'))  
09   .then(() => console.log('Resolved3'))  
10   .catch(() => console.log('Rejected'))  
11   .then(() => console.log('Resolved4'));
```

What is the result when the Promise in the execute function is rejected?

- ☒ A. Rejected Resolved4
- ☐ B. Resolved1 Resolved2 Resolved3 Rejected Resolved4
- ☐ C. Resolved1 Resolved2 Resolved3 Resolved4
- ☐ D. Rejected

Question 22 of 63



Choose 3 options.

Which three browser specific APIs are available for developers to persist data between page loads?

- ☒ A. localStorage
- ☒ B. indexedDB
- ☒ C. cookies
- ☐ D. global variables
- ☐ E. IIFEs

Question 23 of 63



Choose 2 options.

Given a value, which two options can a developer use to detect if the value is NaN?

- ☐ A. `value === Number.NaN`
- ☐ B. `value == NaN`
- ☒ C. `isNaN(value)`
- ☒ D. `Object.is(value, NaN)`

Question 24 of 63



Choose 1 option.

A developer wants to use a module called `DatePrettyPrint`. This module exports one default function called `printDate()`.

How can a developer import and use the `printDate()` function?

- ☐ A. `import DatePrettyPrint() from '/path/DatePrettyPrint.js';`
`printDate();`
- ☐ B. `import DatePrettyPrint from '/path/DatePrettyPrint.js';`
`DatePrettyPrint.printDate();`
- ☐ C. `import printDate from '/path/DatePrettyPrint.js';`
`DatePrettyPrint.printDate();`
- ☒ D. `import printDate from '/path/DatePrettyPrint.js';`
`printDate();`

Question 25 of 63



Choose 1 option.

Which option is true about the strict mode in imported modules?

- ☒ A. Imported modules are in strict mode whether you declare them as such or not.
- ☐ B. Add the statement `use strict = false;` before any other statements in the module to enable not-strict mode.
- ☐ C. A developer can only reference `notStrict()` functions from the imported module.
- ☐ D. Add the statement `use non-strict;` before any other statements in the module to enable not-strict mode.

Question 26 of 63



Choose 1 option.

Refer to the code below:

```
01 new Promise((resolve, reject) => {  
02   const fraction = Math.random();  
03   if (fraction > 0.5) reject('fraction > 0.5, ' + fraction);  
04   resolve(fraction);  
05 })  
06 .then(() => console.log('resolved'))  
07 .catch((error) => console.error(error))  
08 .finally(() => console.log('when am I called?'));
```

When does `Promise.finally` on line 08 get called?

- ☐ A. When rejected
- ☐ B. When resolved and settled
- ☐ C. When resolved
- ☒ D. When resolved or rejected

Question 27 of 63



Choose 1 option.

Which statement accurately describes the behavior of the `async/await` keywords?

- ☐ A. The associated class contains some asynchronous functions.
- ☐ B. The associated function can only be called via asynchronous methods.
- ☐ C. The associated function sometimes returns a promise.
- ☒ D. The associated function is asynchronous, but acts like synchronous code.

Question 27 of 63



Choose 1 option.

Which statement accurately describes the behavior of the `async/await` keywords?

- ☐ A. The associated class contains some asynchronous functions.
- ☐ B. The associated function can only be called via asynchronous methods.
- ☐ C. The associated function sometimes returns a promise.
- ☒ D. The associated function is asynchronous, but acts like synchronous code.

Question 28 of 63



Choose 1 option.

Refer to the HTML below:

```
<div id="main">
  <ul>
    <li>Leo</li>
    <li>Tony</li>
    <li>Tiger</li>
  </ul>
</div>
```

Which JavaScript statement results in changing "Leo" to "The Lion"?

- ☐ A. `document.querySelectorAll('#main #Leo').innerHTML = 'The Lion';`
- ☐ B. `document.querySelector('#main li:second-child').innerHTML = 'The Lion';`
- ☐ C. `document.querySelectorAll('#main li.Leo').innerHTML = 'The Lion';`
- ☒ D. `document.querySelector('#main li:nth-child(1)').innerHTML = 'The Lion';`

Question 29 of 63



Choose 1 option.

Which statement accurately describes an aspect of promises?

- ☐ A. `.then()` cannot be added after a `catch`.
- ☐ B. In a `.then()` function, returning results is not necessary since callbacks will catch the result of a previous promise.
- ☒ C. Arguments for the callback function passed to `.then()` are optional.
- ☐ D. `.then()` manipulates and returns the original promise.

Refer to the following code block:

```
01 class Animal {
02   constructor(name) {
03     this.name = name;
04   }
05
06   makeSound() {
07     console.log(`${this.name} is making a sound.`);
08   }
09 }
10
11 class Dog extends Animal {
12   constructor(name) {
13     super(name);
14     this.name = name;
15   }
16   makeSound() {
17     console.log(`${this.name} is barking.`);
18   }
19 }
20
21 let myDog = new Dog('Puppy');
22 myDog.makeSound();
```

What is the console output?

- ☐ A. > Uncaught ReferenceError
- ☐ B. > Undefined
- ☒ C. > Puppy is barking.

Question 31 of 63



Choose 1 option.

Refer to the code below:

```
const pi = 3.1415926;
```

What is the data type of `pi`?

☒ A. Number

☐ B. Float

☐ C. Double

☐ D. Decimal

Question 32 of 63



Choose 1 option.

Refer to the code snippet:

```
01 function getAvailabilityMessage(item) {  
02     if (getAvailability(item)) {  
03         var msg = "Username available";  
04     }  
05     return msg;  
06 }
```

A developer writes this code to return a message to a user attempting to register a new username. If the username is available, a variable named `msg` is declared and assigned a value on line 03.

What is the return value of `msg` when `getAvailabilityMessage("newUserName")` is executed and `getAvailability("newUserName")` returns false?

- ☐ A. "newUserName"
- ☐ B. "msg is not defined"
- ☒ C. undefined
- ☐ D. "Username available"

Question 33 of 63



Choose 1 option.

Refer to the code below:

```
01 function changeValue(param) {  
02   param = 5;  
03 }  
04 let a = 10;  
05 let b = a;  
06  
07 changeValue(b);  
08 const result = a + ' - ' + b;
```

What is the value of `result` when the code executes?

- ☐ A. 5-5
- ☐ B. 5-10
- ☐ C. 10-5
- ☒ D. 10-10

Question 34 of 63



Choose 1 option.

Universal Containers recently launched its new landing page to host a crowd-funding campaign. The page uses an external library to display some third-party ads. Once the page is fully loaded, it creates more than 50 new HTML items placed randomly inside the DOM, like the one in the code below:

```
<!-- This is an ad -->
<div class="ad-library-item ad-hidden" onload="myFunction()">
  
</div>
```

All the elements include the same `ad-library-item` class. They are hidden by default, and they are randomly displayed while the user navigates through the page.

Tired of all the ads, what can the developer do to temporarily and quickly remove them?

- ☒ A. Use the browser console to execute a script that removes all the elements containing the class `ad-library-item`.
- ☐ B. Use the DOM inspector to remove all the elements containing the class `ad-library-item`.
- ☐ C. Use the browser console to execute a script that prevents the `load` event to be fired.
- ☐ D. Use the DOM inspector to prevent the `load` event to be fired.

Question 35 of 63



Choose 1 option.

Universal Containers (UC) just launched a new landing page, but users complain that the website is slow. A developer found some functions that might cause this problem. To verify this, the developer decides to execute everything and log the time each of these three suspicious functions consumes.

```
01 console.time('Performance');  
02  
03 maybeAHeavyFunction();  
04  
05 thisCouldTakeTooLong();  
06  
07 orMaybeThisOne();  
08  
09 console.endTime('Performance');
```

Which function can the developer use to obtain the time spent by every one of the three functions?

- ☒ A. `console.timeLog()`
- ☐ B. `console.trace()`
- ☐ C. `console.timeStamp()`
- ☐ D. `console.getTime()`

Question 36 of 63



Choose 1 option.

Given the code below:

```
01 const delay = async delay => {  
02   return new Promise((resolve, reject) => {  
03     console.log(1);  
04     setTimeout(resolve, delay);  
05   });  
06 };  
07  
08 const callDelay = async () => {  
09   console.log(2);  
10   const yup = await delay(1000);  
11   console.log(3);  
12 };  
13  
14 console.log(4);  
15 callDelay();  
16 console.log(5);
```

What is logged to the console?

☐ A. 4 2 1 3 5

☒ B. 4 2 1 5 3

☐ C. 1 4 2 3 5

☐ D. 4 5 1 2 3

Question 37 of 63



Choose 1 option.

A developer is setting up a Node.js server and is creating a script at the root of the source code, `index.js`, that will start the server when executed. The developer declares a variable that needs the folder location that the code executes from.

Which global variable can be used in the script?

- ☐ A. `__filename`
- ☐ B. `window.location`
- ☐ C. `this.path`
- ☒ D. `__dirname`

Question 38 of 63



Choose 1 option.

Refer to the code below:

```
flag();  
  
function flag() {  
  console.log('flag');  
}  
  
const anotherFlag = () => {  
  console.log('another flag');  
}  
  
anotherFlag();
```

What is result of the code block?

- ☐ A. The console logs only 'flag'.
- ☐ B. An error is thrown.
- ☐ C. The console logs 'flag' and then an error is thrown.
- ☒ D. The console logs 'flag' and 'another flag'.

Question 39 of 63



Choose 2 options.

A developer is creating a simple webpage with a button. When a user clicks this button for the first time, a message is displayed.

The developer wrote the JavaScript code below, but something is missing. The message gets displayed every time a user clicks the button, instead of just the first time.

```
01 function listen(event) {  
02  
03   alert('Hey! I am John Doe');  
04  
05 }  
06 button.addEventListener('click', listen);
```

Which two code lines make this code work as required?

- ☒ A. On line 04, use `button.removeEventListener('click', listen);`
- ☐ B. On line 02, use `event.first` to test if it is the first execution.
- ☐ C. On line 04, use `event.stopPropagation();`
- ☒ D. On line 06, add an option called `once` to `button.addEventListener()`.

Question 40 of 63



Choose 1 option.

Refer to the code below:

```
01 let first = 'Who';
02 let second = 'What';
03 try {
04   try {
05     throw new Error('Sad trombone');
06   } catch (err) {
07     first = 'Why';
08     throw err;
09   } finally {
10     second = 'When';
11   }
12 } catch (err) {
13   second = 'Where';
14 }
```

What are the values for `first` and `second` once the code executes?

- ☐ A. `first` is Who and `second` is Where.
- ☒ B. `first` is Why and `second` is Where.
- ☐ C. `first` is Who and `second` is When.
- ☐ D. `first` is Why and `second` is When.

Question 41 of 63



Choose 2 options.

A developer needs to test this function:

```
01 const sum3 = (arr) => {  
02   if (!arr.length) return 0;  
03   if (arr.length === 1) return arr[0];  
04   if (arr.length === 2) return arr[0] + arr[1];  
05   return arr[0] + arr[1] + arr[2];  
06 };
```

Which two assert statements are valid tests for this function?

- ☒ A. `console.assert(sum3([1, '2']) == 12);`
- ☒ B. `console.assert(sum3([0]) === 0);`
- ☐ C. `console.assert(sum3([-3, 2]) === -1);`
- ☐ D. `console.assert(sum3(['hello', 2, 3, 4]) === NaN);`

Question 42 of 63



Choose 1 option.

Refer to the code below:

```
const searchText = 'Yay! Salesforce is amazing!';  
  
let result1 = searchText.search(/sales/i);  
let result2 = searchText.search(/sales/);  
  
console.log(result1);  
console.log(result2);
```

After running this code, which result is displayed on the console?

- ☐ A. > 5
 > undefined
- ☐ B. > 5
 > 0
- ☐ C. > true
 > false
- ☒ D. > 5
 > -1

Question 43 of 63



Choose 2 options.

A developer is leading the creation of a new web server for their team that will fulfill API requests from an existing client.

The team wants a web server that runs on Node.js, and they want to use the new web framework Minimalist.js. The lead developer wants to advocate for a more seasoned back-end framework that already has a community around it.

Which two frameworks could the lead developer advocate for?

- ☐ A. Angular
- ☒ B. Express
- ☐ C. Gatsby
- ☒ D. Next.js

Choose 1 option.

A developer wrote the following code:

```
01 let x = object.value;
02
03 try {
04   handleObjectValue(x);
05 } catch(error) {
06   handleError(error);
07 }
```

The developer has a `getNextValue` function to execute after `handleObjectValue()`, but does not want to execute `getNextValue()` if an error occurs.

How can the developer change the code to ensure this behavior?

☐ A. 03 try {
04 handleObjectValue(x);
05 } catch(error) {
06 handleError(error);
07 } then {
08 getNextValue();
09 }

☒ B. 03 try {
04 handleObjectValue(x);
05 getNextValue();
06 } catch(error) {
07 handleError(error);
08 }

☐ C. 03 try {
04 handleObjectValue(x);
05 } catch(error) {

Question 45 of 63



Choose 1 option.

Considering type coercion, what does the following expression evaluate to?

```
true + '13' + NaN
```

☒ A. 'true13NaN'

☐ B. '113NaN'

☐ C. 14

☐ D. 'true13'

Question 46 of 63



Choose 1 option.

Refer to the code below:

```
01 const server = require('server');  
02  
03 // Insert code here
```

A developer imports a library that creates a web server. The imported library uses events and callbacks to start the server.

Which code should be inserted at line 03 to set up an event and start the web server?

- ☒ A. `server.on('connect', (port) => {
 console.log('Listening on', port);
});`
- ☐ B. `server.start();`
- ☐ C. `server((port) => {
 console.log('Listening on', port);
});`
- ☐ D. `server();`

Question 47 of 63



Choose 1 option.

At Universal Containers, every team has its own way of copying JavaScript objects. The code snippet shows an implementation from one team:

```
01 function Person() {  
02   this.firstName = "John";  
03   this.lastName = "Doe";  
04   this.name = () => {  
05     console.log(`Hello ${this.firstName} ${this.lastName}`);  
06   }  
07 }  
08  
09 const john = new Person();  
10 const dan = JSON.stringify(JSON.parse(john));  
11 dan.firstName = 'Dan';  
12 dan.name();
```

What is the output of the code execution?

- ☐ A. Hello John Doe
- ☐ B. Hello Dan Doe
- ☒ C. SyntaxError: Unexpected token in JSON
- ☐ D. Hello Dan

Question 48 of 63



Choose 2 options.

Refer to the code below:

```
01 const event = new CustomEvent(  
02   //Missing code  
03 );  
04 obj.dispatchEvent(event);
```

A developer needs to dispatch a custom event called `update` to send information about `recordId`.

Which two options could a developer insert at the placeholder in line 02 to achieve this?

☐ A. `{type : 'update', recordId : '123abc'}`

☒ B. `'update', {
 detail : {
 recordId : '123abc'
 }
}`

☐ C. `'update', '123abc'`

☒ D. `'update', {
 recordId : '123abc'
}`

Question 49 of 63



Choose 1 option.

Given the HTML below:

```
<div>
  <div id="row-uc">Universal Containers</div>
  <div id="row-as">Applied Shipping</div>
  <div id="row-bt">Burlington Textiles</div>
</div>
```

Which statement adds the `priority-account` CSS class to the Applied Shipping row?

- ☐ A. `document.querySelectorAll('#row-as').classList.add('priority-account');`
- ☐ B. `document.querySelector('#row-as').classList.add('priority-account');`
- ☐ C. `document.querySelector('#row-as').classes.push('priority-account');`
- ☒ D. `document.getElementById('row-as').addClass('priority-account');`

Question 50 of 63



Choose 1 option.

A developer is required to write a function that calculates the sum of elements in an array but is getting undefined every time the code is executed. The developer needs to find what is missing in the code below.

```
01 const sumFunction = arr => {  
02   return arr.reduce((result, current) => {  
03     //  
04     result += current;  
05     //  
06   }, 10);  
07 };
```

Which line replacement makes the code work as expected?

- ☐ A. 03 if(arr.length == 0) { return 0; }
- ☐ B. 04 result = result + current;
- ☐ C. 02 arr.map((result, current) => {
- ☒ D. 05 return result;

Choose 1 option.

A developer wants to create a simple image upload in the browser using the File API. The HTML is below:

```
<input type="file" onchange="previewFile()">
<img src="" height="200" alt="Image preview..."/>
```

The JavaScript portion is:

```
01 function previewFile() {
02   const preview = document.querySelector('img');
03   const file = document.querySelector('input[type=file]').files[0];
04   // line 4 code
05   reader.addEventListener("load", () => {
06     preview.src = reader.result;
07   }, false);
08   //line 8 code
09 }
```

In lines 04 and 08, which code allows the user to select an image from their local computer, and to display the image in the browser?

- ☐ A. 04 const reader = new File();
08 if (file) URL.createObjectURL(file);
- ☒ B. 04 const reader = new FileReader();
08 if (file) reader.readAsDataURL(file);
- ☐ C. 04 const reader = new FileReader();
08 if (file) URL.createObjectURL(file);
- ☐ D. 04 const reader = new File();
08 if (file) reader.readAsDataURL(file);

Choose 2 options.

A developer copied a JavaScript object:

```
01 function Person() {  
02   this.firstName = "John";  
03   this.lastName = "Doe";  
04   this.name = () => `${this.firstName},${this.lastName}`;  
05 }  
06  
07 const john = new Person();  
08 const dan = Object.assign(john);  
09 dan.firstName = 'Dan';
```

How does the developer access dan's firstName, lastName?

- ☐ A. dan.firstName() + dan.lastName()
- ☒ B. dan.name()
- ☐ C. dan.name
- ☒ D. dan.firstName + dan.lastName

Choose 2 options.

A developer copied a JavaScript object:

```
01 function Person() {  
02   this.firstName = "John";  
03   this.lastName = "Doe";  
04   this.name = () => `${this.firstName},${this.lastName}`;  
05 }  
06  
07 const john = new Person();  
08 const dan = Object.assign(john);  
09 dan.firstName = 'Dan';
```

How does the developer access dan's firstName, lastName?

- ☐ A. dan.firstName() + dan.lastName()
- ☒ B. dan.name()
- ☐ C. dan.name
- ☒ D. dan.firstName + dan.lastName

Question 53 of 63



Choose 1 option.

A developer publishes a new version of a package with bug fixes but no breaking changes. The old version number was 2.1.1.

What should the new package version number be based on semantic versioning?

☒ A. 2.1.2

☐ B. 2.2.0

☐ C. 2.2.1

☐ D. 3.1.1

Question 54 of 63



Choose 1 option.

A developer wants to use a module named `universalContainersLib` and then call functions from it.

How should a developer import every function from the module and then call the functions `foo` and `bar`?



A.

```
import * as lib from '/path/universalContainersLib.js';  
lib.foo();  
lib.bar();
```



B.

```
import * from '/path/universalContainersLib.js';  
universalContainersLib.foo();  
universalContainersLib.bar();
```



C.

```
import all from '/path/universalContainersLib.js';  
universalContainersLib.foo();  
universalContainersLib.bar();
```



D.

```
import {foo,bar} from '/path/universalContainersLib.js';  
foo();  
bar();
```

Question 55 of 63



Choose 1 option.

Refer to the following object:

```
01 const cat = {  
02   firstName: 'Fancy',  
03   lastName: 'Whiskers',  
04   get fullName() {  
05     return this.firstName + ' ' + this.lastName;  
06   }  
07 };
```

How can a developer access the `fullName` property for `cat`?

- ☐ A. `cat.fullName()`
- ☐ B. `cat.get.fullName`
- ☐ C. `cat.function.fullName()`
- ☒ D. `cat.fullName`

Question 56 of 63



Choose 1 option.

A developer has two ways to write a function:

Option A:

```
01 function Monster() {  
02   this.growl = () => {  
03     console.log("Grr!");  
04   }  
05 }
```

Option B:

```
01 function Monster() {};  
02 Monster.prototype.growl = () => {  
03   console.log("Grr!");  
04 }
```

After deciding on an option, the developer creates 1000 monster objects.

How many growl methods are created with Option A and Option B?

- ☐ A. 1000 growl methods are created regardless of which option is used.
- ☐ B. 1 growl method is created regardless of which option is used.
- ☒ C. 1000 growl methods are created for Option A.
1 growl method is created for Option B.
- ☐ D. 1 growl method is created for Option A.
1000 growl methods are created for Option B.

Refer to the code below:

```
01 <html lang="en">
02   <table onclick="console.log('Table log');">
03     <tr id="row1">
04       <td>Click me!</td>
05     </tr>
06   </table>
07   <script>
08     function printMessage(event) {
09       console.log('Row log');
10       event.stopPropagation();
11     }
12
13     let elem = document.getElementById('row1');
14     elem.addEventListener('click', printMessage, false);
15   </script>
16 </html>
```

Which code change should be done for the console to log the following when 'Click me!' is clicked?

> Row log
> Table log

- ☐ A. Change line 14 to `elem.addEventListener('click', printMessage, true);`
- ☐ B. Remove lines 13 and 14
- ☐ C. Change line 10 to `event.stopPropagation(false);`
- ☒ D. Remove line 10

Question 58 of 63



Choose 3 options.

```
01 function Animal(size, type) {  
02   this.type = type || 'Animal';  
03   this.canTalk = false;  
04 }  
05  
06 Animal.prototype.speak = function() {  
07   if (this.canTalk) {  
08     console.log("It spoke!");  
09   }  
10 };  
11  
12 let Pet = function(size, type, name, owner) {  
13   Animal.call(this, size, type);  
14   this.size = size;  
15   this.name = name;  
16   this.owner = owner;  
17 }  
18  
19 Pet.prototype = Object.create(Animal.prototype);  
20 let pet1 = new Pet();
```

Given the code above, which three properties are set for pet1?

- ☒ A. speak
- ☐ B. owner
- ☒ C. canTalk
- ☐ D. name
- ☒ E. type

Question 59 of 63



Choose 2 options.

A developer wrote the following code to test a `sum3` function that takes in an array of numbers and returns the sum of the first three numbers in the array. The test passes:

```
01 let res = sum3([1, 2, 3]);  
02 console.assert(res === 6);  
03  
04 res = sum3([1, 2, 3, 4]);  
05 console.assert(res === 6);
```

A different developer made changes to the behavior of `sum3` to instead sum **all** of the numbers present in the array.

Which two results occur when running the test on the updated `sum3` function?

- ☐ A. The line 02 assertion fails.
- ☐ B. The line 05 assertion passes.
- ☒ C. The line 05 assertion fails.
- ☒ D. The line 02 assertion passes.

Question 60 of 63



Choose 1 option.

Given the code below:

```
01 function Person() {  
02   this.firstName = 'John';  
03 }  
04  
05 Person.prototype = {  
06   job: x => 'Developer'  
07 };  
08  
09 const myFather = new Person();  
10 const result = myFather.firstName + ' ' + myFather.job();
```

What is the value of `result` when line 10 executes?

- ☒ A. Error: `myFather.job` is not a function
- ☐ B. undefined Developer
- ☐ C. John Developer
- ☐ D. John undefined

Question 61 of 63



Choose 1 option.

Given the code below:

```
01 setCurrentUrl();  
02 console.log('The current URL is: ' + url);  
03  
04 function setCurrentUrl() {  
05     url = window.location.href;  
06 }
```

What happens when the code executes?

- ☐ A. The `url` variable has global scope and line 02 throws an error.
- ☒ B. The `url` variable has global scope and line 02 executes correctly.
- ☐ C. The `url` variable has local scope and line 02 executes correctly.
- ☐ D. The `url` variable has local scope and line 02 throws an error.

Question 62 of 63



Choose 1 option.

Refer to the code:

```
01 function Vehicle(name, price) {  
02   this.name = name;  
03   this.price = price;  
04 }  
05 Vehicle.prototype.priceInfo = function () {  
06   return `Cost of the ${this.name} is ${this.price}$`;   
07 }  
08 var ford = new Vehicle('Ford Fiesta', '20,000');
```

Given the requirement to refactor the code above to JavaScript class format, which class definition is correct?

☒ A. 01 class Vehicle {
02 constructor(name, price) {
03 this.name = name;
04 this.price = price;
05 }
06 priceInfo() {
07 return `Cost of the \${this.name} is \${this.price}\$`;
08 }
09 }

☐ B. 01 class Vehicle {
02 vehicle(name, price) {
03 this.name = name;
04 this.price = price;
05 }
06 priceInfo() {
07 return `Cost of the \${this.name} is \${this.price}\$`;
08 }
09 }

EXAM: Salesforce Certified JavaScript Developer - Multiple Choice

GRADE: Pass

The report below shows the percentage of questions in each section that you answered correctly for the Salesforce Certified JavaScript Developer - Multiple Choice exam. You will receive this information in your exam results email and can also access it via My Dashboard in Trailhead Academy.

SECTION NAME:	PERCENT CORRECT:
Variables, Types, and Collections	93%
Objects, Functions, and Classes	100%
Browser and Events	90%
Debugging and Error Handling	100%
Asynchronous Programming	100%
Server Side JavaScript	100%
Testing	75%