

Question 1 of 60

Choose 1 option.

Which exception type cannot be caught?

- ☐ A. A custom exception
- ☒ B. `LimitException`
- ☐ C. `NoAccessException`
- ☐ D. `CalloutException`

Question 2 of 60



Choose 2 options.

A developer created a child Lightning web component nested inside a parent Lightning web component. The parent component needs to pass a string value to the child component.

In which two ways can this be accomplished?

- ☒ A. The parent component can invoke a public method in the child component.
- ☒ B. The parent component can use a public property to pass the data to the child component.
- ☐ C. The parent component can use the Apex controller class to send data to the child component.
- ☐ D. The parent component can use a custom event to pass the data to the child component.

Question 3 of 60

Choose 1 option.

Flow Builder uses an Apex action to provide additional information about multiple Contacts, stored in a custom `ContactInfo`.

Which is the correct definition of the Apex method that gets the additional information?

- ☐ A. `@InvocableMethod(label='Additional Info')`
`public List<ContactInfo> getInfo(List<Id> contactIds)`
`{ /*implementation*/ }`
- ☐ B. `@InvocableMethod(label='Additional Info')`
`public ContactInfo getInfo(Id contactId)`
`{ /*implementation*/ }`
- ☐ C. `@InvocableMethod(label='Additional Info')`
`public static ContactInfo getInfo(Id contactId)`
`{ /*implementation*/ }`
- ☒ D. `@InvocableMethod(label='Additional Info')`
`public static List<ContactInfo> getInfo(List<Id> contactIds)`

Question 4 of 60



Choose 2 options.

When a user edits the Postal Code on an Account, a custom Account text field named "Timezone" must be updated based on the values in a `PostalCodeToTimezone__c` custom object.

Which two automation tools can be used to implement this feature?

- ☐ A. Approval process
- ☐ B. Quick actions
- ☒ C. Fast Field Updates record-triggered flow
- ☒ D. Account trigger

Question 5 of 60



Choose 1 option.

Which statement generates a list of Leads and Contacts that have a field with the phrase 'ACME'?

- ☐ A. `List <sObject> searchList = [FIND '*ACME*' IN ALL FIELDS RETURNING Contact, Lead];`
- ☐ B. `Map <sObject> searchList = [FIND '*ACME*' IN ALL FIELDS RETURNING Contact, Lead];`
- ☐ C. `List<List <sObject>> searchList = [SELECT Name, ID FROM Contact, Lead WHERE Name like '%ACME%'];`
- ☒ D. `List<List <sObject>> searchList = [FIND '*ACME*' IN ALL FIELDS RETURNING Contact, Lead];`

Question 6 of 60

Choose 1 option.

Which scenario is valid for execution by unit tests?

- ☐ A. Generate a Visualforce PDF with `getContentAsPDF()`.
- ☐ B. Execute anonymous Apex as a different user.
- ☒ C. Set the created date of a record using a system method.
- ☐ D. Load data from a remote site with a callout.

Question 7 of 60

Choose 1 option.

A developer is tasked with building a custom Lightning web component to collect Contact information.

The form will be shared among many different types of users in the org. There are security requirements that only certain should be edited and viewed by certain groups of users.

What should the developer use in their Lightning Web Component to support the security requirements?

- ☐ A. `aura-input-field`
- ☐ B. `ui-input-field`
- ☒ C. `lightning-input-field`
- ☐ D. `force-input-field`

Question 8 of 60



Choose 2 options.

Universal Containers decides to use purely declarative development to build out a new Salesforce application.

Which two options can be used to build out the business logic layer for this application?

☒ A. Record-Triggered Flow

☐ B. Batch Jobs

☒ C. Validation Rules

☐ D. Remote Actions

Question 9 of 60

Choose 1 option.

A developer created these three Rollup Summary fields in the custom object, `Project__c`:

`Total_Timesheets__c`

`Total_Approved_Timesheets__c`

`Total_Rejected_Timesheet__c`

The developer is asked to create a new field that shows the ratio between rejected and approved timesheets for a

Which should the developer use to implement the business requirement in order to minimize maintenance overhead

- ☐ A. Apex trigger
- ☐ B. Roll-up summary field
- ☐ C. Record-triggered flow
- ☒ D. Formula field

Question 10 of 60

Choose 1 option.

A developer is asked to update code that requires them to validate input into a trigger.

Which Apex Control Flow Statement should the developer use?

- ☒ A. Conditional (If-Else) Statement
- ☐ B. While Loop
- ☐ C. Switch Statement
- ☐ D. For Loop



Choose 2 options.

A developer wants to send an outbound message when a record meets a specific criteria.

Which two features satisfy this use case?

- ☒ A. Flow Builder can be used to check the record criteria and send an outbound message.
- ☒ B. Approval Process can be used to check the record criteria and send an outbound message without Apex code.
- ☐ C. Next Best Action can be used to check the record criteria and send an outbound message.
- ☐ D. Entitlement Process can be used to check the record criteria and send an outbound message without Apex code.

Question 12 of 60

Choose 2 options.

Which two events need to happen when deploying to a production org?

- ☒ A. All Apex code must have at least 75% test coverage.
- ☐ B. All custom objects must have visibility set to a value other than In Development.
- ☐ C. All Visual flows must have at least 1% test coverage.
- ☒ D. All triggers must have some test coverage.

Question 13 of 60

Choose 1 option.

A company has a custom object, `Sales_Help_Request__c`, that has a Lookup relationship to Opportunity. The `Sales_Help_Request__c` has a number field, `Number_of_Hours__c`, that represents the amount of time spent on `Sales_Help_Request__c`.

A developer is tasked with creating a field, `Total_Hours__c`, on Opportunity that should be the sum of all of the `Number_of_Hours__c` values for the `Sales_Help_Request__c` records related to that Opportunity.

What should the developer use to implement this?

- ☐ A. A roll-up summary field on the `Sales_Help_Request__c` object
- ☒ B. A roll-up summary field on the Opportunity object
- ☐ C. A record-triggered flow on the `Sales_Help_Request__c` object
- ☐ D. A trigger on the Opportunity object

Question 14 of 60

Choose 3 options.

Which three Salesforce resources can be accessed from a Lightning web component?

- ☐ A. Content asset files
- ☒ B. SVG resources
- ☒ C. All external libraries
- ☐ D. Third-party web components
- ☒ E. Static resources

Question 15 of 60



Choose 2 options.

Universal Containers hires a developer to build a custom search page to help users find the Accounts they want. Users will be able to search on Name, Description, and a custom comments field.

Which consideration should the developer be aware of when deciding between SOQL and SOSL?

- ☐ A. SOSL is able to return more records.
- ☒ B. SOQL is able to return more records.
- ☒ C. SOSL is faster for text searches.
- ☐ D. SOQL is faster for text searches.

Question 16 of 60



Choose 1 option.

Universal Containers needs to create a custom user interface component that allows users to enter information about their accounts. The component should be able to validate the user input before saving the information to the database.

What is the best technology to create this component?

- ☐ A. Visualforce
- ☒ B. Lightning Web Components
- ☐ C. Flow
- ☐ D. VUE JavaScript framework

Question 17 of 60

Choose 3 options.

Refer to the code snippet below:

```
import fetchOpps from '@salesforce/apex/OpportunitySearch.fetchOpportunities';  
@wire(fetchOpps)  
opportunities;
```

When a Lightning web component is rendered, a list of opportunities that match certain criteria should be retrieved from the database and displayed to the end-user.

Which three considerations must the developer implement to make the `fetchOpportunities` method available within the Lightning web component?

- ☒ A. The method must be annotated with the `@AuraEnabled` annotation.
- ☐ B. The method must be annotated with the `@InvocableMethod` annotation.
- ☒ C. The method cannot mutate the result set retrieved from the database.

Which three considerations must the developer implement to make the `fetchOpportunities` method a Lightning web component?

- ☒ A. The method must be annotated with the `@AuraEnabled` annotation.
- ☐ B. The method must be annotated with the `@InvocableMethod` annotation.
- ☒ C. The method cannot mutate the result set retrieved from the database.
- ☒ D. The method must specify the `(cacheable=true)` attribute.
- ☐ E. The method must specify the `(continuation=true)` attribute.

Question 18 of 60

Choose 3 options.

Which three resources in an Aura component can contain JavaScript functions?

- ☒ A. Helper
- ☐ B. Style
- ☐ C. Design
- ☒ D. Renderer
- ☒ E. Controller

Question 19 of 60



Choose 2 options.

Where are two locations a developer can look to find information about the status of batch or future methods?

- ☒ A. Apex Flex Queue
- ☒ B. Apex Jobs
- ☐ C. Paused Flow Interviews component
- ☐ D. Developer Console

Question 20 of 60



Choose 1 option.

Which code statement includes an Apex method named `updateAccounts` in the class `AccountController` for use in a Lightning web component?

- ☐ A. `import updateAccounts from 'AccountController';`
- ☐ B. `import updateAccounts from '@salesforce/apex/AccountController.updateAccounts';`
- ☒ C. `import updateAccounts from '@salesforce/apex/AccountController';`
- ☐ D. `import updateAccounts from 'AccountController.updateAccounts';`

Question 21 of 60

Choose 2 options.

Universal Containers wants Opportunities to no longer be editable when it reaches the Closed/Won stage.

Which two strategies can a developer use to accomplish this?

- ☒ A. Use a validation rule.
- ☐ B. Use an auto-response rule.
- ☒ C. Use a before-save Apex trigger.
- ☐ D. Use an automatically launched Approval Process.

Question 22 of 60



Choose 2 options.

What are two benefits of using declarative customizations over code?

- ☐ A. Declarative customizations automatically generate test classes.
- ☒ B. Declarative customizations automatically update with each Salesforce release.
- ☒ C. Declarative customizations generally require less maintenance.
- ☐ D. Declarative customizations cannot generate run time errors.

Question 23 of 60



Choose 1 option.

A team of many developers work in their own individual orgs that have the same configuration as the production org.

Which type of org is best suited for this scenario?

- ☐ A. Partner Developer Edition
- ☐ B. Developer Sandbox
- ☒ C. Full Sandbox
- ☐ D. Developer Edition

Question 24 of 60



Choose 1 option.

A developer has an integer variable called `maxAttempts`. The developer needs to ensure that once `maxAttempts` is initialized, it preserves its value for the length of the Apex transaction; while being able to share the variable's state between trigger executions.

How should the developer declare `maxAttempts` to meet these requirements?

- ☐ A. Declare `maxAttempts` as a private static variable on a helper class.
- ☐ B. Declare `maxAttempts` as a member variable on the trigger definition.
- ☒ C. Declare `maxAttempts` as a constant using the `static` and `final` keywords.
- ☐ D. Declare `maxAttempts` as a variable on a helper class.

Question 25 of 60



Choose 1 option.

A developer needs to create a baseline set of data (Accounts, Contacts, Products, Assets) for an entire suite of Apex tests allowing them to test isolated requirements for various types of Salesforce cases.

Which approach can efficiently generate the required data for each unit test?

- ☐ A. Create a mock using the `HttpCalloutMock` interface.
- ☒ B. Use `@TestSetup` with a void method.
- ☐ C. Add `@IsTest (seeAllData=true)` at the start of the unit test class.
- ☐ D. Create test data before `Test.startTest()` in the unit test.

Question 26 of 60

Choose 1 option.

What is one limitation of Agentforce's language support capabilities?

- ☐ A. Language support for toxicity is the same as the supported languages.
- ☐ B. Topic and action instructions are supported in multiple languages.
- ☐ C. Language and tone settings impact the output of agent actions when specified.
- ☒ D. Language support may differ by agent type.

Question 27 of 60

Choose 1 option.

A developer is creating an app that contains multiple Lightning web components.

One of the child components is used for navigation purposes. When a user clicks a button called Next in the child component, the parent component must be alerted so it can navigate to the next page.

How should this be accomplished?

- ☐ A. Update a property on the parent.
- ☒ B. Create a custom event.
- ☐ C. Fire a notification.
- ☐ D. Call a method in the Apex controller.

Question 28 of 60

Choose 2 options.

Which two settings must be defined in order to update a record of a junction object?

- ☐ A. Read access on the primary relationship
- ☒ B. Read/Write access on the primary relationship
- ☒ C. Read/Write access on the secondary relationship
- ☐ D. Read/Write access on the junction object

Question 29 of 60



Choose 1 option.

A company has a custom object, `Order__c`, that has a required, unique external ID field called `Order_Number__c`.

Which statement should be used to perform the DML necessary to insert new records and update existing records in a list of `Order__c` records using the external ID field?

- ☐ A. `upsert orders;`
- ☐ B. `merge orders;`
- ☐ C. `merge orders Order_Number__c;`
- ☒ D. `upsert orders Order_Number__c;`

Question 30 of 60

Choose 1 option.

Which annotation exposes an Apex class as a RESTful web service?

- ☒ A. `@AuraEnabled(cacheable=true)`
- ☐ B. `@RemoteAction`
- ☐ C. `@HttpInvocable`
- ☐ D. `@RestResource(urlMapping='/myService/*')`

Question 31 of 60

Choose 1 option.

What can be used to override the Account's standard Edit button for Lightning Experience?

- ☐ A. Lightning flow
- ☐ B. Lightning page
- ☐ C. Lightning action
- ☒ D. Lightning component

Question 32 of 60

Choose 1 option.

What is a benefit of developing applications in a multi-tenant environment?

- ☐ A. Unlimited processing power and memory
- ☐ B. Enforced unit testing and code coverage best practices
- ☐ C. Preconfigured storage for big data
- ☒ D. Access to predefined computing resources

Question 33 of 60

Choose 1 option.

A developer must create a `CreditCardPayment` class that provides an implementation of an existing `Payment` class.

```
public virtual class Payment {  
    public virtual void makePayment(Decimal amount) { /*implementation*/ }  
}
```

Which is the correct implementation?

- ☒ A.

```
public class CreditCardPayment extends Payment {  
    public override void makePayment(Decimal amount) { /*implementation*/ }  
}
```
- ☐ B.

```
public class CreditCardPayment implements Payment {  
    public override void makePayment(Decimal amount) { /*implementation*/ }  
}
```

Question 34 of 60

Choose 2 options.

A developer is using Agentforce Dev Assistant. Inline autocomplete is not available.

What are two possible causes?

- ☒ A. Auto Completions are toggled off.
- ☐ B. Telemetry settings are misconfigured.
- ☐ C. VSCode has been idle for 1 hour.
- ☒ D. VSCode Inline Suggest is not enabled.

Question 35 of 60

Choose 1 option.

A developer is creating a Lightning web component to show a list of sales records.

The Sales Representative user should be able to see the commission field on each record. The Sales Assistant user should be able to see all fields on the record except the commission field.

How should this be enforced so that the component works for both users without showing any errors?

- ☒ A. Use `Security.stripInaccessible` to remove fields inaccessible to the current user.
- ☐ B. Use Lightning Data Service to get the collection of sales records.
- ☐ C. Use `WITH SECURITY_ENFORCED` in the SOQL that fetches the data for the component.
- ☐ D. Use Lightning Locker Service to enforce sharing rules and field-level security.

Question 36 of 60



Choose 3 options.

Which three statements are accurate about debug logs?

- ☐ A. Debug log levels are cumulative, where FINE log level includes all events logged at the DEBUG, INFO, WARN, and ERROR levels.
- ☒ B. System debug logs are retained for 24 hours.
- ☐ C. Only the 20 most recent debug logs for a user are kept.
- ☒ D. Debug logs can be set for specific users, classes, and triggers.
- ☒ E. The maximum size of a debug log is 5 MB.

Question 37 of 60

Choose 3 options.

What are three ways for a developer to execute tests in an org?

- ☒ A. Tooling API
- ☒ B. Salesforce DX
- ☐ C. Metadata API
- ☒ D. Setup Menu
- ☐ E. Bulk API

Question 38 of 60

Choose 2 options.

What are two use cases for executing Anonymous Apex code?

- ☒ A. To schedule an Apex class to run periodically
- ☐ B. To delete 15,000 inactive Accounts in a single transaction after a deployment
- ☒ C. To run a batch Apex class to update all Contacts
- ☐ D. To add unit test code coverage to an org



Choose 1 option.

An Opportunity needs to have an amount rolled up from a custom object that is not in a master-detail relationship.

How can this be achieved?

- ☐ A. Use the Metadata API to create real-time roll-up summaries.
- ☒ B. Write a trigger on the child object and use an aggregate function to sum the amount for all related child objects under the Opportunity.
- ☐ C. Write a trigger on the Opportunity object and use tree sorting to sum the amount for all related child objects under the Opportunity.
- ☐ D. Use the Streaming API to create real-time roll-up summaries.

Question 40 of 60



Choose 1 option.

A developer created a trigger on the Account object. While testing the trigger, the developer sees the error message 'Maximum trigger depth exceeded'.

What could be the possible causes?

- ☒ A. The trigger is getting executed multiple times.
- ☐ B. The trigger is too long and should be refactored into a helper class.
- ☐ C. The trigger does not have sufficient code coverage.
- ☐ D. The developer does not have the correct user permission.

Question 41 of 60

Choose 1 option.

In the following example, which sharing context will `myMethod` execute when it is invoked?

```
public class myClass {  
    public void myMethod() { /* implementation */ }  
}
```

- ☒ A. Sharing rules will be inherited from the calling context.
- ☐ B. Sharing rules will be enforced for the running user.
- ☐ C. Sharing rules will not be enforced for the running user.
- ☐ D. Sharing rules will be enforced by the instantiating class.

Question 42 of 60



Choose 1 option.

Universal Containers wants to ensure that all new leads created in the system have a valid email address. They have already created a validation rule to enforce this requirement, but want to add an additional layer of validation using automation.

What would be the best solution for this requirement?

- ☐ A. Use a custom Lightning Web component to make a callout to validate the fields on a third party system.
- ☒ B. Use a before-save Apex trigger on the Lead object to validate the email address and display an error message if it is invalid
- ☐ C. Submit a REST API Callout with a JSON payload and validate the fields on a third party system
- ☐ D. Use an Approval Process to enforce the completion of a valid email address using an outbound message action.

Question 43 of 60



Choose 1 option.

While working in a sandbox, an Apex test fails when run in the Test Runner. However, executing the Apex logic in the Execute Anonymous window succeeds with no exceptions or errors.

Why did the method fail in the sandbox test framework but succeed in the Developer Console?

- ☒ A. The test method relies on existing data in the sandbox.
- ☐ B. The test method has a syntax error in the code.
- ☐ C. The test method is calling an `@future` method.
- ☐ D. The test method does not use `System.runAs` to execute as a specific user.

Question 44 of 60

Choose 1 option.

A developer must perform a complex SOQL query that joins two objects in a Lightning component.

How can the Lightning component execute the query?

- ☐ A. Create a flow to execute the query and invoke from the Lightning component.
- ☒ B. Invoke an Apex class with the method annotated as `@AuraEnabled` to perform the query.
- ☐ C. Write the query in a custom Lightning web component wrapper and invoke from the Lightning component.
- ☐ D. Use the Salesforce Streaming API to perform the SOQL query.

Question 45 of 60

Choose 1 option.

What will be the output in the debug log in the event of a `QueryException` during a call to the `aQuery` method in the following example?

```
public class myClass {  
    class CustomException extends Exception {}  
    public static Account aQuery() {  
        Account theAccount;  
        try {  
            system.debug('Querying Accounts.');            theAccount = [SELECT Id FROM Account WHERE CreatedDate > TODAY];  
        }  
        catch (CustomException eX) {  
            system.debug('Custom Exception.');        }  
        catch (QueryException eX) {  
            system.debug('Query Exception.');        }  
        finally {  
            system.debug('Done.');        }  
    }  
}
```

Choose 1 option.

```
        return theAccount;  
    }  
}
```

- ☐ A. Querying Accounts.
Custom Exception.
- ☐ B. Querying Accounts.
Custom Exception.
Done.
- ☒ C. Querying Accounts.
Query Exception.
Done.
- ☐ D. Querying Accounts.
Query Exception.

Question 46 of 60

Choose 1 option.

Which code displays the contents of a Visualforce page as a PDF?

- ☐ A. `<apex:page contentType="application/pdf">`
- ☒ B. `<apex:page renderAs="pdf">`
- ☐ C. `<apex:page renderAs="application/pdf">`
- ☐ D. `<apex:page contentType="pdf">`

Question 47 of 60



Choose 2 options.

A developer created a trigger on the Account object and wants to test if the trigger is properly bulkified. The developer team decided that the trigger should be tested with 200 account records with unique names.

What two things should be done to create the test data within the unit test with the least amount of code?

- ☒ A. Create a static resource containing test data.
- ☐ B. Use the `@isTest(isParallel=true)` annotation in the test class.
- ☒ C. Use `Test.loadData` to populate data in your test methods.
- ☐ D. Use the `@isTest(seeAllData=true)` annotation in the test class.

Question 49 of 60

Choose 1 option.

A Developer Edition org has five existing accounts. A developer wants to add 10 more accounts for testing purposes.

The following code is executed in the Developer Console using the Execute Anonymous window:

```
Account myAccount = new Account(Name = 'MyAccount');
insert myAccount;

Integer x = 1;
List<Account> newAccounts = new List<Account>();
do {
    Account acct = new Account (Name = 'New Account ' + x++);
    newAccounts.add(acct);
} while (x < 10);
```

How many total accounts will be in the org after this code is executed?

☐ A. 15

```
newAccounts.add(acct);  
} while (x < 10);
```

How many total accounts will be in the org after this code is executed?

☐ A. 15

☐ B. 6

☐ C. 5

☒ D. 10

Question 50 of 60

Choose 1 option.

Universal Containers has a support process that allows users to request support from its engineering team using a custom `Engineering_Support__c`.

Users should be able to associate multiple `Engineering_Support__c` records to a single Opportunity record. Additionally, aggregate information about the `Engineering_Support__c` records should be shown on the Opportunity record.

Which relationship field should be implemented to support these requirements?

- ☐ A. Lookup field from `Engineering_Support__c` to Opportunity
- ☒ B. Master-detail field from `Engineering_Support__c` to Opportunity
- ☐ C. Master-detail field from Opportunity to `Engineering_Support__c`

Question 51 of 60

Choose 3 options.

For which three items can a trace flag be configured?

- ☐ A. Flow
- ☒ B. Apex Class
- ☐ C. Visualforce
- ☒ D. Apex Trigger
- ☒ E. User

Question 52 of 60

Choose 2 options.

Which two operations affect the number of times a trigger can fire?

- ☒ A. After-save record-triggered flow
- ☐ B. Email messages
- ☒ C. Roll-up summary fields
- ☐ D. Criteria-based sharing calculations

Question 53 of 60



Choose 1 option.

Universal Containers has an order system that uses an Order Number to identify an order for customers and service agents. Order records will be imported into Salesforce.

How should the Order Number field be defined in Salesforce?

- ☐ A. Indirect Lookup
- ☒ B. External ID and Unique
- ☐ C. Lookup
- ☐ D. Direct Lookup

Question 54 of 60



Choose 2 options.

If Apex code executes inside the `execute()` method of an Apex class when implementing the `Batchable` interface, which two statements are true regarding governor limits?

- ☐ A. The Apex governor limits are omitted while calling the constructor of the Apex class.
- ☐ B. The Apex governor limits will use the asynchronous limit levels.
- ☒ C. The Apex governor limits are reset for each iteration of the `execute()` method.
- ☒ D. The Apex governor limits cannot be exceeded due to the asynchronous nature of the transaction.

Question 55 of 60



Choose 1 option.

A custom picklist field, `Food_Preference__c`, exists on a custom object. The picklist contains the following options: 'Vegan', 'Kosher', 'No Preference'. The developer must ensure a value is populated every time a record is created or updated.

What is the optimal way to ensure a value is selected every time a record is saved?

- ☒ A. Mark the field as Required on the field definition.
- ☐ B. Write an Apex trigger to ensure a value is selected.
- ☐ C. Set "Use the first value in the list as the default value" to True.
- ☐ D. Mark the field as Required on the object's page layout.

Question 56 of 60



Choose 1 option.

A developer needs to confirm that a Contact trigger works correctly without changing the organization's data.

What should the developer do to test the Contact trigger?

- ☐ A. Use Deploy from the VSCode IDE to deploy an 'insert Contact' Apex class.
- ☐ B. Use the Open Execute Anonymous feature on the Developer Console to run an 'insert Contact' DML statement.
- ☐ C. Use the New button on the Salesforce Contacts Tab to create a new Contact record.
- ☒ D. Use the Test menu on the Developer Console to run all test classes for the Contact trigger.

Question 57 of 60



Choose 1 option.

Which Apex class contains methods to return the amount of resources that have been used for a particular governor, such as the number of DML statements?

- ☐ A. Exception
- ☐ B. Messaging
- ☐ C. OrgLimits
- ☒ D. Limits

Question 58 of 60

Choose 1 option.

Which action causes a before trigger to fire by default for Accounts?

- ☐ A. Converting Leads to Contacts
- ☒ B. Importing data using the Data Loader and the Bulk API
- ☐ C. Renaming or replacing picklists
- ☐ D. Updating addresses using the Mass Address update tool

Question 59 of 60

Choose 2 options.

Management asked for opportunities to be automatically created for accounts with annual revenue greater than \$1,000. A developer created the following trigger on the Account object to satisfy this requirement.

```
for(Account a: Trigger.new){
    if(a.AnnualRevenue > 1000000){
        List<Opportunity> oppList = [SELECT Id FROM Opportunity WHERE accountId = :a.Id];
        if(oppList.size() == 0){
            Opportunity oppty = new Opportunity(Name = a.name, StageName = 'Prospecting',
            CloseDate = system.today().addDays(30));
            insert oppty;
        }
    }
}
```

Users are able to update the account records via the UI and can see an opportunity created for high annual revenue accounts. However, when the administrator tries to upload a list of 179 accounts using Data Loader, it fails with custom exception.

```
        }  
    }  
}
```

Users are able to update the account records via the UI and can see an opportunity created for high annual revenue accounts. However, when the administrator tries to upload a list of 179 accounts using Data Loader, it fails with `System.Exception` errors.

Which two actions should the developer take to fix the code segment shown above?

- ☒ A. Move the DML that saves opportunities outside the `for` loop.
- ☐ B. Check if all the required fields for Opportunity are being added on creation.
- ☐ C. Use `Database.query` to query the opportunities.
- ☒ D. Query for existing opportunities outside the `for` loop.

Question 60 of 60



Choose 2 options.

In terms of the MVC paradigm, what are two advantages of implementing the view layer of a Salesforce application using Lightning Web Component-based development over Visualforce?

- ☒ A. Rich component ecosystem
- ☐ B. Server-side run-time debugging
- ☒ C. Self-contained and reusable units of an application
- ☐ D. Automatic code generation

EXAM: Salesforce Certified Platform Developer

GRADE: Pass

The report below shows the percentage of questions in each section that you answered correctly for the Salesforce Certified Platform Developer exam. You will receive this information in your exam results email and can also access it via My Dashboard in Trailhead Academy.

SECTION NAME:	PERCENT CORRECT:
Developer Fundamentals	94%
Process Automation and Logic	71%
User Interface	87%
Testing, Debugging, and Deployment	83%

Question 39 of 60

Choose 1 option.

A developer receives an error when compiling the following code.

```
switch on sobject {  
  when Account a, Contact c {  
    System.debug('account ' + a);  
    System.debug('contact ' + c);  
  }  
  when null {  
    System.debug('null');  
  }  
  when else {  
    System.debug('default');  
  }  
}
```

What is the error?

- ☐ A. There is an unexpected token.

```
    System.debug('null');  
}  
when else {  
    System.debug('default');  
}  
}
```

What is the error?

- ☐ A. There is an unexpected token 'Contact'.
- ☒ B. Only one sObject type per when block can be used.
- ☐ C. There is incompatible variable binding.
- ☐ D. Switch statements cannot contain multiple when values.

Question 19 of 60

Choose 2 options.

Which two Agentforce limitations should a developer consider when building an agent?

- ☐ A. Version control is supported for agents.
- ☐ B. The Agent API has a 90-second timeout.
- ☒ C. Custom actions that reference an Apex class or flow support only primitive data types.
- ☒ D. Inbound messages sent via messaging channels have character limits.

Question 24 of 60

Choose 1 option.

A developer is using Agentforce Dev Assistant and noticed that the output from their prompt resembles proprietary code.

Which model training considerations should the developer be aware of when utilizing the extension?

- ☐ A. Dev Assistant anonymized PII data in customer code that was used to train the model.
- ☒ B. Dev Assistant generated output that resembles the code that was used to train the model.
- ☐ C. Dev Assistant can reference other developers' code and train the model in near real time.
- ☐ D. Dev Assistant can reference the developer's prior prompts to generate output in near real time.