

## Question 1 of 60

Choose 1 option.

Which action causes a before trigger to fire by default for Accounts?

- ☐ A. Renaming or replacing picklists
- ☒ B. Importing data using the Data Loader and the Bulk API
- ☐ C. Converting Leads to Contacts
- ☐ D. Updating addresses using the Mass Address update tool

## Question 2 of 60



Choose 1 option.

Which code displays the contents of a Visualforce page as a PDF?

- ☒ A. `<apex:page renderAs="pdf">`
- ☐ B. `<apex:page contentType="pdf">`
- ☐ C. `<apex:page renderAs="application/pdf">`
- ☐ D. `<apex:page contentType="application/pdf">`

### Question 3 of 60



Choose 1 option.

Which Apex class contains methods to return the amount of resources that have been used for a particular governor, such as the number of DML statements?

- ☐ A. Messaging
- ☒ B. Limits
- ☐ C. Exception
- ☐ D. OrgLimits

### Question 4 of 60



Choose 1 option.

Flow Builder uses an Apex action to provide additional information about multiple Contacts, stored in a custom class, `ContactInfo`.

Which is the correct definition of the Apex method that gets the additional information?

- ☐ A. 

```
@InvocableMethod(label='Additional Info')
public ContactInfo getInfo(Id contactId)
{ /*implementation*/ }
```
- ☐ B. 

```
@InvocableMethod(label='Additional Info')
public static ContactInfo getInfo(Id contactId)
{ /*implementation*/ }
```
- ☐ C. 

```
@InvocableMethod(label='Additional Info')
public List<ContactInfo> getInfo(List<Id> contactIds)
{ /*implementation*/ }
```
- ☒ D. 

```
@InvocableMethod(label='Additional Info')
public static List<ContactInfo> getInfo(List<Id> contactIds)
{ /*implementation*/ }
```

### Question 5 of 60



Choose 2 options.

A developer wants to send an outbound message when a record meets a specific criteria.

Which two features satisfy this use case?

- ☐ A. Next Best Action can be used to check the record criteria and send an outbound message.
- ☒ B. Flow Builder can be used to check the record criteria and send an outbound message.
- ☐ C. Entitlement Process can be used to check the record criteria and send an outbound message without Apex code.
- ☒ D. Approval Process can be used to check the record criteria and send an outbound message without Apex code.

### Question 6 of 60



Choose 2 options.

Management asked for opportunities to be automatically created for accounts with annual revenue greater than \$1,000,000. A developer created the following trigger on the Account object to satisfy this requirement.

```
for(Account a: Trigger.new){
    if(a.AnnualRevenue > 1000000){
        List<Opportunity> oppList = [SELECT Id FROM Opportunity WHERE accountId = :a.Id];
        if(oppList.size() == 0){
            Opportunity oppty = new Opportunity(Name = a.name, StageName = 'Prospecting',
            CloseDate = system.today().addDays(30));
            insert oppty;
        }
    }
}
```

Users are able to update the account records via the UI and can see an opportunity created for high annual revenue accounts. However, when the administrator tries to upload a list of 179 accounts using Data Loader, it fails with `System.Exception` errors.

Which two actions should the developer take to fix the code segment shown above?

- ☐ A. Use `Database.query` to query the opportunities.

## Question 6 of 60



Choose 2 options.

```
List<Opportunity> oppList = [SELECT Id FROM Opportunity WHERE accountId = :a.Id];
if(oppList.size() == 0){
    Opportunity oppty = new Opportunity(Name = a.name, StageName = 'Prospecting',
    CloseDate = system.today().addDays(30));
    insert oppty;
}
}
```

Users are able to update the account records via the UI and can see an opportunity created for high annual revenue accounts. However, when the administrator tries to upload a list of 179 accounts using Data Loader, it fails with `System.Exception` errors.

Which two actions should the developer take to fix the code segment shown above?

- ☐ A. Use `Database.query` to query the opportunities.
- ☒ B. Move the DML that saves opportunities outside the `for` loop.
- ☒ C. Query for existing opportunities outside the `for` loop.
- ☐ D. Check if all the required fields for Opportunity are being added on creation.

## Question 7 of 60



Choose 2 options.

A developer created a child Lightning web component nested inside a parent Lightning web component. The parent component needs to pass a string value to the child component.

In which two ways can this be accomplished?

- ☐ A. The parent component can use the Apex controller class to send data to the child component.
- ☒ B. The parent component can invoke a public method in the child component.
- ☐ C. The parent component can use a custom event to pass the data to the child component.
- ☒ D. The parent component can use a public property to pass the data to the child component.

### Question 8 of 60



Choose 1 option.

A developer is tasked with building a custom Lightning web component to collect Contact information.

The form will be shared among many different types of users in the org. There are security requirements that only certain fields should be edited and viewed by certain groups of users.

What should the developer use in their Lightning Web Component to support the security requirements?

- ☐ A. lightning-input-field
- ☒ B. force-input-field
- ☐ C. ui-input-field
- ☐ D. aura-input-field

### Question 9 of 60



Choose 2 options.

When a user edits the Postal Code on an Account, a custom Account text field named "Timezone" must be updated based on the values in a `PostalCodeToTimezone__c` custom object.

Which two automation tools can be used to implement this feature?

- ☒ A. Fast Field Updates record-triggered flow
- ☐ B. Quick actions
- ☐ C. Approval process
- ☒ D. Account trigger

### Question 10 of 60



Choose 1 option.

How is a controller and extension specified for a custom object named "Notice" on a Visualforce page?

- ☐ A. `apex:page standardController="Notice__c" extensions="myControllerExtension"`
- ☒ B. `apex:page controller="Notice__c" extensions="myControllerExtension"`
- ☐ C. `apex:page controllers="Notice__c, myControllerExtension"`
- ☐ D. `apex:page=Notice extends="myControllerExtension"`

### Question 11 of 60



Choose 1 option.

What should be used to create scratch orgs?

- ☐ A. Sandbox refresh
- ☒ B. Salesforce CLI
- ☐ C. Workbench
- ☐ D. Developer Console

### Question 12 of 60



Choose 1 option.

A developer is integrating with a legacy on-premise SQL database.

What should the developer use to ensure the data being integrated is matched to the right records in Salesforce?

- ☒ A. External ID field
- ☐ B. Formula field
- ☐ C. Lookup field
- ☐ D. External Object

### Question 13 of 60



Choose 2 options.

Which two settings must be defined in order to update a record of a junction object?

- ☒ A. Read/Write access on the primary relationship
- ☒ B. Read/Write access on the secondary relationship
- ☐ C. Read access on the primary relationship
- ☐ D. Read/Write access on the junction object

### Question 14 of 60



Choose 3 options.

Which three Salesforce resources can be accessed from a Lightning web component?

- ☐ A. Third-party web components
- ☒ B. SVG resources
- ☐ C. All external libraries
- ☒ D. Static resources
- ☒ E. Content asset files

### Question 15 of 60



Choose 2 options.

What are two use cases for executing Anonymous Apex code?

- ☐ A. To add unit test code coverage to an org
- ☒ B. To run a batch Apex class to update all Contacts
- ☐ C. To delete 15,000 inactive Accounts in a single transaction after a deployment
- ☒ D. To schedule an Apex class to run periodically

### Question 16 of 60



Choose 2 options.

Universal Containers hires a developer to build a custom search page to help users find the Accounts they want. Users will be able to search on Name, Description, and a custom comments field.

Which consideration should the developer be aware of when deciding between SOQL and SOSL?

- ☐ A. SOQL is faster for text searches.
- ☒ B. SOSL is faster for text searches.
- ☒ C. SOQL is able to return more records.
- ☐ D. SOSL is able to return more records.

### Question 17 of 60



Choose 1 option.

A custom picklist field, `Food_Preference__c`, exists on a custom object. The picklist contains the following options: 'Vegan', 'Kosher', 'No Preference'. The developer must ensure a value is populated every time a record is created or updated.

What is the optimal way to ensure a value is selected every time a record is saved?

- ☒ A. Mark the field as Required on the field definition.
- ☐ B. Write an Apex trigger to ensure a value is selected.
- ☐ C. Mark the field as Required on the object's page layout.
- ☐ D. Set "Use the first value in the list as the default value" to True.

### Question 18 of 60



Choose 2 options.

Universal Containers wants Opportunities to no longer be editable when it reaches the Closed/Won stage.

Which two strategies can a developer use to accomplish this?

- ☐ A. Use an auto-response rule.
- ☐ B. Use an automatically launched Approval Process.
- ☒ C. Use a validation rule.
- ☒ D. Use a before-save Apex trigger.

### Question 19 of 60



Choose 3 options.

Which three statements are accurate about debug logs?

- ☒ A. System debug logs are retained for 24 hours.
- ☐ B. The maximum size of a debug log is 5 MB.
- ☒ C. Debug log levels are cumulative, where FINE log level includes all events logged at the DEBUG, INFO, WARN, and ERROR levels.
- ☒ D. Debug logs can be set for specific users, classes, and triggers.
- ☐ E. Only the 20 most recent debug logs for a user are kept.

## Question 20 of 60



Choose 1 option.

A developer is creating an app that contains multiple Lightning web components.

One of the child components is used for navigation purposes. When a user clicks a button called Next in the child component, the parent component must be alerted so it can navigate to the next page.

How should this be accomplished?

- ☐ A. Fire a notification.
- ☐ B. Call a method in the Apex controller.
- ☐ C. Update a property on the parent.
- ☒ D. Create a custom event.

## Question 21 of 60



Choose 1 option.

A Developer Edition org has five existing accounts. A developer wants to add 10 more accounts for testing purposes.

The following code is executed in the Developer Console using the Execute Anonymous window:

```
Account myAccount = new Account (Name = 'MyAccount');
insert myAccount;

Integer x = 1;
List<Account> newAccounts = new List<Account>();
do {
    Account acct = new Account (Name = 'New Account ' + x++);
    newAccounts.add(acct);
} while (x < 10);
```

How many total accounts will be in the org after this code is executed?

- ☐ A. 15
- ☐ B. 10
- ☒ C. 6

### Question 22 of 60



Choose 1 option.

An Opportunity needs to have an amount rolled up from a custom object that is not in a master-detail relationship.

How can this be achieved?

- ☐ A. Write a trigger on the Opportunity object and use tree sorting to sum the amount for all related child objects under the Opportunity.
- ☒ B. Write a trigger on the child object and use an aggregate function to sum the amount for all related child objects under the Opportunity.
- ☐ C. Use the Streaming API to create real-time roll-up summaries.
- ☐ D. Use the Metadata API to create real-time roll-up summaries.

### Question 23 of 60



Choose 2 options.

Which two operations affect the number of times a trigger can fire?

- ☐ A. Email messages
- ☒ B. After-save record-triggered flow
- ☐ C. Criteria-based sharing calculations
- ☒ D. Roll-up summary fields

## Question 24 of 60



Choose 2 options.

Universal Containers recently transitioned from Classic to Lightning Experience.

One of its business processes requires certain values from the Opportunity object to be sent via an HTTP REST callout to its external order management system when the user presses a custom button on the Opportunity detail page. Example values are as follows:

- Name
- Amount
- Account

Which two methods should the developer implement to fulfill the business requirement?

- ☒ A. Create an after update trigger on the Opportunity object that calls a helper method using `@Future(Callout=true)` to perform the HTTP REST callout.
- ☐ B. Create a Remote Action on the Opportunity object that executes an Apex immediate action to perform the HTTP REST callout whenever the Opportunity is updated.
- ☐ C. Create a Lightning component quick action that performs the HTTP REST callout, and use a Lightning Action to expose the component on the Opportunity detail page.
- ☒ D. Create a custom Visualforce quick action that performs the HTTP REST callout, and use a Visualforce quick

## Question 25 of 60



Choose 1 option.

A team of many developers work in their own individual orgs that have the same configuration as the production org.

Which type of org is best suited for this scenario?

- ☒ A. Developer Sandbox
- ☐ B. Partner Developer Edition
- ☐ C. Developer Edition
- ☐ D. Full Sandbox

### Question 26 of 60



Choose 1 option.

Which code statement includes an Apex method named `updateAccounts` in the class `AccountController` for use in a Lightning web component?

- ☐ A. `import updateAccounts from 'AccountController';`
- ☐ B. `import updateAccounts from '@salesforce/apex/AccountController';`
- ☒ C. `import updateAccounts from '@salesforce/apex/AccountController.updateAccounts';`
- ☐ D. `import updateAccounts from 'AccountController.updateAccounts';`

### Question 27 of 60



Choose 1 option.

A developer is creating a Lightning web component to show a list of sales records.

The Sales Representative user should be able to see the commission field on each record. The Sales Assistant user should be able to see all fields on the record except the commission field.

How should this be enforced so that the component works for both users without showing any errors?

- ☐ A. Use `WITH SECURITY_ENFORCED` in the SOQL that fetches the data for the component.
- ☐ B. Use Lightning Data Service to get the collection of sales records.
- ☐ C. Use Lightning Locker Service to enforce sharing rules and field-level security.
- ☒ D. Use `Security.stripInaccessible` to remove fields inaccessible to the current user.

### Question 28 of 60



Choose 1 option.

While working in a sandbox, an Apex test fails when run in the Test Runner. However, executing the Apex logic in the Execute Anonymous window succeeds with no exceptions or errors.

Why did the method fail in the sandbox test framework but succeed in the Developer Console?

- ☐ A. The test method is calling an `@future` method.
- ☐ B. The test method does not use `System.runAs` to execute as a specific user.
- ☐ C. The test method has a syntax error in the code.
- ☒ D. The test method relies on existing data in the sandbox.

### Question 29 of 60



Choose 1 option.

A developer created these three Rollup Summary fields in the custom object, `Project__c`:

```
Total_Timesheets__c  
Total_Approved_Timesheets__c  
Total_Rejected_Timesheet__c
```

The developer is asked to create a new field that shows the ratio between rejected and approved timesheets for a given project.

Which should the developer use to implement the business requirement in order to minimize maintenance overhead?

- ☐ A. Roll-up summary field
- ☐ B. Record-triggered flow
- ☒ C. Formula field
- ☐ D. Apex trigger

### Question 30 of 60



Choose 2 options.

If Apex code executes inside the `execute()` method of an Apex class when implementing the `Batchable` interface, which two statements are true regarding governor limits?

- ☐ A. The Apex governor limits will use the asynchronous limit levels.
- ☐ B. The Apex governor limits are omitted while calling the constructor of the Apex class.
- ☒ C. The Apex governor limits cannot be exceeded due to the asynchronous nature of the transaction.
- ☒ D. The Apex governor limits are reset for each iteration of the `execute()` method.

### Question 31 of 60



Choose 1 option.

Which annotation exposes an Apex class as a RESTful web service?

- ☐ A. `@AuraEnabled(cacheable=true)`
- ☒ B. `@RestResource(urlMapping='/myService/*')`
- ☐ C. `@HttpInvocable`
- ☐ D. `@RemoteAction`

### Question 32 of 60



Choose 2 options.

Which two events need to happen when deploying to a production org?

- ☐ A. All Apex code must have at least 75% test coverage.
- ☒ B. All triggers must have some test coverage.
- ☐ C. All custom objects must have visibility set to a value other than In Development.
- ☐ D. All Visual flows must have at least 1% test coverage.

### Question 32 of 60



Choose 2 options.

Which two events need to happen when deploying to a production org?

- ☒ A. All Apex code must have at least 75% test coverage.
- ☒ B. All triggers must have some test coverage.
- ☐ C. All custom objects must have visibility set to a value other than In Development.
- ☐ D. All Visual flows must have at least 1% test coverage.

### Question 33 of 60



Choose 3 options.

A developer needs to allow users to complete a form on an Account record that will create a record for a custom object.

The form needs to display different fields depending on the user's job role. The functionality should only be available to a small group of users.

Which three things should the developer do to satisfy these requirements?

- ☒ A. Create a Custom Permission for the users.
- ☒ B. Add a Dynamic Action to the Account Record Page.
- ☐ C. Create a Lightning web component.
- ☒ D. Create a Dynamic Form.
- ☐ E. Add a Dynamic Action to the Users' assigned Page Layouts.

### Question 34 of 60



Choose 1 option.

A developer needs to confirm that a Contact trigger works correctly without changing the organization's data.

What should the developer do to test the Contact trigger?

- ☐ A. Use Deploy from the VSCode IDE to deploy an 'insert Contact' Apex class.
- ☐ B. Use the New button on the Salesforce Contacts Tab to create a new Contact record.
- ☒ C. Use the Test menu on the Developer Console to run all test classes for the Contact trigger.
- ☐ D. Use the Open Execute Anonymous feature on the Developer Console to run an 'insert Contact' DML statement.

### Question 35 of 60



Choose 1 option.

A developer needs to create a baseline set of data (Accounts, Contacts, Products, Assets) for an entire suite of Apex tests allowir them to test isolated requirements for various types of Salesforce cases.

Which approach can efficiently generate the required data for each unit test?

- ☐ A. Create test data before `Test.startTest()` in the unit test.
- ☐ B. Create a mock using the `HttpCalloutMock` interface.
- ☒ C. Use `@TestSetup` with a void method.
- ☐ D. Add `@IsTest(seeAllData=true)` at the start of the unit test class.

### Question 36 of 60



Choose 1 option.

Cloud Kicks has a multi-screen flow that its call center agents use when handling inbound service desk calls.

At one of the steps in the flow, the agents should be presented with a list of order numbers and dates that are retrieved from an external order management system in real time and displayed on the screen.

What should a developer use to satisfy this requirement?

- ☐ A. An invocable method
- ☒ B. An Apex REST class
- ☐ C. An Apex controller
- ☐ D. An outbound message

### Question 37 of 60



Choose 1 option.

Which scenario is valid for execution by unit tests?

- ☐ A. Execute anonymous Apex as a different user.
- ☒ B. Set the created date of a record using a system method.
- ☐ C. Generate a Visualforce PDF with `getContentAsPDF()`.
- ☐ D. Load data from a remote site with a callout.

### Question 38 of 60



Choose 2 options.

A developer is implementing an Apex class for a financial system. Within the class, the variables 'creditAmount' and 'debitAmount' should not be able to change once a value is assigned.

In which two ways can the developer declare the variables to ensure their value can only be assigned one time?

- ☒ A. Use the `final` keyword and assign its value when declaring the variable.
- ☐ B. Use the `static` keyword and assign its value in a static initializer.
- ☒ C. Use the `final` keyword and assign its value in the class constructor.
- ☐ D. Use the `static` keyword and assign its value in the class constructor.

### Question 39 of 60



Choose 3 options.

Which three resources in an Aura component can contain JavaScript functions?

- ☒ A. Renderer
- ☐ B. Style
- ☒ C. Controller
- ☒ D. Helper
- ☐ E. Design

### Question 40 of 60



Choose 2 options.

What are two benefits of using declarative customizations over code?

- ☐ A. Declarative customizations cannot generate run time errors.
- ☒ B. Declarative customizations automatically update with each Salesforce release.
- ☐ C. Declarative customizations automatically generate test classes.
- ☒ D. Declarative customizations generally require less maintenance.

### Question 41 of 60



Choose 1 option.

Universal Containers needs to create a custom user interface component that allows users to enter information about their accounts. The component should be able to validate the user input before saving the information to the database.

What is the best technology to create this component?

- ☒ A. Lightning Web Components
- ☐ B. Flow
- ☐ C. Visualforce
- ☐ D. VUE JavaScript framework

### Question 42 of 60



Choose 3 options.

What are three ways for a developer to execute tests in an org?

- ☒ A. Setup Menu
- ☒ B. Tooling API
- ☐ C. Bulk API
- ☒ D. Salesforce DX
- ☐ E. Metadata API

### Question 43 of 60



Choose 1 option.

In the following example, which sharing context will `myMethod` execute when it is invoked?

```
public Class myClass {  
    public void myMethod() { /* implementation */ }  
}
```

- ☐ A. Sharing rules will not be enforced for the running user.
- ☒ B. Sharing rules will be inherited from the calling context.
- ☐ C. Sharing rules will be enforced for the running user.
- ☐ D. Sharing rules will be enforced by the instantiating class.

### Question 44 of 60



Choose 2 options.

Where are two locations a developer can look to find information about the status of batch or future methods?

- ☐ A. Paused Flow Interviews component
- ☒ B. Apex Jobs
- ☐ C. Developer Console
- ☒ D. Apex Flex Queue

### Question 45 of 60



Choose 1 option.

Which exception type cannot be caught?

- ☐ A. A custom exception
- ☐ B. `CalloutException`
- ☐ C. `NoAccessException`
- ☒ D. `LimitException`

### Question 46 of 60



Choose 1 option.

A developer has an integer variable called `maxAttempts`. The developer needs to ensure that once `maxAttempts` is initialized, it preserves its value for the length of the Apex transaction; while being able to share the variable's state between trigger execution.

How should the developer declare `maxAttempts` to meet these requirements?

- ☒ A. Declare `maxAttempts` as a constant using the `static` and `final` keywords.
- ☐ B. Declare `maxAttempts` as a variable on a helper class.
- ☐ C. Declare `maxAttempts` as a private static variable on a helper class.
- ☐ D. Declare `maxAttempts` as a member variable on the trigger definition.

### Question 47 of 60



Choose 1 option.

A company has a custom object, `Order__c`, that has a required, unique external ID field called `Order_Number__c`.

Which statement should be used to perform the DML necessary to insert new records and update existing records in a list of `Order__c` records using the external ID field?

- ☐ A. `merge orders Order_Number__c;`
- ☒ B. `upsert orders Order_Number__c;`
- ☐ C. `merge orders;`
- ☐ D. `upsert orders;`

### Question 48 of 60



Choose 2 options.

Universal Containers decides to use purely declarative development to build out a new Salesforce application.

Which two options can be used to build out the business logic layer for this application?

- ☐ A. Batch Jobs
- ☒ B. Validation Rules
- ☐ C. Remote Actions
- ☒ D. Record-Triggered Flow

### Question 49 of 60



Choose 1 option.

A developer created a trigger on the Account object. While testing the trigger, the developer sees the error message 'Maximum trigger depth exceeded'.

What could be the possible causes?

- ☐ A. The developer does not have the correct user permission.
- ☒ B. The trigger is getting executed multiple times.
- ☐ C. The trigger does not have sufficient code coverage.
- ☐ D. The trigger is too long and should be refactored into a helper class.

### Question 50 of 60



Choose 1 option.

Which statement generates a list of Leads and Contacts that have a field with the phrase 'ACME'?

- ☐ A. `List <sObject> searchList = [FIND '*ACME*' IN ALL FIELDS RETURNING Contact, Lead];`
- ☐ B. `List<List <sObject>> searchList = [SELECT Name, ID FROM Contact, Lead WHERE Name like '%ACME%'];`
- ☒ C. `List<List <sObject>> searchList = [FIND '*ACME*' IN ALL FIELDS RETURNING Contact, Lead];`
- ☐ D. `Map <sObject> searchList = [FIND '*ACME*' IN ALL FIELDS RETURNING Contact, Lead];`

### Question 51 of 60



Choose 1 option.

Universal Containers has an order system that uses an Order Number to identify an order for customers and service agents. Order records will be imported into Salesforce.

How should the Order Number field be defined in Salesforce?

- ☐ A. Indirect Lookup
- ☐ B. Direct Lookup
- ☒ C. External ID and Unique
- ☐ D. Lookup

### Question 52 of 60



Choose 1 option.

Refer to the following Apex code:

```
Integer x = 0;  
do {  
    x = 1;  
    x++;  
} while (x < 1);  
System.debug(x);
```

What is the value of x when it is written to the debug log?

- ☐ A. 3
- ☐ B. 0
- ☒ C. 2
- ☐ D. 1

### Question 53 of 60



Choose 1 option.

Universal Containers has a support process that allows users to request support from its engineering team using a custom object `Engineering_Support__c`.

Users should be able to associate multiple `Engineering_Support__c` records to a single Opportunity record. Additionally, aggregate information about the `Engineering_Support__c` records should be shown on the Opportunity record.

Which relationship field should be implemented to support these requirements?

- ☐ A. Lookup field from `Engineering_Support__c` to Opportunity
- ☐ B. Master-detail field from Opportunity to `Engineering_Support__c`
- ☒ C. Master-detail field from `Engineering_Support__c` to Opportunity
- ☐ D. Lookup field from Opportunity to `Engineering_Support__c`

### Question 54 of 60



Choose 1 option.

A developer must create a `CreditCardPayment` class that provides an implementation of an existing `Payment` class.

```
public virtual class Payment {  
    public virtual void makePayment(Decimal amount) { /*implementation*/ }  
}
```

Which is the correct implementation?

- ☐ A. 

```
public class CreditCardPayment implements Payment {  
    public override void makePayment(Decimal amount) { /*implementation*/ }  
}
```
- ☒ B. 

```
public class CreditCardPayment extends Payment {  
    public override void makePayment(Decimal amount) { /*implementation*/ }  
}
```
- ☐ C. 

```
public class CreditCardPayment implements Payment {  
    public virtual void makePayment(Decimal amount) { /*implementation*/ }  
}
```
- ☐ D. 

```
public class CreditCardPayment extends Payment {  
    public virtual void makePayment(Decimal amount) { /*implementation*/ }  
}
```

## Question 55 of 60



Choose 2 options.

A developer created a trigger on the Account object and wants to test if the trigger is properly bulkified. The developer team decided that the trigger should be tested with 200 account records with unique names.

What two things should be done to create the test data within the unit test with the least amount of code?

- ☒ A. Use `Test.loadData` to populate data in your test methods.
- ☐ B. Use the `@isTest(isParallel=true)` annotation in the test class.
- ☒ C. Create a static resource containing test data.
- ☐ D. Use the `@isTest(seeAllData=true)` annotation in the test class.

## Question 56 of 60



Choose 1 option.

A developer created this Apex trigger that calls `MyClass.myStaticMethod`:

```
trigger myTrigger on Contact (before insert)
{
    MyClass.myStaticMethod(trigger.new);
}
```

The developer creates a test class with a test method that calls `MyClass.myStaticMethod` directly, resulting in 81% overall code coverage.

What happens when the developer tries to deploy the trigger and two classes to production, assuming no other code exists?

- ☐ A. The deployment passes because the Apex code has the required >75% code coverage.
- ☐ B. The deployment fails because no assertions were made in the test method.
- ☐ C. The deployment passes because both classes and the trigger were included in the deployment.
- ☒ D. The deployment fails because the Apex trigger has no code coverage.

### Question 57 of 60



Choose 1 option.

An org has an existing flow that edits an Opportunity with an Update Records element. A developer must update the flow to also create a Contact and store the created Contact's ID on the Opportunity.

Which update must the developer make in the flow?

- ☐ A. Add a new Get Records element.
- ☐ B. Add a new Roll Back Records element.
- ☒ C. Add a new Create Records element.
- ☐ D. Add a new Update Records element.

### Question 58 of 60



Choose 1 option.

A developer created a new `after insert` trigger on the Lead object that creates Task records for each Lead.

After deploying to production, an existing outside integration that inserts Lead records in batches to Salesforce is occasionally reporting total batch failures being caused by the Task insert statement. This causes the integration process in the outside system to stop, requiring a manual restart.

Which change should the developer make to allow the integration to continue when some records in a batch cause failures due to the Task insert statement, so that manual restarts are not needed?

- ☒ A. Use the `Database` method with `allOrNone` set to `false`.
- ☐ B. Remove the Apex class from the integration user's profile.
- ☐ C. Deactivate the trigger before the integration runs.
- ☐ D. Use a try-catch block after the `insert` statement.

### Question 59 of 60



Choose 1 option.

A developer is working on a project to import data from an external system into Salesforce. The data contains sensitive information that should not be visible to all users in Salesforce.

What should the developer do to ensure that the data is secure?

- ☐ A. Use the Apex Data Loader to import the data and write Apex code to handle security and access control.
- ☐ B. Use the Salesforce CLI to import the data and set up user permissions to restrict access to sensitive data.
- ☐ C. Use a third-party tool to encrypt the sensitive data before importing it into Salesforce.
- ☒ D. Use the Data Import Wizard to import the data and set up field-level security to restrict access to sensitive fields.

### Question 60 of 60



Choose 3 options.

What are three capabilities of the `<ltng:require>` tag when loading JavaScript resources in Aura components?

- ☐ A. Loading files from Documents
- ☒ B. Specifying loading order
- ☐ C. Loading externally hosted scripts
- ☒ D. One-time loading for duplicate scripts
- ☒ E. Loading scripts in parallel

## Item Review

The table below shows the questions and if they have been marked for review.

- To go to a question, click the question in the table below or use the buttons at the bottom of the screen to navigate through groups of questions.
- If you are finished and would like to submit your answers for scoring, click the **Finish Exam** button.

| Sequence | Question                                                     | Marked | Incomplete |
|----------|--------------------------------------------------------------|--------|------------|
| 1        | Which action causes a before trigger to fire by default for  |        |            |
| 2        | Which code displays the contents of a Visualforce page as a  |        |            |
| 3        | Which Apex class contains methods to return the amount of re |        |            |
| 4        | Flow Builder uses an Apex action to provide additional infor |        |            |
| 5        | A developer wants to send an outbound message when a record  |        |            |
| -        | Management asked for opportunities to be                     |        |            |

## Salesforce Certified Platform Developer Score Report

CANDIDATE: Pr

DATE: 8/9/2025

CANDIDATE ID

REGISTRATION

EXAM CODE: Pla

EXAM: Salesforce Certified Platform Developer

GRADE: Pass

The report below shows the percentage of questions in each section that you answered correctly on the Salesforce Certified Platform Developer exam. You will receive this information in your exam results email via My Dashboard in Trailhead Academy.

| SECTION NAME:                      | PERCENTAGE |
|------------------------------------|------------|
| Developer Fundamentals             | 100%       |
| Process Automation and Logic       | 80%        |
| User Interface                     | 80%        |
| Testing, Debugging, and Deployment | 100%       |