

Question 57 of 60



Choose 1 option.

Which scenario is valid for execution by unit tests?

- ☐ A. Execute anonymous Apex as a different user.
- ☐ B. Generate a Visualforce PDF with `getContentAsPDF()`.
- ☒ C. Set the created date of a record using a system method.
- ☐ D. Load data from a remote site with a callout.



Review



Comment

Back

Next



Question 56 of 60



Choose 1 option.

A developer is creating an app that contains multiple Lightning web components.

One of the child components is used for navigation purposes. When a user clicks a button called Next in the child component, the parent component must be alerted so it can navigate to the next page.

How should this be accomplished?

- ☐ A. Update a property on the parent.
- ☒ B. Create a custom event.
- ☐ C. Fire a notification.
- ☐ D. Call a method in the Apex controller.



Review



Comment

Back

Next



ENG

18:13

05-10-2025



Question 55 of 60



Choose 1 option.

While working in a sandbox, an Apex test fails when run in the Test Runner. However, executing the Apex logic in the Execute Anonymous window succeeds with no exceptions or errors.

Why did the method fail in the sandbox test framework but succeed in the Developer Console?

- ☐ A. The test method is calling an @Future method.
- ☒ B. The test method relies on existing data in the sandbox.
- ☐ C. The test method does not use System.runAs to execute as a specific user.
- ☐ D. The test method has a syntax error in the code.



Review



Comment

Back

Next



ENG

18:13

05-10-2025



Question 53 of 60



Choose 2 options.

Universal Containers wants Opportunities to no longer be editable when it reaches the Closed/Won stage.

Which two strategies can a developer use to accomplish this?

- ☒ A. Use a before save Apex trigger.
- ☒ B. Use a validation rule.
- ☐ C. Use an auto-response rule.
- ☐ D. Use an automatically launched Approval Process.



Review



Comment

Back

Next



ENG

18:13

05-10-2025



Question 52 of 60



Choose 1 option.

A company has a custom object, `Order__c`, that has a required, unique external ID field called `Order_Number__c`.

Which statement should be used to perform the DML necessary to insert new records and update existing records in a list of `Order__c` records using the external ID field?

- ☒ A. `upsert orders Order_Number__c;`
- ☐ B. `upsert orders;`
- ☐ C. `merge orders;`
- ☐ D. `merge orders Order_Number__c;`



Review



Comment

Back

Next



ENG

18:13

05-10-2025



Question 51 of 60



Choose 1 option.



Review



Comment

Back

Next

Input

00:39:14



ENG

18:13

05-10-2025



Question 51 of 60



Choose 1 option.

What should be used to create scratch orgs?

- ☐ A. Developer Console
- ☒ B. Salesforce CLI
- ☐ C. Sandbox refresh
- ☐ D. Workbench



Review



Comment

Back

Next

Input

00:39:13



ENG

18:13

05-10-2025



Question 50 of 60



Choose 1 option.

A developer created a new `after insert` trigger on the Lead object that creates Task records for each Lead.

After deploying to production, an existing outside integration that inserts Lead records in batches to Salesforce is occasionally reporting total batch failures being caused by the Task insert statement. This causes the integration process in the outside system to stop, requiring a manual restart.

Which change should the developer make to allow the integration to continue when some records in a batch cause failures due to the Task insert statement, so that manual restarts are not needed?

- ☒ A. Use the Database method with `allowNone` set to `false`.
- ☐ B. Deactivate the trigger before the integration runs.
- ☐ C. Remove the Apex class from the integration user's profile.
- ☐ D. Use a try catch block after the `insert` statement.



Review



Comment

Back

Next



ENG

18:13

05-10-2025



Question 49 of 60



Choose 1 option.

A developer created a trigger on the Account object. While testing the trigger, the developer sees the error message 'Maximum trigger depth exceeded'.

What could be the possible causes?

- ☐ A. The trigger does not have sufficient code coverage.
- ☒ B. The trigger is getting executed multiple times.
- ☐ C. The developer does not have the correct user permission.
- ☐ D. The trigger is too long and should be refactored into a helper class.



Review



Comment

Back

Next



ENG

18:13

05-10-2025



Question 48 of 60



Choose 1 option.

Cloud Kicks has a multi screen flow that its call center agents use when handling inbound service desk calls.

At one of the steps in the flow, the agents should be presented with a list of order numbers and dates that are retrieved from an external order management system in real time and displayed on the screen.

What should a developer use to satisfy this requirement?

- ☐ A. An Apex REST class
- ☒ B. An invocable method
- ☐ C. An Apex controller
- ☐ D. An outbound message



Review



Comment

Back

Next



ENG

18:13

05-10-2025



Question 47 of 60



Choose 3 options.

What are three ways for a developer to execute tests in an org?

- ☒ A. Tooling API
- ☒ B. Salesforce DX
- ☐ C. Bulk API
- ☐ D. Metadata API
- ☒ E. Setup Menu



Review



Comment

Back

Next



Question 46 of 60



Choose 2 options.

Management asked for opportunities to be automatically created for accounts with annual revenue greater than \$1,000,000. A developer created the following trigger on the Account object to satisfy this requirement.

```
for(Account a: Trigger.new){
    if(a.AnnualRevenue > 1000000){
        List<Opportunity> oppList = (SELECT Id FROM Opportunity WHERE accountId = :a.Id);
        if(oppList.size() == 0){
            Opportunity oppty = new Opportunity(Name = a.name, StageName = 'Prospecting',
            CloseDate = system.today().addDays(30));
            insert oppty;
        }
    }
}
```

Users are able to update the account records via the UI and can see an opportunity created for high annual revenue accounts. However, when the administrator tries to upload a list of 179 accounts using Data Loader, it fails with System.Exception errors.

Which two actions should the developer take to fix the code segment shown above?

- ☒ A. Query for existing opportunities outside the `for` loop.
- ☒ B. Move the DML that saves opportunities outside the `for` loop.
- ☐ C. Check if all the required fields for Opportunity are being added on creation.
- ☐ D. Use `Database.query` to query the opportunities.



Review



Comment

Back

Next



ENG

18:13

05-10-2025



Question 46 of 60



Choose 2 options.

Management asked for opportunities to be automatically created for accounts with annual revenue greater than \$1,000,000. A developer created the following trigger on the Account object to satisfy this requirement.

```
for(Account a: Trigger.new){
    if(a.AnnualRevenue > 1000000){
        List<Opportunity> oppList = (SELECT Id FROM Opportunity WHERE accountId = :a.Id);
        if(oppList.size() == 0){
            Opportunity oppty = new Opportunity(Name = a.name, StageName = 'Prospecting',
            CloseDate = system.today().addDays(30));
            insert oppty;
        }
    }
}
```

Users are able to update the account records via the UI and can see an opportunity created for high annual revenue accounts. However, when the administrator tries to upload a list of 179 accounts using Data Loader, it fails with System.Exception errors.

Which two actions should the developer take to fix the code segment shown above?

- ☒ A. Query for existing opportunities outside the `for` loop.
- ☒ B. Move the DML that saves opportunities outside the `for` loop.
- ☐ C. Check if all the required fields for Opportunity are being added on creation.
- ☐ D. Use `Database.query` to query the opportunities.



Review



Comment

Back

Next



ENG

18:13

05-10-2025



Question 46 of 60



Choose 2 options.

Management asked for opportunities to be automatically created for accounts with annual revenue greater than \$1,000,000. A developer created the following trigger on the Account object to satisfy this requirement.

```
for(Account a: Trigger.new){
    if(a.AnnualRevenue > 1000000){
        List<Opportunity> oppList = (SELECT Id FROM Opportunity WHERE accountId = :a.Id);
        if(oppList.size() == 0){
            Opportunity oppty = new Opportunity(Name = a.name, StageName = 'Prospecting',
            CloseDate = system.today().addDays(30));
            insert oppty;
        }
    }
}
```

Users are able to update the account records via the UI and can see an opportunity created for high annual revenue accounts. However, when the administrator tries to upload a list of 179 accounts using Data Loader, it fails with System.Exception errors.

Which two actions should the developer take to fix the code segment shown above?

- ☒ A. Query for existing opportunities outside the `for` loop.
- ☒ B. Move the DML that saves opportunities outside the `for` loop.
- ☐ C. Check if all the required fields for Opportunity are being added on creation.
- ☐ D. Use `Database.query` to query the opportunities.



Review



Comment

Back

Next



ENG

18:13

05-10-2025



Question 45 of 60



Choose 3 options.

What are three capabilities of the `<Lightning:require>` tag when loading JavaScript resources in Aura components?

- ☒ A. Loading scripts in parallel
- ☒ B. One time loading for duplicate scripts
- ☐ C. Loading externally hosted scripts
- ☒ D. Specifying loading order
- ☐ E. Loading files from Documents



Review



Comment

Back

Next



ENG

18:13

05-10-2025



Question 45 of 60



Choose 3 options.

What are three capabilities of the `<lightning:require>` tag when loading JavaScript resources in Aura components?

- ☒ A. Loading scripts in parallel
- ☒ B. One time loading for duplicate scripts
- ☐ C. Loading externally hosted scripts
- ☒ D. Specifying loading order
- ☐ E. Loading files from Documents



Review



Comment

Back

Next



ENG

18:13

05-10-2025



Question 45 of 60



Choose 3 options.

What are three capabilities of the `<lightning:require>` tag when loading JavaScript resources in Aura components?

- ☒ A. Loading scripts in parallel
- ☒ B. One time loading for duplicate scripts
- ☐ C. Loading externally hosted scripts
- ☒ D. Specifying loading order
- ☐ E. Loading files from Documents



Review



Comment

Back

Next



ENG

18:13

05-10-2025



Question 43 of 60



Choose 2 options.

A developer is implementing an Apex class for a financial system. Within the class, the variables 'creditAmount' and 'debitAmount' should not be able to change once a value is assigned.

In which two ways can the developer declare the variables to ensure their value can only be assigned one time?

- ☐ A. Use the `static` keyword and assign its value in the class constructor.
- ☒ B. Use the `final` keyword and assign its value when declaring the variable.
- ☐ C. Use the `static` keyword and assign its value in a static initializer.
- ☒ D. Use the `final` keyword and assign its value in the class constructor.



Review



Comment

Back

Next



ENG

18:12

05-10-2025



Question 42 of 60



Choose 1 option.

A developer is working on a project to import data from an external system into Salesforce. The data contains sensitive information that should not be visible to all users in Salesforce.

What should the developer do to ensure that the data is secure?

- ☐ A. Use the Salesforce CLI to import the data and set up user permissions to restrict access to sensitive data.
- ☒ B. Use the Data Import Wizard to import the data and set up field-level security to restrict access to sensitive fields.
- ☐ C. Use the Apex Data Loader to import the data and write Apex code to handle security and access control.
- ☐ D. Use a third-party tool to encrypt the sensitive data before importing it into Salesforce.



Review



Comment

Back

Next



ENG

18:12

05-10-2025



Question 41 of 60



Choose 1 option.

In the following example, which sharing context will `myMethod` execute when it is invoked?

```
public class MyClass {  
    public void myMethod() { /* Implementation */ }  
}
```

- ☐ A. Sharing rules will be enforced for the running user.
- ☐ B. Sharing rules will not be enforced for the running user.
- ☐ C. Sharing rules will be enforced by the instantiating class.
- ☒ D. Sharing rules will be inherited from the calling context.



Review



Comment

Back

Next



ENG



Question 40 of 60



Choose 1 option.

A developer created this Apex trigger that calls `MyClass.myStaticMethod`:

```
trigger myTrigger on Contact {before insert}
{
    MyClass.myStaticMethod(trigger.new);
}
```

The developer creates a test class with a test method that calls `MyClass.myStaticMethod` directly, resulting in 81% overall code coverage.

What happens when the developer tries to deploy the trigger and two classes to production, assuming no other code exists?

- ☐ A. The deployment passes because the Apex code has the required >75% code coverage.
- ☐ B. The deployment passes because both classes and the trigger were included in the deployment.
- ☒ C. The deployment fails because the Apex trigger has no code coverage.
- ☐ D. The deployment fails because no assertions were made in the test method.



Review



Comment

Back

Next



ENG

18:12

05-10-2025



Question 39 of 60



Choose 1 option.

Which action causes a before trigger to fire by default for Accounts?

- ☒ A. Importing data using the Data Loader and the Bulk API
- ☐ B. Converting Leads to Contacts
- ☐ C. Updating addresses using the Mass Address update tool
- ☐ D. Renaming or replacing picklists



Review



Comment

Back

Next



ENG

18:12

05-10-2025



Question 38 of 60



Choose 1 option.

Which Apex class contains methods to return the amount of resources that have been used for a particular governor, such as the number of DML statements?

- ☐ A. OrgLimits
- ☒ B. Limits
- ☐ C. Exception
- ☐ D. Messaging



Review



Comment

Back



Input

00:38:34



ENG

18:12

05-10-2025



Question 37 of 60



Choose 1 option.

Flow Builder uses an Apex action to provide additional information about multiple Contacts, stored in a custom class, `ContactInfo`.

Which is the correct definition of the Apex method that gets the additional information?

- ☒ A. `@InvocableMethod(label='Additional Info')`
`public static List<ContactInfo> getInfo(List<Id> contactIds)`
`{ /*implementation*/ }`
- ☐ B. `@InvocableMethod(label='Additional Info')`
`public static ContactInfo getInfo(Id contactId)`
`{ /*implementation*/ }`
- ☐ C. `@InvocableMethod(label='Additional Info')`
`public ContactInfo getInfo(Id contactId)`
`{ /*implementation*/ }`
- ☐ D. `@InvocableMethod(label='Additional Info')`
`public List<ContactInfo> getInfo(List<Id> contactIds)`
`{ /*implementation*/ }`



Review



Comment

Back

Next



ENG

18:12

05-10-2025



Question 36 of 60



Choose 2 options.

A developer wants to send an outbound message when a record meets a specific criteria.

Which two features satisfy this use case?

- ☒ A. Flow Builder can be used to check the record criteria and send an outbound message.
- ☐ B. Next Best Action can be used to check the record criteria and send an outbound message.
- ☒ C. Approval Process can be used to check the record criteria and send an outbound message without Apex code.
- ☐ D. Entitlement Process can be used to check the record criteria and send an outbound message without Apex code.



Review



Comment

Back

Next



ENG

18:12

05-10-2025



Question 36 of 60



Choose 2 options.

A developer wants to send an outbound message when a record meets a specific criteria.

Which two features satisfy this use case?

- ☒ A. Flow Builder can be used to check the record criteria and send an outbound message.
- ☐ B. Next Best Action can be used to check the record criteria and send an outbound message.
- ☒ C. Approval Process can be used to check the record criteria and send an outbound message without Apex code.
- ☐ D. Entitlement Process can be used to check the record criteria and send an outbound message without Apex code.



Review



Comment

Back

Next



ENG

18:12

05-10-2025



Question 35 of 60



Choose 1 option.

A developer needs to create a baseline set of data (Accounts, Contacts, Products, Assets) for an entire suite of Apex tests allowing them to test isolated requirements for various types of Salesforce cases.

Which approach can efficiently generate the required data for each unit test?

- ☐ A. Add `@IsTest (seeAllData=true)` at the start of the unit test class.
- ☒ B. Use `@testSetup` with a void method.
- ☐ C. Create test data before `Test.startTest()` in the unit test.
- ☐ D. Create a mock using the `HttpCalloutMock` interface.



Review



Comment

Back

Next



ENG

18:12

05-10-2025



Question 31 of 60



Choose 1 option.

Universal Containers has a support process that allows users to request support from its engineering team using a custom object, `Engineering_Support__c`.

Users should be able to associate multiple `Engineering_Support__c` records to a single Opportunity record. Additionally, aggregate information about the `Engineering_Support__c` records should be shown on the Opportunity record.

Which relationship field should be implemented to support these requirements?

- ☐ A. Master-detail field from Opportunity to `Engineering_Support__c`
- ☒ B. Master-detail field from `Engineering_Support__c` to Opportunity
- ☐ C. Lookup field from Opportunity to `Engineering_Support__c`
- ☐ D. Lookup field from `Engineering_Support__c` to Opportunity



Review



Comment

Back

Next



ENG

18:12

05-10-2025



Question 28 of 60



Choose 1 option.

An org has an existing flow that edits an Opportunity with an Update Records element. A developer must update the flow to also create a Contact and store the created Contact's ID on the Opportunity.

Which update must the developer make in the flow?

- ☐ A. Add a new Update Records element.
- ☐ B. Add a new Get Records element.
- ☐ C. Add a new Roll Back Records element.
- ☒ D. Add a new Create Records element.



Review



Comment

Back

Next



ENG

18:12

05-10-2025



Question 27 of 60



Choose 1 option.

Universal Containers needs to create a custom user interface component that allows users to enter information about their accounts. The component should be able to validate the user input before saving the information to the database.

What is the best technology to create this component?

- ☐ A. VUE JavaScript framework
- ☐ B. Visualforce
- ☒ C. Lightning Web Components
- ☐ D. Flow



Review



Comment

Back

Next



ENG

18:12

05-10-2025



Question 26 of 60



Choose 1 option.

Which exception type cannot be caught?

- ☐ A. A custom exception
- ☐ B. CalloutException
- ☒ C. LimitException
- ☐ D. NoAccessException



Review



Comment

Back

Next



ENG

18:12

05-10-2025



Question 24 of 60



Choose 1 option.

A developer needs to confirm that a Contact trigger works correctly without changing the organization's data.

What should the developer do to test the Contact trigger?

- ☐ A. Use the New button on the Salesforce Contacts Tab to create a new Contact record.
- ☐ B. Use Deploy from the VSCode IDE to deploy an 'insert Contact' Apex class.
- ☐ C. Use the Open Execute Anonymous feature on the Developer Console to run an 'insert Contact' DML statement.
- ☒ D. Use the Test menu on the Developer Console to run all test classes for the Contact trigger.



Review



Comment

Back

Next



ENG

18:12

05-10-2025



Question 23 of 60



Choose 1 option.

Universal Containers has an order system that uses an Order Number to identify an order for customers and service agents. Order records will be imported into Salesforce.

How should the Order Number field be defined in Salesforce?

- ☒ A. External ID and Unique
- ☐ B. Indirect Lookup
- ☐ C. Direct Lookup
- ☐ D. Lookup



Review



Comment

Back

Next



ENG



Question 23 of 60



Choose 1 option.

Universal Containers has an order system that uses an Order Number to identify an order for customers and service agents. Order records will be imported into Salesforce.

How should the Order Number field be defined in Salesforce?

- ☒ A. External ID and Unique
- ☐ B. Indirect Lookup
- ☐ C. Direct Lookup
- ☐ D. Lookup



Review



Comment

Back

Next



ENG

18:12

05-10-2025



Question 22 of 60



Choose 2 options.

A developer created a child Lightning web component nested inside a parent Lightning web component. The parent component needs to pass a string value to the child component.

In which two ways can this be accomplished?

- ☒ A. The parent component can use a public property to pass the data to the child component.
- ☐ B. The parent component can use the Apex controller class to send data to the child component.
- ☐ C. The parent component can use a custom event to pass the data to the child component.
- ☒ D. The parent component can invoke a public method in the child component.



Review



Comment

Back

Next



ENG

18:12

05-10-2025



Question 22 of 60



Choose 2 options.

A developer created a child Lightning web component nested inside a parent Lightning web component. The parent component needs to pass a string value to the child component.

In which two ways can this be accomplished?

- ☒ A. The parent component can use a public property to pass the data to the child component.
- ☐ B. The parent component can use the Apex controller class to send data to the child component.
- ☐ C. The parent component can use a custom event to pass the data to the child component.
- ☒ D. The parent component can invoke a public method in the child component.



Review



Comment

Back

Next



ENG

18:11

05-10-2025



Question 21 of 60



Choose 1 option.

A developer must create a `CreditCardPayment` class that provides an implementation of an existing `Payment` class.

```
public virtual class Payment {  
    public virtual void makePayment(Decimal amount) { /*Implementation*/ }  
}
```

Which is the correct implementation?

- ☐ A.

```
public class CreditCardPayment extends Payment {  
    public virtual void makePayment(Decimal amount) { /*Implementation*/ }  
}
```
- ☐ B.

```
public class CreditCardPayment implements Payment {  
    public virtual void makePayment(Decimal amount) { /*Implementation*/ }  
}
```
- ☐ C.

```
public class CreditCardPayment implements Payment {  
    public override void makePayment(Decimal amount) { /*Implementation*/ }  
}
```
- ☒ D.

```
public class CreditCardPayment extends Payment {  
    public override void makePayment(Decimal amount) { /*Implementation*/ }  
}
```



Review



Comment

Back

Next



ENG

18:11

05-10-2025



Question 20 of 60



Choose 1 option.

A team of many developers work in their own individual orgs that have the same configuration as the production org.

Which type of org is best suited for this scenario?

- ☐ A. Partner Developer Edition
- ☐ B. Developer Edition
- ☐ C. Full Sandbox
- ☒ D. Developer Sandbox



Review



Comment

Back

Next



ENG

18:11

05-10-2025



Question 19 of 60



Choose 2 options.

Which two settings must be defined in order to update a record of a junction object?

- ☐ A. Read/Write access on the junction object
- ☒ B. Read/Write access on the secondary relationship
- ☐ C. Read access on the primary relationship
- ☒ D. Read/Write access on the primary relationship



Review



Comment

Back

Next



ENG

18:11

05-10-2025



Question 18 of 60



Choose 1 option.

Which statement generates a list of Leads and Contacts that have a field with the phrase 'ACME'?

- ☐ A. `List<SObject> searchList = [FIND '*ACME*' IN ALL FIELDS RETURNING Contact, Lead];`
- ☐ B. `Map<SObject> searchList = [FIND '*ACME*' IN ALL FIELDS RETURNING Contact, Lead];`
- ☒ C. `List<List<SObject>> searchList = [FIND '*ACME*' IN ALL FIELDS RETURNING Contact, Lead];`
- ☐ D. `List<List<SObject>> searchList = [SELECT Name, ID FROM Contact, Lead WHERE Name like 'ACME*'];`



Review



Comment

Back

Next



ENG

18:11

05-10-2025



Question 17 of 60



Choose 2 options.

Universal Containers hires a developer to build a custom search page to help users find the Accounts they want. Users will be able to search on Name, Description, and a custom comments field.

Which consideration should the developer be aware of when deciding between SOQL and SOSL?

- ☒ A. SOQL is able to return more records.
- ☒ B. SOSL is faster for text searches.
- ☐ C. SOSL is able to return more records.
- ☐ D. SOQL is faster for text searches.



Review



Comment

Back

Next



ENG

18:11

05-10-2025



Question 17 of 60



Choose 2 options.

Universal Containers hi
to search on Name, De

Which consideration sh



Review



Comment

Back

Next

Input

00:37:37



18:11
05-10-2025



Question 16 of 60



Choose 2 options.

What are two use cases for executing Anonymous Apex code?

- ☒ A. To schedule an Apex class to run periodically
- ☒ B. To run a batch Apex class to update all Contacts
- ☐ C. To delete 15,000 inactive Accounts in a single transaction after a deployment
- ☐ D. To add unit test code coverage to an org



Review



Comment

Back

Next



Question 15 of 60



Choose 2 options.

Where are two locations a developer can look to find information about the status of batch or future methods?

- ☒ A. Apex Jobs
- ☐ B. Developer Console
- ☐ C. Paused Flow Interviews component
- ☒ D. Apex Flex Queue



Review



Comment

Back

Next



Question 15 of 60



Choose 2 options.

Where are two locations a developer can look to find information about the status of batch or future methods?

- ☒ A. Apex Jobs
- ☐ B. Developer Console
- ☐ C. Paused Flow Interviews component
- ☒ D. Apex Flex Queue



Review



Comment

Back

Next

Input

00:37:31



ENG

18:11

05-10-2025



Question 14 of 60



Choose 2 options.

Universal Containers recently transitioned from Classic to Lightning Experience.

One of its business processes requires certain values from the Opportunity object to be sent via an HTTP REST callout to its external order management system when the user presses a custom button on the Opportunity detail page. Example values are as follows:

- Name
- Amount
- Account

Which two methods should the developer implement to fulfill the business requirement?

- ☒ A. Create a custom Visualforce quick action that performs the HTTP REST callout, and use a Visualforce quick action to expose the component on the Opportunity detail page.
- ☒ B. Create a Lightning component quick action that performs the HTTP REST callout, and use a Lightning Action to expose the component on the Opportunity detail page.
- ☐ C. Create an after update trigger on the Opportunity object that calls a helper method using `$Platform.Callout=true` to perform the HTTP REST callout.
- ☐ D. Create a Remote Action on the Opportunity object that executes an Apex immediate action to perform the HTTP REST callout whenever the Opportunity is updated.



Review



Comment

Back

Next



ENG

18:11

05-10-2025



Question 13 of 60



Choose 1 option.

Which annotation exposes an Apex class as a RESTful web service?

- ☐ A. `@HttpInvocable`
- ☒ B. `@RestResource(urlMapping='/myService/*')`
- ☐ C. `@RemoteAction`
- ☐ D. `@AuraEnabled(cacheable=true)`



Review



Comment

Back

Next



ENG

18:11

05-10-2025



Question 12 of 60



Choose 2 options.

What are two benefits of using declarative customizations over code?

- ☐ A. Declarative customizations cannot generate run time errors.
- ☐ B. Declarative customizations automatically generate test classes.
- ☒ C. Declarative customizations generally require less maintenance.
- ☒ D. Declarative customizations automatically update with each Salesforce release.



Review



Comment

Back

Next



ENG

18:11

05-10-2025



Question 11 of 60



Choose 2 options.

If Apex code executes inside the `execute {}` method of an Apex class when implementing the `Batchable` interface, which two statements are true regarding governor limits?

- ☒ A. The Apex governor limits cannot be exceeded due to the asynchronous nature of the transaction.
- ☒ B. The Apex governor limits are reset for each iteration of the `execute {}` method.
- ☐ C. The Apex governor limits are omitted while calling the constructor of the Apex class.
- ☐ D. The Apex governor limits will use the asynchronous limit levels.



Review



Comment

Back

Next



ENG

18:11

05-10-2025



Question 10 of 60



Choose 3 options.

Which three resources in an Aura component can contain JavaScript functions?

- ☒ A. Controller
- ☒ B. Renderer
- ☐ C. Design
- ☐ D. Style
- ☒ E. Helper



Review



Comment

Back

Next

Input

00:37:23



ENG

18:11

05-10-2025



Question 9 of 60



Choose 3 options.

Which three Salesforce resources can be accessed from a Lightning web component?

- ☒ A. Content asset files
- ☒ B. SVG resources
- ☐ C. Third-party web components
- ☒ D. Static resources
- ☐ E. All external libraries



Review



Comment

Back

Next

Input

00:37:21



ENG

18:11

05-10-2025



Question 8 of 60



Choose 3 options.

Which three statements are accurate about debug logs?

- ☐ A. The maximum size of a debug log is 5 MB.
- ☐ B. Debug log levels are cumulative, where FINE log level includes all events logged at the DEBUG, INFO, WARN, and ERROR levels.
- ☒ C. Debug logs can be set for specific users, classes, and triggers.
- ☒ D. System debug logs are retained for 24 hours.
- ☒ E. Only the 20 most recent debug logs for a user are kept.



Review



Comment

Back

Next



ENG

18:11

05-10-2025



Question 7 of 60



Choose 1 option.

A developer created these three Rollup Summary fields in the custom object, `Project__c`:

`Total_Timesheets__c`
`Total_Approved_Timesheets__c`
`Total_Rejected_Timesheet__c`

The developer is asked to create a new field that shows the ratio between rejected and approved timesheets for a given project.

Which should the developer use to implement the business requirement in order to minimize maintenance overhead?

- ☒ A. Formula field
- ☐ B. Record-triggered flow
- ☐ C. Roll up summary field
- ☐ D. Apex trigger



Review



Comment

Back

Next



ENG

18:11

05-10-2025



Question 6 of 60



Choose 2 options.

Universal Containers decides to use purely declarative development to build out a new Salesforce application.

Which two options can be used to build out the business logic layer for this application?

- ☒ A. Validation Rules
- ☐ B. Batch Jobs
- ☐ C. Remote Actions
- ☒ D. Record-Triggered Flow

-06:04



Review



Comment



0%

Back

-06:04/06:33

Input

00:37:15



ENG

18:11

05-10-2025



Question 5 of 60



Choose 1 option.

An Opportunity needs to have an amount rolled up from a custom object that is not in a master detail relationship.

How can this be achieved?

- ☐ A. Use the Metadata API to create real time roll up summaries.
- ☐ B. Use the Streaming API to create real time roll up summaries.
- ☐ C. Write a trigger on the Opportunity object and use tree sorting to sum the amount for all related child objects under the Opportunity.
- ☒ D. Write a trigger on the child object and use an aggregate function to sum the amount for all related child objects under the Opportunity.



Review



Comment

Back

Next



ENG

18:11

05-10-2025



Question 4 of 60



Choose 3 options.



Review



Comment

Back

Next

Input



ENG

18:11

05-10-2025



00:37:04

Question 4 of 60



Choose 3 options.

A developer needs to allow users to complete a form on an Account record that will create a record for a custom object.

The form needs to display different fields depending on the user's job role. The functionality should only be available to a small group of users.

Which three things should the developer do to satisfy these requirements?

- ☐ A. Create a Lightning web component.
- ☒ B. Create a Dynamic Form.
- ☒ C. Create a Custom Permission for the users.
- ☒ D. Add a Dynamic Action to the Account Record Page.
- ☐ E. Add a Dynamic Action to the Users' assigned Page Layouts.



Review



Comment

Back

Next



Question 3 of 60



Choose 2 options.

When a user edits the Postal Code on an Account, a custom Account text field named "Timezone" must be updated based on the values in a PostalCodeToTimezone custom object.

Which two automation tools can be used to implement this feature?

- ☒ A. Account trigger
- ☒ B. Fast Field Updates record triggered flow
- ☐ C. Quick actions
- ☐ D. Approval process



Review



Comment

Back

Next



ENG

18:11

05-10-2025



Question 2 of 60



Choose 1 option.

How is a controller and extension specified for a custom object named "Notice" on a Visualforce page?

- ☐ A. `apex:page-Notice extends="myControllerExtension"`
- ☐ B. `apex:page controllers="Notice__c, myControllerExtension"`
- ☒ C. `apex:page controller="Notice__c" extensions="myControllerExtension"`
- ☐ D. `apex:page standardController="Notice__c" extensions="myControllerExtension"`



Review



Comment

Back

Next



ENG

18:11

05-10-2025



Question 1 of 60



Choose 1 option.

A custom picklist field, `Food_Preference__c`, exists on a custom object. The picklist contains the following options: 'Vegan', 'Kosher', 'No Preference'. The developer must ensure a value is populated every time a record is created or updated.

What is the optimal way to ensure a value is selected every time a record is saved?

- ☐ A. Write an Apex trigger to ensure a value is selected.
- ☐ B. Set "Use the first value in the list as the default value" to True.
- ☐ C. Mark the field as Required on the object's page layout.
- ☒ D. Mark the field as Required on the field definition.



Review



Comment

Back

Next



ENG

18:11

05-10-2025



Salesforce Certified Platform Developer Score Report

CANDIDATE: [REDACTED]
CANDIDATE ID: [REDACTED] AM
REGISTRATION NUMBER: [REDACTED]

DATE: 10/5/2025
EXAM CODE: Plat-Dev-201

EXAM: Salesforce Certified Platform Developer

GRADE: Pass

The report below shows the percentage of questions in each section that you answered correctly for the Salesforce Certified Platform Developer exam. You will receive this information in your exam results email and can also access it via My Dashboard in Trailhead Academy.

SECTION NAME:	PERCENT CORRECT:
Developer Fundamentals	100%
Process Automation and Logic	89%
User Interface	73%
Testing, Debugging, and Deployment	85%



Close



ENG



Question 60 of 60



Choose 2 options.

A developer created a trigger on the Account object and wants to test if the trigger is properly bulkified. The developer team decided that the trigger should be tested with 200 account records with unique names.

What two things should be done to create the test data within the unit test with the least amount of code?

- ☐ A. Use the `@IsTest(isParallel=true)` annotation in the test class.
- ☒ B. Use `Test.loadData` to populate data in your test methods.
- ☐ C. Use the `@IsTest(seeAllData=true)` annotation in the test class.
- ☒ D. Create a static resource containing test data.



Review



Comment

Back

Next



ENG

18:13

05-10-2025



Question 59 of 60



Choose 1 option.

Which code displays the contents of a Visualforce page as a PDF?

- ☐ A. `<apex:page contentType="pdf">`
- ☐ B. `<apex:page renderAs="application/pdf">`
- ☐ C. `<apex:page contentType="application/pdf">`
- ☒ D. `<apex:page renderAs="pdf">`



Review



Comment

Back

Next



ENG

18:13

05-10-2025



Question 58 of 60



Choose 2 options.

Which two operations affect the number of times a trigger can fire?

- ☐ A. Email messages
- ☒ B. Roll up summary fields
- ☐ C. Criteria-based sharing calculations
- ☒ D. After-save record-triggered flow



Review



Comment

Back

Next



ENG

18:13

05-10-2025

