

**EXAM:** Salesforce Certified Platform Developer II - Multiple Choice

**GRADE:** Pass

The report below shows the percentage of questions in each section that you answered correctly for the Salesforce Certified Platform Developer II - Multiple Choice exam. You will receive this information in your exam results email and can also access it via My Dashboard in Trailhead Academy.

| SECTION NAME:                              | PERCENT CORRECT: |
|--------------------------------------------|------------------|
| Advanced Developer Fundamentals            | 78%              |
| Process Automation, Logic, and Integration | 88%              |
| User Interface                             | 83%              |
| Testing, Debugging, and Deployment         | 100%             |
| Performance                                | 100%             |

**Question 62 of 62**



Choose 1 option.

```
private static searchRecords_Test() {  
    List<List<sObject>> records = searchFeature.searchRecords('Test');  
    System.assertNotEquals(records.size(), 0);  
}
```

However, when the test runs, no data is returned and the assertion fails.

Which edit should the developer make to ensure the test class runs successfully?

- ☐ A. Enclose the method call within `Test.startTest()` and `Test.stopTest()`.
- ☐ B. Implement the `seeAllData=true` attribute in the `@IsTest` annotation.
- ☐ C. Implement the `without sharing` keyword in the `searchFeature` Apex class.
- ☒ D. Implement the `setFixedSearchResults` method in the test class.

**Question 62 of 62**



Choose 1 option.

Consider the following code snippet:

```
public class searchFeature {  
    public static List<List<sObject>> searchRecords(string searchquery) {  
        return [FIND searchquery IN ALL FIELDS RETURNING Account, Opportunity, Lead];  
    }  
}
```

A developer created the following test class to provide the proper code coverage for the snippet above:

```
@IsTest  
private class searchFeature_Test {  
  
    @TestSetup  
    private static void makeData() {  
        //insert opportunities, accounts and lead  
    }  
}
```

### Question 61 of 62



Choose 2 options.

A Lightning web component exists in the system and displays information about the record in context as a modal. Salesforce administrators need to use this component within the Lightning App Builder.

Which two settings should the developer configure within the xml resource file?

- ☐ A. Set the `isVisible` attribute to `true`.
- ☒ B. Set the `isExposed` attribute to `true`.
- ☒ C. Specify the target to be `lightning__RecordPage`.
- ☐ D. Specify the target to be `lightning__AppPage`.

### Question 60 of 62



Choose 1 option.

A developer is asked to look into an issue where a scheduled Apex is running into DML limits. Upon investigation, the developer finds that the number of records processed by the scheduled Apex has recently increased to more than 10,000.

What should the developer do to eliminate the limit exception error?

- ☒ A. Implement the `Batchable` interface.
- ☐ B. Use platform events.
- ☐ C. Use the `@future` annotation.
- ☐ D. Implement the `Queueable` interface.

### Question 59 of 62



Choose 2 options.

A Salesforce org has more than 50,000 contacts. A new business process requires a calculation that aggregates data from all of these contact records. This calculation needs to run once a day after business hours.

Which two steps should a developer take to accomplish this?

- ☐ A. Use the `@future` annotation.
- ☐ B. Implement the `Database.Batchable` interface.
- ☒ C. Implement the `Schedulable` interface.
- ☒ D. Implement the `Queueable` interface.

### Question 58 of 62



Choose 1 option.

A developer is writing a Visualforce page that queries accounts in the system and presents a data table with the results. The users want to be able to filter the results based on up to five fields. However, the users want to pick the five fields to use as filter fields when they run the page.

Which Apex code feature is required to facilitate this solution?

- ☒ A. Dynamic SOQL
- ☐ B. Metadata API
- ☐ C. Streaming API
- ☐ D. Variable binding

### Question 57 of 62



Choose 1 option.

```
Line 4  
Line 5     @AuraEnabled  
Line 6     public List<String> getStringArray() {  
Line 7         String[] arrayItems = new String[]{ 'red', 'green', 'blue' };  
Line 8         return arrayItems;  
Line 9     }  
Line 10 }
```

What is wrong with this code?

- ☐ A. Lines 1 and 6: class and method must be global
- ☐ B. Line 1: class must be global
- ☒ C. Line 6: method must be static
- ☐ D. Line 8: method must first serialize the list to JSON before returning

### Question 57 of 62



Choose 1 option.

Consider the Apex controller below, that is called from an Aura component.

```
Line 1 public class AttributeTypes  
Line 2 {  
Line 3     private final String[] arrayItems;  
Line 4  
Line 5     @AuraEnabled  
Line 6     public List<String> getStringArray() {  
Line 7         String[] arrayItems = new String[]{ 'red', 'green', 'blue' };  
Line 8         return arrayItems;  
Line 9     }  
Line 10 }
```

What is wrong with this code?

- ☐ A. Lines 1 and 6: class and method must be global

### Question 56 of 62



Choose 1 option.

The use of the transient keyword in Visualforce page controllers helps with which common performance issue?

- ☒ A. Reduces view state
- ☐ B. Improves query performance
- ☐ C. Reduces load times
- ☐ D. Improves page transfers

### Question 55 of 62



Choose 1 option.

A developer is trying to decide between creating a Visualforce component or a Lightning component for a custom screen.

Which functionality consideration impacts the final decision?

- ☐ A. Does the screen need to be accessible from the Lightning Experience UI?
- ☐ B. Will the screen be accessed via a mobile app?
- ☐ C. Will the screen make use of a JavaScript framework?
- ☒ D. Does the screen need to be rendered as a PDF without using a third-party application?

### Question 54 of 62



Choose 1 option.

There are user complaints about slow render times of a custom data table within a Visualforce page that loads thousands of Account records at once.

What can a developer do to help alleviate such issues?

- ☐ A. Use the transient keyword in the Apex code when querying the Account records.
- ☐ B. Upload a third-party data table library as a static resource.
- ☒ C. Use the standard Account List controller and implement pagination.
- ☐ D. Use JavaScript remoting to query the accounts.

### Question 53 of 62



Choose 1 option.

size form factor when on a record page.

What should the developer add to the component's record page target configuration to meet this requirement?

- ☐ A. `<supportedFormFactors>`  
    `<supportedFormFactor type="Large"/>`  
    `</supportedFormFactors>`
- ☐ B. `<lightningLayout formFactor="Large">`  
    `</lightningLayout>`
- ☐ C. `<design>`  
    `<designAttribute name="formFactor" value="Large"/>`  
    `</design>`
- ☒ D. `<property name="formFactor" value="Large">`  
    `</property>`

### Question 53 of 62



Choose 1 option.

A developer needs to add code to a Lightning web component's configuration file so the component only renders for a desktop size form factor when on a record page.

What should the developer add to the component's record page target configuration to meet this requirement?

- ☐ A. `<supportedFormFactors>`  
    `<supportedFormFactor type="Large"/>`  
    `</supportedFormFactors>`
- ☐ B. `<lightningLayout formFactor="Large">`  
    `</lightningLayout>`
- ☐ C. `<design>`  
    `<designAttribute name="formFactor" value="Large"/>`  
    `</design>`

### Question 52 of 62



Choose 1 option.

```
delete testAccounts;
testAccounts = [SELECT Id, Name from Account WHERE Name like 'Test%'];
System.assert(testAccounts.size() == 0);
}
```

The developer org has five accounts where the name starts with "Test". The developer executes this test in the Developer Console.

After the test code runs, which statement is true?

- ☒ A. There will be five accounts where the name starts with "Test".
- ☐ B. There will be no accounts where the name starts with "Test".
- ☐ C. There will be six accounts where the name starts with "Test".
- ☐ D. The test will fail.

## Question 52 of 62



Choose 1 option.

A developer created the following test method:

```
@isTest(SeeAllData= true)
public static void testDeleteTrigger(){

    Account testAccount = new Account(name = 'Test1');
    insert testAccount;

    List<Account> testAccounts = [SELECT Id, Name from Account WHERE Name like 'Test%'];
    System.assert(testAccounts.size() > 0);

    delete testAccounts;
    testAccounts = [SELECT Id, Name from Account WHERE Name like 'Test%'];
    System.assert(testAccounts.size() == 0);
}
```

The developer org has five accounts where the name starts with "Test". The developer executes this test in the Developer Console.

## Question 51 of 62



Choose 1 option.

A company needs to automatically delete sensitive information after seven years. This could delete almost a million records every day.

How can this be achieved?

- ☐ A. Schedule an @future process to query records older than seven years, and then recursively invoke itself in 1,000 record batches to delete them.
- ☐ B. Use aggregate functions to query for records older than seven years, and then delete the AggregateResult objects.
- ☐ C. Perform a SOSL statement to find records older than 7 years, and then delete the entire result set.
- ☒ D. Schedule a batch Apex process to run every day that queries and deletes records older than seven years.

## Question 50 of 62



Choose 1 option.

Both custom objects have a CurrencyIsoCode text field that contains the currency code they should use. If a Catalog's CurrencyIsoCode changes, all of its Catalog Items' CurrencyIsoCodes should be changed as well.

What should a developer use to update the CurrencyIsoCodes on the Catalog Items when the Catalog's CurrencyIsoCode changes?

- ☐ A. An after insert trigger on Catalog that updates the Catalog Items if the Catalog's CurrencyIsoCode is different
- ☐ B. An after insert trigger on Catalog Item that updates the Catalog Items if the Catalog's CurrencyIsoCode is different
- ☐ C. A Database.Schedulable and Database.Batchable class that queries the Catalog object and updates the Catalog Items if the Catalog CurrencyIsoCode is different
- ☒ D. A Database.Schedulable and Database.Batchable class that queries the Catalog Item object and updates the Catalog Items if the Catalog CurrencyIsoCode is different

### Question 50 of 62



Choose 1 option.

A company manages information about their product offerings in custom objects named Catalog and Catalog Item. Catalog Item has a master-detail field to Catalog, and each Catalog may have as many as 100,000 Catalog Items.

Both custom objects have a CurrencyIsoCode text field that contains the currency code they should use. If a Catalog's CurrencyIsoCode changes, all of its Catalog Items' CurrencyIsoCodes should be changed as well.

What should a developer use to update the CurrencyIsoCodes on the Catalog Items when the Catalog's CurrencyIsoCode changes?

- ☐ A. An `after insert` trigger on Catalog that updates the Catalog Items if the Catalog's CurrencyIsoCode is different
- ☐ B. An `after insert` trigger on Catalog Item that updates the Catalog Items if the Catalog's CurrencyIsoCode is different
- ☐ C. A `Database.Schedulable` and `Database.Batchable` class that queries the Catalog object and updates the Catalog Items if the Catalog's CurrencyIsoCode is different

### Question 49 of 62



Choose 1 option.

When developing a Lightning web component, which setting displays lightning-layout-items in one column on small devices, such as mobile phones, and in two columns on tablet-size and desktop-size screens?

- ☐ A. Set `size="12"` `tablet-device-size="6"`
- ☐ B. Set `size="6"` `small-device-size="12"`
- ☒ C. Set `size="12"` `medium-device-size="6"`
- ☐ D. Set `size="6"` `mobile-device-size="12"`

### Question 48 of 62



Choose 2 options.

A developer is tasked with creating a Lightning web component that is responsive on various devices.

Which two components should help accomplish this goal?

- ☐ A. `lightning-input-location`
- ☒ B. `lightning-layout`
- ☒ C. `lightning-navigation`
- ☐ D. `lightning-layout-item`



### Question 47 of 62



Choose 1 option.

A developer needs to send Account records to an external system for backup purposes. The process must take a snapshot of Accounts as they are saved and then make a callout to a RESTful web service. The web service can only receive, at most, one record per call.

What should a developer do to implement these requirements?

- ☐ A. Implement platform events.
- ☐ B. Create a future method.
- ☒ C. Implement the Queueable interface.
- ☐ D. Expose an Apex class as a web service.

### Question 46 of 62



Choose 1 option.

Universal Containers uses a custom Lightning page to provide a mechanism to perform a step-by-step wizard search for Accounts. One of the steps in the wizard is to allow the user to input text into a text field, ERP\_Number\_\_c, that is then used in a query to find matching Accounts.

```
erpNumber = erpNumber + '%';  
List<Account> accounts = [SELECT Id, Name FROM Account WHERE ERP_Number__c LIKE :erpNumber]
```

A developer receives the exception 'SOQL query not selective enough'.

Which step should be taken to resolve the issue?

- ☐ A. Move the SOQL query to within an asynchronous process.
- ☐ B. Mark the ERP\_Number\_\_c field as required.
- ☒ C. Mark the ERP\_Number\_\_c field as an external ID.

### Question 45 of 62



Choose 1 option.

Universal Containers is leading a development team that follows the source-driven development approach in Salesforce. As part of their continuous integration and delivery (CI/CD) process, they need to automatically deploy changes to multiple environments, including sandbox and production.

Which mechanism or tool would best support their CI/CD pipeline in source-driven development?

- ☒ A. Salesforce CLI with Salesforce DX
- ☐ B. Change Sets
- ☐ C. Salesforce Extensions for Visual Studio Code
- ☐ D. Ant Migration Tool



### Question 44 of 62



Choose 1 option.

A developer is writing code that requires making callouts to an external web service.

Which scenario necessitates that the callout be made in an asynchronous method?

- ☐ A. The callout could take longer than 60 seconds to complete.
- ☒ B. The callouts will be made in an Apex trigger.
- ☐ C. Over 10 callouts will be made in a single transaction.
- ☐ D. The callouts will be made using the REST API.

### Question 43 of 62



Choose 1 option.

A developer is tasked with ensuring that email addresses entered into the system for Contacts and for a custom object called `Survey_Response__c` do not belong to a list of blocked domains.

The list of blocked domains is stored in a custom object for ease of maintenance by users. The `Survey_Response__c` object is populated via a custom Visualforce page.

What is the optimal way to implement this?

- ☐ A. Implement the logic in validation rules on the Contact and the `Survey_Response__c` objects.
- ☒ B. Implement the logic in a helper class that is called by an Apex trigger on Contact and from the custom Visualforce page controller.
- ☐ C. Implement the logic in an Apex trigger on Contact and also implement the logic within the custom Visualforce page controller.

### Question 42 of 62



Choose 1 option.

Universal Charities (UC) uses Salesforce to collect electronic donations in the form of credit card deductions from individuals and corporations.

When a customer service agent enters the credit card information, it must be sent to a 3rd-party payment processor for the donation to be processed. UC uses one payment processor for individuals and a different one for corporations.

What should a developer use to store the payment processor settings for the different payment processors, so that their system administrator can modify the settings once they are deployed, if needed?

- ☒ A. Hierarchy custom setting
- ☐ B. Custom label
- ☐ C. Custom metadata
- ☐ D. List custom setting

### Question 41 of 62



Choose 1 option.

```
extension.inputValue = 'test';
PageReference pageRef = extension.update();
System.assertNotEquals(null, pageRef);
}
```

What should be added to the setup, in the location indicated, for the unit test above to create the controller extension for the test?

- ☐ A. `AccountControllerExt extension = new AccountControllerExt(acct);`
- ☒ B. `ApexPages.StandardController sc = new ApexPages.StandardController(acct);`  
`AccountControllerExt extension = new AccountControllerExt(sc);`
- ☐ C. `ApexPages.StandardController sc = new ApexPages.StandardController(acct.Id);`  
`AccountControllerExt extension = new AccountControllerExt(sc);`
- ☐ D. `AccountControllerExt extension = new AccountControllerExt(acct.Id);`

### Question 41 of 62



Choose 1 option.

```
@isTest
static void testUpdateSuccess() {
    Account acct = new Account(Name = 'test');
    insert acct;

    // Add code here

    extension.inputValue = 'test';
    PageReference pageRef = extension.update();
    System.assertNotEquals(null, pageRef);
}
```

What should be added to the setup, in the location indicated, for the unit test above to create the controller extension for the test?

- ☐ A. `AccountControllerExt extension = new AccountControllerExt(acct);`

### Question 40 of 62



Choose 1 option.

How should a developer assert that a trigger with an asynchronous process has successfully run?

- ☐ A. Create all test data, use `@future` in the test class, then perform assertions.
- ☐ B. Create all test data in the test class, use `System.runAs()` to invoke the trigger, then perform assertions.
- ☒ C. Create all test data in the test class, invoke `Test.startTest()` and `Test.stopTest()` and then perform assertions.
- ☐ D. Insert records into Salesforce, use `seeAllData=true`, then perform assertions.

### Question 39 of 62



Choose 1 option.

```

    insert a;
    a.name = a.name + '1';
    update a;
    List<AccountHistory> ahList = AccountHistoryManager.getAccountHistory(a);
    System.assert(ahList.size() > 0);
}

```

What should be done to make this test pass?

- ☐ A. Use `@isTest(SeeAllData=true)` to see historical data from the org and query for `AccountHistory` records.
- ☒ B. Use `Test.isRunningTest()` in `getAccountHistory()` to conditionally return fake `AccountHistory` records.
- ☐ C. The test method should be deleted since this code cannot be tested.
- ☐ D. Create `AccountHistory` records manually in the test setup and write a query to get them.

### Question 39 of 62



Choose 1 option.

A developer wrote a class named `AccountHistoryManager` that relies on field history tracking. The class has a static method called `getAccountHistory` that takes in an `Account` as a parameter and returns a list of associated `AccountHistory` object records.

The following test fails:

```

@isTest
public static void testAccountHistory(){
    Account a = new Account(name = 'test');
    insert a;
    a.name = a.name + '1';
    update a;
    List<AccountHistory> ahList = AccountHistoryManager.getAccountHistory(a);
    System.assert(ahList.size() > 0);
}

```

What should be done to make this test pass?

### Question 38 of 62



Choose 2 options.

```

public static void setPricingStructure(Opportunity thisOpp){
    Pricing_Structure__c ps = [Select Type__c FROM Pricing_Structure__c WHERE industry__c =
:thisOpp.Account_Industry__c];
    thisOpp.Pricing_Structure__c = ps.Type__c;
    update thisOpp;
}
}

```

Which two best practices should the developer implement to optimize this code?

- ☒ A. Remove the DML statement.
- ☐ B. Change the trigger context to after update, after insert.
- ☒ C. Query the `Pricing_Structure__c` records outside of the loop.
- ☐ D. Use a collection for the DML statement.

### Question 38 of 62



Choose 2 options.

Consider the following code snippet:

```
trigger OpportunityTrigger on Opportunity (before insert, before update) {
    for(Opportunity opp : Trigger.new){
        OpportunityHandler.setPricingStructure(opp)
    }
}

public class OpportunityHandler{
    public static void setPricingStructure(Opportunity thisOpp){
        Pricing_Structure__c ps = [Select Type__c FROM Pricing_Structure__c WHERE industry__c =
:thisOpp.Account_Industry__c];
        thisOpp.Pricing_Structure__c = ps.Type__c;
        update thisOpp;
    }
}
```

Which two best practices should the developer implement to optimize this code?

### Question 37 of 62



Choose 1 option.

Universal Containers needs to integrate with their own, existing, internal custom web application. The web application accepts JSON payloads, resizes product images, and sends the resized images back to Salesforce.

What should the developer use to implement this integration?

- ☐ A. An Apex trigger that calls an @future method that allows callouts
- ☐ B. A flow that calls an @future method that allows callouts
- ☐ C. A flow with an outbound message that contains a session ID
- ☒ D. A platform event that makes a callout to the web application

### Question 36 of 62



Choose 1 option.

Refer to the markup below:

```
<template>
    <!-- ... other code ... -->
    <lightning-record-form
        record-id={recordId}
        object-api-name="Account"
        layout-type="Full">
    </lightning-record-form>
</template>
```

A Lightning web component displays the Account name and two custom fields out of 275 that exist on the object. The custom fields are correctly declared and populated. However, the developer receives complaints that the component performs slowly.

What can the developer do to improve the performance?

- ☒ A. Replace layout-type="Full" with fields={fields}.

### Question 35 of 62



Choose 1 option.

Universal Containers uses Salesforce to track orders in an `Order__c` object.

The `Order__c` object has private organization-wide defaults. The `Order__c` object has a custom field, `Quality_Controller__c`, that is a Lookup to User and is used to indicate that the specified User is performing quality control on the `Order__c`.

What should be used to automatically give read only access to the User set in the `Quality_Controller__c` field?

- ☐ A. User managed sharing
- ☐ B. Record ownership
- ☒ C. Apex managed sharing
- ☐ D. Criteria-based sharing

### Question 34 of 62



Choose 1 option.

```
<c-my-child-component></c-my-child-component>
</template>
```

What is the correct way to communicate the new value of a property named "passthrough" to `my-parent-component` if the property is defined within `my-child-component`?

- ☐ A. `let cEvent = new CustomEvent('passthrough', { detail: 'this.passthrough' });`  
`this.dispatchEvent(cEvent);`
- ☐ B. `let cEvent = new CustomEvent('passthrough');`  
`this.dispatchEvent(cEvent);`
- ☒ C. `let cEvent = new CustomEvent('passthrough', { detail: this.passthrough });`  
`this.dispatchEvent(cEvent);`
- ☐ D. `let cEvent = new CustomEvent($passthrough);`  
`this.dispatchEvent(cEvent);`

### Question 34 of 62



Choose 1 option.

Given the following containment hierarchy:

```
<!-- myParentComponent.html -->
<template>
  <c-my-child-component></c-my-child-component>
</template>
```

What is the correct way to communicate the new value of a property named "passthrough" to `my-parent-component` if the property is defined within `my-child-component`?

- ☐ A. `let cEvent = new CustomEvent('passthrough', { detail: 'this.passthrough' });`  
`this.dispatchEvent(cEvent);`
- ☐ B. `let cEvent = new CustomEvent('passthrough');`  
`this.dispatchEvent(cEvent);`
- ☒ C. `let cEvent = new CustomEvent('passthrough', { detail: this.passthrough });`  
`this.dispatchEvent(cEvent);`

### Question 33 of 62



Choose 1 option.

A developer is debugging an Apex-based order creation process that has a requirement to have three savepoints, SP1, SP2, and SP3 (created in order), before the final execution of the process.

During the final execution process, the developer has a routine to roll back to SP1 for a given condition. Once the condition is fixed, the code then calls a roll back to SP3 to continue with final execution. However, when the roll back to SP3 is called, a runtime error occurs.

Why does the developer receive a runtime error?

- ☐ A. The developer has too many DML statements between the savepoints.
- ☒ B. SP3 became invalid when SP1 was rolled back.
- ☐ C. The developer should have called SP2 before calling SP3.
- ☐ D. The developer used too many savepoints in one trigger session.

### Question 32 of 62



Choose 1 option.

A developer is writing a Lightning Web component that queries accounts in the system and presents a `lightning-datatable` with the results. The users want to be able to filter the results based on up to five fields, that will vary according to their selections when running the page.

Which feature of Apex code is required to facilitate this solution?

- ☐ A. `describeObjects()`
- ☐ B. REST API
- ☐ C. SOSL queries
- ☒ D. Dynamic SQL

### Question 31 of 62



Choose 1 option.

A business requires that every parent record must have a child record. A developer writes an Apex method with two DML statements to insert a parent record and a child record.

A validation rule blocks child records from being created. The method uses a try/catch block to handle the DML exception.

What should the developer do to ensure the parent always has a child record?

- ☐ A. Use `Database.insert()` and set the `allOrNone` parameter to true.
- ☐ B. Delete the parent record in the catch statement when an error occurs on the child record DML operation.
- ☒ C. Set a database savepoint to rollback if there are errors.
- ☐ D. Use `addError()` on the parent record if an error occurs on the child record.

### Question 30 of 62



Choose 3 options.

What are three reasons that a developer should write Jest tests for Lightning web components?

- ☒ A. To test basic user interaction
- ☐ B. To test a component's non-public properties
- ☐ C. To test how multiple components work together
- ☒ D. To verify the DOM output of a component
- ☒ E. To verify that events fire when expected

### Question 29 of 62



Choose 1 option.

Salesforce users consistently receive a "Maximum trigger depth exceeded" error when saving an Account.

How can a developer fix this error?

- ☐ A. Split the trigger logic into two separate triggers.
- ☐ B. Modify the trigger to use the `isMultiThread=true` annotation.
- ☐ C. Convert the trigger to use the `@future` annotation, and chain any subsequent trigger invocations to the Account object.
- ☒ D. Use a helper class to set a Boolean to TRUE the first time a trigger is fired, and then modify the trigger to only fire when the Boolean is FALSE.

### Question 28 of 62



Choose 1 option.

A software company uses a custom object, `Defect__c`, to track defects in their software. `Defect__c` has organization-wide defaults set to private. Each `Defect__c` has a related list of `Reviewer__c` records, each with a lookup field to User that is used to indicate that the User will review the `Defect__c`.

What should be used to give the User on the `Reviewer__c` record read only access to the `Defect__c` record on the `Reviewer__c` record?

- ☒ A. View All on `Defect__c`
- ☐ B. Criteria-based sharing
- ☐ C. Lightning web component
- ☐ D. Apex managed sharing



### Question 27 of 62



Choose 2 options.

A developer is tasked with creating a Lightning web component that allows users to create a Case for a selected product, directly from a custom Lightning page. The input fields in the component are displayed in a non-linear fashion on top of an image of the product to help the user better understand the meaning of the fields.

Which two components should a developer use to implement the creation of the Case from the Lightning web component?

- ☐ A. lightning-record-form
- ☒ B. lightning-record-edit-form
- ☒ C. lightning-input-field
- ☐ D. lightning-input

### Question 26 of 62



Choose 2 options.

A large company uses Salesforce across several departments. Each department has its own Salesforce Administrator. It was agreed that each Administrator would have their own sandbox in which to test changes.

Recently, users notice that fields that were recently added for one department suddenly disappear without warning.

Which two statements are true regarding these issues and resolution?

- ☐ A. The administrators are deploying their own Change Sets, thus deleting each other's fields from the objects in production.
- ☒ B. The administrators are deploying their own Change Sets over each other, thus replacing entire Page Layouts in production.
- ☐ C. Page Layouts should never be deployed via Change Sets, as this causes Field-Level Security to be reset and fields to disappear.
- ☒ D. A sandbox should be created to use as a unified testing environment instead of deploying Change Sets directly to production.

### Question 25 of 62



Choose 1 option.

A company has a Lightning page with many Lightning Components, some that cache reference data. It is reported that the page does not always show the most current reference data.

What can a developer use to analyze and diagnose the problem in the Lightning page?

- ☒ A. Salesforce Lightning Inspector Storage tab
- ☐ B. Salesforce Lightning Inspector Event Log tab
- ☐ C. Salesforce Lightning Inspector Actions tab
- ☐ D. Salesforce Lightning Inspector Transactions tab

## Question 24 of 62



Choose 1 option.

```

        </apex:pageBlockSection>
    </apex:pageBlock>
</apex:form>
</apex:page>

```

Users of this Visualforce page complain that the page does a full refresh every time the Search button is pressed.

What should the developer do to ensure that a partial refresh is made so that only the section identified with `opportunityList` is re-drawn on the screen?

- ☐ A. Enclose the DATA table within the `<apex:actionRegion>` tag.
- ☐ B. Implement the `<apex:actionFunction>` tag with `immediate = true`.
- ☐ C. Ensure the action method search returns null.
- ☒ D. Implement the `reRender` attribute on the `<apex:commandButton>` tag.

## Question 24 of 62



Choose 1 option.

Consider the following code snippet:

```

<apex:page docType="html-5.0" controller="FindOpportunities">
    <apex:form >
        <apex:pageBlock >
            <apex:pageBlockSection title="find opportunity">
                <apex:input label="opportunity name"/>
                <apex:commandButton value="search" action="{!search}" />
            </apex:pageBlockSection>
            <apex:pageBlockSection title="Opportunity List" id="opportunityList">
                <!-- DATA Table -->
            </apex:pageBlockSection>
        </apex:pageBlock>
    </apex:form>
</apex:page>

```

Users of this Visualforce page complain that the page does a full refresh every time the Search button is pressed.

What should the developer do to ensure that a partial refresh is made so that only the section identified with

## Question 23 of 62



Choose 1 option.

Given a list of Opportunity records named `opportunityList`, which code snippet is best for querying all Contacts of the Opportunity's Account?

- ☒ A. 

```

List<Contact> contactList = new List<Contact>();
Set<Id> accountIds = new Set<Id> ();
for(Opportunity o : opportunityList){
    accountIds.add(o.AccountId);
}
for(Account a : [SELECT Id, (SELECT Id FROM Contacts) FROM Account WHERE Id IN :accountIds]){
    contactList.addAll(a.Contacts);
}

```
- ☐ B. 

```

List<Contact> contactList = new List<Contact>();
for ( Contact c : [SELECT Id FROM Contact WHERE AccountId IN :opportunityList.AccountId] ){
    contactList.add(c);
}

```

### Question 22 of 62



Choose 1 option.

The Account after-update trigger fires whenever an Account's address is updated, and it updates every associated Contact with that address. The Contact after-update trigger fires on every edit, and it updates every Campaign Member record related to the Contact with the Contact's state.

Consider the following: A mass update of 200 Account records' addresses, where each Account has 50 Contacts. Each Contact has one Campaign Member. This means there are 10,000 Contact records across the Accounts and 10,000 Campaign Member records across the contacts.

What will happen when the mass update occurs?

- ☐ A. The mass update of Account address will succeed, but the Contact address updates will fail due to exceeding number of records processed by DML statements.
- ☐ B. There will be no error, since each trigger fires within its own context and each trigger does not exceed the limit of the number of records processed by DML statements.
- ☒ C. The mass update will fail, since the two triggers fire in the same context, thus exceeding the number of records

### Question 21 of 62



Choose 1 option.

Which statement is considered a best practice for writing bulk safe Apex triggers?

- ☐ A. Add `LIMIT 50000` to every SOQL statement.
- ☒ B. Add records to collections and perform DML operations against these collections.
- ☐ C. Use the Database methods with `allOrNone` set to `false` instead of DML statements.
- ☐ D. Perform all DML operations from within a future method.

### Question 20 of 62



Choose 1 option.

Universal Containers (UC) has enabled the translation workbench and has translated picklist values. UC has a custom multi-select picklist field, `Products__c`, on the Account object that allows sales reps to specify which of UC's products an Account already has. A developer is tasked with writing an Apex method that retrieves Account records, including the `Products__c` field.

What should the developer do to ensure the value of `Products__c` is in the current user's language?

- ☒ A. Use `toLabel(Products__c)` in the fields list of the SOQL query.
- ☐ B. Call the `translate()` method on each record in the SOQL result list.
- ☐ C. Set the locale on each record in the SOQL result list.
- ☐ D. Use the `locale` clause in the SOQL query.

### Question 19 of 62



Choose 1 option.

Universal Containers decided to use Salesforce to manage a new hire interview process. A custom object called Candidate was created with organization-wide defaults set to Private. A lookup on the Candidate object sets an employee as an Interviewer.

What should be used to automatically give Read access to the record when the lookup field is set to the Interviewer user?

- ☒ A. The record can be shared using an Apex class.
- ☐ B. The record can be shared using a permission set.
- ☐ C. The record can be shared using a sharing rule.
- ☐ D. The record cannot be shared with the current setup.

### Question 18 of 62



Choose 2 options.

```
06:         return contacts;
07:     }
08:
09:     private static List<Contact> getFiveMostRecent(Id accountId) {
10:         //...implementation...
11:     }
12: }
```

Which two lines must change in the above code to make the Apex method able to be wired?

- ☒ A. Add `public` to line 04.
- ☐ B. Add `@AuraEnabled(cacheable=true)` to line 08.
- ☐ C. Remove `private` from line 09.
- ☒ D. Add `@AuraEnabled(cacheable=true)` to line 03.

### Question 18 of 62



Choose 2 options.

A developer created a Lightning web component for the Account record page that displays the five most recently contacted Contacts for an Account. The Apex method, `getRecentContacts`, returns a list of Contacts and will be wired to a property in the component.

```
01:
02: public class ContactFetcher {
03:
04:     static List<Contact> getRecentContacts(Id accountId) {
05:         List<Contact> contacts = getFiveMostRecent(accountId);
06:         return contacts;
07:     }
08:
09:     private static List<Contact> getFiveMostRecent(Id accountId) {
10:         //...implementation...
11:     }
12: }
```

Which two lines must change in the above code to make the Apex method able to be wired?

### Question 17 of 62



Choose 1 option.

A developer created a JavaScript library that simplifies the development of repetitive tasks and features and uploaded the library as a static resource called jsUtils in Salesforce. Another developer is coding a new Lightning web component (LWC) and wants to leverage the library.

Which statement properly loads the static resource within the LWC?

- ☒ A. `import jsUtilities from '@salesforce/resourceUrl/jsUtils';`
- ☐ B. `import {jsUtilities} from '@salesforce/resourceUrl/jsUtils';`
- ☐ C. `const jsUtility = $A.get('$Resource.jsUtils');`
- ☐ D. `<lightning-require scripts="{!$Resource.jsUtils}"/>`

### Question 16 of 62



Choose 1 option.

// Insert SELECT statement here

- ☐ A. `[SELECT AccountId, CreatedDate, Field, NewValue, OldValue  
FROM Account__History  
WHERE CreatedDate <= :initialDate AND CreatedDate <= :endDate];`
- ☐ B. `[SELECT AccountId, CreatedDate, Field, NewValue, OldValue  
FROM Account__History  
WHERE CreatedDate >= :endDate AND CreatedDate <= :initialDate];`
- ☐ C. `[SELECT AccountId, CreatedDate, Field, NewValue, OldValue  
FROM AccountHistory  
WHERE CreatedDate BETWEEN :initialDate AND :endDate];`
- ☒ D. `[SELECT AccountId, CreatedDate, Field, NewValue, OldValue  
FROM AccountHistory  
WHERE CreatedDate >= :initialDate AND CreatedDate <= :endDate];`

### Question 16 of 62



Choose 1 option.

A developer needs to implement a system audit feature that allows users, assigned to a custom profile named "Auditors", to perform searches against the historical records in the Account object. The developer must ensure the search is able to return history records that are between 6 and 12 months old.

Given the code below, which select statement should be inserted below as a valid way to retrieve the Account History records ranging from 6 to 12 months old?

```
Date initialDate = System.Today().addMonths(-12);  
Date endDate = System.Today().addMonths(-6);  
// Insert SELECT statement here
```

- ☐ A. `[SELECT AccountId, CreatedDate, Field, NewValue, OldValue  
FROM Account__History  
WHERE CreatedDate <= :initialDate AND CreatedDate <= :endDate];`
- ☐ B. `[SELECT AccountId, CreatedDate, Field, NewValue, OldValue  
FROM Account__History  
WHERE CreatedDate >= :endDate AND CreatedDate <= :initialDate];`

### Question 15 of 62



Choose 1 option.

Universal Containers wants to notify an external system, in the event that an unhandled exception occurs, by publishing a custom event using Apex.

What is the appropriate publish/subscribe logic to meet this requirement?

- ☒ A. Publish the error event using the `Eventbus.publish()` method and have the external system subscribe to the event using CometD.
- ☐ B. Publish the error event using the `addError()` method and have the external system subscribe to the event using CometD.
- ☐ C. Publish the error event using the `addError()` method and write a trigger to subscribe to the event and notify the external system.
- ☐ D. Have the external system subscribe to the event channel. No publishing is necessary.

### Question 14 of 62



Choose 1 option.

A developer notices the execution of all the test methods in a class takes a long time to run, due to the initial setup of all the test data that is needed to perform the tests.

What should the developer do to speed up test execution?

- ☐ A. Define a method that creates test data and annotate with `@createData`.
- ☐ B. Reduce the amount of test methods in the class.
- ☒ C. Define a method that creates test data and annotate with `@testSetup`.
- ☐ D. Ensure proper usage of test data factory in all test methods.

### Question 13 of 62



Choose 1 option.

A developer is asked to find a way to store secret data with an ability to specify which profiles and users can access which secrets.

What should be used to store this data?

- ☐ A. Static resources
- ☐ B. Custom metadata
- ☒ C. Custom settings
- ☐ D. `System.Cookie` class



## Question 12 of 62



Choose 1 option.

```
@isTest
public static void testSearchTestAccounts(){
    Account a = new Account(name='test');
    insert a;
    Account [] accounts = TestAccountFinder.searchTestAccounts();
    System.assert(accounts.size() == 1 );
}
```

What should be used to fix this failing test?

- ☐ A. @isTest (SeeAllData=true) to access org data for the test
- ☐ B. Test.loadData to set up expected data
- ☒ C. Test.fixedSearchResults() method to set up expected data
- ☐ D. @testSetup method to set up expected data

## Question 12 of 62



Choose 1 option.

A developer wrote the following method to find all the test accounts in the org:

```
public static Account[] searchTestAccounts(){
    List<List<SObject>> searchList = [ FIND 'test' IN ALL FIELDS
                                      RETURNING Account(Name)];
    return (Account[]) searchList[0];
}
```

However, the test method below fails.

```
@isTest
public static void testSearchTestAccounts(){
    Account a = new Account(name='test');
    insert a;
    Account [] accounts = TestAccountFinder.searchTestAccounts();
    System.assert(accounts.size() == 1 );
}
```

What should be used to fix this failing test?

## Question 11 of 62



Choose 2 options.

A company has reference data stored in multiple custom metadata records that represent default information and delete behavior for certain geographic regions.

When a contact is inserted, the default information should be set on the contact from the custom metadata records based on the contact's address information. Additionally, if a user attempts to delete a contact that belongs to a flagged region, the user must get an error message.

Depending on company personnel resources, what are two ways to automate this?

- ☐ A. Remote action
- ☒ B. Flow Builder
- ☐ C. Apex invocable method
- ☒ D. Apex trigger



### Question 10 of 62



Choose 2 options.

As part of a custom interface, a developer team creates various new Lightning web components. Each of the components handles errors using toast messages. When the development is complete, all the components are added to the same Lightning page.

During acceptance testing, users complain about the long chain of toast messages that display when errors occur loading the components.

Which two techniques should the developer implement to improve the user experience?

- ☐ A. Use a Lightning web component to aggregate and display all errors.
- ☐ B. Use the `window.alert()` method to display the error messages.
- ☒ C. Use a `<template>` tag to display in-place error messages.
- ☒ D. Use public properties on each component to display the error messages.

### Question 9 of 62



Choose 1 option.

An Apex trigger creates a Contract record every time an Opportunity record is marked as Closed and Won. This trigger is working great, except (due to a recent acquisition) historical Opportunity records need to be loaded into the Salesforce instance.

When a test batch of records are loaded, the Apex trigger creates Contract records. A developer is tasked with preventing Contract records from being created when mass loading the Opportunities, but the daily users still need to have the Contract records created.

What is the most extendable way to update the Apex trigger to accomplish this?

- ☐ A. Add the Profile ID of the user who loads the data to the trigger, so the trigger will not fire for this user.
- ☐ B. Add a validation rule to the Contract to prevent Contract creation by the user who loads the data.
- ☐ C. Use a list custom setting to disable the trigger for the user who loads the data.
- ☒ D. Use a hierarchy custom setting to skip executing the logic inside the trigger for the user who loads the data.

### Question 8 of 62



Choose 1 option.

An org has a requirement that an Account must always have one and only one Contact listed as Primary. So selecting one Contact will de-select any others. The client wants a checkbox on the Contact called 'Is Primary' to control this feature. The client also wants to ensure that the last name of every Contact is stored entirely in uppercase characters.

What is the optimal way to implement these requirements?

- ☐ A. Write a Validation Rule on the Contact for the Is Primary logic and a before update trigger on Contact for the last name logic.
- ☐ B. Write an after update trigger on Contact for the Is Primary logic and a separate before update trigger on Contact for the last name logic.
- ☐ C. Write an after update trigger on Account for the Is Primary logic and a before update trigger on Contact for the last name logic.
- ☒ D. Write a single trigger on Contact for both after update and before update and callout to helper classes to handle each set of logic.

### Question 7 of 62



Choose 1 option.

In an organization that has multi-currency enabled, a developer is tasked with building a Lightning component that displays the top ten Opportunities most recently accessed by the logged in user. The developer must ensure the Amount and LastModifiedDate field values are displayed according to the user's locale.

What is the most effective approach to ensure values displayed respect the user's locale settings?

- ☒ A. Use the `FORMAT()` function in the SOQL query.
- ☐ B. Use a wrapper class to format the values retrieved via SOQL.
- ☐ C. Use REGEX expressions to format the values retrieved via SOQL.
- ☐ D. Use the `FOR VIEW` clause in the SOQL query.

### Question 6 of 62



Choose 1 option.

An org records customer order information in a custom object, `Order__c`, that has fields for the shipping address. A developer is tasked with adding code to calculate shipping charges on an order, based on a flat percentage rate associated with the region of the shipping address.

What should the developer use to store the rates by region, so that when the changes are deployed to production no additional steps are needed for the calculation to work?

- ☒ A. Custom metadata type
- ☐ B. Custom list setting
- ☐ C. Custom object
- ☐ D. Custom hierarchy setting

### Question 5 of 62



Choose 2 options.

As part of point-to-point integration, a developer must call an external web service which, due to high demand, takes a long time to provide a response. As part of the request, the developer must collect key inputs from the end user before making the callout.

Which two elements should the developer use to implement these business requirements?

- ☐ A. Batch Apex
- ☒ B. Lightning web component
- ☐ C. Screen Flow
- ☒ D. Apex method that returns a Continuation object

#### Question 4 of 62



Choose 1 option.

```
trigger on Case(before update) {
    CaseTriggerHandler.handle(Trigger.new);
}

D. public class CaseTriggerHandler {
    public static Boolean firstRun = true;
    public static void handle(List<Case> cases) {
        for (Case c : cases) {
            c.Edit_Count__c = c.Edit_Count__c + 1;
        }
    }
}

trigger on Case(before update) {
    if (CaseTriggerHandler.firstRun) {
        CaseTriggerHandler.handle(Trigger.new);
    }
    CaseTriggerHandler.firstRun = false;
}
```

#### Question 4 of 62



Choose 1 option.

An Apex trigger and Apex class increment a counter, Edit\_Count\_\_c, any time the Case is changed.

```
public class CaseTriggerHandler {
    public static void handle(List<Case> cases) {
        for (Case c : cases) {
            c.Edit_Count__c = c.Edit_Count__c + 1;
        }
    }
}

trigger on Case(before update) {
    CaseTriggerHandler.handle(Trigger.new);
}
```

A new before-save record-triggered flow on the Case object was just created in production for when a Case is created or updated. Since the process was added, there are reports that Edit\_Count\_\_c is being incremented more than once for Case edits.

Which Apex code fixes this problem?

#### Question 3 of 62



Choose 1 option.

A developer has a test class that creates test data before making a mock callout but now receives a 'You have uncommitted work pending. Please commit or rollback before calling out' error.

Which step should be taken to resolve the error?

- ☐ A. Ensure both the insertion and mock callout occur after the `Test.stopTest()`.
- ☐ B. Ensure the records are inserted before the `Test.startTest()` statement and the mock callout occurs within a method annotated with `@testSetup`.
- ☒ C. Ensure the records are inserted before the `Test.startTest()` statement and the mock callout occurs after the `Test.startTest()`.
- ☐ D. Ensure both the insertion and mock callout occur after the `Test.startTest()`.

## Question 2 of 62



Choose 1 option.

A company has a native iOS order placement app that needs to connect to Salesforce to retrieve consolidated information from many different objects in a JSON format.

Which is the optimal method to implement this in Salesforce?

- ☐ A. Apex SOAP web service
- ☐ B. Apex SOAP callout
- ☐ C. Apex REST callout
- ☒ D. Apex REST web service

## Question 1 of 62

Choose 1 option.

```
}  
}
```

A developer is experiencing issues with a Lightning web component. The component must surface information about Opportunities owned by the currently logged-in user.

When the component is rendered, the following message is displayed: "Error retrieving data".

Which modification should be implemented to the Apex class to overcome the issue?

- ☐ A. Use the `Continuation=true` attribute in the Apex method.
- ☐ B. Edit the code to use the `without sharing` keyword in the Apex class.
- ☒ C. Use the `Cacheable=true` attribute in the Apex method.
- ☐ D. Ensure the OWD for the Opportunity object is Public.

## Question 1 of 62



Choose 1 option.

Refer to the following code snippets:

### MyOpportunities.js

```
import { LightningElement, api, wire } from 'lwc';
import getOpportunities from '@salesforce/apex/OpportunityController.findMyOpportunities';

export default class MyOpportunities extends LightningElement {
  @api userId;
  @wire(getOpportunities, {oppOwner: '$userId'})
  opportunities;
}
```

### OpportunityController.cls

```
public with sharing class OpportunityController {
  @AuraEnabled
  public static List<Opportunity> findMyOpportunities(Id oppOwner) {
    return [
      SELECT Id, Name, Amount
    ]
```