

Question 2 of 62

Choose 2 options.

A developer is tasked with creating a Lightning web component that is responsive on various devices.

Which two components should help accomplish this goal?

- ☐ A. `lightning-layout-item`
- ☐ B. `lightning-input-location`
- ☒ C. `lightning-navigation`
- ☒ D. `lightning-layout`

Question 3 of 62



Choose 1 option.

Refer to the following code snippets:

MyOpportunities.js

```
import { LightningElement, api, wire } from 'lwc';
import getOpportunities from '@salesforce/apex/OpportunityController.findMyOpportunities';

export default class MyOpportunities extends LightningElement {
    @api userId;
    @wire(getOpportunities, {oppOwner: '$userId'})
    opportunities;
}
```

OpportunityController.cls

```
public with sharing class OpportunityController {
    @AuraEnabled
    public static List<Opportunity> findMyOpportunities(Id oppOwner) {
        return [
            SELECT Id, Name, Amount
            FROM Opportunity
            WHERE OwnerId = :oppOwner
            WITH SECURITY_ENFORCED
            LIMIT 10
        ];
    }
}
```

Choose 1 option.

```
        FROM Opportunity
        WHERE OwnerId = :oppOwner
        WITH SECURITY_ENFORCED
        LIMIT 10
    ],
}
}
```

A developer is experiencing issues with a Lightning web component. The component must surface information about Opportunities owned by the currently logged-in user.

When the component is rendered, the following message is displayed: "Error retrieving data".

Which modification should be implemented to the Apex class to overcome the issue?

- ☐ A. Ensure the OWD for the Opportunity object is Public.
- ☐ B. Use the `Continuation=true` attribute in the Apex method.
- ☒ C. Use the `Cacheable=true` attribute in the Apex method.
- ☐ D. Edit the code to use the `without sharing` keyword in the Apex class.

Question 4 of 02

Choose 1 option.

Which statement is true regarding savepoints?

- ☐ A. You can roll back to any savepoint variable created in any order.
- ☒ B. Static variables are not reverted during a rollback.
- ☐ C. Savepoints are not limited by DML statement governor limits.
- ☐ D. Reference to savepoints can cross trigger invocations.

Question 5 of 62



Choose 1 option.

A developer wrote an Apex class to make several callouts to an external system.

If the URLs used in these callouts will change often, which feature should the developer use to minimize changes needed to the Apex class?

- ☒ A. Named Credentials
- ☐ B. Connected Apps
- ☐ C. Remote Site Settings
- ☐ D. Session Id

Question 6 of 62

Choose 1 option.

Given the following code:

```
for ( Contact c : [SELECT Id, LastName FROM Contact WHERE CreatedDate = TODAY] )
{
    Account a = [SELECT Id, Name FROM Account WHERE CreatedDate = TODAY LIMIT 5];
    c.AccountId = a.Id;
    update c;
}
```

Assuming there were 10 Contacts and five Accounts created today, what is the expected result?

- ☒ A. System.QueryException: List has more than one row for Assignment on Account
- ☐ B. System.LimitException: Too many SOQL Queries on Contact
- ☐ C. System.LimitException: Too many SOQL Queries on Account
- ☐ D. System.QueryException: Too many DML Statement errors on Contact

Question 7 of 62



Choose 1 option.

A developer has a Visualforce page that automatically assigns ownership of an Account to a queue upon save. The page appears to correctly assign ownership, but an assertion validating the correct ownership fails.

What can cause this problem?

- ☐ A. The test class does not implement the `Queueable` interface.
- ☒ B. The test class does not retrieve the updated value from the database.
- ☐ C. The test class does not use the `seeAllData=true` annotation.
- ☐ D. The test class does not use the Bulk API for loading test data.

Question 8 of 62



Choose 1 option.

A developer is asked to build a solution that will automatically send an email to the customer when an Opportunity stage changes. The solution must scale to allow for 10,000 emails per day. The criteria to send the email should be evaluated after certain conditions are met.

What is the optimal way to accomplish this?

- ☐ A. Use an Apex trigger with Batch Apex.
- ☒ B. Use an Email Alert with Flow Builder.
- ☐ C. Use `MassEmailMessage()` with an Apex trigger.
- ☐ D. Use `SingleEmailMessage()` with an Apex trigger.

Question 9 of 62



Choose 3 options.

Which three actions must be completed in a Lightning web component for a JavaScript file in a static resource to be loaded?

- ☒ A. Call `loadScript`.
- ☒ B. Import the static resource.
- ☒ C. Import a method from the `platformResourceLoader`.
- ☐ D. Reference the static resource in a `<script>` tag.
- ☐ E. Append the static resource to the DOM.



Choose 1 option.

Universal Containers wants to use a Customer Community with Customer Community Plus licenses to allow their customers access to track how many containers they have rented and when they are due back. Universal Containers uses a Private sharing model for External users.

Many of their customers are multi-national corporations with complex Account hierarchies. Each account on the hierarchy represents a department within the same business.

One of the requirements is to allow certain community users within the same Account hierarchy to see several departments' containers, based on a custom junction object that relates the Contact to the various Account records that represent the departments.

Which solution solves these requirements?

- ☒ A. An Apex trigger that creates Apex managed sharing records based on the junction object's relationships
- ☐ B. A custom list view on the junction object with filters that will show the proper records based on owner
- ☐ C. A Visualforce page that uses a custom controller that specifies `without sharing` to expose the records
- ☐ D. A Lightning web component on the Community Home Page that uses Lightning Data Services.

Question 11 of 62

Choose 1 option.

Part of a custom Lightning component displays the total number of Opportunities in the org, which are in the millions. The Lightning component uses an Apex method to get the data it needs.

What is the optimal way for a developer to get the total number of Opportunities for the Lightning component?

- ☒ A. COUNT () SOQL aggregate query on the Opportunity object
- ☐ B. Apex batch job that counts the number of Opportunity records
- ☐ C. SUM () SOQL aggregate query on the Opportunity object
- ☐ D. SOQL for loop that counts the number of Opportunities records

Question 12 of 62

Choose 1 option.

Which tag should a developer use to display different text while an `<apex:commandButton>` is processing an action?

- ☒ A. `<apex:actionStatus>`
- ☐ B. `<apex:actionPoller>`
- ☐ C. `<apex:pageMessages>`
- ☐ D. `<apex:actionSupport>`

Question 13 of 62



Choose 1 option.

A developer creates a Lightning web component to allow a Contact to be quickly entered. However, error messages are not displayed.

```
<template>
  <lightning-record-edit-form
    object-api-name="Contact">
    <lightning-input-field field-name="FirstName"></lightning-input-field>
    <lightning-input-field field-name="LastName"></lightning-input-field>
    <lightning-input-field field-name="Email"></lightning-input-field>
    <lightning-button type="submit"
      name="submit"
      label="Create Contact">
    </lightning-button>
  </lightning-record-edit-form>
</template>
```

Which component should the developer add to the form to display error messages?

- ☒ A. lightning-messages
- ☐ B. lightning-error
- ☐ C. apex:messages

</template>

Which component should the developer add to the form to display error messages?

- ☒ A. lightning-messages
- ☐ B. lightning-error
- ☐ C. apex:messages
- ☐ D. aura:messages

Question 14 of 62

Choose 1 option.

A company uses Salesforce to sell products to customers. They also have an external product information management (PIM) system that is the system of record for products.

A developer received these requirements:

- Whenever a product is created or updated in the PIM, a product must be created or updated as a Product2 record in Salesforce and a PricebookEntry record must be created or updated automatically by Salesforce.
- The PricebookEntry should be created in a Pricebook2 that is specified in a custom setting.

What should the developer use to satisfy these requirements?

- ☐ A. SOBJECT REST
- ☒ B. Custom Apex REST
- ☐ C. Invocable Action
- ☐ D. Event Monitoring

Question 15 of 62



Choose 1 option.

A developer is writing a Jest test for a Lightning web component that conditionally displays child components based on a user's checkbox selections.

What should the developer do to properly test that the correct components display and hide for each scenario?

- ☐ A. Add a teardown block to reset the DOM after each test.
- ☐ B. Create a new describe block for each test.
- ☐ C. Create a new `jsdom` instance for each test.
- ☐ D. Reset the DOM after each test with the `afterEach()` method.

Question 16 of 62



Choose 1 option.

A developer sees test failures in the sandbox but not in production. No code or metadata changes have been actively made to either environment since the sandbox was created.

Which consideration should be checked to resolve the issue?

- ☐ A. Ensure test classes are using `SeeAllData = true`.
- ☐ B. Ensure the Apex classes are on the same API version.
- ☒ C. Ensure the sandbox is on the same release as production.
- ☐ D. Ensure that Disable Parallel Apex Testing is unchecked.

Question 17 of 62



Choose 1 option.

A company's support process dictates that any time a case is closed with a status of 'Could not fix,' an Engineering Review custom object record should be created and populated with information from the case, the contact, and any of the products associated with the case.

What is the correct way to automate this using an Apex trigger?

- ☐ A. A `before update` trigger on Case that creates the Engineering Review record and inserts it
- ☐ B. An `after upsert` trigger on Case that creates the Engineering Review record and inserts it
- ☐ C. A `before upsert` trigger on Case that creates the Engineering Review record and inserts it
- ☒ D. An `after update` trigger on Case that creates the Engineering Review record and inserts it



Choose 1 option.

A developer built an Aura component for guests to self-register upon arrival at a front desk kiosk. Now the developer needs to create a component for the utility tray to alert users whenever a guest arrives at the front desk.

What should be used?

- ☐ A. DML Operation
- ☐ B. ChangeLog
- ☒ C. Application Event
- ☐ D. Component Event

Question 19 of 62



Choose 2 options.

A developer created an Opportunity trigger that updates the account rating when an associated opportunity is considered high value. Current criteria for an opportunity to be considered high value is an amount greater than or equal to \$1,000,000. However, this criteria value can change over time.

There is a new requirement to also display high value opportunities in a Lightning web component.

Which two actions should the developer take to meet these business requirements, and also prevent the business logic that obtains the high value opportunities from being repeated in more than one place?

- ☐ A. Leave the business logic code inside the trigger for efficiency.
- ☒ B. Use custom metadata to hold the high value amount.
- ☐ C. Call the trigger from the Lightning web component.
- ☒ D. Create a helper class that fetches the high value opportunities.

Question 20 of 62



Choose 2 options.

A developer created a Lightning web component that allows users to input a text value that is used to search for Accounts by calling an Apex method. The Apex method returns a list of `AccountWrappers` and is called imperatively from a JavaScript event handler.

```
01:
02: public class AccountSearcher {
03:
04:     public static List<AccountWrapper> search(String term) {
05:         List<AccountWrapper> wrappers = getMatchingAccountWrappers(term);
06:         return wrappers;
07:     }
08:
09:
10:     public class AccountWrapper {
11:         public Account { get; set; }
12:         public Decimal matchProbability { get; set; }
13:     }
14:     // ...other methods, including getMatchingAccountWrappers implementation...
15: }
```

Which two changes should the developer make so the Apex method functions correctly?

- ☐ A. Add `@AuraEnabled` to line 01.

19: }

Which two changes should the developer make so the Apex method functions correctly?

- ☐ A. Add @AuraEnabled to line 01.
- ☐ B. Add @AuraEnabled to line 09.
- ☒ C. Add @AuraEnabled to lines 11 and 12.
- ☒ D. Add @AuraEnabled to line 03.

Question 21 of 62

Choose 1 option.

A developer needs to store variables to control the style and behavior of a Lightning Web Component.

Which feature can be used to ensure that the variables are testable in both Production and all Sandboxes?

- ☒ A. Custom metadata
- ☐ B. Custom object
- ☐ C. Custom setting
- ☐ D. Custom variable

Question 22 of 62



Choose 1 option.

A Salesforce developer is hired by a multi-national company to build a custom Lightning application that shows employees their employment benefits and earned commissions over time. The application must acknowledge and respect the user's locale context for dates, times, numbers, currency, and currency symbols.

When using Aura components, which approach should the developer implement to ensure the Lightning application complies with the user's locale?

- ☐ A. Use the `$User` global variable to retrieve the user preferences.
- ☐ B. Create a Hierarchical custom setting to store user preferences.
- ☒ C. Use the `$Locale` value provider to retrieve the user preferences.
- ☐ D. Use the `$Label` global value provider.

Question 23 of 62



Choose 3 options.

A company recently deployed a Visualforce page with a custom controller that has a data grid of information about Opportunities in the org. Users report that they receive a "Maximum view state size limit" error message under certain conditions.

According to Visualforce best practice, which three actions should the developer take to reduce the view state?

- ☒ A. Use the transient keyword in the Apex controller for variables that do not maintain state.
- ☐ B. Use the private keyword in the controller for variables.
- ☐ C. Use the final keyword in the controller for variables that will not change.
- ☒ D. Use filters and pagination to reduce the amount of data.
- ☒ E. Refine any SOQL queries to return only data relevant to the page.



Choose 1 option.

An Apex trigger creates a Contract record every time an Opportunity record is marked as Closed and Won. This trigger is working great, except (due to a recent acquisition) historical Opportunity records need to be loaded into the Salesforce instance.

When a test batch of records are loaded, the Apex trigger creates Contract records. A developer is tasked with preventing Contract records from being created when mass loading the Opportunities, but the daily users still need to have the Contract records created.

What is the most extendable way to update the Apex trigger to accomplish this?

- ☐ A. Add the Profile ID of the user who loads the data to the trigger, so the trigger will not fire for this user.
- ☐ B. Add a validation rule to the Contract to prevent Contract creation by the user who loads the data.
- ☒ C. Use a hierarchy custom setting to skip executing the logic inside the trigger for the user who loads the data.
- ☐ D. Use a list custom setting to disable the trigger for the user who loads the data.



Choose 1 option.

A company wants to incorporate a third-party web service to set the Address fields when an Account is inserted, if they have not already been set.

What is the optimal way to achieve this?

- ☐ A. Create a Before Save Flow, execute a Queueable job from it, and make a callout from the Queueable job.
- ☐ B. Create an Apex class, execute a Batch Apex job from it, and make a callout from the Batch Apex job.
- ☒ C. Create an Apex trigger, execute a Queueable job from it, and make a callout from the Queueable job.
- ☐ D. Create an Apex class, execute a Future method from it, and make a callout from the Future method.



Question 26 of 62

Choose 2 options.

Refer to the code:

```
01 <!-- Lightning Web Component HTML file -->
02
03 <template>
04   <lightning-button label="Call server" onclick={handleClick}></lightning-button>
05 </template>
```

```
01 // Lightning Web Component JS file
02
03 import {LightningElement} from 'lwc';
04 import serverEcho from '@salesforce/apex/SimpleServerSideController.serverEcho';
05
06 export default class Helloworld extends LightningElement {
07   firstName = 'world';
08   handleClick() {
09     serverEcho({ firstName: this.firstName })
10       .then((result) => {
11         alert('From server: ' + result);
12       })
13       .catch((error) => {
14         console.error(error);
15       });
16   }
17 }
```

Choose 2 options.

```
14         console.error(error);  
15     });  
16 }  
17 }
```

```
01 // Apex Controller for Lightning Component  
02  
03 public with sharing class SimpleServerSideController {  
04     @AuraEnabled  
05     public static String serverEcho(sObject firstName) {  
06         String firstNameStr = (String)firstName.get('firstName');  
07         return ('Hello from the server, ' + firstNameStr);  
08     }  
09 }
```

Given the code above, which two changes need to be made in the Apex Controller for the code to work?

- ☐ A. Annotate the entire class as @AuraEnabled instead of just the single method.
- ☒ B. Change the argument in the Apex Controller line 05 from sObject to String.
- ☒ C. Remove line 06 from the Apex Controller and instead use firstName in the return on line 07.
- ☐ D. Change the method signature to be global static, not public static.



Review



Comment

Back

Question 27 of 62



Choose 3 options.

A developer is building a complex commission calculation engine in Apex that is called from an Opportunity trigger. During QA it was reported that the calculations are incorrect.

The developer has representative test data and passing test methods in their developer sandbox.

Which three tools or techniques could the developer use to execute the code and pause it at key lines to visually inspect values of various Apex variables?

- ☒ A. Apex Interactive Debugger
- ☒ B. Apex Replay Debugger
- ☐ C. Workbench
- ☒ D. Developer Console
- ☐ E. Breakpoints

Question 28 of 62



Choose 1 option.

Consider the following code snippet:

```
01 public class with sharing AccountsController{
02
03     @AuraEnabled
04     public List<Accounts> getAllAccounts() {
05         return [Select Id, Name, Industry FROM Account];
06     }
07
08 }
```

As part of the deployment cycle, a developer creates the following test class:

```
01 private class with sharing AccountsController_Test{
02
03     @TestSetup
04     private static void makeData() {
05         User user1 = [Select Id FROM User WHERE Profile.Name = 'System Administrator' and
isActive = true LIMIT 1 ];
06         User user2 = [Select Id FROM User WHERE Profile.Name = 'Standard User' and userName =
'test@test.com' and isActive = true LIMIT 1];
07
08         TestUtils.insertAccounts(10,user1.Id);
09         TestUtils.insertAccounts(20,user2.Id);
10     }
```

```
15         List<Account> result = AccountsController.getAllAccounts();
16         System.assertEquals(20, result.size());
17
18     }
19
20 }
```

When the test class runs, the assertion fails.

Which change should the developer implement in the Apex test method to ensure the test method executes successfully?

- ☐ A. Add `@IsTest(seeAllData=true)` to line 12 and enclose lines 15 and 16 within `Test.startTest()` and `Test.stopTest()`.
- ☐ B. Add `System.runAs(User)` to line 14 and enclose line 15 within `Test.startTest()` and `Test.stopTest()`.
- ☒ C. Query the Standard User into memory and enclose lines 15 and 16 within the `System.runAs(user)` method.
- ☐ D. Query the Administrator user into memory and enclose lines 15 and 16 within the `System.runAs(user)` method.

Question 29 of 62

Choose 1 option.

Consider the Apex class below that defines a RemoteAction used on a Visualforce search page.

```
global with sharing class MyRemoter {  
    public String accountName { get; set; }  
    public static Account account { get; set; }  
    public MyRemoter() {}  
  
    @RemoteAction  
    global static Account getAccount(String accountName) {  
        account = [SELECT Id, Name, NumberOfEmployees  
                    FROM Account WHERE Name = :accountName];  
        return account;  
    }  
}
```

Which code snippet will assert that the remote action returned the correct Account?

- ☐ A.

```
MyRemoter remote = new MyRemoter();  
Account a = remote.getAccount('TestAccount');  
System.assertEquals( 'TestAccount', a.Name );
```
- ☐ B.

```
MyRemoter remote = new MyRemoter('TestAccount');  
Account a = remote.getAccount();  
System.assertEquals( 'TestAccount', a.Name );
```

```
        return account;  
    }  
}
```

Which code snippet will assert that the remote action returned the correct Account?

- ☐ A.

```
MyRemoter remote = new MyRemoter();  
Account a = remote.getAccount('TestAccount');  
System.assertEquals( 'TestAccount', a.Name );
```
- ☐ B.

```
MyRemoter remote = new MyRemoter('TestAccount');  
Account a = remote.getAccount();  
System.assertEquals( 'TestAccount', a.Name );
```
- ☐ C.

```
Account a = controller.getAccount('TestAccount');  
System.assertEquals( 'TestAccount', a.Name );
```
- ☒ D.

```
Account a = MyRemoter.getAccount('TestAccount');  
System.assertEquals( 'TestAccount', a.Name );
```

Question 30 of 62

Choose 2 options.

Consider the queries in the options below and the following information:

- For these queries, assume that there are more than 200,000 Account records.
- These records include soft-deleted records; that is, deleted records that are still in the Recycle Bin.
- There are two fields that are marked as External Id on the Account. These fields are `Customer_Number__c` and `ERP_Key__c`.

Which two queries are optimized for large data volumes?

- ☒ A. `SELECT Id FROM Account WHERE Name != '' AND Customer_Number__c = 'ValueA'`
- ☐ B. `SELECT Id FROM Account WHERE Name != '' AND IsDeleted = false`
- ☐ C. `SELECT Id FROM Account WHERE Name != NULL`
- ☒ D. `SELECT Id FROM Account WHERE Id IN :aListVariable`

Question 31 of 62

Choose 1 option.

An Aura component has a section that displays some information about an Account and it works well on the desktop, but users have to scroll horizontally to see the description field output on their mobile devices and tablets.

```
<lightning:layout multipleRows="false">
  <lightning:layoutItem size="6">{!v.rec.Name}
</lightning:layoutItem>

  <lightning:layoutItem size="6">{!v.rec.Description__c}
</lightning:layoutItem>
</lightning:layout>
```

How should a developer change the component to be responsive for mobile and tablet devices?

- ☒ A.

```
<lightning:layout multipleRows="true">
  <lightning:layoutItem size="12" largeDeviceSize="6">{!v.rec.Name}
</lightning:layoutItem>

  <lightning:layoutItem size="12" largeDeviceSize="6">{!v.rec.Description__c}
</lightning:layoutItem>
</lightning:layout>
```
- ☐ B.

```
<lightning:layout multipleRows="false">
  <lightning:layoutItem smallDeviceSize="12" largeDeviceSize="6">{!v.rec.Name}
```

Choose 1 option:

```
<lightning:layoutItem smallDeviceSize="12" largeDeviceSize="6">
  {!v.rec.Description__c}
</lightning:layoutItem>
</lightning:layout>
```

☐ C.

```
<lightning:layout multipleRows="true">
  <lightning:layoutItem smallDeviceSize="12" largeDeviceSize="6">{!v.rec.Name}
</lightning:layoutItem>
```

```
<lightning:layoutItem smallDeviceSize="12" largeDeviceSize="6">
  {!v.rec.Description__c}
</lightning:layoutItem>
</lightning:layout>
```

☐ D.

```
<lightning:layout multipleRows="false">
  <lightning:layoutItem size="12" largeDeviceSize="6">{!v.rec.Name}
</lightning:layoutItem>
```

```
<lightning:layoutItem size="12" largeDeviceSize="6">{!v.rec.Description__c}
</lightning:layoutItem>
</lightning:layout>
```



Choose 2 options.

A developer created a class that implements the Queueable Interface, as follows:

```
public class without sharing OrderQueueableJob implements Queueable {  
    public void execute(QueueableContext context) {  
        // implementation logic  
        System.enqueueJob(new FollowUpJob());  
    }  
}
```

As part of the deployment process, the developer is asked to create a corresponding test class.

Which two actions should the developer take to successfully execute the test class?

- ☐ A. Implement `seeAllData=true` to ensure the Queueable job is able to run in bulk mode.
- ☐ B. Implement `Test.isRunningTest()` to prevent chaining jobs during test execution.
- ☒ C. Ensure the running user of the test class has, at least, the View All permission on the Order object.
- ☒ D. Enclose `System.enqueueJob(new OrderQueueableJob())` within `Test.startTest` and `Test.stopTest()`.

Question 33 of 62

Choose 1 option.

A developer is writing code that requires making callouts to an external web service.

Which scenario necessitates that the callout be made in an asynchronous method?

- ☐ A. The callout could take longer than 60 seconds to complete.
- ☐ B. The callouts will be made using the REST API.
- ☒ C. The callouts will be made in an Apex trigger.
- ☐ D. Over 10 callouts will be made in a single transaction.

Question 34 of 62



Choose 1 option.

A developer wants to write a generic Apex method that will compare the Salesforce Name field between any two object records. For example, to compare the Name field of an Account and an Opportunity; or the Name of an Account and a Contact.

Assuming the Name field exists, how should the developer do this?

- ☐ A. Use a `String.replace()` method to parse the contents of each Name field and then compare the results.
- ☐ B. Use the Salesforce Metadata API to extract the value of each object and compare the Name fields.
- ☒ C. Cast each object into an `sObject` and use `sObject.get('Name')` to compare the Name fields.
- ☐ D. Invoke a `Schema.describe()` function to compare the values of each Name field.

Question 34 of 62



Choose 1 option.

A developer wants to write a generic Apex method that will compare the Salesforce Name field between any two object records. For example, to compare the Name field of an Account and an Opportunity; or the Name of an Account and a Contact.

Assuming the Name field exists, how should the developer do this?

- ☐ A. Use a `String.replace()` method to parse the contents of each Name field and then compare the results.
- ☐ B. Use the Salesforce Metadata API to extract the value of each object and compare the Name fields.
- ☒ C. Cast each object into an `sObject` and use `sObject.get('Name')` to compare the Name fields.
- ☐ D. Invoke a `Schema.describe()` function to compare the values of each Name field.

Question 35 of 62

Choose 1 option.

After a platform event is defined in a Salesforce org, events can be published via which mechanism?

- ☐ A. External Apps require the standard Streaming API.
- ☐ B. Internal Apps can use outbound messages.
- ☒ C. External Apps use an API to publish event messages.
- ☐ D. Internal Apps can use entitlement processes.

Question 36 of 62



Choose 1 option.

An Apex trigger creates an `Order__c` record every time an Opportunity is won by a Sales Rep. Recently the trigger is creating two orders.

What is the optimal technique for a developer to troubleshoot this?

- ☐ A. Disable all flows, and then re-enable them one at a time to see which one causes the error.
- ☐ B. Set up debug logging for every Sales Rep, then monitor the logs for errors and exceptions.
- ☐ C. Run the Apex Test Classes for the Apex trigger to ensure the code still has sufficient code coverage.
- ☒ D. Add `system.debug()` statements to the code and use the Developer Console logs to trace the code.

Question 37 of 62



Choose 3 options.

Refer to the following code snippet:

```
public class LeadController {  
    public static List<Lead> getFetchLeadList(String searchTerm, Decimal aRevenue) {  
        String safeTerm = '%' + searchTerm.escapeSingleQuote() + '%'  
        return [  
            SELECT Name, Company, AnnualRevenue  
            FROM Lead  
            WHERE AnnualRevenue >= :aRevenue  
            AND Company LIKE :safeTerm;  
            LIMIT 20  
        ];  
    }  
}
```

A developer created a JavaScript function as part of a Lightning web component (LWC) that surfaces information about Leads by wire calling `getFetchLeadList` when certain criteria are met.

Which three changes should the developer implement in the Apex class above to ensure the LWC can display data efficiently while preserving security?

- ☒ A. Use the `WITH SECURITY_ENFORCED` clause within the SOQL query.
- ☒ B. Implement the `with sharing` keyword in the class declaration.

```
}
```

A developer created a JavaScript function as part of a Lightning web component (LWC) that surfaces information about Leads by wire calling `getFetchLeadList` when certain criteria are met.

Which three changes should the developer implement in the Apex class above to ensure the LWC can display data efficiently while preserving security?

- ☒ A. Use the `WITH SECURITY_ENFORCED` clause within the SOQL query.
- ☒ B. Implement the `with sharing` keyword in the class declaration.
- ☒ C. Annotate the Apex method with `@AuraEnabled(Cacheable=true)`.
- ☐ D. Implement the `without sharing` keyword in the class declaration.
- ☐ E. Annotate the Apex method with `@AuraEnabled`.

Question 38 of 62



Choose 1 option.

A company notices that their unit tests in a test class with many methods to create many records for prerequisite reference data are slow.

What can a developer to do address the issue?

- ☐ A. Turn off triggers, flows, and validations when running tests.
- ☐ B. Move the prerequisite reference data setup to the constructor for the test class.
- ☐ C. Move the prerequisite reference data setup to a `@testSetup` method in the test class.
- ☒ D. Move the prerequisite reference data setup to a `TestDataFactory` and call that from each test method.

Question 39 of 62



Choose 2 options.

A company has reference data stored in multiple custom metadata records that represent default information and delete behavior for certain geographic regions.

When a contact is inserted, the default information should be set on the contact from the custom metadata records based on the contact's address information. Additionally, if a user attempts to delete a contact that belongs to a flagged region, the user must get an error message.

Depending on company personnel resources, what are two ways to automate this?

- ☒ A. Apex trigger
- ☐ B. Remote action
- ☒ C. Flow Builder
- ☐ D. Apex invocable method

Question 40 of 62



Choose 1 option.

A developer used custom settings to store some configuration data that changes occasionally. However, tests are now failing in some of the sandboxes that were recently refreshed.

What should be done to eliminate this issue going forward?

- ☐ A. Set the setting type on the custom setting to List.
- ☐ B. Replace custom settings with static resources.
- ☒ C. Replace custom settings with custom metadata.
- ☐ D. Set the setting type on the custom setting to Hierarchy.

Question 41 of 62



Choose 1 option.

A developer is responsible for formulating the deployment process for a Salesforce project. The project follows a source-driven development approach, and the developer wants to ensure efficient deployment and version control of the metadata changes.

Which tool or mechanism should be utilized for managing the source-driven deployment process?

- ☐ A. Data Loader
- ☐ B. Change Sets
- ☒ C. Salesforce CLI with Salesforce DX
- ☐ D. Unmanaged Packages

Question 42 of 62



Choose 1 option.

Universal Containers is using a custom Salesforce application to manage customer support cases. The support team needs to collaborate with external partners to resolve certain cases. However, they want to control the visibility and access to the cases shared with the external partners.

Which Salesforce feature can help achieve this requirement?

- ☐ A. Apex managed sharing
- ☒ B. Sharing sets
- ☐ C. Role hierarchy
- ☐ D. Criteria-based sharing rules

Question 43 of 62



Choose 2 options.

```
trigger AssignOwnerByRegion on Account ( before insert, before update )
{
    List<Account> accountList = new List<Account>();
    for( Account anAccount : trigger.new )
    {
        Region__c theRegion = [
            SELECT Id, Name, Region_Manager__c
            FROM Region__c
            WHERE Name = :anAccount.Region_Name__c
        ];
        anAccount.OwnerId = theRegion.Region_Manager__c;

        accountList.add( anAccount );
    }

    update accountList;
}
```

Consider the above trigger intended to assign the Account to the manager of the Account's region.

Which two changes should a developer make in this trigger to adhere to best practices?

- ☒ A. Remove the last line updating `accountList` as it is not needed.

Consider the above trigger intended to assign the Account to the manager of the Account's region.

Which two changes should a developer make in this trigger to adhere to best practices?

- ☒ A. Remove the last line updating `accountList` as it is not needed.
- ☐ B. Use a Map `accountMap` instead of List `accountList`.
- ☐ C. Use a Map to cache the results of the `Region__c` query by Id.
- ☒ D. Move the `Region__c` query to outside the loop.

Question 44 of 62

Choose 1 option.

A developer is building a Lightning web component that retrieves data from Salesforce and assigns it to the record property

```
import { LightningElement, api, wire } from 'lwc';
import { getRecord } from 'lightning/uiRecordApi';

export default class Record extends LightningElement {
  @api fields;
  @api recordId;
  record;
}
```

What must be done in the component to get the data from Salesforce?

- ☐ A. Add the following code above record;
@api(getRecord, { recordId: '\$recordId' })
Get the fields in renderedCallback() and assign them to record.
- ☐ B. Add the following code above record;
@wire(getRecord, { recordId: '\$recordId' })
Get the fields in renderedCallback() and assign them to record.
- ☐ C. Add the following code above record;
@api(getRecord, { recordId: '\$recordId', fields: '\$fields' })

- ☐ B. Add the following code above record;

```
@wire(getRecord, { recordId: '$recordId' })
```

Get the fields in `renderedCallback()` and assign them to record.

- ☐ C. Add the following code above record;

```
@api(getRecord, { recordId: '$recordId', fields: '$fields' })
```

- ☒ D. Add the following code above record;

```
@wire(getRecord, { recordId: '$recordId', fields: '$fields' })
```

Question 45 of 62



Choose 2 options.

Consider the following code snippet:

```
HttpRequest req = new HttpRequest();  
req.setEndpoint('https://TestEndpoint.example.com/some_path');  
req.setMethod('GET');  
Blob headerValue = Blob.valueOf('myUserName' + ':' + 'strongPassword');  
String authorizationHeader = 'BASIC ' + EncodingUtil.base64Encode(headerValue);  
req.setHeader('Authorization', authorizationHeader);  
Http http = new Http();  
HTTPResponse res = http.send(req);
```

Which two steps should the developer take to add flexibility to change the endpoint and credentials without needing to modify code?

- ☐ A. Use `req.setEndpoint(Label endPointURL);`.
- ☒ B. Use `req.setEndpoint('callout:endPoint_NC');` within the callout request.
- ☐ C. Store the URL of the endpoint in a custom Label named `endPointURL`.
- ☒ D. Create a Named Credential, `endPoint_NC`, to store the endpoint and credentials.

Question 46 of 62



Choose 1 option.

Which code snippet processes records in the most memory efficient manner, avoiding governor limits such as "Apex heap size too large"?

- ☐ A.

```
Map<Id, Opportunity> opportunities new Map<Id, Opportunity>([SELECT Id, Amount from Opportunity]);  
for(Id oppId: opportunities.keySet()){  
    // perform operation here  
}
```
- ☐ B.

```
for(Opportunity opp: [SELECT Id, Amount from Opportunity]){  
    // perform operation here  
}
```
- ☒ C.

```
List<Opportunity> opportunities = Database.query('SELECT Id, Amount from Opportunity');  
for(Opportunity opp: opportunities){  
    // perform operation here  
}
```
- ☐ D.

```
List<Opportunity> opportunities = [SELECT Id, Amount from Opportunity];  
for(Opportunity opp: opportunities){  
    // perform operation here  
}
```




Choose 1 option.

A developer is working with existing functionality that tracks how many times a stage has changed for an Opportunity. When the Opportunity's stage is changed, a workflow rule is fired to increase the value of a field by one. The developer wrote an after trigger to create a child record when the field changes from 4 to 5.

A user changes the stage of an Opportunity and manually sets the count field to 4. The count field updates to 5, but the child record is not created.

What is the reason this is happening?

- ☐ A. After triggers fire before workflow rules.
- ☐ B. Trigger.new does not change after a field update.
- ☒ C. Trigger.old does not contain the updated value of the count field.
- ☐ D. After triggers are not fired after field updates.

Question 48 of 62

Choose 1 option.

A Visualforce page loads slowly due to the large amount of data it displays.

Which strategy can a developer use to improve the performance?

- ☐ A. Use the transient keyword for the List variables used in the custom controller.
- ☒ B. Use lazy loading to load the data on demand, instead of in the controller's constructor.
- ☐ C. Use JavaScript to move data processing to the browser instead of the controller.
- ☐ D. Use an `<apex:actionPoller>` in the page to load all of the data asynchronously.

Question 49 of 62



Choose 1 option.

A developer is developing a reusable Aura component that will reside on an sObject Lightning page with the following HTML snippet:

```
<aura:component implements="force:hasRecordId,flexipage:availableForAllPageTypes">
<div>Hello!</div>
</aura:component>
```

How can the component's controller get the context of the Lightning page that the sObject is on without requiring additional test coverage?

- ☐ A. Create a design attribute and configure via App Builder.
- ☐ B. Set the sObject type as a component attribute.
- ☐ C. Use the `getSObjectType()` method in an Apex class.
- ☒ D. Add `force:hasSObjectName` to the `implements` attribute.



Choose 1 option.

A developer is creating a Lightning web component to display a calendar. The component will be used in multiple countries. In some locales, the first day of the week is a Monday, or a Saturday, or a Sunday.

What should the developer do to ensure the calendar displays accurately for users in every locale?

- ☐ A. Query the `FirstDayOfWeek` field from the `Locale` for the current user.
- ☐ B. Use a custom metadata type to store key/value pairs.
- ☐ C. Use `UserInfo.getLocale()` in the component.
- ☒ D. Import the `@salesforce/i18n` module and use the `firstDayOfWeek` internationalization property.

Question 51 of 62



Choose 1 option.

The Salesforce admin at Cloud Kicks created a custom object called `Region__c` to store all postal zip codes in the United States and the Cloud Kicks sales region the zip code belongs to.

Object Name:

`Region__c`

Fields:

`Zip_Code__c` (Text)

`Region_Name__c` (Text)

Cloud Kicks wants a trigger on the Lead to populate the Region based on the Lead's zip code.

Which code segment is the most efficient way to fulfill this request?

- ☐ A.

```
Set<String> zips = new Set<String>();  
for(Lead l : Trigger.new) {  
    if(l.PostalCode != Null) {  
        zips.add(l.PostalCode);  
    }  
}  
  
for(Lead l : Trigger.new) {  
    List<Region__c> regions = [SELECT Zip_Code__c,  
        Region_Name__c FROM Region__c WHERE Zip_Code__c IN :zips];
```

Choose 1 option.

```
for(Lead l : Trigger.new) {  
    List<Region__c> regions = [SELECT Zip_Code__c,  
    Region_Name__c FROM Region__c WHERE Zip_Code__c IN :zips];  
    for(Region__c r :regions) {  
        if(l.PostalCode == r.Zip_Code__c) {  
            l.Region__c = r.Region_Name__c;  
        }  
    }  
}
```

☐ B. Set<String> zips = new Set<String>();

```
for(Lead l : Trigger.new) {  
    if(l.PostalCode != Null) {  
        zips.add(l.PostalCode);  
    }  
}
```

```
List<Region__c> regions = [SELECT Zip_Code__c,  
Region_Name__c FROM Region__c WHERE Zip_Code__c IN :zips];
```

```
for(Lead l : Trigger.new) {  
    for(Region__c r :regions) {  
        if(l.PostalCode == r.Zip_Code__c) {  
            l.Region__c = r.Region_Name__c;  
        }  
    }  
}
```

☐ C.

```
for(Lead l : Trigger.new) {  
    Region__c reg = [SELECT Region_Name__c FROM Region__c  
    WHERE Zip_Code__c = :l.PostalCode];  
    l.Region__c = reg.Region_Name__c;  
}
```

☒ D.

```
Set<String> zips = new Set<String>();  
for(Lead l : Trigger.new) {  
    if(l.PostalCode != Null) {  
        zips.add(l.PostalCode);  
    }  
}
```

```
List<Region__c> regions = [SELECT Zip_Code__c,  
Region_Name__c FROM Region__c WHERE Zip_Code__c IN :zips];
```

```
Map<String, String> zipMap = new Map<String, String>();  
for(Region__c r :regions) {  
    zipMap.put(r.Zip_Code__c, r.Region_Name__c);  
}
```

```
        l.Region__c = reg.Region_Name__c;
    }
}
```

⦿ D. Set<String> zips = new Set<String>();

```
for(Lead l : Trigger.new) {
    if(l.PostalCode != Null) {
        zips.add(l.PostalCode);
    }
}
```

```
List<Region__c> regions = [SELECT Zip_Code__c,
Region_Name__c FROM Region__c WHERE Zip_Code__c IN :zips];
```

```
Map<String, String> zipMap = new Map<String, String>();
for(Region__c r :regions) {
    zipMap.put(r.Zip_Code__c, r.Region_Name__c);
}
```

```
for(Lead l : Trigger.new) {
    if(l.PostalCode != Null) {
        l.Region__c = zipMap.get(l.PostalCode);
    }
}
```




Choose 1 option.

Refer to the code snippet below:

```
public static void updateCreditMemo(String customerId, Decimal newAmount){  
    List<Credit_Memo__c> toUpdate = new List<Credit_Memo__c>();  
    for(Credit_Memo__c creditMemo : [Select Id, Name, Amount__c FROM Credit_Memo__c WHERE  
Customer_Id__c = :customerId LIMIT 50]){  
        creditMemo.Amount__c = newAmount;  
        toUpdate.add(creditMemo);  
    }  
    Database.update(toUpdate, false);  
}
```

A custom object called `Credit_Memo__c` exists in a Salesforce environment. As part of a new feature development that retrieves and manipulates this type of record, the developer needs to ensure race conditions are prevented when a set of records are modified within an Apex transaction.

In the preceding Apex code, how can the developer alter the query statement to use SOQL features to prevent race conditions within a transaction?

- ☒ A. `[Select Id, Name, Amount__c FROM Credit_Memo__c WHERE Customer_Id__c = :customerId
LIMIT 50 FOR UPDATE]`
- ☐ B. `[Select Id, Name, Amount__c FROM Credit_Memo__c WHERE Customer_Id__c = :customerId
USING SCOPE LIMIT 50]`

within a transaction?

- ☒ A. [Select Id, Name, Amount__c FROM Credit_Memo__c WHERE Customer_Id__c = :customerId
LIMIT 50 FOR UPDATE]
- ☐ B. [Select Id, Name, Amount__c FROM Credit_Memo__c WHERE Customer_Id__c = :customerId
USING SCOPE LIMIT 50]
- ☐ C. [Select Id, Name, Amount__c FROM Credit_Memo__c WHERE Customer_Id__c = :customerId
LIMIT 50 FOR REFERENCE]
- ☐ D. [Select Id, Name, Amount__c FROM Credit_Memo__c WHERE Customer_Id__c = :customerId
LIMIT 50 FOR VIEW]

Question 53 of 62



Choose 1 option.

Universal Containers decided to use Salesforce to manage a new hire interview process. A custom object called Candidate was created with organization-wide defaults set to Private. A lookup on the Candidate object sets an employee as an Interviewer.

What should be used to automatically give Read access to the record when the lookup field is set to the Interviewer user?

- ☒ A. The record can be shared using an Apex class.
- ☐ B. The record cannot be shared with the current setup.
- ☐ C. The record can be shared using a permission set.
- ☐ D. The record can be shared using a sharing rule.

Question 1 of 62



Choose 1 option.

Business rules require a Contact to always be created when a new Account is created.

What can be used when developing a custom screen to ensure an Account is not created if the creation of the Contact fails?

- ☒ A. Use `setSavePoint()` and `rollback()` with a try-catch block.
- ☐ B. Use a Database Savepoint method with a try-catch block.
- ☐ C. Use the `Database.Insert` method with `allOrNone` set to `false`.
- ☐ D. Use the `Database.Delete` method if the Contact insertion fails.

Question 54 of 62

Choose 1 option.

A developer creates an application event that has triggered an infinite loop.

What may have caused this problem?

- ☐ A. The event has multiple handlers registered in the project.
- ☒ B. The event is fired from a custom renderer.
- ☐ C. An event is fired 'ontouchend' and is unhandled.
- ☐ D. The event handler calls a trigger.

Question 55 of 62



Choose 1 option.

A company uses Opportunities to track sales to their customers and their org has millions of Opportunities. They want to begin to track revenue over time through a related Revenue object.

As part of their initial implementation, they want to perform a one-time seeding of their data by automatically creating and populating Revenue records for Opportunities, based on complex logic.

They estimate that roughly 100,000 Opportunities will have Revenue records created and populated.

What is the optimal way to automate this?

- ☒ A. Use `Database.executeBatch()` to invoke a `Database.Batchable` class.
- ☐ B. Use `System.enqueueJob()` to invoke a `Queueable` class.
- ☐ C. Use `Database.executeBatch()` to invoke a `Queueable` class.
- ☐ D. Use `System.scheduleJob()` to schedule a `Database.Scheduleable` class.

Question 56 of 62



Choose 1 option.

A company has an Apex process that makes multiple extensive database operations and web service callouts. The database processes and web services can take a long time to run and must be run sequentially.

How should the developer write this Apex code without running into governor limits and system limitations?

- ☐ A. Use Apex Scheduler to schedule each process.
- ☐ B. Use Limits class to stop entire process once governor limits are reached.
- ☐ C. Use multiple `@future` methods for each process and callout.
- ☒ D. Use Queueable Apex to chain the jobs to run sequentially.



Choose 1 option.

Universal Containers has an Apex trigger on Account that creates an Account Plan record when an Account is marked as a Customer.

Recently a record-triggered flow was added so that whenever an Account is marked as a Customer, a 'Customer Since' date field is updated with today's date. Since the addition of the flow, two Account Plan records are created whenever the Account is marked as a Customer.

What might cause this to happen?

- ☐ A. The Apex trigger is not bulk safe and calls insert inside of a for loop.
- ☐ B. The flow is configured to use an 'Update Records' element.
- ☒ C. The flow is configured to evaluate when a record is created and every time it is edited.
- ☐ D. The Apex trigger does not use a static variable to ensure it only fires once.

Question 58 of 62



Choose 1 option.

Refer to the test method below:

```
@isTest
static void testIncrement() {
    Account acct = new Account(Name = 'Test');
    acct.Number_Of_Times_Viewed__c = 0;
    insert acct;

    AuditUtil.incrementViewed(acct.Id);
    Account acctAfter = [SELECT Number_Of_Times_Viewed__c FROM Account WHERE Id = :acct.Id][0];

    System.assertEquals(1, acctAfter.Number_Of_Times_Viewed__c);
}
```

The test method calls an @future method that increments the Number_of_Times_Viewed__c value. The assertion is failing because the Number_of_Times_Viewed__c equals 0.

What is the optimal way to fix this?

- ☐ A. Change the assertion to `System.assertEquals(0, acctAfter.Number_Of_Times_Viewed__c)`.
- ☐ B. Add `Test.startTest()` before and `Test.stopTest()` after `insert acct`.

The test method calls an `@future` method that increments the `Number_of_Times_Viewed__c` value. The assertion is failing because the `Number_of_Times_Viewed__c` equals 0.

What is the optimal way to fix this?

- ☐ A. Change the assertion to `System.assertEquals(0, acctAfter.Number_Of_Times_Viewed__c)`.
- ☐ B. Add `Test.startTest()` before and `Test.stopTest()` after `insert acct`.
- ☐ C. Change the initialization to `acct.Number_Of_Times_Viewed__c = 1`.
- ☒ D. Add `Test.startTest()` before and `Test.stopTest()` after `AuditUtil.incrementViewed`.

Question 59 of 62



Choose 1 option.

A developer implemented a custom data table in a Lightning web component with filter functionality. However, users are submitting support tickets about long load times when the filters are changed. The component uses an Apex method that is called to query for records based on the selected filters.

What should the developer do to improve performance of the component?

- ☐ A. Use SOSL to query the records on filter change.
- ☒ B. Use `setStorable()` in the Apex method to store the response in the client-side cache.
- ☐ C. Return all records into a list when the component is created and filter the array in JavaScript.
- ☐ D. Use a selective SOQL query with a custom index.

Question 60 of 62



Choose 1 option.

A developer is tasked with ensuring that email addresses entered into the system for Contacts and for a custom object called `Survey_Response__c` do not belong to a list of blocked domains.

The list of blocked domains is stored in a custom object for ease of maintenance by users. The `Survey_Response__c` object is populated via a custom Visualforce page.

What is the optimal way to implement this?

- ☐ A. Implement the logic in an Apex trigger on Contact and also implement the logic within the custom Visualforce page controller.
- ☐ B. Implement the logic in validation rules on the Contact and the `Survey_Response__c` objects.
- ☒ C. Implement the logic in a helper class that is called by an Apex trigger on Contact and from the custom Visualforce page controller.
- ☐ D. Implement the logic in the custom Visualforce page controller and call that method from an Apex trigger on Contact.

Question 61 of 62



Choose 2 options.

A large company uses Salesforce across several departments. Each department has its own Salesforce Administrator. It was agreed that each Administrator would have their own sandbox in which to test changes.

Recently, users notice that fields that were recently added for one department suddenly disappear without warning.

Which two statements are true regarding these issues and resolution?

- ☒ A. The administrators are deploying their own Change Sets over each other, thus replacing entire Page Layouts in production.
- ☐ B. Page Layouts should never be deployed via Change Sets, as this causes Field-Level Security to be reset and fields to disappear.
- ☒ C. A sandbox should be created to use as a unified testing environment instead of deploying Change Sets directly to production.
- ☐ D. The administrators are deploying their own Change Sets, thus deleting each other's fields from the objects in production.

Question 62 of 62



Choose 1 option.

An org records customer order information in a custom object, `Order__c`, that has fields for the shipping address. A developer is tasked with adding code to calculate shipping charges on an order, based on a flat percentage rate associated with the region of the shipping address.

What should the developer use to store the rates by region, so that when the changes are deployed to production no additional steps are needed for the calculation to work?

- ☐ A. Custom object
- ☐ B. Custom list setting
- ☐ C. Custom hierarchy setting
- ☒ D. Custom metadata type

EXAM: Salesforce Certified Platform Developer II - Multiple Choice

GRADE: Pass

The report below shows the percentage of questions in each section that you answered correctly for the Salesforce Certified Platform Developer II - Multiple Choice exam. You will receive this information in your exam results email and can also access it via My Dashboard in Trailhead Academy.

SECTION NAME:	PERCENT CORRECT:
Advanced Developer Fundamentals	89%
Process Automation, Logic, and Integration	94%
User Interface	92%
Testing, Debugging, and Deployment	67%
Performance	91%